



INDEX DIAGRAM

TOWNSHIP 5 SOUTH, RANGE 23 EAST,

	24		22							
20	6	49	5		4		3		2	1
	48		47							
17	7	46	8		9		10		11	12
	46		45							
15	18	44	17	38	16	35	15	31	14	13
			43		38		35			
12	19	42	20	37	21	34	22	30	23	24
	42		41		36		34			
9	30	41	29		28	33	27	29	26	27
	40				36		32		29	26
8	31	39	32		33	31	34	27	35	24
										36

Camp Goodwin Military Reservation pp 4-7

- Subdivision Sec. 17 pp 50-51
- Subdivision Sec. 19 pp 52-53
- Subdivision Sec. 20 pp 53-53
- Subdivision Sec. 26 pp 53-55
- Subdivision Sec. 30 pp 55-56
- Subdivision Sec. 34 pp 56-57
- Subdivision Sec. 35 pp 57-57

## BOOK 5315

T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the dependent resurvey of portions, of the Camp Goodwin Military Reservation, (abandoned), of the west boundary, of the north boundary, of the subdivisional lines and the subdivision of selected sections, in Township 5 South, Range 23 East, Gila and Salt River Meridian, Arizona.

The exterior boundaries and subdivisional lines were surveyed in 1875 by Theodore F. White. The abandoned Camp Goodwin Military Reservation through the township was surveyed and a portion of the west and north boundaries and subdivisional lines were resurveyed in 1888, by Clarence H. Wallace. The abandoned Fort Thomas Military Reservation was surveyed by Earl D. Thomas, an Army Lieutenant, in 1876. Lorenzo D. Chillson surveyed a portion of the subdivisional lines, resurveyed a portion of the north boundary and the boundaries of the abandoned Fort Thomas Military Reservation within the township, in 1894. The south boundary and south four and one half miles of the west boundary were resurveyed by Phillip Contzen in 1900. The east half mile of the south boundary was resurveyed in 1916 by Albert B. Rich. The north mile of the east boundary and a portion of the subdivisional lines were resurveyed and section 1 subdivided in 1965 by Leonard W. Murphy. The east four miles of the north boundary were resurveyed in 1965-67 by Leonard W. Murphy and Paul G. Bauer. The south boundary was resurveyed by Kenneth D. Herman and Gary T. Oviatt, in 1967. In 1976 Paul L. Reeves under the supervision of Boyd S. Owens, resurveyed a portion of the abandoned Fort Thomas Military Reservation, portions of the east and north township boundaries and a portion of the subdivisional lines, and subdivided certain sections.

The resurvey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the special instructions for Group No. 634, Arizona, dated April 8, 1982, and the supplemental special instructions dated January 11, 1985.

The direction of lines of this survey was determined by altitude observation of the sun and refer to the true meridian. Angles and distances were measured by a Hewlett Packard 3820A Total Station, a Zeiss Elta 4 Theodolite and a Zeiss Elta 46 Theodolite.

## BOOK 5315

T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS

Preliminary to the resurvey the lines of the original survey were retraced and a search made for all corners and other calls of record. Identified corners were remonumented in their original positions; lost corners were restored and remonumented at proportionate positions based on the original record. the retraced data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of section 25, T. 5 S., R. 22 E., as determined from a tie to the U.S. Coast and Geodetic Survey triangulation station "STEER", located in section 11, T. 6 S., R. 22 E., is as follows:

NAD 27 Latitude: 32°57'43.10" N Longitude: 110°02'02.83" W

The mean magnetic declination is 13 1/2° E.

---

Dependent Resurvey of a Portion,  
Camp Goodwin Military Reservation, (abandoned)  
T. 5 S., R. 23 E., Gila and Salt River Mer., Arizona

---

Restoring the survey executed by Clarence H. Wallace, in 1888

Beginning at the point of intersection of the line bet. secs. 5 and 32, on the N. bdy. of the Tp., and line 2-3 of the Camp Goodwin Military Reservation, (abandoned).

Set an aluminum post, 28 ins. long, 1 in. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.

```

          T4S R23E
           /
          CC
         /
        C  S32  S32
         /
        G  -----
         /
        M S 5  S 5
         /
        R  CC
           \
           T5S
            1985
  
```

Set a steel fence post alongside the cor.

From this point, the 1/4 sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp., bears N. 89°42' E., 14.185 chs. dist., hereinafter described.

Dependent Resurvey of a Portion,  
Camp Goodwin Military Reservation, (abandoned),  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS

From this same cor. point, the cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., bears S. 89°42' W., 26.065 chs. dist., hereinafter described.

From this same cor. point, the reestablished 1888 position for Cor. No. 2 of Camp Goodwin Military Reservation (abandoned), bears N. 44°57' E., 10.761 chs. dist. This position was determined at record bearing and dist. from the 1/4 sec. cor. of secs. 5 and 32, Tps. 4 and 5 S, R 23 E, based on the 1888 record of Clarence H. Wallace, U.S. Deputy Surveyor. This is accepted as the best available evidence of the 1888 cor. position. This position was used to control the alignment of line 2-3, of Camp Goodwin Military Reservation, (abandoned), through Tps. 4 and 5 S, Rs. 22 and 23 E.

From this cor. position, the 1/4 sec. cor. of secs. 5 and 32, T. 4 and 5 S., R. 23 E., bears S. 41°07' E., 10.01 chs. dist., hereinafter described.

From this same cor. point, the new point for Cor. No. 2, Camp Goodwin Military Reservation, (abandoned), bears N. 44°57' E., 11.865 chs. dist.. This point is at the intersection of the extension of the line projected from corner 3 through the reestablished 1888 position for corner 2, Camp Goodwin Military Reservation, (abandoned), and line 3-4 of the Camp Thomas Military Reservation, (abandoned), as described in the dependent resurvey of a portion of the Camp Thomas Military Reservation, (abandoned), T. 4 S., R. 23 E., executed concurrently under this same group.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T4S R23E  
S32  
CGMR / CIMR  
COR.2  
S32  
1985

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.

Set a steel fence post alongside the cor.

From this cor. point, a stone 16 x 10 x 5 ins., laying on the ground, mkd. C GMP. bears S. 45°40' E., 9.90 chs. dist. Not reconcilable with record, buried in place.

Dependent Resurvey of a Portion,  
Camp Goodwin Military Reservation, (abandoned),  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p>From this same cor. point, a stone, 16 x 18 x 6 ins., laying on the ground, mkd. GM IR, with an X on top, bears S. 59°59 E., 10.58 chs. dist. Not reconcilable with record, buried in place.</p> <p>S. 44°57' W., on line 2-3, Camp Goodwin Military Reservation.</p> <p>Over gently rolling land, through medium creosote and scattered mesquite.</p> <p>36.21 Point for the closing cor., at intersection with the line bet. secs. 5 and 6.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T5S R23E CGMR S 6   S 5 CC CC S 6   S 5 1985</p> </div> <p>Set a steel fence post alongside the cor.</p> <p>From this cor. point, the cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., bears N. 1°04' W., 25.48 chs. dist., hereinafter described.</p> <p>From this same cor. point, the 1/4 sec. cor. of secs. 5 and 6, bears S. 1°04' E., 14.30 chs. dist., hereinbefore described.</p> <p>113.25 Point for the closing cor. at intersection with the line bet. secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5S R23E CC S 6 / S 6 S 7 / S 7 CC 1985</p> </div> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.</p>
---------------	---

Dependent Resurvey of a Portion,  
Camp Goodwin Military Reservation, (abandoned),  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Set a steel fence post alongside the cor.</p> <p>From this cor. point, the 1/4 sec. cor. of secs. 6 and 7, bears N. 89°15' E., 15.65 chs. dist., hereinafter described.</p> <p>From this same cor. point, the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., bears S. 89°15' W., 25.60 chs. dist., hereinafter described.</p> <p>149.35 Point for a closing cor., at intersection with the line bet. secs. 7 and 12, on the W. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T5S R22E R23E CGMR S12   S 7 CC /   CC S12   S 7 1985</p> </div> <p>Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, W. of cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>From this cor. point, the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., bears N. 0°13' W., 25.21 chs. dist., hereinafter described.</p> <p>From this same cor. point, the 1/4 sec. cor. of sec. 12 only, T. 5 S., R. 22 E., bears S. 0°13' E., 11.41 chs. dist., hereinafter described.</p> <p>From this same cor. point, the original Cor. No. 3 of the Camp Goodwin Military Reservation, bears S. 44°57' W., 139.242 chs. dist., monumented with a granite stone, 11 x 9 x 4 ins., loosely set and mkd. CGMR 3.</p> <p>Not remonumented</p>
--------	---

Dependent Resurvey, Portion of the West Boundary,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Restoring the resurvey executed by Phillip Contzen, in 1899</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the stan. cor. of Tps. 5 S., Rs. 22 and 23 E., on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 5 ins. from the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td colspan="2" style="padding: 0 5px;">T5S</td> </tr> <tr> <td style="padding: 0 5px;">R22E</td> <td style="padding: 0 5px;">R23E</td> </tr> <tr> <td style="padding: 0 5px;">S36</td> <td style="padding: 0 5px;">S31</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; padding-top: 5px;">1967</td> </tr> </table> </div> <p>Not remonumented</p> <p>A post, 4 x 4 ins., projecting 14 ins. from ground, is set alongside the cor.</p> <p>N. 1°06' W., on the W. bdy. of sec. 31.</p> <p>Over level terrain, through light brush and mesquite.</p> <p>39.44 The 1/4 sec. cor. of sec. 31 only, T. 5 S., R. 23 E., determined from the remains of a bearing tree of record</p> <p style="padding-left: 40px;">A dead mesquite stump, 7 ins. diam., bears S. 38°30' E., 26 1/2 lks. dist., with no marks visible.</p> <p>Point is monumented by a granite rock, 16 x 8 x 8 ins., loosely set on top of the ground, mkd. 31 on E. face,</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td colspan="2" style="padding: 0 5px;">T5S</td> </tr> <tr> <td style="padding: 0 5px;">R22E</td> <td style="padding: 0 5px;">R23E</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">  1/4 S31</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; padding-top: 5px;">1982</td> </tr> </table> </div> <p>Bury the stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 7°21' E., beginning new measurement.</p> <p>0.88 The 1/4 sec. cor. of sec. 36 only, T. 5 S., R. 22 E., monumented with a granite rock, 16 x 10 x 6 ins., loosely set, with rock mkd. 1/4 36.</p>	T5S		R22E	R23E	S36	S31	1967		T5S		R22E	R23E	1/4 S31		1982	
T5S																	
R22E	R23E																
S36	S31																
1967																	
T5S																	
R22E	R23E																
1/4 S31																	
1982																	

Dependent Resurvey, Portion of the West Boundary,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R22E R23E 1/4 S36   1982</p> <p>from which</p> <p style="text-align: center;">A mesquite, 8 ins. diam., bears S. 23 1/2° W., 88 lks. dist., mkd. T5S R22E 1/4 S36 BT.</p> <p>Deposit mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°05' W., beginning new measurement.</p> <p>Over level, partially open land.</p>
38.14	<p>The sec. cor. of secs. 30 and 31 only, T. 5 S., R. 23 E., monumented with an iron post, 2 1/2 ins. diam., projecting 8 ins. from ground, with brass cap mkd.</p> <p style="text-align: center;">T5S   T5S R22E   S30 ----- S36   S31 R23E 1976</p> <p>Cor. falls in a wash area, bears NE and SW.</p> <hr/> <p>North, on the W. bdy. of sec. 30.</p>
1.93	<p>The sec. cor. of secs. 25 and 36 only, T. 5 S., R. 22 E., monumented with a granite stone, 12 x 8 x 6 ins., firmly set, with 5 notches on the North.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 25 ins. in the ground, with aluminum cap mkd.</p>

Dependent Resurvey, Portion of the West Boundary,  
T 5 S, R 23 E, Gila and Salt River Meridian, Arizona

CHAINS	<div style="text-align: center; margin-bottom: 10px;"> <p>T5S R22E R23E S25   ----- S30 S36   1982</p> </div> <p>from which</p> <p style="margin-left: 40px;">A mesquite, 5 ins. diam., bears S. 62° W., 85 lks. dist., mkd. T5S R22E S36.</p> <p style="margin-left: 40px;">A mesquite, 5 ins. diam., bears N. 14° W., 47 lks. dist., mkd. T5S R22E S25 BT.</p> <p>Deposit the stone alongside the aluminum post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°10' W., beginning new measurement.</p> <p>18.08 Point for the S 1/16 sec. cor. of sec. 30 only, T. 5 S., R. 23 E.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 6 ins. in the ground, in a mound of stone, 2 1/2 ft. base to top, with aluminum cap mkd.</p> <div style="text-align: center; margin-bottom: 10px;"> <p>T5S R22E R23E   S 1/16 S30 1982</p> </div> <p>from which</p> <p style="margin-left: 40px;">A catclaw, 5 ins. diam., bears S. 52° E., 72 lks. dist., mkd. S 1/16 S30 BT.</p> <p>20.045 Point for the S 1/16 sec. cor. of sec. 25 only, T. 5 S., R. 23 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 10px;"> <p>T5S R22E R23E S 1/16 S25   1982</p> </div>
--------	--

Dependent Resurvey, Portion of the West Boundary,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Set a steel fence post alongside the cor.</p>
38.09	<p>The point for the 1/4 sec. cor. of sec. 30 only, T. 5 S., R. 23 E., at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T5S R22E R23E   1/4 S30 1982</p> </div> <p>from which</p> <p style="margin-left: 40px;">A catclaw, 14 ins. diam., bears N. 24 1/2° E., 72 lks. dist., mkd. T5S R22E 1/4 S30 BT.</p> <p>Cor. falls in a wash, 80 lks. wide, drains NE.</p> <p>Over wash area of brush and mesquite.</p>
40.09	<p>Point for the 1/4 sec. cor. of sec. 25 only, T. 5 S., R. 23 E.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T5S R22E R23E 1/4 S25   1982</p> </div> <p>from which</p> <p style="margin-left: 40px;">A mesquite, 10 ins. diam., bears N. 57° W., 120 lks. dist., mkd. T5S R22E 1/4 S25 BT.</p> <p>Cor. is set in a wash, 20 lks. wide, drains NE.</p> <p>Over area of brush and mesquite.</p>


Dependent Resurvey, Portion of the West Boundary,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS																			
77.82	<p>The sec. cor. of secs. 19 and 30, monumented with an iron post, 28 ins. long, 2 1/2 ins. diam., projecting 3 ins. from ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T5S</td> <td> </td> <td>S19</td> </tr> <tr> <td>R22E</td> <td> </td> <td></td> </tr> <tr> <td colspan="3"><hr/></td> </tr> <tr> <td>S25</td> <td> </td> <td>S30</td> </tr> <tr> <td></td> <td> </td> <td>R23E</td> </tr> <tr> <td>1976</td> <td></td> <td></td> </tr> </table> </div> <p>Not remonumented</p> <p>A mound of stone, 2 1/2 x 2 ft., is set E. of the cor.</p> <hr/> <p>N. 0°07' W. on the W. bdy. of sec. 19.</p>	T5S		S19	R22E			<hr/>			S25		S30			R23E	1976		
T5S		S19																	
R22E																			
<hr/>																			
S25		S30																	
		R23E																	
1976																			
2.37	<p>The sec. cor. of secs. 24 and 25 only, monumented with a granite stone, 8 x 8 x 8 ins., firmly set, projecting 7 ins. from ground, mkd. with 2 notches on the S. and 4 notches on the N. edge, with a mound of stone, 2 ft. base, 1 ft. high, set to the S. of cor.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td></td> <td>T5S</td> <td></td> </tr> <tr> <td>R22E</td> <td> </td> <td>R23E</td> </tr> <tr> <td>S24</td> <td> </td> <td></td> </tr> <tr> <td colspan="3"><hr/></td> </tr> <tr> <td>S25</td> <td> </td> <td>S19</td> </tr> <tr> <td>1982</td> <td></td> <td></td> </tr> </table> </div> <p>Rebuild the mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Deposit stone in the mound of stone.</p> <hr/> <p>N. 0°19' W., beginning new measurement.</p> <p>Through area of creosote.</p>		T5S		R22E		R23E	S24			<hr/>			S25		S19	1982		
	T5S																		
R22E		R23E																	
S24																			
<hr/>																			
S25		S19																	
1982																			
17.59	<p>Point for the S 1/16 sec. cor. of sec. 19 only, T. 5 S., R. 23 E.</p>																		

Dependent Resurvey, Portion of the West Boundary,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base to top, with aluminum cap mkd.</p> <p style="text-align: center;">T5S R22E R23E S 1/16   S19 1982</p>
<p>20.04</p>	<p>Point for the S 1/16 sec. cor. of sec. 24 only, T. 5 S., R. 22 E.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base to top, with aluminum cap mkd.</p> <p style="text-align: center;">T5S R22E R23E S 1/16   S24   1985</p>
<p>37.55</p>	<p>Set a steel fence post alongside the cor.</p> <p>The 1/4 sec. cor. of sec. 19 only, T. 5 S., R. 23 E., monumented with a sandstone, 11 x 10 x 7 ins., firmly set, projecting 5 ins. from the ground, mkd. 1/4 19 on the E. face, from which, a bearing tree of record</p> <p style="padding-left: 40px;">A mesquite, 6 ins. diam., bears S. 56° E., 99 1/2 lks. dist., mkd. 1/4 S19 BT.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 28 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T5S R22E   R23E   1/4 S19 1982</p> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 6 ins. diam., bears S. 74° E., 165 lks. dist., mkd. 1/4 S19 BT.</p>

Dependent Resurvey, Portion of the West Boundary,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona


CHAINS	
	<p>Raise a mound of stone, 1 1/2 ft. base, 1 ft. high, E. of cor.</p>
	<p>Deposit the mkd. stone in the mound of stone.</p>
	<p>N. 0°04' W., beginning new measurement.</p>
2.53	<p>The 1/4 sec. cor. of sec. 24 only, T. 5 S., R. 22 E., monumented</p>
	<p>with a stone, 8 x 5 x 4 ins., set flush with the surface of the</p>
	<p>ground, mkd. 1/4 2 on the W. face, from which, a bearing tree of</p>
	<p>record</p>
	<p>A mesquite, 6 ins. diam., bears S. 50° W., 196 lks. dist.,</p>
	<p>mkd. 1/4 S24 BT.</p>
	<p>At the cor. point</p>
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 30 ins. in the</p>
	<p>ground, with aluminum cap mkd.</p>
	
	<p>from which</p>
	<p>A mesquite, 6 ins. diam., bears S. 85° W., 72.8 lks. dist.,</p>
	<p>mkd. 1/4 S24 BT.</p>
	<p>Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p>
	<p>Deposit the mkd. stone in the mound of stone.</p>
	<p>N. 0°20' W., beginning new measurement.</p>
	<p>Over rolling terrain, through area of creosote.</p>
37.47	<p>The sec. cor. of secs. 18 and 19 only, T. 5 S., R. 23 E.,</p>
	<p>monumented with a granite stone, 18 x 10 x 7 ins., laying loose</p>
	<p>near scattered mound of stone, 2 x 1 ft., mkd. with 3 notches</p>
	<p>each on 2 edges. This is accepted as the best available evidence</p>
	<p>of the original cor. position.</p>

Dependent Resurvey, Portion of the West Boundary,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with aluminum cap mkd.



Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, E. of cor.

Deposit the mkd. stone in the mound of stone.

N. 0°06' E., on the W. bdy. of sec. 18.

2.69


The sec. cor. of secs. 13 and 24 only, T. 5 S., R. 22 E., monumented with a granite stone, 8 x 12 ins., firmly set, with 3 notches on the N. edge and 3 notches on the S. edge, from which bearing trees of record

A mesquite, 6 ins. diam., bears S. 40° W., 290 lks. dist., no marks visible.

A mesquite, 6 ins. diam., bears N. 81° W., 197 lks. dist., no marks visible.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with aluminum cap mkd.



Deposit the stone alongside the aluminum post.

Dependent Resurvey, Portion of the West Boundary,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>N. 0°26' W., beginning new measurement.</p> <p>Through area of creosote and mesquite.</p> <p>37.32 The 1/4 sec. cor. of sec. 18 only, T. 5 S., R. 23 E., monumented with a sandstone, 8 x 7 ins., projecting 4 ins. from the ground, mkd. 1/4 18 on E. face, from which bearing trees of record</p> <p style="padding-left: 40px;">A mesquite, 6 ins. diam., bears N. 48° E., 102 lks. dist. (Record: N. 46 1/2° E., 103 1/2 lks. dist.)</p> <p style="padding-left: 40px;">A mesquite, 6 ins. diam., bears S. 42° E., 85 lks. dist., no marks visible.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, E. of cor.</p> <p>Deposit the mkd. stone in the mound of stone.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°08' W., beginning new measurement.</p> <p>2.85 The 1/4 sec. cor. of sec. 13 only, T. 5 S., R. 22 E., monumented with a granite stone, 10 x 15 ins., firmly set, mkd. 1/4 13 on W. face, from which bearing trees of record</p> <p style="padding-left: 40px;">A mesquite stump, 8 ins. diam., bears N. 84° W., 145 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A mesquite, 8 ins. diam., bears N. 5° W., 144 lks. dist., no marks visible. (Record: 148 lks. dist.)</p> <p>At the cor. point</p>
--------	--

Dependent Resurvey, Portion of the West Boundary,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T5S R22E   R23E 1/4 S13 1982</p> </div> <p>from which</p> <p style="margin-left: 40px;">A mesquite, 6 ins. diam., bears N. 68° W., 53 lks. dist., mkd. 1/4 S13 BT.</p> <p>Deposit the stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°10' W., beginning new measurement.</p> <p>37.06 The sec. cor. of secs. 7 and 18 only, T. 5 S., R.23 E., monumented with a granite stone, 14 x 10 x 8 ins. firmly set, mkd. with 2 grooves on the N. face and 4 grooves on the S. face , with a scattered mound of stone set to the E.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 5 ft. base to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T5S R22E   R23E S 7 S13   S18 1982</p> </div> <p>Deposit the mkd. stone in the mound of stone.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°13' E., on the W. bdy. of sec. 7.</p>
--------	--

Dependent Resurvey, Portion of the West Boundary,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>3.06 The sec. cor. of secs. 12 and 13 only, T. 5 S., R. 22 E., monumented with a granite stone, 18 x 8 x 10 ins., firmly set, mkd. with 4 notches on the S. face and 2 grooves on the N. face, a scattered mound of stone is set to the W., from which the remains of a bearing tree of record</p> <p style="padding-left: 40px;">A mesquite stump, 17 ins. diam., bears N. 36 1/2° W., 186 lks. dist., with no marks visible. (Record: N. 40° W., 188 lks. dist.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 3 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base to top with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <pre> T5S R22E   R23E S12    -----  S 7 S13    1982                </pre> </div> <p>Deposit stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°13' W., beginning new measurement.</p> <p>Through area of creosote and mesquite.</p> <p>36.84 The 1/4 sec. cor. of sec. 7 only, T. 5 S., R. 23 E., monumented with a granite stone, 12 x 8 x 16 ins. firmly set, mkd. 1/4 7 on E. face, with a mound of stone, 2 1/2 x 1 ft., set E. of cor.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <pre> T5S R22E R23E                 1/4 S 7         1982                </pre> </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.</p>
--------	---

Dependent Resurvey, Portion of the West Boundary,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit the mkd. stone alongside the aluminum post.</p> <hr/>
	<p>N. 0°06' W., beginning new measurement.</p>
3.36	<p>The 1/4 sec. cor. of sec. 12 only, T. 5 S., R. 22 E., monumented with a granite stone, 8 x 6 x 15 ins. firmly set, mkd. with 1/4 12 on the W. face, with a scattered mound of stone, 3 x 1 ft., set W. of the cor..</p>
	<p>At the cor. point</p>
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base to top, with aluminum cap mkd.</p>
	<div style="text-align: center;"> <p>T5S R22E   R23E 1/4 S12 1982</p> </div>
	<p>Deposit the stone alongside the aluminum post.</p> <hr/>
	<p>N. 0°13' W., beginning new measurement.</p>
10.53	<p>A granite stone, 14 x 6 x 8 ins., mkd. CC CGMR on N. face, with scattered mound of stone set to the N., bears West, 4 lks. dist. Buried in place.</p>
11.44	<p>The closing cor. on the Camp Goodwin Military Reservation bdy. (abandoned), hereinbefore described.</p>
	<p>From this cor. point, the closing cor. of Camp Goodwin Military Reservation and the line between secs. 5 and 32, on the N. bdy. of the Tp, bears N. 44°57' E., 149.355 chs. dist., hereinbefore described.</p>
	<p>From this same cor. point, original Cor. No. 3 of the Camp Goodwin Military Reservation, bears S. 44°57' W., 139.292 chs. dist., hereinbefore described.</p>
	<hr/> <p style="text-align: center;">Restoring the survey executed by Theodore F. White, in 1875</p> <hr/>

Dependent Resurvey, Portion of the West Boundary,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS											
12.745	A granite stone, 14 x 10 x 9 ins., loosely set, mkd. CC on top, previously established for a closing cor., bears West, 15.4 lks. dist. Mkd. AM on the stone and buried in place.										
36.62	The cor. of secs. 1, 6, 7 and 12, on the W. bdy of the Tp., determined at the center of a mound of stone, 2 1/2 x 1 1/2 ft. This is accepted as the best available evidence of the original cor. position.										
	At the cor. point										
	Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with aluminum cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T5S</td> </tr> <tr> <td style="text-align: center;">R22E</td> <td style="text-align: center;">R23E</td> </tr> <tr> <td style="text-align: center;">S 1</td> <td style="text-align: center;">S 6</td> </tr> <tr> <td style="text-align: center;">S12</td> <td style="text-align: center;">S 7</td> </tr> <tr> <td colspan="2" style="text-align: center;">1982</td> </tr> </table>	T5S		R22E	R23E	S 1	S 6	S12	S 7	1982	
T5S											
R22E	R23E										
S 1	S 6										
S12	S 7										
1982											
	Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, W. of cor.										
	From this cor., U.S.C.&G.S. triangulation station "GOOD, 1945", bears N 24°49'58" W, 154.685 chs. dist., monumented with a brass tablet, set in concrete, flush with ground, mkd. GOOD 1945 and a triangle in the center.										
	N. 0°07' W., bet. secs. 1 and 6, on the W. bdy of the Tp.										
	Over gently rolling land, through medium creosote and scattered mesquite.										
39.96	The 1/4 sec. cor. of secs. 1 and 6, determined by the remains of a bearing tree of record										
	A mesquite snag, 5 ins. diam., bears S. 65°30' E., 175 lks. dist., no marks visible.										
	Point falls in a mound of stone, 3 x 1 ft.										
	At the cor. point										
	Set an aluminum post, 28 ins. long, 1 in. diam., 4 ins. in the ground, in a mound of stone, 3 1/2 ft. base, 2 ft. high, with aluminum cap mkd.										

Dependent Resurvey, Portion of the West Boundary,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS

T5S  
1/4  
R22E | R23E  
S 1 | S 6  
1982

---

N. 0°04' W., beginning new measurement.

Over relatively flat terrain, through mesquite and creosote.

39.93

The cor. of Tps. 4 and 5 S., Rs. 22 and 23 E., determined by the remains of a wood post in mound of stone. This is accepted as the best available evidence of the original cor. position.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base to top, with aluminum cap mkd.

T4S  
R22E R23E  
S36 | S31  
S 1 | S 6  
T5S  
1982

From this cor. point, a fence cor., bears SE, 36 lks. dist., fences extend N. and E.

---

Dependent Resurvey, Portion of the North Boundary  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

---

Restoring the survey by Lorence O. Chillson, in 1894

---

From the cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 10 ins. from ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.

Dependent Resurvey, Portion of the North Boundary  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	<div style="text-align: center; margin-bottom: 20px;"> <p>T4S R23E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S32</td> <td style="padding: 2px 5px;">S33</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 5</td> <td style="padding: 2px 5px;">S 4</td> </tr> </table> <p>T5S 1965</p> </div> <p>Not remonumented</p> <p>S. 89°42' W., bet. secs. 5 and 32, on the N. bdy. of the Tp.</p> <p>Descend from mesa top, across open area.</p> <p>32.155 Intersect the Camp Thomas Military Reservation bdy. (abandoned), monumented with a aluminum post, 28 ins. long, 1 ins. diam., 20 ins. in the ground, in a mound of stone 2 1/2 ft. to top, with brass cap mkd.</p> <div style="text-align: center; margin-bottom: 20px;"> <p>T4SR23E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 5px;">CC</td> <td style="padding: 2px 5px;"></td> <td style="padding: 2px 5px;">C</td> </tr> <tr> <td style="padding: 2px 5px;">S32</td> <td style="border-right: 1px solid black; padding: 2px 5px;">S32</td> <td style="padding: 2px 5px;">T</td> </tr> <tr> <td style="padding: 2px 5px;">S5</td> <td style="border-right: 1px solid black; padding: 2px 5px;">S5</td> <td style="padding: 2px 5px;">M</td> </tr> <tr> <td style="padding: 2px 5px;"></td> <td style="padding: 2px 5px;">CC</td> <td style="padding: 2px 5px;">R</td> </tr> </table> <p>1965</p> </div> <p>Not remonumented</p> <p>From this cor. point, the closing cor. of secs. 4 and 5, bears S. 59°14' E., 37.64 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. from the ground, in a mound of stone, 2 1/2 ft. base to top, with brass cap mkd.</p> <div style="text-align: center; margin-bottom: 20px;"> <p>T5SR23E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 5px;">CTMR</td> <td style="padding: 2px 5px;"></td> </tr> <tr> <td style="padding: 2px 5px;">CC</td> <td style="padding: 2px 5px;"></td> </tr> <tr> <td style="padding: 2px 5px;">S5</td> <td style="border-right: 1px solid black; padding: 2px 5px;">S4</td> </tr> <tr> <td style="padding: 2px 5px;">S5</td> <td style="border-right: 1px solid black; padding: 2px 5px;">S4</td> </tr> </table> <p>1976</p> </div> <p>Not remonumented</p> <p>From this same cor. point, the new Cor. No. 2 of the Camp Goodwin Military Reservation, bears N. 59°14' W., 16.17 chs. dist., hereinbefore described.</p>	S32	S33	S 5	S 4	CC		C	S32	S32	T	S5	S5	M		CC	R	CTMR		CC		S5	S4	S5	S4
S32	S33																								
S 5	S 4																								
CC		C																							
S32	S32	T																							
S5	S5	M																							
	CC	R																							
CTMR																									
CC																									
S5	S4																								
S5	S4																								

Dependent Resurvey, Portion of the North Boundary,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.25	<p>Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 ins. diam., 22 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T4S R23E S32 1/4 — S5 T5S R23E 1982</p> </div> <p>from which</p> <p style="padding-left: 40px;">A crucifixion tree, 10 ins. diam., bears N. 13° E., 71 lks. dist., mkd. T4S R23E S32 BT.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p>
54.435	<p>The closing cor. on the Camp Goodwin Military Reservation (abandoned), hereinbefore described.</p> <p>From this cor. point, the new Cor. No. 2 of Camp Goodwin Military Reservation, bears N. 44°57' E., 11.865 chs. dist., hereinbefore described.</p> <p>From this same point, the original Cor. No. 3 of the Camp Good Military Reservation, bears S. 44°57' W., 288.125 chs. dist., hereinbefore described.</p>
80.50	<p>Point for the cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. in the ground, in a mound of stone, 2 ft. base to top, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T4S R23E S31   S32 —   — S 6   S 5 T5S R23E 1982</p> </div>

Dependent Resurvey, Portion of the North Boundary,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>S. 89°42'. W, bet. secs. 6 and 31, on the N. bdy. of the Tp.</p> <p>Over hilly terrain, through mesquite and creosote.</p>								
39.99	<p>Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base to top, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T4S R23E S31 1/4 _____ S 6 T5S R23E 1982</p> </div> <p>Cor. is located 8 lks. N. of a ravine, drains W.</p> <p>An fence, bears S. of cor. for approximately 1.5 chs., extends E. and W.</p> <p>Set a steel fence post alongside the cor.</p>								
79.71	<p>The cor. of secs. 1, 6, 31 and 36, Tps. 4 and 5 S., Rs. 22 and 23 E., hereinbefore described.</p> <hr/> <p style="text-align: center;">Dependent Resurvey, Portion of the Subdivisional Lines, T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>Restoring the survey executed by Theodore F. White, in 1875</p> <div style="text-align: center; margin: 10px 0;"> <p>_____</p> </div> <p>From the stan. cor. of secs. 35 and 36, on the S. bdy. of the Tp., monumented with an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins. from ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2" style="text-align: center;">S C</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">T5S</td> <td style="padding: 2px 5px;">R23E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S35</td> <td style="padding: 2px 5px;">S36</td> </tr> <tr> <td colspan="2" style="text-align: center; border-top: 1px solid black; padding-top: 5px;">1967</td> </tr> </table> </div> <p>N. 0°05' W., bet. secs. 35 and 36.</p>	S C		T5S	R23E	S35	S36	1967	
S C									
T5S	R23E								
S35	S36								
1967									

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p>Over rugged terrain and into open area, descend gently.</p>
<p>39.99</p>	<p>Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., on rock surface, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5S R23E 1/4 S35   S36 1982</p> </div>
<p>79.98</p>	<p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5S R23E S26   S25 ----- S35   S36 1982</p> </div> <p>Cor. is located 29 lks. S. of an E. and W. fence and 43 lks. S. of an E. and W. track road.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy of the Tp., monumented with a rebar, 1/2 in. diam., set 8 ins. below the surface of a dirt road, with a 1 in. cap, illegible mkds., laying next to the rebar. This is accepted as a careful and faithful perpetuation of the position of the original cor.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 8 ins. below the road surface, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T5S R23E R24E S25   S30 ----- S36   S31 1982</p> </div>

Dependent Resurvey, Portion, of the Subdivisional Lines,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>An X chiseled on a concrete canal headwall, 4 x 4 ft. wide, bears N. 35° E., 37.5 lks. dist.</p> <p>An iron post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°30' E., 52.16 ft. dist., with brass cap mkd. RM T5S R24E S31 52.16 FT 1982, and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, for a reference monument, bears S. 22° W., 33.90 ft. dist., with brass cap mkd. RM T5S R23E S36 33.90 FT 1982, and an arrow pointing to the cor.</p> <p>Deposit rebar inside the aluminum post.</p> <p>The cor. is located in the center of an E. and W. graded gravel road.</p> <p>Cor. is located 49 lks. N. of a fence cor.</p> <p>From this cor. point, the 1/4 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp., bears S. 0°15' E., 40.03 chs. dist., monumented with an iron post, 2 1/2 ins. diam., projecting 4 ins. from ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5S R23E R24E 1/4 S36   S31 1976</p> </div> <p>Not remonumented</p> <p>A mound of stone, 2 ft. x 6 ins., is set W. of the cor.</p> <p>N. 89°53' W., bet. secs. 25 and 36.</p>
39.77	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Not remonumented.</p>
79.53	<p>The cor. of secs. 25, 26, 35 and 36.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>N. 0°18' W., bet. secs. 25 and 26.</p> <p>Over level land, through creosote.</p> <p>39.99 The point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td colspan="2">T5S R23E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S26</td><td>S25</td></tr> <tr><td colspan="2">1982</td></tr> </table> </div> <p>From this cor. point, a fence cor., bears N. 28° W., 148 lks. dist., fences extending N. and E.</p> <p>79.98 The cor. of secs. 23, 24, 25 and 26, monumented with a rebar, (no cap), 11 ins. long, 5/8 in. diam., projecting 2 ins. from ground. This is accepted as a careful and faithful perpetuation of the position of the original cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td colspan="2">T5S R23E</td></tr> <tr><td>S23</td><td>S24</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S26</td><td>S25</td></tr> <tr><td colspan="2">1982</td></tr> </table> </div> <p>Deposit rebar alongside the iron post.</p> <p>Cor. is located 24 lks. E. of a N. and S. fence and 61 lks. S. of a fence, bears SE and NW.</p> <hr style="border: 0.5px solid black;"/> <p>From the stan. cor. of secs. 34 and 35, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. from ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td colspan="2">S C</td></tr> <tr><td colspan="2">T5S R23E</td></tr> <tr><td>S34</td><td>S35</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td colspan="2">1967</td></tr> </table> </div>	T5S R23E		1/4		S26	S25	1982		T5S R23E		S23	S24	-----		S26	S25	1982		S C		T5S R23E		S34	S35	-----		1967	
T5S R23E																													
1/4																													
S26	S25																												
1982																													
T5S R23E																													
S23	S24																												
-----																													
S26	S25																												
1982																													
S C																													
T5S R23E																													
S34	S35																												
-----																													
1967																													

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>N. 1°36' W., bet. secs. 34 and 35.</p> <p>39.45 The 1/4 sec. cor. of secs. 34 and 35, monumented with a stone, 12 x 7 x 6 ins. set flush with the ground, mkd. 1/4.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td colspan="2">T5S R23E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S34</td><td> </td><td>S35</td></tr> <tr><td colspan="3">1982</td></tr> </table> </div> <p>Deposit the stone alongside the cor.</p> <p>Set a steel fence post alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°21' E., beginning new measurement</p> <p>40.03 Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of a dirt road, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td colspan="2">T5S R23E</td></tr> <tr><td>S27</td><td> </td><td>S26</td></tr> <tr><td colspan="3">-----</td></tr> <tr><td>S34</td><td> </td><td>S35</td></tr> <tr><td colspan="3">1982</td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 60° E., 24.62 ft. dist., with brass cap mkd. RM T5S R24E S35 24.62 FT 1982, and an arrow pointing to the cor.</p> <p style="margin-left: 40px;">An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 71°30' W., 28.25 ft. dist., with brass cap mkd. RM T5S R23E S34 28.25 FT 1982, and an arrow pointing to the cor.</p> <p>The cor. falls in the center of an E. and W. road.</p> <hr style="width: 60%; margin: 10px auto;"/>	T5S R23E		1/4		S34		S35	1982			T5S R23E		S27		S26	-----			S34		S35	1982		
T5S R23E																									
1/4																									
S34		S35																							
1982																									
T5S R23E																									
S27		S26																							
-----																									
S34		S35																							
1982																									

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89°41' W., bet. secs. 26 and 35.</p> <p>Along a dirt road, parallel to an E. and W. fence line.</p>
20.04	<p>Point for the E 1/16 sec. cor. of secs. 26 and 35.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E S26 1/4 ——— S35 1982</p> <p>Cor. is located 17 1/2 lks. S. of a fence line, bears E. and W.</p>
40.09	<p>Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E S26 1/4 ——— S35 1982</p> <p>Cor. is located 6 lks. S. of a fence line, bears E. and W., and 23 lks. S. of a road.</p>
80.17	<p>The cor. of secs. 26, 27, 34 and 35.</p>
40.04	<p>N. 0°26' W., bet. secs. 26 and 27.</p> <p>Over level terrain, through creosote.</p> <p>Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with aluminum cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,  
T 5 S, R 23 E, Gila and Salt River Meridian, Arizona

CHAINS	
80.08	<p style="text-align: center;">T5S R23E 1/4 S27   S26 1982</p> <p>The sec. cor. of secs. 22, 23, 26 and 27, monumented with an iron post, 28 ins. long, 3 ins. diam., projecting 6 ins. from ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E S22   S23 ----- S27   S26 1976</p> <p>Not remonumented</p> <p>Cor. is located 2 lks. W. of a wood post, 3 ins. diam.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 28 ins. long, 2 1/2 ins. diam., projecting 8 ins. from the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E 1/4 S22   S23 1976</p> <p>Not remonumented</p> <p>A mound of stone, 1 1/2 ft. x 8 ins. is set to W. of the cor. N. 0°08' W., bet. secs. 22 and 23. Over level terrain, through creosote.</p>
40.03	<p>Point for the cor. of secs. 14, 15, 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E S15   S14 ----- S22   S23 1982</p> <p>Cor. is located 40 lks. E. of a fence line, bears N. and S.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Cor. is located 130 lks. S. of an old fence line, bears SE and NW.</p> <p>Cor. is located 40 lks. E. of a fence line, bears N. and S.</p> <p>Cor. is located 130 lks. S. of an old fence line, bears SE and NW.</p> <p>From this cor. point, the cor. of secs. 13, 14, 23 and 24, bears N. 89°46' E., 79.93 chs. dist., monumented with an iron post, 6 ins. long, 2 1/2 ins. diam., projecting 8 ins. from ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2">T5S R23E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S14</td> <td style="padding: 2px 5px;">S13</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S23</td> <td style="padding: 2px 5px;">S24</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">1976</td> </tr> </table> </div> <p>Not remonumented</p> <p>A mound of stone, 2 1/2 x 1 ft. is set W of cor.</p> <p>No trace of the intermediate cor. was found.</p> <hr/> <p>N. 0°05' W., bet. secs. 14 and 15.</p> <p>20.02 The S 1/16 sec. cor. of secs. 14 and 15, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. from ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2">T5S R23E</td> </tr> <tr> <td colspan="2">S 1/16</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S15</td> <td style="padding: 2px 5px;">S14</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">1976</td> </tr> </table> </div> <p>Not remonumented</p> <p>A mound of stone, 2 1/2 x 1 ft., is set W. of cor.</p> <hr/> <p>From the stan. cor. of secs. 33 and 34, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. from ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2">S C</td> </tr> <tr> <td colspan="2">T5S R23E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S33</td> <td style="padding: 2px 5px;">S34</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">1967</td> </tr> </table> </div> <p>Not remonumented</p>	T5S R23E		S14	S13	S23	S24	1976		T5S R23E		S 1/16		S15	S14	1976		S C		T5S R23E		S33	S34	1967	
T5S R23E																									
S14	S13																								
S23	S24																								
1976																									
T5S R23E																									
S 1/16																									
S15	S14																								
1976																									
S C																									
T5S R23E																									
S33	S34																								
1967																									

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 0°24' W., bet. secs. 33 and 34.</p>
<p>39.92</p>	<p>The 1/4 sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5S R23E 1/4 S33   S34 1982</p> </div>
<p>79.84</p>	<p>Point for the cor. of secs. 27, 28, 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5S R23E S28   S27 ----- S33   S34 1982</p> </div> <p>Cor. is located 140 lks. N. of the center of a dirt road, bears E. and W., and 150 lks. N. of an E. and W. fence line.</p>
<p>39.74</p>	<hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°36' W., bet. secs. 27 and 34.</p> <p>Over flat terrain, along dirt road paralleling an E. and W. fence line.</p> <p>Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 4 ins. in the ground, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap mkd.</p> <p style="text-align: center;">T5S R23E S27 1/4 ——— S34 1982</p>
79.47	<p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/>
	<p>N. 0°17' W., bet. secs. 27 and 28.</p> <p>Over level terrain, through creosote.</p>
39.92	<p>Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T5S R23E 1/4 S28   S27 1982</p>
	<p>Set a steel fence post alongside the cor.</p>
79.84	<p>Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T5S R23E S21   S22 ——— S28   S27 1982</p>
	<p>from which</p> <p style="text-align: center;">A mesquite, 10 ins. diam., bears N. 21° W., 125 lks. dist., mkd. T5S R23E S21 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, N. of cor.</p> <hr/>

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89°46' W., bet. secs. 22 and 27.</p> <p>Over level terrain, through creosote.</p>
39.61	<p>Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T5S R23E S22 1/4 ——— S27 1982</p> </div> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 7 ins. diam., bears S. 5° E., 259 lks. dist., mkd. 1/4 S27 BT.</p>
79.22	<p>The cor. of secs. 21, 22, 27 and 28.</p> <hr/>
	<p>N. 0°31' W., bet. secs. 21 and 22.</p> <p>Over broken mesa's.</p>
39.92	<p>Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T5S R23E 1/4 S21   S22 1982</p> </div> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 8 ins. diam., bears S. 18° E., 189 lks. dist., mkd. 1/4 S22 BT.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS											
78.84	<p>The cor. of secs. 15, 16, 21 and 22, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. from ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T5S R23E</td> </tr> <tr> <td style="text-align: center;">S16</td> <td style="text-align: center;">S15</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S21</td> <td style="text-align: center;">S22</td> </tr> <tr> <td colspan="2" style="text-align: center;">1976</td> </tr> </table>	T5S R23E		S16	S15	-----		S21	S22	1976	
T5S R23E											
S16	S15										
-----											
S21	S22										
1976											
	<p>Not remonumented</p>										
	<hr/> <p>From the cor. of secs. 14, 15, 22 and 23. N. 89°56' W., bet. secs. 15 and 22. Over broken terrain through area of creosote.</p>										
39.86	<p>Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate dist.; there is no remaining evidence of the original cor. Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with aluminum cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T5S R23E</td> </tr> <tr> <td colspan="2" style="text-align: center;">S15</td> </tr> <tr> <td style="text-align: center;">1/4</td> <td style="text-align: center;">-----</td> </tr> <tr> <td colspan="2" style="text-align: center;">S22</td> </tr> <tr> <td colspan="2" style="text-align: center;">1982</td> </tr> </table>	T5S R23E		S15		1/4	-----	S22		1982	
T5S R23E											
S15											
1/4	-----										
S22											
1982											
	<p>Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W. of cor.</p>										
79.72	<p>The cor. of secs. 15, 16, 21 and 22.</p>										
	<hr/> <p>N. 0°06' W., bet. secs. 15 and 16.</p>										
39.39	<p>The 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 2 1/2 ins. diam., projecting 8 ins. from the ground, in a mound of stone, 2 1/2 ft. base to top, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T5S R23E</td> </tr> <tr> <td colspan="2" style="text-align: center;">1/4</td> </tr> <tr> <td style="text-align: center;">S16</td> <td style="text-align: center;">S15</td> </tr> <tr> <td colspan="2" style="text-align: center;">1976</td> </tr> </table>	T5S R23E		1/4		S16	S15	1976			
T5S R23E											
1/4											
S16	S15										
1976											
	<p>Not remonumented</p>										

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89°49' W., bet. secs. 28 and 33.</p> <p>Along a dirt road, parallel to an E. and W. fence line.</p>
39.75	<p>Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5S R23E S28 1/4 ——— S33 1982</p> </div>
79.50	<p>Cor. is located at W. edge of a track road, bears SE and NW and 222 lks. N. of an E. and W. fence.</p> <p>The cor. of secs. 28, 29, 32 and 33, monumented with an iron post, 2 1/2 ins. diam., projecting 7 ins. from ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5S R23E S29   S28 ——— ——— S32   S33 1976</p> </div> <p>Not remonumented</p> <p>A 3 x 3 ft. wood post is set W. of cor.</p>
39.61	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 89°43' W., bet. secs. 21 and 28.</p> <p>Over rolling terrain, through creosote.</p> <p>Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with aluminum cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 5 S., 13. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.23	<p style="text-align: center;">T5S R23E S21 1/4 _____ S28 1982</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W. of cor.</p> <p>The cor. of secs. 20, 21, 28 and 29, monumented with an iron post, 2 1/2 ins. diam., projecting 4 ins. from ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E S20   S21 ----- ----- S29   S28 1976</p> <p>Not remonumented</p> <p>A mound of stone, 2 x 1 ft., to the W. of the cor.</p> <hr/>
39.26	<p>N 0°15' W, bet. secs. 20 and 21.</p> <p>Through area of creosote and mesquite.</p> <p>The 1/4 sec. cor. of secs. 20 and 21, determined by the center of a mound of stone, 6 x 18 ins., on top of earth base. This is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T5S R23E 1/4 S20   S21 1982</p>
39.98	<p>Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W. of cor.</p> <hr/> <p>N. 0°06' W., beginning new measurement</p> <p>Point for the cor. of secs. 16, 17, 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T5S R23E</td> <td></td> </tr> <tr> <td>S17</td> <td>S16</td> </tr> <tr> <td>S20</td> <td>S21</td> </tr> <tr> <td colspan="2">1982</td> </tr> </table> </div>	T5S R23E		S17	S16	S20	S21	1982			
T5S R23E											
S17	S16										
S20	S21										
1982											
<p>39.37</p>	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 89°52' W., bet. secs. 16 and 21.</p> <p>Through area of creosote and mesquite.</p> <p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T5S R23E</td> <td></td> </tr> <tr> <td>S16</td> <td></td> </tr> <tr> <td>1/4</td> <td>_____</td> </tr> <tr> <td>S21</td> <td></td> </tr> <tr> <td colspan="2">1982</td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 5 ins. diam., bears S. 27 1/2° W., 90 lks. dist., mkd. 1/4 S21 BT.</p>	T5S R23E		S16		1/4	_____	S21		1982	
T5S R23E											
S16											
1/4	_____										
S21											
1982											
<p>78.73</p>	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>N. 0°36' W., bet. secs. 16 and 17.</p> <p>Over level terrain, through area of creosote and mesquite.</p>										
<p>19.995</p>	<p>Point for the S 1/16 sec. cor. of secs. 16 and 17.</p>										

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T5S R23E S 1/16 S17   S16 1982</p>
39.99	<p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a collar of stone, with aluminum cap mkd.</p>
	<p style="text-align: center;">T5S R23E 1/4 S17   S16 1982</p>
79.98	<p>The cor. of secs. 8, 9, 16 and 17, monumented with an iron post, 2 1/2 ins. diam., projecting 8 ins. from ground, with brass cap mkd.</p>
	<p style="text-align: center;">T5S R23E S 8   S 9 ----- S17   S16 1976</p>
	<p>Not remonumented</p>
	<p>A mound of stone, 2 x 1 1/2 ft. is W. of the cor.</p>
	<p>From the stan. cor. of secs. 31 and 32, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. from ground, with brass cap mkd.</p>
	<p style="text-align: center;">S C T5S R23E S31   S32 ----- 1967</p>
	<p>Not remonumented</p>

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A mound of stone, 2 x 1 ft. is set N. of the cor.</p>
	<p>N. 0°32' W., bet. secs. 31 and 32.</p>
39.89	<p>Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. in the ground, in a mound of stone, 2 ft. base to top, with aluminum cap mkd.</p>
	<p style="text-align: center;">T5S R23E 1/4 S31   S32 1982</p>
	<p>Cor. is located in a wash, 40 lks. wide, drains NE.</p>
79.78	<p>The cor. of secs. 29, 30, 31 and 32, monumented with an iron post, 2 1/2 ins. diam., projecting 9 ins. from ground, with brass cap mkd.</p>
	<p style="text-align: center;">T5S R23E S30   S29 ----- S31   S32 1976</p>
	<p>Not remonumented</p>
	<p>A mound of stone, 2 1/2 x 1 1/2 ft. is set W. of the cor.</p>
	<p>S. 89°08' W., bet. secs. 30 and 31.</p>
39.78	<p>Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T5S R23E S30 1/4 ——— S31 1982</p>

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
79.72	<p>The cor. of secs. 30 and 31 only, on the W. bdy. of the Tp., hereinbefore described.</p> <p>From this cor., the cor. of secs. 25 and 36 only, on the W. bdy. of the Tp., bears North, 1.93 chs. dist., hereinbefore described.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 2 1/2 ins. diam., projecting 8 ins. from ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E 1/4 S30   S29 1976</p> <p>Not remonumented</p> <p>A mound of stone, 2 1/2 x 1 1/2 ft. is set W. of the cor.</p> <p>N. 0°02' W., bet. secs. 29 and 30.</p>
39.89	<p>Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, in a mound of stone, 2 1/2 ft. base to top, with aluminum cap mkd.</p> <p style="text-align: center;">T5S R23E S19   S20 ----- S30   S29 1982</p> <p>Cor. is located on E. bank of a wash, 2.5 chs. wide, drains NE.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89°52' W., bet. secs. 20 and 29.</p>
39.84	<p>The 1/4 sec. cor. of secs. 20 and 29, monumented with an iron post, 2 1/2 ins. diam., projecting 5 ins. from ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E S20 1/4 ----- S29 1976</p>

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Not remonumented
	A mound of stone, 3 x 1 ft. is set N. of the cor.
79.67	The cor. of secs. 19, 20, 29 and 30.
	S. 89°07' W., bet. secs. 19 and 30.
39.91	Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 23 ins. in the ground, with aluminum cap mkd.
	T5S R23E S19 1/4 ——— S30 1982
79.93	The cor. of secs. 19 and 30 only, on the W. bdy. of the Tp., hereinbefore described.
	From this cor. point, the cor. of secs. 24 and 25 only, on the W. bdy. of the Tp., bears N. 0°07' W., 2.37 chs. dist., hereinbefore described.
	From the Cor. of secs. 19, 20, 29 and 30.
	N. 0°19' E., bet. secs. 19 and 20.
	Through area of creosote and mesquite.
39.89	Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base to top, with aluminum cap mkd.
	T5S R23E 1/4 S19   S20 1982

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS											
79.78	<p>The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 1/2 ins. diam., projecting 4 ins. from ground, with brass cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T5S R23E</td> </tr> <tr> <td style="text-align: center;">S18</td> <td style="text-align: center;">S17</td> </tr> <tr> <td style="border-right: 1px solid black; border-bottom: 1px solid black;"></td> <td style="border-bottom: 1px solid black;"></td> </tr> <tr> <td style="text-align: center;">S19</td> <td style="text-align: center;">S20</td> </tr> <tr> <td colspan="2" style="text-align: center;">1976</td> </tr> </table>	T5S R23E		S18	S17			S19	S20	1976	
T5S R23E											
S18	S17										
S19	S20										
1976											
	<p>Not remonumented.</p>										
	<p>A mound of stone, 3 x 1 1/2 ft. is set W. of the cor.</p>										
	<hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p>										
	<p>N. 89°46' W., bet. secs. 17 and 20.</p>										
19.755	<p>Point for the E 1/16 sec. cor. of secs. 17 and 20.</p>										
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with aluminum cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T5S R23E</td> </tr> <tr> <td colspan="2" style="text-align: center;">S17</td> </tr> <tr> <td style="text-align: center;">E 1/16</td> <td style="border-bottom: 1px solid black;"></td> </tr> <tr> <td colspan="2" style="text-align: center;">S20</td> </tr> <tr> <td colspan="2" style="text-align: center;">1982</td> </tr> </table>	T5S R23E		S17		E 1/16		S20		1982	
T5S R23E											
S17											
E 1/16											
S20											
1982											
39.51	<p>Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the original cor.</p>										
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 23 ins. in the ground, with aluminum cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T5S R23E</td> </tr> <tr> <td colspan="2" style="text-align: center;">S17</td> </tr> <tr> <td style="text-align: center;">1/4</td> <td style="border-bottom: 1px solid black;"></td> </tr> <tr> <td colspan="2" style="text-align: center;">S20</td> </tr> <tr> <td colspan="2" style="text-align: center;">1982</td> </tr> </table>	T5S R23E		S17		1/4		S20		1982	
T5S R23E											
S17											
1/4											
S20											
1982											
79.02	<p>The cor. of secs. 17, 18, 19 and 20.</p>										
	<hr/>										

Dependent Resurvey, Portion, Subdivisional Lines,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.27	<p>S. 89°14' W., bet. secs. 18 and 19.</p> <p>Through area of creosote and scattered juniper.</p> <p>Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T5S R23E S18 ----- S19 1982</p>
80.76	<p>Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>The cor. of secs. 18 and 19 only, on the W. bdy of the Tp., hereinbefore described.</p> <p>From this cor. point, the cor. of secs. 13 and 24 only, on the W. bdy. of the Tp., bears N. 0°06' W., 2.69 chs. dist., hereinbefore described.</p> <hr/>
39.92	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°08' W., bet. secs. 17 and 18.</p> <p>Over mesa's, through area of creosote and some mesquite.</p> <p>Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.</p> <p style="text-align: center;">T5S R23E 1/4 S18   S17 1982</p>
79.84	<p>The cor. of secs. 7, 8, 17 and 18, determined at the center of a mound of stone, 4 x 1 ft. This is accepted as the best available evidence of the original cor. position.</p>

Dependent Resurvey, Portion of the Subdivisional Lines  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS											
	<p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 18 ins. in the ground, with aluminum cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T5S R23E</td></tr> <tr><td style="text-align: center;">S 7</td><td style="text-align: center;">S 8</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S18</td><td style="text-align: center;">S17</td></tr> <tr><td colspan="2" style="text-align: center;">1982</td></tr> </table>	T5S R23E		S 7	S 8	-----		S18	S17	1982	
T5S R23E											
S 7	S 8										
-----											
S18	S17										
1982											
	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89°51' W., between secs. 8 and 17.</p>										
19.59	<p>Point for the E 1/16 sec. cor. of secs. 8 and 9.</p> <p>Set a aluminum post, 28 ins. long, 1 ins. diam., 22 ins. in the ground, in a collar of stone, with aluminum cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T5S R23E</td></tr> <tr><td colspan="2" style="text-align: center;">S8</td></tr> <tr><td colspan="2" style="text-align: center;">E 1/16 1/4 -----</td></tr> <tr><td colspan="2" style="text-align: center;">S17</td></tr> <tr><td colspan="2" style="text-align: center;">1982</td></tr> </table>	T5S R23E		S8		E 1/16 1/4 -----		S17		1982	
T5S R23E											
S8											
E 1/16 1/4 -----											
S17											
1982											
39.18	<p>Point for the 1/4 sec. cor. of secs. 8 and 17 at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set a aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with aluminum cap mkd.</p>										
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T5S R23E</td></tr> <tr><td colspan="2" style="text-align: center;">S8</td></tr> <tr><td colspan="2" style="text-align: center;">1/4 -----</td></tr> <tr><td colspan="2" style="text-align: center;">S17</td></tr> <tr><td colspan="2" style="text-align: center;">1982</td></tr> </table>	T5S R23E		S8		1/4 -----		S17		1982	
T5S R23E											
S8											
1/4 -----											
S17											
1982											
	<p>Raise a mound of stone, 2 1/2 x 1 ft., W. of the cor.</p>										
78.35	<p>The cor. of secs. 7, 8, 17 and 18.</p>										

Dependent Resurvey, Portion of the Subdivisional Lines  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>S. 89°49' W., bet. secs. 7 and 18.</p> <p>Over broken mesa's, through area of mesquite and creosote.</p> <p>39.91 The 1/4 sec. cor. of secs. 7 and 18, determined by the remains of a bearing tree of record</p> <p style="padding-left: 40px;">A mesquite, 15 ins. diam., bears S. 62°30' W., 100 lks. dist.</p> <p>Point falls in a mound of earth, with a wood post, 3 ins. diam., lying loose flattened on one end, no marks visible.</p> <p>At the cor. point</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; padding-left: 100px;"> <p>T5S R23E S 7 1/4 ——— S18 1982</p> </div> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>Deposit remains of original post alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/>
41.04	<p>S. 88°46' W., beginning new measurement</p> <p>The cor. of secs. 7 and 18 ,only, on the W. bdy of the Tp., hereinbefore described.</p> <p>From this cor., the cor. of secs. 12 and 13 only, on the W. bdy. of the Tp., bears N. 0°13' W., 3.06 chs. dist., hereinbefore described.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°07' W., bet. secs. 7 and 8.</p> <p>Over level terrain, through creosote and mesquite.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS																					
39.73	<p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base to top, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td colspan="2">T5S R23E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 7</td><td>  S 8</td></tr> <tr><td colspan="2">1982</td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A crucifixion tree, 4 ins. diam., bears N. 18° W., 25 lks. dist., mkd. 1/4 S7 BT.</p>	T5S R23E		1/4		S 7	S 8	1982													
T5S R23E																					
1/4																					
S 7	S 8																				
1982																					
79.46	<p>The cor. of secs. 5, 6, 7 and 8, monumented with an iron post, 2 1/2 ins. diam., projecting 12 ins. from ground, in a mound of stone, 2 1/2 ft. base to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td colspan="2">T5S R23E</td></tr> <tr><td>S 6</td><td>  S 5</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S 7</td><td>  S 8</td></tr> <tr><td colspan="2">1976</td></tr> </table> </div> <p>Not remonumented</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 4, 5, 8 and 9, monumented with an iron post, 2 1/2 ins. diam., projecting 8 ins. from ground, in a mound of stone, 2 1/2 ft. base to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td colspan="2">T5S R23E</td></tr> <tr><td>S 5</td><td>  S 4</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S 8</td><td>  S 9</td></tr> <tr><td colspan="2">1976</td></tr> </table> </div> <p>Not remonumented</p> <p>S. 89°46' W., bet. secs. 5 and 8.</p> <p>Over rolling land, through medium creosote.</p>	T5S R23E		S 6	S 5	-----		S 7	S 8	1976		T5S R23E		S 5	S 4	-----		S 8	S 9	1976	
T5S R23E																					
S 6	S 5																				
-----																					
S 7	S 8																				
1976																					
T5S R23E																					
S 5	S 4																				
-----																					
S 8	S 9																				
1976																					

Dependent Resurvey, Portion Subdivisional Lines,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.45	<p>Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 6 ins. in the ground, in a mound of stone, 4 1/2 ft. base to top, with aluminum cap mkd.</p> <p style="text-align: center;">T5S R23E S 5 1/4 ——— S 8 1982</p>
78.90	<p>The cor. of secs. 5, 6, 7 and 8.</p> <hr/> <p>S. 89°56' W., bet. secs. 6 and 7.</p> <p>Over rolling lands, through area of creosote.</p>
39.81	<p>The 1/4 sec. cor. of secs. 6 and 7, determined by the remains of a wood post in the center of a mound of earth and rocks, 3 ft. x 6 ins.. This is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stone, 3 1/2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E S 6 1/4 ——— S 7 1982</p> <p>Bury remains of wood post alongside the cor.</p> <hr/> <p>S. 89°15' W., beginning new measurement</p>
15.65	<p>The closing cor. on the Camp Goodwin Military Reservation bdy. (abandoned), hereinbefore described.</p>

Dependent Resurvey, Portion Subdivisional Lines,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, the new Cor. No. 2, Camp Goodwin Military Reservation, bears N. 44°47' E., 125.115 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the original Cor. No. 3 of Camp Goodwin Military Reservation, bears S. 44°57' W., 174.875 chs. dist., hereinbefore described.</p>
41.25	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp. hereinbefore described.</p>
	<hr/> <p>N. 1°04' W., bet. secs. 5 and 6.</p> <p>Over level terrain, through area of creosote and mesquite.</p>
39.96	<p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 22 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T5S R23E 1/4 S 6   S 5 1982</p>
	<p>Set a steel fence post alongside the cor.</p>
54.26	<p>The closing cor. of the Camp Goodwin Military Reservation bdy. (abandoned), hereinbefore described.</p> <p>From this cor. point, the new Cor. No. 2 of Camp Goodwin Military Reservation, bears N. 44°57' E., 48.075 chs. dist., hereinbefore described.</p> <p>From this same cor. point, the original Cor. No. 3 of Camp Goodwin Military Reservation, bears S. 44°57' W., 251,915 chs. dist., hereinbefore described.</p>
79.74	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., hereinbefore described</p> <hr/>

Subdivision of Selected Sections,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Subdivision of Section 17
	From the 1/4 sec. cor. of secs. 17 and 20.
	N. 0°22' W., on the N. and S. center line of sec. 17.
19.975	Point for the center S 1/16 sec. cor. of sec. 17.
	Set an aluminum post, 28 ins. long, 1 in. diam., 6 ins. in the ground, in a mound of stone, 2 1/2 ft. base to top, with aluminum cap mkd.
	T5S R23E C S 1/16   S17 C 1982
39.95	Point for the center 1/4 sec. cor. of sec. 17, at the intersection with the E. and W. center line of sec. 17.
	Set an aluminum post, 28 ins. long, 1 in. diam., 23 ins. in the ground, with aluminum cap mkd.
	T5S R23E C 1/4 S17 1982
78.89	Raise a mound of stone, 3 ft. base, 1 ft. high, W. of cor. The 1/4 sec. cor. of secs. 8 and 17.
	From the 1/4 sec. cor. of secs. 16 and 17.
	N. 89°49' W., on the E. and W. center line of sec. 17.
	Over level terrain, through creosote.
19.67	Point for the center E 1/16 sec. cor. of sec. 17.
	Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. in the ground, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap mkd.

Subdivision of Selected Sections,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">T5S R23E E 1/16 C ————— C S17 1982</p> <p>39.34 The center 1/4 sec. cor. of sec. 17.</p> <p>78.67 The 1/4 sec. cor. of secs. 17 and 18.</p> <hr/> <p style="text-align: center;">SE 1/4 of Section 17</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 17 and 20.</p> <p>N. 0°29' W., on the N. and S. center line of the SE 1/4 of sec. 17.</p> <p>Over level terrain, through creosote.</p> <p>19.98 Point for the SE 1/16 sec. cor. of sec. 17, at intersection with the E. and W. center line of the SE 1/4 of sec. 17.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 23 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T5S R23E SE 1/16 S17 1982</p> <p>39.97 The center E 1/16 sec. cor. of sec. 17.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 16 and 17.</p> <p>N. 89°47' W., on the E. and W. center line of the SE 1/4 of sec. 17.</p> <p>Over level terrain, through creosote.</p> <p>19.72 The SE 1/16 sec. cor. of sec. 17.</p> <p>39.43 The center S 1/16 sec. cor. of sec. 17.</p> <hr/>
--------	---

Subdivision of Selected Sections,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	Subdivision of Section 19
	<p>From the 1/4 sec. cor. of secs. 19 and 30.</p> <p>N. 0°03' E., on the N. and S. center line of sec. 19.</p>
19.95	<p>Point for the center S 1/16 sec. cor. of sec. 19.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone, 2 1/2 ft. base to top, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T5S R23E C S 1/16   S19 C 1982</p> </div>
39.90	<p>Point for the center 1/4 sec. cor. of sec. 19, at the intersection with the E. and W. center line of sec. 19.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 4 ins. in the ground, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T5S R23E C 1/4 S19 1982</p> </div>
79.86	<p>The 1/4 sec. cor. of secs. 18 and 19.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 20.</p> <p>S. 89°09' W., on the E. and W. center line of sec. 19.</p> <p>Through area of creosote.</p>
40.08	<p>The center 1/4 sec. cor. of sec. 19.</p>
80.33	<p>The 1/4 sec. cor. of sec. 19, on the W. bdy. of the Tp.</p> <hr/>

Subdivision of Selected Sections,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	Subdivision of Section 20
39.58	<p>From the 1/4 sec. cor. of secs. 20 and 29. N. 0°04' E., on the E. and W. center line of sec. 20.</p> <p>Point for the center 1/4 sec. cor. of sec. 20, at the intersection with the E. and W. center line of sec. 20.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T5S R23E C 1/4 S20 1982</p> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 5 ins. diam., bears N. 74 1/2° W., 72.5 lks. dist., mkd. C 1/4 S20 BT.</p>
79.51	<p>The 1/4 sec. cor. of secs. 17 and 20.</p>
39.62	<p>From the 1/4 sec. cor. of secs. 20 and 21. N. 89°41' W., on the E. and W. center line of sec. 20.</p> <p>The center 1/4 sec. cor. of sec. 20.</p>
79.29	<p>The 1/4 sec. cor. of secs. 19 and 20.</p>
	<p style="text-align: center;">Subdivision of Section 26</p> <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 35. N. 0°23' W., on the N. and S. center line of sec. 26. Over level terrain, through creosote.</p>

Subdivision of Selected Sections,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.02	<p>Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E. and W. center line of sec. 26.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T5S R23E C 1/4 S26 1982</p> <p>Cor. is located 18 lks. N. of an E. and W. fence line.</p>
80.04	<p>The 1/4 sec. cor. of secs. 23 and 26.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26.</p> <p>S. 89°43' W., on the E. and W. center line of sec. 26.</p>
20.06	<p>Point for the center E 1/16 sec. cor. of sec. 26.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 25 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T5S R23E E 1/16 C ————— C S26 1982</p> <p>From this cor. point a fence cor., bears N. 80° W., 124 lks. dist., fence bears E. and W.</p>
40.12	<p>The center 1/4 sec. cor. of sec. 26.</p>
60.18	<p>Point for the center W 1/16 sec. cor. of sec. 26.</p> <p>Set a copperweld, 28 ins. long, 5/8 in. diam., 6 ins. below ground surface of a trail road, with aluminum cap mkd.</p> <p style="text-align: center;">T5S R23E W 1/16 C ————— C S26 1982</p>

Subdivision of Selected Sections,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>An aluminum post, 28 ins. long, 1 in. diam., set 27 ins. in the ground, for a reference monument, bears S. 26°30' W., 14.60 ft. dist., with aluminum cap mkd. RM T5S R23E S26 14.60 FT 1982, and an arrow pointing to the cor.</p> <p>An aluminum post, 28 ins. long, 1 in. diam., set 26 ins. in the ground, for a reference monument, bears N. 19°30' W., 12.79 ft. dist., with aluminum cap mkd. RM T5S R23E S26 12.79 FT 1982, and an arrow pointing to the cor.</p> <p>Cor. is located 8 lks. E. of a N. and S. fence and 21 lks. S. of an E. and W. fence.</p>
80.24	The 1/4 sec. cor. of secs. 26 and 27.
<hr/> Subdivision of Section 30 <hr/>	
	<p>From the 1/4 sec. cor. of secs. 30 and 31.</p> <p>N. 0°07' W., on the N. and S. center line of sec. 30.</p>
19.96	Point for the center S 1/16 sec. cor. of sec. 30.
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 21 ins. in the ground, in a mound of stone, 2 ft. base, to top, with aluminum cap mkd.</p> <p style="text-align: center;">T5S R23E C S 1/16   S30 C 1982</p>
	<p>from which</p> <p>A mesquite, 6 ins. diam., bears N. 52° E., 41.5 lks. dist., mkd. C S 1/16 S30 BT.</p> <p>A mesquite, 5 ins. diam., bears S. 26 1/2° E., 60 lks. dist., mkd. C S 1/16 S30 BT.</p>
39.92	Point for the center 1/4 sec. cor. of sec. 30, at the intersection with the E. and W. center line of sec. 30.

Subdivision of Selected Sections,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set an aluminum post, 28 ins. long, 1 in. diam., 20 ins. in the ground, with aluminum cap mkd.
	<p style="text-align: center;">T5S R23E C 1/4 S30 1982</p>
	Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.
79.74	The 1/4 sec. cor. of secs. 19 and 30.
	From the 1/4 sec. cor. of secs. 29 and 30.
	S. 89°14' W., on the E. and W. center line of sec. 30.
39.85	The center 1/4 sec. cor. of sec. 30.
79.83	The 1/4 sec. cor. of sec. 30 only, on the W. bdy. of the Tp.
	Subdivision of Section 34
	From the stan. 1/4 sec. cor. of sec. 34, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 5 ins. from ground, with brass cap mkd.
	<p style="text-align: center;">S C T5S R23E 1/4 S34 ----- 1967</p>
	N. 0°29' W., on the N. and S. center line of sec. 34.
39.71	Point for the center 1/4 sec. cor. of sec. 34, at the intersection with the E. and W. center line of sec. 34.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T5S R23E C 1/4 S34 1982</p>
79.66	The 1/4 sec. cor. of secs. 27 and 34.

Subdivision of Selected Sections,  
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>From the 1/4 sec. cor. of secs. 34 and 35.</p> <p>N. 89°33' W., on the E. and W. center line of sec. 34.</p> <p>39.15 The center 1/4 sec. cor. of sec. 34.</p> <p>78.94 The 1/4 sec. cor. of secs. 33 and 34.</p> <hr/> <p style="text-align: center;">Subdivision of Section 35</p> <hr/> <p>From the stan. 1/4 sec. cor. of sec. 35, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. from ground, with brass cap mkd.</p> <p style="text-align: center;">S C T5S R23E 1/4 S35</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">1967</p> <p>Not remonumented</p> <p>N. 0°21' W., on the N. and S. center line of sec. 35.</p> <p>39.74 Point for the center 1/4 sec. cor. of sec. 35, at the intersection with the E. and W. center line of sec. 35.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 23 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T5S R23E C 1/4 S35 1982</p> <p>79.75 The 1/4 sec. cor. of secs. 26 and 35.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 35 and 36.</p> <p>S. 89°39' W., on the E. and W. center line of sec. 35.</p> <p>39.88 The center 1/4 sec. cor. of sec. 35.</p> <p>80.47 The 1/4 sec. cor. of secs. 34 and 35.</p> <hr/>
--------	--

T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS

## GENERAL DESCRIPTION

The land encompassed in this survey is located just south of Camp Thomas, Arizona. The elevation ranges from about 2700 to 3100 feet from sea level.

The land varies from nearly level to gently rolling with some mesa's. The vegetation consists of creosote, mesquite and cacti, with some cottonwood and ash along Black Rock Wash. Black Rock Wash drains across the township in a northeasterly direction.

Access is by way of U.S. Highway No. 70, which crosses the northeastern portion of the township in a north-northwesterly direction, paralleled by the Southern Pacific Railroad. There are several unimproved or lightly graveled roads throughout the township.

The mean magnetic declination is 13 1/2° E.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Vince Hanneken	Land Surveyor
Kevin L. Miller	Surveying Technician
Donald L. Brewer	Surveying Technician
Neil A. Hemminger	Surveying Technician
Delbert L. Bybee	Surveying Technician

## CERTIFICATE OF SURVEY

We, Paul L. Reeves and Will C. Gabonay, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 8th day of April, 1982 and supplemental special instructions dated and approved January 11, 1985. We have dependently resurveyed portions, of the Camp Goodwin Military Reservation, (abandoned), of the west boundary, of the north boundary, of the subdivisional lines and the subdivision of selected sections in Township 5 South, Range 23 East, of the Gila and Salt River Meridian, in the State of Arizona which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Paul L. Reeves and Will C. Gabonay are no longer assigned to this office and are not available for signatures.

6/6/91  
(Date)

James L. Dinkel  
(Field Supervisor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Arizona State Office  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the Camp Goodwin Military Reservation, (abandoned), of the west boundary, of the north boundary, of the subdivisional lines and the subdivision of selected sections in Township 5 South, Range 23 East, Gila and Salt River Meridian, Arizona, executed by Paul L. Reeves and Will C. Gabonay, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

JUN 11 1991

(Date)

James P. Kelley  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I Certify that the foregoing transcript of the field notes of the above-described surveys in T 5 S, R 23 E, Gila and Salt River Meridian, Arizona is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~