
B00K 5317

ORIGINAL

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT



FIELD NOTES

OF THE
DEPENDENT RESURVEY OF A PORTION OF THE
ARIZONA-NEW MEXICO STATE LINE
AND THE
DEPENDENT RESURVEY OF A PORTION OF THE
NORTH AND SOUTH BOUNDARIES AND SUBDIVISIONAL LINES
AND THE
SURVEY OF SUBDIVISIONS IN SECTIONS 2, 21, 22, AND 27,
TOWNSHIP 7 NORTH, RANGE 31 EAST
Of theGila and Salt River Meridian,
In the State ofArizona
EXECUTED BY
Paul L. Reeves, Cadastral Surveyor
Under special instructions dated August 5, 1983, approved August 5, 1983,
, which provided for the surveys included under Group Number
and assignment instructions dated August 5, 1983,
Survey commenced August 9 , 1983
Survey completed September 5 , 1985

2

INDEX DIAGRAM

	T(OWNSHIP 7 NORT	H, RANGE 31	EAST,	203 M 4 . A 204 M R
6	5	4	3	29 28 2 30 30 25	6 Z O N 205 M A I N 7 E
7	8	9	10	11	206 M M E X I C
18	17	16 4 45	15	25 14	207 M S T 10 A
19	20 4:			22 23	208 M L I
30	29	28 3	3 27	20 26	N E
31	32	33 3		18 35	
16		14	12		1

SUBDIVISION OF SECTION 2.....pp. 47-50 SUBDIVISION OF SECTION 21.....pp. 50-57 SUBDIVISION OF SECTION 22.....pp. 57-81 SUBDIVISION OF SECTION 27.....pp. 81-85

BOOK 5317

T 7 N, R 31 E, Gila and Salt River Mer., Arizona

CHAINS

The following field notes are these of the dependent resurvey of a portion of the Arizona-New Mexico State Line from the 203rd mile corner to the 206th mile cor. and from the 207th mile corner to the 208th mile cor., the dependent resurvey of portions of the south boundary, north boundary and subdivisional lines, and a survey of subdivisions in sections 2, 21, 22, and 27, Township 7 North, Range 31 East, Gila and Salt River Meridian, Arizona.

Chandler Robbins surveyed the east boundary (Arizona-New Mexico State Line), in 1875. C. Burton Foster surveyed a portion of the west boundary in 1875. W.R. Fitzgerald resurveyed the north three miles of the west boundary and surveyed the south three miles of the west boundary, the south and north boundaries and the subdivisional lines in 1883. W.H. Thorn resurveyed the east boundary (Arizona-New Mexico State Line), and a portion of the north boundary in 1902-03. Benjamin J. Kinsey resurveyed the west boundary in 1925. Lloyd E. Toland dependently resurveyed a portion of the state line in 1937 while surveying in Township 4 South, Range 21 West, New Mexico Principal Meridian. Roger F. Wilson reconstructed the northwest corner of section 2 in 1936 while surveying in Township 8 North, Range 31 East, Gila and Salt River Meridian. Gary T. Oviatt retraced a portion of the east boundary (Arizona-New Mexico State Line), and resurveyed a portion of the south boundary in 1969. The corner of sections 2, 3, 10, and 11 was remonumented by Charles C. Doak of the U.S. Forest Service in 1974. Paul L. Reeves remonumented the southwest corner of section 34 in 1976 while surveying in Township 6 North, Range 31 East. A portion of the east boundary (Arizona-New Mexico State Line), was retraced and a portion of the north boundary was resurveyed by Harry K. Smith in 1979.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 646, Arizona dated August 5, 1983.

The direction of the lines of this survey was determined by altitude observations on the sun and refer to the true meridian. Distances were measured with a Hewlett Packard 3820A and Ziess Elta 46, total station instruments.

T 7 N. R 31 E. Gila and Salt River Mer., Arizona

CHAINS

Preliminary to the resurvey the lines of the surveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic postion of the cor. of secs. 2, 3, 34, and 35, Tps. 6 and 7 N, R 31 E, as computed from a tie to U.S.G.S. triangulation station "Loco", located in sec. 17, T 7 N, R 31 E, is as follows:

NAD 27: Latitude: 33°57'04.8" N Longitude: 109 03'16.0" W

The mean magnetic declination is 13 1/2 E.

Reestablishment of the retracement by Harry K. Smith in 1979.

Beginning at mile cor. 203 on the Arizona-New Mexico State Line, monumented with an iron post, 2 1/2 ins. diam., projecting 7 ins. above the ground, with brass cap mkd.

203M | NEW ARIZONA | MEXICO 1979

A mount of stone, 2 1/2 ft. base, 2 ft. high is W of the cor.

Cor. is located 49 lks. E of a N and S fence.

S O Ol' E, on the 204th mile of the Arizona-New Mexico State Line.

Over gently rolling grassland, through scattered timber.

	AT IZOId-New Mexico State Line
CHAINS	
40.31	The closing cor. of secs. 26 and 35, T 8 N, R 31 E, Gila and Salt River Meridian, Arizona, monumented with an iron post, $2\frac{1}{2}$ ins. diam., projecting 7 ins. above the ground, with brass cap mkd.
	cc $\frac{\frac{T8N}{526}}{\frac{535}{835}}$ R31E 1979
	from which
	A juniper, 4 ins. diam., bears S 39° W, 1.15 chs. dist., mkd. T8N R31E CC S35 BT.
	A windmill, bears S 58°54' W.
	A pinyon, 12 ins. diam., bears N 57° W, 59 lks. dist., mkd. T8N R31E CC S26 BT.
	A mound of stone, 2 1/2 ft. base, 1 1/2 ft. high is W of cor.
44.68	The closing cor. of secs. 9 and 16, T 3 S, R 21 W, New Mexico Prin. Mer., monumented with an iron post, 2 ins. diam., projecting 15 ins. above ground, with brass cap mkd.
	ARIZ C S 9 C S16
	1914
	Cor. is located 1 lk. N of a fence, bears E and W, 32.5 lks. dist. to a fence cor.; fences extend N, E, and S 63° W.
79.40	U.S. Forest Service road No. 205, bears E and W.
79.92	Point for mile cor. 204 on the Arizona-New Mexico State Line, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 72 ins. long, $\frac{3}{4}$ in. diam., 66 ins. in the ground, with cap mkd.

204M ARIZONA NEW MEXICO

CHAINS

Cor. is located in a fence, 4.5 lks. N of a fence cor., fences extend N, S and W.

1983

S 0°04' W, on the 205th mile of the Arizona-New Mexico State Line.

Over nearly level grassland, along a fence.

The closing cor. of secs. 2 and 35, Tps. 7 and 8 N, R 31 E, Gila and Salt River Mer., Arizona, identical with Boundary Post 74 of the Black Mesa Forest Reserve, monumented with an iron post, $3\frac{1}{2}$ ins. diam., projecting 10 ins. above a mound of stone, 3 ft. base, 6 ins. high, with brass cap mkd. as described in the official record of the 1902-03 resurvey.

Cor. is located 1 lk. W of a N and S fence.

The closing cor. of secs. 16 and 21, T 3 S, R 21 W, New Mexico Prin. Mer., monumented with a U.S. Dept. of Agriculture aluminum post, $2\frac{1}{2}$ ins. diam., projecting 6 ins. above ground, in a mound of stone, 2 ft. base, to top, with cap mkd.

From this point the closing cor. of secs. 16 and 21, T 3 S, R 21 W, New Mexico Prin. Mer., set in 1914, bears East, 3.4 lks. dist., monumented with an iron post, 2 ins. diam., projecting 15 ins. above the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap mkd.

Cor. is located in a N and S fence.

	A1201a-New Mexico State IIIIe
CHAINS	
54.795	From this point on line a U.S. Dept. of Agriculture aluminum post, 2½ ins. diam., bears West, 2.1 lks. dist., projecting 8 ins. above the ground, with cap mkd.
	T3S R21W Lot 5 CC IS Tot 6 7258 S21 1980
	Cor. is located 4 lks. W of a fence cor., fences extend N, E and S.
60.67	Point for the N 1/16 sec. cor. of sec. 2 only, Frac. T 7 N, R 31 E, Gila and Salt River Mer., Arizona, hereinafter described.
80.225	The 205th mile cor. on the Arizona-New Mexico State Line, monumented with an iron post, $2\frac{1}{2}$ ins. diam., projecting 8 ins. above the ground, with brass cap mkd.
	205M
	New
	Arizona Mexico 1979
	A mound of stone, 3 ft. base, l_2^1 ft. high is W of the cor.
	Cor. is located in a fence, 1.5 lks. N of a fence cor., fences extend N, S and W.
	Reestablishment of the resurvey executed by W.H. Thorn, U.S. Surveyor, in 1902.
	S 0°03' W, on the 206th mile of the Arizona-New Mexico State Line.
0.32	Point for the ½ sec. cor. of sec. 2 only, Frac. T 7 N, R 31 E, Gila and Salt River Mer., Arizona, hereinafter described.
4.55	The $\frac{1}{4}$ sec. cor. of sec. 21 only, T 3 S, R 21 W, New Mexico Prin. Mer., monumented with a U.S. Forest Service aluminum post, $2\frac{1}{2}$ ins. diam., projecting 7 ins. above the ground, with cap mkd.
	L

	Arizona-New Mexico State Line
CHAINS	
	T3S ½ IS CC 7258 S21 R21W 1980
	A steel fence post is alongside the cor.
	Cor. is located 1.5 lks. E of a N and S fence.
11.425	A rebar, ½ in. diam., projecting 3 ins. above ground, with tag attached and mkd. IS 7258, located 2.5 lks. E of a N and S fence, with a steel fence post alongside.
14.545	A U.S. Forest Service aluminum post, $2\frac{1}{2}$ ins. diam., projecting 4 ins. above ground, with cap mkd.
	T3S R21W Lot 7 CC Lot 8 S21 LS 7258 1980
	A steel fence post is alongside the cor.
	Cor. is located 1.5 lks. E of a N and S fence.
	Continue through medium timber.
20.195	Point for the S 1/16 sec. cor. of sec. 2 only, Frac. T 7 N, R 31 E, Gila and Salt River Meridian, Arizona, hereinafter described.
29.425	Forest Reserve Cor. 73, monumented with an iron post, $3\frac{1}{2}$ ins. diam., projecting 22 ins. above ground, with brass cap mkd. as described in the official record of the 1902-03 resurvey.
	Cor. is located 1 lk. E of a N and S fence.
40.07	The closing cor. of secs. 2 and 11, T 7 N, R 31 E, Gila and Salt River Mer., Arizona, hereinafter described.

	THIZOID NEW MEXICO DEADE DIME
CHAINS	
44.53	The closing cor. of secs. 21 and 28, T 3 S, R 21 W, New Mexico Prin. Mer., monumented with a U.S. Forest Service aluminum post, $2\frac{1}{2}$ ins. diam., projecting 8 ins. above the ground, in a mound of stone, $1\frac{1}{2}$ ft. base, to top, with cap mkd.
	T3S S21 CC LS S28 7258 R21W 1980
	From this point, the original closing cor. of secs. 21 and 28, bears East, 1.5 lks. dist., monumented with sandstone, 12 x 12 x 4 ins. above ground, marks visible, CC on E face, from which original bearing trees.
	A ponderosa pine stump, 40 ins. diam., bears N 17° E, 87.5 lks. dist., no marks visible. (Record N 13½° E, 1 ch. dist.)
	A ponderosa pine, 32 ins. diam., bears S 73° E, 2.22 chs. dist., mkd. T 3 S R 21 W S28. (Record S 78° E, 2.37 chs. dist.)
80.15	The 206th mile cor. on the Arizona-New Mexico State Line, monumented with a U.S. Dept. of Agriculture aluminum post, $2\frac{1}{2}$ ins. diam., projecting 7 ins. above the ground, in a mound of stone, $1\frac{1}{2}$ ft. base, to top, with cap mkd.
	206M ARIZONA NEW MEXICO 7258 1980 RLS 11758
	A steel fence post is alongside the cor.
	from which a 1902-03 bearing tree
	An oak, 17 ins. diam., bears N 27° E, 1.035 chs. dist., marks visible N only. (Record N 23¼° E, 99 lks. dist.)
	and from which new bearing trees
	A ponderosa pine, 16 ins. diam., bears S 66° E, 1.05 chs. dist., mkd. NEW MEXICO 206 M BT.

CHAINS	
	A ponderosa pine, 7 ins. diam., bears N 6° W, 1.16 chs. dist., mkd. 206 M AZ BT.
	Add the date 1983 to the cap.
	From the 207th mile cor. on the Arizona-New Mexico State Line, monumented with a lava stone, 12 x 11 x 27 ins. above the ground, in a mound of stone, $3\frac{1}{2}$ ft. base, 1 ft. high, firmly set and mkd. 207 on N face, N.M. on E face, 32 WL on S face and ARIZ on W face, from which the original bearing trees
	A dead standing oak, 10 ins. diam., bears N 10°12' E, 34 lks. dist., illegible scribe marks visible.
	A ponderosa pine, 18 ins. diam., bears S 71° E, 28 lks. dist., healed blaze.
	A stump hole, bears S $42\frac{1}{2}^{\circ}$ W, 14 lks. dist.
	and from which new bearing trees
	A ponderosa pine, 10 ins. diam., bears N $75\frac{1}{2}^{\circ}$ E, 1.15 chs. dist., mkd. 207 M NM BT.
	A ponderosa pine, 8 ins. diam., bears N 24° W, 5.5 lks. dist., mkd. 207M AZ BT.
	S 0°06' W, on the 208th mile of the Arizona-New Mexico State Line.
39.33	Point for the closing cor. of secs. 14 and 23, T 7 N, R 31 E, Gila and Salt River Mer., Arizona at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, and in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	CC $\frac{\frac{\text{T7N}}{\text{S14}}}{\frac{\text{S23}}{\text{R31E}}}$ 1983
	from which
	A Douglas fir, 9 ins. diam., bears S 17° W, 56.5 lks. dist., mkd. T7N R31E S23 CC BT.

	Arizona-New Mexico State Line
CHAINS	
	A ponderosa pine, 16 ins. diam., bears N 5° W, 1.00 ch. dist., mkd. T7N R31E S14 CC BT.
44.17	From this point on line, the closing cor. of secs. 4 and 33, Tps. 3 and 4 S, R 21 W, New Mexico Prin. Mer., bears East, 5.8 lks. dist., monumented with an iron post, 3 ins. diam., projecting 16 ins. above the ground, with brass cap mkd.
	ARIZ T3S R21W S33 CC S 4 T4S T4S 1914
	from which the original bearing trees
	A dead standing spruce, 16 ins. diam., bears N 21° E, 78 lks. dist., mkd. T3S R21W S33 CC BT.
	A dead standing spruce, 12 ins. diam., bears S 47° W, 79 lks. dist., healed blaze.
47.385	From this point on line, the Black Mesa Forest Reserve post 71 bears East, 4 lks. dist., monumented with an iron post, $3\frac{1}{2}$ ins. diam., projecting 32 ins. above ground, with brass cap mkd. as described in the official record of the 1902-03 resurvey.
79.59	The 208th mile cor. on the Arizona-New Mexico State Line, monumented with an iron post, 2 ins. diam., projecting 18 ins. above ground, in mound of stone, 2 ft. base, 6 ins. high, with brass cap mkd.
	208
	ARI NM 1937
	from which the 1875 bearing trees
	A ponderosa pine, 23 ins. diam., bears S 86° E, 65 lks. dist., marks visible 08. (Record East)
	A dead fallen oak, 13 ins. diam., bears S 8° W, 28 lks. dist., marks visible 0. (Record S 20° W)

CHAINS

A ponderosa pine, 28 ins. diam., bears N 25° W, 45 lks. dist., marks visible on old blaze 208. This tree was reblazed and remkd. in the 1937 resurvey, marks visible 208 ARIZ BT. (1937 Record N 31½° W)

and from which the 1937 bearing trees

- A ponderosa pine, 14 ins. diam., bears N 40° E, 79 lks. dist., healed blaze. (Record N 35¾° E, 74 lks. dist.)
- A ponderosa pine, 28 ins. diam., bears S 65° E, 65 lks. dist., mkd. 208 NM BT (Record S 66½° E, 60 lks. dist.)
- A white oak, 22 ins. diam., bears West, 1.06 chs. dist., mkd. 208 ARIZ BT. (Record S 86½° W, 99 lks. dist.).

Dependent Resurvey of a Portion of the South Boundary T 7 N, R 31 E, Gila and Salt River Mer., Arizona

Reestablishment of the resurvey by W. R. Fitzgerald in 1883.

From the cor. of secs. 2, 3, 34, and 35, Tps. 6 and 7 N, R 31 E, monumented with an iron post, $2\frac{1}{2}$ ins. diam., projecting 5 ins. above the ground, with brass cap mkd.

T7N R31E S34 | S35 S 3 | S 2 T6N 1969

from which an original bearing tree

A pine stump, 25 ins. diam., bears N 49¾° E, 75 lks. dist., marks visible 5 BT.

and from which the 1969 bearing trees

- A ponderosa pine, 12 ins. diam., bears S 77% E, 1.28 chs. dist., marks visible through partly healed blaze N S2 BT.
- A ponderosa pine, 10 ins. diam., bears S 47½° W, 1.87 chs. dist., mkd. T6N R31E S3 BT.

	1 / N, K 31 E, Gila and Salt River Mer., Arizona
CHAINS	
	and from which new bearing trees
	A ponderosa pine, 6 ins. diam., bears N $8\frac{1}{2}^{\circ}$ E, 21.5 lks. dist., mkd. T7N R31E S35 BT.
	A ponderosa pine, 6 ins. diam., bears N $44\frac{3}{4}^{\circ}$ W, 1.41 chs. dist., mkd. T7N R31E S34 BT.
	A mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high is W of cor.
	Add the marks 1985 to the cap.
	N 89°42' W, bet. secs. 3 and 34.
	Over gently rolling land, through medium timber.
40.08	The $\frac{1}{4}$ sec. cor. of secs. 3 and 34, monumented with a basalt stone, 30 x 20 x 8 ins., projecting 25 ins. above ground, mkd. $\frac{1}{4}$ on top, from which remains of an original bearing tree
	A pine stump, 14 ins. diam., bears S 39½° E, 4 lks. dist., no marks visible.
	At the cor. point
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, with cap mkd.
	T7N R31E 1 ₄ <u>S34</u> S 3 T6N 1985
	from which
	A ponderosa pine, 10 ins. diam., bears N $6\frac{1}{2}^{\circ}$ E, 15 lks. dist., mkd. $\frac{1}{4}$ S34 BT.
	A ponderosa pine, 6 ins. diam., bears S $49\frac{1}{4}^{\circ}$ W, 28 lks. dist., mkd. $\frac{1}{4}$ S3 BT.
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

	T / N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
	Bury the mkd. stone in the mound of stone.
	Set a steel fence post near the cor.
	N 89°47' W, beginning new measurement.
40.12	The cor. of secs. 3, 4, 33, and 34, monumented with an iron post, $2\frac{1}{2}$ ins. diam., projecting 6 ins. above the ground, with brass cap mkd.
	T7N R31E S33 S34 S 4 S 3 T6N 1976
	from which the remains of the 1883 bearing trees
	A stump hole of a fallen pine, 10 ins. diam., bears N 68½° E, 36 lks. dist., tree mkd. T7N R31E S34 BT.
	A ponderosa pine, 15 ins. diam., bears S 40° E, 26 lks. dist., marks visible through partly healed blaze 31 E S.
:	and from which the 1976 bearing trees
	A ponderosa pine, 6 ins. diam., bears N 40° E, 61.5 lks. dist., mkd. T7N R31E S34 BT.
	A ponderosa pine, 18 ins. diam., bears S 5° E, 83 lks. dist., mkd. T6N R31E S3 BT.
	A ponderosa pine, 17 ins. diam., bears S 22° W, 42.5 lks. dist., mkd. T6N R31E S4 BT.
	A ponderosa pine, 10 ins. diam., bears N 20° W, 64.5 lks. dist., mkd. T7N R31E S33 BT.
	S 88°57' W, bet. secs. 4 and 33.
	Over rolling land, through medium timber.
40.67	Point for the ½ sec. cor. of secs. 4 and 33, at proportionate dist.; there is no remaining evidence of the original cor.

	IN	S

Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 32 ins. in the ground, with cap mkd.

T7N R31E

1/4 S33
S 4
T6N
1983

from which

An aspen, 3 ins. diam., bears S 43° E, 19.5 lks. dist., bark scribed X at breast height, and BT at base.

An aspen, 4 ins. diam., bears N 71° W, 49 lks. dist., bark scribed X at breast height, and BT at base.

81.34 Point for the cor. of secs. 4, 5, 32, and 33, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, with cap mkd.

from which

- A Douglas fir, 5 ins. diam., bears N 60° E, 34 lks. dist., mkd. T7N R31E S33 BT.
- A ponderosa pine, 6 ins. diam., bears S 14° E, 59.5 lks. dist., mkd. T6N R31E S4 BT.
- A ponderosa pine, 6 ins. diam., bears S 27° W, 57.5 lks. dist., mkd. T6N R31E S5 BT.
- A Douglas fir, 6 ins. diam., bears N 63° W, 7 lks. dist., mkd. T7N R31E S32 BT.

Set a steel fence post near the cor.

CHAINS

From this point the cor. of Tps. 6 and 7 N, Rs. 30 and 31 E, bears S 88°57' W, 162.69 chs. dist., monumented with an iron post, 3 ins. diam., projecting 4 ins. above the ground, with brass cap mkd.

T7N
R30E | R31E
S36 | S31
S 1 | S 6
T6N
1925

from which the 1925 bearing trees

- A Douglas fir, 22 ins. diam., bears N 73° E, 24 lks. dist., healed blaze.
- A ponderosa pine, 10 ins. diam., bears S 13½° E, 26 lks. dist., mkd. T6N R31E S6 BT.
- An aspen, 12 ins. diam., bears S 27° W, 12 lks. dist., and bark scribed T6N R30E S1 BT.
- A Douglas fir, 20 ins. diam., bears N 4° W, 24 lks. dist., mkd. T7N R30E S36 BT.

A mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, is W of cor.

The control line was fully retraced and no evidence of the intervening cors. was found.

Dependent Resurvey of a Portion of the North Boundary T 7 N, R 31 E, Gila and Salt River Mer., Arizona

Reestablishment of the resurvey executed by Harry K. Smith in 1979.

From the cor. of secs. 2, 3, 34, and 35, monumented with an iron post, 2 ins. diam., projecting 14 ins. above the ground, with brass cap mkd.

CHAINS	
	T8N R31E S34 S35 S 3 S 2 T7N 1936
	from which an 1883 bearing tree
	A pinyon pine, 12 ins. diam., bears S ½° W, 1.14 chs. dist., mkd. T7N R31E S2 BT.
	and from which 1936 bearing trees
	A pinyon, 12 ins. diam., bears N 25½° E, 3.53 chs. dist., mkd. T8N R31E S35 BT.
	A pine stump, 13 ins. diam., bears S 10° W, 1.23 chs. dist., the bottom end of a healed blaze is the only remaining mark.
	A juniper, 12 ins. diam., bears N 64° W, 3.90 chs. dist., mkd. T8N R31E S34 BT.
	and from which
	An iron post, 4 ins. diam., projecting 22 ins. above the ground, bears S 70½° E, 2.57 chs. dist., with brass cap mkd. U.S. Forest Reserve boundary post 75 1902.
	A mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, is W of cor.
	S 88°45' E, bet. secs. 2 and 35.
	Over gently rolling land through scattered juniper and pinyon.
9.97	Point for the W-W 1/64 sec. cor. of secs. 2 and 35.
	Set a monument, 30 ins. long, composed of an iron post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 25 ins. in the ground, with brass cap mkd.
	S35 W-W 1/64 S2 1983

	T / N, R 31 E, Glia and Salt River Mer., Arizona
CHAINS	
	from which
	A pinyon, 9 ins. diam., bears S 12° W, 1.01 chs. dist., mkd. W-W 1/64 S2 BT.
	A fence cor. bears N 68° W, 1.22 chs. dist., fences extend S 3° W and S 88° W.
	Set a steel fence post near the cor.
19.94	Point for the W 1/16 sec. cor. of secs. 2 and 35.
	Set a monument, 30 ins. long, composed of an iron post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 25 ins. in the ground, with brass cap mkd.
	T8N R31E W 1/16 S35
	S 2 T7N
	1983
	from which
	A fence cor. bears N 16½° W, 2.80 chs. dist., fences extend N and E.
	Raise a mound of stone, 2 ft. base, 1 ft. high, N of cor.
	Set a steel fence post near the cor.
39.38	The closing cor. of secs. 2 and 35, on the Arizona-New Mexico State Line, hereinbefore described.
	From this point the 204th mile cor., bears N 0°04' E, 41.37 chs. dist., hereinbefore described.
	Dependent Resurvey of a Portion of the Subdivisional Lines T 7 N, R 31 E, Gila and Salt River Mer., Arizona
	Reestablishment of the survey executed by W. R. Fitzgerald in 1883

	1 / N, K 31 E, GIIA and Sait River Her., Alizona
CHAINS	
	From the cor. of secs. 2, 3, 34, and 35, Tps. 6 and 7 N, R 31 E, hereinbefore described.
	N 0°38' E, bet. secs. 34 and 35.
	Over rolling land, through medium to dense timber.
38.72	Point for the ½ sec. cor. of secs. 34 and 35 at proportionate dist.; there is no evidence of the original cor.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.
	T7N R31E
	S34 S35 1985
	from which
	A ponderosa pine, 8 ins. diam., bears S $55\frac{1}{4}^{\circ}$ E, 88 lks. dist., mkd. $\frac{1}{4}$ S35 BT.
	A Douglas fir, 10 ins. diam., bears N 19½° W, 91.5 1ks. dist., mkd. ¼ S34 BT.
	Cor. is located 35 lks. S of Forest Service road 851, bears S 80° E and N 80° W.
77.44	Point for the cor. of secs. 26, 27, 34, and 35, determined from an original bearing tree
	A ponderosa pine stump, 13 ins. diam., bears S 20° E, 30 lks. dist., mkd. T7N R31E S35 BT.
	At the cor. point
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 32 ins. in the ground, with cap mkd.
	T7N R31E S27 S26 S34 S35
	1985

CHAINS

from which new bearing trees

- A pine, 7 ins. diam., bears N $49\frac{3}{4}^{\circ}$ E, 25.5 lks. dist., mkd. T7N R31E S26 BT.
- A ponderosa pine, 5 ins. diam., bears S 23½° E, 31 lks. dist., mkd. X BT.
- A pine, 13 ins. diam., bears S $65\frac{1}{4}^{\circ}$ W, 29.5 lks. dist., mkd. T7N R31E S34 BT.
- A pine, 9 ins. diam., bears N $33\frac{1}{4}^{\circ}$ W, 56 lks. dist., mkd. T7N R31E S27 BT.

Raise a mound of stone, 4 ft. base, 3 ft. high, W of cor.

Set a steel fence post near the cor.

N 2°45' W, bet. secs. 26 and 27.

Over rolling land, through medium to dense ponderosa pine and juniper.

39.62 | E

Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27 at proportionate dist.; there is no evidence of the original cor.

Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 18 ins. in the ground, in a mound of stone, 4 ft. base, to top, with cap mkd.

T7N R31E 1/4 S27 | S26 1985

from which

- A ponderosa pine, 10 ins. diam., bears N $22\frac{3}{4}^{\circ}$ E, 85 lks. dist., mkd. $\frac{1}{4}$ S26 BT.
- A ponderosa pine, 7 ins. diam., bears N 50½° W, 13.5 lks. dist., mkd. ½ S27 BT.

Set a steel fence post near the cor.

	1 / N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
59.43	Point for the N 1/16 sec. cor. of secs. 26 and 27.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, with cap mkd.
	T7N R31E N 1/16 S27 S26 1985
	from which
	A ponderosa pine, 13 ins. diam., bears S $75\frac{3}{4}^{\circ}$ E, 30 lks. dist., mkd. N 1/16 S 26 BT.
į	A ponderosa pine, 14 ins. diam., bears N $40\frac{1}{2}^{\circ}$ W, 53.5 lks. dist., mkd. N $1/16$ S27 BT.
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, 1 ft. high, W of cor.
	Set a steel fence post near the cor.
79.24	The cor. of secs. 22, 23, 26, and 27, monumented with a mound of stone, $2\frac{1}{2}$ ft. base, 1 ft. high, from which an original bearing tree
	A fallen pine, 16 ins. diam., bears S 45° W, 38 lks. dist., mkd. T7N R31E S27 BT.
!	At the cor. point
	Set a monument, 30 ins. long, composed of an iron post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 3 ins. in the ground to solid rock, set monument over a cross chiseled in rock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T7N R31E
	S22 S23
	S27 S26 1983
	from which new bearing trees
	A ponderosa pine, 16 ins. diam., bears N 42° E, 39.5 lks. dist., mkd. T7N R31E S23 BT.

	T 7 N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
	A ponderosa pine, 15 ins. diam., bears S 9° E, 34.5 lks. dist., mkd. T7N R31E S26 BT.
	A ponderosa pine, 16 ins. diam., bears S 23° W, 96 lks. dist., mkd. T7N R31E S27 BT.
	A ponderosa pine, 13 ins. diam., bears N 60° W, 34 lks. dist., mkd. T7N R31E S22 BT.
	Set a steel fence post near the cor.
	From this cor., U.S. Coast and Geodetic triangulation station "Loco", bears N 54°09'19" W (forward bearing), 264.208 chs. dist., monumented with a brass tablet, $3\frac{1}{2}$ ins. diam., set in concrete, mkd. LOCO 1936.
	N 0°10' E, bet. secs. 22 and 23.
	Over gently rolling land, through medium ponderosa pine.
20.10	Point for the S 1/16 sec. cor. of secs. 22 and 23.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	T7N R31E S 1/16 S22 S23 1983
	from which
	A ponderosa pine, 10 ins. diam., bears S 47° E, 68.5 lks. dist., mkd. S 1/16 23 BT.
	A ponderosa pine, 10 ins. diam., bears S 59° W, 64 lks. dist., mkd. S 1/16 S22 BT.
	Set a steel fence post near the cor.
40.20	The ½ sec. cor. of secs. 22 and 23, determined from an original bearing tree
	A ponderosa pine, 16 ins. diam., bears S 45° E, 44 lks. dist., healed blaze, opened the blaze to read ½ S BT.
	At the cor. point

CHAINS Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 25 ins. in the ground, with brass cap mkd. T7N R31E s22 | s23 from which A ponderosa pine, 9 ins. diam., bears N 24° E, 84 lks. dist., mkd. ½ S23 BT. A ponderosa pine, 12 ins. diam., bears N 65° W, 44.5 lks. dist., mkd. 4 S22 BT. Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor. Set a steel fence post near the cor. N 0°25' E, beginning new measurement. 20.12 Point for the N 1/16 sec. cor. of secs. 22 and 23. Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 27 ins. in the ground, with brass cap mkd. T7N R31E N 1/16 S22 | S23 1983 from which

A ponderosa pine, 14 ins. diam., bears N 30° E, 29 lks. dist., mkd. N 1/16 S23 BT.

A ponderosa pine, 10 ins. diam., bears N 75° W, 14 lks. dist., mkd. N 1/16 S22 BT.

Set a steel fence post near the cor.

40.24 Point for the cor. of secs. 14, 15, 22, and 23, at proportionate dist.; there is no evidence of the original cor.

CHAINS

Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 25 ins. in the ground, with brass cap mkd.

T7N R31E S15 | S14 S22 | S23 1983

from which

A ponderosa pine, 15 ins. diam., bears N 39° E, 41.5 lks. dist., mkd. T7N R31E S14 BT.

A ponderosa pine, 14 ins. diam., bears S 11° E, 52.5 lks. dist., mkd. T7N R31E S23 BT.

A ponderosa pine, 13 ins. diam., bears S 74° W, 74 lks. dist., mkd. T7N R31E S22 BT.

A ponderosa pine, 12 ins. diam., bears N 44° W, 44.5 lks. dist., mkd. T7N R31E S15 BT.

Set a steel fence post near the cor.

N 88°48' E, bet. secs. 14 and 23.

Over rolling land, through medium ponderosa pine and juniper.

39.60

Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23, at proportionate dist.; there is no evidence of the original cor.

Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam, 32 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.

T7N R311 \frac{1}{4} \frac{\text{S14}}{\text{S23}} 1983

from which

A ponderosa pine, 14 ins. diam., bears N 11½° E, 33 lks. dist., mkd. ¼ S14 BT.

A Douglas fir, 10 ins. diam., bears S 3° W, 42 lks. dist., mkd. $\frac{1}{4}$ S23 BT.

	1 / N, K 31 L, GIId diki bait kivel kel., miladid
CHAINS	
	Set a steel fence post near the cor.
40.34	The closing cor. of secs. 14 and 23, on the Arizona-New Mexico State Line, hereinbefore described.
	From this cor. the 207th mile cor. on the Arizona-New Mexico State Line, bears N 0°06' E, 39.33 chs. dist., hereinbefore described.
	From the cor. of secs. 14, 15, 22, and 23.
	N 0°29' W, bet. secs. 14 and 15.
	Over gently rolling land, through scattered ponderosa pine and juniper.
40.24	The $\frac{1}{4}$ sec. cor. of secs. 14 and 15, monumented with a mound of stone, $2\frac{1}{2}$ ft. base, 1 ft. high.
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
	T7N R31E
	1/4
	S15 S14 1983
	Rebuild mound of stone, 3 ft. base, 1½ ft. high, W of cor.
	Set a steel fence post near the cor.
	From this cor. the cor. of secs. 2, 3, 10, and 11, bears N 0°14' E, 119.96 chs. dist., perpetuated by Charles C. Doak, LS 4476, in 1974, recorded at Book 186, Page 39, Apache County, Arizona, monumented with an iron post, 2½ ins. diam., projecting 16 ins. above the ground, in a mound of stone, 2½ ft. base, 1 ft. high, with brass cap mkd.
	T7N R31E S 3 S 2 S10 S11 LS 4476 1974
	1

	T / N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
	from which an 1883 bearing tree
	A ponderosa pine, 38 ins. diam., bears N 30° W, 68 lks. dist., mkd. T7N R31E S3 BT. (Record 78 lks. dist.)
	and from which bearing trees mkd. by Charles C. Doak in 1974
	A ponderosa pine, 8 ins. diam., bears S $48\frac{1}{2}^{\circ}$ E, 69 lks. dist., mkd. with healed blaze. (Record S $51\frac{1}{2}^{\circ}$ E)
	A ponderosa pine, 20 ins. diam., bears S 10½° W, 95 lks. dist., mkd. BT. (Record S 7° E)
	and from which new bearing trees
	A ponderosa pine, 12 ins. diam., bears N 63° E, 1.15 chs. dist., mkd. T7N R31E S2 BT.
	A juniper, 5 ins. diam., bears N 32½° W, 58 lks. dist., mkd. T7N R31E S3 BT.
	Rebuild the mound of stone, 3 ft. base, to top, around cor.
	Add the marks 1983 to the cap.
	From the cor. of secs. 2, 3, 10, and 11.
: :	N 89°39' E, bet. secs. 2 and 11.
	Over gently rolling land, through medium ponderosa pine, scattered pinyon, juniper and oak, along a fence.
20.27	Point for the W 1/16 sec. cor. of secs. 2 and 11.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 23 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.
	T7N R31E W 1/16 <u>S 2</u> S11 1983
	from which
	A ponderosa pine, ll ins. diam., bears S ½° W, 63 lks. dist., mkd. W 1/16 S11 BT.

	T 7 N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
	A pinyon, 7 ins. diam., bears N 46½° W, 41.5 lks. dist., mkd. W 1/16 S2 BT.
	Set a steel fence post near the cor.
	Cor. is located 10 lks. S of an E and W fence.
40.355	Point for the closing cor. of secs. 2 and 11, T 7 N, R 31 E, Gila and Salt River Meridian, Arizona, on the Arizona-New Mexico State Line.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 23 ins. in the ground, with brass cap mkd.
	CC T7N New S11 Mexico R31E 1983
	from which
	A ponderosa pine, 9 ins. diam., bears S 46° W, 28 lks. dist., mkd. T7N R31E S11 CC BT.
	A ponderosa pine, 13 ins. diam., bears N 20° W, 88 lks. dist., mkd. T7N R31E S2 CC BT.
	Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.
	Cor. is located 1 lk. W of a fence cor., fences extend N and W.
	From this point a local cor. bears N 89°39' E, 1.1 lks. dist., monumented with an iron pin, ½ in. diam., projecting 4 ins. above the ground. This pin is accepted as the best available evidence of the original closing cor. of secs. 2 and 11, T 7 N, R 31 E, Gila and Salt River Meridian, on the Arizona-New Mexico State Line. This iron pin now is an amended monument and was left in place.
	From this same point the 206th mile cor. on the Arizona-New Mexico State Line, bears S 0°03' W, 40.08 chs. dist., hereinbefore described.

	1 , N, R of B, Office and bare rever refer, reflection
CHAINS	
	From the cor. of secs. 2, 3, 10, and 11.
	N 0°45' E, bet. secs. 2 and 3.
	Over rolling land, through scattered pinyon and juniper.
20.10	The S 1/16 sec. cor. of secs. 2 and 3.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 23 ins. in the ground, with brass cap mkd.
	T7N R31E S 1/16 S 3 S 2 1983
	from which
	A pinyon, 13 ins. diam., bears N 17½° E, 1.21 chs. dist., mkd. S 1/16 S2 BT.
	A pinyon, 10 ins. diam., bears N 82° W, 1.05 chs. dist., mkd. S 1/16 S3 BT.
	A fence cor. bears S 83° W, 52 lks. dist., fences extend E and S.
	Set a steel fence post near the cor.
40.20	Point for the ½ sec. cor. of secs. 2 and 3, at proportionate dist.; there is no evidence of the original cor.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 23 ins. in the ground, with brass cap mkd.
	T7N R31E
	s 3 s 2 1983
	from which
	A pinyon, 12 ins. diam., bears S 58° W, 94 lks. dist., mkd. ½ S3 BT.

CHAINS	
CHAINS	A pinyon, 14 ins. diam., bears N 37½° W, 51 lks. dist., mkd. X at breast height and BT at base.
	Raise a mound of stone, $1\frac{1}{2}$ ft. base, 1 ft. high, W of cor.
	Set a steel fence post near the cor.
60.30	The N 1/16 sec. cor. of secs. 2 and 3.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	T7N R31E N 1/16 S 3 S 2 1983
	from which
	A pinyon, 10 ins. diam., bears S $40\frac{1}{2}^{\circ}$ E, 78 lks. dist., mkd. N 1/16 S2 BT.
	An alligator juniper, 12 ins. diam., bears S 76° W, 11 lks. dist., mkd. N 1/16 S3 BT.
	Set a steel fence post near the cor.
80.04	The cor. of secs. 2, 3, 34, and 35, on the N bdy. of the Tp., hereinbefore described.
	The point for the N 1/16 sec. cor. of sec. 2 only, T 7 N, R 31 E, is at proportionate dist., on the E bdy. of sec. 2.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 25 ins. in the ground, with brass cap mkd.
	T7N N 1/16 S 2 NEW MEXICO
	R31E 1983
	Set a steel fence post near the cor.
	Cor. is located in a N and S fence.
1	

CHAINS

From this point the 205th mile cor. on the Arizona-New Mexico State Line, bears S $0^{\circ}04'$ W, 19.555 chs. dist., hereinbefore described.

The point for the $\frac{1}{4}$ sec. cor. of sec. 2 only, T 7 N, R 31 E, is at proportionate dist., on the E bdy. of sec. 2.

Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 25 ins. in the ground, with brass cap mkd.

Set a steel fence post near the cor.

Cor. is located in a N and S fence.

From this point the 205th mile cor. on the Arizona-New Mexico State Line, bears N 0°04' E, 32 lks. dist., hereinbefore described.

The point for the S 1/16 sec. cor. of sec. 2 only, T 7 N, R 31 E, is at proportionate dist. and on the E bdy. of sec. 2.

Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 21 ins. in the ground, with brass cap mkd.

from which

- A pinyon, 6 ins. diam., bears S 85° W, 1.205 chs. dist., mkd. X at breast height and BT at base.
- A ponderosa pine, 8 ins. diam., bears N 35° W, 2.40 chs. dist., mkd. S 1/16 S2 BT.

CHAINS

Raise a mound of stone, $2\frac{1}{2}$ ft. base, 1 ft. high, W of cor.

Cor. is located in a N and S fence.

From this point the 205th mile cor. on the Arizona-New Mexico State Line, bears N 0 $^{\circ}$ 03' E, 20.195 chs. dist., hereinbefore described.

From the cor. of secs. 3, 4, 33, and 34, on the S bdy. of the Tp.

N $0^{\circ}05'$ W, bet. secs. 33 and 34.

Over rolling land, through medium to dense ponderosa pine, juniper and aspen.

40.06

The $\frac{1}{4}$ sec. cor. of secs. 33 and 34, monumented with a sandstone, 20 x 16 x 3 ins., lying loose and mkd. $\frac{1}{4}$; determined cor. point at record bearing and dist. from the remains of an original bearing tree

The remains of a pine stump, bears S 5° E, 28 lks. dist., no marks.

At the cor. point

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock, drill hole in bedrock and cement a magnet in a 1 x 1 x 2 5/8 in. plastic case in bedrock, set monument over magnet in a mound of stone, 4 ft. base, to top with brass cap mkd.

T7N R31E
14
S33 | S34
1985

from which

- A ponderosa pine, 14 ins. diam., bears N 27° E, 30.5 lks. dist., mkd. $\frac{1}{4}$ S34 BT.
- A ponderosa pine, 8 ins. diam., bears N 76° W, 24.5 lks. dist., mkd. ½ S33 BT.

Bury mkd. stone in the mound of stone.

Set a steel fence post near the cor.

	1 / N, R 31 E, Gila and Sait River Mer., Arizona
CHAINS	
	N 0°05' E, beginning new measurement.
39.70	The cor. of secs. 27, 28, 33, and 34, determined from original bearing trees.
	A ponderosa pine, 32 ins. diam., bears N 28¾° E, 40 lks. dist., open healed blaze to read 27 BT. (Record N 30° E)
	A ponderosa pine, 30 ins. diam., bears N 25° W, 61 lks. dist., open blaze to read N R 3 1 E S 28 BT. (Record N 31° W)
	At the cor. point
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T7N R31E <u>\$28 \$27</u> \$33 \$34 1985
	from which
	A ponderosa pine, 10 ins. diam., bears N $62\frac{1}{2}^{\circ}$ E, 2.715 chs. dist., mkd. T7N R31E S27 BT.
	A ponderosa pine, 15 ins. diam., bears S 59¼° E, 60 lks. dist., mkd. T7N R31E S34 BT.
	A ponderosa pine, 12 ins. diam., bears S 48½° W, 46.5 lks. dist., mkd. T7N R31E S33 BT.
	A ponderosa pine, 8 ins. diam., bears N 31½° W, 2.47 chs. dist., mkd. T7N R31E S28 BT.
	Deposit a magnet in a $1 \times 1 \times 2 = 5/8$ in. plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
	From the cor. of secs. 26, 27, 34, and 35.
	N 88°08' W, bet. secs. 27 and 34.
	Over rolling land, through medium ponderosa pine.

	T 7 N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
40.54	Point for the 4 sec. cor. of secs. 27 and 34, at proportionate dist.; there is no evidence of the original cor.
	Set a stainless steel post, 28 ins. long, $\frac{3}{4}$ in. diam., 22 ins. in the ground, with brass cap mkd.
	T7N R31E
	from which
	A ponderosa pine, ll ins. diam., bears N $16\frac{3}{4}^{\circ}$ E, 97 lks. dist., mkd. $\frac{1}{4}$ S27 BT.
	A ponderosa pine, 9 ins. diam., bears S 20½° E, 26.5 lks. dist., mkd. ¼ S34 BT.
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, N of cor.
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
81.08	The cor. of secs. 27, 28, 33, and 34.
	N 1°17' W, bet. secs. 27 and 28.
	Over mountainous land, through dense ponderosa pine, oak and scattered spruce.
37.73	Point for the 4 sec. cor. of secs. 27 and 28 at proportionate dist.; there is no evidence of the original cor.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 8 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.
	T7N R31E
	S28 S27 1985
	from which

	T 7 N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
	A ponderosa pine, 12 ins. diam., bears S $59\frac{1}{2}^{\circ}$ E, 68.5 lks. dist., mkd. ½ S27 BT.
	A ponderosa pine, 12 ins. diam., bears S 34° W, 54 lks. dist., mkd. 4 S28 BT.
	Set a steel fence post near the cor.
75.46	The cor. of secs. 21, 22, 27, and 28, monumented with a mound of stone, 2 ft. base, 1 ft. high, from which original bearing trees
	A dead standing ponderosa pine, 19 ins. diam., bears S 25° E, 33 lks. dist., mkd. S27 BT. (Record S 15° E)
	A ponderosa pine, 18 ins. diam., bears S 40° W, 27 lks. dist., healed blaze. (Record S 20° W)
	A stump hole bears N 30° W, 21 lks. dist., a down ponderosa pine, 12 ins. diam., lying alongside is mkd. T7N R31E S21 BT. (Record N 10° W)
	At the cor. point
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 21 ins. in the ground, with brass cap mkd.
	T7N R31E <u>S21 S22</u> <u>S28 S27</u> 1983
	from which
	A ponderosa pine, 9 ins. diam., bears N 23° E, 1.42 chs. dist., mkd. T7N R31E S22 BT.
	A ponderosa pine, 18 ins. diam., bears S 68° E, 98 lks. dist., mkd. T7N R31E S27 BT.
	A ponderosa pine, 15 ins. diam., bears S 59° W, 91.5 lks. dist., mkd. T7N R31E S28 BT.
	A ponderosa pine, 5 ins. diam., bears N 48° W, 32.5 lks. dist., mkd. X at breast height and BT at base.
	Rebuild mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.

CHAINS	Set a steel fence post near the cor.
	From the cor. of secs. 22, 23, 26, and 27.
İ	S 89°13' W, bet. secs. 22 and 27.
	Over rolling land, through medium ponderosa pine.
9.865	Point for the E-E 1/64 sec. cor. of secs. 22 and 27.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	S22 E-E 1/64 S27 1983
	from which
	A ponderosa pine, 12 ins. diam., bears N 23° E, 52 lks. dist., mkd. E-E 1/64 S22 BT.
	A ponderosa pine, 14 ins. diam., bears S 55° E, 68 lks. dist., mkd. E-E 1/64 S27 BT.
	Set a steel fence post near the cor.
	Cor. is located 60 lks. E of a creek, 15 lks. wide, flows N 20° E.
19.73	Point for the E 1/16 sec. cor. of secs. 22 and 27.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	T7N R31E E 1/16 S22 S27 1983
	from which
	A ponderosa pine, 13 ins. diam., bears N 38° E, 51.5 lks. dist., mkd. E 1/16 S22 BT.

	1 / N, R 31 H, GHd dik bart Rever Per-, 7112010
CHAIN	S
	A ponderosa pine, 12 ins. diam., bears S 61° E, 39 lks. dist., mkd. E 1/16 S27 BT.
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N of cor.
	Set a steel fence post near the cor.
39.46	Point for the ½ sec. cor. of secs. 22 and 27, at proportionate dist.; there is no evidence of the original cor.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T7N R31E ¹ / ₄ S22 S27 1983
	from which
	II OM WITCH
	A ponderosa pine, 9 ins. diam., bears S 42° W, 59.5 lks. dist., mkd. ½ S27 BT.
	A ponderosa pine, 8 ins. diam., bears N 3° W, 21 lks. dist., mkd. ½ S22 BT.
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N of cor.
	Set a steel fence post near the cor.
	Cor. is located 85 lks. W of a track road, bears S 32° E and N 32° W.
59.19	Point for the W 1/16 sec. cor. of secs. 22 and 27.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 22 ins. in the ground, with brass cap mkd.
	T7N R31E W 1/16 S22 S27
	1983
I	

	1 / N, K 51 E, GIIA AIM BATT MVET PET., ALIZOM
CHAINS	
	from which
	A ponderosa pine, 9 ins. diam., bears S 46° W, 39 lks. dist., mkd. W 1/16 S27 BT.
	A ponderosa pine, 7 ins. diam., bears N 6° W, 46 lks. dist., mkd. W 1/16 S22 BT.
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N of cor.
	Set a steel fence post near the cor.
78.92	The cor. of secs. 21, 22, 27, and 28.
	N 0°01' W, bet. secs. 21 and 22.
	Over rolling land, through medium ponderosa pine.
20.05	Point for the S 1/16 sec. cor. of secs. 21 and 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 28 ins. in the ground, in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with cap mkd.
	T7N R31E S 1/16 S21 S22 1983
	from which
	A ponderosa pine, 8 ins. diam., bears N 70° E, 59.5 lks. dist., mkd. S 1/16 S22 BT.
	An alligator juniper, 18 ins. diam., bears N 72° W, 50.5 lks. dist., mkd. S 1/16 S21 BT.
	Set a steel fence post near the cor.
40.10	Point for the ½ sec. cor. of secs. 21 and 22 at proportionate dist.; there is no evidence of the original cor.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS	
	T7N R31E
	S21 S22
	1983
	from which
	A ponderosa pine, 8 ins. diam., bears S 32° E, 8.5 lks. dist., mkd. 4 S22 BT.
	A ponderosa pine, 6 ins. diam., bears N 62° W, 45.5 lks. dist., mkd. ½ S21 BT.
	Set a steel fence post near the cor.
	Cor. is located on a NE slope.
50.125	Point for the S-N 1/64 sec. cor. of secs. 21 and 22.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 27 ins. in the ground, with brass cap mkd.
	S-N 1/64 S21 S22 1983
	from which
	A ponderosa pine, 17 ins. diam., bears S 57° E, 1.00 ch. dist., mkd. S-N 1/64 S22 BT.
	A ponderosa pine, 15 ins. diam., bears N 62° W, 62 lks. dist., mkd. S-N 1/64 S21 BT.
	A fence cor. bears N 70° E, 56.5 lks. dist., fences extend S 45° E and W.
:	Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, W of cor.
	Set a steel fence post near the cor.
	Cor. is located 29 lks. N of a track road, bears S 60° E and N 60° W.
60.15	Point for the N 1/16 sec. cor. of secs. 21 and 22.

Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 23 ins. in the ground, with brass cap mkd.

T7N R31E N 1/16 S21 | S22 1983

from which

A ponderosa pine, 13 ins. diam., bears N $63\frac{1}{2}^{\circ}$ E, 1.00 ch. dist., mkd. N 1/16 S22 BT.

A ponderosa pine, 22 ins. diam., bears S $76\frac{1}{2}^{\circ}$ W, 1.075 chs. dist., mkd. N 1/16 S21 BT.

Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.

Set a steel fence post near the cor.

70.175 Point for the N-N 1/64 sec. cor. of secs. 21 and 22, not monumented.

80.20 The cor. of secs. 15, 16, 21, and 22, monumented with a mound of stone, 2 ft. base, ½ ft. high.

At the cor. point

Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.

T7N R31E S16 | S15 S21 | S22 1983

from which

A ponderosa pine, 10 ins. diam., bears N 39° E, 1.38 chs. dist., mkd. T7N R31E S15 BT.

A ponderosa pine, 16 ins. diam., bears S 30½° E, 19.5 lks. dist., mkd. T7N R31E S22 BT.

A ponderosa pine, 15 ins. diam., bears S 35° W, 98 lks. dist., mkd. T7N R31E S21 BT.

CHAINS

A ponderosa pine, 14 ins. diam., bears N $32\frac{1}{2}^{\circ}$ W, 43 lks. dist., mkd. T7N R31E S16 BT.

Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.

Set a steel fence post near the cor.

From this point the $\frac{1}{4}$ sec. cor. of secs. 15 and 16, bears N 0°01' E, 40.87 chs. dist., monumented with a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high.

At the cor. point

Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 24 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.

T7N R31E 1/4 S16 | S15 1983

from which

A ponderosa pine, 11 ins. diam., bears N 30° E, 45 lks. dist., mkd. ½ S15 BT.

A ponderosa pine, 9 ins. diam., bears N 76° W, 75.5 lks. dist., mkd. ½ S16 BT.

Set a steel fence post near the cor.

From the cor. of secs. 14, 15, 22, and 23.

S 89°03' W, bet. secs. 15 and 22.

Over gently rolling land, through medium ponderosa pine.

19.84

Point for the E 1/16 sec. cor. of secs. 15 and 22.

Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 18 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.

T7N R31E E 1/16 S15 S22 1983

CHAINS	
	from which
	A ponderosa pine, 14 ins. diam., bears S 52° E, 74.5 lks. dist., mkd. E 1/16 S22 BT.
	A ponderosa pine, 14 ins. diam., bears N 7° W, 38.5 lks. dist., mkd. E 1/16 S15 BT.
	Set a steel fence post near the cor.
39.68	Point for the ½ sec. cor. of secs. 15 and 22, at proportionate dist.; there is no evidence of the original cor.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 24 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	T7N R31E 1/4 S15 7 S22 1983
	from which
	A ponderosa pine, 4 ins. diam., bears S 8° W, 2.005 chs. dist., mkd. X at breast height and BT at base.
	An alligator juniper, 5 ins. diam., bears N 72° W, 62 lks. dist., mkd. ½ S15 BT.
	Set a steel fence post near the cor.
59.52	Point for the W 1/16 sec. cor. of secs. 15 and 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 18 ins. in the ground, in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with cap mkd.
	T7N R31E W 1/16 <u>S15</u> S22 1983
	from which
	A ponderosa pine, 8 ins. diam., bears N 42° E, 68 lks. dist., mkd. X at breast height and BT at base.
	A ponderosa pine, 10 ins. diam., bears N 56° W, 27 lks. dist., mkd. W 1/16 S15 BT.

CHAINS	
	Set a steel fence post near the cor.
79.36	The cor. of secs. 15, 16, 21, and 22.
	From the cor. of secs. 21, 22, 27, and 28.
	N 89°28' W, bet. secs. 21 and 28.
	Over mountainous land, through dense ponderosa pine, spruce and Douglas fir.
40.28	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28, at proportionate dist.; there is no evidence of the original cor.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	T7N R31E 1/4 S21 1983
	from which
	A ponderosa pine, 17 ins. diam., bears S 40° W, 98 lks. dist., mkd. ½ S28 BT.
	A ponderosa pine, 7 ins. diam., bears N 47° W, 56 lks. dist., mkd. 4 S21 BT.
	Set a steel fence post near the cor.
80.55	Point for the cor. of secs. 20, 21, 28, and 29 at proportionate dist.; there is no evidence of the original cor.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 27 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	T7N R31E S20 S21 S29 S28 1983
	from which
	An alligator juniper, 28 ins. diam., bears N 77° E, 75 lks. dist., mkd. T7N R31E S21 BT.

CHAINS An alligator juniper, 9 ins. diam., bears S 42° E, 84 lks. dist., mkd. T7N R31E S28 BT.

An alligator juniper, 18 ins. diam., bears S 54° W, 73 lks.

An alligator juniper, 10 ins. diam., bears N 14° W, 52 lks. dist., mkd. T7N R31E S20 BT.

Set a steel fence post near the cor.

dist., mkd. T7N R31E S29 BT.

From this point the cor. of secs. 4, 5, 32, and 33, on the S bdy. of the Tp., bears S 0°21' E, 157.47 chs. dist., hereinbefore described.

The control line was fully retraced, and no evidence of the intervening cors. was found.

From this same point the cor. of secs. 19 and 30 only, on the W bdy. of the Tp., bears S 89°48' W, 160.71 chs. dist., monumented with an iron post, 2 ins. diam., projecting 6 ins. above ground, in a mound of stone, 1 ft. base, to top, with brass cap mkd.

| T7N | R31E | S19 | S30 1925

from which the 1925 bearing trees

- A ponderosa pine, 18 ins. diam., bears N 73½° E, 44 lks. dist., mkd. with a healed blaze.
- A ponderosa pine, 18 ins. diam., bears S 82° E, 74 lks. dist., mkd. with a healed blaze.

The control line was fully retraced and no evidence of the intervening cors. was found.

N 0°13' E, bet. secs. 20 and 21.

Over mountainous land, through medium ponderosa pine and oak brush.

Point for the \(\frac{1}{4} \) sec. cor. of secs. 20 and 21 at proportionate dist.; there is no evidence of the original cor.

CHAINS

Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 34 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.

T7N R31E \$20 | \$21 1983

from which

A ponderosa pine, 7 ins. diam., bears S 81° E, 98 lks. dist., mkd. ½ S21 BT.

A ponderosa pine, 8 ins. diam., bears S 14° W, 33 lks. dist., mkd. ½ S20 BT.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

Set a steel fence post near the cor.

78.74 The cor. of secs. 16, 17, 20 and 21, monumented with a mound of stone, 2 ft. base, embedded in the ground, with an unmarked wooden post 4 ft. long, 4 ins. diam., lying alongside the mound of stone, from which original bearing trees

A stump hole of a burnt out pine, bears N 75° E, 40 lks. dist.

A ponderosa pine, 23 ins. diam., bears S 45° W, 64 lks. dist., healed blaze. (Record N 45° W, 70 lks. dist.)

A fallen ponderosa pine, 16 ins. diam., bears N 28° W, 70 lks. dist., visible marks S17 BT. (Record S 28° W, 66 lks. dist.)

At the cor. point

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T7N R31E S17 | S16 S20 | S21 1983

from which

A ponderosa pine, 9 ins. diam., bears N 45° E, 5.5 lks. dist., mkd. T7N R31E S16 BT.

	T 7 N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
	A ponderosa pine, 12 ins. diam., bears S 38° E, 15 lks. dist., mkd. T7N R31E S21 BT.
	A ponderosa pine, 14 ins. diam., bears N 62° W, 71 lks. dist., mkd. T7N R31E S17 BT.
	Rebuild mound of stone, $2\frac{1}{2}$ ft. base, 1 ft. high, W of cor.
	Set a steel fence post near the cor.
	From the cor. of secs. 15, 16, 21, and 22.
	S 88°47' W, bet. secs. 16 and 21.
	Over rolling land, through moderate to dense ponderosa pine.
9.97	Point for the E-E 1/64 sec. cor. of secs. 16 and 21.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with cap mkd.
	S16
	E-E 1/64
	S21 1983
	from which
	A ponderosa pine, 14 ins. diam., bears S 32° W, 10 lks. dist., mkd. E-E 1/64 S21 BT.
	A ponderosa pine, 6 ins. diam., bears N 13° W, 65 lks. dist., mkd. E-E 1/64 S16 BT.
19.94	Point for the E 1/16 sec. cor. of secs. 16 and 21.
2	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.
	T7N R31E E 1/16 S16 S21
	1983

	1 / N, N 31 E, Gila and Salt River Mer., Arizona
CHAINS	
	from which
	A ponderosa pine, 11 ins. diam., bears S 56½° W, 1.15 chs. dist., mkd. E 1/16 S21 BT.
	A ponderosa pine, 17 ins. diam., bears N 35° W, 72 lks. dist., mkd. E 1/16 S16 BT.
	Set a steel fence post near the cor.
39.88	The $\frac{1}{4}$ sec. cor. of secs. 16 and 21, monumented with a lava stone, 12 x 10 x 4 ins., faintly mkd. $\frac{1}{4}$ and in a mound of stone, 2 ft. base, 6 ins. high, from which bearing trees of unknown origin
	A ponderosa pine, 13 ins. diam., bears N 40° E, 19.5 lks. dist., opened healed blaze, no marks found.
	A ponderosa pine, 13 ins. diam., bears N 65° W, 4 lks. healed blaze.
	At the cor. point
	Set an aluminum post, 36 ins. long, $\frac{3}{2}$ in. diam., 30 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	T7NR31E
	from which new bearing trees
	A ponderosa pine, 12 ins. diam., bears N 53° E, 28 lks. dist., mkd. ¼ S16 BT.
	A ponderosa pine, 13 ins. diam., bears S 4° E, 18.5 lks. dist., mkd. $\frac{1}{4}$ S21 BT.
	Deposit the mkd. stone in the mound of stone, around cor.
	Set a steel fence post near the cor.
	Cor. is located 1.30 chs. S of a track road, bears N 80° E and S 80° W.

	T 7 N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
	N 89°46' W, beginning new measurement.
40.31	The cor. of secs. 16, 17, 20 and 21.
	Subdivision of Section 2 T 7 N, R 31 E, Gila and Salt River Mer., Arizona
	From the 1/4 sec. cor. of sec. 2 only, on the E bdy. of sec. 2, on the Arizona-New Mexico State Line.
	N 89°43' W, on the E and W center line of sec. 2.
	Over gently rolling land, through scattered pinyon and juniper.
19.76	Point for the center W 1/16 sec. cor. of sec. 2.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, 2½ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
	T7N R31E C W 1/16 S 2 1983
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N of cor.
	Set a steel fence post near the cor.
	Cor. is located 70 lks. W of N and S fence.
29.81	Point for the center W-W 1/64 sec. cor. of sec. 2.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 22 ins. in the ground, with brass cap mkd.
	C W-W 1/64 S 2 1983
	from which
	A ponderosa pine, 13 ins. diam., bears N 84° E, 2.83 chs. dist., mkd. C-W-W 1/64 S2 BT.
:	
	L

	T 7 N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
	A ponderosa pine, 6 ins. diam., bears S 26° W, 2.405 chs. dist., mkd. C-W-W 1/64 S2 BT.
	A fence cor. bears S 62° W, 2.735 chs. dist., fences extend N, E and S.
i	Set a steel fence post near the cor.
39.86	The ½ sec. cor. of secs. 2 and 3.
	SW ¹ ₄ of Section 2
	From the W 1/16 sec. cor. of secs. 2 and 11.
	N 0°31' E, on the N and S center line of the SW_4^1 of sec. 2.
	Over gently rolling land, through medium ponderosa pine and juniper.
19.99	Point for the SW $1/16$ sec. cor. of sec. 2, at intersection with the E and W center line of the SW_4 of sec. 2.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	T7N R31E SW 1/16 S2 1983
	from which
	A ponderosa pine, 6 ins. diam., bears N 63° E, 54 lks. dist., mkd. SW 1/16 S2 BT.
	A pinyon, 4 ins. diam., bears S 25° E, 16.5 lks. dist., mkd. SW 1/16 S2 BT.
	Set a steel fence post near the cor.
39.98	The center W 1/16 sec. cor. of sec. 2.
	From the S 1/16 sec. cor. of sec. 2 only, on the E bdy. of sec. 2, on the Arizona-New Mexico State Line.

	T 7 N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
	S 89°58' W, on the E and W center line of the SW_4^1 of sec. 2.
	Over rolling land, through medium to dense ponderosa pine, juniper and oak.
19.92	The SW 1/16 sec. cor. of sec. 2.
30.01	Point for the center W-SW 1/64 sec. cor. of sec. 2.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
	S2 C-W-SW 1/64 1983
	from which
	A ponderosa pine, 10 ins. diam., bears N 6° E, 1.22 chs. dist., mkd. C-W-SW 1/64 S2 BT.
	A pinyon, 9 ins. diam., bears S 52° E, 1.01 chs. dist., mkd. C-W-SW 1/64 S2 BT.
	Set a steel fence post near the cor.
40.10	The S 1/16 sec. cor. of secs. 2 and 3.
	NW ¹ ₄ of Section 2
	From the center W 1/16 sec. cor. of sec. 2.
	N 0°32' E, on the N and S center line of the NW_4^1 of sec. 2.
	Over rolling open land.
19.985	Point for the NW $1/16$ sec. cor. of sec. 2, at intersection with the E and W center line of the NW_4^1 of sec. 2.
	Set an aluminum post, 72 ins. long, $\frac{3}{4}$ in. diam., 68 ins. in the ground, with cap mkd.

	T 7 N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
	T7N R31E NW 1/16 S2 1983
	Set a steel fence post near the cor.
	Cor. is located at the westerly edge of a wash 1 ch. wide, drains northerly.
39.50	The W 1/16 sec. cor. of secs. 2 and 35.
	From the N 1/16 sec. cor. of sec. 2 only, on the E bdy. of sec. 2, on the Arizona-New Mexico State Line.
	N 89°24' W, on the E and W center line of the NW4 of sec. 2.
	Over gently rolling land.
19.60	The NW 1/16 sec. cor. of sec. 2.
29.61	Point for the center W-NW 1/64 sec. cor. of sec. 2.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 25 ins. in the ground, with brass cap mkd.
	S2 C-W-NW 1/64 1983
	Set a steel fence post near the cor.
:	Cor. is located 1.65 chs. E of a N and S fence.
39.62	The N 1/16 sec. cor. of secs. 2 and 3.
	Subdivision of Section 21 T 7 N, R 31 E, Gila and Salt River Mer., Arizona
	From the $\frac{1}{4}$ sec. cor. of secs. 21 and 28.
ļ	N 0°15.5' E, on the N and S center line of sec. 21.

	T 7 N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
	Over mountainous land, through medium to dense ponderosa pine, pinyon, juniper, oak and spruce.
39.73	Point for the center \(\frac{1}{4} \) sec. cor. of sec. 21, at the intersection with the E and W center line of sec. 21.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 28 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	T7N R31E C ¹ 4 S21 1983
	from which
	An alligator juniper, 15 ins. diam., bears N 34° E, 80 lks. dist., mkd. C4 S21 BT.
	A ponderosa pine, 14 ins. diam., bears N 63° W, 35.5 lks. dist., mkd. C4 S21 BT.
i	Set a steel fence post near the cor.
49.54	Point for the center S-N 1/64 sec. cor. of sec. 21, not monumented.
59.35	Point for the center N 1/16 sec. cor. of sec. 21.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 35 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	T7N R31E
	C
	N 1/16 S21 C
	1983
	from which
	A ponderosa pine, 10 ins. diam., bears S 76° E, 22.5 lks. dist., mkd. C-N 1/16 S21 BT.
	A ponderosa pine, 16 ins. diam., bears N 53° W, 41 lks. dist., mkd. C-N 1/16 S21 BT.
	Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, W of cor.
	Set a steel fence post near the cor.

	T / N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
78.97	The ½ sec. cor. of secs. 16 and 21.
	From the $\frac{1}{4}$ sec. cor. of secs. 21 and 22.
	N 89°58' W, on the E and W center line of sec. 21.
	Over mountainous land, through dense timber.
20.03	Point for the center E 1/16 sec. cor. of sec. 21.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 32 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	T7N R31E C E 1/16 S21 1983
	from which
	A ponderosa pine, 15 ins. diam., bears S 73° E, 2.19 chs. dist., mkd. C-E 1/16 S21 BT.
	A ponderosa pine, 16 ins. diam., bears S 8° W, 3.12 chs. dist., mkd. C-E 1/16 S21 BT.
	Set a steel fence post near the cor.
30.045	Point for the center W-E 1/64 sec. cor. of sec. 21, not monumented.
40.06	The center 4 sec. cor. of sec. 21.
80.34	The $\frac{1}{4}$ sec. cor. of secs. 20 and 21.
	NE ¹ ₄ of Section 21
	From the center E 1/16 sec. cor. of sec. 21.
	N 0°06.5' E, on the N and S center line of the NE% of sec. 21.
	Over rolling land, through medium timber.
9.915	Point for the center S-NE 1/64 sec. cor. of sec. 21.

	T / N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	S21
	C-S-NE 1/64
	1983
	from which
	A ponderosa pine, 7 ins. diam., bears N 16° E, 2.04 chs. dist., mkd. C-S-NE 1/64 S21 BT.
	A ponderosa pine, 10 ins. diam., bears N 60° W, 2.33 chs. dist., mkd. C-S-NE 1/64 S21 BT.
	Cor. is located 3 lks. N of a fence, bears S 82° E and N 82° W.
19.83	Point for the NE $1/16$ sec. cor. of sec. 21, at intersection with the E and W center line of the NE $\frac{1}{4}$ of sec. 21.
	Set a monument, 30 ins. long, composed of an iron post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
	T7N R31E NE 1/16 S21 1983
	from which
	A pondersoa pine, 8 ins. diam., bears S 39° E, 1.41 chs. dist., mkd. NE 1/16 S21 BT.
	A ponderosa pine, 10 ins. diam., bears N 68° W, 2.82 chs. dist., mkd. NE 1/16 S21 BT.
	Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W of cor.
	Set a steel fence post near the cor.
29.745	Point for the center N-NE 1/64 sec. cor. of sec. 21.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 31 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.

	T 7 N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
	S21 C-N-NE 1/64 1983
	from which
	A ponderosa pine, 9 ins. diam., bears N 31° E, 96 lks. dist., mkd. C-N-NE 1/64 S21 BT.
	An alligator juniper, 36 ins. diam., bears N 79° W, 69 lks. dist., mkd. C-N-NE 1/64 S21 BT.
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.
	Set a steel fence post near the cor.
39.66	The E 1/16 sec. cor. of secs. 16 and 21.
	From the N 1/16 sec. cor. of secs. 21 and 22.
	S 89°24' W, on the E and W center line of the NE4 of sec. 21.
	Over rolling land, through medium timber.
9.995	Point for the center E-NE 1/64 sec. cor. of sec. 21, not monumented.
19.99	The NE 1/16 sec. cor. of sec. 21.
29.98	Point for the center W-NE 1/64 sec. cor. of sec. 21.
	Set an aluminum post, 72 ins. long, $\frac{3}{4}$ in. diam., 68 ins. in the ground, with cap mkd.
	S21 C-W-NE 1/64 1983
	from which
	A ponderosa pine, 10 ins. diam., bears N 58° W, 79 lks. dist., mkd. C-W-NE 1/64 S21 BT.
	A ponderosa pine, 16 ins. diam., bears N 16° W, 86 lks. dist., mkd. X at breast height and BT at base.

	T / N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
	A fence cor. bears N 57° E, 44.5 lks. dist., fences extend N 59° E and S 5° W.
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
	Set a steel fence post near the cor.
	Cor. is located 46 lks. N of a wash, 45 lks. wide, drains N 75° E.
39.97	The center N 1/16 sec. cor. of sec. 21.
	NE ¹ ₄ of the NE ¹ ₄ of Section 21
	From the point for the center E-NE 1/64 sec. cor. of sec. 21.
	N 0°03' E, on the N and S center line of the NE4 of the NE4 of sec. 21.
9.97	Point for the NE-NE $1/64$ sec. cor. of sec. 21, at intersection with the E and W center line of the NE $\frac{1}{4}$ of the NE $\frac{1}{4}$ of sec. 21.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 32 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	S21
	NE-NE
	1/64 1983
	from which
	A ponderosa pine, 9 ins. diam., bears S 81° E, 78 lks. dist., mkd. NE-NE 1/64 S21 BT.
	A ponderosa pine, 14 ins. diam., bears N ½° W, 1.295 chs. dist., mkd. NE-NE 1/64 S21 BT.
	Set a steel fence post near the cor.
	Cor. is located 4 lks. S of a fence, bears N 50° E and S 50° W.
19.94	The E-E 1/64 sec. cor. of secs. 16 and 21.

	T 7 N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	From the point for the N-N 1/64 sec. cor. of secs. 21 and 22.
	S 89°05.5' W, on the E and W center line of the NE% of the NE% of sec. 21.
9.98	The NE-NE 1/64 sec. cor. of sec. 21.
19.96	The center N-NE 1/64 sec. cor. of sec. 21.
	SW4 of the NE4 of Section 21
	From the point for the center W-E 1/64 sec. cor. of sec. 21.
	N 0°11' E, on the N and S center line of the SW_4^1 of the NE $_4^1$ of sec. 21.
9.86	Point for the SW-NE $1/64$ sec. cor. of sec. 21, at intersection with the E and W center line SW_4^1 of the NE_4^1 of sec. 21.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 34 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	S21 SW-NE 1/64 1983
:	from which
	A ponderosa pine, 23 ins. diam., bears S 3° E, 46 lks. dist., mkd. SW-NE 1/64 S21 BT.
	A ponderosa pine, 18 ins. diam., bears N 59° W, 1.205 chs. dist., mkd. SW-NE 1/64 S21 BT.
	A fence cor. bears N 78° E, 62 lks. dist., fences extend N 5° E, S 82° E and N 82° W.
	Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, N of cor.
	Set a steel fence post near the cor.
	Cor. is located 96 lks. E of a track road, bears S 36° E and N 36° W.
19.72	The center W-NE 1/64 sec. cor. of sec. 21.

	T / N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	From the center S-NE 1/64 sec. cor. of sec. 21.
	S 89°43' W, on the E and W center line of the SW4 of the NE4 of sec. 21.
10.005	The point for the SW-NE 1/64 sec. cor. of sec. 21.
20.01	The point for the center S-N 1/64 sec. cor. of sec. 21.
	Subdivision of Section 22 T 7 N, R 31 E, Gila and Salt River Mer., Arizona
	From the ½ sec. cor. of secs. 22 and 27.
	N 0°08' E, on the N and S center line of sec. 22.
	Over rolling land, through medium timber.
15.06	Point for the center N-S-S 1/256 sec. cor. of sec. 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.
	C N-S-S 1/256 S22 C 1983
	from which
	A ponderosa pine, 4 ins. diam., bears S 65° W, 44.5 lks. dist., mkd. X at breast height and BT at base.
	A ponderosa pine, 12 ins. diam., bears N 10° W, 36.5 lks. dist., mkd. C-N-S-S 1/256 S22 BT.
	Set a steel fence post near the cor.
20.08	Point for the center S 1/16 sec. cor. of sec. 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, 2 ft. base, to top, with cap mkd.
	T7N R31E
	s 1/16 s22
	C 1983

CHAINS	
	from which
	A ponderosa pine, 5 ins. diam., bears N 18° E, 9 1ks. dist., mkd. C-S 1/16 S22 BT.
	A ponderosa pine, 4 ins. diam., bears S 13° E, 30 lks. dist., mkd. X at breast height and BT at base.
	Set a steel fence post near the cor.
25.10	Point for the center S-N-S 1/256 sec. cor. of sec. 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.
	C S-N-S 1/256 S22
	C 1983
	from which
	A ponderosa pine, 14 ins. diam., bears N 64° E, 1.185 chs. dist., mkd. C-S-N-S 1/256 S22 BT.
	A ponderosa pine, 22 ins. diam., bears S 54° E, 1.69 chs. dist., mkd. C-S-N-S 1/256 S22 BT.
	Set a steel fence post near the cor.
40.16	Point for the center ½ sec. cor. of sec. 22, at the intersection with the E and W center line of sec. 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.
	T7N R31E
	C ¹ ₄ S22 1983
	from which
	A ponderosa pine, 8 ins. diam., bears N 5° E, 75.5 lks. dist., mkd. C^1_4 S22 BT.
	A ponderosa pine, 16 ins. diam., bears S 32° W, 1.40 chs. dist., mkd. C^1_4 S22 BT.

	T 7 N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
	Set a steel fence post near the cor.
55.22	Point for the center N-S-N 1/256 sec. cor. of sec. 22.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	C N-S-N 1/256 S22 C 1983
	from which
	A ponderosa pine, 15 ins. diam., bears S 27° E, 1.03 chs. dist., mkd. C-N-S-N 1/256 S22 BT.
	A ponderosa pine, 11 ins. diam., bears S 40° W, 35 lks. dist., mkd. C-N-S-N 1/256 S22 BT.
	A fence cor., bears S 52° E, 35 lks. dist., fences extend N 72° E, S 24° E and N 50° W.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	Set a steel fence post near the cor.
60.24	Point for the center N 1/16 sec. cor. of sec. 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.
	T7N R3lE
	N 1/16 S22
	C 1983
	from which
	A ponderosa pine, 8 ins. diam., bears S 54° E, 38 lks. dist., mkd. C-N 1/16 S22 BT.
	A ponderosa pine, 8 ins. diam., bears N 72° W, 17 lks. dist., mkd. C-N 1/16 S22 BT.
	Set a steel fence post near the cor.

	T 7 N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
	Cor. is located on a SW slope.
65.26	Point for the center S-N-N 1/256 sec. cor. of sec. 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 18 ins. in the ground, in a mound of stone, 4 ft. base, to top, with cap mkd.
	S22 C-S-N-N 1/256 1983
	from which
	A ponderosa pine, 8 ins. diam., bears S $21\frac{1}{2}^{\circ}$ E, 18 lks. dist., mkd. C-S-N-N 1/256 S22 BT.
	A ponderosa pine, 10 ins. diam., bears N 82½° W, 5.5 lks. dist., mkd. C-S-N-N 1/256 S22 BT.
	Set a steel fence post near the cor.
	Cor. is located on a W slope.
80.32	The ½ sec. cor. of secs. 15 and 22.
	From the 4 sec. cor. of secs. 22 and 23.
	S 89°09' W, on the E and W center line of sec. 22.
	Over rolling land, through medium timber.
19.74	Point for the center E 1/16 sec. cor. of sec. 22.
	Set a brass tablet, $3\frac{1}{4}$ ins. diam., $3\frac{1}{2}$ in. stem, in bedrock, 4 ins. below ground, with top mkd.
	T7N R31E C E 1/16 S22 1983
	from which
	A ponderosa pine, 9 ins. diam., bears N 24° E, 43.5 lks. dist., mkd. C-E 1/16 S22 BT.

	T / N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
	A ponderosa pine, 10 ins. diam., bears S 64° E, 45 lks. dist., mkd. C-E 1/16 S22 BT.
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.
	Set a steel fence post near the cor.
39.48	The center \(\frac{1}{4} \) sec. cor. of sec. 22.
59.26	Point for the center W 1/16 sec. cor. of sec. 22.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	T7N R31E C W 1/16 S22 1983
	from which
,	A ponderosa pine, ll ins. diam., bears S 32° W, 61 lks. dist., mkd. C-W 1/16 S22 BT.
	A ponderosa pine, 10 ins. diam., bears N 11° W, 7 lks. dist., mkd. C-W 1/16 S22 BT.
	Set a steel fence post near the cor.
69.15	Point for the center W-W 1/64 sec. cor. of sec. 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 33 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	C W-W 1/64 S22 1983
	from which
	A ponderosa pine, 12 ins. diam., bears N 54° E, 2 lks. dist., mkd. C-W-W 1/64 S22 BT.
	A ponderosa pine, 7 ins. diam., bears S 1° E, 17.5 lks. dist., mkd. C-W-W 1/64 S22 BT.
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N of cor.

	T 7 N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
	Set a steel fence post near the cor.
	Cor. is located 90 lks. S of a track road, bears S 40° E and N 40° W.
79.04	The ½ sec. cor. of secs. 21 and 22.
	NE ¹ ₄ of Section 22
	From the center E 1/16 sec. cor. of sec. 22.
	N 0°16.5' E, on the N and S center line of the NE% of sec. 22.
	Over gently rolling land, through scattered timber.
20.11	Point for the NE 1/16 sec. cor. of sec. 22, at intersection with the E and W center line of the NE of sec. 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with cap mkd.
	T7N R31E NE 1/16 S22 1983
	from which
	A ponderosa pine, 11 ins. diam., bears S 44° E, 13 lks. dist., mkd. NE 1/16 S22 BT.
	A ponderosa pine, 7 ins. diam., bears S 66° W, 56.5 lks. dist., mkd. NE 1/16 S22 BT.
	Set a steel fence post near the cor.
40.21	The E 1/16 sec. cor. of secs. 15 and 22.
	From the N 1/16 sec. cor. of secs. 22 and 23.
	S 89°05' W, on the E and W center line of the NE4 of sec. 22.
	Over gently rolling land, through scattered timber.
19.79	The NE 1/16 sec. cor. of sec. 22.

	T 7 N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
34.64	Point for the center W-W-NE 1/256 sec. cor. of sec. 22.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 6 ins. in the ground, over a cross chiseled in bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	S22
	C-W-W-NE
	1/256
	1983
	from which
	A ponderosa pine, 14 ins. diam., bears N 46° E, 12.5 lks. dist., mkd. C-W-W-NE 1/256 S22 BT.
	A ponderosa pine, 16 ins. diam., bears N 42° W, 21 lks. dist., mkd. C-W-W-NE 1/256 S22 BT.
	Set a steel fence post near the cor.
39.59	The center N 1/16 sec. cor. of sec. 22.
	NW4 of the SW4 of the NE4 of Section 22
	From the center N-S-N 1/256 sec. cor. of sec. 22
	N 89°06.5' E on a portion of the E and W center line of the NW_4^1 of the NE_4^1 of sec. 22.
4.945	Point for the NW-SW-NE 1/256 sec. cor. of sec. 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	S22 NW-SW-NE 1/256 1983
	from which
	A ponderosa pine, 13 ins. diam., bears N 88° W, 20.5 lks. dist., mkd. NW-SW-NE 1/256 S22 BT.

	T 7 N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
	A ponderosa pine, 9 ins. diam., bears N 2° W, 37 lks. dist., mkd. X at breast height and BT at base.
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.
	Set a steel fence post near the cor.
	N 0°09.5' E, on a portion of the N and S center line of the NW $\frac{1}{4}$ of the SW $\frac{1}{4}$ of the NE $\frac{1}{4}$ of sec. 22.
5.023	The center W-W-NE 1/256 sec. cor. of sec. 22.
	SW4 of the NW4 of the NE4 of Section 22
	From the center W-W-NE 1/256 sec. cor. of sec. 22.
	N 0°09.5' E, on a portion of the N and S center line of the SW_4^1 of the NW_4^1 of the NE_4^1 of sec. 22.
5.022	Point for the SW-NW-NE 1/256 sec. cor. of sec. 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 28 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	S22
	SW-NW-NE
	1/256 1983
	1903
	from which
	A ponderosa pine, 12 ins. diam., bears S 12° W, 87.5 lks. dist., mkd. SW-NW-NE 1/256 S22 BT.
	A ponderosa pine, 10 ins. diam., bears N 84° W, 73.5 lks. dist., mkd. SW-NW-NE 1/256 S22 BT.
	S 89°04.5' W, on a portion of the E and W center line of the SW $\frac{1}{4}$ of the NW $\frac{1}{4}$ of the NE $\frac{1}{4}$ of sec. 22.
4.952	The center S-N-N 1/256 sec. cor. of sec. 22.

	1 / N, R 51 E, Gila and Salt River Mer., Arizona
CHAINS	SE ¹ 4 of Section 22
	From the E 1/16 sec. cor. of secs. 22 and 27.
	N 0°08' E, on the N and S center line of the SE_4^1 of sec. 22.
	Over gently rolling land, through medium timber.
5.022	Point for the center S-S-SE 1/256 sec. cor. of sec. 22.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 25 ins. in the ground, with brass cap mkd.
	S22 C-S-S-SE 1/256 1983
	from which
	A ponderosa pine, ll ins. diam., bears S 66° E, 15.5 lks. dist., mkd. C-S-S-SE 1/256 S22 BT.
:	A ponderosa pine, 12 ins. diam., bears S 78° W, 35.5 lks. dist., mkd. C-S-S-SE 1/256 S22 BT.
	Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.
	Set a steel fence post near the cor.
10.045	Point for the center S-SE 1/64 sec. cor. of sec. 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	S22 C-S-SE 1/64 1983
	from which
	A ponderosa pine, 14 ins. diam., bears N 88° W, 1.00 ch. dist., mkd. C-S-SE 1/64 S22 BT.

CHAINS	
	A ponderosa pine, 7 ins. diam., bears S 55° W, 26.5 lks. dist., mkd. C-S-SE 1/64 S22 BT.
	Set a steel fence post near the cor.
16.10	Descend into canyon, edge, bears S 20° E and N 20° W.
20.09	Point for the SE $1/16$ sec. cor. of sec. 22 at intersection with the E and W center line of the SE $_4^1$ of sec. 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 24 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	T7N R31E SE 1/16 S22 1983
	from which
	A ponderosa pine, 10 ins. diam., bears S 10° W, 69.5 lks. dist., mkd. SE 1/16 S22 BT.
	A Douglas fir, 4 ins. diam., bears N 86° W, 16 lks. dist., mkd. X at breast height and BT at base.
	Set a steel fence post near the cor.
	Cor. is located 10 lks. S of a creek, 10 lks. wide, flows N 50° W.
	Ascend from canyon bottom, through dense Douglas fir, aspen, oak, and ponderosa pine.
40.18	The center E 1/16 sec. cor. of sec. 22.
	From the S 1/16 sec. cor. of secs. 22 and 23.
	S 89°10' W, on the E and W center line of the SE14 of sec. 22.
	Over nearly level land, through scattered timber.
14.70	Begin descend into canyon, through dense timber, edge bears S 35° E and N 35° W.
19.73	The SE 1/16 sec. cor. of sec. 22.
	Ascend from canyon.

CILANIC	T / N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
29.50	Top of ascent.
34.528	Point for the center W-W-SE 1/256 sec. cor. of sec. 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	S22 C-W-W-SE 1/256 1983
	from which
	A ponderosa pine, 9 ins. diam., bears N 80° E, 26.5 lks. dist., mkd. C-W-W-SE 1/256 S22 BT.
	A ponderosa pine, 10 ins. diam., bears N 26° W, 22 lks. dist., mkd. C-W-W-SE 1/256 S22 BT.
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N of cor.
	Set a steel fence post near the cor.
39.46	The center S 1/16 sec. cor. of sec. 22.
	SE¼ of the SE¼ of Section 22
	From the E-E 1/64 sec. cor. of secs. 22 and 27.
	N 0°08.5' E on a portion of the N and S center line of the SE $\frac{1}{4}$ of the SE $\frac{1}{4}$ of sec. 22.
5.025	Point for the center S-SE-SE 1/256 sec. cor. of sec. 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 20 ins. in the ground, in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with cap mkd.
	S22 C-S-SE-SE 1/256 1983
	from which

	1 / N, K 31 E, GITA AIR SAIT REVEL PREI , ALIZORA
CHAINS	
	A ponderosa pine, 15 ins. diam., bears S 3° W, 20.5 lks. dist., mkd. C-S-SE-SE 1/256 S22 BT.
	A ponderosa pine, 14 ins. diam., bears N 35° W, 23 lks. dist., mkd. C-S-SE-SE 1/256 S22 BT.
	Set a steel fence post near the cor.
	S 89°12.5' W, on the E and W center line of the SW_4^1 of the SE_4^1 of the SE_4^1 of sec. 22.
9.865	The center S-S-SE 1/256 sec. cor. of sec. 22.
ļ	
	SW4 of the SE4 of Section 22
	From the center S-SE 1/64 sec. cor. of sec. 22.
	S 89°11.5' W, on a portion of the E and W center line of the SW_4^1 of the SE_4^1 of sec. 22.
	Through medium timber.
9.865	Point for the SW-SE 1/64 sec. cor. of sec. 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	S22
	SW-SE
	1/64 1983
	from which
i i	A ponderosa pine, 8 ins. diam., bears S 64° W, 24 lks. dist., mkd. SW-SE 1/64 S22 BT.
	A ponderosa pine, 6 ins. diam., bears N 48° W, 95 lks. dist., mkd. SW-SE 1/64 S22 BT.
	Cor. is located 88 lks. W of a wash, 8 ft. deep, 25 lks. wide, drains NW.
	L

	T' / N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
	Set a steel fence post near the cor.
	N 0°08' E, on a portion of the N and S center line of the SW_4^1 of the SE_4^1 of sec. 22.
5.022	Point for the center N-SW-SE 1/256 sec. cor. of sec. 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	S22 C-N-SW-SE 1/256 1983
	from which
	A ponderosa pine, 8 ins. diam., bears N 54° E, 37 lks. dist., mkd. C-N-SW-SE 1/256 S22 BT.
	A ponderosa pine, 8 ins. diam., bears N 57° W, 36 lks. dist., mkd. C-N-SW-SE 1/256 S22 BT.
	Set a steel fence post near the cor.
	S 89°10.5' W, on a portion of the E and W center line of the NW_4^1 of the SE_4^1 of sec. 22.
4.933	Point for the NW-SW-SE 1/256 sec. cor. of sec. 22.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	S22 NW-SW-SE 1/256 1983
	from which
	A ponderosa pine, 4 ins. diam., bears S 62° W, 50.5 lks. dist., mkd. X at breast height and BT at base.
	A ponderosa pine, 4 ins. diam., bears N 64° W, 1.05 chs. dist., mkd. X at breast height and BT at base.

	T / N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.
	Set a steel fence post near the cor.
	Cor. is located 55 lks. S of a wash, 8 ft. deep, 25 lks. wide, drains N 55° W.
	N 0°08' E, on a portion of the N and S center line of the NW_4^1 of the SW_4^1 of the SE_4^1 of sec. 22.
5.02	The center W-W-SE 1/256 sec. cor. of sec. 22.
	NW ¹ ₄ of the SE ¹ ₄ of Section 22
	From the center W-W-SE 1/256 sec. cor. of sec. 22.
	N 0°08' E, on a portion of the N and S center line of the SW $\frac{1}{4}$ of the NW $\frac{1}{4}$ of the SE $\frac{1}{4}$ of sec. 22.
5.02	Point for the SW-NW-SE 1/256 sec. cor. of sec. 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	S22 SW-NW-SE 1/256 1983
	from which
	A ponderosa pine, 9 ins. diam., bears S 54° W, 1.07 chs. dist., mkd. SW-NW-SE 1/256 S22 BT.
	A ponderosa pine, 7 ins. diam., bears N 43° W, 53.5 lks. dist., mkd. SW-NW-SE 1/256 S22 BT.
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.
	Set a steel fence post near the cor.
	S 89°10' W, on a portion of the E and W center line of the SW_4^1 of the NW_4^1 of the SE_4^1 of sec. 22.

	T / N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
4.932	The center S-N-S 1/256 sec. cor. of sec. 22.
	SW ¹ ₄ of Section 22
	From the W 1/16 sec. cor. of secs. 22 and 27.
	N 0°04' E, on the N and S center line of the SW_4^1 of sec. 22.
	Over rolling land, through medium timber.
20.06	Point for the SW $1/16$ sec. cor. of sec. 22 at intersection with the E and W center line of the SW $\frac{1}{4}$ of sec. 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 20 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	T7N R31E SW 1/16 S22 1983
	from which
	A ponderosa pine, 9 ins. diam., bears N 44° E, 78.5 lks. dist., mkd. SW 1/16 S22 BT.
	A ponderosa pine, 12 ins. diam., bears N 63° W, 54 lks. dist., mkd. SW 1/16 S22 BT.
	Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, W of cor.
	Set a steel fence post near the cor.
25.075	Point for the center S-N-SW 1/256 sec. cor. of sec. 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 36 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	S22 C-S-N-SW 1/256 1983
	from which

	1 / N, K 31 E, GITA and batt Rever Mer., MIZORA
CHAINS	
	A ponderosa pine, 8 ins. diam., bears N 49° E, 62.5 lks. dist., mkd. C-S-N-SW 1/256 S22 BT.
	A ponderosa pine, 10 ins. diam., bears S 14° W, 91 lks. dist., mkd. C-S-N-SW 1/256 S22 BT.
	Raise a mound of stone, $1\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, S of cor.
	Set a steel fence post near the cor.
	Cor. is located on the southerly edge of a track road, bears S 40° E and N 70° W.
	From this point a U.S.G.S. B.M., bears N 22°33' W, 97.2 lks. dist., monumented with a brass tablet, $3\frac{1}{2}$ ins. diam., set in a granite boulder, 3 x $2\frac{1}{2}$ x 1 ft., marks on tablet have been removed.
40.12	The center W 1/16 sec. cor. of sec. 22.
	From the center S 1/16 sec. cor. of sec. 22.
	S 89°12' W, on the E and W center line of the SW4 of sec. 22.
	Over gently rolling land, through medium timber.
9.88	Point for the center E-SW 1/64 sec. cor. of sec. 22 not monumented.
14.82	Point for the center W-E-SW 1/256 sec. cor. of sec. 22.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 21 ins. in the ground, with brass cap mkd.
	S22
	C-W-E-SW
	1/256 1983
	from which
	A ponderosa pine, 9 ins. diam., bears S 80° E, 47 lks. dist., mkd. C-W-E-SW 1/256 S22 BT.
	A ponderosa pine, 9 ins. diam., bears N 73° W, 42.5 lks. dist., mkd. C-W-E-SW 1/256 S22 BT.

	•
CHAINS	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
	Set a steel fence post near the cor.
	Cor. is located 36 lks. E of a fence, bears S 18° E and N 18° W and 60 lks. E of a track road, bears S 18° E and N 18° W.
19.76	The SW 1/16 sec. cor. of sec. 22.
39.52	The S 1/16 sec. cor. of secs. 21 and 22.
	NE¼ of the SW¼ of Section 22
	From the center W-E-SW 1/256 sec. cor. of sec. 22.
	N 0°05' E, on a portion of the N and S center line of the SW $\frac{1}{4}$ of the NE $\frac{1}{4}$ of the SW $\frac{1}{4}$ of sec. 22.
5.015	Point for the SW-NE-SW 1/256 sec. cor. of sec. 22.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 20 ins. in the ground, with brass cap mkd.
	S22 SW-NE-SW 1/256 1983
	from which
	A ponderosa pine, 9 ins. diam., bears S 42½° E, 27.5 lks. dist., mkd. SW-NE-SW 1/256 S22 BT.
	A ponderosa pine, 13 ins. diam., bears S 24° W, 14 lks. dist., mkd. SW-NE-SW 1/256 S22 BT.
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.
: :	Set a steel fence post near the cor.
	S 89°11.5' W, on a portion of the E and W center line of the SW_4^1 of the NE_4^1 of the SW_4^1 of sec. 22.
4.942	The center S-N-SW 1/256 sec. cor. of sec. 22.

CHAINS	I , II, II SI E, SIIG GIN BATE IGVEL INTO, INCLUMENT
	SE ¹ ₄ of the SW ¹ ₄ of Section 22
	From the center N-S-S 1/256 sec. cor. of sec. 22.
	S 89°12' W, on the E and W center line of the N_2^1 of the SE_4^1 of the SW_4^1 of sec. 22.
9.875	Point for the center N-SE-SW 1/256 sec. cor. of sec. 22.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 20 ins. in the ground, with brass cap mkd.
	S22 C-N-SE-SW 1/256 1983
	from which
	A ponderosa pine, 9 ins. diam., bears S 24° E, 46.5 lks. dist., mkd. C-N-SE-SW 1/256 S22 BT.
	A ponderosa pine, 8 ins. diam., bears S 18° W, 60 lks. dist., mkd. C-N-SE-SW 1/256 S22 BT.
	Set a steel fence post near the cor.
14.812	Point for the NW-SE-SW 1/256 sec. cor. of sec. 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 32 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	S22 NW-SE-SW 1/256 1983
	from which
	A ponderosa pine, 11 ins. diam., bears N 72° E, 23.5 lks. dist., mkd. NW-SE-SW 1/256 S22 BT.
	A ponderosa pine, 8 ins. diam., bears S 13° E, 24.5 lks. dist., mkd. NW-SE-SW 1/256 S22 BT.

T 7 N, R 31 E, Gila and Salt River Mer., Arizona
Set a steel fence post near the cor.
N 0°05' E, on a portion of the N and S center line of the NW $\frac{1}{4}$ of the SE $\frac{1}{4}$ of the SW $\frac{1}{4}$ of sec. 22.
The center W-E-SW 1/256 sec. cor. of sec. 22.
NW4 of the SW4 of Section 22
From the center S-N-SW 1/256 sec. cor. of sec. 22.
S 89°11.5' W, on a portion of the E and W center line of the SE_4^1 of the SW_4^1 of sec. 22.
Point for the SE-NW-SW 1/256 sec. cor. of sec. 22.
Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 32 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.
S22 SE-NW-SW 1/256 1983
from which
A ponderosa pine, 12 ins. diam., bears N 54° E, 38.5 lks. dist., mkd. SE-NW-SW 1/256 S22 BT.
A ponderosa pine, 8 ins. diam., bears S 76° W, 34.5 lks. dist., mkd. SE-NW-SW 1/256 S22 BT.
Set a steel fence post near the cor.
N 0°02' E, on a portion of the N and S center line of the SE^{1}_{4} of the SW^{1}_{4} of the SW^{1}_{4} of sec. 22.
Point for the center E-NW-SW 1/256 sec. cor. of sec. 22.
Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 20 ins. in the ground, with brass cap mkd.

CHAINS	
	S22
ĺ	C-E-NW-SW
	1/256 1983
	1303
	from which
	A ponderosa pine, 21 ins. diam., bears N 86° E, 34.5 lks. dist., mkd. C-E-NW-SW 1/256 S22 BT.
	A ponderosa pine, 12 ins. diam., bears S 58° W, 36 lks. dist., mkd. C-E-NW-SW 1/256 S22 BT.
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.
	Set a steel fence post near the cor.
	Cor. is located 71 lks. N of a creek, drains northeasterly.
	S 89°10.5' W, on a portion of the E and W center line of the NW_4 of the SW_4 of sec. 22.
4.943	Point for the NW-SW 1/64 sec. cor. of sec. 22.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 22 ins. in the ground, with brass cap mkd.
	S22
	NW-SW
	1/64
	1983
	from which
	A ponderosa pine, 15 ins. diam., bears N 81° E, 37.5 lks. dist., mkd. NW-SW 1/64 S22 BT.
	A ponderosa pine, 10 ins. diam., bears N 54° W, 58 lks. dist., mkd. NW-SW 1/64 S22 BT.
	Set a steel fence post near the cor.
	N 0°01.5' E, on a portion of the N and S center line of the NW $\frac{1}{4}$ of the SW $\frac{1}{4}$ of sec. 22.

	T / N, R 31 E, Gila and Sait River Mer., Arizona
CHAINS	
10.03	The center W-W 1/64 sec. cor. of sec. 22.
	NW ¹ ₄ of Section 22
	From the center W 1/16 sec. cor. of sec. 22.
	N 0°04' E, on the N and S center line of the NW4 of sec. 22.
	Over gently rolling land, through medium timber.
10.035	Point for the center S-NW 1/64 sec. cor. of sec. 22.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
	S22 C-S-NW 1/64 1983
	from which
	A ponderosa pine, 16 ins. diam., bears N 88° E, 83 lks. dist., mkd. C-S-NW 1/64 S22 BT.
	A ponderosa pine, 12 ins. diam., bears N 2° W, 56 lks. dist., mkd. C-S-NW 1/64 S22 BT.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	Set a steel fence post near the cor.
20.07	Point for the NW $1/16$ sec. cor. of sec. 22, at intersection with the E and W center line of the NW_4^1 of sec. 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 28 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	T7N R31E NW 1/16 S22 1983

	T / N, R 31 E, Gila and Sait River Mer., Arizona
CHAINS	
	from which
	A ponderosa pine, 6 ins. diam., bears N 9° E, 10 lks. dist., mkd. NW 1/16 S22 BT.
	A ponderosa pine, 8 ins. diam., bears S 57° E, 31.5 lks. dist., mkd. NW 1/16 S22 BT.
	Set a steel fence post near the cor.
40.14	The W 1/16 sec. cor. of secs. 15 and 22.
	From the center N 1/16 sec. cor. of sec. 22.
	S 89°07.5' W, on the E and W center line of the NW of sec. 22.
	Over gently rolling land, through medium timber.
4.953	Point for the center E-E-NW 1/256 sec. cor. of sec. 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 32 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	S22 C-E-E-NW 1/256 1983
	from which
	A ponderosa pine, 15 ins. diam., bears S 27° W, 1.10 chs. dist., mkd. C-E-E-NW 1/256 S22 BT.
	A ponderosa pine, 16 ins. diam., bears N 27° W, 1.065 chs. dist., mkd. C-E-E-NW 1/256 S22 BT.
ļ.	Set a steel fence post near the cor.
	Cor. is located at the W side of a boulder 5 x 4 x 3 ft. above ground; and 93 lks. W of a fence, bears S 35° E and N 35° W.
9.905	Point for the center E-NW 1/64 sec. cor. of sec. 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.

	T 7 N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	
	S22 C-E-NW 1/64 1983
	Set a steel fence post near the cor.
19.81	The NW 1/16 sec. cor. of sec. 22.
39.62	The N 1/16 sec. cor. of secs. 21 and 22.
	SE½ of the NE¼ of the NW¾ of Section 22
	From the center E-E-NW 1/256 sec. cor. of sec. 22.
	N 0°07' E, on a portion of the N and S center line of the SE_4^1 of the NE_4^1 of the NW_4^1 of sec. 22.
5.02	Point for the SE-NE-NW 1/256 sec. cor. of sec. 22.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 28 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	S22 SE-NE-NW 1/256 1983
	from which
	A ponderosa pine, 10 ins. diam., bears S 36° W, 39 lks. dist., mkd. SE-NE-NW 1/256 S22 BT.
	Set a steel fence post near the cor.
į	Cor. is located in creek bottom, course northerly.
	N 89°06.5' E, on a portion of the E and W center line of the SE_4^1 of the NE_4^1 of the NW_4^1 of sec. 22.
4.955	The center S-N-N 1/256 sec. cor. of sec. 22.
ļ	

	T 7 N, R 31 E, Gila and Salt River Mer., Arizona
CHAINS	SE ¹ ₄ of the NW ¹ ₄ of Section 22
	From the center S-NW 1/64 sec. cor. of sec. 22.
	N 89°08.5' E, on a portion of the E and W center line of the SE4
	of the NW4 of sec. 22.
9.90	Point for the SE-NW 1/64 sec. cor. of sec. 22.
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 26 ins. in the ground, with brass cap mkd.
	S22
	SE-NW
	1/64 1983
	from which
	A ponderosa pine, 20 ins. diam., bears N 22° E, 1.24 chs. dist., mkd. SE-NW 1/64 S22 BT.
	A ponderosa pine, 6 ins. diam., bears S 63° W, 53 lks. dist., mkd. SE-NW 1/64 S22 BT.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	Set a steel fence post near the cor.
	N 0°06' E, on a portion of the N and S center line of the SE_4 of the NW_4 of sec. 22.
10.038	The center E-NW 1/64 sec. cor. of sec. 22.
	SW4 of the NW4 of Section 22
	From the center W-W 1/64 sec. cor. of sec. 22.
	N 0°01.5' E, on a portion of the N and S center line of the $SW^{\frac{1}{4}}$ of the $NW^{\frac{1}{4}}$ of sec. 22.
10.03	Point for the SW-NW 1/64 sec. cor. of sec. 22.

CHAINS	
	Set a monument, 30 ins. long, composed of a stainless steel post, 25 ins. long, $2\frac{1}{2}$ ins. diam., bonded to a magnetic poly breakaway base, 24 ins. in the ground, with brass cap mkd.
	S22 SW-NW 1/64 1983
	from which
	A ponderosa pine, 12 ins. diam., bears S 76° E, 1.255 chs. dist., mkd. SW-NW 1/64 S22 BT.
	A ponderosa pine, 10 ins. diam., bears S 27° W, 99 lks. dist., mkd. SW-NW 1/64 S22 BT.
	Set a steel fence post near the cor.
	S 89°08.5' W, on a portion of the E and W center line of the SW4 of the NW4 of sec. 22.
9.90	The S-N 1/64 sec. cor. of secs. 21 and 22.
	Subdivision of Section 27 T 7 N, R 31 E, Gila and Salt River, Mer., Arizona
	From the $\frac{1}{4}$ sec. cor. of secs. 27 and 34.
	N 2°02' W, on the N and S center line of sec. 27.
	Over rolling land, through medium to dense pine, oak and aspen.
38.67	Point for the center \(\frac{1}{4} \) sec. cor. of sec. 27, at the intersection with the E and W center line of sec. 27.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 20 ins. in the ground, in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with cap mkd.
	T7N R31E C ¹ 4 S27 1985
	from which

	1 / N, R SI E, GIIA and Sait River Per., Arrzona
CHAINS	
	A ponderosa pine, 7 ins. diam., bears N 22° E, 1.06 chs. dist., mkd. C ¹ ₄ S27 BT.
	A ponderosa pine, 8 ins. diam., bears N 62½° W, 77.5 lks. dist., mkd. C½ S27 BT.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	Set a steel fence post near the cor.
58.005	Point for the center N 1/16 sec. cor. of sec. 27.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	T7N R31E
	C
	N 1/16 S27 C
	1985
	from which
	A ponderosa pine, 6 ins. diam., bears N $54\frac{3}{4}^{\circ}$ E, 50 lks. dist., mkd. C-N $1/16$ S27 BT.
	A Douglas fir, 14 ins. diam., bears N 48° W, 70 lks. dist., mkd. C-N 1/16 S27 BT.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	Set a steel fence post near the cor.
77.34	The $\frac{1}{4}$ sec. cor. of secs. 22 and 27.
	From the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.
	N 89°26' W, on the E and W center line of sec. 27.
	Over rolling land, through medium to dense pine, oak and aspen.
19.995	Point for the center E 1/16 sec. cor. of sec. 27.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 15 ins. in the ground, in a mound of stone, 3 ft. base, to top, with cap mkd.

	1 / N, R 31 E, Gila and Sait River Mer., Arizona
CHAINS	
	T7N R31E C E 1/16 C S27 1985
	from which
	A ponderosa pine, 14 ins. diam., bears N 38% E, 1.16 chs. dist., mkd. C-E 1/16 S27 BT.
	A Douglas fir, 9 ins. diam., bears N 20° W, 47.5 lks. dist., mkd. C-E 1/16 S27 BT.
	Set a steel fence post near the cor.
39.99	The center ½ sec. cor. of sec. 27.
79.99	The $\frac{1}{4}$ sec. cor. of secs. 27 and 28.
	NE ¹ ₄ of Section 27
	From the center E 1/16 sec. cor. of sec. 27.
	N 2°23' W,, on the N and S center line of the NE4 of sec. 27.
	Over rolling land, through medium pine, oak and aspen.
19.575	Point for the NE $1/16$ sec. cor. of sec. 27, at intersection with the E and W center line of the NE $\frac{1}{4}$ of sec. 27.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with cap mkd.
	T7N R31E NE 1/16 S27 1983
	from which
	A ponderosa pine, 12 ins. diam., bears S 81¾° E, 54 lks. dist., mkd. NE 1/16 S27 BT.
	A ponderosa pine, 6 ins. diam., bears N 8° W, 57 lks. dist., mkd. NE 1/16 S27 BT.
	Raise a mound of stone, 3 ft. base, 4 ft. high, W of cor.

	T / N, R 31 E, G11a and Salt River Mer., Arizona
CHAINS	
	Set a steel fence post near the cor.
34.255	Point for the center N-N-NE 1/256 sec. cor. of sec. 27.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, $1\frac{1}{2}$ ft. base, to top, with cap mkd.
	S27 C-N-N-NE 1/256 1985
	from which
	A ponderosa pine, 8 ins. diam., bears S 58¾° E, 24.5 lks. dist., mkd. C-N-N-NE 1/256 S27 BT.
	A ponderosa pine, 6 ins. diam., bears S 79° W, 3.5 lks. dist., mkd. C-N-N-NE 1/256 S27 BT.
	Set a steel fence post near the cor.
39.145	The E 1/16 sec. cor. of secs. 22 and 27.
	From the N 1/16 sec. cor. of secs. 26 and 27.
	S 89°55' W, on the E and W center line of the NE% of sec. 27.
	Over rolling land, through medium pine, oak and aspen.
19.86	The NE 1/16 sec. cor. of sec. 27.
39.72	The center N 1/16 sec. cor. of sec. 27.
	NE¼ of the NE¼ of Section 27
	From the center N-N-NE 1/256 sec. cor. of sec. 27.
	N 89°25' E, on the E and W center line of the NW $\frac{1}{4}$ of the NE $\frac{1}{4}$ of the NE $\frac{1}{4}$ of sec. 27.
9.88	Point for the center N-NE-NE 1/256 sec. cor. of sec. 27.
	Set an aluminum post, 36 ins. long, $\frac{3}{4}$ in. diam., 30 ins. in the ground, in a mound of stone, $1\frac{1}{2}$ ft. base, to top, with cap mkd.

CHAINS			
	S27 C-N-NE-NE		
	1/256		
	1985		
	from which		
	A ponderosa pine, 10 ins. diam., bears S 38½° E, 55 lks. dist., mkd. C-N-NE-NE 1/256 S27 BT.		
	A ponderosa pine, 10 ins. diam., bears S 54½° W, 24 lks. dist., mkd. C-N-NE-NE 1/256 S27 BT.		
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.		
	Set a steel fence post near the cor.		
	N 2°34' W, on a portion of the N and S center line of the NE $\frac{1}{4}$ of the NE $\frac{1}{4}$ of sec. 27.		
4.92	The E-E 1/64 sec. cor. of secs. 22 and 27.		
	General Description		
	The land encompassed in this survey is located about 20 miles SE of Springerville, Arizona. The elevation ranges from about 7,600 ft. to 9,100 ft. above sea level.		
	The land varies from gently rolling to mountainous, covered with scattered to dense ponderosa pine, spruce, white pine, Douglas fir, oak, and aspen, with some open areas.		
	Access is by way of numerous forest service and track roads.		

UNITES STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Alferd L. Pons	Cadastral Surveyor
Kevin L. Miller	Surveying Technician
Robert Mokwa	Surveying Technician
Robert J. Lyle	Surveying Technician
Don L. Brewer	Surveying Technician
Rebecca Ramirez	Surveying Aid
Tim Duck	Surveying Aid
Daryl Moistner	Surveying Aid
Tim Tietjen	Surveying Aid

CERTIFICATE OF SURVEY

I, Paul L. Reeves, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 5th day of August 1983, I have dependently resurveyed a portion of the Arizona-New Mexico State Line, dependently resurveyed a portion of the north and south boundaries and subdivisional lines and surveyed subdivisions in sections 2, 21, 22, and 27, Township 7 North, Range 31 East, of the Gila and Salt River Meridian, in the State of Arizona which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

2/10/88	Vauf L. Reeves
/ (Date)	(Cadastral Surveyor)
(Date)	(Cadastral Surveyor)
CERTIF	ICATE OF APPROVAL
	Arizona State Office
	Bureau of Land Management Phoenix, Arizona
Arizona-New Mexico State Line, the north and south boundaries and sub subdivisions in sections 2, 21, 22 Gila and Salt River Meridian, Ariz	ependent resurvey of a portion of the dependent resurvey of a portion of the divisional lines and the survey of , and 27, Township 7 North, Range 31 East, ona, executed by Paul L. Reeves, Cadastral xamined and found correct, are hereby
JUN	(Chief Cadastral Surveyor of Arizona)
(Date)	(Chief Cadastral Surveyor of Arizona)
CERTIFIC	CATE OF TRANSCRIPT
I Certify That the foregoing trans above-described surveys in T 7 N, Arizona, is a true copy of the original	R 31 E, Gila and Salt River Meridian,
(Date)	(Chief Cadastral Surveyor of Arizona)