UKIGINAL

BOOK 5360

1

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

R-5360

FIELD NOTES

OF THE
DEPENDENT RESURVEY OF A PORTION OF THE
FIFTH STANDARD PARALLEL NORTH (SOUTH BOUNDARY)
AND
THE EXTERIOR BOUNDARIES
OF
TOWNSHIP 21 NORTH, RANGE 26 EAST
Of theGila and Salt River Meridian,
In the State of Arizona
EXECUTED BY
Stephen J. Malloy, Gary D. Johnson and Darren R. Breckenridge, Cadastral Surveyors
Under Special Instructions dated <u>January 12, 1987</u> , approved <u>February 23, 1987</u> ,
Supplemental Special Instructions dated October 13, 1987, approved October 13, 1987,
Supplemental Special Instructions dated <u>February 29, 1988</u> , approved <u>February 29</u> ,
1988, and Amended Supplemental Special Instructions dated <u>January 11, 1989</u> , approved
January 11, 1989, provided for the surveys included under Group No. 685, and
Assignment Instructions dated April 21, 1987, April 27, 1988 and November 14, 1988
and Corrected Assignment Instructions dated <u>July 27. 1990</u> .

Survey compensed November 15, 1988
Survey completed March 31, 1992

2

INDEX DIAGRAM

TOWNSHIP 21 NORTH , RANGE 26 EAST ,

			r	T			
	36	35	33	33	32	30	
29	6	5	4	3	2	1	22
28	7	8	9	10	11	12	21
26	18	17	16	15	14	13	20
25	19	20	21	22	23	24	18
24	30	29	28	27	26	25	17
23	31	32	33	34	35	36	16
	4	5	7	9	11	13	

T. 21 N., R. 26 E., Gila and Salt River Mer., Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the Fifth Standard Parallel North (south boundary) and Exterior boundaries of Township 21 North, Range 26 East, Gila and Salt Rivers Meridian, Arizona.

The Fifth Standard Parallel North (south boundary), North, East, and West boundaries were surveyed by Frank Follman in 1882. Ty White dependently resurveyed a portion of the Fifth Standard Parallel North (south boundary), the North boundary, and West boundary in 1947.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated January 12, 1987, the Supplemental Instructions dated October 13, 1987 and February 29, 1988, and Amended Supplemental Special Instructions dated January 11, 1989 for Group No. 685, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of all lines were determined by observations on a U.S. Coast and Geodetic Survey triangulation network, confirmed by hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with a Zeiss Elta 46, Hewlett-Packard 3820 and Geodimeter 140 total stations.

The geographic position of the township corner of Tps. 21 N., Rs. 26 and 27 E., sections 31 and 36, as determined from a tie made to U.S. Coast and Geodetic Survey triangulation station "DEAD", located in T. 20 N., R. 25 E., is as follows:

NAD 27 Latitude 35°10'12.03" N. Longitude 109°31'37.64" W.

The mean magnetic declination as taken from quadrangle map NORTH MILL WELL, ARIZ., published in 1972 by U.S. Geological Survey, is 13 1/2° E.

	T
CHAINS	Restoring the survey executed by Frank Follman in 1882
	Beginning at the stan. cor. of Tp. 21 N., Rs. 25 and 26 E., monumented by Ty White in 1947, with an iron post, 3 ins. diam., firmly set, projecting 7 ins. from the ground, with brass cap mkd. SC T21N R25E R26E S31 S36 1947, from which the remains of the 1947 bearing trees
	A juniper, 10 ins. diam., bears N. 29° E., 118 lks. dist., with scribe marks T21N R26E S31 SC BT visible on a partially healed blaze. (Record: N. 29 1/4° E., 119 lks. dist.)
	A juniper, 13 ins. diam., bears N. 13° W., 56 lks. dist., with scribe marks T21N R25E S36 on a partially healed blaze. (Record: N. 13 3/4° W., 54 lks. dist.)
i	Add the marks 1988 to the brass cap.
	From this cor. point, a rebar, set by person(s) unknown, 1/2 ins. diam., firmly set, projecting 5 ins. from the ground, bears S. 45° E., 38.1 lks. dist.
	N. 89°47' E., on the S. bdy. of sec. 31.
	Over gently rolling land, with moderate juniper.
20.44	An iron pipe, set by person(s) unknown, 2 ins. diam., firmly set, projecting 6 ins. from the ground bears South, 78 lks. dist.
20.56	Cor. of fences bears South, 7 lks. dist., fences extending E., S., and W.,
39.84	Point for the stan. 1/4 sec. cor. of sec. 31, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	S C T21N R26E 1/4 S31
	1988

CHAINS	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
	Cor. is located 7 lks. N. of a barbed wire fence, bears E. and W.
61.60	Point for a witness point on the S. bdy. of sec. 31.
	Set an aluminum post, 36 ins. long, 3/4 in. diam., 29 ins. in the ground, with aluminum cap mkd.
	WP T21N R26E <u>S 31</u> 1988
79.68	Point for the stan. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	S C T21N R26E
	S31 S32 ————————————————————————————————————
	from which
	A juniper, 8 ins. diam., bears N. 4 3/4° E., 159 lks. dist., mkd. T21N R26E S32 SC BT.
	Deposit a magnet in a $1 \times 1 \times 2$ 5/8 in. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
	N. 89°47' E., on the S. bdy. of sec. 32.
17.52	A local cor. established by Lacy Greer, LS 5704, bears South, 3 lks. dist., monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 9 ins. from the ground, with brass cap mkd., LS 704 T20N R26 E S6 S5 1971.

CHAINS	Cor. is located in a barbed wire fence, bears E. and W.
39.84	Point for the stan. 1/4 sec. cor. of sec. 32, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	S C T21N R26E 1/4 S32
	1988
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
	From this cor. point, a rebar, set by person(s) unknown, 1/2 ins. diam., firmly set, projecting 6 ins. from the ground, bears S. 89 3/4° W., 210 lks. dist.
	Cor. is located in a barbed wire fence, bears E. and W.
57.92	A local cor. establish by Lacy Greer, LS 5704, bears North, 4 lks. dist., monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 16 ins. from the ground, with brass cap mkd., LS 5704 T20N R26E S5 1/4 1971.

CHAINS	Cor. is located in a barbed wire fence, bears E. and W.
79.68	Point for the stan. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	S C T21N R26E S32 S33
	1988
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
	N. 89°47' E., on the S. bdy. of sec. 33.
	Begin ascent.
7.05	Top of spur, bears NE and SW.
12.70	Top of ridge, bears NE and SW., begin steep descent.
15.25	Bottom of ridge, enter range land.
19.18	A local cor. established by Lacy Greer, LS 5704, bears North, 29 lks. dist., monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 9 ins. from the ground, with brass cap mkd., LS 5704 T20N R26E WC S5 S4 1971. A mound of stone 2 ft. base, 1 ft. high is alongside.
	Cor. is located 16 lks. N. of a barbed wire fence, bears E. and W.
39.25	Gulch, 30 lks. wide, 10 ft. deep, drains SW.
	I.

	1. 21 N., R. 20 E., Gila and Salt River Meridian, Arizona	
CHAINS		
39.84	Point for the stan. 1/4 sec. cor. of sec. 33, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	
Ī	S C T21N R26E 1/4 S33	
	1988	
	from which	
	A juniper, 8 ins. diam., bears N. 29 1/2° W., 208 1/2 lks. dist. mkd. 1/4 S33 SC BT.	
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white plastic case beneath the stainless steel post.	
	Set a steel fence post near the cor.	
	Cor. is located 9 lks. S. of a barbed wire fence, bears E. and W.	
40.80	Gulch, 29 lks. wide, 10 ft. deep, drains SW.	
44.55	Wash, 50 lks. wide, 1 ft. deep, drains SW.	
79.40	Wash, 4 lks. wide, 1 ft. deep, drains SW.	
79.68	Point for the stan. cor. of secs. 33 and 34, at proportionate dist., there is no remaining evidence of the original cor.	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.	
	S C T21N R26E S33 S34 1988	
	from which	
	LION WILCII	
	A juniper, 10 ins. diam., bears N. 16 3/4° E., 60 lks. dist. mkd. T21N R26E S34 SC BT.	

611.1116	
CHAINS	A juniper, 9 ins. diam., bears N. 76 3/4° W., 234 lks. dist. mkd. T21N R26E S33 SC BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
	Cor is located 1 lk. S. of a barbed wire fence, bears E. and W.
	N. 89°47' E., on the S. bdy. of sec. 34.
0.25	Top of ridge, bears NE and SW, begin descend.
2.75	Enter nearly level land.
14.80	Wash, 87 lks. wide, 2 ft. deep, drains SSW.
19.87	A local cor. established by Lacy Greer, LS 5704, bears North, 4 lks. dist., monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 17 ins. from the ground, with brass cap mkd., LS 5704 T20N R26E S4 S3 CC 1971.
33.30	Top of spur, bears S. and NW, begin descend.
36.45	Enter nearly level land.
37.60	Right bank of braided wash, bears NW and SE.
39.15	Left bank of braided wash, bears NE and SW.
39.84	The stan. 1/4 sec. cor. of sec. 34 only, remonumented by Ty White in 1947 with an iron post, 1 in. diam., firmly set, projecting 4 ins. from the ground, with brass cap mkd. SC T21N R27E 1/4 S34 1947. A mound of stone, 3 ft. base, 1 ft. high, is set to the N.
	Add mks. 1988 to brass cap.

CHAINS	From this cor. point, a rebar, set by person(s) unknown, 1/2 ins.
	diam., firmly set, projecting 3 ins. from the ground, bears N. 89°19' E., 27.0 lks. dist.
	Cor. is located S. 87 3/4° W., 98 1/4 lks. dist. from barbed wire fences, extending E. and SW.
	Cor. is located N. 22 1/4° E., 267 1/4 lks. dist. from barbed wire fence, extending W. and NE.
	S. 89°40' E., beginning new measurement.
	Over nearly level land.
20.52	A local cor. established by Lacy Greer, LS 5704, bears North, 15 lks. dist., monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 12 ins. from the ground, with brass cap mkd., LS 5704 T20N R26E CC 1/4 S3 1971. A mound of stone 2 ft. base, 1 ft. high is alongside.
	Cor. is located 15 lks. N. of a barbed wire fence, bears E. and W.
39.40	Wash, 3 lks. wide, 1 ft. deep, drains NW.
39.99	The stan. cor. of secs. 34 and 35, monumented with a sandstone, 18 x 11 x 5 ins., loosely set, mkd. with 2 grooves on the W. face, 4 grooves on the E. face, and with SC on the N. face.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

CHAINS	
	S C
	T21N R26E S34 S35
	1988
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
	Bury the stone alongside the stainless steel post.
	Set a steel fence post near the cor.
	From this cor. point, an iron pipe, set by person(s) unknown, 1 1/4 ins. diam., firmly set, projecting 6 ins. from the ground, bears N. 68 1/4° E., 81 lks. dist.
	Cor. is located 51 lks. S. of a barbed wire fence, bears E. and W.
	S. 89°56' E., on S. bdy. of sec. 35.
	Over nearly level land.
18.60	Low ridge, bears NE and SW.
21.01	A local cor. established by Lacy Greer, LS 5704, bears South, 36 lks. dist., monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 9 ins. from the ground, with brass cap mkd., LS 5704 T20N R26E S3 S2 CC 1971.
	Cor. is located 14 lks. S. of a barbed wire fence, bears E. and W.

Wash, 10 lks. wide, drains SSW.
Top of spur, bears E. and S., descend over rolling land.
Enter open, nearly level land.
Wash, 23 lks. wide, 2 ft. deep, drains S.
Barbed wire fence, bears NE and SW.
The stan. 1/4 sec. cor. of sec. 35 only, monumented with a sandstone, 17 x 10 x 2 ins., lying loose, mkd. 1/4 on down face.
At the cor. point
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
S C T21N R26E 1/4 S35
1988
Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white plastic case beneath the stainless steel post.
Bury the stone alongside the stainless steel post.
Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of cor.
Set a steel fence post near the cor.
Cor. is located 50 lks. S. of a barbed wire fence, bears E. and W.
N. 89°56' E., beginning new measurement.
Over open, rolling land.
Wash, 20 lks. wide, 1 ft. deep, drains S.

CHAINS 18.45	Top of spur, bears N. and S.	
19.95	Wash, 2 lks. wide, 1 ft. deep, drains S.	
21.45	Top of spur, bears SSE and NNW.	
24.05	Wash, 15 lks. wide, 1 ft. deep, drains SSE.	
33.90	Top of spur, bears S. and N.	
39.90	Point for the stan. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.	
	s c	
	T21N R26E	
	S35 S36	
	1988	
	from which	
	A juniper, 8 ins. diam. at the base, bears N. 35 3/4° E., 71 lks. dist., mkd. T21N R26E S36 SC BT.	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.	
	Set a steel fence post near the cor.	
	Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of cor.	
	Cor. is located 62 lks. S. of a barbed wire fence, bears E. and W.	
	N. 89°56' E., on the S. bdy. of sec. 36.	
	Over rolling land.	
1.35	Wash, 15 lks. wide, 1 ft. deep, drains SW.	

CHAINS 2.45	Mach 12 lkg wide 1 ft door during MMM
	Wash, 12 lks. wide, 1 ft. deep, drains WNW.
5.10	Wash, 8 lks. wide, 1 ft. deep, drains SSW.
21.10	Top of knoll, bears N. and S.
21.33	A local cor. established by Lacy Greer, LS 5704, bears South, 3 lks. dist., monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 9 ins. from the ground, with brass cap mkd., LS 5704 T21N R26E S2 S1 T20N R26E 1970.
31.90	Top of ridge, bears NNE and SSW.
39.90	Point for the stan. 1/4 sec. cor. of sec. 36, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	s c
	T21N R26E
	1/4 S36
	1988
	1900
	from which
	An aluminum post, 36 ins. long, 3/4 in. diam., set 32 ins. in the ground, for a reference monument, bears N. 1° E., 32.1 ft. dist., with cap mkd. T21N R26E 1/4 S36 SC RM 32.1 FT. 1988, and an arrow pointing to the cor. RM is located in a barbed wire fence, bears E. and W.

CHAINS	An aluminum post, 36 ins. long, 3/4 in. diam., set 26 ins. in the ground, and in a mound of stone, 2 ft. base, to top, for a reference monument, bears N. 62°30' W., 69.5 ft. dist., with cap mkd. T21N R26E 1/4 S36 SC RM 69.5 FT. 1988, and an arrow pointing to the cor. RM is
	located in a barbed wire fence, bears E. and W. Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
51.40	Wash, 8 lks. wide, 1 ft. deep, drains SSW.
54.25	Wash, 80 lks. wide, 2 ft. deep, drains SW.
61.32	A local cor., established by Lacy Greer, LS 5704, bears South, 3 lks. dist., monumented with an iron pipe, 2 ins. diam., firmly set, projecting 6 ins. from the ground, with brass cap mkd., LS 5704 T20N R26E 1/4 S1 CC 1971, with a mound of stone, 2 ft. base, to top alongside. Cor. is located 26 lks. S. of a barbed wire fence, bears E. and W.
68.55	Dirt road, 10 lks. wide, bears NNE and SSW.
69.90	Top of spur, descend over NE slope.
73.50	Ravine, drains irregularly SE; descend 18 ft. over NE slope.
75.15	Top of spur, descend over NE slope.
76.40	Wash, 15 lks. wide, drains SE.
79.80	The stan. cor. of T. 21 N., Rs. 26 and 27 E., monumented with a Sandstone, 15 x 13 x 6 ins. loosely set, projection 10 ins. from the ground, mkd. with 6 grooves on the N., E., and W. faces.
	At the cor. point

CHAINS

Set a stainless steel post, 28 ins, long 2 1/2 ins diam., 21 ins. in the ground, and with a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.

> S C **T21N** R26E | R27E S36 S31 1988

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Bury the original stone alongside the stainless steel post.

Set a steel fence post near the cor.

Cor. is located 3 lks. S. of a barbed wire fence, bears E. and W.

From this cor. point, U.S. Coast and Geodetic Survey triangulation station "DEAD 1936", with published latitude 35°08'29.426" and longitude 109°39'26.711" NAD 27, bears S. 75°05' W., (forward bearing), 610.87 chs. dist., monumented with a brass disk, 4 ins. diam., set flush in a concrete pillar, 9 x 9 ins., projecting 11 ins. from the ground, with top mkd. DEAD 1936 and a triangle.

Dependent Resurvey, the East Boundary T. 21 N., R. 26 E., Gila and Salt River Meridian, Arizona

Restoring the survey executed by Frank Follman in 1882

From the stan. cor. of secs. 36 and 31, T. 21 N., Rs. 26 and 27 E., hereinbefore described.

N. 0°19' E., bet. secs. 31 and 36.

Over rolling land

39.98

Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

CHAINS	
	T21N 1/4 R26E R27E S36 S31 1990
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
79.96	Point for the cor. of secs. 25, 30, 31, and 36, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T21E
	R26E R27E
	S25 S30
	S36 S31
	1990
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
	N. 0°19' E., bet. secs. 25 and 30.
	Over rolling land
1.60	Wash 18 lks. wide, 2 ft. deep, drains SE and SW.
39.98	Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS	
	T21N 1/4 R26E R27E S25 S30 1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
40.55	Wash, 10 lks. wide, drains E.
79.96	Point for the cor. of secs. 19, 24, 25, and 30, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T21E R26E R27E S24 S19
	s25 s30 1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
	N. 0°19' E., bet. secs. 19 and 24.
	Over rolling land
0.70	Wash 8 lks. wide, drain SE.
39.75	Ridge, bears E. and W., descend over N. slope.
39.98	Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the original cor.

CHAINS												
	Set	а	stainless	steel	post,	28	ins.	long,	2	1/2	ins.	diam.,

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T21N 1/4 R26E | R27E S24 | S19 1992

Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Set a steel fence post near the cor.

42.50 Draw, 59 lks. wide, drains SE.

CHAINS

79.96 Point for the cor. of secs. 13, 18, 19, and 24, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

T21E	3
R26E	R27E
S13	S18
-	
S24	S19
1992	<u> </u>

from which

- A juniper, 11 ins. diam., bears N. 49° E., 95 1/2 lks. dist., mkd. T21N R27E S18 BT.
- A juniper, 7 ins. diam., bears S. 60° E., 70 1/2 lks. dist., mkd. T21N R27E S19 BT.

Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.

Set a steel fence post near the cor.

CHAINS	
	N. 0°19' E., bet. secs. 13 and 18.
	Over rolling land
39.98	Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T21N
	1/4 R26E R27E
	S13 S18 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
79.96	Point for the cor. of secs. 7, 12, 13, and 18, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T21E
	R26E R27E S12 S7
:	S13 S18
	1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
	Cor. is located 186 lks. E. of a track road, bears N. and S.

CHAINS	
	N. 0°19' E., bet. secs. 7 and 12.
	Over rolling land
39.98	Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T21N 1/4 R26E R27E S12 S7 1992
:	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
	Cor. is located 141 lks. E. of a track road, bears N. and S.
79.96	Point for the cor. of secs. 1, 6, 7, and 12, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T21E R26E R27E S1 S6 S12 S7 1990
	from which
	A juniper, 9 ins. diam., bears N. 60° E., 184 lks. dist., mkd. T21N R27E S6 BT.

	T. 21 N., R. 26 E., Gila and Salt River Meridian, Arizona
CHAINS	
	A juniper, 7 ins. diam., bears S. 46° E., 271 lks. dist., mkd. T21N R27E S7 BT.
	A juniper, 13 ins. diam., bears N. 15° W., 134 lks. dist., mkd. T21N R27E S1 BT.
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
	Cor. is located 86 lks. E. of a track road, bears SW and NW.
	N. 0°19' E., bet. secs. 1 and 6.
i	Over rolling land
39.98	Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the original cor.
·	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T21N 1/4 R26E R27E S1 S6 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white plastic case beneath the stainless steel post.
	Set a steel fence post near the cor.
	Cor. is located 43 lks. E. of a track road, bears E. and SW.
79.96	The cor of Tps. 21 and 22 N., Rs. 26 and 27 E., hereinafter described.

BOOK 25 360

CHAINS	Restoring the resurvey executed by Ty White in 1947
	From the stan. cor. of secs. 31 and 36, Tps. 21 N., Rs. 25 and 26 E., hereinbefore described.
	N. 0°05' E., bet. secs. 31 and 36.
28.00	Top of low ridge, bears NE and SW.
40.67	The 1/4 sec. cor. of secs. 31 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. from the ground, with brass cap mkd. T21N 1/4 R25E R26E S31 S36 1947, from which the remains of the 1947 bearing trees
	A juniper, 16 ins. diam., bears S. 6 3/4° E., 307 lks. dist., with scribe marks 1/4 S31 BT visible on a partially healed blaze. (Record: 302 lks. dist.)
•	A juniper, 9 ins. diam., bears N. 34 1/2° W., 151 lks. dist., with scribe marks 1/4 S36 BT visible on a partially healed blaze. (Record 152 lks. dist.)
	Add the marks 1990 to the brass cap.
	N. 0°04' E., beginning new measurement.
10.50	Wash, 12 lks. wide, drains SW.
25.71	Wash, 30 lks. wide, drains SW.
28.45	Wash, 15 lks. wide, drains W.
30.70	Wash, 15 lks. wide, drains W.
37.15	Wash, 4 lks. wide, drains W.
40.60	The cor. of secs. 25, 30, 31, and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 9 1/2 ins. from the ground, with brass cap mkd. T21N R25E R26E S25 S30 S31 S36 1947, from which the remains of the 1947 bearing trees
	A juniper, 16 ins. diam., bears N. 16 1/2° E., 221 lks. dist., with scribe marks T21N R26E S30 BT visible on a partially healed blaze.
<u>.</u>	

CHAINS	
	A juniper, 8 ins. diam., bears S. 22 1/2° E., 145 lks. dist., with scribe marks T21N R26E S31 BT visible on a partially healed blaze.
	A juniper, 11 ins. diam., bears S. 30 1/2° W., 342 lks. dist., with scribe marks T21N R25E S36 BT visible on a partially healed blaze.
	A juniper, 8 ins. diam., bears N. 37 3/4° W., 105 lks. dist., with scribe marks T21N R25E S25 BT visible on a partially healed blaze.
	Cor. is located in a barbed wire fence, 6 strands, bears N. and S.
	N. 0°05' E., bet. secs. 25 and 30.
19.35	Wash, 9 lks. wide drains SW.
39.05	Wash, 8 lks. wide drains SW.
40.66	The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 ins. diam., firmly set, projecting 10 ins. from the ground, with brass cap mkd. T21N 1/4 R25E R26E S25 S30 1947, from which the remains of the 1947 bearing trees
	A juniper, 10 ins. diam., bears S. 72 1/4° E., 181 lks. dist., with scribe marks 1/4 S30 BT visible on a partially healed blaze. (Record: S. 72° E., 178 lks. dist.)
	A juniper, 14 ins. diam., bears N. 34 1/2° W., 90 lks. dist., with scribe marks 1/4 S25 BT visible on a partially healed blaze. (Record: 89 lks. dist.)
	Add the marks 1990 to the brass cap.
	Cor. is located in a barbed wire fence, 6 strands, bears N. and S.
	N. 0°05' E., beginning new measurement.
15.60	Track road, bears NE and SW.

	
40.60	The cor. of secs. 19, 24, 25, and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. from the ground, with brass cap mkd. T21N R25E R26E S19, S24, S25 and S30
	1947, from which the remains of the 1947 bearing trees
	A juniper, 6 ins. diam., bears N. 52 3/4° E., 171 lks. dist., with scribe marks T21N R26E S19 BT visible on a partially healed blaze. (Record: 173 lks. dist.)
	A juniper, 12 ins. diam., bears S. 58° E., 126 lks. dist., with scribe marks T21N R26E S30 BT visible on a partially healed blaze.
	A juniper, 11 ins. diam., bears S. 15 1/2° W., 49 lks. dist., with scribe marks T21N R25E S25 BT visible on a partially healed blaze.
	A juniper, 11 ins. diam., bears N. 31 3/4° W., 105 lks. dist., with scribe marks T21N R25E S24 BT visible on a partially healed blaze.
	Add the marks 1990 to the brass cap.
	Cor. is located in a barbed wire fence, 6 strands, bears N. and S.
	N. 0°04' E., bet. secs. 19 and 24.
31.00	Wash, 20 lks. wide, bears NW.
34.40	Wash, 30 lks. wide, drains SW.
40.68	The 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 1 ins. diam., firmly set, projecting 14 ins. from the ground, with brass cap mkd. T21N 1/4 R25E R26E S19 S24 1947, from which the remains of the 1947 bearing trees
	A juniper, 11 ins. diam., bears N. 88 1/2° E., 175 lks. dist., with scribe marks 1/4 S19 BT visible on a partially healed blaze. (Record: S. 89 3/4°E., 176 lks. dist.)
	A juniper, 8 ins. diam., bears S. 86 3/4° W., 118 lks. dist., with scribe marks 1/4 S24 BT visible on a partially healed blaze. (Record: S. 86 1/2° W.)

Add the marks 1990 to the brass cap.			
Cor. is located in a barbed wire fence, 6 strands, bears N. and S.			
N. 0°06' E., beginning new measurement.			
The cor. of secs. 13, 18, 19, and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. from the ground, with brass cap mkd. T21N R25E R26E S13 S18 S19 S24 1947, from which the remains of the 1947 bearing trees			
A juniper, 8 ins. diam., bears N. 18° E., 79 lks. dist., with scribe marks T21N R26E S18 BT visible on a partially healed blaze.			
A juniper, 13 ins. diam., bears S. 30 3/4° E., 46 lks. dist., with scribe marks T21N R26E S19 BT visible on a partially healed blaze.			
A juniper, 10 ins. diam., bears S. 66 1/4° W., 61 lks. dist., with scribe marks T21N R25E S24 BT visible on a partially healed blaze.			
A juniper, 10 ins. diam., bears N. 10 1/2° W., 78 lks. dist., with scribe marks T21N R25E S24 BT visible on a partially healed blaze. (Record: 76 lks. dist.)			
Add the marks 1990 to the brass cap.			
Cor. is located in a barbed wire fence, 6 strands, bears N. and S.			
N. 0°05' E., bet. secs. 13 and 18.			
Over rolling land.			
Wash, 30 lks. wide drains SW.			
Barbed wire fence, 4 strand bears E.			
Spur, slopes W., desc. over a N. slope.			
Wash, 5 lks. wide, drains W.			

CHAINS		
29.45	Spur, slopes W., desc. N. slope.	
39.55	Wash, 5 lks. wide, drains W.	
40.65	The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 1 ins. diam., firmly set, projecting 9 ins. from the ground, with brass cap mkd. T21N 1/4 R25E R26E S13 S18 1947, from which the remains of a 1947 bearing tree	
	A juniper, 16 ins. diam., bears N. 35° W., 109 lks. dist., with scribe marks 1/4 S13 BT visible on a partially healed blaze. (Record: S. 33 3/4° W., 106 lks. dist.)	
	Add the marks 1990 to the brass cap.	
	Cor. is located in a barbed wire fence, 6 strands, bears N. and S.	
•		
	N. 0°06' E., beginning new measurement.	
24.70	Wash, 10 lks. wide, drains W.	
33.70	Spur, slopes E., desc. N. slope.	
40.67	The cor. of secs. 7, 12, 13, and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. from the ground, with brass cap mkd. T21N R25E R26E S7 S12 S13 S18 1947, from which the remains of the 1947 bearing trees	
	A juniper, 18 ins. diam., bears N. 17 3/4° E., 188 lks. dist. with scribe marks T21N R26E S7 BT visible on a partially healed blaze.	
	A juniper, 12 ins. diam., bears S. 73 1/4° E., 211 lks., dist. with scribe marks T21N R26E S18 BT visible on a partially healed blaze.	
	A juniper, 16 ins. diam., bears S. 86 1/4° W., 132 lks., dist. with scribe marks T21N R25E S13 BT visible on a partially healed blaze.	
	A juniper, 18 ins. diam., bears N. 20° W., 117 lks., dist. with scribe marks T21N R25E S12 BT. visible on a partially healed blaze.	

CHAINS	Cor. is located in a barbed wire fence, 6 strands, bears N. and S. N. 0°06' E., bet. secs. 7 and 12. Over rolling land.		
40.64	The 1/4 sec. cor. of secs. 7 and 12, monumented with an iron post, 1 ins. diam., firmly set, projecting 9 ins. from the ground, with brass cap mkd. T21N 1/4 R25E R26E S7 S12 1947, from which the remains of the 1947 bearing trees		
	A juniper, 10 ins. diam., bears N. 32 3/4° E., 532 lks. dist., with scribe marks 1/4 S7 BT visible on a partially healed blaze.		
	A juniper, 9 ins. diam., bears N. 13 3/4° E., 300 lks. dist., with scribe marks 1/4 S12 BT visible on a partially healed blaze.		
	Cor. is located in a barbed wire fence, 6 strands, bears N. and S.		
	N. 0°06' E., beginning new measurement.		
1.40	Cut bank, 9 ft. high, bears E. and W.		
7.35	Left bank of the Dead wash, 20 ft. high, course SW.		
17.25	Right bank of the Dead wash, 20 ft. high, course SW.		
39.85	The cor. of secs. 1, 6, 7, and 12, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. from the ground, with brass cap mkd. T21N R25E R26E S1 S6 S7 S12 1947, from which the remains of the 1947 bearing trees		
	A juniper, 13 ins. diam., bears N. 4 3/4° E., 225 lks. dist. with scribe marks T21N R26E S6 BT visible on a partially healed blaze.		
	L		

	The state of the s			
CHAINS				
	A juniper, 6 ins. diam., bears S. 37 1/2° E., 363 lks., dist. with scribe marks T21N R26E S7 BT visible on a partially healed blaze.			
	A sawed juniper stump, 7 ins. diam., bears S. 60° W., 13 lks., dist. with no marks visible.			
	A juniper, 7 ins. diam., bears N. 23 1/2° W., 424 lks., dist. with scribe marks T21N R25E S1 BT visible on a partially healed blaze.			
	Cor. is located in a barbed wire fence, 6 strands, bears N. and S.			
	N. 0°07' E., bet. secs. 1 and 6.			
	Over rolling land.			
22.10	Draw, drains SE.			
40.65	The 1/4 sec. cor. of secs. 1 and 6, monumented with an iron post, 1 ins. diam., firmly set, projecting 10 ins. from the ground, with brass cap mkd. T21N 1/4 R25E R26E S1 S6 1947, from which the remains of the 1947 bearing trees			
	A juniper, 12 ins. diam., bears N. 67° E., 82 lks. dist., with scribe marks 1/4 S6 BT visible on a partially healed blaze.			
	A juniper, 6 ins. diam., bears N. 80 3/4° E., 18 lks. dist., with scribe marks 1/4 S1 BT visible on a partially healed blaze.			
	Cor. is located in a barbed wire fence, 6 strands, bears N. and S.			
	N. 0°07' E., beginning new measurement.			
40.63	The cor. of Tps. 21 and 22 N., Rs. 25 and 26 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 1 ins. from the ground, with brass cap mkd. T22N R25E R26E S31 S6 S1 S36 T21N 1947, from which the remains of the 1947 bearing trees			

CHAINS

- A juniper, 8 ins. diam., bears N. 30 3/4° E., 148 lks. dist., with scribe marks T22N R26E S31 BT visible on a partially healed blaze. (Record: N. 30° E., 149 lks. dist.).
- A juniper, 10 ins. diam., bears S. 23 3/4° E., 202 lks., dist., with scribe marks T21N R26E S6 BT visible on a partially healed blaze.
- A juniper, 13 ins. diam., bears S. 81 3/4° W., 285 lks., dist., with scribe marks T21N R25E S1 BT visible on a partially healed blaze. (Record: S. 81 1/4 W., 286 lks. dist.)
- A juniper, 15 ins. diam., bears N. 54 3/4° W., 200 lks., dist., with scribe marks T22N R25E S36 BT visible on a partially healed blaze. (Record: N. 55 1/4 W., 202 lks. dist.)

Add the marks 1990 to the brass cap.

Cor. is located at the intersections of a barbed wire fence, 6 strands, bears E., SE., and W.

Dependent Resurvey, the North Boundary T. 21 N., R. 26 E., Gila and Salt River Meridian, Arizona

Restoring the survey executed by Ty White in 1947

From the cor. of Tps. 21 and 22 N., Rs. 26 and 27 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. from the ground, with brass cap mkd. T22N R26E R27E S31 S6 S1 S36 T21N 1947, from which the remains of the 1947 bearing trees

- A burned juniper stump, 9 ins. diam., bears N. 47 3/4° E., 517 lks., dist. with no marks visible. (Record: N. 48° E., 510 lks. dist.)
- A juniper, 16 ins. diam., bears S. 54 3/4° E., 367 lks., dist. with scribe marks T21N R27E S6 BT visible on a partially healed blaze. (Record: 369 lks. dist.)
- A juniper, 15 ins. diam., bears S. 84 1/4° W., 209 lks., dist. with scribe marks T21N R26E S1 BT visible on a partially healed blaze. (Record: 210 lks. dist.)

CHAINS	
	A juniper, 13 ins. diam., bears N. 67 1/4° W., 153 lks., dist. with scribe marks T22N R26E S36 BT visible on a partially healed blaze.
	Add the marks 1990 to the brass cap.
Cor. is located 2 lks. N. of a cor. of barbed wire fend strands, extending E., S., and W.	
	N. 89°17' W., bet. secs. 36 and 1.
40.05	The 1/4 sec. cor. of secs. 1 and 36, monumented with an iron post, 1 ins. diam., firmly set, projecting 7 ins. from the ground, with brass cap mkd. 1/4 S36 S1 1947, from which the remains of the 1947 bearing trees
	A juniper, 15 ins. diam., bears N. 34 3/4° E., 158 lks. dist., with illegible scribe marks visible on a partially healed blaze. (Record: N. 35° E., 152 lks. dist.)
	A juniper, 6 ins. diam., bears S. 5 3/4° E., 234 lks. dist., with scribe marks 1/4 S1 BT visible on a partially healed blaze. (Record: 235 lks. dist.)
	Add the marks 1990 to the brass cap.
:	Cor. is located 3 lks. N. of a barbed wire fence, 5 strands, bears E. and W.
	N. 89°11' W., beginning new measurement.
40.04	The cor. of secs. 1, 2, 35, and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. from the ground, with brass cap mkd. T22N R26E S36 S1 S2 S35 T21N 1947, from which the remains of the 1947 bearing trees
	A juniper, 13 ins. diam., bears N. 62 1/4° E., 304 lks., dist. with scribe marks T22N R26E S36 BT visible on a partially healed blaze.
	A juniper, 34 ins. diam., bears S. 34 1/4° E., 72 lks., dist. with scribe marks T21N R26E S1 BT visible on a partially healed blaze.
	A juniper, 8 ins. diam., bears S. 45 3/4° W., 213 lks., dist. with scribe marks T21N R26E visible on a partially healed blaze. (Record: S. 45° W.)

CHAINS	
Cimino	A juniper, 9 ins. diam., bears N. 39 3/4° W., 485 lks., dist. with scribe marks T22N R26E S35 BT visible on a partially healed blaze. (Record: 486 lks. dist.)
	Add the marks 1990 to the brass cap.
	Cor. is located 6 lks. N. of a barbed wire fence, 5 strands, bears E. and W.
	N. 89°16' W., bet. secs. 2 and 35.
40.03	The 1/4 sec. cor. of secs. 2 and 35, monumented with an iron post, 1 ins. diam., firmly set, projecting 6 ins. from the ground, with brass cap mkd. 1/4 S35 S1 1947, from which the remains of the 1947 bearing trees
	A juniper stump, 12 ins. diam., bears N. 11° E., 36 lks. dist., a down juniper branch alongside with scribe marks 1/4 S35 BT visible on partially healed blaze. (Record: N. 12 1/2° E.)
	A juniper stump, 12 ins. diam., bears S. 86 1/4° W., 14 lks. dist., with scribe marks 1/4 S2 BT visible on a partially healed blaze. (Record: S. 87 1/4° W.)
	Add the marks 1990 to the brass cap.
	Cor. is located in a barbed wire fence, 5 strands, bears E. and W.
	N. 89°15' W., beginning new measurement.
40.03	The cor. of secs. 2, 3, 34, and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. from the ground, with brass cap mkd. T22N R26E S35 S2 S3 S34 T21N 1947, from which the remains of the 1947 bearing trees
	A juniper, 15 ins. diam., bears N. 75 1/2° E., 207 lks. dist., with scribe marks T22N R26E S35 BT visible on a partially healed blaze. (Record: N. 76° E.)
	A juniper, 14 ins. diam., bears S. 53 3/4° E., 84 lks. dist., with scribe marks T21N R26E S2 BT visible on a partially healed blaze. (Record: S. 52 3/4° E.)
40.03	The cor. of secs. 2, 3, 34, and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. from the ground, with brass cap mkd. T22N R26E S35 S2 S3 S34 T21N 1947, from which the remains of the 1947 bearing trees A juniper, 15 ins. diam., bears N. 75 1/2° E., 207 lks. dist., with scribe marks T22N R26E S35 BT visible on a partially healed blaze. (Record: N. 76° E.) A juniper, 14 ins. diam., bears S. 53 3/4° E., 84 lks. dist., with scribe marks T21N R26E S2 BT visible on a

CHAINS					
	A juniper, 6 ins. diam., bears S. 6° W., 190 lks. dist., with no marks visible. (Record: S. 6 1/2° W.)				
	A juniper, 7 ins. diam., bears N. 65° W., 311 lks. dist., with scribe marks BT visible on a partially healed blaze. (Record: 320 lks. dist.)				
	Add the marks 1990 to the brass cap.				
	Cor. is located in a barbed wire fence, 5 strands, bears E. and W.				
	N. 89°14' W., bet. secs. 3 and 34.				
	Over rolling land.				
40.04	The 1/4 sec. cor. of secs. 3 and 34, monumented with an iron post, 1 ins. diam., firmly set, projecting 11 ins. from the ground, with brass cap mkd. 1/4 S34 S3 1947.				
	Cor. is located in a barbed wire fence, 5 strands, bears E. and W.				
	N. 89°15' W., beginning new measurement.				
40.03	The cor. of secs. 3, 4, 33, and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. from the ground, with brass cap mkd. T22N R26E S34 S3 S4 S33 T21N 1947, from which the remains of the 1947 bearing trees				
	A juniper, 13 ins. diam., bears N. 22° E., 165 lks., dist. with scribe marks T22N R26E S34 BT visible on partially healed blaze.				
	A juniper, 14 ins. diam., bears S. 68 1/2° W., 93 lks., dist. with scribe marks T21N R26E S4 BT visible on a partially healed blaze.				
	Cor. is located in a barbed wire fence, 5 strands, bears E. and W.				
	N. 89°15' W., bet. secs. 4 and 33.				
	,				

	T. 21 N., R. 20 E., Glia and Sait River Meridian, Arizona		
CHAINS			
	Over rolling land.		
40.05	The 1/4 sec. cor. of secs. 4 and 33, monumented with an iron post, 1 ins. diam., firmly set, projecting 9 ins. from the ground, with brass cap mkd. 1/4 S33 S4 1947, from which the remains of the 1947 bearing trees		
	A juniper stump, 4 ins. diam., bears N. 47° E., 236 lks. dist., with scribe marks 1/4 S33 BT visible on a partially healed blaze. (Record: 237 lks. dist.)		
A juniper stump, 29 ins. diam., bears S. 23 1/4° W., 331 lks. dist., with scribe marks 1/4 S4 BT visible partially healed blaze. (Record: S. 33 1/2° E.)			
	Add the marks 1990 to the brass cap.		
	Cor. is located in a barbed wire fence, 5 strands, bears E. and W.		
N. 89°15' W., beginning new measurement.			
40.06	The cor. of secs. 4, 5, 32, and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. from the ground, with brass cap mkd. T22N R26E S33 S4 S5 S32 T21N 1947, from which the remains of the 1947 bearing trees		
	A juniper, 15 ins. diam., bears N. 21 1/4° E., 197 lks. dist., with scribe marks T22N R26E S33 BT visible on a partially healed blaze.		
	A juniper, 7 ins. diam., bears S. 38 3/4° E., 47 lks. dist., with scribe marks T21N R26E S4 BT visible on a partially healed blaze.		
	A juniper, 8 ins. diam., bears S. 72 1/2° W., 84 lks. dist., with healed blaze. (Record: S. 74° W.)		
	A juniper, 10 ins. diam., bears N. 60° W., 120 lks., dist. with scribe marks BT visible on a partially healed blaze. (Record: N. 59 1/2° W., 127 lks. dist.)		
	Add the marks 1990 to the brass cap.		
ļ	Cor. is located in a barbed wire fence, 5 strands, bears E. and W.		

CHAINS				
	N. 89°14' W., bet. secs. 5 and 32. Over rolling land.			
40.03	The 1/4 sec. cor. of secs. 5 and 32, determined from a 1947 bearing tree			
	A juniper, 14 ins. diam., bears N. 72 1/4° W., 256 lks. dist., with scribe marks 1/4 S32 BT visible on a partially healed blaze.			
	At the cor. point			
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.			
	T22N R26E			
	S32			
	1/4 S5			
	T21N			
	1990 from which			
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 23 ins. in the ground, for a reference monument, bears S. 77°50' E., 206.9 ft. dist., with brass cap mkd. RM T21N R26E 1/4 S5 206.9 FT 1990, with arrow pointing the true corner point.			
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bea N. 11°17' W., 130.8 ft. dist., with brass cap mkd. RM T22N R26E 1/4 S32 206.9 FT 1990, with arrow pointing to the true corner point.			
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel posts. Set a steel fence post near the cor. Cor. is located in the center of a wash, drains SW; set on top of a fence post.			
	Cor. is also located 2 lks. N. of a barbed fence, 5 strands bears E. and W.			

CHAINS	T T		
CHAINS			
	N. 89°17' W., beginning new measurement.		
39.99	The cor. of secs. 5, 6, 31, and 32, monumented with an iron p 2 ins. diam., firmly set, projecting 7 ins. from the ground, brass cap mkd. T22N R26E S32 S5 S6 S32 T21N 1947, from which remains of the 1947 bearing trees		
	A juniper, 9 ins. diam., bears N. 35 1/2° E., 160 lks. dist., with scribe marks T22N R26E S32 BT visible on a partially healed blaze.		
	A juniper, 8 ins. diam., bears N. 8° W., 474 lks. dist., with scribe marks T21N R26E S31 BT. visible on a partially healed blase.(Record: 470 lks. dist.)		
	Add the marks 1990 to the brass cap.		
	Cor. is located in a barbed wire fence, 5 strands, bears E. and W.		
	N. 89°16' W., bet. secs. 6 and 31.		
34.90	Wash, 135 lks. wide, 11 ft. deep, drains SW, asc. over a NW slope.		
38.50	Wash, 169 lks. wide, 9 ft. deep, drains S.		
39.99	The 1/4 sec. cor of secs. 6 and 31, monumented with an iron post, 1 ins. diam., firmly set, projecting 7 ins. from the ground, with brass cap mkd. 1/4 S31 S6 1947, from which the remains of the 1947 bearing trees		
	A juniper, 11 ins. diam., bears S. 55 3/4° W., 375 lks. dist., with scribe marks 1/4 S6 BT visible on a partially healed blaze. (Record: 373 lks. dist.)		
	A juniper, 12 ins. diam., bears N. 38° W., 339 lks. dist., with scribe marks 1/4 S31 BT visible on a partially healed blaze. (Record: 341 lks. dist.)		
	Add the marks 1990 to the brass cap.		
	N. 89°13' W., beginning new measurement.		

CHAINS	Over rolling land.			
39.43	39.43 The cor of Tps. 21 and 22 N., Rs. 25 and 26 E., hereinbefor described.			
	GENERAL DESCRIPTION			
	The land encompassed in this survey is located approximately 5 miles northwest of the town of Navajo, Arizona. Elevations range from 5000 to 6000 feet above sea level.			
	Access is extremely limited. Several private drive ways and livestock water tank check roads are the extent of improved dirt roads south of the standard. Access from the north is nonexistent.			
	The area is primarily used for the grazing of livestock. The flora consists of grasses, sage, and juniper, ranging from sparse to moderate in density.			

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Daniel Patterson	Land Surveyor
Luke B. Granger	Surveying Technician
Stephen K. Hansen	Surveying Technician
Gary D. Knoff	Surveying Technician
Robert J. Lyle	Surveying Technician
Gerry VanWagenen	Surveying Technician
Ted E. Cazier	Surveying Aid
Craig McFarland	Surveying Aid
Bruce Olson	Surveying Aid
Keith Prim	Со-ор
Mark Wahler	Со-ор
	<u> </u>

CERTIFICATE OF SURVEY

We, Stephen J. Malloy, Gary D. Johnson and Darren R. Breckenridge, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 12th day of January, 1987, supplemental special instructions bearing date of the 13th day of October, 1987, supplemental special instructions bearing date of the 29th day of February, 1988, and amended supplemental special instructions bearing date of the 11th day of January, 1989, We have dependently resurveyed a portion of the Fifth Standard Parallel North (south boundary) and the exterior boundaries of Township 21 North, Range 26 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Gary D. Johnson and Darren R. Breckenridge are no longer assigned to this office and are unavailable for signatures.

(Date)

Styl J Mulling
(Supervisory Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Arizona State Office Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the fifth standard parallel north (south boundary) and the exterior boundaries of Township 21 North, Range 26 East, Gila and Salt River Meridian, Arizona, executed by Gary D. Johnson and Darren R. Breckenridge, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

JUN 1 7 1992	(Chief Cadastral Surveyor of Arizona)
(Date)	(Chief Cadastral Surveyor of Arizona)
	CERTIFICATE OF TRANSCRIPT
	CHAILICAID OF HANDCAILI
	transcript of the field notes of the above-described ., Gila and Salt River Meridian, Arizona is a true copy
-	
(Date)	(Chief Cadastral Surveyor of Arizona)