1

ORIGINAL

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

THE ARIZONA - NEW MEXICO STATE BOUNDARY
FROM MILE POST 316 TO MILE POST 321,
AND PORTIONS OF THE SOUTH BOUNDARY AND SUBDIVISIONAL LINES,
THE SUBDIVISION OF CERTAIN SECTIONS
AND THE METES-AND-BOUNDS SURVEY OF THE
PELONCILLO MOUNTAINS WILDERNESS AREA BOUNDARY
IN
TOWNSHIP 12 SOUTH, RANGE 32 EAST,
Of theGila and Salt River Meridian, In the State ofArizona
EXECUTED BY Robert C. Umbanhowar and Stephen K. Hansen, Cadastral Surveyors

Under Special Instructions dated <u>January 6, 1992</u>, approved <u>January 6, 1992</u>, which provided for the surveys included under Group Number <u>739</u>, and assignment instructions dated <u>January 8, 1992</u>, and <u>August 6, 1992</u>.

Survey Commenced <u>June 16, 1992</u> Survey Completed <u>June 13, 1993</u>

INDEX DIAGRAM

TOWNSHIP 12 SOUTH , RANGE 32 EAST 315M 5 3 2 6 - 316M -20--31--27--39-2Ó 9 27 10 39 8 11 7 - 317M -26--18--38-38 14 17 15 18 16 - 318M -25--18--37-17 25 22 23 19 36 20 21 319M 30 24 -15-34 29 28 23 27 14 26 33 29 30 320M -22-29 -13 -32--32 21 34 12 35 32 28 33 31 321M 31 -11--10-

Subdivision of Sec. 4 - page 40 Subdivision of Sec. 7 - pages 41-42 Subdivision of Sec. 18 - pages 42-43 Subdivision of Sec. 19 - pages 43-45 Subdivision of Sec. 26 - pages 46-47 Subdivision of Sec. 27 - pages 47-50 Subdivision of Sec. 29 - pages 50-52 Subdivision of Sec. 30 - pages 52-54 Subdivision of Sec. 31 - pages 54-57 Subdivision of Sec. 33 - pages 57-59 Subdivision of Sec. 34 - pages 59-61 Metes and Bounds Survey - pages 61-133 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of the dependent resurvey of the Arizona-New Mexico State Boundary from Mile Post 316 to Mile Post 321, and portions of the south boundary and subdivisional lines, the subdivision of certain sections, and the metes-and-bounds survey of the Peloncillo Mountain Wilderness Area Boundary in Township 12 South, Range 32 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this resurvey is as follows: Chandler Robbins surveyed the Arizona-New Mexico State Boundary in 1875. Clarence Goddard resurveyed a portion of the Arizona-New Mexico State Boundary and the south boundary and subdivisional lines of T. 22 S., R. 21 W., New Mexico Principal Meridian, New Mexico, in 1904. William B. Kimmel surveyed the north, west, and a portion of the south boundaries, and a portion of the subdivisional lines in 1914. Guy R. Veal and Karl L. Siebecker retraced a portion of the Arizona-New Mexico State Boundary, and surveyed a portion of the south boundary and completed the subdivisional lines in 1919-20. Sidney E. Blout corrected a portion of the Arizona-New Mexico State Boundary and subdivisional lines in 1921. Mr. Blout had no knowledge of the existence of the 1904 resurvey record of the Arizona-New Mexico State Boundary. Dupree R. Averill resurveyed a portion of the Arizona-New Mexico State Boundary in 1933.

The survey was executed in accordance with the specifications as set forth in the <u>Manual of Surveying Instructions</u>, 1973, and the Special Instructions dated January 6, 1992, for Group No. 739, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The purpose of this survey was to determine the boundary of the Peloncillo Mountains Wilderness Area.

The directions of all lines were determined by direct hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with a Topcon GTS3B Total Station, a Leitz Set 4 electronic instrument and a Pentax PTS-iii05 Total Station.

The geographic position of the corner of sections 3, 4, 33 and 34, on the S. bdy. of the Tp. as determined from a tie made to United States Geological Survey triangulation station "Doubtful 1948", located in the SW quarter of section 23, Township 12 South, Range 32 East, is as follows:

T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS

Latitude: 32°20'21.34" N. Longitude: 109°04'24.26" W. NAD 27

The mean magnetic declination as taken from quadrangle map ENGINE MOUNTAIN, ARIZ., published in 1987 by United States Geological Survey, is $11\ 1/2^{\circ}$ E.

Dependent Resurvey of the Arizona-New Mexico State Bdy., from Mile Post 316 to Mile Post 321, T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

Restoring the resurveys executed by Clarence Goddard in 1904 and Guy R. Veal and Karl L. Siebecker in 1919 and Sidney E. Blout in 1921

Beginning at the 316 Mile Post, monumented with a basalt stone, $8 \times 10 \times 18$ ins., firmly set, projecting 9 ins. above ground, in a scattered collar of stone, with the marks NM on the E., WL32 on the S., 316 on the N., and AZ on the W. faces, with a scattered mound of stone to the N.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled in a collar of stone, 3 ft. diam., with brass cap mkd.

31	L6M
AZ	NM
T12S	T22S
R32E	R21W
S2	S7
19	92

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Deposit the basalt stone alongside the stainless steel post, in the collar of stone.

S. $0^{\circ}04^{\circ}$ E., on the 317th mile of the Arizona-New Mexico State Bdy.

- 8.07 Point for the closing cor. of secs. 2 and 11, T. 12 S., R. 32 E., Gila and Salt River Mer., Arizona, hereinafter described.
- 65.18 Point for AP 6, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.

5

Dependent Resurvey of the Arizona-New Mexico Bdy., from Mile Post 316 to Mile Post 321, T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

	1. 12 be, No 52 be, Glid disk ball Rivel intraction.
CHAINS	
68.78	From this point, the closing cor. of secs. 7 and 18, T. 22 S., R. 21 W., New Mexico Principal Meridian, New Mexico, monumented with a stone, 12 x 10 x 9 ins., firmly set, projecting 9 ins. above ground, with marks CC on E. face, bears East, 0.03 chs. dist.
80.21	The 317 Mile Post, monumented with a limestone, 6 x 12 x 14 ins., firmly set, projecting 10 ins. above ground in a scattered collar of stone, mkd. NM on the E., 32WL on the S., 317 on the N., and AZ on the W. faces,
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	317 M
	AZ NM T12S T22S
	R32E R21W
	S11 S18 1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	Deposit the limestone alongside the stainless steel post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	S. 0°07' W., on the 318th Mile of the Arizona-New Mexico State Bdy.
8.19	Point for the closing cor. of secs. 11 and 14, T. 12 S., R. 32 E., Gila and Salt River Mer., Arizona, hereinafter described.
15.48	Point for AP 1, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
79.26	Point for the 318 Mile Post, at proportionate dist. based on the 1921 record and on line with the original witness cor. to restore the integrity of the original survey; there is no remaining evidence of the 1904 cor.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled in a collar of stone, with brass cap mkd.

6

Dependent Resurvey of the Arizona-New Mexico Bdy., from Mile Post 316 to Mile Post 321,

T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

	1. 12 de, R. 32 de, Gild dist bate river religion, Arizona
CHAINS	
	318 M AZ NM T12S T22S R32E R21W S14 S19 PMWA 1992 Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case
	S. 0°07' W., on the 319th Mile of the Arizona-New Mexico State Bdy.
8.62	Point for the closing cor. of secs. 14 and 23, T. 12 S., R. 32 E., Gila and Salt River Mer., Arizona, hereinafter described.
35.19	The witness cor. to the 318 Mile Post, monumented with a granite stone, 16 x 18 x 22 ins. high, mkd. NM on the E., and AZ on the W. faces, no other marks visible, set in a scattered mound of stone, 3 ft. base.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., on the surface bedrock, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.
	WC
	318 M
	AZ
	S23 S19 PMWA
	1992
	Deposit the original stone in the supporting mound of stone.
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	S. 0°03'E., beginning new measurement.
43.58	The 319 Mile Post, established in 1904, monumented with a granite stone, 7 x 11 x 18 ins., loosely set, on bedrock, with the marks NM on the east face, 32WL on the S., 319 on the N., and ARIZ on the W. faces, in a supporting mound of stone, 5 ft. base, to top of stone.

Dependent Resurvey of the Arizona-New Mexico Bdy., from Mile Post 316 to Mile Post 321,

T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS	
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., on bedrock, in a mound of stone, 5 ft. base, to top, with brass cap mkd.
	319 M AZ NM T12S T22S R32E R21W S23 S30 1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case inside the stainless steel post.
	Deposit the granite stone in the supporting mound of stone.
	S. 0°02' E., on the 320th Mile of the Arizona-New Mexico State Bdy.
9.65	Point for the closing cor. of secs. 23 and 26, T. 12 S., R. 32 E., Gila and Salt River Mer., Arizona, hereinafter described.
29.71	Point for the N 1/16 sec. cor. of sec. 26 only, T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona, hereinafter described.
49.77	Point for the 1/4 sec. cor. of sec. 26 only, T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona, hereinafter described.
69.83	Point for the S 1/16 sec. cor. of sec. 26 only, T. 12 S., R. 32 E. Gila and Salt River Meridian, Arizona, hereinafter described.
78.50	The closing cor. of secs. 30 and 31, T. 22 S., R. 21 W., New Mexico Principal Meridian, New Mexico, monumented with a stone, 15 x 8 x 4 ins., firmly set, projecting 7 ins. above ground, with marks CC on E. face, with scattered mound of stone to the E.
79.65	Point selected for a witness cor. for the 320th Mile Post.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled in a collar of stone, with brass cap mkd.

8

Dependent Resurvey of the Arizona-New Mexico Bdy., from Mile Post 316 to Mile Post 321,

T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

С	H	٩I	N	S

WC 320 M
AZ | NM
T12S | T22S
R32E | R21W
S26 | S31
1993

Deposit a magnet in a 1 \times 1 \times 2 ins. white plastic case beneath the stainless steel post.

Cor. is located 2 lks. E. of barbed wire fence, 4 strand, bears N. and S.

80.10 True point for the 320 Mile Post, at proportionate dist. based on the 1904 record; there is no remaining evidence of the 1904 cor. Point falls in wash, 3 lks. wide, 3 ft. deep, drains SSW., and is impracticable to monument.

S. $0^{\circ}02^{\circ}$ E., on the 321st Mile of the Arizona-New Mexico State Bdy..

- 9.79 The closing cor. of secs. 26 and 35, hereinafter described.
- 80.11 The 321 Mile Post, monumented with a granite stone, 9 x 16 x 18 ins., loosely set, projecting 16 ins. above ground, encircled in a collar of stone, 4 ft. diam. with the marks NM on E., 32WL on S., 321 on N., and ARIZ on the W. faces.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled in a collar of stone, with brass cap mkd.

Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Bury the granite stone along N. side of the stainless steel post.

Cor. is located 9 lks. E. of barbed wire fence, 4 strand, bears N. and S.

Dependent Resurvey of a Portion of the South Boundary T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	Restoring the Surveys Executed by William B. Kimmel in 1914 and Guy R. Veal and Karl L. Siebecker in 1919
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 20 ins. above ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd. T12S R32E S34 S35 S3 S2 T33S 1919.
	Add the marks 1993 to the brass cap.
	Cor. is located 2 lks. W. of cor. of barbed wire fence, 4 strand, bears N. and E., and 15 lks. W. of trail road, bears N. and SSW.
	S. 89°57' W., bet. secs. 3 and 34.
20.00	Point for the E 1/16 sec. cor. of secs. 3 and 34.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
·	T12S R32E PMWA S34 E 1/16 — S 3 T13S 1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
40.00	The 1/4 sec. cor. of secs. 3 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with a mound of stone to the N., 2 ft. base, 1 ft. high, with brass cap mkd. 1/4 S34 S3 1919.
	Add the marks T12S R32E T13S 1993 to the brass cap.
	S. 89°59' W., beginning new measurement.
19.985	Point for the W 1/16 sec. cor. of secs. 3 and 34.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
·	T12S R32E S34 PMWA W 1/16 —— S 3 T13S 1993

Dependent Resurvey of a Portion of the South Boundary T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
39.97	The cor. of secs. 3, 4, 33 and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. T12S R32E S33 S34 S4 S3 T13S 1919.
	Add the marks 1993 to the brass cap.
	Cor. is located 3 lks. SW of cor. of barbed wire fence, 4 strand, bears S. and W.
	From this cor. point, U.S.G.S. triangulation station "Doubtful 1948", with published latitude of 32° 22' 29.334" N. and longitude of 109° 03' 22.053" W., NAD 27, bears N. 22° 24' 50" E. (foward bearing), 212.01 chains distant, with a chiseled "x" on a boulder.
	West, bet. secs. 4 and 33.
19.96	Point for the E 1/16 sec. cor. of secs. 4 and 33.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T12S R32E
	PMWA S33
	E 1/16 —
	S 4
1	T13S
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 6 lks. S. of cor. of barbed wire fence, 4 strand, bears N. and E.
28.66	AP 95, T. 13 S., R. 32 E., on the Peloncillo Mountains Wilderness Area Bdy., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T12S R32E S33 AP95 PMWA S4 T13S 1993, as described in the field notes of the Metes and Bounds survey of the Peloncillo Mountains Wilderness Area Bdy., T. 13 S., R. 32 E., executed concurrently under this same group.
39.92	The 1/4 sec. cor. of secs. 4 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 20 ins. above ground, with brass cap mkd. 1/4 S33 S4 1919, from which the original bearing trees
L	<u> </u>

Dependent Resurvey of a Portion of the South Boundary T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS	A cedar limb, 8 ins. diam., bears S. 7 1/4° E., 116 lks. dist., mkd. 1/4 S4 BT. (Record: S. 6 1/2° E., 112 lks.)
	A cedar, 9 ins. diam., bears N. 25° W., 26 lks. dist., mkd. 1/4 S33 BT. (Record: N. 27° W.)
	Add the marks T12S R32E T13S 1993 to the brass cap.
	Build mound of stone, 3 ft. base, to top of brass cap.
	S. 89°58' W., beginning new measurement.
39.88	The true point for the cor. of secs. 4, 5, 32 and 33, at proportionate dist. Point falls on steep face of rock cliff, and is impractical to monument.
40.40	The witness cor. of secs. 4, 5, 32 and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 24 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. T12S R32E S32 S33 WC S5 S4 T13S 1919, from which the original bearing tree
	A Utah Juniper, 8 ins. diam., bears S. 16 1/2° W., 253 lks. dist., mkd. T13S R32E S5 BT. (Record: 284 lks. dist.)
	Add the marks 1993 to the brass cap.
	From the cor. of secs. 5, 6, 31 and 32, monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above ground, with a scattered mound of stone to W., with brass cap mkd. T12S R32E S31 S32 S6 S5 T33S 1919.
	Add the marks 1992 to the brass cap.
i	Rebuild mound of stone W. of cor., 3 ft. base x 2 ft. high.
	S. 89°59' W., bet. secs. 6 and 31.
20.01	Point for the E 1/16 sec. cor. of secs. 6 and 31.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled in a collar of stone, with brass cap mkd.
	T12S R32E
	S31 E 1/16
	s 6
	T13S 1993

Dependent Resurvey of a Portion of the South Boundary T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS	from which
	A boulder, 15 x 6 x 6 ft. high, bears N. 25 1/4° E., 123 lks. dist, with X BO chiseled on the SW face.
	A boulder, 7 x 4 x 3 ft. high, bears S. 87 3/4° W., 71 lks. dist., with X BO chiseled on the NE face.
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
39.14	Wash, 30 lks. wide, 2 ft. deep, drains NE.
40.02	The 1/4 sec. cor. of secs. 6 and 31, monumented with an iron post, 1 in. diam., loosely set, projecting 16 ins. above ground in a scattered mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. 1/4 S31 S6 1919, from which the original bearing trees
	A cedar, 18 ins. diam., bears N. 32° E., 5 lks. dist., mkd. 1/4 S31 BT.
	A cedar, 14 ins. diam., bears S. 27 1/2° W., 47 lks. dist., mkd. 1/4 S33 BT. (Record: 43 lks. dist.)
	Add the marks 1992 to the brass cap.
	Rebuild mound of stone, 4 ft. base, to top.
	Dependent Resurvey of a Portion of the Subdivisional Lines T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°02' W., bet. secs. 34 and 35.
39.99	The 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 20 ins. above ground, with brass cap mkd. 1/4 S34 S35 1919.
	Add the marks 1993 to the brass cap.
	Cor. is located 2 lks. W. of barbed wire fence, 4 strand, bears N. and S.
	N. 0°10' E., beginning new measurement.

39.91	The cor. of secs. 26, 27, 34 and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. T12S R32E S27 S26 S34 S35 1919.
	Add the marks 1993 to the brass cap.
	Cor. is located 4 lks. S. of cor. of barbed wire fence, 4 strand, bears S. and W.
	N. 89°58' E., bet. secs. 26 and 35.
20.01	Point for the W 1/16 sec. cor. of secs. 26 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12S R32E
	PMWA S26 W 1/16 ——
	w 1/16 —— S35
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
40.02	The 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with a mound of stone to the N., 3 ft. base, 2 ft. high, with brass cap mkd. 1/4 S26 S35 1919.
	Add the marks T12S R32E 1993 to the brass cap.
	S. 89°47' E., beginning new measurement.
1.56	The original closing cor. of secs. 26 and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 24 ins. above ground, in a scattered mound of stone, with brass cap mkd. T12S R32E S26 S35 CC 1919.
	Add the marks AM to the brass cap, cut the iron post in half, and bury in place.
1.59	Intersect the Arizona-New Mexico State Bdy.
	Point for the closing cor. of secs. 26 and 35.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled in a collar of stone, with brass cap mkd.

CHAINS	
	T12S R32E
į.	S26
	œ —
	S35
	1993 '
	Deposit a magnet in a 1 \times 1 \times ins. white plastic case beneath the stainless steel post.
	Cor. is located 2 lks. E. of barbed wire fence, 4 strand, bears N. and S.
	From this cor. point, the 320 Mile Post on the Arizona-New Mexico State Bdy., bears N. 0°02' W., 9.79 chs. dist., hereinbefore described.
	From the cor. of secs. 26, 27, 34 and 35.
	N. 0°16' E., bet. secs. 26 and 27.
20.00	Point for the S 1/16 sec. cor. of secs. 26 and 27.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, on top of a rock outcrop, 12 x 6 x 1 ft. high, with top mkd.
	T12S R32E
	S 1/16
	S27 S26
	PMWA 1
	1993
	Deposit a magnet, 1 x 7/8 in. diam., beneath the brass tablet.
40.00	The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with a mound of stone to the W., 4 ft. base, 1 1/2 ft. high, with brass cap mkd. 1/4 S27 S26 1919.
	Add the marks 1993 to the brass cap.
	N. 0°04' W., beginning new measurement,
19.94	Point for the N 1/16 sec. cor. of secs. 26 and 27.

	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, on a rock face, with top mkd.
	T12S R32E N 1/16 S27 S26 1993
	Deposit a magnet, 1 in. x 7/8 in. diam., beneath the brass tablet.
	Cor. is located 200 lks. E. of the E. face of a canyon wall.
39.88	The cor. of secs. 22, 23, 26 and 27, monumented with an iron post, 2 ins. diam. firmly set, projecting 30 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. T12S R32E S22 S23 S27 S26 1919.
	Add the marks 1993 to the brass cap.
	N. 89°25' E., bet. secs. 23 and 26.
19.90	Point for the W 1/16 sec. cor. of secs. 23 and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to bedrock, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.
	T12S R32E
	W 1/16 ——
	\$26 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 white plastic case beneath the stainless steel post.
39.80	The 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 30 ins. above ground, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd. 1/4 S26 S35 1919.
	Add the marks 1993 to the brass cap.
	S. 88°53' E., beginning new measurement.

CHAINS **1.65**

The original closing cor. of secs. 23 and 26, at intersection with the Arizona-New Mexico State Bdy., monumented with an iron post, 2 ins. diam., firmly set, projecting 24 ins. above ground, in a scattered mound of stone, with brass cap mkd.T12S R32E S26 S35 CC 1919.

Add the marks 1993 to the brass cap.

From this cor. point, the 319 Mile Post on the Arizona-New Mexico State Bdy., bears N. 0°02' W., 9.65 chs. dist., hereinbefore described.

The point for the 1/4 sec. cor. of sec. 26 only, T. 12 S., R. 32 E., is at midpoint on the E. bdy. of sec. 26.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.

Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

The cor. is located 60 lks. W. of barbed wire fence, 4 strand, bears N. and S.

From this cor. point, the 320 Mile Post on the Arizona-New Mexico State Bdy., bears S. 0°02'E., 30.33 chs. dist., hereinbefore described.

The point for the N 1/16 sec. cor. of sec. 26 only, T. 12 S., R. 32 E., is at midpoint bet. the closing cor. of secs. 23 and 26 and the 1/4 sec. cor. of sec. 26 only, on the E. bdy. of sec. 26.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

CHAINS

From this cor. point, the 319 Mile Post on the Arizona-New Mexico State Bdy., bears N. 0°02'W., 29.71 chs. dist., hereinbefore described.

The point for the S 1/16 sec. cor. of sec. 26 only, T. 12 S., R. 32 E., is at midpoint bet. the 1/4 sec. cor. of sec. 26 only, and the closing cor. of secs. 26 and 35, on the E. bdy. of sec. 26.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T12S | R32E | S 1/16 | S 26 | 1993

Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

From this cor. point, the 320 Mile Post on the Arizona-New Mexico State Bdy., bears S. 0°02'E., 10.27 chs. dist., hereinbefore described.

From the cor. of secs. 22, 23, 26 and 27.

North, bet. secs. 22 and 23.

The 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd. 1/4 S22 S23 1919.

Add the marks 1993 to the brass cap.

N. 0°05' E., beginning new measurement.

itt o oo zi, zeginiing new needer energy

The cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with a mound of stone to the W., 2 ft. base, 1 ft. high, with brass cap mkd. T12S R32E S15 S14 S22 S23 1919.

Add the marks 1993 to the brass cap.

	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	S. 89°59' E., bet. secs. 14 and 23.
39.74	The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 1 in. diam., firmly set, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd. 1/4 S14 S23 1919.
	Add the marks T12S R32E 1993 to the brass cap.
	N. 87°19' E., beginning new measurement.
1.57	The original closing cor. of secs. 14 and 23, monumented with an iron post, 2 ins. diam., firmly set, projecting 13 ins. above ground, in a scattered mound of stone, with brass cap mkd. T12S R32E S14 S23 CC 1919.
	Add the marks AM to the brass cap, remove brass cap from iron post and bury in place.
1.66	Intersect the Arizona-New Mexico State Bdy.
	Point for the closing cor. of secs. 14 and 23.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 8 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.
	AZ NM T12S T22S R32E R21W CC S14 S19 S23 S19 1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located on a steep slope, facing N.
	From this cor. point, the 318 Mile Post on the Arizona-New Mexico State Bdy., bears N. 0°07' E., 8.62 chs. dist., hereinbefore described.
	From the cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. T12S R32E S10 S11 S15 S14 1920.

	1. 12 St, N. SZ Et, GIId din Gaio Nivel Included, Included
CHAINS	Add the marks 1992 to the brass cap.
	S. 89°49' E., bet. secs. 11 and 14.
38.43	Point for AP 4, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
39.98	Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the original cor.
	Set stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T12S R32E S11
	1/4
	S14
	1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	Cor. is located 41 lks. S. of wash, 18 lks. wide, 2 1/2 ft. deep, drains E., and 17 lks. N. of trail road, bears ENE and SW.
41.71	The original closing cor. of secs. 11 and 14, monumented with an iron post, 2 ins. diam., firmly set, projecting 26 ins. above ground, in a scattered mound of stone, with brass cap mkd. T12S R32E S11 S14 CC 1920 NEW MEXICO.
	Add the marks AM to the brass cap, remove brass cap from iron post and bury inverted, in place, on top of clear broken glass and 7 nails.
41.76	Intersect the Arizona-New Mexico State Bdy.
	Point for the closing cor. of secs. 11 and 14.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled with a collar of stone, 3 ft. diam., with brass cap mkd.
	AZ NM T12S T22S R32E R21W S11 S18 S14 1992

CHAINS	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	From this cor. point, the 317 Mile Post on the Arizona-New Mexico State Bdy., bears N. 0°07' E., 8.19 chs. dist., hereinbefore described.
	From the cor. of secs. 10, 11, 14 and 15.
	N. 0°03' W., bet. secs. 10 and 11.
40.28	The 1/4 sec. cor. of secs. 10 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, encircled by a collar of stone, with brass cap mkd. 1/4 S10 S11 1920.
	Add the marks 1992 to the brass cap.
	N. 0°20' E., beginning new measurement.
31.35	Point for AP 17, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
39.92	The cor. of secs. 2, 3, 10 and 11, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with a scattered mound of stone to the W., with brass cap mkd. T12S R32E S3 S2 S10 S11 1914, from which the original bearing tree
	A root hole, with a down oak, 22 ins. diam. alongside, bears N. 65° W., 183 lks. dist., with no visible markings.
	Add the marks 1992 to the brass cap.
	Rebuild mound of stone to the W., 3 ft. base, 2 ft. high.
	East, bet. secs. 2 and 11.
40.00	The 1/4 sec. cor. of secs. 2 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with a mound of stone to the N., 3 ft. base, 1 ft. high, with brass cap mkd. 1/4 S2 S11 1914.
	Add the marks 1992 to the brass cap.
	N. 89°54' E., beginning new measurement.
1.49	Intersect the Arizona-New Mexico State Bdy.

CHAINS

Point for the closing cor. of secs. 2 and 11.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T12S T22S

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Raise a mound of stone, 2 ft. base, 1/2 ft. high to the W.

From this cor. point, the original closing cor. of secs. 2 and 11, bears N. 89°54' E., 2 lks. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, encircled in a collar of stone, with a mound of stone to the W, 3 ft. base x 1 ft. high, with brass cap mkd. T12S S2 S11 CC R32E 1914.

Add the marks AM 1993 to the brass cap, invert post and bury in place.

From this same cor. point, the 316 Mile Post on the Arizona-New Mexico State Bdy., bears N. 0°04' W., 8.07 chs. dist., hereinbefore described.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.

N. 0°03' W., bet. secs. 33 and 34.

20.01

Point for the S 1/16 sec. cor. of secs. 33 and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T12S R32E S 1/16 S33 | S34 1993

Deposit a magnet in a $1 \times 1 \times 2$ in. diam. in a white plastic case beneath the stainless steel post.

	T. 12 S., R. 32 E., Gila and Sait River Meridian, Arizona
CHAINS	Cor. is located 59 lks. E. of a wash, 18 lks. wide, 6 ft. deep, drains SE.
40.02	The 1/4 sec. cor. of secs. 33 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 26 ins. above ground, in a scattered mound of stone, with brass cap mkd. 1/4 S33 S34 1919.
	Add the marks 1993 to the brass cap.
	Rebuild supporting mound of stone, 5 ft. base, to top.
	Cor. is located 7 lks. S. of the S. edge of a wash, 300 lks. wide, 8 ft. deep, drains ESE.
	N. 0°03' W., beginning new measurement.
39.98	The cor. of secs. 27, 28, 33 and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above ground, in a mound of stone, 4 ft. base, 1 ft. high, with brass cap erroneously mkd. T12S R32 S28 S27 S33 S34 1919, from which the original bearing trees
	A Utah Juniper, 40 ins. diam., bears N. 31 1/2° E., 69 lks. dist., mkd. T12S R on a partially healed blaze on a limb, 18 ins. diam.
	A Utah Juniper, 24 ins. diam., bears S. 8 1/2° E., 74 lks. dist., mkd. T12S R32E S34 BT.
	A Utah Juniper, 36 ins. diam., bears S. 40° W., 152 lks. dist., mkd. T12S R32E S33 BT.
	A Utah Juniper, 84 ins. diam. at root crown, bears N. 41 1/2° W., 98 lks. dist., mkd. T12S R32E S28 BT on a blazed limb, 20 ins. diam., facing SE.
	Add the marks E 1993 to the brass cap.
	From the cor. of secs. 26, 27, 34 and 35.
	S. 89°49' W., bet. secs. 27 and 34.
40.18	The 1/4 sec. cor. of secs. 27 and 34, monumented with an iron post, 1 in. diam., loosely set, projecting 27 ins. above ground, in a scattered mound of stone, with brass cap mkd. 1/4 S27 S34 1919.
	Add the marks 1993 to the brass cap.

CHAINS	Rebuild supporting mound of stone, 4 ft. base to top.
	N. 89°44' W., beginning new measurement.
19.97	Point for the W 1/16 sec. cor. of secs. 27 and 34.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, on top of a boulder, 4 x 2 x 1 ft. high, with top mkd.
	T12S R32E
	W 1/16 —
	S34
	1993
	Deposit a magnet, 1 x 7/8 in. diam., beneath the brass tablet.
39.94	The cor. of secs. 27, 28, 33 and 34.
	N. 0°15' W., bet. secs. 27 and 28.
20.02	Point for the S 1/16 sec. cor. of secs. 27 and 28.
	Set a stainless steel post, 2 1/2 ins. diam., 28 ins. long, 23 ins. in the ground, encircled in a collar of stone, with brass cap mkd.
	T12S R32E
	S 1/16
	S28 S27 1993
	Deposit a magnet in a 1 x 1 x 2 ins. diam., white plastic case beneath the stainless steel post.
40.04	The true point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate dist. Point falls on a steep rock face, and is impractical to monument.
41.59	The witness 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above a mound of stone, 4 ft. base, 1 1/2 ft. high, with brass cap mkd. 1/4 S28 S27 WC 1919, from which the original bearing trees
	A Utah Juniper, 48 ins. diam. at root crown, bears S. 80° E., 116 lks. dist., mkd. WC 1/4 S27 BT. (Record: N. 41° E., 176 lks. dist.)

	1. 12 5., R. 32 E., Gila and Sait Rivel Periodal, Arizona
CHAINS	A Utah Juniper, 60 ins. diam. at root crown, bears S. 41° W., 89 lks. dist., mkd. WC 1/4 S28 BT. (Record: S. 71 1/2° W., 199 lks. dist.)
	Add the marks 1993 to brass cap.
	N. 0°11' E., beginning new measurement.
38.22	The witness cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap erroneously mkd. WC T12S R32E S21 S22 S28 S27 1919 (C of WC is inverted), from which the original bearing trees
	A Utah Juniper, 36 ins. diam. at root crown diam., bears N. 7 1/4° E., 152 lks. dist., faintly mkd. WC T12S R32E S22 BT on a blazed limb, 8 ins. diam. (Record: NE, 258 lks. dist.)
	A Utah Juniper, 10 ins. diam., bears S. 75 1/2° E., 441 lks. dist., mkd. WC T12S R32E S2 on partially healed blaze, the remainder being illegible. (Record: SE, 441 lks. dist.)
	A Utah Juniper, 18 ins. diam., bears S. 43° W., 311 lks. dist., mkd. WC on almost completely healed blaze. (Record: SW, 327 lks. dist.)
	A dead Utah Juniper, 30 ins. root crown diam., bears N. 36 1/2° W., 268 lks. dist., mkd. WC T12S R32E S21 BT. (Record: NW, 258 lks. dist.)
	Add the marks 1993 to brass cap.
	N. 0°04' E., beginning new measurement.
0.17	The true point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist. Point falls on a rock ledge, and is impractical to monument.
	From the cor. of secs. 22, 23, 26 and 27.
	N. 89°53' W., bet. secs. 22 and 27.
40.09	The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd. 1/4 S22 S27 1919.

	T. 12 S., R. 32 E., Gild and Sait River Meridian, Arizona
CHAINS	Add the marks 1993 to the brass cap.
	N. 89°53' W., beginning new measurement.
8.20	Point for AP 143, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
9.05	Point for AP 127 on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
40.23	The true point for secs. 21, 22, 27 and 28.
	N. 0°04' E., bet. secs. 21 and 22.
40.13	The 1/4 sec. cor. of secs. 21 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, encircled in a collar of stone, with brass cap mkd. 1/4 S21 S22 1919, from which the original bearing trees
	A Utah Juniper, 5 ft. diam. at root crown, bears N. 39 1/4° E., 178 lks. dist., with healed blaze on limb, 10 in. diam. (Record: N. 42° E., 189 lks. dist.)
	A Utah Juniper, 12 in. diam., bears S. 52° W., 48 lks. dist., mkd. S21 BT on partially healed blaze. (Record: S. 38° W., 43 lks. dist.)
	Add the marks 1993 to the brass cap.
	N. 0°08' E., beginning new measurement.
40.05	The cor. of secs. 15, 16, 21 and 22, monumented with an iron post, 2 ins. diam, firmly set, projecting 6 ins. above a mound of stone, 3 ft. base, 3 ft. high, with brass cap erroneously mkd. WC T12S R32E S16 S15 S21 S22 1919.
	Add the marks 1993 to the brass cap.
	From the cor. of secs. 14, 15, 22 and 23.
	S. 89°52' W., bet. secs. 15 and 22.
40.27	The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above mound of stone, 3 ft. base 3 ft. high, with brass cap mkd. 1/4 S15 S22 1920.

	T. 12 S., R. 32 E., Gild allu Sait River Ferruran, Arizona
CHAINS	Add the marks 1993 to the brass cap.
	N. 89°29' W., beginning new measurement.
39.98	The cor. of secs. 15, 16, 21 and 22.
	From the cor. of secs. 10, 11, 14 and 15.
	S. 89°40' W., bet. secs. 10 and 15.
40.15	The 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. 1/4 S10 S15 1920, from which the original bearing trees
	A forked Utah Juniper, 36 ins. diam., bears N. 84 1/2° E., 207 lks. dist., mkd. 4 S10 BT on partially healed blaze on limb, 14 ins. diam.
	A forked Utah Juniper, 18 ins. diam., bears S. 40 1/4° W., 81 lks. dist., mkd. 4 S15 BT on partially healed blaze. (Record: S. 39° W., 80 lks. dist.)
	Add the marks 1992 to the brass cap.
	N. 89°57' W., beginning new measurement.
39.75	The cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with a mound of stone to the W., 2 ft. base, 1 1/2 ft. high, with brass cap mkd. T12S R32E S9 S10 S16 S15 1919, from which the original bearing trees
	A root hole, with a down oak, 9 ins. diam., alongside, bears N. 71 1/4° E., 30 lks. dist., with healed blaze.
	A root hole, with a down oak, 13 ins. diam., alongside, bears S. 87° E., 26 lks. dist., mkd. 12S on partially healed blaze.
	from which
	A rock outcrop, 130 ft. wide x 20 ft. high, bears S. 80 1/2° E., 26 lks. dist., with X BO chiseled on the NW face.
1	

	1. 12 5., R. 52 E., Gila alia sait rivel Periodali, Alizona
CHAINS	Add the marks 1992 to the brass cap.
	N. 0°02' E., bet. secs. 9 and 10.
40.12	The 1/4 sec. cor. of secs. 9 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 31 ins. above ground, in a scattered mound of stone, with brass cap mkd. 1/4 S9 S10 1920.
	Add the marks 1992 to the brass cap.
	Rebuild the mound of stone, 3 ft. base, to top.
	N. 0°04' E., beginning a new measurement.
40.23	The cor. of secs. 3, 4, 9 and 10, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above ground, with scattered mound of stone to the W., with brass cap mkd. S4 S3 S9 S10 1914.
	from which
	A sandstone boulder, 10 x 6 x 3 ft. high, bears N. 23° E., 2.50 chs. dist., mkd. X BO on the SW face,
	A sandstone outcrop, 80 x 80 x 20 ft. high, bears N. 24 1/2° W., 3.69 chs. dist., mkd. X BO on the S. face.
	Add the marks 1992 to the brass cap.
	Rebuild mound of stone to the W., 3 ft. base, 2 ft. high.
	From the cor. of secs. 2, 3, 10 and 11.
į	S. 89°58' W., bet. secs. 3 and 10.
40.01	The 1/4 sec. cor. of secs. 3 and 10, monumented with an iron post, 1 in. diam, firmly set, projecting 17 ins. above ground, encircled in a collar of stone, with a mound of stone to the N., 3 ft. base, 2 ft. high, with brass cap mkd. S3 1/4 S10 1914.
	Add the marks 1992 to the brass cap.
	West, beginning a new measurement.

CHAINS 40.00	The cor. of secs. 3, 4, 9 and 10.
	From the true point for the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°06' W., bet. secs. 32 and 33.
40.10	The 1/4 sec. cor. of secs. 32 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, encircled in a collar of stone, with brass cap mkd. 1/4 S32 S33 1919, from which the original bearing trees
	A Utah Juniper, 10 ins. diam, bears N. 63° E., 125 lks. dist., mkd. 1/4 on partially healed blaze on SW face.
	A Utah Juniper, 48 ins. diam. at root crown, bears N. 36 1/2° W., 16 lks. dist., mkd. 1/4 S32 BT on blaze on limb, 10 ins. diam. (Record: N. 42° W., 12 lks. dist.)
!	Add the marks T12S R32E 1993 to the brass cap.
	N. 0°01' W., beginning new measurement.
40.06	The cor. of secs. 28, 29, 32 and 33, determined from the remaining original bearing trees
	A Utah Juniper, 19 ins. diam., bears N. 13° E., 45 lks. dist., mkd. T12S R32E S28 BT. (Record: N. 16°E.)
	A Utah Juniper, 18 ins. diam., bears S. 8 1/2° E., 115 lks. dist., mkd. T12S R32E S33 BT. (Record: S. 9 1/2°E., 113 lks. dist.)
	A Utah Juniper, 25 ins. diam., bears S. 36 1/2° W., 43 lks. dist., mkd. T12S R32E S32 BT. (Record: S. 35° W.)
	A Utah Juniper, 18 ins. diam., bears N. 60° W., 87 lks. dist., mkd. T12S R32E S29 BT. (Record: N. 59° W., 82 lks. dist.)
	At the cor. point
	Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, cemented in place, encircled in a collar of stone, 36 ins. diam., with aluminum cap mkd.

CHAINS	T12S R32E S29 S28
	S32 S33 1993
	Cor. is located on a steep, NW facing slope.
	From the cor. of secs. 27, 28, 33 and 34.
	N. 89 51' W., bet. secs. 28 and 33.
39.94	The 1/4 sec. cor. of secs. 28 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 20 ins. above ground, with brass cap mkd. 1/4 S28 S33 1919, from which the original bearing trees
	A Utah Juniper, 11 ins. diam., bears N. 57 3/4° E., 64 lks. dist., faintly mkd. 1/4 S28 BT. (Record: N. 57° E., 66 lks. dist.)
	A Utah Juniper, 10 ins. diam., bears S. 44 1/2° W., 210 lks. dist., faintly mkd. 1/4 S33 BT. (Record: S. 44° W., 206 lks. dist.)
	Add the marks 1993 to the brass cap.
	Raise a mound of stone, 4 ft. base to top.
	N. 89°59' W., beginning new measurement.
39.87	The cor. of secs. 28, 29, 32 and 33.
	N. 0°05' E., bet. secs. 28 and 29.
39.80	The 1/4 sec. cor. of secs. 28 and 29, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above a supporting mound of stone, 3 1/2 ft. base x 2 ft. high, with brass cap erroneously mkd. S29 S30 1919, from which the original bearing trees
	A Utah Juniper, 18 ins. diam., bears S. 2 1/2° E., 334 lks. dist., mkd. 1/4 S28 BT. (Record: 329 lks. dist.)
	A Utah Juniper limb, 8 ins. diam., bears S. 69 1/2° W., 188 lks. dist., mkd. 1/4 S29 BT.
	Add the marks 1/4 1992 to the brass cap.

	1. 12 5., R. 52 E., GIId aim Bait Rivel Pelitilan, Alizona
CHAINS	N. 0°05' W., beginning new measurement.
19.95	True point for the N 1/16 sec. cor. of secs. 28 and 29. Point falls on a steep rock slope, facing W., and is impractical to monument.
	From this point, the point selected for a witness cor., bears S. 79°21' W., 0.84 chs. dist.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd. T12S R32E WC N1/16 S29 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	from which
	A boulder, 11 x 12 x 9 ft. high, bears N. 78 1/2° E., 43 lks. dist., with X BO chiseled on the SW face.
39.90	The cor. of secs. 20, 21, 28 and 29, monumented with an iron post, 2 ins. diam, firmly set, projecting 8 ins. above a scattered mound of stone, 3 ft. diam., 2 ft. high, with a mound of stone to the W., 3 ft. diam., 3 ft. high, with brass cap mkd. T12S R32E S20 S21 S29 S28 1919, from which the original bearing trees
	A Utah Juniper, 25 ins. diam., bears S. 30 3/4° E., 256 lks. dist., with healed blaze.
	A Utah Juniper, 20 ins. diam., bears S. 6 1/4° W., 422 lks. dist., faintly mkd. T R32E BT.
	Add the marks 1992 to the brass cap.
	N. 0°03' E., bet. secs. 20 and 21.
40.10	The 1/4 sec. cor. of secs. 20 and 21, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, in a scattered mound of stone, with brass cap mkd. 1/4 S20 S21 1919, from which the original bearing trees
	A Utah Juniper, 18 ins. diam., bears S. 50° E., 34 lks. dist., mkd. 1/4 S21 BT.
	A Utah Juniper, 48 ins. diam. at root crown, bears S. 10° W., 49 lks. dist., mkd. 1/4 S20 BT on limb, 12 ins. diam. (Record: 47 lks. dist.)
1	L

Add the marks 1993 to the brass cap.

CHAINS	Cor. is located on a steep, N. facing slope.
	From the cor. of secs. 3, 4, 9 and 10.
	West, bet. secs. 4 and 9.
40.02	The 1/4 sec. cor. of secs. 4 and 9, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, encircled in collar of stone, with brass cap mkd. S4 1/4 S9 1914, from which the remaining original bearing tree
	A Utah Juniper, 20 ins. diam., bears S. 56 1/4° E., 107 lks. dist., mkd. S9 BT.
	Add the marks 1992 to the brass cap.
	From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.
	North, bet. secs. 31 and 32.
20.03	Point for the S 1/16 sec. cor. of secs. 31 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12S R32E
	PMWA S 1/16
	S31 S32
	1992
	Deposit a magnet in a $1 \times 1 \times 2$ 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located on a rocky ledge, 10 ft. below a rock rim which bears N and S, ledge measures 23 x 8 ft., and approximately 30 ft. above the desert floor.
40.06	The 1/4 sec. cor. of secs. 31 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 30 ins. above ground, in a supporting mound of stone, 4 ft. base, 2 1/2 ft. high, with a mound of stone to the N., 3 ft. base x 3 ft. high, with brass cap mkd. 1/4 S31 S32 1914.
	from which
	A boulder, 4 x 4 x 4 ft. high, bears N. 40 1/4° E., 6 lks. dist., mkd X BO on the SW face.

CHAINS	T
	A boulder, 12 x 11 x 8 ft. high, bears N. 89 3/4° W., 15 lks. dist., mkd. X BO on the SE face.
	Add the marks 1992 to the brass cap.
	From the cor. of secs. 28, 29, 32 and 33.
	S. 89°59' W., bet. secs. 29 and 32.
40.05	The 1/4 sec. cor. of secs. 29 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. 1/4 S29 S32 1919, from which the original bearing tree
	A Utah Juniper, 13 ins. diam., bears N. 52 1/2° E., 163 lks. dist., mkd. 1/4 S29 BT.
	Add the marks 1992 to the brass cap.
	N. 89°59' W., beginning new measurement.
39.93	The cor. of secs. 29, 30, 31 and 32, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above ground, with a mound of stone to the W., 4 ft. base, 4 ft. high, with brass cap mkd. T12S R32E S30 S29 S31 S32 1914, from which the original bearing tree
	A cedar, 15 ins. diam., bears S. 72 1/2° E., 137 lks. dist., faintly mkd. S32 BT.
	from which
	A boulder, 5 x 4 1/2 x 3 ft. high, bears S. 14 1/4° W., 35 lks.dist., mkd. X BO on the NE face.
	Add the marks 1992 to the brass cap.
:	S. 89°54' W., bet. secs. 30 and 31.
20.02	Point for the E 1/16 sec. cor. of secs. 30 and 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.
	T12S R32E S30
	E 1/16 —
	S31 1992

The 1/4 sec. cor. of secs. 30 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above a supporting mound of stone, 3 ft. base, 2 1/2 ft. high, with brass cap mkd. S30 1/4 S31 1914. Add the marks 1992 to the brass cap. S. 89°51' W., beginning new measurement. The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. T12S R31E R32E S25 S30 S36 S31 1914 1992 as described in the field notes of the dependent resurvey of the E. bdy. of T. 12 S., R. 31 E., executed concurrently under this same group. From the cor. of secs. 29, 30, 31 and 32. North, bet. secs. 29 and 30. The witness cor. to the 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground in a scattered mound of stone, with a scattered mound of stone to the W., with brass cap mkd. 1/4 S30 WC S29 1914.
S. 89°51' W., beginning new measurement. The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. T12S R31E R32E S25 S30 S36 S31 1914 1992 as described in the field notes of the dependent resurvey of the E. bdy. of T. 12 S., R. 31 E., executed concurrently under this same group. From the cor. of secs. 29, 30, 31 and 32. North, bet. secs. 29 and 30. The witness cor. to the 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground in a scattered mound of stone, with a scattered mound of stone to the W., with brass cap mkd. 1/4 S30 WC S29 1914.
The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. T12S R31E R32E S25 S30 S36 S31 1914 1992 as described in the field notes of the dependent resurvey of the E. bdy. of T. 12 S., R. 31 E., executed concurrently under this same group. From the cor. of secs. 29, 30, 31 and 32. North, bet. secs. 29 and 30. The witness cor. to the 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground in a scattered mound of stone, with a scattered mound of stone to the W., with brass cap mkd. 1/4 S30 WC S29 1914.
monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. T12S R31E R32E S25 S30 S36 S31 1914 1992 as described in the field notes of the dependent resurvey of the E. bdy. of T. 12 S., R. 31 E., executed concurrently under this same group. From the cor. of secs. 29, 30, 31 and 32. North, bet. secs. 29 and 30. The witness cor. to the 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground in a scattered mound of stone, with a scattered mound of stone to the W., with brass cap mkd. 1/4 S30 WC S29 1914.
North, bet. secs. 29 and 30. The witness cor. to the 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground in a scattered mound of stone, with a scattered mound of stone to the W., with brass cap mkd. 1/4 S30 WC S29 1914.
The witness cor. to the 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground in a scattered mound of stone, with a scattered mound of stone to the W., with brass cap mkd. 1/4 S30 WC S29 1914.
monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground in a scattered mound of stone, with a scattered mound of stone to the W., with brass cap mkd. 1/4 S30 WC S29 1914.
from which
A boulder, 11 x 11 x 7 ft. high, bears N. 86 3/4° E., 151 lks. dist, mkd. X BO.
A boulder, 15 x 6 x 3 ft. high, bears S. 0 1/4° W., 32 lks. dist., mkd. X BO.
Add the marks 1992 to the brass cap.
N. 0°05' W., beginning new measurement.
1.00 The true point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate dist. Point falls in a wash, and is impractical to monument.
5.83 Point for AP 68, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
20.98 Point for the N 1/16 sec. cor. of secs. 29 and 30.

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T12S R32E N 1/16 PMWA S30 | S29 1992

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

40.96

The cor. of secs. 19, 20, 29 and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with scattered mound of stone to the W., with brass cap mkd. T12S R32E S19 S20 S30 S29 1914, from which the original bearing tree

A Utah Juniper, 11 ins. diam., bears S. 36° W., 61 lks. dist., mkd. T12S R32E S30 BT. (Record: S. 37° W.)

Add the marks 1992 to the brass cap.

Rebuild mound of stone to the W., 3 ft. base x 2 ft. high.

From the cor. of secs. 20, 21, 28 and 29.

N. 89°56' W., bet. secs. 20 and 29.

20.07

Point for the E 1/16 sec. cor. of secs. 20 and 29.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd..

T12S R32E S20 E 1/16 —— S29 1992

Deposit a magnet in a $1 \times 1 \times 2$ 5/8 ins. white plastic case beneath the stainless steel post.

Cor. is located 122 lks. E. of wash, 30 lks. wide, 8 ft. deep, drains S.

40.14

The 1/4 sec. cor. of secs. 20 and 29, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd. 1/4 S20 S29 1919.

CHAINS	Add the marks 1992 to the brass cap.
	N. 89°46' W., beginning new measurement.
39.86	The cor. of secs. 19, 20, 29 and 30.
	S. 89°48' W., bet. secs. 19 and 30.
40.11	The 1/4 sec. cor. of secs. 19 and 30, determined at record bearing and distance from the remnants of the remaining original bearing tree
:	A catclaw stump, 14 ins. diam, bears N. 11° W., 152 lks. dist., mkd. 1/4 S19 BT.
ļ	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a steel fence post, 5 ft. long, projecting 16 ins. above ground, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.
	T12S R32E S19
	1/4 —— S30
	1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	from which
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 14 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, for a reference monument, bears N. 88 3/4° E., 42.8 ft. dist., with brass cap mkd. RM T12S R32E 42.8 FT TO COR S19 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 23 ins. in the ground, for a reference monument, bears S. 8 3/4° W., 17.9 ft. dist., with brass cap mkd. RM T12S R32E 17.9 FT TO COR S30 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	S. 89°44' W., beginning new measurement.

	1. 12 5., R. 32 5., Gild alm batt River Periodal, Altzon
19.92	Point for the W 1/16 sec. cor. of secs. 19 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled in a collar of stone, with brass cap mkd.
	T12S R32E
	S19 W 1/16 ——
	S30
	1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
39.84	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 4 ft. base, to top, with a mound of stone, to the W., 2 ft. base, 2 ft. high, with brass cap mkd. T12S R31E R32E S24 S19 S25 S30 1914 1992, as described in the field notes of the dependent resurvey of the E. bdy. of T. 12 S., R. 31 E., executed concurrently under this same group.
	From the cor. of secs. 19, 20, 29 and 30.
	North, bet. secs. 19 and 20.
10.67	Point for AP 63, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
11.58	Point for AP 38, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
20.01	Point for the S 1/16 sec. cor. of secs. 19 and 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T12S R32E PMWA S 1/16 S19 S20 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

CITATIO	1. 12 S., R. SZ E., GIIA AIM SAIT RIVEL PERIODAI, AITZONA
40.02	The 1/4 sec. cor. of secs. 19 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, in a scattered mound of stone, with a scattered mound of stone to the W., with brass cap mkd. 1/4 S19 S20 1914.
	Rebuild the mound of stone 3 ft. base, 1 1/2 ft. high.
	Rebuild mound of stone to W., 3 ft. base, 2 ft. high.
	Add the marks 1992 to the brass cap.
	N. 0°04' W., beginning new measurement.
39.85	The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 ins. diam, firmly set, projecting 13 ins. above ground, in a scattered mound of stone, with a scattered mound of stone to the W., with brass cap mkd. T12S R32E S18 S17 S19 S20 1914.
	Rebuild mound of stone, 2 ft. base, to top.
	Rebuild mound of stone to W., 2 ft. base, 1 ft. high.
	Add the marks 1992 to the brass cap.
	S. 89°51' W., bet. secs. 18 and 19.
39.94	The 1/4 sec. cor. of secs. 18 and 19, monumented with an iron
	post, 1 in. diam., firmly set, projecting 4 ins. above a supporting mound of stone, 4 ft. base, 2 ft. high, with a mound of stone to the W., 4 ft. base, 3 ft. high, with brass cap mkd. S18 1/4 S19 1914.
	supporting mound of stone, 4 ft. base, 2 ft. high, with a mound of stone to the W., 4 ft. base, 3 ft. high, with brass cap mkd.
	supporting mound of stone, 4 ft. base, 2 ft. high, with a mound of stone to the W., 4 ft. base, 3 ft. high, with brass cap mkd. S18 1/4 S19 1914.
19.99	supporting mound of stone, 4 ft. base, 2 ft. high, with a mound of stone to the W., 4 ft. base, 3 ft. high, with brass cap mkd. S18 1/4 S19 1914. Add the marks 1992 to the brass cap.
19.99	supporting mound of stone, 4 ft. base, 2 ft. high, with a mound of stone to the W., 4 ft. base, 3 ft. high, with brass cap mkd. S18 1/4 S19 1914. Add the marks 1992 to the brass cap. S. 89°46' W., beginning new measurement.
19.99	supporting mound of stone, 4 ft. base, 2 ft. high, with a mound of stone to the W., 4 ft. base, 3 ft. high, with brass cap mkd. S18 1/4 S19 1914. Add the marks 1992 to the brass cap. S. 89°46' W., beginning new measurement. Point for the W 1/16 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a supporting mound of stone, 3 ft.
19.99	supporting mound of stone, 4 ft. base, 2 ft. high, with a mound of stone to the W., 4 ft. base, 3 ft. high, with brass cap mkd. S18 1/4 S19 1914. Add the marks 1992 to the brass cap. S. 89°46' W., beginning new measurement. Point for the W 1/16 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a supporting mound of stone, 3 ft.
19.99	supporting mound of stone, 4 ft. base, 2 ft. high, with a mound of stone to the W., 4 ft. base, 3 ft. high, with brass cap mkd. S18 1/4 S19 1914. Add the marks 1992 to the brass cap. S. 89°46' W., beginning new measurement. Point for the W 1/16 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a supporting mound of stone, 3 ft.

	1. 12 S., R. 32 E., Gila and Sait River Periodan, Arizona
CHAINS	T12S R32E PMWA S18 W 1/16 — S19 1992 Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
39.98	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 22 ins. above ground, in a mound of stone, 3 ft. base, to top, with a mound of stone to the W., 3 ft. base, 2 ft. high, with brass cap mkd. T12S R31E R32E S13 S18 S24 S19 1914 1992, as described in the field notes of the dependent resurvey of the E. bdy. of T. 12 S., R. 31 E., executed concurrently under this same group.
	From the 1/4 sec. cor. of secs. 17 and 18, monumented with an iron post, 1 in. diam, firmly set, projecting 22 ins. above ground, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd. 1/4 S18 S17 1914.
	Add the marks 1992 to the brass cap.
	Cor. is located on a rocky, N. facing ridge, overlooking Indian Springs.
	N. 0°02' W., bet. secs. 17 and 18.
40.06	The cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above a supporting mound of stone, 3 ft. base, 2 ft. high, with a mound of stone to the W., 3 ft. base, 1 ft. high, with brass cap mkd. T12S R32E S7 S8 S18 S17 1914.
	Add the marks 1992 to the brass cap.
	Rebuild supporting mound of stone, 4 ft. base to top.
	S. 89°43' W., bet. secs. 7 and 18.
39.97	The 1/4 sec. cor. of secs. 7 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. S7 1/4 S18 1914.
	Add the marks 1992 to the brass cap.

	1. 12 5., R. 52 E., Gila and Sait River Periodal, Arizona
CHAINS	S. 89°44' W., beginning new measurement.
39.94	The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 28 ins. above ground, in a mound of stone, 4 ft. base, to top, with a mound of stone to the W., 4 ft. base, 2 ft. high, with brass cap mkd. T12S R31E R32E S12 S7 S13 S18 1914 1992, as described in the field notes of the dependent resurvey of the E. bdy. of T. 12 S., R.31 E., executed concurrently under this same group.
	From the cor. of secs. 7, 8, 17 and 18.
	North, bet. secs. 7 and 8.
40.06	The 1/4 sec. cor. of secs. 7 and 8, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. 1/4 S7 S8 1914.
	Add the marks 1992 to the brass cap.
	N. 0°01' E., beginning new measurement.
39.91	The cor. of secs. 5, 6, 7 and 8, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above a supporting mound of stone, 5 ft. base, 2 ft. high, with brass cap mkd. T12S R32E S6 S5 S7 S8 1914.
	Add the marks 1992 to the brass cap.
	S. 89°48' W., bet. secs. 6 and 7.
39.77	The 1/4 sec. cor. of secs. 6 and 7, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above a mound of stone, 4 ft. base, 1 ft. high, with brass cap mkd. S6 1/4 S7 1914.
	Add the marks 1992 to the brass cap.
	S. 89°47' W., beginning new measurement.
20.07	Point for the W 1/16 sec. cor. of secs. 6 and 7.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	T12S R32E PMWA S6 W 1/16 — S7 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
40.14	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 3 ft. base, to top, with a mound of stone to the W., 2 ft. base, 1/2 ft. high, with brass cap mkd. T12S R31E R32E S1 S6 S12 S7 1914 1992, as described in the field notes of the dependent resurvey of the E. bdy. of T. 12 S., R. 31 E., executed concurrently under this same group.
	Subdivision of Section 4 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
i.	From the 1/4 sec. cor. of secs. 4 and 9.
	North, on the N and S centerline of sec. 4.
35.78	Point selected for a witness point on the N and S centerline of sec. 4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled in a collar of stone, 2 ft. diam. with brass cap mkd.
	WP T12S R32E
	C PMWA S 4
	t 1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
79.71	The 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. 1/4 S33 S4 1914 1992, as described in the field notes of the subdivision of sec. 33, T. 11 S., R. 32 E., executed concurrently under this same group.

Subdivision of Section 7 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	From the 1/4 sec. cor. of secs. 7 and 18.
	N. 0°09' E., on the N and S centerline of sec. 7.
40.07	Point for the center 1/4 sec. cor. of sec. 7, at intersection with the E and W centerline of section 7.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.
	T12S R32E PMWA C1/4 S 7 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.03	The 1/4 sec. cor. of secs. 6 and 7.
	From the 1/4 sec. cor. of secs. 7 and 8.
	S. 89°44' W., on the E and W centerline of sec. 7.
39.86	The center 1/4 sec. cor. of sec. 7.
54.20	Point for AP 32, Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
59.88	Point for the center W 1/16 sec. cor. of sec. 7.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled in a collar of stone, with brass cap mkd.
	T12S R32E
	W 1/16
	C — C S 7
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
79.90	The 1/4 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, encircled with a collar of stone, with brass cap mkd. 1/4 S12 S7 1914 1992, as described in the field notes of the dependent resurvey of the E. bdy. of T. 12 S., R. 31 E., executed concurrently under this same group.

Subdivision of Section 7 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHADIS	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	NW 1/4
	From the center W 1/16 sec. cor. of sec. 7.
	N. 0°05' E., on the N and S centerline of the NW 1/4 of sec. 7.
12.21	Point for AP 29, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
39.98	The W 1/16 sec. cor. of secs. 6 and 7.
	Subdivision of Section 18 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. for secs. 18 and 19.
	N. 0°03' W., on the N and S centerline of sec. 18.
40.00	True point for the center 1/4 sec. cor. of sec. 18 at intersection with the E and W center line of section 18. Point falls on the edge of a rock outcrop, and is impractical to monument.
	From this point, the point selected for a witness cor., bears N. 88°47' E., 0.86 chs. dist.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd. T12S R32E C1/4 S18 WC PMWA 1992, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.02	The 1/4 sec. cor. of secs. 7 and 18.
	From the 1/4 sec. cor. of secs. 17 and 18.
	S. 89°47' W., on the E and W centerline of sec. 18.
39.97	The true point for the center 1/4 sec. cor. of sec. 18.
59.95	Point for the center W 1/16 sec. cor. of sec. 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled in a collar of stone, with brass cap mkd.

BOOK 5407

Subdivision of Section 18 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

T12S R32E W 1/16 C ————————————————————————————————————
Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
The 1/4 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. in the ground, in a mound of stone, 2 ft. base, to top, with a mound of stone to the W., 3 ft. base, 2 ft. high, with brass cap mkd. 1/4 S13 S18 1914 1992, as described in the field notes of the dependent resurvey of the E. bdy. of T. 12 S., R. 31 E., executed concurrently under this same group.
SW 1/4
From the W 1/16 sec. cor. of secs. 18 and 19.
N. 0°02' W., on the N and S centerline of the SW 1/4 of sec. 18.
The center W 1/16 sec. cor. of sec. 18.
Subdivision of Section 19 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
From the 1/4 sec. cor. of secs. 19 and 30.
N. 0°05' E., on the N and S centerline of sec. 19.
Point for the center S 1/16 sec. cor. of sec. 19.
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
T12S R32E PMWA C
S 1/16 S19
1992
Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.

Subdivision of Section 19 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

	1. 12 be, N. 32 be, Gild and ball hivel heliular, hillion
CHAINS 39.96	Point for the center 1/4 sec. cor. of sec. 19, at intersection with the E and W center line of sec. 19.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.
	T12S R32E C1/4 S19 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located on S. bank of wash, 15 lks. wide, 3 ft. deep, drains NW.
79.91	The 1/4 sec. cor. of secs. 18 and 19.
	From the 1/4 sec. cor. of secs. 19 and 20.
	S. 89°42' W., on the E and W centerline of sec. 19.
40.04	The center 1/4 sec. cor. of sec. 19.
60.00	Point for the center W 1/16 sec. cor. of sec. 19.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12S R32E
	W 1/16 C C
	S19 1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
79.96	The 1/4 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 23 ins. above ground, in a mound of stone, 3 ft. base, to top, with a mound of stone to the W., 3 ft. base, 2 ft. high, with brass cap mkd. 1/4 S24 S19 1919 1924, as described in the field notes of the dependent resurvey of the E. bdy. of T. 12 S., R. 32 E., executed concurrently under this same group.
	SE 1/4

Subdivision of Section 19 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

	1. 12 5., R. 52 E., Glid and balt River reliable, introdu
CHAINS	From the S 1/16 sec. cor. of secs. 19 and 20.
	S. 89°44' W., on the E and W centerline of the SE 1/4 of sec. 19.
40.07	The center S 1/16 sec. cor. of sec. 19.
	SW 1/4
	From the W 1/16 sec. cor. of secs. 19 and 30.
	N. 0°01' E., on the N and S centerline of the SW 1/4 of sec. 19.
5.91	Point for AP 37, on the Peloncillo Mountain Wilderness Area Bdy., hereinafter described.
19.97	Point for the SW 1/16 sec. cor. of sec. 19, at intersection with the E and W center line of the SW 1/4 of sec. 19.
	Set a brass tablet, 3 1/4 in. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, on a rock ledge, with top mkd.
	T12S R32E PMWA SW1/16 S19 1992
	Deposit a magnet, 1 x 7/8 in. diam., beneath the brass tablet.
39.94	The center W 1/16 sec. cor. of sec. 19.
	From the center S 1/16 sec. cor. of sec. 19.
	S. 89°43' W., on the E and W centerline of the SW 1/4 of sec. 19.
19.94	The SW 1/16 sec. cor. of sec. 19.
39.88	The S 1/16 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam, firmly set, projecting 8 ins. above ground, encircled with a collar of stone, with brass cap mkd. T12S R31E R32E S 1/16 PMWA S24 S19 1992, as described in the field notes of the dependent resurvey of the E. bdy. of T. 12 S., R.31 E., executed concurrently under this same group.

Subdivision of Section 26 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

	T. 12 S., R. 32 E., Gila and Sait River Meridian, Arizona
CHAINS	From the 1/4 sec. cor. of secs. 26 and 27.
	N. 89°49' E., on the E and W centerline of sec. 26.
19.91	Point for the center W 1/16 sec. cor. of sec. 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12S R32E
	PMWA W 1/16
	C ——— C
	S26
	1993
	Deposit a magnet in a 1 \times 1 \times 2 ins. white plastic case beneath the stainless steel post.
41.41	The 1/4 sec. cor. of sec. 26 only, on the E. bdy. of the Tp.
	SW 1/4
	From the W 1/16 sec. cor. of secs. 26 and 35.
	N. 0°08' E., on the N and S centerline of the SW 1/4 of sec. 26.
20.02	Point for the SW 1/16 sec. cor. of sec. 26, at intersection with the E and W center line of the SW 1/4 of sec. 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.
	T12S R32E
	SW1/16 S26
	PMMA
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
40.05	The center W 1/16 sec. cor. of sec. 26.
	From the S 1/16 sec. cor. of secs. 26 and 27.
	N. 89°54' E., on the E and W centerline of the SW 1/4 of sec. 26.
19.96	The SW 1/16 sec. cor. of sec. 26

Subdivision of Section 26 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS 41.51	The S 1/16 sec. cor. of sec. 26 only, on the E. bdy. of the Tp.
	NW 1/4
	From the center W 1/16 sec. cor. of sec. 26.
	N. 0°05' W., on the N and S centerline of the NW 1/4 of sec. 26.
20.01	True point for the NW 1/16 sec. cor. of sec. 26, at intersection with the E and W center line of the NW 1/4 of sec. 26. Point falls on the south face of a sheer rock slope, and is impractical to monument.
	From this point, the point selected for a witness cor., bears S. 45°00' E., 5.00 chs. dist.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd. WC T12S R32E PMWA NW1/16 S26 1993 and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
40.02	The W 1/16 sec. cor. of secs. 23 and 26.
	From the N 1/16 sec. cor. of secs. 26 and 27.
	N. 89°40' E., on the E and W centerline of the NW 1/4 of sec. 26.
19.90	The true point for the NW 1/16 sec. cor. of sec. 26.
41.42	The N 1/16 sec. cor. for sec. 26 only, on the E. bdy. of the Tp.
	Subdivision of Section 27 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 27 and 34.
	N. 0°09' E., on the N and S centerline of sec. 27.
20.09	Point for the center S 1/16 sec. cor. of sec. 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. in the ground, to bedrock, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.

Subdivision of Section 27 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	T12S R32E PMWA C S 1/16 S27 C PMWA 1993 Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath
40.18	Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E and W center line of sec. 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to bedrock, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.
	T12S R32E PMWA C1/4 S27 1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 182 lks. N. of wash, 36 lks. wide, 1 ft. deep, drains E.
66.77	Point for AP 122, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
68.44	Point for AP 148, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
80.10	The 1/4 sec. cor. of secs. 22 and 27.
	From the 1/4 sec. cor. of secs. 26 and 27. N. 89°56' W., on the E and W centerline of sec. 27.
22.76	Point for AP 156, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
23.60	Point for AP 116, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
40.25	The center 1/4 sec. cor. of sec. 27.
60.37	Point for the center W 1/16 sec. cor of sec. 27.

Subdivision of Section 27 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, with a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.
	T12S R32E
	W 1/16
	C ——— C S27
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 18 lks. N. of wash, 15 lks. wide, 2 ft. deep, drains E.
80.49	The true point for the 1/4 sec. cor. of secs. 27 and 28.
	SE 1/4
	From the S 1/16 sec. cor. of secs. 26 and 27.
	S. 89°57' W., on the E and W centerline of the SE 1/4 of sec. 27.
1.38	Point for AP 112, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
12.71	Point for AP 115, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
40.22	The center S 1/16 sec. cor. of sec. 27.
	SW 1/4
	From the W 1/16 sec. cor. of secs. 27 and 34.
	N. 0°03' W., on the N and S centerline of the SW 1/4 of sec. 27.
20.05	Point for the SW 1/16 sec. cor. of sec. 27, at intersection with the E and W center line of the SW 1/4 of sec. 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Subdivision of Section 27 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS	T12S R32E
	SW1/16 S27
	PMWA
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
40.10	The center W 1/16 sec. cor. of sec. 27.
	From the center S 1/16 of sec. 27.
	N. 89°50' W., on the E and W centerline of the SW 1/4 of sec. 27.
20.05	The SW 1/16 sec. cor. of sec. 27.
40.10	The S 1/16 sec. cor. of secs. 27 and 28.
	Subdivision of Section 29 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 29 and 32.
	N. 0°05' W., on the N and S centerline of sec. 29.
39.91	True point for the center 1/4 of sec. 29, at intersection with the E and W center line of sec. 29. Point falls on the edge of a boulder, and is impractical to monument.
	From this point, the point selected for a witness cor., bears S. 54°19' E., 0.43 chs. dist.
	Set a brass tablet, 3 1/4 ins. diam, 3 1/2 ins. stem, in a drill hole, cemented in place, on a rock ledge, with top mkd. T12S R32E WC C1/4 S29 PMWA 1992, and an arrow pointing to the corner. Deposit a magnet, 1 in. x 7/8 in. diam., beneath the brass tablet.
59.85	The center N 1/16 sec. cor. of sec. 29.
	Set a brass tablet, 3 $1/4$ ins. diam., 3 $1/2$ ins. stem, in a drill hole, cemented in place, on a boulder, 2 x 2 $1/2$ x $1/2$ ft. high, with top mkd.

Subdivision of Section 29 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHADIC	1. 12 5., R. 52 E., Gila ala bait Rivel Perialan, Introduc
CHAINS	T12S R32E PMWA C N 1/16 S29 C 1992 Deposit a magnet, 1 x 7/8 in. diam., beneath the brass tablet. from which A boulder, 6 1/2 x 3 x 4 1/2 ft. high, bears S. 61 1/4° E.,
79.79	21 lks. dist, with X BO chiseled on the NW face. Cor. is located in the center of a boulder strewn wash, 35 lks. wide, 8 ft, deep, drains WNW. The 1/4 sec. cor. of secs. 20 and 29.
	From the 1/4 sec. cor. of secs. 28 and 29. N. 89°54' W., on the E and W centerline of sec. 29.
20.08	Point for the center E 1/16 sec. cor. of sec. 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled in a collar of stone, with brass cap mkd.
	T12S R32E E 1/16 C ——— C S29 PMWA 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 59 lks. N. of wash, 15 lks. wide, 2 ft. deep, drains SSW.
40.16	The true point for the center 1/4 sec. cor. of sec. 29.
42.405	Point for AP 67, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
80.03	The true point for the 1/4 sec. cor. of secs. 29 and 30.

Subdivision of Section 29 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	NE 1/4
	From the center E 1/16 sec. cor. of sec. 29.
	N. 0°06' W., on the N and S centerline of the NE 1/4 of sec. 29.
19.95	Point for the NE 1/16 sec. cor. of sec. 29, at intersection with the E and W center line of the NE 1/4 of sec. 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.
:	T12S R32E NE1/16 S29
1	PMNA 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
39.89	The E 1/16 sec. cor. of secs. 20 and 29.
	From the true point for the N 1/16 sec. cor. of secs. 28 and 29.
	N. 89°55' W., on the E and W centerline of the NE 1/4 of sec. 29.
20.07	The NE 1/16 sec. cor. of sec. 29.
40.14	The center N 1/16 sec. cor. of sec. 29.
	NW 1/4
	From the center N 1/16 sec. cor. of sec. 29.
	N. 89°50 W., on the E and W centerline of the NW 1/4 of sec. 29.
39.87	The N 1/16 sec. cor. of secs. 29 and 30.
	Subdivision of Section 30 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 30 and 31.
	N. 0°06' W., on the N and S centerline of sec. 30.

Subdivision of Section 30

T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
15.20	Point for AP 75, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
39.95	Point for the center 1/4 sec. cor. of sec. 30, at intersection with the E and W center line of sec. 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled in a collar of stone, with brass cap mkd.
	T12S R32E C1/4 S30 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located on the E. edge of a wash, 15 lks. wide, 1 ft. deep, drains SSW.
79.89	The 1/4 sec. cor. of secs. 19 and 30.
	From the true point for the 1/4 sec. cor. of secs. 29 and 30.
	S 89°50' W., on the E and W centerline of sec. 30.
13.08	Point for AP 70, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
20.05	Point for the center E 1/16 sec. cor. of sec. 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T12S R32E E 1/16
	$c \frac{2}{30} c$
i	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
40.10	The center 1/4 sec. cor. of sec. 30.

Subdivision of Section 30 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

	1. 12 S., R. 52 E., Gila and Salt River Periodal, Alizona
CHAINS 80.01	The 1/4 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, encircled with a collar of stone, with a mound of stone to the W., 3 ft. base, 2 ft. high, with brass cap mkd. 1/4 S25 S30 1914 1992, as described in the field notes of the dependent resurvey of the E. bdy., T. 12 S., R. 31 E., executed concurrently under this same group.
	SE 1/4
	From the E 1/16 sec. cor. of secs. 30 and 31.
	N. 0°03' W., on the N and S centerline of the SE 1/4 of sec. 30.
15.41	Point for AP 73, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
37.56	Point for AP 72, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
39.97	The center E 1/16 sec. cor. of sec. 30.
	Subdivision of Section 31 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 6 and 31, on the S. bdy of the Tp.
	N. 0°01' W., on the N and S centerline of sec. 31.
20.00	Point for the center S 1/16 sec. cor. of sec. 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12S R32E
	s 1/16 s31 C 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 100 lks. W. of wash, 50 lks. wide, 2 ft. deep, drains N.

Subdivision of Section 31 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS 29.08	Point for AP 102, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
30.38	Point for AP 91, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
40.00	Point for the center 1/4 sec. cor. of sec. 31, at intersection with the E and W centerline of sec. 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, encircled in a collar of stone, with brass cap mkd.
	T12S R32E
	C1/4 S31
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
80.03	The 1/4 sec. cor. of secs. 30 and 31.
	From the 1/4 sec. cor. of secs. 31 and 32.
	S. 89°55' W., on the E and W centerline of sec. 31.
20.01	Point for the center E 1/16 sec. cor. of sec. 31.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole, on a rock ledge, 9 x 14 ft., with top mkd.
	T12S R32E
	E 1/16
	c —— c
	S31
	1992
	Deposit a magnet, 1 x 7/8 in. diam., beneath the brass tablet.
40.02	The center 1/4 sec. cor. of sec. 31.
51.36	Point for AP 88, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
52.14	Point for AP 105, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.

Subdivision of Section 31 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	The 1/4 sec. cor. of secs. 31 and 36, on the W. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 3 ft. base, to top, with a mound of stone to the W., 3 ft. base, 2 ft. high, with brass cap mkd. 1/4 S36 S31 1914 1992, as described in the field notes of the dependent resurvey of the E. bdy. of T. 12 S., R. 31 E., executed concurrently under this same group.
	SE 1/4
	From the E 1/16 sec. cor. of secs. 6 and 31, on the S. bdy. of the Tp.
	North, on the N and S centerline of the SE 1/4 of sec. 31.
20.02	Point for the SE 1/16 sec. cor. of sec. 31, at intersection with the E and W center line of the SE 1/4 of sec. 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12S R32E
	SE1/16 S 31 1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
20.82	Point for AP 98, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described,
21.80	Point for AP 95, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
40.04	The center E 1/16 sec. cor. of sec. 31.
	From the S 1/16 sec. cor. of secs. 31 and 32.
	S. 89°57' W., on the E and W centerline of the SE 1/4 of sec. 31.
14.20	Point for AP 96, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
16.85	Point for AP 97, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
20.02	The SE 1/16 sec. cor. of sec. 31.
	L

Subdivision of Section 31 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

	1. 12 S., R. 32 E., GIIA dim Balt Rivel Periodian, Arizona
CHAINS 40.04	The center S 1/16 sec. cor. of sec. 31.
	Subdivision of Section 33 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 4 and 33 on the S. bdy. of the Tp.
	N. 0°04' W., on the N and S centerline of sec. 33.
20.03	Point for the center S 1/16 sec. cor. of sec. 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.
·	T12S_R32E
	C S 1/16 S33
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located on the N. bank of a wash, 50 lks. wide, 8 ft. deep, drains SE.
40.06	Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E and W center line of sec. 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12S R32E
	C1/4 S33 1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	from which
	A boulder, 25 x 15 x 35 ft. high, bears S. 33 3/4° W., 71 lks. dist, mkd. X BO on the NE face.
80.13	The 1/4 sec. cor. of secs. 28 and 33.
	From the 1/4 sec. cor. of secs. 33 and 34.

Subdivision of Section 33 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

	1. 12 S., R. 32 E., Gila and Sait River Meridian, Arizona
CHAINS	N. 89°58' W., on the E and W centerline of sec. 33.
19.96	Point for the center E 1/16 sec. cor. of sec. 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12S R32E E 1/16 C ———————————————————————————————————
	Deposit a magnet in a 1 \times 1 \times 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 32 lks. W. of barbed wire fence, 4 strand, bears N. and S.
39.92	The center 1/4 sec. cor. of sec. 33.
79.82	The 1/4 sec. cor. of secs. 32 and 33.
	SE 1/4
	From the E 1/16 sec. cor. of secs. 4 and 33 on the S. bdy. of the Tp.
	N. 0°04' W., on the N and S centerline of the SE 1/4 of sec. 33.
20.02	Point for the SE 1/16 sec. cor. of sec. 33, at intersection with the E and W center line of the SE 1/4 of sec. 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T12S R32E
	PMWA SE1/16 S33
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 16 lks. W. of barbed wire fence, 4 strand, bears N. and S.
40.04	The center E 1/16 sec. cor. of sec. 33.

Subdivision of Section 33

	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	From the S 1/16 sec. cor. of secs. 33 and 34.
	N. 89°59' W., on the E and W centerline of the SE 1/4 of sec. 33.
19.96	The SE 1/16 sec. cor. of sec. 33.
39.92	The center S 1/16 sec. cor. of sec. 33.
	Subdivision of Section 34 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp.
	N. 0°04' W., on the N and S centerline of sec. 34.
20.01	Point for the center S 1/16 sec. cor. of sec. 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12S R32E
	S 1/16 S34
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
40.02	Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E and W centerline of sec. 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T12S R32E C1/4 S34 1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
79.81	The 1/4 sec. cor. of secs. 27 and 34.
	From the 1/4 sec. cor. of secs. 34 and 35.
	S. 89°59' W., on the E and W centerline of sec. 34.

Subdivision of Section 34

T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

	T. 12 S., R. 32 E., GIIA and Salt River Meridian, Arizona
20.01	Point for the center E 1/16 sec. cor. of sec. 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.
	T12S R32E E 1/16 C ———————————————————————————————————
	Deposit a magnet in a 1 \times 1 \times 2 ins. white plastic case beneath the stainless steel post.
40.02	The center 1/4 sec. cor. of sec. 34.
60.00	Point for the center W 1/16 sec. cor. of sec. 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T12S R32E E 1/16 C ————————————————————————————————————
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
79.98	The 1/4 sec. cor. of secs. 33 and 34.
	SE 1/4
	From the E $1/16$ sec. cor. of secs. 3 and 34 on the S. bdy. of the Tp.
	N. 0°03' W., on the N and S centerline of the SE 1/4 of sec. 34.
40.00	The center E 1/16 sec. cor. of sec. 34.
	SW 1/4
	From the W $1/16$ sec. cor. of secs. 3 and 34 on the S. bdy. of the Tp.
	N. 0°03' W., on the N and S centerline of the SW 1/4 of sec. 34.

Subdivision of Section 34 T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

20.01	Point for the SW 1/16 sec. cor. of sec. 27 at intersection with the E and W centerline of the SW 1/4 of sec. 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.
	T12S R32E SW1/16 S34 PMWA 1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
40.02	The center W 1/16 sec. cor. of sec. 34.
	From the center S 1/16 sec. cor. of sec. 34.
	S. 89°59' W., on the E and W centerline of the SW 1/4 of sec. 34.
19.98	The SW 1/16 sec. cor. of sec. 34.
39.96	The S 1/16 sec. cor. of secs. 33 and 34.
	Metes-and-Bounds Survey of the Peloncillo Wilderness Area Boundary T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
	In Section 14
	From the point for AP 1, on the Arizona-New Mexico State Bdy.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled in a collar of stone, with brass cap mkd.
	AZ NM T12S AP1 T22S PMWA R21W R32E S18 S14 1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.

	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	From this cor. point, the closing cor. of secs. 11 and 14, bears N. 0°07' E., 7.29 chs. dist., hereinbefore described.
	N. 56°57' W., on line 1-2.
6.54	Point for AP 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T12S R32E
	AP2
	PMWA S14
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	N. 30°07' E., on line 2-3.
2.91	Point for AP 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.
	T12S R32E
	AP3
	PMWA / S14
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	N. 30°20' E., on line 3-4.
1.40	Point for AP 4, on the line bet. secs. 11 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, with brass cap mkd.
	T12S R32E AP4 / S11 PMWA / S14
	1992
1]

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case

beneath the stainless steel post.

Cor. is located 45 lks. W. of wash, 6 lks. wide, 2 1/2 ft. deep, drains NNE.

From this cor. point, the 1/4 sec. cor. of secs. 11 and 14, bears S. 89°49' E., 1.55 chs., hereinbefore described.

In Sec. 11


N. 22°14' E., on line 4-5.

8.84 Point for AP 5, identical with the 317 Mile Post on the Arizona-New Mexico State Bdy., hereinbefore described.

> N. 0004'W., on line 5-6, identical with a portion of the Arizona-New Mexico State Bdy.

15.03 Point for AP 6, on the Arizona-New Mexico State Bdy.

> Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled in a collar of stone, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 ins. in a white plastic case beneath the stainless steel post.

Cor. is located 50 lks. W. of wash, 76 lks. wide, 7 ft. deep, drains NE.

N. 40°18' W., on line 6-7.

8.26 Point for AP 7.

> Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS T12S R32E S11 PMWA 1992 Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Cor. is located 114 lks. S. of trail road, bears SE and NW. N. 38°21' W., on line 7-8. 9.49 Point for AP 8. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd. T12S R32E AP8 Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Cor. is located 50 lks. SW of trail road, bears SSE and NNW. N. 31°24' W., on line 8-9. 6.98 Point for AP 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd. T12S R32E **S11** AP9 PMWA 1992 Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

	1. 12 Br, No 52 Br, Gild alm Ballo little limited, 12 Br.
CHAINS	Cor. is located 186 lks. W. of electric fence, 2 strand, bears N and S.
	N. 24°36' W., on line 9-10.
11.11	Point for AP 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T12S R32E
	AP10 S11 PMWA 1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	Cor. is located 55 lks. SW of trail road, bears SE and N.
	N. 30°10' W., on line 10-11.
12.14	Point for AP 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T12S R32E
	AP11 S11
	PMWA
	1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	Cor. is located 41 lks. SW of trail road, bears SE and NNW.
	N. 33°00' W., on line 11-12.
6.84	Point for AP 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary

T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS

T12S R32E **AP12 S11 PMWA** 1992

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.


Cor. is located 45 lks. NW of wash, 23 lks. wide, 1 ft. deep, drains NE.

N. 66°17' W., on line 12-13.

2.74 Point for AP 13.

> Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

> > T12S R32E **S11**



Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Cor. is located 45 lks. SSW of trail road, bears ESE and SW.

S. 49°11' W., on line 13-14.

3.41 Point for AP 14.

> Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

> > T12S R32E S11 **AP14 PMWA**

> > > 1992

	1. 12 S., R. 32 E., Gila and Sait River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 76 lks. S of trail road, bears ESE and WNW.
	N. 63°08' W., on line 14-15.
2.12	Point for AP 15.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T12S R32E
	AP15 S11
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 42 lks. WSW of trail road, bears N and ESE, and 118 lks. WNW of a wash, 17 lks. wide, 2 ft. deep and drains WNW.
	N. 15°03' E., on line 15-16.
2.96	Point for AP 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T12S R32E S11
	AP16 PMWA
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 45 lks. SSE of trail road, bears SE and W, and 145 lks. WNW of a wash, 6 lks. wide, 3 ft. deep and drains NE.
i	

	,
CHAINS	S. 88°15' W., on line 16-17.
6.09	Point for AP 17, on the line bet. secs. 10 and 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T12S R32E S10 S11 AP 17 PM WA 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 56 lks. S. of trail road, bears E and WNW.
	From this cor. point, the cor. of secs. 2, 3, 10 and 11, bears N. 0°20' E., 8.57 chs. dist., hereinbefore described.
	In Sec. 10
	N. 69°35' W., on line 17-18.
12.42	Point for AP 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T12S R32E
	\ s10
	AP18
	PMWA
	1992
	Deposit a magnet in a 1 \times 1 \times 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 115 lks. SSE of trail road, bears WSW and NW, and 65 lks SE of wash, 12 lks. wide, 4 ft. deep, drains. NE.
	N. 36°18' W., on line 18-19.
4.82	Point for AP 19.

	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, with brass cap mkd.
	T12S R32E
	AP19 PMWA
	1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	Cor. is located 68 lks. SW of trail road, bears SE and NW, and 15 lks. NW of wash, 5 lks. wide, 2 ft. deep, drains ENE, and 105 lks. NW of wash, 23 lks. wide, 1 ft. deep.
	S. 89°16' W., on line 19-20.
5.04	Point for AP 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T12S R32E
	S10
	AP20 PMWA
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 55 lks. SSE of trail road, bears WSW and ENE, and 36 lks. N of wash, 5 lks. wide, 2 ft. deep, drains ESE.
	S. 58°09' W., on line 20-21.
2.93	Point for AP 21.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, with brass cap mkd.

BOOK 54 07

70

CHAINS	T12S R32E
	S10 AP21
	PMMA
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 55 lks. S. of trail road, bears WSW and ENE.
	S. 74°15' W., on line 21-22.
13.96	Point for AP 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12S R32E S10
	AP22
	PMWA
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 44 lks. S. of trail road, bears E. and W.,
	S. 87°17' W., on line 22-23.
7.12	Point for AP 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, with brass cap mkd.
	T12S R32E
	S10
	AP23 PMWA 1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.

	1. 12 S., R. 32 E., Gila and Sait River Meridian, Arizona
CHAINS	Cor. is located 55 lks. S. of trail road, bears ENE. and WNW.
	N. 84°40' W., on line 23-24.
14.06	Point for AP 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, 1 1/2 ft. high, with brass cap mkd.
	T12S R32E
	S10 AP24
	PMWA 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 3 lks. SW of fence cor., barbed wire, 5 strand, bears SSW. and WNW.
	S. 12°05' W., on line 24-25.
17.71	Point for AP 25.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, with brass cap mkd.
	T12S R32E
	S10AP25 PMWA
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 2 lks. WNW. of fence cor., barbed wire, 5 strand, bears NNE. and W.
	S. 75°51' W., on line 25-26.
6.96	Point for AP 26.

CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, with brass cap mkd.
	T12S R32E
	AP26 S10 PMWA 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 3 lks. S. of fence cor., barbed wire, 5 strand, bears NW. and W.
	N. 41°41' W., on line 26-27.
19.29	Point for AP 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.
	T12S R32E
	1
	AP27 PMWA S10
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 2 lks. SW. of fence cor., barbed wire, 5 strand, bears SE. and NW.
	N. 0°40' W., on line 27-28.
9.39	Point for AP 28, identical with the cor. of secs. 3, 4, 9 and 10, hereinbefore described.
	In Sec. 4
	West, on the line bet. secs. 4 and 9.
40.02	The 1/4 sec. cor. of secs. 4 and 9, hereinbefore described.

	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	North, on the N and S centerline of sec. 4.
35.78	The witness point on the N and S centerline of sec. 4, hereinbefore described.
79.71	The 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp., hereinbefore described.
	In Sec. 7
	From the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.
	N. 89047' E., on the line bet. secs. 6 and 7.
20.07	The W 1/16 sec. cor. of secs. 6 and 7, hereinbefore descried.
	S.0005' W., on the N and S centerline of sec. 7.
27.77	Point for AP 29, on the N and S centerline of the NW 1/4 of sec. 7.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, encircled in a collar of stone, with brass cap mkd. T12S R32E
	PMWA
	AP29
	S7
	1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	N. 86°37' E., on line 29-30.
3.29	Point for AP 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.

	•
CHAINS	T12S R32E
	PMWA
	S7 AP30
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	S. 7°38' E., on line 30-31.
7.45	Point for AP 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, with a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.
	T12S R32E
	PMWA AP31
	S7 AP31
	1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	S. 15°33' E., on line 31-32.
5.19	Point for AP 32, on the E and W centerline of sec. 7.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled with a collar of stone, with brass cap mkd.
	T12S R32E
	PMWA
	→ AP32 S7
	1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.


	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	N. 89044' E., on the E and W center line of sec. 7.
14.34	The center 1/4 sec. cor. of sec. 7, hereinbefore described.
54.20	The 1/4 sec. cor. of secs. 7 and 8, hereinbefore described.
<u>.</u>	South, on the line bet. secs. 7 and 8.
40.06	The cor. of secs. 7, 8, 17 and 18, hereinbefore described.
	In Sec. 18
	S. 0002' E., on the line bet. secs. 17 and 18.
40.06	The 1/4 sec. cor. of secs. 17 and 18, hereinbefore described.
	S. 89047' W., on the E and W center line of sec. 18.
39.97	The true point for the center 1/4 sec. cor. of sec. 18, hereinbefore described.
59.95	The W 1/16 sec. cor. of sec. 18, hereinbefore described.
	S. 0002' E., on the N and S center line of the SW 1/4 of sec. 18.
40.00	The W 1/16 sec. cor. of secs. 18 and 19, hereinbefore described.
	S. 89046' W., on the line bet. secs. 18 and 19.
19.99	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.
	In Sec. 19
	S. 0001' E., on the line bet. secs. 19 and 24, on the W. bdy. of the Tp.
40.00	The 1/4 sec. cor. of secs. 19 and 24, hereinbefore described.
	S. 0002' E., on the line bet. secs. 19 and 24, on the W. bdy. of the Tp.
19.96	The S 1/16 sec. cor. of secs. 19 and 24, hereinbefore described.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

22.32

Point for AP 33, on the line bet. secs. 19 and 24.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.




Deposit a magnet in a $1 \times 1 \times 2$ 5/8 ins. white plastic case beneath the stainless steel post.

S. 68°45' E., on line 33-34.

4.03 Point for AP 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled with a collar of stone, with brass cap mkd.

T12S R32E



Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Cor. is located 50 lks. N. of trail road, bears E. and W.

S. 87°34' E., on line 34-35.

5.17 | Point for AP 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.

	+
CHAINS	
	T12S R32E
	PMNA
	AP35
	S19
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case
	beneath the stainless steel post.
	Con in leasted 106 lbm N of twell wood beauty CE and NW
	Cor. is located 106 lks. N. of trail road, bears SE. and NW.
,	- 404001 - 1: 05.06
	S. 42°39' E., on line 35-36.
11.92	Point for AP 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	23 ins. in the ground, with brass cap mkd.
	T12S R32E
	1125 R32E
	PMWA
	AP36
	S19
	1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	Cor. is located 68 lks. E. of trail road, bears SSE. and NNW.
	Col. 1s located to lks. E. Of that load, hears bot. and him.
	C 69°201 E on line 26-27
	S. 68°30' E., on line 36-37.
3.15	Point for AP 37, on the N and S centerline of the SW 1/4 of sec. 19.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	21 ins. in the ground, with brass cap mkd.
	T12S R32E
	PMWA
	AP37
	S19
	1992
	L

CHAINS	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 52 lks. N. of trail road, bears E. and W.
	N. 0001' E., on the N and S center line of the SW 1/4 of sec. 19.
14.06	The SW 1/16 sec. cor. of sec. 19, hereinbefore described.
	N. 89°43' E., on the E and W centerline of the SW 1/4 of sec. 19.
19.94	The center S 1/16 sec. cor. of sec. 19, hereinbefore described.
	N. 89044' E., on the E and W centerline of the SE 1/4 of sec. 19.
40.07	The S 1/16 sec. cor. of secs. 19 and 20, hereinbefore described.
	South, on the line bet. secs. 19 and 20.
8.43	Point for AP 38, on the line bet. secs. 19 and 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T12S R32E
	PMWA AP38
	S19 A250
	1992 s20
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	In Sec. 20
	N. 65°21' E., on line 38-39.
6.35	Point for AP 39.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

CHAINS	m12g p22g
	T12S R32E
	PMWA /
	AP39 S20
	1002
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 35 lks. N. of trail road, bears NE. and SW.
	N. 31°04' E., on line 39-40.
3.45	Point for AP 40.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T12S R32E
	PMWA AP40 S20
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 55 lks. W. of trail road, bears ENE. and SW.
	N. 55°51' E., on line 40-41.
4.16	Point for AP 41.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T12S R32E
	PMWA /
	AP41
	S20
	1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.

	1. 12 5., R. 52 E., Gila and bate River resident, Alizona
CHAINS	Cor. is located 118 lks. W. of trail road, bears NNE. and SSW., and 52 lks. W. of a wash, 48 lks wide, 2 ft. deep, drains SW.
	N. 39°13' E., on line 41-42.
6.92	Point for AP 42.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T12S R32E
	PMWA AP42 S20
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 32 lks. W. of trail road, bears NNE. and SSW., and 68 lks. E. of a wash, 41 lks wide, 2 ft. deep, drains S.
	N. 7°24' E., on line 42-43.
3.90	Point for AP 43.
·	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T12S R32E
	PMNA
	AP43
	S20
	1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	Cor. is located 82 lks. W. of trail road, bears NE. and SSW., and 68 lks. E. of a wash, 45 lks wide, 3 ft. deep, drains SSW.
	N. 39°53' E., on line 43-44.
10.93	Point for AP 44.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd. T12S R32E PMWA AP44 1992 Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Cor. is located 61 lks. W. of trail road, bears NE. and SW., and 66 lks. E. of E. channel of a wash, 15 lks wide, 2 ft. deep, drains SSW. N. 55°38' E., on line 44-45. 3.26 Point for AP 45. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T12S R32E PMWA **AP45** S20 1992 Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Cor. is located 41 lks. N. of trail road, bears ENE. and WSW., and 59 lks. S. of S. channel of a wash, 27 lks wide, 2 ft. deep, drains SW. N. 72°14' E., on line 45-46.

8.68 | Point for AP 46.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

CHAINS	
	T12S R32E
	PMWA AP46
	S20
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 56 lks. N. of trail road, bears E. and WSW.
	N. 77°00' E., on line 46-47.
5.63	Point for AP 47.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.
	T12S R32E
	PMWA.
	AP47
	S20
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 52 lks. N. of trail road, bears NE. and SW.
	N. 52°07' E., on line 47-48.
4.25	Point for AP 48.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled in a collar of stone, with brass cap mkd.
	T12S R32E
	PMWA AP48

	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 107 lks. W. of trail road, bears ENE. and SW., and 145 lks. S. of a wash, 53 lks. wide, 2 ft. deep, drains WSW.
	N. 61°48' E., on line 48-49.
4.23	Point for AP 49.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.
	T12S R32E
	PMWA AP49
	S20
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 38 lks. NNE. of cattle tank, concrete, 7 1/2 ft. diam., 2 1/2 ft. high.
	S. 52°14' E., on line 49-50.
2.48	Point for AP 50.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled in a collar of stone, with brass cap mkd.
	T12S R32E
	PMWA AP50
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

	1. 12 5., K. 32 E., GIIA AM BATC RIVEL PETICIAN, ATLEGIA
CHAINS	Cor. is located 86 lks. NE. of east end of dam, concrete, 1 ft. wide, 20 ft long, 8 ft. high, bears WNW.
	S. 17°15' E., on line 50-51.
5.92	Point for AP 51.
	Set a brass tablet, 3 1/4 ins. diam, 3 1/2 ins. stem, in a drill hole, cemented in place, on a rock outcrop, 100 x 40 x 13 ft. high, with top mkd.
	T12S R32E
:	S20 PMWA AP51
	1992
	Deposit a magnet, 1 x 7/8 in. diam. beneath the stem.
	boposto a magnes, I ii //o iiii arami bonoadi dio bodiii
	Cor. is located 185 lks. SE. of east end of dam, concrete, 8 ins. wide, 12 ft long, 6 ft. high, bears WSW.
	S. 78°43' W., on line 51-52.
1.63	Point for AP 52.
	Set a brass tablet, 3 1/4 ins. diam, 3 1/2 ins. stem, in a drill hole, cemented in place, on a boulder, 15 x 7 x 7 ft. high, with top mkd.
	T12S R32E
	\s20
	AP52
	PMWA
	1992
	Deposit a magnet, 1 x 7/8 in. diam. beneath the stem.
	N. 47°26' W., on line 52-53.
6.52	Point for AP 53.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled in a collar of stone, with brass cap mkd.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS T12S R32E S20 **PMWA** 1992 Deposit a magnet in a $1 \times 1 \times 2 = 5/8$ ins. white plastic case beneath the stainless steel post. Cor. is located 83 lks. E. of trail road, bears NE. and SSW. S. 46°44' W., on line 53-54. 2.84 Point for AP 54. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd. T12S R32E S20 **AP54** PMWA 1992 Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Cor. is located 30 lks. S. of trail road, bears ENE. and W. S. 69°11' W., on line 54-55. Point for AP 55. 5.52 Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.

CHAINS	
	T12S R32E
	S20
	AP55
	PMWA
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 41 lks. S. of trail road, bears E. and WSW.
	S. 75°15' W., on line 55-56.
10.66	Point for AP 56.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.
	T12S R32E
	S20
	AP56
	PMWA
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 106 lks. S. of trail road, bears E. and WSW.
	S. 53°52' W., on line 56-57.
2.82	Point for AP 57.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.

CHAINS	
	T12S R32E
	S20
	AP57
	PMWA
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 117 lks. E. of trail road, bears NE. and SSW.
	S. 39°32' W., on line 57-58.
10.18	Point for AP 58.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.
	T12S R32E
	S20
	AP58
	PMWA
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 121 lks. S. of trail road, bears NE. and SSW.
	S. 11°33' W., on line 58-59.
3.88	Point for AP 59.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.

CHAINS	
	T12S R32E
	S20 AP59 PMWA
į	1992
	Deposit a magnet in a $1 \times 1 \times 2$ 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 64 lks. E. of trail road, bears NNE. and SSW.
	s. 40°20' W., on line 59-60.
7.93	Point for AP 60.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T12S R32E
	S20 /
	AP60 PMWA
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 38 lks. E. of trail road, bears NE. and WSW.
	s. 55°13' W., on line 60-61.
3.82	Point for AP 61.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary

T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS

T12S R32E

S20 **AP61** PMWA

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Cor. is located 88 lks. E. of trail road, bears NNE. and SSW.

S. 37°31' W., on line 61-62.

4.63 Point for AP 62.

> Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

> > T12S R32E

AP62 PMWA

1992

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Cor. is located 89 lks. S. of trail road, bears NE. and SW.

S. 71°01' W., on line 62-63.

5.84 Point for AP 63, on the line bet. secs. 19 and 20.

> Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

> > T12S R32E

S19 PMWA

90

	T. 12 S., R. 32 E., Glid ditt Sait River Periodan, Arizona
CHAINS	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	South, on the line bet. secs. 19 and 20.
10.67	The cor. of secs. 19, 20, 29 and 30, hereinbefore described.
	In Sec. 29
	S. 0005' E., on the line bet. secs. 29 and 30.
19.98	The N 1/16 sec. cor. of secs. 29 and 30, hereinbefore described.
}	S. 89°50' E., on the E and W centerline of the NW 1/4 of sec. 29.
39.87	The center N 1/16 sec. cor. of sec. 29, hereinbefore described.
	S. 89°55' E., on the E and W centerline of the NE 1/4 of sec. 29.
20.07	The NE 1/16 sec. cor. of sec. 29, hereinbefore described.
	S. 0006' E., on the N and S centerline of the NE 1/4 of sec. 29.
19.95	The center E 1/16 sec. cor. of sec. 29, hereinbefore described.
	N. 89054' W., on the E and W centerline of sec. 29.
20.08	Point for AP 64, identical with the true point for the center 1/4 sec. cor.of sec. 29, hereinbefore described.
	S. 20°30' W., on line 64-65.
2.35	Point for AP 65.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.
	T12S R32E
	s29 /
	AP65
	PMWA 1992

CHAINS	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	N. 67°16' W., on line 65-66.
1.54	Point for AP 66.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12S, R32E
	S29
	AP66
	PMWA 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	N. 0°01' W., on line 66-67.
1.61	Point for AP 67, on the E and W centerline of sec. 29.
	Set a brass tablet, 3 1/4 ins. diam, 3 1/2 ins. stem, in a drill hole, cemented in place, on a sandstone ledge, with top mkd.
	T12S R32E
	PMWA S29
	AP67
	1992
đ.	Deposit a magnet, 1 x 7/8 in. diam. beneath the stem.
	Cor. is located 42 lks. N. of a wash, 45 lks. wide, 3 ft. deep, drains WNW.
	N. 89054' W., on the E and W centerline of sec. 29.
37.625	The true point for the 1/4 sec. cor. of secs. 29 and 30, hereinbefore described.
	N. 0005' W., on the line bet. secs. 29 and 30.
4.83	Point for AP 68, on the line bet. secs. 29 and 30.

	1. 12 S., R. 32 E., GIIA and Batt River Perfection, Introdu
CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T12S R32E
	S30 S29
	AP68 PMWA 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 44 lks. S. of a trail road, bears NE. and SW.
	In Sec. 30
	S. 52°20' W., on line 68-69.
3.95	Point for AP 69.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T12S R32E
	s30 /
	AP69
	PMWA 1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	Cor. is located 30 lks. N. of and on a rock ledge, 20 ft. high, bears ESE. and WNW., and 50 lks. S. of trail road, bears ESE. and WNW.
	S. 76°08' W., on line 69-70.
10.24	Point for AP 70, on the E and W centerline of sec. 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

CHAINS	
	T12S R32E
	s30
	AP70
	PMWA
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 32 lks. N. of and on a rock ledge, 40 ft. high, bears E. and W., and 30 lks. S. of trail road, bears ENE. and W.
	From this cor. point, the center E 1/16 sec. cor. of sec. 30, bears S. 89°50' W., 6.97 chs. dist., hereinbefore described.
	S. 66°24' W., on line 70-71.
5.26	Point for AP 71.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.
	T12S R32E
	S30
	AP71
	PMWA
	1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	Cor. is located 39 lks. N. of and on a rock ledge, 150 ft. high, bears ENE. and WSW., and 68 lks. S. of trail road, bears ENE. and W.
	S. 81°16' W., on line 71-72.
2.17	Point for AP 72, on the N and S centerline of the SE 1/4 of sec. 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, with supporting mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary

T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	T12S R32E
	S30 AP72 PMWA 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 83 lks. S. of trail road, bears ENE. and W.
	From this cor. point, the center E 1/16 sec. cor. of sec. 30, bears N. 0°03' W., 2.41 chs. dist., hereinbefore described.
	S. 0°03' E., on line 72-73, identical with a portion of the N and S centerline of the SE 1/4 of sec. 30.
22.15	Point for AP 73, on the N and S centerline of the SE 1/4 of sec. 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T12S R32E
	AP73 PMWA 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 80 lks. S. of wash, 38 lks. wide, 15 ft. deep, drains W.
	From this cor. point, the E 1/16 sec. cor. of secs. 30 and 31, bears S. 0°03' E., 15.41 chs. dist., hereinbefore described.
	N. 76°54' W., on line 73-74.
9.20	Point for AP 74.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

CHAINS	T12S R32E
	s30
	AP74
1	PMWA 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	S. 78°08' W., on line 74-75.
11.31	Point for AP 75, on the N and S centerline of sec. 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T12S R32E
	s30
	AP75
	PMWA 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 136 lks. S. of wash, 83 lks. wide, 3 ft. deep, drains W.
	From this cor. point, the center 1/4 sec. cor. of sec. 30, bears N. 0°06' W., 24.75 chs. dist., hereinbefore described.
	N. 78°01' W., on line 75-76.
9.35	Point for AP 76.
	Set a brass tablet, 3 1/4 ins. diam, 3 1/2 ins. stem, in a drill hole, cemented in place, on a boulder, 28 x 30 x 8 ft. high, with top mkd.

CHAINS	
	T12S R32E
	S30
	AP76
	PMWA
	1992
	Deposit a magnet, 1 x 7/8 in. diam., beneath the stem.
	Cor. is located 76 lks. S. of a wash, 52 lks. wide, 1 ft. deep, drains WNW.
	N. 69°24' W., on line 76-77.
12.18	Point for AP 77.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.
	T12S R32E
	S30
	AP77
	PMWA
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	S. 73°57' W., on line 77-78.
6.28	Point for AP 78.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.
	T12S R32E
	S30
	AP78 PMWA 1992
	L

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 137 lks. NE. of cor. of corral, wood rails, bears SW. and S.

S. 1°03' E., on line 78-79.

2.05 | Point for AP 79.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T12S R32E S30 PMWA AP79 1992

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Cor. is located 30 lks. SE. of cor. of corral, wood rails, bears N. and SW.

S. 48°01' W., on line 79-80.

6.07 Point for AP 80.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

T12S R32E S30 PMWA AP80 1992

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Cor. is located 29 lks. SE. of cor. of fences, barbed wire, 4 strand, bears NE. and SW., and 49 lks. SE. of improved dirt road, 12 ft. wide, bears NE. and SW.

S. 42°21' W., on line 80-81.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

13.20

Point for AP 81, on the line bet. secs. 25 and 30, on the W. bdy. of the Tp., identical with AP 16, T. 12 S., R. 31 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, encircled with a collar of stone, with brass cap mkd. T12S R31E R32E S25 S30 AP16 AP81 PMWA 1992, as described in the field notes of the Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Bdy., T.12 S., R.31 E., executed concurrently under this same group.

From this cor. point, the cor. of secs. 25, 30, 31 and 36, bears South, 3.94 chs. dist, hereinbefore described.

In Sec. 31

From the point for AP 82, on the line bet. secs. 31 and 36, on the W. bdy. of the Tp., identical with AP 21, T. 12 S., R. 31 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, encircled with a collar of stone, with brass cap mkd. T12S R31E R32E PMWA AP21 AP82 S36 S31 1992, as described in the field notes of the Metes-and-Survey of the Peloncillo Mountain Wilderness Area Bdy., T. 12 S., R. 31 E., executed concurrently under this same group.

From this cor. point, the 1/4 sec. cor. for secs. 31 and 36, bears South, 6.42 chs. dist, hereinbefore described.

S. 63°58' E., on line 82-83.

2.66 | Point for AP 83.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T12S R32E

PMWA

AP83

S31

1992

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Cor. is located 47 lks. N. of trail road, bears E. and WNW., and 125 lks. N. of wash, 137 lks. wide, 2 ft. deep, drains WNW.

S. 88°41' E., on line 83-84.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona


CHAINS Point for AP 84. 6.00 Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd. T12S R32E PMWA **AP84 S31** 1992 Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Cor. is located 62 lks. N. of trail road, bears E. and W., and 77 lks. N. of wash, 120 lks. wide, 2 ft. deep, drains W. N. 82°38' E., on line 84-85. 10.13 Point for AP 85. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. T12S R32E PMWA **AP85 S31** 1992 Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Cor. is located 79 lks. N. of trail road, bears ESE. and W., and 67 lks. N. of wash, 70 lks. wide, 2 ft. deep, drains W. S. 71°06' E., on line 85-86. Point for AP 86. 6.44 Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary

T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS

T12S R32E



Deposit a magnet in a $1 \times 1 \times 2$ 5/8 ins. white plastic case beneath the stainless steel post.


Cor. is located 115 lks. N. of wash, 156 lks. wide, 2 ft. deep drains WNW., and 67 lks. N. of trail road, bears SE. and WNW.

S. 48°55' E., on line 86-87.

4.15 | Point for AP 87.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T12S R32E



Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Cor. is located 73 lks. N. of center of wash, 185 lks. wide, 2 ft. deep, drains NW., and 61 lks. N. of trail road, bears SSE. and NW.

S. 32017' E., on line 87-88.

1.84 Point for AP 88, on the E and W centerline of sec. 31.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

101

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona CHAINS T12S R32E PMWA **AP88** 1992 Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Cor. is located 56 lks. S. of center of wash, 214 lks. wide, 2 ft. deep, drains NW., and 44 lks. E. of trail road, bears SSE. and NW. From this cor. point, the center 1/4 sec. cor. of sec. 31, bears N. 89°55' E., 11.34 chs. dist., hereinbefore described. S. 39°24' E., on line 88-89. 6.80 Point for AP 89. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T12S R32E PMWA S31 1992 Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Cor. is located 39 lks. N. of center of wash, 147 lks. wide, 2 ft. deep, drains NW., and 77 lks. N. of trail road, bears ESE. and NW. S. 60°42' E., on line 89-90. 4.05 Point for AP 90. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS T12S R32E PMWA **AP90** S31 1992 Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Cor. is located 58 lks. N. of wash, 110 lks. wide, 1 ft. deep, drains WNW., and 35 lks. N. of trail road, bears SE. and WNW. S. 55°50' E., on line 90-91. 4.22 Point for AP 91, on the N and S centerline of sec. 31. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T12S R32E PMWA **AP91** S31 1992 Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post. Cor. is located 100 lks. N. of wash, 79 lks. wide, 2 ft. deep, drains NW., and 100 lks. N. of trail road, bears SE. and NW. From this cor. point, the center 1/4 sec. cor. of sec. 31, bears N. 0°01' W., 9.62 chs. dist., hereinbefore described. S. 51°46' E., on line 91-92. 10.10 Point for AP 92. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

103

A** :	
CHAINS	
	T12S R32E
	∠ PMWA
	AP92
	S31 1992
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 65 lks. N. of wash, 83 lks. wide, 3 ft. deep, drains NW., and 80 lks. N. of trail road, bears SE. and NW.
	S. 63°20' E., on line 92-93.
3.80	Point for AP 93.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T12S R32E
	PMWA AP93
	S31 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 80 lks. N. of wash, 64 lks. wide, 2 ft. deep, drains WNW., and 48 lks. N. of trail road, bears E. and WNW.
	S. 88°49' E., on line 93-94.
7.07	Point for AP 94.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12S R32E
	PMWA AP94
	S31 1992

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS

Deposit a magnet in a $1 \times 1 \times 2 = 5/8$ ins. white plastic case beneath the stainless steel post.


Cor. is located 64 lks. N. of wash, 64 lks. wide, 3 ft. deep, drains W., and 74 lks. N. of trail road, bears ESE. and W.

S. 73°34' E., on line 94-95.

1.69 Point for AP 95, on the N and S centerline of the SE 1/4 of sec. 31.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T12S R32E



Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

Cor. is located 44 lks. N. of wash, 100 lks. wide, 4 ft. deep, drains WNW., and 44 lks. N. of trail road, bears ESE. and WNW.

From this cor. point, the center E 1/16 sec. cor. of sec. 31, bears North, 18.24 chs. dist., hereinbefore described.

S. 73°04' E., on line 95-96.

6.08 Point for AP 96, on the E and W centerline of the SE 1/4 of sec.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T12S R32E

PMWA AP96 S31 1992

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.

BOOK 5407

105

	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	Cor. is located 85 lks. N. of wash, 55 lks. wide, 4 ft. deep, drains WNW., and 85 lks. N. of trail road, bears SE. and WNW.
	N. 89°57' E., on the E and W centerline of the SE 1/4 of sec. 31.
14.20	The S 1/16 sec. cor. of secs. 31 and 32, hereinbefore described.
	South, on the line bet. secs. 31 and 32.
20.03	The cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the Tp., hereinbefore described.
	S. 89°59' W., on the line bet. secs. 6 and 31, on the S. bdy. of the Tp.
20.01	The E 1/16 sec. cor. of secs. 6 and 31, hereinbefore described.
	North, on the N and S centerline of the SE 1/4 of sec. 31.
20.02	The SE 1/16 sec. cor. of sec. 31, hereinbefore described.
	N. 89°57' E., on the E and W centerline of the SE 1/4 of sec. 31.
3.17	Point for AP 97, on the E and W center line of the SE 1/4 of sec. 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T12S R32E
	PMWA
	AP97 S31
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	Cor. is located 55 lks. S. of wash, 79 lks. wide, 4 ft. deep, drains WNW., and 55 lks. S. of trail road, bears ESE. and WNW.
	N. 75°53' W., on line 97-98.
3.27	Point for AP 98, on the N and S centerline of the SE 1/4 of sec. 31.

	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12S R32E
	AP98 S31 PMWA
	1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	Cor. is located 53 lks. S. of wash, 100 lks. wide, 4 ft. deep, drains WNW., and 53 lks. S. of trail road, bears ESE. and WNW.
	From this cor. point, the SE 1/16 sec. cor. of sec. 31, bears South, 0.80 chs. dist., hereinbefore described.
	N. 81°15' W., on line 98-99.
1.31	Point for AP 99.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12S R32E
	S31
	AP99
	PMWA 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 62 lks. S. of wash, 64 lks. wide, 3 ft. deep, drains W., and 55 lks. S. of trail road, bears ESE. and W.
	N. 87°18' W., on line 99-100.
7.39	Point for AP 100.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS	
	T12S R32E
	S31
	AP100 PMWA 1992
	Deposit a magnet in a $1 \times 1 \times 2$ 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 62 lks. S. of wash, 64 lks. wide, 2 ft. deep, drains WNW., and 62 lks. S. of trail road, bears E. and WNW.
	N. 67°19' W., on line 100-101.
4.53	Point for AP 101.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T12S R32E
	s31
	AP101
	PMWA 1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	Cor. is located 82 lks. S. of wash, 83 lks. wide, 3 ft. deep, drains NW., and 73 lks. S. of trail road, bears SE. and NW.
	N. 50°14' W., on line 101-102.
9.32	Point for AP 102, on the N and S centerline of sec. 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T12S R32E
	AP102 PMWA
	1992

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary

T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS

Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.


Cor. is located 39 lks. S. of wash, 79 lks. wide, 2 ft. deep, drains NW., and 39 lks. S. of trail road, bears SE. and NW.

From this cor. point, the center S 1/16 sec. cor. of sec. 31, bears S. 0°01' E., 9.08 chs. dist., hereinbefore described.

N. 56°37' W., on line 102-103.

4.77 Point for AP 103.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.




Deposit a magnet in a $1 \times 1 \times 2$ 5/8 ins. white plastic case beneath the stainless steel post.

Cor. is located 62 lks. S. of wash, 124 lks. wide, 1 ft. deep, drains WNW., and 94 lks. S. of trail road, bears SE. and WNW.

N. 58°50' W., on line 103-104.

4.20 | Point for AP 104.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.



Deposit a magnet in a $1 \times 1 \times 2$ 5/8 ins. white plastic case beneath the stainless steel post.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Cor. is located 82 lks. S. of wash, 147 lks. wide, 2 ft. deep, drains WNW., and 52 lks. S. of trail road, bears SE. and WNW.
	N. 36°39' W., on line 104-105.
7.62	Point for AP 105, on the E and W centerline of sec. 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12S R32E
	S31
	AP105 \ PMWA
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 112 lks. W. of wash, 214 lks. wide, 2 ft. deep, drains NW., and 36 lks. W. of trail road, bears SSE. and NW.
	From this cor. point, the 1/4 sec. cor. of secs. 31 and 36, on the W. bdy. of the Tp., bears S. 89° 55' W., 27.86 chs. dist., hereinbefore described.
	N. 45°47' W., on line 105-106.
1.26	Point for AP 106.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T12S R32E
	S31
	3D106
	AP106 PMWA
	1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	Cor. is located 56 lks. S. of wash, 185 lks. wide, 2 ft. deep,

drains NW., and 70 lks. S. of trail road, bears SE. and NW.

	1. 12 5., R. 52 E., Gila aim bait Rivel literatury in 150.2
CHAINS	N. 48°55' W., on line 106-107.
4.03	Point for AP 107.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T12S R32E
	S31
	AP107
	PMWA 1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located in center of wash, 156 lks. wide, 2 ft. deep, drains WNW., and 48 lks. S. of trail road, bears SE. and WNW.
	N. 72°43' W., on line 107-108.
5.92	Point for AP 108.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T12S R32E
	S31
	AP108 PMWA 1992
	1992
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
	Cor. is located 44 lks. S. of center of wash, 70 lks. wide, 3 ft. deep, drains W., and 33 lks. S. of trail road, bears ESE. and W.
	S. 82°14' W., on line 108-109.
9.86	Point for AP 109.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

CHAINS	
	T12S R32E
	AP109
	PMWA
	1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	Cor. is located 35 lks. S. of center of wash, 120 lks. wide, 3 ft. deep, drains W., and 33 lks. S. of trail road, bears ESE. and W.
	N. 87°02' W., on line 109-110.
6.77	Point for AP 110.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T12S R32E
	s31
	AP110
	PMWA
	1992
	Deposit a magnet in a 1 x 1 x 2 $5/8$ ins. white plastic case beneath the stainless steel post.
	Cor. is located 77 lks. S. of wash, 138 lks. wide, 2 ft. deep, drains WNW., and 77 lks. S. of trail road, bears ESE. and WNW.
	N. 77°17' W., on line 110-111.
1.79	Point for AP 111, on the line bet. secs. 31 and 36, on the W. bdy. of the Tp., identical with AP 22, T. 12 S., R. 31 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, encircled with a collar of stone, with brass cap mkd. T12S R31E R32E S36 S31 AP22 AP111 PMWA 1992, as described in the field notes of the Metes-and-Bounds survey of the Peloncillo Mountain Wilderness Area Bdy., T. 12 S., R. 31 E., executed concurrently under this same group.
	Cor. is located 108 lks. S. of wash, 152 lks. wide, 2 ft. deep, drains WNW., and 85 lks. S. of trail road, bears ESE. and WNW.

CHAINS	From this cor. point, the 1/4 sec. cor. of secs. 31 and 36, bears South, 4.74 chs. dist, hereinbefore described.
	In Sec. 33
	From AP 95, on the line bet. secs. 4 and 33, on the S. bdy. of the Tp., hereinbefore described.
	East, on the line bet. secs. 4 and 33, on the S. bdy. of the Tp.
8.70	The E 1/16 sec. cor. of secs. 4 and 33, hereinbefore described.
	N. 0004' W., on the N and S centerline of the SE 1/4 of sec. 33.
20.02	The SE 1/16 sec. cor. of sec. 33, hereinbefore described.
	S.89059' E., on the E and W centerline of the SE 1/4 of sec. 33.
19.96	The S 1/16 sec. cor. of secs. 33 and 34, hereinbefore described.
	In Sec. 34
	N. 89059' E., on the E and W centerline of the SW 1/4 of sec. 34.
19.98	The SW 1/16 sec. cor. of sec. 34, hereinbefore described.
	S. 0003' E., on the N and S centerline of the SW 1/4 of sec. 34.
20.01	The W 1/16 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., hereinbefore described.
	N. 89°59' E., on the line bet. secs. 3 and 34, on the S. bdy. of the Tp.
19.985	The 1/4 sec. cor. of secs. 3 and 34, hereinbefore described.
	N. 89°57' E., on the line bet. secs. 3 and 34, on the S. bdy. of the Tp.
20.00	The E 1/16 sec. cor. of secs. 3 and 34, hereinbefore described.
	N. 0003' W., on the N and S centerline of the SE 1/4 of sec. 34.

BOOK 5407

113

CHAINS 40.00	The center E 1/16 sec. cor. of sec. 34, hereinbefore described.
	N. 89°59' E., on the E and W centerline of sec. 34.
20.01	The 1/4 sec. cor. of secs. 34 and 35, hereinbefore described.
	N. 0º10' E., on the line bet. secs. 34 and 35.
39.91	The cor. of sec. 26, 27, 34 and 35, hereinbefore described.
	In Sec. 26
	N. 89°58' E., on the line bet. secs. 26 and 35.
20.01	The W 1/16 sec. cor. of secs. 26 and 35, hereinbefore described.
	N. 0008' E., on the N and S center line of the SW 1/4 of sec. 26.
20.02	The SW 1/16 sec. cor. of sec. 26, hereinbefore described.
	S. 89°54' W., on the E and W centerline of the SW 1/14 of sec. 26.
19.96	The S 1/16 sec. cor. of secs. 26 and 27, hereinbefore described.
	In Sec. 27
:	S. 89°57' W., on the E and W centerline of the SE 1/4 of sec. 27.
1.38	Point for AP 112, on the E and W centerline of the SE 1/4 of sec. 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T12S R32E
	S27 AP112 PMWA 1993
	Deposit a magnet in a 1 \times 1 \times 2 ins. white plastic case beneath the stainless steel post.

BOOK 5407

114

	1. 12 5., R. 52 E., Gila aim Sait River Periodal, Arizona
CHAINS	Cor. is located 29 lks. E. of trail road, bears N. and SSW.
	S. 41°59' W., on line 112-113.
3.25	Point for AP 113.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12S R32E
	S27
	AP113 PMWA
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 73 lks. S. of trail road, bears ENE. and W.
	N. 80°04' W., on line 113-114.
5.06	Point for AP 114.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T12S R32E
	S27
	AP114
	PMWA 1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 55 lks. S. of trail road, bears E. and W.
	N. 69°47' W., on line 114-115.
4.45	Point for AP 115, on the E and W centerline of the SE 1/4 of sec. 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

115

	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	T12S R32E
	S27
	AP115
	PMMA
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 9 lks. S. of wash, 5 lks. wide, 2 ft. deep, drains N., and 55 lks. W. of trail road, bears ESE. and WNW.
	S. 89°57' W., on the E and W centerline of the SE 1/4 of sec. 27.
27.51	The center S 1/16 sec. cor. of sec. 27, hereinbefore described.
	N.89°50' W., on the E and W centerline of the SW 1/4 of sec. 27.
20.05	The SW 1/16 sec. cor. of sec. 27, hereinbefore described.
	N. 0003' W., on the N and S centerline of the SW 1/4 of sec. 27.
20.05	The center W 1/16 sec. cor. of sec. 27, hereinbefore described.
	S. 89°56' E., on the E and W centerline of sec. 27.
20.12	The center 1/4 sec. cor. of sec. 27, hereinbefore described.
36.77	Point for AP 116, on the E and W centerline of sec. 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T12S R32E
	PMWA AP116
	\$27 1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 32 lks. W. of trail road, bears NNW. and SSE.

	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	N. 22°08' E., on line 116-117.
0.94	Point for AP 117.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled in a collar of stone, with brass cap mkd.
	T12S R32E
	PMWA
	AP117 / S27 1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 36 lks. W. of trail road, bears NNE. and SSW.
	N. 31°49' W., on line 117-118.
8.09	Point for AP 118.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T12S R32E
	PMWA AP118 S27
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 73 lks. W. of trail road, bears NW and SSE.
	N. 29°27' W., on line 118-119.
4.94	Point for AP 119.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS

T12S R32E

PMWA
AP119 S27
1993


Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Cor. is located 77 lks. W. of trail road, bears NNW. and SSE.

N. 52°32' W., on line 119-120.

5.94 | Point for AP 120.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.




Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Cor. is located 100 lks. W. of trail road, bears N. and SE.

N. 12°58' W., on line 120-121.

4.57 | Point for AP 121.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.



Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Cor. is located 55 lks. W. of trail road, bears NNW. and SSE.


N. 34°45' W., on line 121-122.

Metes-and-Bounds Survey of the
Peloncillo Mountains Wilderness Area Boundary
T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS **7.90**

Point for AP 122, on the N and S centerline of sec. 27.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.



Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.


Cor. is located 45 lks. W. of trail road, bears NNW. and SE.

From this cor. point, the center 1/4 sec. cor. of sec. 27, bears S. 0°09' W., 26.59 chs. dist., hereinbefore described.

N. 44°41' W., on line 122-123.

5.02 Point for AP 123.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.



Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Cor. is located 36 lks. W. of trail road, bears NW. and SSE.

N. 52°54' W., on line 123-124.

3.51 Point for AP 124.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.


Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary 1. 12 S., R. 32 E., Gila and Salt River Meridian, Arizon

T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona **CHAINS** T12S R32E 1993 Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post. Cor. is located 33 lks. W. of trail road, bears N. and SSE. N. 0°08' E., on line 124-125. 3.43 Point for AP 125. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T12S R32E AP125 PMWA Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post. Cor. is located 65 lks. W. of trail road, bears N. and SSW.

N. 44°52' W., on line 125-126.

1.90 Point for AP 126.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



1993

Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

CHAINS	
Chains	Cor. is located 64 lks. W. of trail road, bears NW. and ESE.
	N. 25°05' W., on line 126-127.
3.18	Point for AP 127, on the line bet. secs. 22 and 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T12S R32E
	PMWA S22
	AP127 S27 1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 41 lks. W. of trail road, bears NNW. and SSE.
	From this cor. point, the true point for the cor. of secs. 21, 22, 27 and 28, bears N. 89°53' W., 31.18 chs. dist., hereinbefore described.
	In Sec. 22
	In Sec. 22 N. 48°06' W., on line 127-128.
5.35	
5.35	N. 48°06' W., on line 127-128.
5.35	N. 48°06' W., on line 127-128. Point for AP 128. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
5.35	N. 48°06' W., on line 127-128. Point for AP 128. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
5.35	N. 48°06' W., on line 127-128. Point for AP 128. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. T12S R32E AP128 S22 PMWA
5.35	N. 48°06' W., on line 127-128. Point for AP 128. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. T12S R32E AP128 S22 PMWA 1993 Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath
5.35	N. 48°06' W., on line 127-128. Point for AP 128. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. T12S R32E AP128 AP128 S22 PMWA 1993 Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T12S R32E
AP129 S22
PMWA 1993

Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Cor. is located 85 lks. W. of trail road, bears N. and S.

N. 6°51' E., on line 129-130.

4.84 Point for AP 130.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled in a collar of stone, with brass cap mkd.

T12S R32E

PMWA S22
AP130 1993

Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Cor. is located 119 lks. W. of trail road, bears NW. and S.

N. 15°31' W., on line 130-131.

5.08 Point for AP 131.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T12S R32E
PMWA S22
AP131
1993

Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

	1. 12 5., R. 32 E., Gila aim Sait River Periutali, Arizona
CHAINS	Cor. is located 59 lks. W. of trail road, bears N. and S.
	N. 10°44' W., on line 131-132.
3.72	Point for AP 132.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled in a collar of stone, with brass cap mkd.
	T12S R32E
	PMWA S22
	AP132 \ 1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 106 lks. W. of trail road, bears WNW. and S.
	N. 51°54' W., on line 132-133.
9.85	Point for AP 133.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T12S R32E
	PMWA S22 AP133
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 4.20 chs. E. of wash, 45 lks. wide, 5 ft. deep, drains SE.
	N. 30°18' E., on line 133-134.
12.36	Point for AP 134.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem., in a drill hole, cemented in place, on a rock outcrop, 4 x 3 x 3 ft. high, with brass cap mkd.


CHAINS	T12S R32E
	PMWA AP134 S22
	1993
	Deposit a magnet, 1 x 7/8 in. diam. beneath the brass tablet stem.
	S. 79°50' E., on line 134-135.
5.52	Point for AP 135.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem., in a drill hole, cemented in place, on a rock outcrop, with brass cap mkd.
	T12S R32E
	S22 PMWA AP135
	1993
	Deposit a magnet, 1 x 7/8 in. diam. beneath the brass tablet stem.
	S. 29°27' W., on line 135-136.
12.88	Point for AP 136.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12S R32E
	S22 PMWA AP136
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 2.40 chs. E. of trail road, bears S. and NW.
	S. 41°01' E., on line 136-137.
I	1

CHAINS 3.11

Point for AP 137.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T12S R32E



Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Cor. is located 166 lks. E. of trail road, bears WNW. and SE.

S. 43°09' E., on line 137-138.

2.95 | Point for AP 138.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, encircled in a collar of stone, with brass cap mkd.

T12S R32E

Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.


Cor. is located 83 lks. E. of trail road, bears S. and WNW.

S. 6°36' E., on line 138-139.

3.22 Point for AP 139.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled in a collar of stone, with brass cap mkd.

T12S R32E



	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 144 lks. E. of trail road, bears N. and S.
	S. 12°02' E., on line 139-140.
5.50	Point for AP 140.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T12S R32E
	PMWA
	S22 AP140
	1993
	Deposit a magnet in a 1 \times 1 \times 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 51 lks. E. of trail road, bears NNW. and S., and 170 lks. W. of wash, 34 lks. wide, 2 ft. deep, drains S.
	S. 9°20' W., on line 140-141.
5.21	Point for AP 141.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12S R32E
	S22 PMWA AP141
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 59 lks. E. of trail road, bears NNE. and S.
	S. 34°21' E., on line 141-142.
4.68	Point for AP 142.

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T12S R32E
PMWA
S22 AP142

Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.


Cor. is located 2.10 chs. E. of trail road, bears ESE. and NNW.

S. 39°30' E., on line 142-143.

5.75 Point for AP 143, on the line bet. secs. 22 and 27.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T12S R32E



Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Cor. is located 32 lks. E. of trail road, bears SSE. and NNW.

From this cor. point, the 1/4 sec. cor. of secs. 22 and 27, bears S. 89°53' E., 8.20 chs. dist., hereinbefore described.

In Sec. 27

S. 31°41' E., on line 143-144.

2.27 Point for AP 144.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

127

	1. 12 b., K. 32 b., Gild alm ball River reflection, in 1962.
CHAINS	
	T12S R32E
	► PMWA
	S27 AP144
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 55 lks. E. of trail road, bears SE. and NNW.
	S. 50°12' E., on line 144-145.
2.83	Point for AP 145.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T12S R32E
	PMWA S27 AP145
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 73 lks. E. of trail road, bears SSW. and N.
	S. 8°42' W., on line 145-146.
3.67	Point for AP 146.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12S R32E
	S27 PMWA AP146
	,
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

128

CHAINS	
	Cor. is located 45 lks. E. of trail road, bears N. and S.
	S. 54°27' E., on line 146-147.
2.78	Point for AP 147.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T12S R32E
	S27 PMWA AP147
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 55 lks. E. of trail road, bears NW. and SE.
	S. 49°01' E., on line 147-148.
4.10	Point for AP 148, on the N and S centerline of sec. 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T12S R32E
	PMWA AP148
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 41 lks. E. of trail road, bears NW. and SE.
	From this cor. point, the 1/4 sec. cor. of secs. 22 and 27, bears N. 0°09' E., 11.66 chs. dist., hereinbefore described.
	S. 46°24' E., on line 148-149.
3.08	Point for AP 149.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary T. 12 S. R. 32 E. Gila and Salt River Meridian. Arizon

T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona **CHAINS** Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T12S R32E **PMWA** AP149 S27 1993 Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post. Cor. is located 59 lks. N. of trail road, bears NW. and SSE. S. 31°25' E., on line 149-150. 6.89 Point for AP 150. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. T12S R32E **PMWA** 1993 Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post. Cor. is located 55 lks. E. of trail road, bears NNW. and SSE. S. 10°32' E., on line 150-151. 3.10 Point for AP 151. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. T12S R32E PMWA

AP151

S27

1993


	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 55 lks. E. of trail road, bears N. and SE.
	S. 47°12' E., on line 151-152.
7.19	Point for AP 152.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T12S R32E
	PMWA
	S27 AP152
	`
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 48 lks. E. of trail road, bears NNW. and SSE.
	S. 28°41' E., on line 152-153.
4.48	Point for AP 153.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, encircled in a collar of stone, with brass cap mkd.
	T12S R32E
	PMWA
	AP153
	S27 \
	1993
	Deposit a magnet in a 1 \times 1 \times 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 41 lks. E. of trail road, bears NW. and SSE.
	S. 24°52' E., on line 153-154.
3.14	Point for AP 154.

1.31

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.




Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Cor. is located 32 lks. E. of trail road, bears N. and S.

S. 32°11' E., on line 154-155.

5.48 | Point for AP 155.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.



Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Cor. is located 55 lks. E. of trail road, bears NNW. and SSE.

S. 34°07' W., on line 155-156.

1.12 Point for AP 156, on the E and W centerline of sec. 27.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, encircled with a collar of stone, with brass cap mkd.

132

	1. 12 5., R. 32 E., Gila alk Bait River Periodal, Arizota
CHAINS	
	T12S R32E
	PMWA AP156 S27
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 27 lks. E. of trail road, bears N. and SSE., and 30 lks. W. of a wash, 18 lks wide, 1 ft. deep drains N.
	S.89°56'E., on the E and W centerline of sec. 27.
22.76	The 1/4 sec. cor. of secs. 26 and 27, hereinbefore described.
	In Sec. 26
	N.89049'E., on the E and W centerline of sec. 26.
19.91	The center W 1/16 sec. cor. of sec. 26, hereinbefore described.
	N.0005' W., on the N and S centerline of the NW 1/4 of sec. 26.
20.01	The true point for the NW 1/16 sec. cor. of sec. 26, hereinbefore described.
	N. 89040' E., on the E and W centerline of the NW 1/4 of sec. 26.
21.52	The N 1/16 sec. cor. of sec. 26 only, on the E. bdy. of the Tp., identical with the Arizona-New Mexico State Bdy., hereinbefore described.
	N. 0002' W., along the E. bdy. of sec. 26, identical with a portion of the Arizona-New Mexico State Bdy.
20.06	The closing cor. of secs. 23 and 26, hereinbefore described.
	In Sec. 23

	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	N. 0002' W., on the E. bdy. of sec. 23, identical with a portion of the Arizona-New Mexico State Bdy.
9.65	Mile Post 319, on the Arizona-New Mexico State Bdy., hereinbefore described.
	N. 0003' W., on the E. bdy. of sec. 23, identical with a portion of the boundary bet. Arizona and New Mexico.
43.58	The witness cor. for Mile Post 318, on the Arizona-New Mexico State Bdy., hereinbefore described.
	N. 0007' E. on the E. bdy. of sec. 23, identical with a portion of the Arizona-New Mexico State Bdy.
26.57	The closing cor. of secs. 14 and 23, hereinbefore described.
	In Sec. 14
	N. 0007' E., on the E. bdy. of sec. 14, identical with a portion of the Arizona-New Mexico State Bdy.
8.62	Mile Post 318, on the Arizona-New Mexico State Bdy., hereinbefore described.
72.40	AP 1, on the Arizona-New Mexico State Bdy., point of beginning.
	GENERAL DESCRIPTION
	This survey is located approximately 12 miles northeast of the town of San Simon, Arizona. The elevation ranges from 4000 feet to 5600 feet above sea level. The general terrain encompassed in this resurvey and metes-and-bounds survey is mountainous.
	The general drainage is to the southwest to the San Simon River, and the east, which then drains northwest to the Gila River basin.
	The soil is rocky and does not promote much usable vegetation. Various cacti, greasewood, and agave abound at lower and middle elevations, some cedar growth at upper elevations.

T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS

There are various range improvements in the township consisting of improved dirt roads, corrals and water tanks. Land usage consists primarily of grazing cattle. Other significant uses of the land would be for recreational and hunting purposes. Quail, javelina, rabbits and lizards are abundant in the area encompassed by this survey.

DESCRIPTION OF THE PELONCILLO MOUNTAINS WILDERNESS AREA BOUNDARY T. 12 S., R. 32 E., GILA AND SALT RIVER MERIDIAN, ARIZONA

The following description is for informational purposes only.

Beginning at Angle Point 1, on the Arizona-New Mexico State Bdy.

```
thence N. 56°57' W., 6.54 chs. dist., to Angle Point 2;
```

thence N. 30°07' E., 2.91 chs. dist., to Angle Point 3;

thence N. 30°20' E., 1.40 chs. dist., to Angle Point 4, on

the line bet. secs. 11 and 14.

thence N. 22°14' E., 8.84 chs. dist., to Angle Point 5, identical with the 317 Mile Post on the Arizona-New Mexico State Bdy.;

thence N. 0°04' W., on the Arizona-New Mexico State Bdy., 15.03 chs. dist., to Angle Point 6;

thence N. 40°18' W., 8.26 chs. dist., to Angle Point 7;

thence N. 38°21' W., 9.49 chs. dist., to Angle Point 8;

thence N. 31°24' W., 6.98 chs. dist., to Angle Point 9;

thence N. 24°36' W., 11.11 chs. dist., to Angle Point 10;

thence N. 30°10' W., 12.14 chs. dist., to Angle Point 11;

thence N. 33°00' W., 6.84 chs. dist., to Angle Point 12;

thence N. 66°17' W., 2.74 chs. dist., to Angle Point 13;

thence S. 49°11' W., 3.41 chs. dist., to Angle Point 14;

thence N. 63°08' W., 2.12 chs. dist., to Angle Point 15;

thence N. 15°03' E., 2.96 chs. dist., to Angle Point 16;

thence S. 88°15' W., 6.09 chs. dist., to Angle Point 17, on

the line bet. secs. 10 and 11;

thence N. 69°35' W., 12.42 chs. dist., to Angle Point 18;

thence N. 36°18' W., 4.82 chs. dist., to Angle Point 19;

thence S. 89°16' W., 5.04 chs. dist., to Angle Point 20;

thence S. 58°09' W., 2.93 chs. dist., to Angle Point 21;

thence S. 74°15' W., 13.96 chs. dist., to Angle Point 22;

thence S. 87°17' W., 7.12 chs. dist., to Angle Point 23;

thence N. 84°40' W., 14.06 chs. dist., to Angle Point 24;

thence S. 12°05' W., 17.71 chs. dist., to Angle Point 25;

thence S. 75°51' W., 6.96 chs. dist., to Angle Point 26; thence N. 41°41' W., 19.29 chs. dist., to Angle Point 27;

thence N. 0°40' W., 9.39 chs. dist., to Angle Point 28,

identical with the cor. of secs. 3, 4, 9 and 10;

•	T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	thence West, on the line bet. secs. 4 and 9, 40.02 chs. dist., to the 1/4 sec. cor. of secs. 4 and 9; thence North, on the N and S centerline of sec. 4, 79.71 chs. dist., to the 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.
	From the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.
	thence N. 89°47' E., on the line bet. secs. 6 and 7, 20.07 chs.
	dist. to the W 1/16 sec. cor. of secs. 6 and 7; thence S.0°05' W., on the N and S centerline of the NW 1/4 of sec. 7, 27.77 chs. dist., to Angle Point 29;
	thence N. 86°37' E., 3.29 chs. dist., to Angle Point 30; thence S. 7°38' E., 7.45 chs. dist., to Angle Point 31; thence S. 15°33' E., 5.19 chs. dist., to Angle Point 32, on
	the E and W centerline of sec. 7; thence N. 89°44' E., on the E and W centerline of sec. 7, 54.20
	chs. dist. to the 1/4 sec. cor. of secs. 7 and 8; thence South, on the line bet. secs. 7 and 8, 40.06 chs. dist. to the cor. of secs. 7, 8, 17 and 18;
	thence S. 0°02' E., on the line bet. secs. 17 and 18, 40.06 chs. dist., to the 1/4 sec. cor. of secs. 17 and 18; thence S. 89°47' W., on the E and W centerline of sec. 18, 59.95
	chs. dist., to the center W $1/16$ sec. cor. of sec. 18; thence S. 0°02' E., on the N and S center line of the SW $1/4$ of
	sec. 18, 40.00 chs. dist., to the W 1/16 sec. cor. of secs. 18 and 19; thence S. 89°46' W., on the line bet. secs. 18 and 19, 19.99 chs.
	dist., to the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp.; thence S. 0°01' E., on the line bet. secs. 19 and 24, 40.00 chs.
	dist., to the 1/4 sec. cor. of secs. 19 and 24; thence S. 0°02' E., on the line bet. secs. 19 and 24, 22.32 chs.
	dist., to Angle Point 33; thence S. 68°45' E., 4.03 chs. dist., to Angle Point 34; thence S. 87°34' E., 5.17 chs. dist., to Angle Point 35;
	thence S. 42°39' E., 11.92 chs. dist., to Angle Point 36; thence S. 68°30' E., 3.15 chs. dist., to Angle Point 37, on the N and S centerline of the SW 1/4 of sec. 19;
	thence N. 0°01' E. on the N and S centerline of the SW 1/4 of sec. 19, 14.06 chs. dist., to the SW 1/16 sec. cor. of sec.
	19; thence N. 89°43' E., on the E and W centerline of the SW 1/4 of sec. 19, 19.94 chs. dist., to the center S 1/16 sec. cor. of
	sec. 19; thence N. 89°44' E., on the E and W centerline of the SE 1/4 of sec. 19, 40.07 chs. dist., to the S 1/16 sec. cor. of secs.
	19 and 20; thence South, on the line bet. secs. 19 and 20, 8.43 chs. dist.,
	to Angle Point 38; thence N. 65°21' E., 6.35 chs. dist., to Angle Point 39;

```
CHAINS
        thence N. 31°04' E.,
                              3.45 chs. dist., to Angle Point 40;
        thence N. 55°51' E.,
                              4.16 chs. dist., to Angle Point 41;
        thence N. 39°13' E.,
                              6.92 chs. dist., to Angle Point 42;
                              3.90 chs. dist., to Angle Point 43;
                   7°24' E.,
        thence N.
        thence N. 39°53' E., 10.93 chs. dist., to Angle Point 44;
        thence N. 55°38' E., 3.26 chs. dist., to Angle Point 45;
        thence N. 72°14' E.,
                             8.68 chs. dist., to Angle Point 46;
        thence N. 77°00' E.,
                             5.63 chs. dist., to Angle Point 47;
        thence N. 52°07' E.,
                             4.25 chs. dist., to Angle Point 48;
                             4.23 chs. dist., to Angle Point 49;
        thence N. 61°48' E.,
        thence S. 52°14' E., 2.48 chs. dist., to Angle Point 50;
        thence S. 17°15' E., 5.92 chs. dist., to Angle Point 51;
        thence S. 78°43' W., 1.63 chs. dist., to Angle Point 52;
        thence N. 47°26' W., 6.52 chs. dist., to Angle Point 53;
        thence S. 46°44' W., 2.84 chs. dist., to Angle Point 54;
        thence S. 69°11' W.,
                             5.52 chs. dist., to Angle Point 55;
        thence S. 75°15' W., 10.66 chs. dist., to Angle Point 56;
        thence S. 53°52' W., 2.82 chs. dist., to Angle Point 57;
        thence S. 39°32' W., 10.18 chs. dist., to Angle Point 58;
        thence S. 11°33' W., 3.88 chs. dist., to Angle Point 59;
        thence S. 40°20' W., 7.93 chs. dist., to Angle Point 60;
        thence S. 55°13' W., 3.82 chs. dist., to Angle Point 61;
        thence S. 37°31' W., 4.63 chs. dist., to Angle Point 62;
        thence S. 71°01' W., 5.84 chs. dist., to Angle Point 63, on
             the line bet. secs. 19 and 20;
        thence South, on the line bet. secs. 19 and 20, 10.67 chs. dist.,
             to the cor. of secs. 19, 20, 29 and 30;
        thence S. 0°05' E., on the bet. secs. 29 and 30, 19.98 chs.
             dist., to the N 1/16 sec. cor. of secs. 29 and 30;
        thence S. 89°50' E., on the E and W centerline of the NW 1/4 of
             sec. 29, 39.87 chs. dist. to the center N 1/16 sec. cor. of
             sec. 29;
        thence S. 89°55' E., on the E and W centerline of the NE 1/4 of
             sec. 29, 20.07 chs. dist., to the NE 1/16 sec. cor. of sec.
        thence S. 0°06' E., on the N and S centerline of the NE 1/4 of
             sec. 29, 19.95 chs. dist., to the center E 1/16 sec. cor. of
             sec. 29;
        thence N. 89°54' W., on the E and W centerline of sec. 29, 20.08
             chs. dist. to Angle Point 64, identical with the center 1/4
             sec. cor. of sec. 29;
        thence S. 20°30' W., 2.35 chs. dist., to Angle Point 65;
        thence N. 67°16' W., 1.54 chs. dist., to Angle Point 66;
        thence N. 0°01' W., 1.61 chs. dist., to Angle Point 67, on
             the E and W centerline of sec. 29,
        thence N. 89°54' W., on the E and W centerline of sec. 29, 37.625
             chs. dist., to the 1/4 sec. cor. of secs. 29 and 30;
        thence N. 0°05' W., on the line bet. secs. 29 and 30, 4.83 chs.
             dist., to Angle Point 68;
        thence S. 52°20' W., 3.95 chs. dist., to Angle Point 69;
        thence S. 76°08' W., 10.24 chs. dist., to Angle Point 70, on
             the E and W centerline of sec. 30;
```

```
CHAINS
        thence S. 66°24' W., 5.26 chs. dist., to Angle Point 71;
        thence S. 81°16' W., 2.17 chs. dist., to Angle Point 72, on
             the N and S centerline of the SE 1/4 of sec. 30;
        thence S. 0°03' E., on the N and S centerline of the SE 1/4 of
             sec. 30, 22.15 chs. dist., to Angle Point 73;
        thence N. 76°54' W., 9.20 chs. dist., to Angle Point 74;
        thence S. 78°08' W., 11.31 chs. dist., to Angle Point 75, on
             the N and S centerline of sec. 30;
        thence N. 78°01' W., 9.35 chs. dist., to Angle Point 76;
        thence N. 69°24' W., 12.18 chs. dist., to Angle Point 77;
        thence S. 73°57' W., 6.28 chs. dist., to Angle Point 78;
        thence S. 1°03' E., 2.05 chs. dist., to Angle Point 79;
        thence S. 48°01' W., 6.07 chs. dist., to Angle Point 80;
        thence S. 42°21' W., 13.20 chs. dist., to Angle Point 81, on
             the line bet. secs. 25 and 30, on the W. bdy. of the Tp.,
             identical with Angle Point 16, T. 12 S.,
                                                        R. 31 E.;
        From Angle Point 82, on the line bet. secs. 31 and 36, on the W.
        bdy. of the Tp., identical with Angle Point 21, T. 12 S.,
        R. 31 E.
        thence S. 63°58' E., 2.66 chs. dist., to Angle Point 83;
        thence S. 88°41' E., 6.00 chs. dist., to Angle Point 84;
        thence N. 82°38' E., 10.13 chs. dist., to Angle Point 85;
        thence S. 71°06' E., 6.44 chs. dist., to Angle Point 86;
        thence S. 48°55' E., 4.15 chs. dist., to Angle Point 87;
        thence S. 32°17' E., 1.84 chs. dist., to Angle Point 88, on
             the E and W centerline of sec. 31;
        thence S. 39°24' E., 6.80 chs. dist., to Angle Point 89;
        thence S. 60°42' E., 4.05 chs. dist., to Angle Point 90;
        thence S. 55°50' E., 4.22 chs. dist., to Angle Point 91, on
             the N and S centerline of sec. 31;
        thence S. 51°46' E., 10.10 chs. dist., to Angle Point 92;
        thence S. 63°20' E., 3.80 chs. dist., to Angle Point 93;
        thence S. 88°49' E., 7.07 chs. dist., to Angle Point 94;
        thence S. 73°34' E., 1.69 chs. dist., to Angle Point 95, on
             the N and S centerline of the SE 1/4 ofsec. 31;
        thence S. 73°04' E., 6.08 chs. dist., to Angle Point 96, on
             the E and W centerline of the SE 1/4 of sec. 31;
        thence N. 89°57' E., on the E and W centerline of the SE 1/4
             of sec. 31, 14.20 chs. dist., to the S 1/16 sec. cor. of
             secs. 31 and 32;
        thence South, on the line bet. secs. 31 and 32, 20.03 chs. dist.,
             to the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the
        thence S. 89°59' W., on the line bet. secs. 6 and 31, 20.01 chs.
             dist., to the E 1/16 sec. cor. of secs. 6 and 31;
        thence North, on the N and S centerline of the SE 1/4 of sec. 31,
             20.02 chs. dist., to the SE 1/16 sec. cor. of sec. 31;
        thence N. 89°57' E., on the E and W centerline of sec. 31,
             3.17 chs. dist., to Angle Point 97;
```

```
CHAINS
        thence N. 75°53' W., 3.27 chs. dist., to Angle Point 98, on
             the N and S centerline of the SE 1/4 of sec. 31;
        thence N. 81°15' W., 1.31 chs. dist., to Angle Point 99;
        thence N. 87°18' W., 7.39 chs. dist., to Angle Point 100;
        thence N. 67°19' W., 4.53 chs. dist., to Angle Point 101;
        thence N. 50°14' W., 9.32 chs. dist., to Angle Point 102, on
             the N and S centerline of Sec. 31;
        thence N. 56°37' W., 4.77 chs. dist., to Angle Point 103;
        thence N. 58°50' W., 4.20 chs. dist., to Angle Point 104;
        thence N. 36°39' W., 7.62 chs. dist., to Angle Point 105, on
             the E and W centerline of sec. 31;
        thence N. 45°47' W., 1.26 chs. dist., to Angle Point 106;
        thence N. 48°55' W., 4.03 chs. dist., to Angle Point 107;
        thence N. 72°43' W., 5.92 chs. dist., to Angle Point 108;
        thence S. 82°14' W., 9.86 chs. dist., to Angle Point 109;
        thence N. 87°02' W., 6.77 chs. dist., to Angle Point 110;
        thence N. 77°17' W., 1.79 chs. dist., to Angle Point 111, on
             the line bet. secs. 31 and 36, on the W. bdy. of the Tp.,
             identical with Angle Point 22, T. 12 S., R. 31 E.
        From Angle Point 95, T. 13 S., R. 32 E., on the line bet. secs. 4
        and 33, on the S. bdy. of the Tp.
        thence East, on the line bet. secs. 4 and 33, 8.70 chs. dist. to
             the E 1/16 sec. cor. of secs. 4 and 33;
        thence N. 0°04' W., on the N and S centerline of the SE 1/4 of
             sec. 33, 20.02 chs. dist. to the SE 1/16 sec. cor. of sec.
        thence S. 89°59' E.; on the E and W centerline of SE 1/4 of
             sec. 33, 19.96 chs. dist., to the S 1/16 sec. cor. of secs.
        thence N. 89°59 E., on the E and W centerline of the SW 1/4 of
             sec. 34, 19.98 chs. dist., to the SW 1/16 sec. cor. of
             sec. 34;
        thence S. 0°03' E., on the N and S centerline of the SW 1/4 of
             sec. 34, 20.01 chs. dist., to the W 1/16 of secs. 3 and 34,
             on the S. bdy. of the Tp.;
        thence N. 89°59' E., on the line bet. secs. 3 and 34, 19.985 chs.
             dist., to the 1/4 sec. cor. of secs. 3 and 34;
        thence N. 89°57' E., on the line bet. secs. 3 and 34, 20.00 chs.
             dist., to the E 1/16 sec. cor. of secs. 3 and 34;
        thence N. 0°03' W., on the N and S centerline of the SE 1/4 of
             sec. 34, 40.00 chs. dist., to the center E 1/16 sec. cor. of
             sec. 34;
        thence N. 89°59' E., on the E and W centerline of sec. 34,
             20.01 chs. dist., to the 1/4 sec. cor. of secs. 34 and 35;
        thence N. 0°10 E., on the line bet. secs. 34 and 35, 39.91 chs.
             dist., to the cor. of secs. 26, 27, 34 and 35;
        thence N. 89°58' E., on the line bet. secs. 26 and 35, 20.01 chs.
             dist., to the W 1/16 sec. cor. of secs. 26 and 35;
```

139

```
CHAINS
        thence N. 0°08' E., on the N and S centerline of the SW 1/4 of
             sec. 26, 20.02 chs. dist., to the SW 1/16 sec. cor. of sec.
             26;
        thence S. 89°54' W., on the E and W centerline of the SW 1/4 of
             sec. 26, 19.96 chs. dist., to the S 1/16 sec. cor. of
             secs. 26 and 27;
        thence S. 89°57' W., on the E and W centerline of the SE 1/4 of
             sec. 27, 1.38 chs. dist., to Angle Point 112;
        thence S. 41°59' W., 3.25 chs. dist., to Angle Point 113;
        thence N. 80°04' W., 5.06 chs. dist., to Angle Point 114;
        thence N. 69°47' W., 4.45 chs. dist., to Angle Point 115, on
             the E and W centerline of the SE 1/4 of sec. 27;
        thence S. 89°57' W., on the E and W centerline of the SE 1/4 of
             sec. 27, 27.51 chs. dist., to the center S 1/16 sec. cor. of
             sec. 27:
        thence N. 89°50' W., on the E and W centerline of the SW 1/4 of
             sec. 27, 20.05 chs. dist., to the SW 1/16 sec. cor of sec.
        thence N. 0°03' W., on the N and S centerline of the SW 1/4 of
             sec. 27, 20.05 chs. dist., to the center W 1/16 sec. cor. of
             sec. 27;
        thence S. 89°56' E., on the E and W centerline of sec. 27,
             36.77 chs. dist., to Angle Point 116;
        thence N. 22°08' E., 0.94 chs. dist., to Angle Point 117;
        thence N. 31°49' W., 8.09 chs. dist., to Angle Point 118;
        thence N. 29°27' W., 4.94 chs. dist., to Angle Point 119;
        thence N. 52°32' W., 5.94 chs. dist., to Angle Point 120;
        thence N. 12°58' W.,
                             4.57 chs. dist., to Angle Point 121;
        thence N. 34°45' W.,
                              7.90 chs. dist., to Angle Point 122, on
             the N and S centerline of sec. 27;
        thence N. 44°41' W.,
                              5.02 chs. dist., to Angle Point 123;
        thence N. 52°54' W.,
                             3.51 chs. dist., to Angle Point 124;
        thence N. 0°08' E.,
                             3.43 chs. dist., to Angle Point 125;
        thence N. 44°52' W.,
                              1.90 chs. dist., to Angle Point 126;
        thence N. 25°05' W.,
                              3.18 chs. dist., to Angle Point 127, on
             the line bet. secs. 22 and 27;
        thence N. 48°06' W.,
                             5.35 chs. dist., to Angle Point 128;
        thence N. 24°44' W.,
                              5.54 chs. dist., to Angle Point 129;
        thence N. 6°51' E.,
                             4.84 chs. dist., to Angle Point 130;
        thence N. 15°31' W.,
                             5.08 chs. dist., to Angle Point 131;
        thence N. 10°44' W.,
                             3.72 chs. dist., to Angle Point 132;
        thence N. 51°54' W.,
                              9.85 chs. dist.; to Angle Point 133;
        thence N. 30°18' E., 12.36 chs. dist.; to Angle Point 134;
        thence S. 79°50' E., 5.52 chs. dist.; to Angle Point 135;
        thence S. 29°27' W., 12.88 chs. dist., to Angle Point 136;
        thence S. 41°01' E., 3.11 chs. dist., to Angle Point 137;
        thence S. 43°09' E.,
                             2.95 chs. dist., to Angle Point 138;
        thence S. 6°36' E., 3.22 chs. dist., to Angle Point 139;
        thence S. 12°02' E., 5.50 chs. dist., to Angle Point 140;
        thence S. 9°20' W., 5.21 chs. dist., to Angle Point 141;
        thence S. 34°21' E.,
                             4.68 chs. dist., to Angle Point 142;
```

```
CHAINS
        thence S. 39°30' E.,
                              5.75 chs. dist., to Angle Point 143, on
             the line bet. secs. 22 and 27;
        thence S. 31°41' E.,
                              2.27 chs. dist., to Angle Point 144;
        thence S. 50°12' E., 2.83 chs. dist., to Angle Point 145;
        thence S. 8°42' W., 3.67 chs. dist., to Angle Point 146;
        thence S. 54°27' E.,
                              2.78 chs. dist., to Angle Point 147;
        thence S. 49°01' E.,
                              4.10 chs. dist., to Angle Point 148 on
             the N and S centerline of sec. 27;
        thence S. 46°24' E.,
                              3.08 chs. dist., to Angle Point 149;
        thence S. 31°25' E., 6.89 chs. dist., to Angle Point 150;
        thence S. 10°32' E.,
                             3.10 chs. dist., to Angle Point 151;
        thence S. 47°12' E., 7.19 chs. dist., to Angle Point 152;
        thence S. 28°41' E., 4.48 chs. dist., to Angle Point 153;
        thence S. 24°52' E., 3.14 chs. dist., to Angle Point 154;
        thence S. 32°11' E., 5.48 chs. dist., to Angle Point 155
        thence S. 34°07' W., 1.12 chs. dist., to Angle Point 156, on
             the E and W centerline of sec. 27;
        thence S. 89°56' E., on the E and W centerline of sec. 27,
             22.76 chs. dist., to the 1/4 sec. cor. of secs. 26 and 27;
        thence N. 89°49' E., on the E and W centerline of sec. 26,
             19.91 chs. dist., to the center W 1/16 sec. cor. of sec. 26;
        thence N. 0°05' W., on the N and S centerline of the NW 1/4 of
             sec. 26, 20.01 chs. dist., to the NW 1/16 sec. cor. of
             sec. 26;
        thence N. 89°40' E., on the E and W centerline of NW 1/4 of
             sec. 26, 21.52 chs. dist., to the N 1/16 sec. cor. of sec.
             26, on the Arizona-New Mexico State Bdy.;
        thence N. 0°02' W., on the Arizona-New Mexico State Bdy., 29.71
             chs. dist., to Mile Post 319;
        thence N. 0°03' W., on the Arizona-New Mexico State Bdy., 43.58
             chs. dist., to the witness cor. for Mile Post 318;
        thence N. 0°07' E., on the Arizona-New Mexico State Bdy., 35.19
             chs. dist., to Mile Post 318;
        thence N. 0°07' E., on the Arizona-New Mexico State Bdy., 63.78
             chs. dist., to AP 1, point of beginning.
```

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Daniel R. Muth	Surveyor in Training
Cheryl A. Baier	Surveying Technician
Gordon R. Bubel	Surveying Technician
Steven R. Buchanan	Surveying Technician
Ted E. Cazier	Surveying Technician
Jeff A. Hill	Surveying Technician
Mark R. Searles	Surveying Technician
Kevin C. Berridge	Surveying Technician
Lawrence T. Kempe	Surveying Technician

CERTIFICATE OF SURVEY

We, Robert C. Umbanhowar and Stephen K. Hansen, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 6th day of January, 1992, We have dependently resurveyed the Arizona-New Mexico State Boundary from Mile Post 316 to Mile Post 321, and portions of the south boundary and subdivisional lines, the subdivision of certain sections, and the mete-and-bounds survey of the Peloncillo Mountains Wilderness Area Boundary, in Township 12 South, Range 32 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

6/14/94	Robert C. Cumhanhawan
/(Date)	(Cadastral Surveyor)
(Date)	Stephe K. Hansen (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Arizona State Office Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the Arizona-New Mexico State Boundary from Mile Post 316 to Mile Post 321, and portions of the south boundary and subdivisional lines, the subdivision of certain sections, and the mete-and-bounds survey of the Peloncillo Mountains Wilderness Area Boundary, in Township 12 South, Range 32 East, of the Gila and Salt River Meridian, in the State of Arizona, executed by Robert C. Umbanhowar and Stephen K. Hansen, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

JUN 2 2 1994	Jame P. Helley	
(Date)	(Chief Cadastral Surveyor of Arizona)	
	SERVICE OF INDANGORIDA	
	EXTIFICATE OF TRANSCRIPT	
I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 12 S., R. 32 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.		
(Det a)		
(Bate)	(Chief Cadastral Surveyor of Arizona)	