BOOK 5409 ORIGINAL

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

	DEPENDENT RESURVEY OF A PORTION OF
	THE SUBDIVISIONAL LINES,
	THE SUBDIVISION OF SEC. 9,
	AND THE METES-AND-BOUNDS SURVEY
	OF THE
	PELONCILLO MOUNTAINS WILDERNESS AREA BOUNDARY
	IN TOWNSHIP 13 SOUTH, RANGE 32 EAST
Of the _ In the State of _	Gila and Salt River Meridian, Arizona
	EXECUTED BY Robert C. Umbanhowar, Cadastral Surveyor

Under Special Instructions dated <u>January 6, 1992</u>, approved <u>January 6, 1992</u>, which provided for the surveys included under Group Number <u>739</u> and assignment instructions dated August 6, 1992.

Survey commenced November 9, 1992
Survey completed June 13, 1993

INDEX DIAGRAM

TOWNSHIP 13 SOUTH , RANGE 32 EAST ,

		~			
6 1			5 3	2	1
7 1	12 8	8 9	5 10	11	12
18 10	10 0 17	7 16	15	14	13
19	20	6 21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision Section 9 ----- 14-16 Metes-and-Bounds PMWA ----- 16-53

T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, the subdivision of section 9, and the metes-and-bounds survey of the Peloncillo Mountain Wilderness Area Boundary, in Township 13 South, Range 32 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this resurvey is as follows: R. C. Powers surveyed the west boundary in 1883. William B. Kimmel surveyed a portion of the north boundary in 1914. Guy R. Veal and Karl L. Siebecker resurveyed the west boundary and surveyed a portion of the north boundary and the subdivisional lines in 1919.

The survey was executed in accordance with the specifications as set forth in the <u>Manual of Surveying Instructions</u>, 1973, and the Special Instructions dated January 6, 1992, for Group No. 739, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The purpose of this survey was to determine the boundary of the Peloncillo Mountains Wilderness Area.

The directions of all lines were determined by direct hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with a Pentax PTS-iii05 Total Station.

The geographic position of the corner of sections 3, 4, 33 and 34 on the N. bdy. of the Tp., as determined from a tie made to U.S. Geological Survey triangulation station "Doubtful, 1948", located in the SW quarter of section 23, Township 12 South, Range 32 East, is as follows:

Latitude: 32°20'21.34" N. Longitude: 109°04'24.26" W. NAD 27

The mean magnetic declination as taken from USGS quadrangle map ENGINE MOUNTAIN, ARIZ., is $11\ 1/2^{\circ}$ E.

	1. 13 5., R. 32 E., Gila and Sait River Meridian, Arizona
CHAINS	Restoring the survey executed by Guy R. Veal and Karl L. Siebecker in 1921
	Beginning at the cor. of secs. 15, 16, 21 and 22, monumented with an iron post, 2 in. diam., firmly set, projecting 30 ins. above ground, in a scattered mound of stone, with brass cap mkd. T13S R32E S16 S15 S21 S22 1919.
	Add the marks 1993 to the brass cap.
	Rebuild supporting mound of stone, 4 ft. base, to top.
	N. 0°01' E., bet. secs. 15 and 16.
39.97	The 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. 1/4 S16 S15 1919.
	Add the marks T13S R32E 1993 the brass cap.
	N. 0°05' E., beginning new measurement.
39.89	The cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2 in. diam., loosely set, projecting 26 ins. above ground, with brass cap mkd. T13S R32E S9 S10 S16 S15 1919, from which bearing trees of unknown origin
	A juniper, 14 ins. diam., bears N. 19 1/4° E., 12 lks. dist., mkd. T13S R32E S10 BT.
	A juniper, 13 ins. diam., bears N. 81 1/2° W., 31 lks. dist., with marks T13S R32E S9 BT barely visible.
	Add the marks 1993 to the brass cap.
	Rebuild supporting mound of stone, 5 ft. base, to top.
	N. 0°01' E., bet. secs. 9 and 10.
40.25	The 1/4 sec. cor. of secs. 9 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, in a scattered mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. 1/4 S9 S10 1919.
	Add the marks T13S R32E 1993 to the brass cap.
	Rebuild supporting mound of stone, 4 1/2 ft. base, to top.

	T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	N. 0°13' W., beginning new measurement.
20.01	Point for the N 1/16 sec. cor. of secs. 9 and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.
	T13S R32E N 1/16 S9 S10 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the stainless steel post.
40.02	Point for the cor. of secs. 3, 4, 9 and 10, at proportionate distance; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T13S R32E S4 S3
	S9 S10 1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	From the 1/4 sec. cor. of secs. 3 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 30 ins. above ground, in a scattered mound of stone, with brass cap mkd. 1/4 S3 S10 1919.
	Add the marks T13S R32E 1993 to the brass cap.
	Rebuild supporting mound of stone, 4 ft. base, to top.
	N. 89°57' W., bet. secs. 3 and 10.
39.95	The cor. of secs. 3, 4, 9 and 10.
	N. 0°05' E., bet. secs. 3 and 4.
40.01	Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original cor.

CHAINS

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled in a collar of stone, with brass cap mkd.

T13S R32E 1/4 S4 | S3 1993

Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Cor. located in wash, 20 lks. wide, 2 ft. deep, drains SE.

80.02

The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. T12S R32E S33 S34 S4 S3 T13S 1919 1993, as described in the field notes of the dependent resurvey of the S. bdy., T. 12 S., R. 32 E., executed concurrently under this same group.

From this cor. point, U.S.G.S. triangulation station "Doubtful 1948", with published latitude of 32° 22' 29.334" N. and longitude of 109° 03' 22.053" W., NAD 27, bears N. 22° 24' 50" E. (forward bearing), 212.01 chs. distant, with a chiseled "x" on a boulder.

From the cor. of secs. 15, 16, 21 and 22.

N. 89°51' W., bet. secs. 16 and 21.

39.96

The 1/4 sec. cor. of secs. 16 and 21, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. S16 1/4 S21 1919.

Add the marks T13S R32E 1993 to the brass cap.

N. 89°51' W., beginning new measurement.

40.12

The cor. of secs. 16, 17, 20 and 21, monumented with an iron post, 2 ins. diam., firmly set, projecting 26 ins. above ground, in a scattered mound of stone, with brass cap mkd. T13S R32E S17 S16 S20 S21 1919, from which the original bearing tree

A cedar stump bears N. 82 1/4° W., 86 lks. dist., no marks visible. (Record: 97 lks. dist.)

Add the marks 1993 to the brass cap.

	1. 13 S., R. 32 E., GIIA AND SAIL RIVER METIDIAN, AFIZONA
CHAINS	Rebuild supporting mound of stone, 4 ft. base, to top.
	N. 0°16' E., bet. secs. 16 and 17.
39.08	The witness 1/4 sec. cor. of secs. 16 and 17, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, with a mound of stone to the W., 2 ft. base, 1/2 ft. high, with brass cap mkd. 1/4 S17 S16 WC 1919.
	Add the marks T13S R32E 1993 to the brass cap.
	Cor. is located 11 lks. E. of wash, 104 lks. wide, 4.5 ft. deep, drains S.
	N. 0°13' E., beginning new measurement.
0.80	True point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate distance. Point falls in a wash, 104 lks. wide, 4.5 ft. deep, drains SSE., impractical to monument.
26.77	Point for AP 61, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
40.73	The cor. of secs. 8, 9, 16 and 17, monumented with an iron post, 2 ins. diam., firmly set, projecting 26 ins. above ground, in a scattered mound of stone, with brass cap mkd. T13S R32E S8 S9 S17 S16 1919.
	Add marks 1993 to the brass cap.
	Rebuild supporting mound of stone, 5 ft. base, to top.
	From the cor. of secs. 9, 10, 15 and 16.
	N. 89°55' W., bet. secs. 9 and 16.
39.71	The 1/4 sec. cor. of secs. 9 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above ground, with a mound of stone to the N., 2 1/2 ft. base, 1/2 ft high, with brass cap mkd. S9 S16 1919.
	Add marks T13S R32E 1/4 1993.
	N. 89°52' W., beginning new measurement.
34.24	Point for AP 65, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.

	T. 13 S., R. 32 E., Gila and Sait River Meridian, Arizona
CHAINS 40.09	The cor. of secs. 8, 9, 16 and 17.
	N. 0°05' W., bet. secs. 8 and 9.
39.87	The 1/4 sec. cor. of secs. 8 and 9, monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above ground, with a mound of stone to the W., 2 ft. base, 1 ft. high, with brass cap mkd. 1/4 S8 S9 1919.
	Add the marks T13S R32E 1993 to the brass cap.
	N. 0°01 W., beginning new measurement.
40.24	The true point for the cor. of secs. 4, 5, 8 and 9, at proportionate distance. Point falls on the face of a steep rock face, sloping W., impracticable to monument.
	From this point, the witness cor. for secs. 4, 5, 8 and 9 bears N. 0°01' W., 2.40 chs. distance, monumented with an iron post, 2 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. T13S R32E S5 S4 S8 S9 WC 1919, from which the original bearing trees
	A scrub oak, 8 ins. diam., bears N. 29 3/4° E., 49 lks. dist, with healed blaze. (Record N. 31 1/4° E., 48 lks. dist.)
	A Utah Juniper, 12 ins. diam., bears S. 72 1/2° E., 50 lks. dist, with no marks visible.
	A scrub oak stump, 10 ins. diam, bears S. 57° W., 63 1/2 lks. dist., mkd. WC T13S R32E S8 BT. (Record 65 lks. dist.)
	A Utah Juniper 30 in. root crown diam., bears N. 1 1/4° W., 147 lks. dist., mkd. WC T13S R32E S5 BT.
	Add the marks 1993 to the brass cap.
	From the cor. of secs. 3, 4, 9 and 10.
	N. 89°57' W., bet. 4 and 9.
16.45	Point for AP 82, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
19.955	Point for the E 1/16 sec. cor. of secs. 4 and 9.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd. T138 R32E PMMA S 4 E 1/16 — S 9 1993 Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post. The 1/4 sec. cor. of secs. 4 and 9, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. 1/4 S4 S9 1919, from which the original bearing tree A cedar, 8 ins. diam., bears N. 63° W., 222 lks. dist., with no marks visible. Add the marks T13S R32E 1993 to the brass cap. S. 89°57' W., beginning new measurement. The true point for the cor. of secs. 4, 5, 8 and 9. From the cor. of secs. 16, 17, 20 and 21. N. 89°55' W., bet. secs. 17 and 20. The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, with a mound of stone to the N., 2 ft. base, 1/2 ft. high, with brass cap mkd. 1/4 S17 S20 1919. Add the marks T13S R32E 1993 to the brass cap. N. 89°57' W., beginning new measurement. The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 in. diam., firmly set, projecting 18 ins. above ground, with a scattered mound of stone to the W. Rebuild mound of stone to W., 3 ft. base, 2 ft. high. Add the marks 1993 to the brass cap.		
PMMA 8 4 E 1/16 — S 9 1993 Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post. 39.91 The 1/4 sec. cor. of secs. 4 and 9, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. 1/4 S4 S9 1919, from which the original bearing tree A cedar, 8 ins. diam., bears N. 63* W., 222 lks. dist., with no marks visible. Add the marks T13S R32E 1993 to the brass cap. S. 89*57' W., beginning new measurement. The true point for the cor. of secs. 4, 5, 8 and 9. From the cor. of secs. 16, 17, 20 and 21. N. 89*55' W., bet. secs. 17 and 20. The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, with a mound of stone to the N., 2 ft. base, 1/2 ft. high, with brass cap mkd. 1/4 S17 S20 1919. Add the marks T13S R32E 1993 to the brass cap. N. 89*57' W., beginning new measurement. 40.09 The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 in. diam., firmly set, projecting 18 ins. above ground, with a scattered mound of stone to the W. Rebuild mound of stone to W., 3 ft. base, 2 ft. high.	CHAINS	
Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post. The 1/4 sec. cor. of secs. 4 and 9, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. 1/4 S4 S9 1919, from which the original bearing tree A cedar, 8 ins. diam., bears N. 63° W., 222 lks. dist., with no marks visible. Add the marks T13S R32E 1993 to the brass cap. S. 89°57' W., beginning new measurement. The true point for the cor. of secs. 4, 5, 8 and 9. From the cor. of secs. 16, 17, 20 and 21. N. 89°55' W., bet. secs. 17 and 20. The 1/4 sec. cor. of secs. 17 and 20. The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, with a mound of stone to the N., 2 ft. base, 1/2 ft. high, with brass cap mkd. 1/4 S17 S20 1919. Add the marks T13S R32E 1993 to the brass cap. N. 89°57' W., beginning new measurement. 40.09 The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 in. diam., firmly set, projecting 18 ins. above ground, with a scattered mound of stone to the W. Rebuild mound of stone to W., 3 ft. base, 2 ft. high.		T13S R32E
Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post. The 1/4 sec. cor. of secs. 4 and 9, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. 1/4 S4 S9 1919, from which the original bearing tree A cedar, 8 ins. diam., bears N. 63* W., 222 lks. dist., with no marks visible. Add the marks T13S R3ZE 1993 to the brass cap. S. 89*57' W., beginning new measurement. The true point for the cor. of secs. 4, 5, 8 and 9. From the cor. of secs. 16, 17, 20 and 21. N. 89*55' W., bet. secs. 17 and 20. The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, with a mound of stone to the N., 2 ft. base, 1/2 ft. high, with brass cap mkd. 1/4 S17 S20 1919. Add the marks T13S R3ZE 1993 to the brass cap. N. 89*57' W., beginning new measurement. The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 in. diam., firmly set, projecting 18 ins. above ground, with a scattered mound of stone to the W. Rebuild mound of stone to W., 3 ft. base, 2 ft. high.		PMWA
Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post. 39.91 The 1/4 sec. cor. of secs. 4 and 9, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. 1/4 S4 S9 1919, from which the original bearing tree A cedar, 8 ins. diam., bears N. 63* W., 222 lks. dist., with no marks visible. Add the marks T13S R32E 1993 to the brass cap. S. 89*57' W., beginning new measurement. The true point for the cor. of secs. 4, 5, 8 and 9. From the cor. of secs. 16, 17, 20 and 21. N. 89*55' W., bet. secs. 17 and 20. The 1/4 sec. cor. of secs. 17 and 20. The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, with a mound of stone to the N., 2 ft. base, 1/2 ft. high, with brass cap mkd. 1/4 S17 S20 1919. Add the marks T13S R32E 1993 to the brass cap. N. 89*57' W., beginning new measurement. 40.09 The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 in. diam., firmly set, projecting 18 ins. above ground, with a scattered mound of stone to the W., 3 ft. base, 2 ft. high.		
Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post. 39.91 The 1/4 sec. cor. of secs. 4 and 9, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. 1/4 S4 S9 1919, from which the original bearing tree A cedar, 8 ins. diam., bears N. 63° W., 222 lks. dist., with no marks visible. Add the marks T13S R32E 1993 to the brass cap. S. 89°57' W., beginning new measurement. The true point for the cor. of secs. 4, 5, 8 and 9. From the cor. of secs. 16, 17, 20 and 21. N. 89°55' W., bet. secs. 17 and 20. The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, with a mound of stone to the N., 2 ft. base, 1/2 ft. high, with brass cap mkd. 1/4 S17 S20 1919. Add the marks T13S R32E 1993 to the brass cap. N. 89°57' W., beginning new measurement. 40.09 The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 in. diam., firmly set, projecting 18 ins. above ground, with a scattered mound of stone to the W. Rebuild mound of stone to W., 3 ft. base, 2 ft. high.		,
the stainless steel post. The 1/4 sec. cor. of secs. 4 and 9, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. 1/4 S4 S9 1919, from which the original bearing tree A cedar, 8 ins. diam., bears N. 63° W., 222 lks. dist., with no marks visible. Add the marks T13S R32E 1993 to the brass cap. S. 89°57' W., beginning new measurement. 39.81 The true point for the cor. of secs. 4, 5, 8 and 9. From the cor. of secs. 16, 17, 20 and 21. N. 89°55' W., bet. secs. 17 and 20. The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, with a mound of stone to the N., 2 ft. base, 1/2 ft. high, with brass cap mkd. 1/4 S17 S20 1919. Add the marks T13S R32E 1993 to the brass cap. N. 89°57' W., beginning new measurement. The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 in. diam., firmly set, projecting 18 ins. above ground, with a scattered mound of stone to the W. Rebuild mound of stone to W., 3 ft. base, 2 ft. high.		
1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. 1/4 S4 S9 1919, from which the original bearing tree A cedar, 8 ins. diam., bears N. 63° W., 222 lks. dist., with no marks visible. Add the marks T13S R32E 1993 to the brass cap. S. 89°57' W., beginning new measurement. The true point for the cor. of secs. 4, 5, 8 and 9. From the cor. of secs. 16, 17, 20 and 21. N. 89°55' W., bet. secs. 17 and 20. The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, with a mound of stone to the N., 2 ft. base, 1/2 ft. high, with brass cap mkd. 1/4 S17 S20 1919. Add the marks T13S R32E 1993 to the brass cap. N. 89°57' W., beginning new measurement. The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 in. diam., firmly set, projecting 18 ins. above ground, with a scattered mound of stone to the W. Rebuild mound of stone to W., 3 ft. base, 2 ft. high.		
with no marks visible. Add the marks T13S R32E 1993 to the brass cap. S. 89°57' W., beginning new measurement. The true point for the cor. of secs. 4, 5, 8 and 9. From the cor. of secs. 16, 17, 20 and 21. N. 89°55' W., bet. secs. 17 and 20. The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, with a mound of stone to the N., 2 ft. base, 1/2 ft. high, with brass cap mkd. 1/4 S17 S20 1919. Add the marks T13S R32E 1993 to the brass cap. N. 89°57' W., beginning new measurement. 40.09 The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 in. diam., firmly set, projecting 18 ins. above ground, with a scattered mound of stone to the W. Rebuild mound of stone to W., 3 ft. base, 2 ft. high.	39.91	1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. 1/4 S4 S9 1919, from which the original bearing
S. 89°57' W., beginning new measurement. 39.81 The true point for the cor. of secs. 4, 5, 8 and 9. From the cor. of secs. 16, 17, 20 and 21. N. 89°55' W., bet. secs. 17 and 20. The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, with a mound of stone to the N., 2 ft. base, 1/2 ft. high, with brass cap mkd. 1/4 S17 S20 1919. Add the marks T13S R32E 1993 to the brass cap. N. 89°57' W., beginning new measurement. 40.09 The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 in. diam., firmly set, projecting 18 ins. above ground, with a scattered mound of stone to the W. Rebuild mound of stone to W., 3 ft. base, 2 ft. high.		
The true point for the cor. of secs. 4, 5, 8 and 9. From the cor. of secs. 16, 17, 20 and 21. N. 89°55' W., bet. secs. 17 and 20. The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, with a mound of stone to the N., 2 ft. base, 1/2 ft. high, with brass cap mkd. 1/4 S17 S20 1919. Add the marks T13S R32E 1993 to the brass cap. N. 89°57' W., beginning new measurement. 40.09 The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 in. diam., firmly set, projecting 18 ins. above ground, with a scattered mound of stone to the W. Rebuild mound of stone to W., 3 ft. base, 2 ft. high.		Add the marks T13S R32E 1993 to the brass cap.
From the cor. of secs. 16, 17, 20 and 21. N. 89°55' W., bet. secs. 17 and 20. The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, with a mound of stone to the N., 2 ft. base, 1/2 ft. high, with brass cap mkd. 1/4 S17 S20 1919. Add the marks T13S R32E 1993 to the brass cap. N. 89°57' W., beginning new measurement. The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 in. diam., firmly set, projecting 18 ins. above ground, with a scattered mound of stone to the W. Rebuild mound of stone to W., 3 ft. base, 2 ft. high.		S. 89°57' W., beginning new measurement.
N. 89°55' W., bet. secs. 17 and 20. The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, with a mound of stone to the N., 2 ft. base, 1/2 ft. high, with brass cap mkd. 1/4 S17 S20 1919. Add the marks T13S R32E 1993 to the brass cap. N. 89°57' W., beginning new measurement. The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 in. diam., firmly set, projecting 18 ins. above ground, with a scattered mound of stone to the W. Rebuild mound of stone to W., 3 ft. base, 2 ft. high.	39.81	The true point for the cor. of secs. 4, 5, 8 and 9.
39.94 The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, with a mound of stone to the N., 2 ft. base, 1/2 ft. high, with brass cap mkd. 1/4 S17 S20 1919. Add the marks T13S R32E 1993 to the brass cap. N. 89°57' W., beginning new measurement. 40.09 The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 in. diam., firmly set, projecting 18 ins. above ground, with a scattered mound of stone to the W. Rebuild mound of stone to W., 3 ft. base, 2 ft. high.		From the cor. of secs. 16, 17, 20 and 21.
post, 1 in. diam., firmly set, projecting 24 ins. above ground, with a mound of stone to the N., 2 ft. base, 1/2 ft. high, with brass cap mkd. 1/4 S17 S20 1919. Add the marks T13S R32E 1993 to the brass cap. N. 89°57' W., beginning new measurement. The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 in. diam., firmly set, projecting 18 ins. above ground, with a scattered mound of stone to the W. Rebuild mound of stone to W., 3 ft. base, 2 ft. high.		N. 89°55' W., bet. secs. 17 and 20.
N. 89°57' W., beginning new measurement. 40.09 The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 in. diam., firmly set, projecting 18 ins. above ground, with a scattered mound of stone to the W. Rebuild mound of stone to W., 3 ft. base, 2 ft. high.	39.94	post, 1 in. diam., firmly set, projecting 24 ins. above ground, with a mound of stone to the N., 2 ft. base, 1/2 ft. high, with
The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 in. diam., firmly set, projecting 18 ins. above ground, with a scattered mound of stone to the W. Rebuild mound of stone to W., 3 ft. base, 2 ft. high.		Add the marks T13S R32E 1993 to the brass cap.
post, 2 in. diam., firmly set, projecting 18 ins. above ground, with a scattered mound of stone to the W. Rebuild mound of stone to W., 3 ft. base, 2 ft. high.		N. 89°57' W., beginning new measurement.
	40.09	post, 2 in. diam., firmly set, projecting 18 ins. above ground,
Add the marks 1993 to the brass cap.		Rebuild mound of stone to W., 3 ft. base, 2 ft. high.
		Add the marks 1993 to the brass cap.

	To be seen and the
CHAINS	N. 89°58' W., bet. secs. 18 and 19.
39.99	The 1/4 sec. cor. of secs. 18 and 19, monumented with a iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, encircled in a collar of stone, 24 ins. diam., with brass cap mkd. 1/4 S18 S19 1919.
	Add the marks 1993 to the brass cap.
	N. 89°57' W., beginning new measurement.
39.00	The cor. of secs. 18 and 19 only, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam. firmly set, projecting 8 ins. above ground with a mound of stone to the E., 3 ft. base, 2 ft. high, with brass cap mkd. T13S R32E S18 S19 1919.
	Add the marks 1993 to the brass cap.
	Cor. is located in a barbed wire fence, 4 strand, bears N. and S.
	From the cor. of secs. 17, 18, 19 and 20.
	N. 0°14' E., bet. secs. 17 and 18.
40.01	The 1/4 cor. of secs. 17 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 30 ins. above ground, in a scattered mound of stone, with brass cap mkd. 1/4 S18 S17 1919.
	Add the marks T13S R32E 1993 to the brass cap.
	Rebuild supporting mound of stone, 3 1/2 ft. base, to top.
	N. 0°10' W., beginning new measurement.
26.47	Point for AP 44, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
39.99	The cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above a scattered mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. T13S R32E S7 S8 S18 S17 1919.
	Add the marks 1993 to brass cap.
	Rebuild mound of stone, 4 ft. base, to top.
	From the cor. of secs. 8, 9, 16 and 17.

C*** 1 ****	
CHAINS	N. 89°47' W., bet. secs. 8 and 17.
40.14	The 1/4 sec. cor. of secs. 8 and 17, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, in a supporting mound of stone, 3 1/2 ft. base, 1/2 ft. high, with brass cap mkd. 1/4 S8 S17 1919.
	Add the marks T13S R32E 1993 to the brass cap.
	N. 89°48' W., beginning new measurement.
40.16	The cor. of secs. 7, 8, 17 and 18.
	N. 89°58' W., bet. secs. 7 and 18.
12.03	Point for AP 40, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
39.98	The 1/4 sec. cor. of secs. 7 and 18, monumented with an iron post, 1 in. diam, leaning, projecting 25 ins. above ground, with scattered mound of stone, with brass cap mkd. 1/4 S7 S18 1919.
	Add the marks T13S R32E 1993 to the brass cap.
	Rebuild supporting mound of stone, 3 1/2 ft. base, to top.
	S. 89°44' W., beginning new measurement.
39.34	The cor. of secs. 7 and 18 only, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 15 ins. above ground, in a scattered mound of stone, with brass cap mkd. T13S S7 S18 R32E 1919 1993, as described in the field notes of the dependent resurvey of the E. bdy., T. 13 S., R. 32 E., executed concurrently under this same group.
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0°01' W., bet. secs. 7 and 8.
	Point for AP 37, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
	Point for AP 25, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.

-	
CHAINS 39.95	The 1/4 sec. cor. of secs. 7 and 8, monumented with an iron post, 1 in. diam, firmly set, projecting 12 ins. above ground, with scattered mound of stone to the W., with brass cap mkd. 1/4 S7 S8 1919.
	Add the marks T13S R32E 1993 to the brass cap.
	Rebuild mound of stone to the W., 3 ft. base, 1 1/2 ft. high.
	N. 0006' E., beginning new measurement.
38.49	The witness cor. for secs. 5, 6, 7, and 8, monumented with an iron post, 2 ins. diam., firmly set, projecting 28 ins. above ground, in a scattered mound of stone, with brass cap mkd. T13S R32E S6 S5 S7 S8 WC 1919.
	Add the marks 1992 to the brass cap.
	Rebuild supporting mound of stone, 3 ft. base, 2 ft. high.
	N. 0°17' E., beginning new measurement.
1.31	The true point for secs. 5, 6, 7, and 8, at proportionate distance. Point fall in a wash, 73 lks. wide, 3 ft. deep, impractical to monument.
	From the true point for the cor. of secs. 4, 5, 8 and 9.
	N. 89°56' W., bet. secs. 5 and 8.
39.72	The witness 1/4 sec. cor. of secs. 5 and 8, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with a mound of stone to the N., 2 1/2 ft. base, 1/2 ft. high, with brass cap mkd. WC 1/4 S5 S8 1919.
	Add the marks T13S R32E 1993 to the brass cap.
	S. 89°49' W., beginning new measurement.
0.31	The true point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate distance. Point falls in a wash, 18 lks. wide, impractical to monument.
40.44	The true point for the cor. of secs. 5, 6, 7 and 8.
	N. 89°45' W., bet. secs. 6 and 7.

CHAINS 39.63	The 1/4 cor. of secs. 6 and 7, monumented with an iron post, 1 in. diam, firmly set, projecting 28 ins. above ground, in a scattered mound of stone, with brass cap mkd. 1/4 S6 S7 1919.
	Add the marks T13S R32E 1992 to the brass cap.
	Rebuild supporting mound of stone, 4 ft. base, to top.
	Cor. is located on a steep, rocky slope, facing SE.
	N. 89°58' W., beginning new measurement.
39.25	The cor. of secs. 6 and 7 only, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 25 ins. above ground, in a supporting mound of stone, 4 ft. base, 2 1/2 ft. high, with brass cap mkd. T13S S6 S7 R32E 1952 1992, as described in the field notes of the dependent resurvey of the E. bdy., T. 13 S., R. 32 E., executed concurrently under this same group.
	From the true point for the cor. of secs. 5, 6, 7 and 8.
	N. 0°17' E., bet. secs. 5 and 6.
40.25	The 1/4 sec. cor. of secs. 5 and 6, monumented with an iron post, 1 in. diam., firmly set, projecting 17 ins. above ground, in a scattered mound of stone, with brass cap mkd. 1/4 S6 S5 1919.
	Add the marks T13S R32E 1992 to brass cap.
	Rebuild supporting mound of stone, 4 ft. base, to top.
	Cor. is located in a line of wooden fenceposts, from a previous fenceline, bears E. and S.
	N. 0°09' W., beginning new measurement.
39.84	The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above ground, with a mound of stone to the W., 3 ft. base, 2 ft. high, with brass cap mkd. T12S R32E S31 S32 S6 S5 T13S 1914 1992, as described in the field notes of the dependent resurvey of the S. bdy., T. 12 S., R. 32 E., executed concurrently under this same group.

Subdivision of Section 9 T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

	T. 13 S., R. 32 E., Gila and Sait River Meridian, Arizona
CHAINS	From the 1/4 sec. cor. of secs. 9 and 16.
	N. 0°14' W., on the N. and S. centerline of sec. 9.
40.07	Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E. and W. centerline of sec. 9.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T13s R32E
	C 1/4 S9
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
60.155	Point for the center N 1/16 sec. cor. of sec. 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T13s_R32E
	N1/16 C S9
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
63.80	Point for AP 76, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
80.24	The 1/4 sec. cor. of secs. 4 and 9.
	From the 1/4 sec. cor. of secs. 9 and 10.
	S. 89°50' W., on the E. and W. centerline of sec. 9.
19.95	Point for the center E 1/16 cor. of sec. 9.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place on a rock spur, 200 x 100 ft., bearing ENE. and WSW., with top mkd.

Subdivision of Section 9 T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

	T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	T13S R32E
	E 1/16
	cc
	S9
	1993
	Deposit a magnet, 1 x 7/8 ins. diam. beneath the brass tablet.
	Raise a mound stone to the N., 3 ft. base, 2 1/2 ft. high.
39.90	The center 1/4 sec. cor. of sec. 9.
43.85	Point for AP 72, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
79.87	The 1/4 sec. cor. of secs. 8 and 9.
	NE 1/4
	From the center E 1/16 sec. cor. of sec. 9.
	N. 0°14' W., on the N. and S. centerline of the NE 1/4 of sec. 9.
20.04	Point for the NE 1/16 sec. cor. of sec. 9, at intersection with the E. and W. centerline of the NE 1/4 of sec. 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.
	T13S R32E
	NE 1/16
	S9
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
32.86	Point for AP 81, on the Peloncillo Mountains Wilderness Area Bdy., hereinafter described.
40.10	The E 1/16 sec. cor. of secs. 4 and 9.
	From the N 1/16 sec. cor. of secs. 9 and 10.
	S. 89°56' W., on the E. and W. centerline of the NE 1/4 of sec. 9.
19.955	The NE 1/16 sec. cor. of sec. 9.

BOOK 54 09

Subdivision of Section 9 T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

	T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS 39.91	The center N 1/16 sec. cor. of sec. 9.
	Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona
	In Sec. 6
	From the point for AP 1, on the W. bdy. of the Tp., identical with AP 12, T. 13 S., R. 31 E., monumented with a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, on a rock ledge, 400 x 100 x 24 ft. high, mkd. T13S R31E R32E PMWA AP12 AP1 S1 S6 1993, as described in the field notes of the Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Bdy., T. 13 S., R. 31 E., executed concurrently under this same group.
	S. 74°17' E., on line 1-2.
3.93	Point for AP 2.
	Set a brass tablet, 3 1/4 ins. diam, 3 1/2 ins. stem, in a drill hole, cemented in place on a rock outcrop, 60 x 15 x 27 ft. high, with top mkd.
	T13S R32E
	PMWA
	S6 AP2
:	1993
	Deposit a magnet 1 x 7/8 ins. beneath brass tablet,
	S. 20°49' W., on line 2-3.
1.89	Point for AP 3.
	Set a brass tablet, 3 1/4 ins. diam, 3 1/2 ins. stem, in a drill hole, cemented in place on a rock outcrop, 55 x 18 x 15 ft. high, with top mkd.
	T13S R32E
	S6 AP3
	PMWA 1993

	T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	Deposit a magnet 1 x 7/8 ins. beneath brass tablet.
	N. 72°25' W., on line 3-4.
3.21	Point for AP 4, on the W. bdy. of the Tp., identical with AP 13, T. 13 S., R. 31 E., monumented with a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, on a rock ledge, 40 x 26 x 25 ft. high, mkd. T13S R31E R32E S1 S6 AP13 AP4 PMWA 1993, as described in the field notes of the Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Bdy., T. 13 S., R. 31 E., executed concurrently under this same group.
	In Sec. 7
	From the point for AP 5, on the W. bdy. of the Tp., identical with AP 46, T. 13 S., R. 31 E., monumented with a stainless steel post, firmly set, projecting 6 ins. above ground, with brass cap mkd. T13S R31E R32E PMWA AP46 AP5 S12 S7 1993, as described in the field notes of the Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Bdy., T. 13 S., R. 31 E., executed concurrently under this same group.
	S. 54°14' E., on line 5-6.
1.68	Point for AP 6.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T13S R32E
	PMWA AP6 S7 1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 43 lks. N. of trail road, bears SE. and NW.
	S. 46°13' E., on line 6-7.
2.72	Point for AP 7.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary

T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

32E
A
7
,
3
99

Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Cor. is located 40 lks. N. of trail road, bears ESE. and NW.

N. 82°07' E., on line 7-8.

2.54 Point for AP 8.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T13S R32E PMWA AP8 S7 1993

Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Cor. is located 50 lks. N. of trail road, bears SE. and W.

S. 52°06' E., on line 8-9.

4.48 Point for AP 9.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T13S R32E PMWA AP9 S7 1993

Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

19

	T. 13 S., R. 32 E., Gila and Sait River Meridian, Arizona
CHAINS	Cor. is located 28 lks. N. of trail road, bears E. and NW.; and 88 lks. S. of wash, 50 lks. wide, 1.5 ft. deep, drains NW.
	S. 86°32' E., on line 9-10.
6.80	Point for AP 10.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T13S R32E PMWA AP10
	S7 1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 50 lks. N. of trail road, bears SE. and WNW.; and 73 lks. S. of wash, 64 lks. wide, 1.5 ft. deep, drains WNW.
	S. 38°31' E., on line 10-11.
3.61	Point for AP 11.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T13S R32E
	PMWA AP11
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 36 lks. E. of trail road, bears S. and NNW.; and 280 lks. S. of wash, 100 lks. wide, 1.5 ft. deep, drains NNW.
	S. 17°48' E., on line 11-12.
4.82	Point for AP 12.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary

T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS

T13S R32E
PMWA
AP12
1993


Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Cor. is located 24 lks. E. of trail road, bears SE. and NNW.

S. 40°19' E., on line 12-13.

5.04 Point for AP 13.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.


Cor. is located 51 lks. N. of trail road, bears SSE. and NW.

S. 30°48' E., on line 13-14.

5.95 | Point for AP 14.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T13S R32E



Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Cor. is located 44 lks. N. of trail road, bears ESE. and NW.

	1. 15 50, No. 52 50, Grid and bare rever rectually Arizona
CHAINS	S. 81°07' E., on line 14-15.
3.61	Point for AP 15.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T13S R32E PMWA AP15
	S7 1993
	Deposit a magnet in a 1 \times 1 \times 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 31 lks. N. of trail road, bears E. and W.; and 95 lks. S. of wash, 5 lks. wide, 1 ft. deep, drains WSW.
	N. 73°34' E., on line 15-16.
3.60	Point for AP 16.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T13S R32E
	PMWA /
	AP16S7
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 31 lks. N. of trail road, bears NE. and WSW.
	N. 38°05' E., on line 16-17.
8.99	Point for AP 17.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary

T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS

T13S R32E

PMWA AP17 S7 1993

Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Cor. is located 45 lks. N. of trail road, bears NNE. and SW.

N. 26°08' E., on line 17-18.

5.15 Point for AP 18.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T13S R32E



Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.


Cor. is located 45 lks. W. of trail road, bears NE. and SSW.

N. 36°36' E., on line 18-19.

3.84 | Point for AP 19.

Set a stainless steel post, 28 in. long, $2\ 1/2$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T13S R32E



Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Cor. is located 54 lks. N. of trail road, bears ENE. and SW.

	T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	N. 72°40' E., on line 19-20.
11.33	Point for AP 20.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T13S R32E
	PMWA AP20 S7 1993
	Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.
	Cor. is located 30 lks. N. of trail road, bears ENE. and WSW.; and 250 lks. S. of wash, 27 lks. wide, 1 ft. deep, drains SW.
	N. 61°08' E., on line 20-21.
5.78	Point for AP 21.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T13s R32E PMWA AP21
	S7 1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 50 lks. N. of trail road, bears E. and WSW.
	N. 85°57' E., on line 21-22.
9.68	Point for AP 22.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

	1. 13 S., R. 52 E., Gila and Sait River Meridian, Arizona
CHAINS	T13S R32E
	PMWA
	AP22
	AF22
	S7
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath
	the stainless steel post.
	Cor. is located 27 lks. N. of trail road, bears NE. and W.
	N. 48°34' E., on line 22-23.
5.92	Point for AP 23.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T13S R32E
	PMWA /
	AP23
	/ s7
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 64 lks. N. of trail road, bears NE. and WSW.
	N. 37°16' E., on line 23-24.
6.27	Point for AP 24.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T13S R32E
	PMWA
	AP24
	/ S7
	1993
:	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 73 lks. N. of trail road, bears E. and SW.

	T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	S. 77°21' E., on line 24-25.
2.05	Point for AP 25, on the line bet. secs. 7 and 8.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T13S R32E PMWA AP 25
	S7 S8 1993
	Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.
	Cor. is located 52 lks. NE. of trail road, bears W. and SE.
	From this cor. point, the 1/4 sec. cor. of secs. 7 and 8, bears N. 0°01' W., 8.52 chs. dist., hereinbefore described.
	In Sec. 8
	N. 60°05' E., on line 25-26.
6.15	Point for AP 26.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T13S R32E
	PMWA AP26 S8
	1993
	Deposit a magnet in a 1 \times 1 \times 2 ins. white plastic case beneath the stainless steel post.
	N. 41°25' E., on line 26-27.
8.60	Point for AP 27.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

	20 20 30, 30 32 20, 3222 20 3023 2023 3023 3
CHAINS	T13S R32E
	PMWA AP27 S8 1993
	Deposit a magnet in a 1 \times 1 \times 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 23 lks. W. of wash, 15 lks. wide, drains S.
	N. 13°27' E., on line 27-28.
9.11	Point for AP 28.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T13S R32E
	AP28 PMWA 1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 41 lks. W. of wash, 45 lks. wide, drains SSW.
	N. 68°14' W., on line 28-29.
7.89	Point for AP 29.
	Set a brass tablet, 3 1/4 ins. diam, 3 1/2 ins. stem, in a drill hole, cemented in place on a rock outcrop, 60 x 30 ft., bears N. and S., with top mkd.
	T13S R32E
	PMWA AP29 S8 1993
	Deposit a magnet 1 x 7/8 ins. beneath brass tablet.
	N. 34°55' E., on line 29-30.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary

T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS 3.44

Point for AP 30.

Set a brass tablet, 3 1/4 ins. diam, 3 1/2 ins. stem, in a drill hole, cemented in place on a rock surface, with top mkd.


T13S R32E PMWA AP30 S8 1993

Deposit a magnet 1 x 7/8 ins. beneath brass tablet.

S. 30°32' E., on line 30-31.

2.93 | Point for AP 31.

Set a brass tablet, 3 1/4 ins. diam, 3 1/2 ins. stem, in a drill hole, cemented in place on a rock ledge, 30 x 15 ft., bears NW. and SE., with top mkd.



Deposit a magnet 1 x 7/8 ins. beneath brass tablet.

S. 78°47' E., on line 31-32.

6.57 Point for AP 32.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T13S R32E PMWA S8 AP32 1993

Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

S. 12°54' W., on line 32-33.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

Point for AP 33. Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T13S R32E

PMWA

S8

AP33

Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Cor. is located 45 lks. E. of trail road, bears N. and S.

S. 21°06' W., on line 33-34.

6.92 | Point for AP 34.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T13S R32E



Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Cor. is located 64 lks. E. of wash, 23 lks. wide, drains SSW.

S. 49°16' W., on line 34-35.

3.55 | Point for AP 35.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T13S R32E

PMWA S8 AP35 1993

	T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 83 lks. E. of wash, 45 lks. wide, drains WSW.
	S. 71°49' W., on line 35-36.
4.58	Point for AP 36.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T13S R32E
	S8
	AP36 PMWA
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 53 lks. E. of wash, 30 lks. wide, drains S.
	S. 51°57' W., on line 36-37.
4.55	Point for AP 37, on the line bet. secs. 7 and 8.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T13S R32E
	S7 S8
	AP 37
	PMWA 1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case inside the stainless steel post.
	Cor. is located 15 lks. E. of the E. bank of a wash, 45 lks. wide, drains WSW.
	From this cor. point the cor. of secs. 7, 8, 17 and 18, bears S. 0°01' E., 27.45 chs. dist., hereinbefore described.

CHAINS	T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	In Sec. 7
	S. 40°12' W., on line 37-38.
12.85	Point for AP 38.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T13S R32E
	S7 PMWA AP38 1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 53 lks. E. of wash, 45 lks. wide, drains SSW.
	S. 4°35' W., on line 38-39.
5.17	Point for AP 39.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T13s R32E
	S7 PMWA AP39 1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 30 lks. E. of wash, 38 lks. wide, drains SSW.
	S. 14°52' W., on line 39-40.
12.91	Point for AP 40, on the line bet. secs. 7 and 18.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary

T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

T13S R32E

S7 AP 40

PMWA

1993

Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Cor. is located 45 lks. E. of wash, 53 lks. wide, drains SSW.

From this cor. point, the cor. of secs. 7, 8, 17 and 18, bears S. 89°58' E., 12.03 chs. dist., hereinbefore described.

In Sec. 18

S. 25°17' W., on line 40-41.

3.86 Point for AP 41.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T13S R32E S18 PMWA AP41 1993

Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Cor. is located 61 lks. E. of wash, 76 lks. wide, drains S.; and 189 lks. N. of wash, 76 lks. wide, drains E.

S. 62°08' E., on line 41-42.

4.60 | Point for AP 42.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T13S R32E

PMWA S18 AP42 1993

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS


Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Cor. is located 86 lks. N. of trail road, bears SSE. and NNW.; and 86 lks. N. of wash, 15 lks. wide drains NNW.

S. 43°13' E., on line 42-43.

6.92 Point for AP 43.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.




Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Cor. is located 38 lks. N. of trail road, bears ESE. and WNW.; and 38 lks. N. of wash, 15 lks. wide drains WSW.

S. 59°56' E., on line 43-44.

5.67 Point for AP 44, on the line bet. secs. 17 and 18.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Cor. is located 91 lks. N. of trail road, bears E. and NW.; and 91 lks. N. of wash, 18 lks. wide, 2 ft. deep, drains NW.

From this cor. point, the cor. of secs. 7, 8, 17 and 18, bears N. 0°10' W., 13.52 chs. dist., hereinbefore described.

33

CHAINS	In Sec. 17
	S. 88°06' E., on line 44-45.
3.22	Point for AP 45.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T13S R32E
	PMWA S17 AP45 1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 45 lks. N. of trail road, bears ESE. and W.; and 45 lks. N. of wash, 100 lks. wide, 6 ft. deep, drains W.
	S. 75°37' E., on line 45-46.
4.59	Point for AP 46.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T13S R32E
	PMWA AP46 1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 66 lks. N. of trail road, bears ESE. and W.; and 45 lks. N. of wash, 100 lks. wide, 5 ft. deep, drains W.
	S. 53°22' E., on line 46-47.
3.81	Point for AP 47.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

	1. 15 5., K. 52 E., Gila and bate River Periodan, Arizona
CHAINS	T13S R32E
	PMWA
	S17 AP47
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 31 lks. N. of trail road, bears E. and WNW.; and 31 lks. N. of centerline of wash, 150 lks. wide, 5 ft. deep, drains WNW.
	S. 85°58' E., on line 47-48.
5.32	Point for AP 48.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T13S R32E
	PMWA
	S17 AP48 1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 54 lks. N. of trail road, bears E. and W., and 54 lks. N. of centerline of wash, 150 lks. wide, 6 ft. deep, drains W.
	N. 759241 D. an line 40 40
	N. 75°34' E., on line 48-49.
3.45	Point for AP 49.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T13S R32E
	PMWA AP49
	S17
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary

T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS	Cor. is located 51 lks. N. of trail road, bears E. and WSW.; and 51 lks. N. of centerline of wash, 100 lks. wide, 4 ft. deep, drains W.
	S. 88°20' E., on line 49-50.
3.10	Point for AP 50.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T13S R32E
	PMWA AP50
	S17
	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 72 lks. N. of trail road, bears NE. and W.; and 72 lks. N. of centerline of wash, 100 lks. wide, 2 ft. deep, drains W.
	N. 56°34' E., on line 50-51.
12.87	Point for AP 51.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T13S R32E
<u> </u>	PMWA AP51
	S17
:	1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 42 lks. W. of trail road, bears E. and SW.
	N. 83°46' E., on line 51-52.
3.64	Point for AP 52.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary

T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

> T13S R32E PMWA **AP52 S17**


Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Cor. is located 54 lks. N. of trail road, bears SE. and W.

S. 44°01' E., on line 52-53.

12.38 Point for AP 53.

> Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.




Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Cor. is located 51 lks. E. of trail road, bears S. and NW.

S. 29°02' E., on line 53-54.

3.05 Point for AP 54.

> Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

BOOK 5409

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS Cor. is located 24 lks. N. of trail road, bears ESE. and NW. S. 68°25' E., on line 54-55. 7.00 Point for AP 55. Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd. T13S R32E PMWA **AP55** 1993 Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post. Cor. is located 45 lks. N. of trail road, bears E. and WNW. S. 86'38' E., on line 55-56. 2.05 Point for AP 56. Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd. T13S R32E PMWA **AP56 S17** 1993 Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post. Cor. is located 48 lks. N. of trail road, bears SE. and W. S. 53°22' E., on line 56-57. 6.79 Point for AP 57. Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary

T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS T13S R32E PMWA **AP57 S17** 1993 Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post. Cor. is located 27 lks. N. of trail road, bears E. and NW. N. 86°15' E., on line 57-58. 3.12 Point for AP 58. Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. T13S R32E PMWA **AP58** S17_ 1993 Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post. Cor. is located 33 lks. N. of trail road, bears ENE. and W. N. 70°33' E., on line 58-59. 4.59 Point for AP 59. Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 12 ins. in the ground, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd. T13S R32E PMWA **AP59** S17 1993 Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post. Cor. is located 50 lks. N. of trail road, bears E. and WNW. S. 70°08' E., on line 59-60.


Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary

T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS **5.63**

Point for AP 60.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.



Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.


Cor. is located 58 lks. N. of intersection of trail roads, bears NNE., SSW. and NW.

N. 26°06' E., on line 60-61.

14.93 Point for AP

Point for AP 61, on the line bet. secs. 16 and 17.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Cor. is located 42 lks. W. of trail road, bears NNE. and SW.

From this cor. point, the cor. of secs. 8, 9, 16 and 17, bears N. 0°13' E., 13.96 chs. dist., hereinbefore described.

In Sec. 16

N. 17°53' E., on line 61-62.

6.64

Point for AP 62.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the

Peloncillo Mountains Wilderness Area Boundary

T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

T13S R32E

PMWA AP62 S16 1993

Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Cor. is located 54 lks. W. of trail road, bears N. and S.; and 54 lks. W. of wash, 100 lks. wide, 2 ft. deep, drains S.

N. 7°10' E., on line 62-63.

3.85 Point for AP 63.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T13S R32E PMWA AP63 S16

Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Cor. is located 50 lks. W. of trail road, bears NE. and S.

N. 36°22' E., on line 63-64.

3.69 Point for AP 64.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T13S R32E

PMWA AP64 S16 1993

Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Cor. is located 71 lks. W. of trail road, bears NE. and SW.

N. 55°03' E., on line 64-65.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary


T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS **1.46**

Point for AP 65, on the line bet. secs. 9 and 16.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T13S R32E



Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

1993

Cor. is located 87 lks. W. of trail road, bears NE. and SW.; and 90 lks. W. of wash, 200 lks. wide, 3 ft. deep, drains SW.

From this cor. point, the cor. of secs. 8, 9, 16 and 17, bears N. 89°52' W., 5.85 chs. dist., hereinbefore described.

In Sec. 9

N. 47°42' E., on line 65-66.

2.98

Point for AP 66.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T13S R32E

Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Cor. is located 60 lks. W. of trail road, bears NNE. and SW.; and 60 lks. W. of the centerline of a wash, 200 lks. wide, 2 ft. deep, drains SW.

N. 29°13' E., on line 66-67.

3.30

Point for AP 67.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary

T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T13S R32E PMWA AP67 S9 1993

Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Cor. is located 60 lks. W. of trail road, bears ENE. and SW.; and 60 lks. W. of a wash, 31 lks. wide, 3 ft. deep, drains SW.

N. 46°34' E., on line 67-68.

10.11 Point for AP 68.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T13S R32E PMWA AP68 S9 1993

Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Cor. is located 96 lks. W. of trail road, bears N. and SSW.; and 96 lks. W. of a wash, 75 lks. wide, 3 ft. deep, drains SSW.

N. 5°35' E., on line 68-69.

5.26 | Point for AP 69.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T13S R32E PMWA AP69 S9 1993

Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

	T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona
CHAINS	Cor. is located 50 lks. W. of trail road, bears NE. and SSW.; and 50 lks. W. of a wash, 38 lks. wide, 4 ft. deep, drains SSW.
	N. 26°21' E., on line 69-70.
20.01	Point for AP 70.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.
	T13S R32E
	PMWA AP70 S9 1993
	Deposit a magnet in a 1 \times 1 \times 2 ins. white plastic case beneath the stainless steel post.
	Cor. is located 179 lks. W. of trail road, bears E. and SW.; and 179 lks. W. of a wash, 92 lks. wide, 3 ft. deep, drains SW.
	N. 71°56' E., on line 70-71.
9.14	Point for AP 71.
:	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T13S R32E
	PMWA /
	AP71 S9 1993
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath
	the stainless steel post.
	Cor. is located 77 lks. W. of trail road, bears NE. and SW.; and 77 lks. W. of a wash, 80 lks. wide, 6 ft. deep, drains SW.
	N. 22°05' E., on line 71-72.
2.31	Point for AP 72, on the E. and W. center line of sec. 9.
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

	1. 15 5., R. 52 E., Gila and Salt River Meridian, Arizona		
CHAINS	T13S R32E		
	PMWA / S9 AP72 / 1993		
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.		
	Cor. is located 176 lks. W. of trail road, bears NE. and SW.; and 176 lks. W. of wash, 93 lks. wide, 4 ft. deep, drains SW.		
	From this cor. point, the center 1/4 sec. cor. of sec. 9, bears N. 89°50' E., 3.95 chs. dist., hereinbefore described.		
	N. 17°12' W., on line 72-73.		
9.91	Point for AP 73.		
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. T13S R32E		
	PMWA AP73 S9 1993		
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.		
	Cor. is located on the E. face of a slope, 12 ft. above and 117 lks. W. of a wash, 95 lks. wide, 3 ft. deep, drains SSW.; and 117 lks. W. of a trail road, bears NNE. and SSW.		
	N. 18°51' E., on line 73-74.		
5.46	Point for AP 74.		
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.		
	T13s R32E PMWA / AP74 / S9 1993		
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.		

BOOK 5409

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary

T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Cor. is located on a spur bearing SE. and NW., 40 ft. above and
	103 lks. W. of a wash, 50 lks. wide, 2 ft. deep, drains SSW.; and

103 lks. W. of a wash, 50 lks. wide, 2 ft. deep, drains SSW.; and 103 lks. W. of a trail road, bears N. and SSW.

N. 18*11' E., on line 74-75.

9.33 Point for AP 75.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T13S R32E


Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Cor. is located 200 lks. N. of trail road, bears NE. and SSE.; 200 lks. N. of wash, 113 lks. wide, 2.5 ft. deep, drains SSE.; and 15 lks. S. of barb wire, 4 strand, bears NW. and SE.

N. 83°13' E., on line 75-76.

2.13 Point for AP 76, on the N. and S. center line of sec. 9.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place on a rock outcrop, bears NW. and SE., 6 x 5 x 1.5 ft. high, with top mkd.



Deposit a magnet, 1 x 7/8 ins. diam. beneath the brass tablet.

Cor. is located 75 lks. N. of trail road, bears ESE. and SW.; 75 lks. N. of wash, 83 lks. wide, 2 ft. deep, drains SW.; and 30 lks. N. of barbed wire fence, 5 strand, bears ENE. and WSW.

From this cor. point, the center N 1/16 sec. cor. of sec. 9, bears S. 0°14' E., 3.645 chs. dist., hereinbefore described.

N. 77°26' E., on line 76-77.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS				
10.07	Point	for	AΡ	77.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

T13S R32E

PMWA AP77 SS

Deposit a magnet in a 1 \times 1 \times 2 ins. white plastic case beneath the stainless steel post.

Cor. is located 106 lks. N. of trail road, bears NE. and WSW.; and 106 lks. N. of wash, 64 lks. wide, 1.5 ft. deep, drains WSW.

N. 38°29' E., on line 77-78.

6.67 Point for AP 78.

Set a stainless steel post, 28 in. long, $2\ 1/2$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T13S R32E

PMWA AP78 S9 1993

Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Cor. is located 53 lks. N. of trail road, bears E. and WSW.; 53 lks. N. of wash, 56 lks. wide, 2 ft. deep, drains WSW.; and 23 lks. N. of barbed wire fence, 5 strand, bears E. and W.

N. 73°44' E., on line 78-79.

2.09 | Point for AP 79.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T13S R32E PMWA AP79

S9 1993

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary

T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS

Deposit a magnet in a 1 \times 1 \times 2 ins. white plastic case beneath the stainless steel post.

Cor. is located 19 lks. N. of the NW. cor. of a log corral; 130 lks N. of trail road, bears SE. and WSW.; and 130 lks. N. of wash, 86 lks. wide, 3 ft. deep, drains WSW.

S. 74°58' E., on line 79-80.

3.60 Point for AP 80.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T13S R32E PMWA AP80 S9 1993

Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Cor. is located 61 lks. W. of the trail road, bears NNE. and SSW.; and 61 lks. W. of wash, 46 lks. wide, 2 ft. deep, drains SSW.

N. 11°59' E., on line 80-81.

2.17 Point for AP 81, on the N. and S. centerline of the NE 1/4 of sec. 9.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T13S R32E

Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Cor. is located 85 lks. W. of trail road, bears NE. and SW.; and 85 lks. W. of wash, 27 lks. wide, 3 ft. deep, drains SW.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

	T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona	
CHAINS	N. 0014' W., on the N. and S. centerline of the NE 1/4 of sec. 9.	
7.24	The E 1/16 sec. cor. of secs. 4 and 9, hereinbefore described.	
	S. 89°57' E., on the line bet. secs. 4 and 9.	
3.505	Point for AP 82.	
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.	
	T13S R32E PMWA\ AP82 S4	
	S9 1993	
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.	
	Cor. is located 58 lks. W. of trail road, bears N. and S.; and 60 lks. W. of wash, 26 lks. wide, 3.5 ft. deep, drains S. In Sec.4	
	In Sec.4	
	In Sec.4 N. 12°14' W., on line 82-83.	
3.80		
3.80	N. 12°14' W., on line 82-83.	
3.80	N. 12°14' W., on line 82-83. Point for AP 83. Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 21	
3.80	N. 12°14' W., on line 82-83. Point for AP 83. Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	
3.80	N. 12°14' W., on line 82-83. Point for AP 83. Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd. T13S R32E PMWA AP83	
3.80	N. 12°14' W., on line 82-83. Point for AP 83. Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd. T13S R32E PMWA AP83 S4	
3.80	N. 12°14' W., on line 82-83. Point for AP 83. Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd. T13S R32E PMWA AP83 S4 1993 Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath	

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary F. 13 S., R. 32 E., Gila and Salt River Meridian, Arizon

	T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona	
CHAINS	N. 52°52' E., on line 83-84.	
13.24	Point for AP 84.	
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.	
	T13S R32E	
	PMWA AP84 S4	
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.	
	Cor. is located 40 ft. above and 107 lks. W. of the trail road, bears N. and SSE.; and 107 lks. W. of wash, 103 lks. wide, 2 ft. deep, drains SSW.	
	N. 25°07' E., on line 84-85.	
10.02	Point for AP 85.	
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	
	T13S R32E	
	PMWA AP85 S4 1993	
	Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.	
	Cor. is located 29 lks. W. of trail road, bears N. and S.; and 125 lks. E. of wash, 46 lks. wide, 2 ft. deep, drains SSE.	
	N. 28°08' W., on line 85-86.	
11.89	Point for AP 86.	
	Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary

T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS

T13S R32E

PMWA
AP86

S4

Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Cor. is located 61 lks. W. of trail road, bears NNW. and SSE.

N. 10°32' W., on line 86-87.

10.16 Point for AP 87.

Set a stainless steel post, 28 in. long, $2\ 1/2$ ins. diam., 18 ins. in the ground, encircled in a collar of stone, with brass cap mkd.

T13S R32E PMWA AP87 S4 1993

Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Cor. is located 88 lks. W. of trail road, bears NNE. and SSW.

N. 34°39' E., on line 87-88.

8.13 Point for AP 88.

Set a stainless steel post, 28 in. long, $2\ 1/2$ ins. diam., 15 ins. in the ground, in a mound of stone, $3\ 1/2$ ft. base, to top, with brass cap mkd.

T13S R32E PMWA AP88 S4 1993

Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Cor. is located 68 lks. W. of trail road, bears N. and SSW.

BOOK 5409

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary

T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS

N. 4°12' W., on line 88-89.

11.11

Point for AP 89.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 13 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T13S R32E

PMWA
AP89 S4
1993

Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Cor. is located 42 lks. W. of trail road, bears N. and S.

N. 25°35' E., on line 89-90.

4.97

Point for AP 90.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

T13S R32E

PMWA AP90 S4

Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Cor. is located N. 34° W., 56 lks. dist., of intersection of trail roads, bears N. and E. and SW.

N. 50°54' W., on line 90-91.

7.11

Point for AP 91.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T13S R32E

AP91 PMWA 1993

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary

T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.


Cor. is located 50 lks. S. of trail road, bears WNW. and SE.

N. 81°57' W., on line 91-92.

5.54 Point for AP 92.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

T13S R32E



1993

Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.


Cor. is located 205 lks. S. of trail road, bears E. and W.; and 68 lks. N. of canyon rim, bears E. and W.

N. 67°40' W., on line 92-93.

4.80 Point for AP 93.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T13S R32E



1993

Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Cor. is located 36 lks. S. of trail road, bears E. and WNW.; and 27 lks. N. of canyon rim, bears ESE. and W.

N. 59°17' W., on line 93-94.

Metes-and-Bounds Survey of the Peloncillo Mountains Wilderness Area Boundary T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS **5.29**

Point for AP 94.

Set a stainless steel post, 28 in. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

T13S R32E
S4
AP94
PMWA
1993


Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

Cor. is located 200 lks. S. of trail road, bears SSE. and NW.; and 154 lks. N. of canyon rim, bears SE. and NW.

N. 34°29' W., on line 94-95.

Point for AP 95, on the line bet. secs. 4 and 33, on the N. bdy. of the Tp.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a $1 \times 1 \times 2$ ins. white plastic case beneath the stainless steel post.

GENERAL DESCRIPTION

This survey is located approximately 9 miles northeast of the town of San Simon, Arizona. The elevation ranges from 4000 feet to 5600 feet above sea level. The general terrain encompassed in this resurvey and metes-and-bounds survey is mountainous. The general drainage is to the southwest to the San Simon River, which then drains northwest to the Gila River basin.

T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS

The soil is rocky and does not promote much usable vegetation. Various cacti, greasewood, and agave abound at lower and middle elevations, some cedar growth at upper elevations.

There are various range improvements in the township consisting of improved dirt roads, corrals and water tanks.

Land usage consists primarily of grazing cattle. Other significant uses of the land would be for recreational and hunting purposes. Quail, javelin, rabbits and lizards are abundant in the area encompassed by this survey.

DESCRIPTION OF THE PELONCILLO MOUNTAINS WILDERNESS AREA BOUNDARY T. 13 S., R. 31 E. Gila and Salt River Mer., Arizona

The following description is for informational purposes only.

Beginning at Angle Point 1, on the W. bdy. of the Tp., identical with Angle Point 12, T. 13 S., R. 31 E.

thence S. 74°17' E., 3.93 chs. dist., to Angle Point 2; thence S. 20°49' W., 1.89 chs. dist., to Angle Point 3; thence N. 72°25' W., 3.21 chs. dist., to Angle Point 4, on the W. bdy. of the Tp., identical with Angle Point 13, T. 13 S., R. 31 E.

From Angle Point 5, on the W. bdy. of the Tp., identical with Angle Point 46, T. 13 S., R. 31 E.

thence S. 54°14' E., 1.68 chs. dist., to Angle Point 6; thence S. 46°13' E., 2.72 chs. dist., to Angle Point 7; thence N. 82°07' E., 2.54 chs. dist., to Angle Point 8; thence S. 52°06' E., 4.48 chs. dist., to Angle Point 9; thence S. 86°32' E., 6.80 chs. dist., to Angle Point 10; thence S. 38°31' E., 3.61 chs. dist., to Angle Point 11; thence S. 17°48' E., 4.82 chs. dist., to Angle Point 12; thence S. 40°19' E., 5.04 chs. dist., to Angle Point 13; thence S. 30°48' E., 5.95 chs. dist., to Angle Point 14; thence S. 81°07' E., 3.61 chs. dist., to Angle Point 15; thence N. 73°34' E., 3.60 chs. dist., to Angle Point 16; thence N. 38°05' E., 8.99 chs. dist., to Angle Point 17, thence N. 26°08' E., 5.15 chs. dist., to Angle Point 18; thence N. 36°36' E., 3.84 chs. dist., to Angle Point 19; thence N. 72°40' E., 11.33 chs. dist., to Angle Point 20; thence N. 61°08' E., 5.78 chs. dist., to Angle Point 21; thence N. 85°57' E., 9.68 chs. dist., to Angle Point 22; thence N. 48°34' E., 5.92 chs. dist., to Angle Point 23; thence N. 37°16' E., 6.27 chs. dist., to Angle Point 24;

T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

CHAINS	
CHAINS	thence S. 77°21' E., 2.05 chs. dist., to Angle Point 25, on
	the line bet. secs. 7 and 8;
	thence N. 60°05' E., 6.15 chs. dist., to Angle Point 26;
	thence N. 41°25' E., 8.60 chs. dist., to Angle Point 27;
	thence N. 13°27' E., 9.11 chs. dist., to Angle Point 28;
	thence N. 68°14' W., 7.89 chs. dist., to Angle Point 29;
	thence N. 34°55' E., 3.44 chs. dist., to Angle Point 30;
	thence S. 30°32' E., 2.93 chs. dist., to Angle Point 31;
	thence S. 78°47' E., 6.57 chs. dist., to Angle Point 32;
	thence S. 12°54' W., 11.59 chs. dist., to Angle Point 33;
	thence S. 21°06' W., 6.92 chs. dist., to Angle Point 34;
	thence S. 49°16' W., 3.55 chs. dist., to Angle Point 35;
	thence S. 71°49' W., 4.58 chs. dist., to Angle Point 36;
	thence S. 51°57' W., 4.55 chs. dist., to Angle Point 37, on
	the line bet. secs. 7 and 8;
	thence S. 40°12' W., 12.85 chs. dist., to Angle Point 38;
	thence S. 4°35' W., 5.17 chs. dist., to Angle Point 39;
	thence S. 14°52' W., 12.91 chs. dist., to Angle Point 40, on
	the line bet. secs. 7 and 18;
	thence S. 25°17' W., 3.86 chs. dist., to Angle Point 41;
	thence S. 62°08' E., 4.60 chs. dist., to Angle Point 42;
	thence S. 43°13' E., 6.92 chs. dist., to Angle Point 43;
	thence S. 59°56' E., 5.67 chs. dist., to Angle Point 44, on
	the line bet, secs. 17 and 18;
	thence S. 88°06' E., 3.22 chs. dist., to Angle Point 45;
	thence S. 75°37' E., 4.59 chs. dist., to Angle Point 46;
	thence S. 53°22' E., 3.81 chs. dist., to Angle Point 47;
	thence S. 85°58' E., 5.32 chs. dist., to Angle Point 48;
	thence N. 75°34' E., 3.45 chs. dist., to Angle Point 49;
	thence S. 88°20' E., 3.10 chs. dist., to Angle Point 50;
	thence N. 56°34' E., 12.87 chs. dist., to Angle Point 51;
	thence N. 83°46' E., 3.64 chs. dist., to Angle Point 52;
	thence S. 44°01' E., 12.38 chs. dist., to Angle Point 53;
	theree S. 44 01 E., 12.30 Chs. dist., to Angle Point 53;
	thence S. 29°02' E., 3.05 chs. dist., to Angle Point 54;
	thence S. 68°25' E., 7.00 chs. dist., to Angle Point 55;
	thence S. 86°38' E., 2.05 chs. dist., to Angle Point 56;
	thence S. 53°22' E., 6.79 chs. dist., to Angle Point 57;
	thence N. 86°15' E., 3.12 chs. dist., to Angle Point 58;
	thence N. 70°33' E., 4.59 chs. dist., to Angle Point 59;
	thence S. 70°08' E., 5.63 chs. dist., to Angle Point 60;
	thence N. 26°06' E., 14.93 chs. dist., to Angle Point 61, on
	the line bet. secs. 16 and 17;
	thence N. 17°53' E., 6.64 chs. dist., to Angle Point 62;
	thence N. 7°10' E., 3.85 chs. dist., to Angle Point 63;
	thence N. 36°22' E., 3.69 chs. dist., to Angle Point 64;
	thence N. 55°03' E., 1.46 chs. dist., to Angle Point 65, on
	the line bet. secs. 9 and 16;
	thence N. 47°42' E., 2.98 chs. dist., to Angle Point 66;
	thence N. 29°13' E., 3.30 chs. dist., to Angle Point 67;
	thence N. 46°34' E., 10.11 chs. dist., to Angle Point 68;
	thence N. 5°35' E., 5.26 chs. dist., to Angle Point 69;
	thence N. 26°21' E., 20.01 chs. dist., to Angle Point 70;

T. 13 S., R. 32 E., Gila and Salt River Meridian, Arizona

```
CHAINS
        thence N. 71°56' E., 9.14 chs. dist., to Angle Point 71;
        thence N. 22°05' E.,
                              2.31 chs. dist., to Angle Point 72, on
             the E. and W. centerline of sec. 9;
        thence N. 17°12' W.,
                              9.91 chs. dist., to Angle Point 73;
        thence N. 18°51' E., 5.46 chs. dist., to Angle Point 74;
        thence N. 18°11' E., 9.33 chs. dist., to Angle Point 75;
        thence N. 83°13' E., 2.13 chs. dist., to Angle Point 76, on
             the N. and S. centerline of sec. 9;
        thence N. 77°26' E., 10.07 chs. dist., to Angle Point 77;
        thence N. 38°29' E., 6.67 chs. dist., to Angle Point 78;
        thence N. 73°44' E., 2.09 chs. dist., to Angle Point 79;
        thence S. 74°58' E., 3.60 chs. dist., to Angle Point 80;
        thence N. 11°59' E., 2.17 chs. dist., to Angle Point 81, on
             the N. and S. centerline of the NE 1/4 of sec. 9,;
        thence N. 0°14' W., on the N. and S. centerline of the NE 1/4
             of sec. 9, 7.24 chs., to the E 1/16 sec. cor. of secs. 4 and
        thence S. 89°57' E., on the line bet. secs. 4 and 9, 3.505 chs.
             dist., to Angle Point 82;
        thence N. 12°14' W., 3.80 chs. dist., to Angle Point 83;
        thence N. 52°52' E., 13.24 chs. dist., to Angle Point 84;
        thence N. 25°07' E., 10.02 chs. dist., to Angle Point 85;
        thence N. 28°08' W., 11.89 chs. dist., to Angle Point 86;
        thence N. 10°32' W., 10.16 chs. dist., to Angle Point 87;
        thence N. 34°39' E., 8.13 chs. dist., to Angle Point 88;
        thence N. 4°12' W., 11.11 chs. dist., to Angle Point 89;
        thence N. 25°35' E., 4.97 chs. dist., to Angle Point 90;
        thence N. 50°54' W.,
                             7.11 chs. dist., to Angle Point 91;
        thence N. 81°57' W., 5.54 chs. dist., to Angle Point 92;
        thence N. 67°40' W., 4.80 chs. dist., to Angle Point 93;
        thence N. 59°17' W., 5.29 chs. dist., to Angle Point 94;
        thence N. 34°29' W., 8.14 chs. dist., to Angle Point 95, on
             the line bet. secs. 4 and 33, on the N. bdy. of the Tp.;
```

BOOK 5409

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Daniel R. Muth	Surveyor in Training
Cheryl A. Baier	Surveying Technician
Gordon R. Bubel	Surveying Technician
Steven J. Buchanan	Surveying Technician
Ted E. Cazier	Surveying Technician
Jeff A. Hill	Surveying Technician
Mark R. Searles	Surveying Technician

CERTIFICATE OF SURVEY

I, Robert C. Umbanhowar, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 6th day of January, 1992, I have dependently resurveyed a portion of the subdivisional lines, the subdivision section 9, and the mete-and-bounds survey of the Peloncillo Mountains Wilderness Area Boundary in Township 13 South, Range 32 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

the foregoing field notes.	
6/14/94 (hata)	Poherd (, limbanhowar) (Cadastral Surveyor)
(Date)	(Cadastral Surveyor)
CEF	RTIFICATE OF APPROVAL
	BUREAU OF LAND MANAGEMENT
	Arizona State Office Phoenix, Arizona
lines, the subdivision of section Mountains Wilderness Area Boundary and Salt River Meridian, in the St	dependent resurvey of a portion of the subdivisional 9, and the mete-and-bounds survey of the Peloncillo 7 in Township 13 South, Range 32 East, of the Gila 2 cate of Arizona, executed by Robert C. Umbanhowar, 2 citically examined and found correct, are hereby
JUN 2 2 1994	James P. Kelley
(Date)	(Chief Cadastral Surveyor of Arizona)
CICION	TETCATE OF TRANSCRIPT
I CERTIFY that the foregoing transsurveys in T. 13 S., R. 32 E., Gil of the original field notes.	cript of the field notes of the above-described a and Salt River Meridian, Arizona, is a true copy

(Chief Cadastral Surveyor of Arizona)

(Date)