ORIGINAL

BOOK 5441

# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

#### FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
A PORTION OF THE SUBDIVISIONAL LINES
AND CERTAIN MINERAL SURVEYS,
THE SUBDIVISION OF SECTION 3
AND THE METES-AND BOUNDS SURVEY OF THE
MOUNT NUTT WILDERNESS AREA BOUNDARY
IN TOWNSHIP 20 NORTH, RANGE 20 WEST
Of theGila and Salt River Meridian, In the State ofArizona
EXECUTED BY Belle A. Craig, Cadastral Surveyor

Under Special Instructions dated <u>October 24, 1991</u>, approved <u>October 24, 1991</u>, which provided for the surveys included under Group Number <u>738</u> and assignment instructions dated <u>September 23, 1992</u>.

Survey commenced <u>December 7, 1992</u> Survey completed <u>May 19, 1993</u> TOWNSHIP 20 NORTH, RANGE 20 WEST,

	<b>1</b>					· · · · · · · · · · · · · · · · · · ·	***************************************		
6 3	4 5	32	4	25	3	14	2	9 1	5
	33-		31		24		12	7	_
7	8		9	23	10		11	12	4
			30		-23				
18	17		16		15		14	13	
			29		22				
19	20	29	21	20	22	12	23	24	
			28		19				
30	29	2 <b>7</b>	28	17 	27	11	26	25	
			27		17				
31	32	26	33	15	34	10	35	36	·
	<u></u>		<del></del>						

Dep. Res. M.S. 3006A

Dep. Res. M.S. 3760B

Subdivision of Section 3

Metes-and-Bounds Survey MNWA

pp. 35-39

pp. 40-42

pp. 42-43 pp. 43-101

### BOOK 5441

#### T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of the dependent resurvey of a portion of the east boundary, a portion of the subdivisional lines and certain mineral surveys, the subdivision of section 3 and the metes-and-bounds survey of the Mount Nutt Wilderness Area Boundary in Township 20 North, Range 20 West, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this resurvey is as follows: Omar H. Case surveyed the Fifth Standard Parallel North through Ranges 19 and 20 West in 1872. Theo. O. Johnston resurveyed the Fifth Standard Parallel North through Range 20 West in 1915. The Fifth Standard Parallel North through a portion of Range 19 West was resurveyed by Guy H. Richardson, Otis Ross, and Hugo Price in 1915. Guy H. Richardson and Otis Ross surveyed the south boundary in 1915. Guy H. Richardson surveyed the east boundary in 1915. Guy H. Richardson and Hugo Price surveyed the subdivisional lines in 1915. Mineral Survey 3006A&B was surveyed by H.G. Schader in 1912. Mineral Survey 3439 was surveyed by Edward L. Haff in 1917. Mineral Survey 3760A&B was surveyed by Herman C. Zulch in 1921. Mineral Survey 4213 was surveyed by L.H. Foster in 1938.

The survey was executed in accordance with the specifications as set forth in the <u>Manual of Surveying Instructions</u>, 1973, and the Special Instructions dated October 24, 1991, for Group No. 738, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The purpose of this survey was to determine the boundary of the Mount Nutt Wilderness Area.

The directions of all lines were determined by direct hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with a Ziess Elta 3 electronic instrument, and a Nikon NTD-4 Theodolite Distancemeter.

The geographic position of the corner of sections 1, 6, 7, and 12, on the East boundary of the Township, was determined by the technique of relative positioning using the Ashtech GPS Geodetic System. The U.S. Geological Survey triangulation station identical with the original closing corner for sections 3 and 4, Township 20 North, Range 19 West, was used as the control station.

Latitude 35°08'29.63" N. Longitude 114°21'01.38" W. NAD 27

## BOOK 5441

### T. 20 N. R. 20 W. Gila and Salt River Meridian, Arizona

CHAINS	
CHAINS	
	The mean magnetic declination as taken from quadrangle map OATMAN, ARIZ., published in 1967 by U.S. Geological Survey, is 15° E.
	Dependent Resurvey of a Portion of the East Boundary, T. 20 N., R. 20 W., Gila and Salt River Meridiam, Arizona
	Restoring the survey executed by Guy H. Richardson, in 1915
	From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., monumented with an iron post, 3 ins. diam, firmly set, projecting 24 ins. above ground, in a mound of stone, 2 ft. base, 1 ft high, with brass cap mkd. T20N R20W R19W S12 S7 S13 S18 1915.
	Add the marks 1992, on the brass cap and rebuild mound of stone 4 ft. base, to top.
	Cor. is located on steep NW slope, in a crevice bet. two boulders, boulder to north, 25 x 15 x 10 ft. high, boulder to south 15 x 6 x 10 ft. high.
	N. 0°10' W., bet. secs. 7 and 12.
	Over mountainous land, through creosote, yucca, and cacti.
40.48	The 1/4 sec. cor. of secs. 7 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 17 ins. above ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd. 1/4 S12 S7 1915.
	Add the marks T20N R20W R19W 1992 on the brass cap and rebuild the mound of stone 5 ft. base, to top.
	Cor. is located on S. slope.
	N. 0°04' W., beginning new measurement.
36.69	Point for AP 23, identical with AP 62, T. 20 N., R. 19 W., on the Mount Nutt Wilderness Area Bdy
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the East Boundary T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona


> T20N R20W R19W S12 S7 MN WA AP23 AP62

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor.is located 62 lks. S. of trail road, bears SSE and NNW, and 25 lks. W. of drainage, 7 lks. wide, 1 ft. deep, drains SSW.

Point for AP 22, identical with AP 57, T. 20 N., R. 19 W., on the Mount Nutt Wilderness Area Bdy..

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.



Deposit a magnet in a  $1 \times 1 \times 2 = 5/8$  in. white colored plastic case beneath the stainless steel post.

Cor. is located 50 lks. E. of trail road, bears SSE and NNW; 110 lks. W. of center of wash 70 lks. wide, 15 ft. deep, drains SE.

39.86 The cor. of secs. 1, 6, 7, and 12, monumented with an iron post, 3 ins. diam., firmly set, projecting 24 ins. above ground, in a scattered mound of stone, with brass cap mkd. T20N R20W R19W S1 S6 S12 S7 1915.

Add the marks 1992 on the brass cap and rebuild the mound of stone 4 ft. base, to top.

Cor. is located 50 lks. W. of center of wash, 50 lks. wide, 5 ft. deep, drains SSE.

N. 0°01' W., bet. secs. 1 and 6.

Over low mountainous terrain, through sparse juniper, creosote, and cacti, asc. NE. slope.

CHAINS

Dependent Resurvey of a Portion of the East Boundary T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona


	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
40.09	The 1/4 sec. cor. of secs. 1 and 6, monumented with an iron post, 1 in. diam., firmly set, projecting 30 in. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. 1/4 S1 S6 1915.
	Add the marks T20N R20W R19W 1993 on the brass cap, and rebuild the mound of stone 3 ft. base, to top.
	Cor. is located on steep S. slope, 190 lks. N. of center of wash, 60 lks. wide, 1 ft. deep, drains ESE.
	North, beginning new measurement.
33.05	Intersect the Fifth Stan. Par. North.
	Point for closing cor. of secs. 1 and 6.
	Set a brass tablet, 3 1/4 ins. diam., 2 1/2 ins. stem, in a drill hole, cemented in place, in a metamorphic rock formation, 15 ft. above ground, with top cap mkd.
	T21N R19W S31
	S1 S6 R20W R19W T20N CC 1993
	1993
	From this cor. point, the stan. 1/4 sec. cor. of sec. 31, T. 21 N., R. 19 W., bears N. 78°00' E., 3.52 chs. dist. monumented with an iron post, 1 in. diam., firmly set, projecting 37 ins. above ground, in a mound of stone, 3 ft. base, to top, with a mound of stone to the N., 3 ft. base, 2 ft. high, with brass cap mkd. T21N R19W SC S31 1/4 1993 1915 as described in the field note record of the dependent resurvey of the Fifth Stan. Par. N., T. 21 N., R. 19 W., executed concurrently under this same group.
	From this same cor. point the orig. closing cor. of secs. 1 and 6 bears North, 0.305 chs. dist., monumented with an iron post, 3 ins. diam., firmly set, projecting 36 ins. above the ground, supported in a mound of stone, 3 ft. base, 4 ft. high, with a mound of stone to S., 3 ft. base, 1/2 ft. high, with a brass cap marked T21N R19W S31 S1 S6 R20W R19W T20N CC 1915. Add the marks 1993 and chisel AM on brass cap. Remove the brass cap from the post and bury the brass cap in place, 6 in. below surface. Dispose of the post.

Dependent Resurvey of a Portion of the East Boundary T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet, a 1 x 7/8 in. diam. cylinder, without a plastic case, beneath tablet stem.
	Cor. is located on SW rock face, in a small ledge, 35 lks. S. of cliff, bears E. and W.
	Dependent Resurvey of a Portion of the Subdivisional Lines, T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
	Restoring the survey executed by Guy. H. Richardson in 1915
	From the cor. of secs. 1, 2, 35, and 36, on the S. Bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 4 ft. base, to top,, with brass cap mkd. T20N R20W S35 S36 S1 S2 T19N 1992 1915, as described in the field note record of the dependent resurvey of a portion of the S. Bdy., T. 19 N., R. 20 W., executed concurrently under this same group.
	N. 0°02' E., bet. secs. 35 and 36.
	Asc. over rugged, mountainous terrain, through yucca, creosote, and cacti.
39.89	The 1/4 cor. of secs. 35 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, in a scattered mound of stone, with brass cap mkd. 1/4 S35 S36 1915.
	Add the marks T20N R20W 1993 on the brass cap, and rebuild the mound of stone, 3 ft. base, to top.
	Cor. is located on a steep W. slope, above Cottonwood Canyon, bears N. and S.
	From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.
	N. 89°45' W., bet. secs. 1 and 12.
	Asc. over mountainous terrain, through creosote, cacti, and yucca.
0.355	Point for a witness point at intersection with line 21-22 of the Mount Nutt Wilderness Area Bdy.

**CHAINS** 

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.




Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 50 lks. E. of trail road, bears SSE and NNW; 110 lks. W. of center of wash 80 lks. wide 20 ft. deep, drains S.

Point for a witness point at intersection with the bdy. of the Mount Nutt Wilderness Area, on line bet. AP 23 and AP 24.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.



Deposit a magnet in a  $1 \times 1 \times 2 = 5/8$  in. white colored plastic case beneath the stainless steel post.

Cor is located 80 lks. W. of trail road, bears SSE and NNW.

39.95 The 1/4 sec. cor of secs. 1 and 12, monumented with an iron post, 1 in. diam., firmly set, in a scattered mound of stone, projecting 24 ins. above ground, brass cap mkd. 1/4 S1 S12 1915.

Add the marks T20N R20W 1993 on the brass cap and rebuild the mound of stone 5 ft. base, to top.

Cor. is located on S. slope.

S. 89°33' W., beginning new measurement.

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
39.50	The cor. of secs. 1, 2, 11, and 12, monumented with an iron post, 2 ins. diam., firmly set, projecting 25 ins. above ground, in a mound of stone, 2 ft. base, 2 ft. high, with brass cap mkd. T20N R20W S1 S2 S11 S12 1915.
	Add the marks 1993 on the brass cap and rebuild the mound of stone, 3 ft. base, to top.
	Cor. is located on N. slope.
	N. 0°04' W., bet. secs. 1 and 2.
	Desc. over mountainous land, through cacti and creosote.
25.08	Point for AP 34, on the Mount Nutt Wilderness Area Bdy.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to bedrock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T20N R20W S2 S1
	52 51
	AP34
	MNWA   1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located on a ridge, in a saddle bet. two rock outcroppings, 20 ft. high, ridge bears WNW and SSE.
40.10	The 1/4 sec. cor. of secs. 1 and 2, monumented with an iron post, 1 in. diam., firmly set, in a mound of stone, projecting 35 ins. above ground, with brass cap mkd. 1/4 S2 S1 1915.
	Add the marks T20N R20W 1993 on the brass cap and rebuild the mound of stone 3 ft. base, to top
	Cor. is located on NE. slope.
	N. 0°03' E., beginning new measurement.
26.03	The orig. closing cor. of secs. 1 and 2, at intersection with the Fifth Stan. Parallel, North, monumented with an iron post, 2 ins. diam., firmly set, in a mound of stone, 3 ft. base, 2 ft. high, projecting 22 ins. above ground, with brass cap mkd. T21N R20W S36 S2 S1 T20N R20W CC 1915.

**CHAINS** 

Add the marks 1993 on the brass cap.

From this cor. point, the stan. 1/4 sec. cor. of sec. 36, bears S. 89°52' E., 5.45 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 17 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. SC T21N R20W 1/4 S36 1993 1915 as described in the field note record of the dependent resurvey of the Fifth Stan. Par. N., T. 21 N., R. 20 W., executed concurrently under this same group.

Cor. is located on steep S. slope, 110 lks. W. of drainage, 12 lks. wide, 2 ft. deep, drains SE.

The point for the 1/4 sec. cor. of sec. 1 only, T. 20 N., R. 20 W., is at midpoint longitudinally on the N. Bdy. of sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T21N R20W

1/4 S1 T20N R20W 1993

From this cor. point, the stan. cor. of Tps. 21 N., Rs. 19 W. and 20 W., bears S. 89°53'E., 5.70 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T21N R19W S36 S31 1992, as described in the field notes of the dependent resurvey of the Fifth Standard Parallel N., T. 21 N., R. 19 W, executed concurrently under this same group.

From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 28 ins. above ground, supported in a mound of stone, 3 ft. base, 18 ins. high, with a mound of stone to the W., 3 ft. base, 2 ft. high, with brass cap mkd. T20N R20W S34 S35 S2 S3 T19N 1992 1915, as described in the field note record of the dependent resurvey of a portion of the S. Bdy., T. 19 N., R. 20 W., executed concurrently under this same group.

N. 0°01' E., bet. secs. 34 and 35.

Over rugged, steep W. slope, through sparse vegetation.

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
39.80	The 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 30 ins. above ground, in a mound of stone, 3 ft. base, 2 ft. high, with a mound of stone to the W., 3 ft. base, 2 ft. high, with brass cap mkd. 1/4 S34 S35 1915.
	Add the marks T20N R20W 1992 on the brass cap.
	Cor. is located in a crevice, bet. two granite boulders.
	N. 0°01' W., beginning new measurement.
39.90	The cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 20 ins. above ground, in a scattered mound of stone, with brass cap mkd. T20N R20W S27 S26 S34 S35 1915.
	Add the marks 1993 on the brass cap and rebuild the mound of stone, 4 ft. base, to top.
	Cor. is located 55 lks. E. of top of cliff, on the left bank of Grapevine Canyon wash, which drains WSW.
	N. O'01' E., bet. secs. 26 and 27.
40.05	The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 22 ins. above ground, in a scattered mound of stone, with brass cap mkd. 1/4 S27 S26 1915.
	Add the marks T20N R20W 1993 on the brass cap and rebuild mound of stone 4 ft. base, to top.
	Cor. is located on steep W. slope, 40 lks W. of cliff face, 150 ft. high, bears SSE and NNW.
	N. 0°01' W., beginning new measurement.
40.10	The cor. of secs. 22, 23, 27, and 26, monumented with an iron post, 2 ins. diam., firmly set, projecting 20 ins. above ground, in a mound of stone, 4 ft. base, 1 ft. high, with brass cap mkd. T20N R20W S22 S23 S27 S26 1915.
	Add the marks 1993 on the brass cap and rebuild the mound of stone 4 ft. base, to top.
	Cor. is located 25 lks. S. of center of wash, 10 lks wide , 2 ft. deep, drains WNW.

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	N. 0°11' W., bet. secs. 22 and 23.
	Over low, mountainous terrain, through creosote and cacti.
39.93	The 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above ground, in a scattered mound of stone, with brass cap mkd. 1/4 S22 S23 1915.
	Add the marks 1993 on the brass cap and rebuild the mound of stone 4 ft. base
	Cor. is located S. of wash at base of wash terrace, bears NE and WSW.
	N. 0°05' E., beginning new measurement.
40.02	The cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, in a scattered mound of stone, with brass cap mkd. T20N R20W S15 S14 S22 S23 1915.
	Add the marks 1993 on the brass cap and rebuild the mound of stone 4 ft. base, to top.
	Cor. is located on rocky W. slope, 105 lks. N. of center of wash 25 lks. wide, 5 ft. deep, drains WNW.
	From the cor. of secs. 1, 2, 11, and 12.
	S. 89°55' W., bet. secs. 2 and 11.
4.58	Point for a witness point on the Mount Nutt Wilderness Area Bdy.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, in volcanic tuft rock formation, with top mkd.
	WP1
	T20N R20W S2
	1993
	Deposit a magnet, a 1 x 7/8 in. diam. cylinder, without a plastic case, beneath tablet stem.
	Cor. is located on top of rocky ridge, 1 ch. N. of grassy saddle, bears N. and S.

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
40.08	The 1/4 sec. cor of secs. 2 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 30 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with a mound of stone to the N., 2 ft. base, 2 ft. high, with brass cap mkd. S2 1/4 S11 1915.
	Add the marks T20N R20W 1993 on the brass cap and rebuild the mound of stone 3 ft. base, to top.
	Cor. is located on E. facing slope.
	N. 89°30' W., beginning new measurement.
1.89	Point for a witness point on the Mount Nutt Wilderness Area Bdy.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 1 in. in the ground, to bedrock, supported in a mound of stone, 5 ft. base, to top, with brass cap mkd.
	WP2 T20N R20W S2
	S11 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located atop cliff bears N. and S.
23.70	Point for a witness point on the Mount Nutt Wilderness Area Bdy.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 1 in. in the ground, to bedrock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	WP3 T20N R20W S2
	S11 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located on a moderate N. slope, N. of a 2 ft. rock ledge, 2 ft. high, bears E. and W.
1	1

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
39.90	The cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 2 ins. diam., firmly set, projecting 36 ins. above ground, in a mound of stone, 3 ft. base, to top, with a mound of stone to the NW., 3 ft. base, 2 ft. high, with brass cap mkd.
	Add the marks 1993 on the brass cap.
	Cor. is located on SW. slope.
	N. O°03' W., bet. secs. 2 and 3.
	Over rugged mountainous terrain, through sparse yucca, and cacti.
35.02	The witness cor. to the 1/4 sec. cor. of secs. 2 and 3, monumented with an iron post, 1 in. diam., firmly set, projecting 36 ins. above ground, in a mound of stone, 3 ft. base, 2 ft. high, with a mound of stone to the W., 2 ft. base, 2 ft. high, with brass cap mkd. 1/4 S3 S2 WC 1915.
	Add the marks T20N R20W 1993 on the brass cap.
	Cor. is located at the base of a cliff, 60 ft. high, bears N. and S.; 20 lks. W. of a saddle, bears E. and W.
	N. 0°01' W., beginning new measurement.
4.51	True point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate dist. Point falls on cliff face where it is impracticable to establish a permanent monument.
30.29	The orig. closing cor. for secs. 2 and 3, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd. T21N R20W S35 S3 S2 T20N R20W CC 1915.
	Add the marks 1993, and chisel AM on the brass cap. Remove the brass cap from the post, and bury in place, 12 in. below surface. Dispose of post.
30.92	Intersect the Fifth Stan. Par. North.
	Point for the closing cor. of secs. 2 and 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T21N R20W
S35

S3 S2
T20N R20W
CC
1993

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

From this cor. point, the stan. 1/4 cor. of sec. 35, bears S. 89°56' E., 5.61 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. SC T21N R20W 1/4 S35 1993 1915, as described in the field note record of the dependent resurvey of the Fifth Stan. Par. N., T. 21 N., R. 20 W.; executed concurrently with this group.


Cor. is located on rocky S. slope, 1.2 chs. S. of ridge top, bears E. and W.

From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 36 ins. above ground, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd. T20N R20W S33 S34 S3 S4 T19N R20W 1992 1915, as described in the field note record of the dependent resurvey of a portion of the S. Bdy., T. 19 N., R. 20 W., executed concurrently under this same group.

N. 0°05' E., bet. secs. 33 and 34.

38.15 Point for AP 135, on the Mount Nutt Wilderness Area Bdy.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.

Form 9600-10a (November 1987) USDI-BLM

39.95

#### CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T20N R20W 1/4 S33 | S34 1993

Deposit a magnet in a  $1 \times 1 \times 2$  5/8 in. white colored plastic case beneath the stainless steel post.

From this cor. point, cor. No. 3, B. & L. No. 3 lode, M.S. 3439, monumented with a weathered wood post, 4 x 4 ins., firmly set, projecting 24 ins. above ground, in a mound of stone 4 ft. base, 1 ft. high, with no discernable marks, bears S. 85°46' W., 27.66 chs. dist. Not remonumented.

From this cor. point, the E. end center, B. & L. No. 3, lode, monumented with a weathered wood post, 4 x 4 ins., firmly set, projecting 24 ins. above ground, in a mound of stone, 4 ft. base, 1 ft. high, with no discernable marks, bears S. 14°07' W., 4.54 chs. dist. Not remonumented.

#### 41.73

Point for AP 130, on the Mount Nutt Wilderness Area Bdy.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 60 lks. S. of trail road, bears NNE. and SSW.

79.90

The cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 21 ins. above ground, in a scattered mound of stone, with brass cap mkd. T20N R20W S27 S28 S33 S34 1915.

Add the marks 1992 on the brass cap and rebuild the mound of stone 3 ft. base, to top

Cor. is located on a moderate NE. slope, at the base of a hill.

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	From the cor. of secs. 26, 27, 34, and 35.
	N. 89°34' W., bet. secs. 27 and 34.
	Desc. over mountainous land, through creosote, cacti and yucca.
39.88	The 1/4 sec. cor. of secs. 27 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 20 ins. above ground, in a scattered mound of stone, with a mound of stone to the N., 4 ft. base, 3 ft. high, with brass cap mkd. S27 1/4 S34 1915.
	Add the marks T20N R20W 1993 on the brass cap and rebuild the mound of stone 4 ft. base, to top.
	Cor. is located on steep S. slope.
	From this cor. point, the NE. cor of a concrete box, 9 x 5.5 x 2 ft. high, bears S. 43°43' W., 1.87 chs. dist., the long side bears S. 75° E. and N. 75° W.
	N. 89°49' W., beginning new measurement.
27.32	Point for AP 108, on the Mount Nutt Wilderness Area Bdy.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, on a small ledge, in a volcanic tuft outcrop, with top mkd.
	T20N R20W
	MNWA S27 AP 108
	1993
	Deposit a magnet, a 1 x $7/8$ in. diam. cylinder, without a plastic case, beneath the tablet stem.
	Cor. is located on left bank of wash, 45 lks. wide, 2 ft. deep, drains NNW.; 45 lks. N. of trail road, bears SSE. and NNW.
39.94	The cor. of secs. 27, 28, 33, and 34.
	N. 0°15' W., bet. secs. 27 and 28.
8.34	Point for AP 104, on the Mount Nutt Wilderness Area Bdy.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T20N R20W S28 S27 AP104 MNWA
İ	1993`
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 40 lks. E. of trail road, bears NE. and SSE. in curve.
15.09	Point for AP 101, on the Mount Nutt Wilderness Area Bdy.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, to bedrock, with brass cap mkd.
	T20N R20W MN WA AP 101
	S28 S27 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 40 lks. N. of trail road, bears ESE. and WNW.
39.96	The 1/4 sec. cor of secs. 27 and 28, monumented with an iron post, 1 in. diam., firmly set, projecting 26 ins. above ground, in a mound of stone, 2 ft. base, 1 ft. high, with a mound of stone to the W., 2 ft. base, 2 ft. high, with brass cap mkd. 1/4 S28 S27 1915.
	Add the marks T20N R20W 1993 on the brass cap and rebuild the mound of stone 3 ft. base, to top.
	Cor. is located on steep W. slope.
	N. 0°03' W., beginning new measurement.
31.93	Point for a witness point at the intersection with line 2-3, Ida lode, M.S. 3006A.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	WP T20N R20W IDA MS3006A  S28 S27 MN WA 1993  Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.  From this cor. point, cor. No. 2, Ida lode, M.S. 3006A, bears N. 83°42' E., 2.79 chs. dist., hereinafter described.
	Cor. is located 40 lks. E. of trail road, bears NNE. and SW.
35.57	Point for a witness point at intersection with line 1-2, Ida lode, M.S. 3006A.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, to bedrock, with brass cap mkd.
	WP
	T20N1R20W
	S27 S28  IDA  MS 3006A
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 110 lks. E. of trail road, bears NNE. and SW.
	From this cor. point, cor. No. 1, Ida lode, M.S. 3006A, bears N. 39°47' W., 4.75 chs. dist., hereinafter described.

40.01

The cor. of secs. 21, 22, 27, and 28, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with a mound of stone to the W., 3 ft. base, 1 ft. high, with brass cap mkd. T20N R20W S21 S22 S27 S28 1915.

Add the marks 1993 on the brass cap.

Cor. is located 60 lks. W. of trail road, bears N. an S.

From the cor. of secs. 22, 23, 26, and 27.

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	N. 89°49' W., bet. secs. 22 and 27.
40.07	The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, in a collar of stone, 3 ft. base, 1 ft. high, with a mound of stone to the N., 2 ft. base, 1 ft. high, with brass cap mkd. S22 1/4 S27 1915.
	Add the marks T20N R20W 1993 on the brass cap.
	Cor. is located on E. slope.
	N. 89°51' W., beginning new measurement.
38.65	Point for AP 90, on the Mount Nutt Wilderness Area Bdy.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, brass cap mkd.
	T20N R20W MNWA S22 AP90
	S27 \ 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 55 lks. E. of trail road, bears N. and S.
39.94	The cor. of secs. 21, 22, 27, and 28.
	N. 0°02' W., bet. secs. 21 and 22.
	Over rolling, low mountainous land, through creosote, yucca, and cacti.
2.43	Point for AP 89, on the Mount Nutt Wilderness Area Bdy.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T20N R20W MNWA AP89 S21 S22 1993

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 60 lks. E. of trail road, bears SE. and WSW. and 35 lks. N. 28° W. from center of prospect pit, 10 x 10 x 2 ft. deep.
11.85	Point for AP 83, on the Mount Nutt Wilderness Area Bdy.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T20N R20W S21 S22
	AP83 MN WA 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 110 lks. S. of trail road, bears ENE. and WSW.
40.00	The 1/4 sec. cor. of secs. 21 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 3 ft. base, to top, with a mound of stone to the W., 3 ft. base, 2 ft. high, with brass cap mkd. S21 S22 1915.
	Add the marks T20N R20W 1/4 1993 on the brass cap.
	Cor is located on SE slope.
	North, beginning new measurement.
30.71	Point for AP 75, on the Mount Nutt Wilderness Area Bdy.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T20N R20W MN WA
	S21 AP75 S22
	1993

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
·	Cor. is located 40 lks. N. of trail road, bears SE. and NW. and 180 lks. S. of center of wash, 6 lks. wide, 3 ft. deep, drains NNW.
39.99	The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 2 ins. diam., firmly set, projecting 24 ins. above ground, in a mound of stone, 5 ft. base, to top, with a mound of stone to N., 3 ft. base, 2 ft high, with brass cap erroneously mkd. T20N R20W S15 S14 S22 S23 1915.
	Remark the brass cap to read S15 S16 S21 S22 and add the marks 1993.
	Cor. is located on S. slope 2.5 chs. N. of center of wash, 15 lks. wide 1 ft. deep, drains NW.
	From the cor. of secs. 14, 15, 22, and 23.
	S. 89°37' W., bet. secs. 15 and 22.
	Over rolling hills, through creosote and cacti.
39.94	The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 21 ins. above ground, in a mound of stone, 3 ft. base, 12 ins. high, with a mound of stone to the N., 3 ft. base, 1 ft. high, with brass cap mkd. S15 1/4 S22 1915.
	Add the marks T20N R20W 1993 on the brass cap.
	Cor. is located on steep S. slope.
	N. 89°13' W., beginning new measurement.
40.02	The cor. of secs. 15, 16, 21, and 22.
	N. 0°09' W. bet. secs. 15 and 16.
	Over rolling hills, through creosote, yucca, and cacti.
39.97	The 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 20 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with a mound of stone to the W., 3 ft. base, 2 ft. high, with brass cap mkd. 1/4 S16 S15 1915.

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Add the marks T20N R20W 1993 on the brass cap and rebuild the mound of 4 ft. base, to top.
	Cor. is located on SE. cor.
	N. 0°10' W., beginning new measurement.
39.91	Point for cor. of secs. 9, 10, 15, and 16, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T20N R20W S9   S10
	S16 S15 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located on S. bank of wash, bears E. and W.
	From the 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 32 ins. above ground, in a scattered mound of stone, with a boulder to N., 2 1/2 ft. base, 2 1/2 ft. high, with brass cap mkd. 1/4 S10 S15 1915.
	Add the marks T20N R20W 1993 on the brass cap and rebuild the mound of stone 3 ft. base, to top.
	Over low mountainous terrain, through creosote and cacti.
	N. 89°54' W., bet. secs. 10 and 15.
40.13	The cor. of secs. 9, 10, 15, and 16.
	N. 0°05' W., bet. secs. 9 and 10.
39.91	Point for 1/4 sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled with a collar of stone, with brass cap mkd.

	1. 20 M., N. 20 M., GIIA AM GAIC RIVEL PETIGEAN, AT 120M
CHAINS	
	T20N R20W
	1/4
	S9   S10 1993
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located in area dissected by drainages that drain SW.
79.82	The cor. of secs. 3, 4, 9, and 10, monumented with an iron post, 2 ins. diam., firmly set, projecting 24 ins. above ground, in a mound of stone, 3 ft. base, to top, with a mound of stone to the W., 3 ft. base, 1 1/2 ft., high, with brass cap mkd. incorrectly marked T20W R20N S3 S4 S9 S10 1915.
	Remark brass cap to read T20N R20W S3 S4 S9 S10 1915, and add the marks 1993.
	Cor. is located on W. slope.
	From the cor. of secs. 2, 3, 10 and 11.
	N. 89°52' W., bet. secs. 3 and 10.
	Over mountainous terrain through creosote and cacti.
16.32	Point for a witness point, on the Mount Nutt Wilderness Area Bdy.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, in volcanic tuft rock formation, with top mkd.
	WP1
	T20N R20W
	S3
	S10
	1993
	Deposit a magnet, a 1 x 7/8 in. diam. cylinder, without a plastic case, beneath the tablet stem.
	Cor. is located 10 lks. S. of cliff top.
39.98	The 1/4 sec. cor. of secs. 3 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. 1/4 S3 S10 1915.
	Add the marks T20N R20W 1993 on the brass cap.

,	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Cor. is located N. slope.
	S. 89°59' W., beginning new measurement.
32.81	Point for a witness point on the Mount Nutt Wilderness Area Bdy.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 1 in. in the ground, to bedrock, supported in a mound of stone, 5 ft. base, to top, with brass cap mkd.
1	
	WP T20N_R20W
	S3
	S10 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 20 lks. N. of cliff top, approximately 100 ft. high, bears ESE and NNW.
40.17	The cor. of secs. 3, 4, 9, and 10.
	N. 0°05' W., bet. secs. 3 and 4.
	Over rolling land, through creosote and cacti.
39.95	The 1/4 sec. cor. of secs. 3 and 4, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 3 ft. diam., 2 ft. high, with brass cap mkd. 1/4 S3 S4 1915.
	Add the marks T20N R20W 1993 on the brass cap and rebuild mound of stone 3 ft. base, to top.
	Cor. is located in heavy cholla cacti, on W. slope.
	N. 0°06' W., beginning new measurement.
25.68	The orig. closing cor. of secs. 3 and 4, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, in a scattered mound of stone, with a scattered mound of stone to the S., with brass cap mkd. T21N R20W S34 S4 S3 R20N R20W CC 1915. Add the marks 1993 and chisel AM on brass cap. Remove brass cap from post and bury in place, 6 in. below surface. Dispose of post.

Dependent Resurvey of a Portion of the Subdivisional Lines

## T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona CHAINS 26.04 Intersect the Fifth Stan. Par. North. Point for the closing cor. of secs. 3 and 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 1 in. in the ground, to bedrock, supported in a mound of stone, 5 ft. base, to top, with brass cap mkd. T21N R20W **S34 S**3 S4 T20N'R20W CC 1993 Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post. From this cor. point, the true point for the stan. 1/4 sec. cor. of sec. 34, bears N. 89°53' E., 5.77 chs. dist., as described in the field note record of the dependent resurvey of the Fifth Stan. Par. N., T. 21 N., R. 20 W., executed concurrently under this same group. Cor. is located on rock outcrop, on steep SW slope. From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., firmly set projecting 2 ins. above, with brass cap mkd. T20N R20W S32 S33 S5 S4 T19N 1993, as described in the field note record of the dependent resurvey of a portion of the S. Bdy., T. 19 N., R. 20 W., executed concurrently under this same group. N. 0°04' W., bet. secs. 32 and 33. Asc. over rolling land, through creosote and cacti. 40.07 The 1/4 sec. cor. of secs. 32 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, in a scattered mound of stone, with brass cap mkd. 1/4 S32 S33 1915. Add the marks T20N R20W 1993 on the brass cap and rebuild the mound of stone, 3 ft. base, to top. Cor. is located 80 lks. W. of drainage 5 lks. wide, 1 ft. deep,

drains W.

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	N. 0°05' E., beginning new measurement.
40.00	The cor. of secs. 28, 29, 32, and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, in a scattered mound of stone, with a mound of stone to the W., 2 ft. base, 2 ft. high, with brass cap mkd. T20N R20W S29 S28 S32 S33
	Add the marks 1993 on the brass cap and rebuild the mound of stone, 3 ft. base, to top.
	Cor. is located on E. slope, 3.15 chs. N. of wash, 45 lks. wide, 2 ft. deep, drains SW.
	From the cor. of secs. 27, 28, 33, and 34.
	N. 89°27' W., bet. secs. 28 and 33.
	Over rolling hills, through creosote and cacti.
40.22	The 1/4 sec. cor. of secs. 28 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. S28 1/4 S33 1915.
	Add the marks T20N R20W 1993 on the brass cap.
	Cor. is located in center of wash, approximately 5 chs. wide, drains WNW.
	S. 89°58' W., beginning new measurement.
39.96	The cor. of secs. 28, 29, 32, and 33.
	N. 0°03' E., bet. secs. 28 and 29.
	Over rolling hills, through creosote, yucca, and cacti.
33.60	Mossback Wash, 1.5 chs wide, 2 ft. deep, drains WNW.
35.70	S. edge of trail road, bears E. and W.
39.97	The 1/4 sec. cor. of secs. 28 and 29, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, in a scattered mound of stone, with a mound of stone to the W., 2 ft. base, 1 ft. high, with brass cap mkd. 1/4 S29 S28 1915.
	Add the marks T20N R20W 1993 on the brass cap and rebuild the mound of stone, 3 ft. base, to top.

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Cor. is located on S. slope, 10 lks. E. of drainage, 4 lks. wide 1 ft. deep, drains S.
	N. 0°01' E., beginning new measurement.
39.93	The cor. of secs. 20, 21, 28, and 29, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, encircled in a collar of stone, with brass cap mkd. T20N R20W S20 S21 S29 S28 1915.
	Add the marks 1993 on the brass cap.
	Cor. is located on SW slope near base of Thumb Butte.
	From the cor. of secs. 21, 22, 27, and 28.
	N. 89° 45' W., bet. secs. 21 and 28.
19.46	Intersect line 1-2, Gladys Mine lode, M.S. 3006A, not monumented.
	From this point, cor. 1, Gladys Mine lode, M.S. 3006A, bears N. 47°01' E., 2.27 chs. dist., hereinafter described.
	From this same point, cor. 2, Gladys Mine lode, identical with cor. 4, Ida lode, cor. 1, Mossback lode, and cor. 1, Mossback Extension lone, M.S. 3006A, bears S. 47°01' W., 6.82 chs. dist., hereinafter described.
39.30	Intersect line 2-3, Mossback Extension lode, M.S. 3006A, not monumented.
	From this point, cor. 2, Mossback Extension lode, identical with cor. 2 Mossback lode, M.S. 3006A, bears S. 36°46' E., 12.31 chs. dist., hereinafter described.
	From this same point, cor. 3, Mossback Extension lode, M.S. 3006A, bears N. 36°46' W., 10.43 chs. dist., hereinafter described.
39.87	The 1/4 sec. cor. of secs. 21 and 28, monumented with an iron post, 1 in. diam., firmly set, projecting 22 ins. above ground, in a mound of stone, 2 ft. base, 12 ins. high, with brass cap mkd. S21 1/4 S28 1915.
	Add the marks T20N R20W 1993 on the brass cap.
	Cor. is located 100 lks. E. of drainage, 10 lks. wide, 2 ft. deep, drains SSW.

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	N. 89° 49' W., beginning new measurement.
40.04	The cor. of secs. 20, 21, 28, and 29.
	N. 0°02' W., bet. secs. 20 and 21.
40.09	The 1/4 sec. cor. of secs. 20 and 21. monumented with an iron post, 1 in. diam., firmly set, projecting 16 in. above ground, with brass cap mkd. 1/4 S20 S21 1993.
	Add the marks T20N R20W 1993 on the brass cap.
	Cor. is located 30 lks. N. of center of drainage, 7 lks. wide, 1 1/2 ft. deep, drains NW.
	N. 0°10' W., beginning new measurement.
39.97	The cor. of secs. 16, 17, 20, and 21, monumented with an iron post, 2 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. T20N R20W S17 S16 S20 S21 1915.
	Add the marks T20N R20W 1993 on the brass cap.
	Cor. is located 2.65 chs. N. of trail road, bears E. and W.
	From the cor. of secs. 15, 16, 21, and 22.
	N. 89°36' W., bet. secs. 16 and 21.
6.53	Point for AP 74, on the Mount Nutt Wilderness Area Bdy.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T20N R20W
	S16 MNWA
	S22 AP74
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 55 lks. E. of trail road, bears SSE and NNW.

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	·
40.11	The 1/4 sec. cor. of 16 and 21, monumented with an iron post, 1 in. diam., firmly set, projecting 20 ins. above ground, in a scattered mound of stone, with a mound of stone to the N., 2 ft. base, 1 1/2 ft. high, with brass cap mkd. S16 1/4 S21 1915.
	Rebuild mound of stone, 2 1/2 ft. base, 1 ft. high.
	Add the marks T20N R20W 1993 on the brass cap.
	N. 89°51' W., beginning new measurement.
39.91	The cor. of secs. 16, 17, 20, and 21.
	From the cor. of secs. 9, 10, 15, and 16.
	N. 89°34' W., bet. secs. 9 and 16.
	Over rolling land, through creosote and cacti.
39.90	Point for 1/4 sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T20N R20W S9 1/4 — S16 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located on N. bank of wash, bears E. and W.
60.57	Point for AP 65, on the Mount Nutt Wilderness Area Bdy.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T20N R20W S9 /MNWA
	S16 / AP65
	1993

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 60 lks. E. of trail road, bears NNE and SSW.
79.80	The cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, in a scattered collar of stone, with a mound of stone to the W., 2 ft. base, 1 ft. high, with brass cap mkd. T20N R20W S8 S9 S16 S17 1915.
	Add the marks 1993 on the brass cap and rebuild the collar of stone.
	Cor. is located on SW slope.
	From the cor. of secs. 3, 4, 9, and 10.
	N. 89°19' W., bet. secs. 4 and 9.
	Over rolling, rocky land, through creosote, yucca, and cacti.
39.76	The 1/4 sec. cor. of secs. 4 and 9, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, in a mound of stone 3 ft., to top, with a mound of stone to the N., 4 ft. base, 2 ft. high, with brass cap mkd. 1/4 S4 S9 1915.
	Add the marks T20N R20W 1993 on the brass cap.
	Cor. is located on a S. slope.
	N. 89°30' W., beginning new measurement.
5.11	Point for AP 54, on the Mount Nutt Wilderness Area Bdy.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to bedrock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T20N R20W S4 MNWA
	S9 AP54 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 2.65 chs. N. of trail road, bears SE and W.

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
39.96	The cor. of secs. 4, 5, 8, and 9, monumented with an iron post, 2 ins. diam., firmly set, projecting 36 ins. above ground, in a mound of stone 3 ft. base, to top, with a mound of stone to the W., 3 ft. base, 2 ft. high, with brass cap mkd. T20N R20W S5 S4 S8 S9 1915.
	Add the marks 1993 on the brass cap.
	Cor. is located on E. slope.
	N. 0°05' W., bet. secs. 4 and 5.
	Over rocky, broken land, creosote and cacti.
18.05	Point for AP 47, on the Mount Nutt Wilderness Area Bdy.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T20N R20W MN WA AP47 S5 S4 1993
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white colored plastic case beneath the stainless steel post.
	Cor. is located 170 lks. E. of trail road, bears ESE and WNW.
40.22	The 1/4 sec. cor. of secs. 4 and 5, monumented with an iron post, 1 in. diam., firmly set, projecting 36 ins. above ground, in a mound of stone, 3 ft. base. 2 ft. high, with a mound of stone to the W., 3 ft. base, 2 ft. high, with brass cap mkd. 1/4 S5 S4 1915.
	Add the marks T20N R20W 1993 on the brass cap.
	Cor. is located on S. slope.
	N. 0°04' E., beginning new measurement.
24.79	The orig. closing cor. of secs. 4 and 5, monumented with an iron post, 2 ins. diam., firmly set, projecting 20 ins. above ground, with a mound of stone to the S., 3 ft. base, 1 1/2 ft. high, with brass cap mkd. T21N R20W S33 S5 S4 T20N R20W CC 1915. Add the marks 1993 and chiseled AM on the brass cap. Remove brass cap
L	1

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	from post, and bury in place 1 ft. below surface. Dispose of post.
24.83	Intersect the Fifth Stan. Par. North.
	Point for the closing cor. of secs. 4 and 5.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T21N R20W S33
	S5 S4 T20N R20W
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located on N. slope, 10 lks. S. of center of wash, 10 lks. wide, 2 ft. deep, drains W.
	From this cor. point the stan. 1/4 sec. cor. of sec. 33, bears N. 89°49' W., 5.40 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 30 ins. above ground, supported in a mound of stone, 3 ft. base, 2 ft. high, with a mound of stone to the E., 3 ft. base, 2 1/2 ft. high, with brass cap mkd. SC T21N R20W S33 1/4 1993 1915, as described in the field note record of the dependent resurvey of the Fifth Stan. Par. N., T. 21 N., R. 20 W., executed concurrently under this same group.
	From the cor. of secs. 4, 5, 8, and 9.
	N. 89°52' W., bet. secs. 5 and 8.
	Over rocky, broken land, through creosote and cacti.
40.13	The 1/4 sec. cor. of secs. 5 and 8, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. S5 1/4 S8 1915.
	Add the marks 1993 on the brass cap.
	Cor. is located on a steep E. slope, at the base of cliff, 15 ft. high, bears ESE and WNW, 50 lks. W. of center of wash, 10 lks. wide, 2 1/2 ft. deep, drains W.

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	N. 89°59' W., beginning new measurement.
40.10	The cor. of secs 5, 6, 7, and 8, monumented with an iron post, 2 ins. diam., firmly set, projecting 20 ins. above ground, in a scattered mound of stone, with brass cap mkd. T20N R20W S5 S4 S8 S9 1915.
	Add the marks 1993 on the brass cap and rebuild the mound of stone, 3 ft. base, to top.
	Cor. is located on NW slope, 120 lks. S. of center of wash, 15 lks. wide, 10 ft. deep, drains SW.
	N. 0°04' W., bet. secs. 5 and 6.
	Over rolling terrain, through creosote, yucca and cacti.
40.31	The 1/4 sec. cor. of secs. 5 and 6, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, supported in a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd. 1/4 S6 S5 1915.
	Add the marks T20N R20W 1993 on the brass cap.
	Cor. is located on steep S. slope, 80 lks. N. of center of wash, 70 lks. wide, 1 1/2 ft deep, drains W.
	N. 0°04' W., beginning new measurement.
24.55	The orig. closing cor. for secs. 5 and 6, at intersection with the Fifth Stan. Par. North, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. T21N R20W S32 S6 S5 T20N R20W CC 1915.
	Add the marks 1993 on the brass cap.
	From this cor. point, the stan. 1/4 sec. cor. of sec. 32, bears N. 89°55' E., 5.67 chs. dist., monumented with an iron post, 1 in. diam., firmly set, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd. SC T21N R2OW 1/4 S32 1993 1915, as described in the field note record of the dependent resurvey of the Fifth Stan. Par. N., T. 21 N., R. 20 W.; executed concurrently under this same group.

Dependent Resurvey of a Portion of M.S. 3006A T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Restoring the survey executed by H. G. Schader, in 1912
	Gladys Mine lode
	From cor. 1, Gladys Mine lode, M.S. 3006A, monumented with a porphyry stone, 6 X 6 ins., firmly set, projecting 10 ins. above ground, mkd. G 1 3006A on S. face. Not remonumented.
	S. 47°01 W., on line 1-2, Gladys Mine lode.
2.27	Intersect the line bet. secs. 21 and 28, not monumented.
	From this point, the cor. of secs. 21, 22, 27, and 28, bears S. 89°45' E., 19.46 chs. dist., hereinbefore described.
9.09	Cor. 2, Gladys Mine lode, identical with cor: 4, Ida lode, cor. 1, Mossback lode, and cor. 1, Mossback Extension lode, M.S. 3006A, determined at the center of a mound, 4 ft. base, 1 ft. high. This is accepted as the best available evidence of the original cor. position.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled in a collar of stone, with brass cap mkd.
	T20N R20W
	GM MSBK MS 3006A S28
	EXT 2
	MS 3006A 1 4 IDA 1 MS 3006A
	MSBK MSBK MS 3006A
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	From this cor. point, the cor. of secs. 21, 22, 27, and 28, bears N. 79°25' E. 24.84 chs. dist., hereinbefore described.
	Cor. is located 55 lks. S. of trail road, bears ESE and WSW.

### Dependent Resurvey of a Portion of M.S. 3006A T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Mossback Extension lode
	From cor. 1, Mossback Extension lode, identical with cor. 2 Gladys lode, cor. 4 Ida lode, and cor. 1, Mossback lode, M.S. 3006A.
	S. 55°41' W., on line 1-2, Mossback Extension lode, identical with line 1-2 Mossback lode.
4.52	The SE. end center, Mossback Extension lode, identical with the NW. end center, Mossback lode, M.S. 3006A, determined at the center of a mound, 3 ft. base, 1 ft. high. This is accepted as the best available evidence of the original cor. position. Not remonumented.
	S. 55°29' W., beginning new measurement.
4.54	Cor. 2, Mossback Extension lode, identical with cor. 2, Mossback lode, M.S. 3006A, monumented with a quartz stone, 7 X 8 ins., firmly set, projecting 13 ins. above ground, mkd. M 2 3006A on E. face and 2 ME on N. face. Not remonumented.
	N. 36°46' W., on line 2-3, Mossback Extension lode.
12.31	Intersect the line bet. secs. 21 and 28, not monumented.
	From this point, the 1/4 sec. cor. of secs. 21 and 28, bears N. 89°45' W., 0.57 chs. dist., hereinbefore described.
22.74	Cor. 3, Mossback Extension lode, M.S. 3006A, monumented with a basalt stone, 8 X 8 ins., firmly set, projecting 18 ins. aboveground, mkd. 3 ME 3006A on E. face. Not remonumented.
	Mossback lode
	From cor. 4, Mossback lode, M.S. 3006A, monumented with a basalt stone, 8 x 8 x 24 ins., firmly set, projecting 8 ins. above ground, mkd. M4 3006A on SW face, with a mound of stone to the S. 2 ft. base, 12 ins. high.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

## Dependent Resurvey of a Portion of M.S. 3006A T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T20N R20W
	MSBK MS 3006A 4 1993
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white colored plastic case beneath the stainless steel post.
	Buried original stone monument alongside steel post.
	Cor. is located 65 lks. W. of trial road, bears NNE and SSW and 70 lks. E. of center of wash, 12 lks. wide, 1 ft. deep, drains SW.
	N. 39°49' W., on line 4-1, Mossback lode, identical in part with line 3-4, Ida lode.
13.84	Point for cor. 3, Ida lode, M.S. 3006A, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case 24 ins. in the ground.
	from which
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins.in the ground, for a reference monument, bears S. 68°07' W., 55.8 ft. dist., with cap mkd. T20N R20W RM IDA3 55.8 FT TO COR 1993, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the steel post.
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, for a reference monument, bears N. 18°33' W., 69.6 ft. dist., with cap mkd. T20N R20W RM IDA3 69.6 FT TO COR 1993, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 5/8 ins. white plastic case beneath the steel post.
	Cor. is located in center of trail road, bears SSE and NW.
21.24	Cor. 1, Mossback lode, identical with cor. 1, Mossback Extension lode, cor. 2, Gladys lode, and cor. 4, Ida lode, M.S. 3006A.

Dependent Resurvey of a Portion of M.S. 3006A T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona


#### **CHAINS**

#### Ida lode

From cor. 1, Ida lode, M.S.3006A, monumented with a porphyry stone  $10 \times 12 \times 24$  ins., firmly set, projecting 8 ins. above the ground, mkd. 1-I 3006 A on the S. face, with mound of stone to the NE, 2 ft. base, 1/2 ft. high.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.



Deposit a magnet in a  $1 \times 1 \times 2 = 5/8$  in. white colored plastic case beneath the stainless steel post.

Buried original stone monument alongside steel post.


From this cor. point the cor. secs. 21, 22, 27, and 28, bears N. 75° 22' E., 3.14 chs. dist., hereinbefore described.

Cor. is located in a drainage 10 lks. wide, 1 ft. deep, drains S.

S. 39°47' E., on line 1-2, Ida lode.

- The witness point at intersection with the line bet. secs. 27 and 28, hereinbefore described.
- 7.54 Point for AP 91, on the Mount Nutt Wilderness Area Bdy.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Dependent Resurvey of a Portion of M.S. 3006A T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Cor. is located 121 lks. W. of center of wash, 6 lks. wide, 6 ins. deep, drains S.
9.09	Cor. 2, Ida lode, M.S. 3006A, monumented with a stone, 6 x 12 x 24 ins., firmly set, projecting 10 ins. above ground, mkd. 3006A, no other marks visible, with mound of stone 3 ft. base, 1/2 ft. high, to S.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T20N R20W IDA MNWA MS 3006A S27
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Buried original stone monument alongside steel post.
	Cor. is located 20 lks. W. of drainage, 6 lks. wide, 1 ft. deep, drains SSW.
	S. 83°42' W., on line 2-3, Ida lode.
2.79	The witness point, at intersection with the line bet. secs. 27 and 28, hereinbefore described.
22.59	Cor. 3, Ida lode, on line 1-4, Mossback lode, M.S. hereinbefore described.
	N. 39°49' W., on line 3-4, identical with a portion of line 1-4, Mossback lode.
7.40	Cor. 4, Ida lode, identical with cor. 1, Mossback lode, cor. 1, Mossback Extension lode, and cor. 2, Gladys Mine lode.
	N. 80°00' E., on line 4-1, Ida lode.
21.71	Cor. 1, Ida lode, and place of beginning.

Dependent Resurvey of M.S. 3760B T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

**CHAINS** 

## Restoring the survey executed by Herman C. Zulch, in 1921


## Independence Mill Site

From cor. 1, Independence Mill Site, M.S. 3760B, monumented with a faint 'X' chiselled on a porphyry boulder, 6 1/2 x 8 x 4 ft. high, clearly mkd. I 1-M.S. 3760B on the S. side, with a scattered mound of stone to the E.

At the cor. point

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, in a 6  $1/2 \times 8 \times 4$  ft. high boulder, with top mkd.

#### T20N R20W



Deposit a magnet, a  $1 \times 7/8$  in. diam. cylinder, without a plastic case, beneath the tablet stem.

Cor. is located in a boulder field in Cottonwood Canyon wash, 90 lks. N. of center of stream, 8 lks. wide, 1/2 ft. deep, drains SW.

From this cor. point, the 1/4 sec. cor. of secs. 35 and 36, bears S. 23°26' E., 5.32 chs. dist. hereinbefore described.

S. 88°53' W., on line 1-2, Independence Mill Site.

Along Cottonwood Canyon wash bottom.

5.45 Cor. 2, Independence Mill Site, M.S. 3760B, monumented with a distinct 'X' chiselled in a porphyry boulder 6 x 9 x 5 ft. high. After a diligent search, was not able to find any other mks. on boulder.

At the cor. point

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, in a boulder 6 x 9 x 5 ft. high, with top mkd.

#### Dependent Resurvey of M.S. 3760B

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

**CHAINS** 

T20N R20W

MNWA 2 I. S35 MS 3760B

1993

Deposit a magnet, a  $1 \times 7/8$  in. diam. cylinder, without a plastic case, beneath the tablet stem.

Cor. is located in Cottonwood Canyon wash 80 lks. N. of center of stream, 8 lks. wide, 1/2 ft. deep, drains SSW.

S. 3°54' W., on line 2-3, Independence Mill Site.

Asc. out of Cottonwood Canyon, through creosote and cacti.

8.77 Cor. 3, Independence Mill Site, M.S. 3760B, monumented with an 'X' chiseled in a 4 x 9 1/2 x 4 ft. high porphyry boulder, mkd. I. 3-3760B on E. face.

At the cor. point

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, in boulder 4 x 9 1/2 x 4 ft. high, with top mkd.

Deposit a magnet, a  $1 \times 7/8$  in. diam. cylinder, without a plastic case, beneath the tablet stem.

Cor. is located on a moderate E. slope.

From this cor. point, a two inch pipe, 18 in. long, with a valve on top, in a dam 15 ft. long, 4 ft. high, bears E. and W., bears N. 38°20' E.

S. 83°40' E., on line 3-4, Independence Mill Site.

3.70 Wash, approximately 2 chs. wide, 3 ft. deep, drains SSW.

## Dependent Resurvey of M.S. 3760B T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

	1. 20 No., No. 20 No., Glia din Batt River Perfutali, Arizona
CHAINS	
5.35	Cor. 4, Independence Mill Site, M.S. 3760B, monumented with a weathered wooden post, 4 ft. long, 4 ins. square, firmly set, projecting 12 ins. above ground, in a collar of stone, with no visible marks on post. This is accepted as the best available evidence of the orig. cor. position.
	At the cor. point
<del>!</del>	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T20N R20W
	I. MNWA MS 3760B S35 4 1993
	Deposit the wood post in the mound of stone.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located on steep W. slope.
	N. 4°22' E., on line 4-1, Independence Mill Site.
9.47	Cor. 1, Independence Mill Site, M.S. 3760B, and place of beginning.
	Subdivision of Section 3 T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 2 and 3.
	N. 89°39' W., on the E. and W. centerline of sec. 3.
	Asc. over rugged, mountainous terrain, through sparse vegetation.
53.82	Point for a witness point, on the Mount Nutt Wilderness Area Bdy.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.


## Subdivision of Section 3 T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	WP T20N R20W  MNWA C —— C S3 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 75 lks. W. of cliff face, bears N. and S.
80.18	The 1/4 sec.cor. of secs. 3 and 4.
	Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
	In Section 1
	From the Stan. Cor. of Tps. T. 21 N., Rs. 19 and 20 W., hereinbefore described.
	N. 89° 53' W., on the Fifth Stan. Par. N., (N. bdy).
5.70	The 1/4 sec. cor. of sec. 1 only, T. 20 N., R. 20 W, hereinbefore described.
	N. 89° 53' W., on the Fifth Stan. Par. N., (N. bdy).
4.42	AP 1, on the Fifth Stan. Par. N., (N. Bdy.), monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. T21N R20W S36 AP1 S1 MNWA T20N 1993, as described in the field note record of the dependent resurvey of the Fifth Stan. Par. N., T. 21 N., R. 20 W., executed concurrently under this group.
	S 16°49' E., on line 1-2.
4.01	Point for AP 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

## Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

CHAINS




Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 110 lks. E. of trail road, bears N. and S.

S. 12°30' E., on line 2-3.

7.82 Point for AP 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.




Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 100 lks. E. of trail road, bears SSE and NNW.

S. 6°21' E., on line 3-4.

3.75 Point for AP 4.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 70 lks. E. of trail road, bears N. and SSE.

## Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary R. 20 W., Gila and Salt River Meridian, Arizona

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	S. 32°06' E., on line 4-5.
6.25	Point for AP 5.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T20N R20W
	S1 AP5 MINWA
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 70 lks. E. of trail road, bears NNW and SE.
	S. 30°39' E., on line 5-6.
5.88	Point for AP 6.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T20N R20W
	S1 AP6 MINIWA
	1993
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white colored plastic case beneath the stainless steel post.
	Cor. is located 110 lks. E. of trail road, bears N. and SE, in curve.
	S. 6°18' W., on line 6-7.
5.24	Point for AP 7.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

## Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

**CHAINS** 

T20N R20W
S1 AP7
MINWA

Deposit a magnet in a  $1 \times 1 \times 2$  5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 30 lks. E. of trail road. bears NNE and SSW, 25 lks. S. of prospect hole 20 ft. diam., 15 ft. deep.

S. 29°13' W., on line 7-8.

3.19 Point for AP 8.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T20N R20W
S1 AP8
MNWA
1993

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 50 lks. E. of trail road, bears NE. and SW.

S. 0°31' W., on line 8-9.

4.64 Point for AP 9.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T20N R20W S1 AP9 MNWA 1993

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 75 lks. E. of trail road. bears SSE and NNW.


## Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary R. 20 W., Gila and Salt River Meridia

,	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	S. 26°23' E., on line 9-10.
4.22	Point for AP 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T20N R20W
	S1 AP10
	MINIWA
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 100 lks. E. of trail road, bears SE and NNW.
	S. 29°54' E., on line 10-11.
3.11	Point for AP 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T20N R20W
	S1 AP11 MNWA
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 60 lks. E. of trail road. bears ESE and WNW.
	S. 66°27' E., on line 11-12.
3.38	Point for AP 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	ı

#### Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

CHAINS




Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 55 lks. E. of trail road, bears ESE and WNW; 110 lks. W. center of drainage, 4 lks. wide, 1 ft. deep, drains SE.

S. 50°16' E., on line 12-13.

4.71 Point for AP 13.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.




Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 100 lks. E. of trail road. bears SSE and NW.

S. 38°11' E., on line 13-14.

4.67 Point for AP 14.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.



Deposit a magnet in a  $1 \times 1 \times 2 = 5/8$  in. white colored plastic case beneath the stainless steel post.

## Metes—and—Bounds Survey of the Mount Nutt Wilderness Area Boundary

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Cor. is located 100 lks. E. of trail road, bears SE and curve.
	S. 27°22' E., on line 14-15.
5.39	Point for AP 15.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T20N R20W
	S1 MNWA AP15
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 50 lks. N. of trail road. bears E and NW.
	N. 74°35' E., on line 15-16.
5.27	Point for AP 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T20N R20W
	MNWA
	AP16
	21 -
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 70 lks. N. of trail road, bears SSE and WNW; 60 lks. E. of abandoned trail road, bears N. and S.
	S. 67°39' E., on line 16-17.
3.20	Point for AP 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

## Metes-and-Bounds Survey of the

Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

CHAINS

T20N R20W MNWA AP17 S1 1993


Deposit a magnet in a  $1 \times 1 \times 2$  5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 60 lks. N. of trail road. bears ESE and WNW.

S. 84°46' E., on line 17-18.

4.84 Point for AP 18.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.




Deposit a magnet in a 1  $\times$  1  $\times$  2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 70 lks. N. of trail road, bears SE and NW, in curve, 40 lks. W. of center of wash, 30 lks. wide, 5 ft. deep, drains SSW.

S. 45°44' E., on line 18-19.

3.08 Point for AP 19.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a  $1 \times 1 \times 2 = 5/8$  in. white colored plastic case beneath the stainless steel post.

## Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Cor. is located 50 lks. N. of trail road. bears ENE and WSW, 50 lks. W. of center of drainage, 4 lks. wide, 1 ft. deep, drains S.
	N. 49°33' E., on line 19-20.
3.14	Point for AP 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T20N R20W MNWA AP20 S1 1993
	Deposit a magnet in a 1 $\times$ 1 $\times$ 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 100 lks. W. of center of a wash, 50 lks. wide, 20 ft. deep, drains SE.
	S. 16°50' E., on line 20-21.
3.04	Point for AP 21.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T20N R20W  MNWA  AP21  S1  1993
	Deposit a magnet in a 1 $\times$ 1 $\times$ 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 50 lks. E. of trail road. bears SSE and NNW; 130 lks. W. of center of wash, 100 lks. wide, 20 ft. deep, drains SSE.
	S. 26°26' E., on line 21-22.
i	

## Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
5.76	The witness point, at intersection with line bet. secs. 1 and 12, hereinbefore described.
	In Section 12
	S. 26°26' E., continuing on line 21-22, beginning new measurement.
0.79	AP 22, on the E. bdy. of the Tp., identical with AP 57, T. 20 N., R. 19 W., hereinbefore described.
	From AP 23, on the E. bdy. of the Tp., identical with AP 62, T. 20 N., R. 19 W., hereinbefore described.
	N. 26°47' W., on line 23-24.
3.55	The witness point, at intersection with line bet. secs. 1 and 12, hereinbefore described.
	In Section 12
	N. 26°47' W., continuing on line 23-24, beginning new measurement.
5.37	Point AP 24
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T20N R20W
	AP24 \ MNWA \ 1993
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white colored plastic case beneath the stainless steel post.
	Cor. is located 50 lks. S. of trail road, bears SE and WNW, in curve.
	N. 87°43' W., on line 24-25.
3.90	Point for AP 25.

## Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

**T20N R20W** 

\_\_\_\_s

AP25

MNWA 1993

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 65 lks. S. of trail road, bears ESE and WNW.

N. 66°51' W., on line 25-26.

8.08 Point for AP 26.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T20N R20W

S1

AP26

MNWA

1993

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 100 lks. S. of trail road. bears SE and NW; 70 lks. W. of center of drainage, 5 lks. wide, 1 ft. deep, drains SW.

S. 85°55' W., on line 26-27.

6.55 Point for AP 27.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T20N R20W

AP27

MNWA

1993

## Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 50 lks. S. of trail road, bears SE and NW; 2 chs. E. of center of wash, 120 lks. wide, 2 ft. deep, drains SSW.
	N. 29°16' W., on line 27-28.
4.74	Point for AP 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T20N R20W
	S1
	AP28
	MNWA \ 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 40 lks. S. of trail road. bears SE and NW, 25 lks. W. of center of drainage, 20 lks. wide, 2 ft. deep, drains SSE.
	S. 56°58' W., on line 28-29.
11.27	Point for AP 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T20N R20W S1
	AP29
	MNWA 1993
	Deposit a magnet in a 1 $\times$ 1 $\times$ 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located on hilltop.
	N. 80°39' W., on line 29-30.

# Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary R. 20 W., Gila and Salt River Meridian, Arizona

,	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
12.71	Point for AP 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T20N R20W S1
	AP30 MNWA 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located on hilltop.
	S. 64°50' W., on line 30-31.
11.82	Point for AP 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, supported in a mound of stone, 3 ft. base, to top with brass cap mkd.
	T20N R20W \ S1
	AP31 MNWA
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located on top of rocky, flat, hilltop.
	N. 30°07' W., on line 31-32.
17.94	Point for AP 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. in the ground, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.

## BOOK 5441

56

## Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary R. 20 W., Gila and Salt River Meridian, Arizona

T. 20 N.

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T20N R20W
	MNWA S1 AP32 1993
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white colored plastic case beneath the stainless steel post.
	Cor. is located on rocky, hilltop.
	N. 55°59' W., on line 32-33.
11.63	Point for AP 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T20N R20W S1
	AP33
	MNWA 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located in the center of rocky, spur, slopes NE.
	N. 86°43' W., on line 33-34.
3.96	AP 34, at intersection with the line bet. secs. 1 and 2, hereinbefore described.
	S. 0°04' E., on line bet. secs. 1 and 2.
25.08	The cor. of secs. 1, 2, 11 and 12, hereinbefore described.
	In Section 2
	S. 89°55' W., on line bet. secs. 2 and 11.
4.58	The witness point, on line bet. secs. 2 and 11, hereinbefore described.
<u> </u>	

## B00K 5441

57

## Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

 т.	20	Ν.,	R.	20	W.,	Gila	and	Salt	River	Meridian,	Arizona

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
40.08	The 1/4 sec. cor. of secs. 2 and 11, hereinbefore described.
	N. 89°30' W., on line bet. secs. 2 and 11.
1.89	The witness point, on line bet. secs. 2 and 11, hereinbefore described.
23.70	The witness point, on line bet. secs. 2 and 11, hereinbefore described.
39.90	The cor. of secs. 2, 3, 10 and 11, hereinbefore described.
	In Section 3
	N. 89°52' W., on line bet. secs. 3 and 10.
16.32	The witness point, on line bet. secs. 3 and 10, hereinbefore described.
39.98	The 1/4 sec. cor. of secs. 3 and 10, hereinbefore described.
	S. 89°59' W., on line bet. secs. 3 and 10.
32.81	The witness point, on line bet. secs. 3 and 10, hereinbefore described.
40.17	The cor. of secs. 3, 4, 9 and 10, hereinbefore described.
	N. 0°05' W., on line bet. secs. 3 and 4.
39.95	The 1/4 sec. cor. of secs. 3 and 4, hereinbefore described.
	S. 89°39' E., on the E. and W. centerline of sec. 3.
26.36	The witness point, on the E. and W. centerline of sec. 3, hereinbefore described.
80.18	The 1/4 sec. cor. of secs. 2, and 3, hereinbefore described.
	N. 0°01' W., on line bet. secs. 2 and 3.
26.41	The closing cor. of secs. 3 and 4, at intersection with the Fifth Stan. Par. N., (N. Bdy), hereinbefore described.

# Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	In Section 2
	S. 89°56' E., on the Fifth Stan. Par. N., (N. Bdy).
5.61	The Stan. 1/4 sec. cor. of sec. 35, hereinbefore described.
	In Section 5
	From AP 35, on the Fifth Stan. Par. N., N. Bdy.), identical with AP 41, T. 21 N., R. 20 W., monumented with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. T21N R20W MNWA S33 AP41 S5 AP35 T20N 1993, as described in the field note record of the dependent resurvey of the Fifth Stan. Par. N., T. 21 N., R. 20 W., executed concurrently under this same group.
	From this cor. point, the stan. 1/4 sec. cor. of sec. 33, bears S. 89°49' E., 18.59 chs. dist, hereinbefore described.
	S. 39°20' W., on line 35-36.
6.00	Point for AP 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. in the ground, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T20N R20W  MNWA S5 AP36
	1993
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white colored plastic case beneath the stainless steel post.
	Cor. is located 100 lks. E. of trail road, bears NNE and SSW.
	S. 25°15' W., on line 36-37.
7.75	Point for AP 37.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

## Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona **CHAINS** T20N R20W Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post. Cor. is located 50 lks. E. of trail road, bears N. and SSE. S. 7°58' W., on line 37-38. 8.92 Point for AP 38. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T20N R20W MNWA **AP38** 1993 Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post. Cor. is located on a spur, slopes SW; 85 lks. E. of trail road, bears NNE and SSW. S. 34°28' W., on line 38-39. 15.81 Point for AP 39. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T20N R20W MNWA **AP39** Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post. Cor. is located 50 lks. E. of trail road, bears NNE. and SSE .

## Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	S. 48°27' E., on line 39-40.
5.79	Point for AP 40.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T20N R20W MNWA S5 AP40
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located on a spur, slopes SW; 100 lks. E. of trail road, bears ESE and NNW, in curve.
	S. 57°15' E., on line 40-41.
5.19	Point for AP 41.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T20N R20W MNWA AP41
	S5 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 105 lks. N. of trail road, bears E. and WSW.
<b>*</b>	S. 85°22' E., on line 41-42.
5.50	Point for AP 42.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
L	

## Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

CHAINS

T20N R20W MNWA AP42 S5 1993

Deposit a magnet in a  $1 \times 1 \times 2$  5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 35 lks. N. of trail road, bears E. and W; 50 lks. E. of center of wash, 10 lks. wide, 1 ft. deep, drains SW.

N. 76°14' E., on line 42-43.

6.28 Point for AP 43.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, with brass cap mkd.

T20N R20W MNWA AP43 S5 1993

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 100 lks. N. of trail road, bears SSE and SW, in curve, 65 lks. E. of center of wash, 15 lks. wide, 2 ft. deep, drains SSE.

S. 26°14' E., on line 43-44.

3.27 Point for AP 44.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T20N R20W MNWA AP44 S5 1993

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

# BOOK 5441 62 Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

	Mount Nutt Wilderness Area Boundary
	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Cor. is located 45 lks. N. of trail road, bears SSW and NNW, 20 lks. W. of right bank of wide flood plain, drains SW.
	S. 2°00' W., on line 44-45.
4.17	Point for AP 45.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, cemented in place, in volcanic rock outcrop, with top mkd.
	T20N R20W   MNWA   AP45
	S5
	1993
	Deposit a magnet, a 1 x 7/8 in. diam. cylinder, without a plastic case, beneath the tablet stem.
	Cor. is located on a spur, slopes SSW, 25 lks. N. of trail road, bears E and WNW, in curve, 35 lks. S. of center of wash, 50 lks. wide, 2 ft. deep, drains WSW.
	N. 86°50' E., on line 45-46.
4.55	Point for AP 46.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T20N R20W MNWA AP46
	S5 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 100 lks. N. of trail road, bears SE and WSW, 75 lks. N. center of wash, 10 lks. wide, 4 ft., drains SSW.
	S. 75°54' E., on line 46-47.
4.49	Point for AP 47, on the line bet. secs. 4 and 5, hereinbefore described.

## Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary R. 20 W., Gila and Salt River Meridian, Arizona

T. 20 N.


	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	In Section 4
	S. 49°35' E., on line 47-48.
5.58	Point for AP 48.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T20N R20W
	MNWA AP48
	S4
	1993
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white colored plastic case beneath the stainless steel post.
	Cor. is located 90 lks. N. of trail road, bears SSE and NW, 75 lks. N. center of wash, 10 lks. wide, 4 ft. deep, drains SSW.
	S. 33°10' E., on line 48-49.
5.43	Point for AP 49.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T20N R20W
	MNWA AP49
	S4 \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 180 lks. E. of trail road, bears N. and SSE, 65 lks. N. center of drainage, 4 lks. wide, 2 ft.deep, drains WNW.
	S. 8°17' E., on line 49-50.
6.70	Point for AP 50.

#### Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.



Deposit a magnet in a  $1 \times 1 \times 2$  5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 40 lks. N. of trail road, bears SSE and NW.

S. 71°37' E., on line 50-51.

5.10 Point for AP 51.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.




Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 35 lks. N. of trail road, bears ENE and WNW.

N. 50°51' E., on line 51-52.

3.41 Point for AP 52.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.



# BOOK 5441 65

## Metes-and-Bounds Survey of the

Mount Nutt Wilderness Area Boundary
T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 85 lks. N. of trail road, bears ESE and SW, 42 lks. W. center of wash, 6 lks. wide, 1 ft. deep, drains SE.
	S. 65°25' E., on line 52-53.
8.39	Point for AP 53.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T20N R20W MNWA AP53
	S4 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 85 lks. N. of trail road, bears ESE and WNW; 175 lks. S. of center of wash, 6 lks. wide, 2 ft. wide, WSW.
	S. 86°57' E., on line 53-54.
11.58	AP 54, on the line bet. secs. 4 and 9, hereinbefore described.
	In section 9
	S. 53°54' E., on line 54-55.
17.57	Point for AP 55.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T20N R20W MNWA AP55 S9
	1993
1	

## Metes—and—Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

#### CHAINS

Deposit a magnet in a  $1 \times 1 \times 2 = 5/8$  in. white colored plastic case beneath the stainless steel post.

Cor. is located 115 lks. E. of trail road, bears SSW and NW, in curve, 140 lks. S. of left bank of wash, 2.5 chs. wide, 2 ft. deep, drains WSW.

S. 48°54' W., on line 55-56.

#### 4.69 Point for AP 56.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.



1993


Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 40 lks. N. of trail road, bears ENE and SSW.

S. 20°30' W., on line 56-57.

#### 6.78 Point for AP 57.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 55 lks. N. of trail road, bears NNE and SW.

S. 39°38' W., on line 57-58.

## Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
5.18	Point for AP 58.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T20N R20W
	S9 MINWA AP58
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 95 lks. E. of trail road, bears ENE and WSW.
	S. 68°50' W., on line 58-59.
3.26	Point for AP 59.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T20N R20W
	S9 MNWA AP59
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 45 lks. E. of trail road, bears ENE and SSE, in curve.
	S. 21°35' E., on line 59-60.
5.29	Point for AP 60.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

#### Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

CHAINS

T20N R20W S9 MNWA AP60 1993

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 135 lks. E. of trail road, bears N. and SSE, 225 lks. W. of center of wash, 70 lks.wide, 1 ft. deep, drains SSW.

S. 22°34' W., on line 60-61.

6.65 Point for AP 61.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T20N R20W MNW

> , 1993

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 55 lks. E. of trail road, bears NNE and SSW.

S. 10°20' W., on line 61-62.

8.85 Point for AP 62.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T20N R20W S9 MNWA AP62 1993

# Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary R. 20 W., Gila and Salt River Meridian, Arizona

20 N.

<b></b>	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 55 lks. E. of trail road, bears NNE and SSW, 65 lks. S. of drainage, 10 lks.wide, 1 ft. deep, drains NE.
	S. 20°32' W., on line 62-63.
10.84	Point for AP 63.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T20N R20W
	S9 MNWA AP63
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 90 lks. E. of trail road, bears NNE and SW.
	S. 31°33' W., on line 63-64.
10.25	Point for AP 64.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T20N R20W
	s9
	MNWA AP64
	1993
	Deposit a magnet in a 1 $\times$ 1 $\times$ 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 110 lks. E. of trail road, bears NE and SSW.
	S. 20°46' W., on line 64-65.
17.41	Point for AP 65, on the line bet. secs. 9 and 16, hereinbefore described.

## Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	In section 16
	S. 19°44' W., on line 65-66.
10.23	Point for AP 66.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T20N R20W
	S16 MNWA AP66
	Deposit a magnet in a 1 $\times$ 1 $\times$ 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 90 lks. E. of trail road, bears N. and SSE.
	S. 19°54' E., on line 66-67.
4.79	Point for AP 67.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.
	T20N R20W
	S16 MNWA AP67
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 95 lks. E. of trail road, bears SSW and NW.
	S. 22°21' W., on line 67-68.
11.42	Point for AP 68.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

## Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

CHAINS

T20N R20W

S16

MINWA AP68

1991

Deposit a magnet in a  $1 \times 1 \times 2$  5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 120 lks. E. of trail road, bears NNE and SSW, 90 lks. S. of center of wash, 9 lks. wide, 1 ft. deep, drains WSW.

S. 66°42' E., on line 68-69.

16.49 Point for AP 69.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T20N R20W MNWA AP69 S16 1993

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 190 lks. E. of trail road, bears ESE and WNW.

S. 54°21' E., on line 69-70.

12.29 Point for AP 70.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T20N R20W MNWA AP70 S16 1993

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

## Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Cor. is located 75 lks. E. of trail road, bears SSE and NW, 60 lks. S. of center of wash, 24 lks. wide, 3 ft. deep, drains WSW.
	S. 36°03' E., on line 70-71.
21.40	Point for AP 71.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T20N R20W MNWA S16 AP71
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 210 lks. E. of trail road, bears SE and NW.
	S. 33°08' E., on line 71-72.
13.82	Point for AP 72.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T20N R20W
	MNWA AP72
	S16 A. / 2
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 60 lks. E. of trail road, bears SE and NW.
	S. 56°36' E., on line 72-73.
14.05	Point for AP 73.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

#### Metes—and—Bounds Survey of the Mount Nutt Wilderness Area Boundary


	Mount Nutt Wilderness Area Boundary T 20 N P 20 W Cile and Salt Bivor Moridian Arizona
CHAINS	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
	T20N R20W MNWA S16 AP73
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 50 lks. E. of trail road, bears SE and NW.
	S. 32°53' E., on line 73-74.
6.31	AP 74, on the line bet. secs. 16 and 21, hereinbefore described.
	In Section 21
	S. 35°01' E., on line 74-75.
11.39	AP 75, on the line bet. secs. 21 and 22, hereinbefore described.
	In Section 22
	S. 38°57' E., on line 75-76.
6.33	Point for AP 76.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T20N R20W MNWA AP76 S22
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white colored plastic case beneath the stainless steel post.
	Cor. is located 50 lks. E. of trail road, bears SSE and NNW.
	s. 15°52' E., on line 76-77.
15.22	Point for AP 77.

#### Metes—and—Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

**CHAINS** 

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.




Deposit a magnet in a  $1 \times 1 \times 2 = 5/8$  in. white colored plastic case beneath the stainless steel post.

Cor. is located 50 lks. E. of trail road, bears SSE and NW, 35 lks. S. of center of wash, 20 lks. wide, 2 ft. deep, drains WNW.

S. 43°16' E., on line 77-78.

8.46 Point for AP 78

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located in an area dissected by several small drainages, 45 lks. E. of trail road, bears SSW and NNW;

S. 1°54' W., on line 78-79.

9.82 Point for AP 79.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T20N R20W

#### Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

	Mount Nutt Wilderness Area Boundary T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	1. 20 No., Ro. 20 Wo., Gila aim Sait Rivel Fælldlall, Alli201a
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.  Corner is located 45 lks. E. of trail road, bears N. and SSE.
	S. 31°35' E., on line 79-80.
4.57	Point for AP 80.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T20N R20W
	S22 MNWA AP80
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Corner is located 55 lks. E. of trail road, bears N. and SSE.
	S. 7°57' E., on line 80-81.
7.77	Point for AP 81.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T20N R20W
	S22 AP81
	MNWA 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Corner is located 115 lks. E. of trail road, bears NNE and SW, 30 lks. S. of center of drainage, 5 lks wide, 1 ft. deep, drains SSW.
	S. 51°45' W., on line 81-82.
15.60	Point for AP 82.

# Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T20N R20W
	S22
	AP82 MNWA
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Corner is located 55 lks. S. of trail road, bears NE and WSW.
	S. 66°45' W., on line 82-83.
5.24	AP 83, on the line bet. secs. 21 and 22, hereinbefore described.
	In Section 21
	S. 64°15' W., on line 83-84.
5.92	Point for AP 84.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T20N R20W
	S21 AP84 MNWA 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Corner is located 40 lks. S. of trail road, bears NE and SE, 70 lks. N. of drainage, 5 lks. wide, 2 ft. deep, drains WSW.
	S. 38°15' W., on line 84-85.
4.81	Point for AP 85.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

### BOOK 5441

77

#### Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

CHAINS

T20N R20W 321 MNWA AP85 1993

Deposit a magnet in a  $1 \times 1 \times 2$  5/8 in. white colored plastic case beneath the stainless steel post.

Corner is located 55 lks. S. of trail road, bears NE and W.

S. 86°01' W., on line 85-86.

3.00 Point for AP 86.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T20N R20W



Deposit a magnet in a  $1 \times 1 \times 2$  5/8 in. white colored plastic case beneath the stainless steel post.

Corner is located 40 lks. S. of trail road, bears NNE and E.

S. 38°11' W., on line 86-87.

5.17 Point for AP 87.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T20N R20W

MNWA
AP87

S21
1993

Deposit a magnet in a  $1 \times 1 \times 2 = 5/8$  in. white colored plastic case beneath the stainless steel post.

## BOOK 5441

#### 78

# Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

Corner is located 60 lks. NE of intersection of two trail roads, NNE, E, and SSW, 90 lks. W. of center of wash, 50 lks. wide, 3 ft. deep, drains SW.  N. 80°57' E., on line 87-88.  12.99 Point for AP 88.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  T20N R20W MNWA AP 88  S21  1993  Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.  Corner is located 75 lks. N. of trail road, bears ESE and WSW, 180 lks., S. of center of wash, 1 ch. wide, 15 ft. deep, drains WSW.  S. 63°17' E., on line 88-89.  1.87 AP 89, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 22  S. 27°58' E., on line 89-90.  2.75 AP 90, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 27  S. 4°21' E., on line 90-91.  6.60 AP 91, on line 1-2, Ida lode, M.S. 3006A, hereinbefore described.  S. 39°47' E., on line 1-2, Ida lode, M.S. 3006A.		T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
NNE, E, and SSW, 90 lks. W. of center of wash, 50 lks. wide, 3 ft. deep, drains SW.  N. 80°57′ E., on line 87-88.  Point for AP 88.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  T20N R20W  NNWA  AP 88  S21  1993  Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.  Corner is located 75 lks. N. of trail road, bears ESE and WSW, 180 lks., S. of center of wash, 1 ch. wide, 15 ft. deep, drains WSW.  S. 63°17′ E., on line 88-89.  AP 89, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 22  S. 27°58′ E., on line 89-90.  2.75  AP 90, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 27  S. 4°21′ E., on line 90-91.  6.60  AP 91, on line 1-2, Ida lode, M.S. 3006A, hereinbefore described.  S. 39°47′ E., on line 1-2, Ida lode, M.S. 3006A.	CHAINS	
Point for AP 88.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  TZON RZOW  MNWA  AP 88  S21  1993  Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.  Corner is located 75 lks. N. of trail road, bears ESE and WSW, 180 lks., S. of center of wash, 1 ch. wide, 15 ft. deep, drains WSW.  S. 63°17' E., on line 88-89.  AP 89, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 22  S. 27°58' E., on line 89-90.  2.75 AP 90, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 27  S. 4°21' E., on line 90-91.  6.60 AP 91, on line 1-2, Ida lode, M.S. 3006A, hereinbefore described.  S. 39°47' E., on line 1-2, Ida lode, M.S. 3006A.		NNE, E, and SSW, 90 lks. W. of center of wash, 50 lks. wide,
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  T20N R20W MNWA  AP 88  S21  1993  Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.  Corner is located 75 lks. N. of trail road, bears ESE and WSW, 180 lks., S. of center of wash, 1 ch. wide, 15 ft. deep, drains WSW.  S. 63°17' E., on line 88-89.  1.87  AP 89, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 22  S. 27°58' E., on line 89-90.  2.75  AP 90, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 27  S. 4°21' E., on line 90-91.  6.60  AP 91, on line 1-2, Ida lode, M.S. 3006A, hereinbefore described.  S. 39°47' E., on line 1-2, Ida lode, M.S. 3006A.		N. 80°57' E., on line 87-88.
24 ins. in the ground, with brass cap mkd.  T20N R20W  MNWA  AP 88  S21  1993  Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.  Corner is located 75 lks. N. of trail road, bears ESE and WSW, 180 lks., S. of center of wash, 1 ch. wide, 15 ft. deep, drains WSW.  S. 63°17' E., on line 88-89.  1.87  AP 89, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 22  S. 27°58' E., on line 89-90.  2.75  AP 90, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 27  S. 4°21' E., on line 90-91.  6.60  AP 91, on line 1-2, Ida lode, M.S. 3006A, hereinbefore described.  S. 39°47' E., on line 1-2, Ida lode, M.S. 3006A.	12.99	Point for AP 88.
Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.  Corner is located 75 lks. N. of trail road, bears ESE and WSW, 180 lks., S. of center of wash, 1 ch. wide, 15 ft. deep, drains WSW.  S. 63°17' E., on line 88-89.  AP 89, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 22  S. 27°58' E., on line 89-90.  2.75 AP 90, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 27  S. 4°21' E., on line 90-91.  6.60 AP 91, on line 1-2, Ida lode, M.S. 3006A, hereinbefore described.  S. 39°47' E., on line 1-2, Ida lode, M.S. 3006A.		<del>-</del>
Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.  Corner is located 75 lks. N. of trail road, bears ESE and WSW, 180 lks., S. of center of wash, 1 ch. wide, 15 ft. deep, drains WSW.  S. 63°17' E., on line 88-89.  AP 89, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 22  S. 27°58' E., on line 89-90.  AP 90, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 27  S. 4°21' E., on line 90-91.  AP 91, on line 1-2, Ida lode, M.S. 3006A, hereinbefore described.  S. 39°47' E., on line 1-2, Ida lode, M.S. 3006A.		
Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.  Corner is located 75 lks. N. of trail road, bears ESE and WSW, 180 lks., S. of center of wash, 1 ch. wide, 15 ft. deep, drains WSW.  S. 63°17' E., on line 88-89.  AP 89, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 22  S. 27°58' E., on line 89-90.  2.75 AP 90, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 27  S. 4°21' E., on line 90-91.  AP 91, on line 1-2, Ida lode, M.S. 3006A, hereinbefore described.  S. 39°47' E., on line 1-2, Ida lode, M.S. 3006A.		AP 88
Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.  Corner is located 75 lks. N. of trail road, bears ESE and WSW, 180 lks., S. of center of wash, 1 ch. wide, 15 ft. deep, drains WSW.  S. 63°17' E., on line 88-89.  AP 89, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 22  S. 27°58' E., on line 89-90.  2.75 AP 90, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 27  S. 4°21' E., on line 90-91.  AP 91, on line 1-2, Ida lode, M.S. 3006A, hereinbefore described.  S. 39°47' E., on line 1-2, Ida lode, M.S. 3006A.		921
case beneath the stainless steel post.  Corner is located 75 lks. N. of trail road, bears ESE and WSW, 180 lks., S. of center of wash, 1 ch. wide, 15 ft. deep, drains WSW.  S. 63°17' E., on line 88-89.  1.87 AP 89, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 22  S. 27°58' E., on line 89-90.  2.75 AP 90, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 27  S. 4°21' E., on line 90-91.  6.60 AP 91, on line 1-2, Ida lode, M.S. 3006A, hereinbefore described.  S. 39°47' E., on line 1-2, Ida lode, M.S. 3006A.		
180 lks., S. of center of wash, 1 ch. wide, 15 ft. deep, drains WSW.  S. 63°17' E., on line 88-89.  1.87 AP 89, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 22  S. 27°58' E., on line 89-90.  2.75 AP 90, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 27  S. 4°21' E., on line 90-91.  6.60 AP 91, on line 1-2, Ida lode, M.S. 3006A, hereinbefore described.  S. 39°47' E., on line 1-2, Ida lode, M.S. 3006A.		
In Section 22  S. 27°58' E., on line 89-90.  2.75  AP 90, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 27  S. 4°21' E., on line 90-91.  AP 91, on line 1-2, Ida lode, M.S. 3006A, hereinbefore described.  S. 39°47' E., on line 1-2, Ida lode, M.S. 3006A.		180 lks., S. of center of wash, 1 ch. wide, 15 ft. deep, drains
In Section 22  S. 27°58' E., on line 89-90.  2.75 AP 90, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 27  S. 4°21' E., on line 90-91.  AP 91, on line 1-2, Ida lode, M.S. 3006A, hereinbefore described.  S. 39°47' E., on line 1-2, Ida lode, M.S. 3006A.		S. 63°17' E., on line 88-89.
S. 27°58' E., on line 89-90.  2.75  AP 90, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 27  S. 4°21' E., on line 90-91.  AP 91, on line 1-2, Ida lode, M.S. 3006A, hereinbefore described.  S. 39°47' E., on line 1-2, Ida lode, M.S. 3006A.	1.87	AP 89, on the line bet. secs. 21 and 22, hereinbefore described.
2.75  AP 90, on the line bet. secs. 21 and 22, hereinbefore described.  In Section 27  S. 4°21' E., on line 90-91.  AP 91, on line 1-2, Ida lode, M.S. 3006A, hereinbefore described.  S. 39°47' E., on line 1-2, Ida lode, M.S. 3006A.		In Section 22
In Section 27  S. 4°21' E., on line 90-91.  AP 91, on line 1-2, Ida lode, M.S. 3006A, hereinbefore described.  S. 39°47' E., on line 1-2, Ida lode, M.S. 3006A.		S. 27°58' E., on line 89-90.
S. 4°21' E., on line 90-91.  AP 91, on line 1-2, Ida lode, M.S. 3006A, hereinbefore described.  S. 39°47' E., on line 1-2, Ida lode, M.S. 3006A.	2.75	AP 90, on the line bet. secs. 21 and 22, hereinbefore described.
AP 91, on line 1-2, Ida lode, M.S. 3006A, hereinbefore described.  S. 39°47' E., on line 1-2, Ida lode, M.S. 3006A.		In Section 27
S. 39°47' E., on line 1-2, Ida lode, M.S. 3006A.		S. 4°21' E., on line 90-91.
	6.60	AP 91, on line 1-2, Ida lode, M.S. 3006A, hereinbefore described.
1.55 Cor. 2, Ida lode, M.S. 3006A, hereinbefore described.		S. 39°47' E., on line 1-2, Ida lode, M.S. 3006A.
	1.55	Cor. 2, Ida lode, M.S. 3006A, hereinbefore described.

## B00K<sub>79</sub>5441

### Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	S. 83°42' W., on line 2-3, Ida lode, M.S. 3006A.
2.79	The witness point, on the line bet. secs. 27 and 28, hereinbefore described.
	In Section 28
	S. 37°51' W., on line bet. the WP on the line bet. secs. 27 and 28 and AP 92.
6.71	Point for AP 92.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T20N R20W
	S28 MNWA AP92 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 45 lks. E. of trail road, bears NE and SW.
	S. 36°12' W., on line 92-93.
11.24	Point for AP 93.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T20N R20W
	S28 MNWA AP93
	1993
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white colored plastic case beneath the stainless steel post.
	Cor. is located 55 lks. S. of trail road, bears NE and SW, 2.75 chs. N. of right bank of wash, 2 chs. wide, 6 ft. deep, drains SW.

## Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary R. 20 W., Gila and Salt River Meridian, Arizona

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	S. 5°23' E., on line 93-94.
6.84	Point for AP 94.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T20N R20W
	S28 MNWA AP94 1993
	1995
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 120 lks. E. of trail road, bears NNE and S, 30 lks. S. of left bank of wash, 2 chs. wide, 8 ft. deep, drains W.
	S. 13°25' W., on line 94-95.
2.20	Point for AP 95.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T20N R20W
	S28 MNWA AP95
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 60 lks. E. of trail road, bears N. and SSE.
	S. 30°26' E., on line 95-96.
11.05	Point for AP 96.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

#### Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

CHAINS

T20N R20W S28 MNWA AP96 1993

Deposit a magnet in a  $1 \times 1 \times 2$  5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 45 lks. E. of trail road, bears SW and NNW, 120 lks. S. of center of drainage, 5 lks wide, 2 ft. deep, drains W.

S. 10°29' E., on line 96-97.

9.99 Point for AP 97.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

T20N R20W
S28 MNWA
AP97
1993

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 50 lks. E. of trail road, bears SSW and NNW, 175 lks. S. of center of wash, 36 lks. wide, 4 ft. deep, drains W.

S. 23°51' W., on line 97-98.

4.88 Point for AP 98.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T20N R20W
S28 MNWA
AP98

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

## Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary R. 20 W., Gila and Salt River Meridian, Arizona

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Cor. is located 45 lks. E. of trail road, bears NNE and S., in curve.
	S. 29°02' E., on line 98-99.
6.82	Point for AP 99.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T20N R20W MNWA AP99 1993
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white colored plastic case beneath the stainless steel post.
	Cor. is located 65 lks. E. of trail road, bears SSE and NNW.
	S. 4°14' E., on line 99-100.
3.37	Point for AP 100.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T20N R20W
	S28 MINWA AP100
	1993
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white colored plastic case beneath the stainless steel post.
	Cor. is located 60 lks. E. of trail road, bears N. and SE, in curve.
	S. 78°22' E., on line 100-101.
1.79	AP 101, on the line bet. secs. 27 and 28, hereinbefore described.

#### Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	In Section 27
	S. 87°52' E., on line 101-102.
1.84	Point for AP 102.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T20N R20W
	MNWA
	AP102
	S27 \
	1993
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white colored plastic case beneath the stainless steel post.
	Cor. is located 40 lks. E. of trail road, bears ESE and WNW, 125 lks. W. of center of wash, 15 lks. wide, 1 ft. deep, drains SSW.
	S. 30°55' E., on line 102-103.
2.94	Point for AP 103.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled in a collar of stone, with brass cap mkd.
	T20N R20W
	\ MNWA
	AP103
	s27
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 80 lks. E. of trail road, bears SSW and N, 2 chs. N. of center of wash, 15 lks. wide, 6 ft. deep, drains WSW.
	S. 38°36' W., on line 103-104.
5.32	AP 104, on the line bet. secs. 27 and 28, hereinbefore described.

## POOK 5441

#### Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	S. 28°42' E., on line 104-105.
2.13	Point for AP 105.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T20N R20W MNWA AP105 S27
	1993
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white colored plastic case beneath the stainless steel post.
	Cor. is located 45 lks. E. of trail road, bears SSE and NNW, 60 lks. S. of center of wash, 20 lks. wide, 3 ft. deep, drains SW.
	S. 76°55' E., on line 105-106.
3 <b>.7</b> 8	Point for AP 106.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T20N R20W MNWA AP106 S27
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 100 lks. N. of trail road, bears ESE and WNW, 130 lks. N. of center of wash, 100 lks. wide, drains WSW.
	S. 59°27' E., on line 106-107.
5.71	Point for AP 107.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

#### Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary


T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

**CHAINS** T20N R20W MNWA **AP107** S27 1993 Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post. Cor. is located 65 lks. E. of trail road, bears SE and NW, 75 lks. N. of center of wash, 85 lks. wide, 2 ft. deep, drains NNW. S. 47°49' E., on line 107-108. 4.10 AP 108, on the line bet. secs. 27 and 34, hereinbefore described. In Section 34 S. 60°19' E., on line 108-109. 5.01 Point for AP 109. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd. T20N R20W MNWA AP109 S34 1993 Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post. Cor. is located 70 lks. E. of trail road, bears SSE and WNW, 45 lks. E. of center of wash, 10 lks. wide, 1 ft. deep, drains NNW. S. 2°08' W., on line 109-110. 5.41 Point for AP 110. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

#### Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

CHAINS




Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 35 lks. N. of trail road, bears SSE and NNW.

S. 34°49' E., on line 110-111.

3.58 Point for AP 111.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.




Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 25 lks. E. of trail road, bears SSE and NNW, 70 lks. W. center of wash, 40 lks. wide, 1 ft. deep, drains N.

S. 73°45' E., on line 111-112.

4.12 Point for AP 112.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

## Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary R. 20 W., Gila and Salt River Meridian, Arizona

T. 20 N.

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Cor. is located 85 lks. E. of trail road, bears SE and WNW.
	S. 43°35' E., on line 112-113.
4.34	Point for AP 113.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T20N R20W MNWA AP113. S34 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
**	Cor. is located 10 lks. N. intersection of two of trail roads, one bears WNW, and SW, the access to Grapevine Canyon, bears NE.
	N. 58°44' E., on line 113-114.
8.35	Point for AP 114.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T20N R20W AP114 MINWA S34
	1993
	Deposit a magnet in a 1 x 1 x 2 $5/8$ in. white colored plastic case beneath the stainless steel post.
	Cor. is located 15 lks. N. of trail road, bears ENE and WSW.
	N. 67°19' E., on line 114-115.
7.24	Point for AP 115.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.

#### Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

**CHAINS** T20N R20W AP115 MNWA S34 1993 Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post. Cor. is located 30 lks. N. of trail road, bears ENE and WSW. N. 51°07' E., on line 115-116. 2.49 Point for AP 116. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd. T20N R20W **AP116** MNWA 1993 Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post. Cor. is located 35 lks. N. of trail road, bears ENE and WSW, 60 lks. S. of S. bank of Grapevine Canyon wash, bears WSW and ENE. S. 89°15' E., on line 116-117. 3.59 Point for AP 117. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T20N R20W **AP117** MNWA S34 1993 Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

### Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary R. 20 W., Gila and Salt River Meridian, Arizona

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Cor. is located 25 lks. E. of trail road, one bears ENE and SW, 10 lks. S. of S. bank of Grapevine Canyon, bears ENE and SW.
	N. 46°20' E., on line 117-118.
5.34	Point for AP 118.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T20N R20W AP118 MINWA
	S34 1993
	Deposit a magnet in a 1 $\times$ 1 $\times$ 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 5 lks. S. of S. bank of Grapevine Canyon, bears ENE and WSW.
	N. 79°42' E., on line 118-119.
1.26	Point for AP 119.
47	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, with a mound of stone 3 ft. base, to top, with brass cap mkd.
	T20N R20W
	AP119
	S34 MNWA
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 15 lks. E. of end of trail road, one bears SW, 5 lks. S. of S. bank of Grapevine Canyon, bears ENE and SW.
	S. 16°13' E., on line 119-120.
1.29	Point for AP 120.
L	

Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

**CHAINS** 

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T20N R20W

Deposit a magnet in a  $1 \times 1 \times 2$  5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 35 lks. E. of trail road, bears SW, 100 lks. S of center of wash, 50 lks. wide, 8 ft. deep, drains N.

S. 53°58' W., on line 120-121.

7.01 Point for AP 121.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T20N R20W

S34

AP121 MNWA 1993

Deposit a magnet in a  $1 \times 1 \times 2 = 5/8$  in. white colored plastic case beneath the stainless steel post.

Cor. is located 25 lks. S. of trail road, bears NNE and W, 30 lks. E. of center of wash, 10 lks. wide, 2 ft. deep, drains NNW.

N. 84°34' W., on line 121-122.

3.22 Point for AP 122.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T20N R20W

S34

AP122 MNWA

1993

## Metes-and-Bounds Survey of the

Mount Nutt Wilderness Area Boundary
R. 20 W., Gila and Salt River Meridian, Arizona T. 20 N..

p	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 20 lks. S. of trail road, bears ENE and WSW.
	S. 50°45' W., on line 122-123.
1.93	Point for AP 123.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T20N R20W S34
	AP123
	MNWA 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 30 lks. S. of trail road, bears NE and SW.
	S. 68°01' W., on line 123-124.
7.29	Point for AP 122.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	T20N R20W S34
	AP124
	MNWA 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
440	Cor. is located 20 lks. S. of trail road, bears ENE and WSW.
	S. 57°36' W., on line 124-125.
7.33	Point for AP 125.

#### Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

_					_
	CU	ľΛ	1	N	•

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T20N R20W S34 AP125 MNWA 1993

Deposit a magnet in a  $1 \times 1 \times 2$  5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 30 lks. S. of trail road, bears ENE and WSW.

S. 42°03' W., on line 125-126.

#### 17.63 Point for AP 126.

45

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T20N R20W S34 AP126 MNWA 1993

Deposit a magnet in a  $1 \times 1 \times 2 = 5/8$  in. white colored plastic case beneath the stainless steel post.

Cor. is located 50 lks. S. of trail road, bears NE and SW, 160 lks. N. of center of wash, 130 lks. wide, 10 ft. deep, drains WSW.

S. 58°03' W., on line 126-127.

#### 8.07 Point for AP 127.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

#### Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

CHAINS

T20N R20W S34 AP127 MNWA 1993

Deposit a magnet in a  $1 \times 1 \times 2 = 5/8$  in. white colored plastic case beneath the stainless steel post.

Cor. is located 52 lks. S. of trail road, bears ENE and WSW, 2.9 chs. W. of center of wash, 2.3 chs. wide, 15 ft. deep, drains SW.

S. 83°09' W., on line 127-128.

4.41 Point for AP 128.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T20N R20W S34 AP128 MNWA 1993

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 50 lks. S. of trail road, bears ENE and WSW, 27 lks. N. of center of wash, 10 lks. wide, 1 ft. deep, drains WSW.

S. 49°54' W., on line 128-129.

3.07 | Point for AP 129.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T20N R20W S34 MNWA AP129

1993

## BOOK 5441

94

#### Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona				
CHAINS					
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.				
	Cor. is located 65 lks. E. of trail road, bears NNE and SSW, 33 lks. W. of center of drainage, 6 lks. wide, 1 ft. deep, drains SSW.				
	S. 34°54' W., on line 129-130.				
3.37	AP 130, on the line bet. secs. 33 and 34, hereinbefore described.				
	In Section 33				
	S. 52°44' W., on line 130-131.				
8.81	Point for AP 131.				
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled in a collar of stone, with brass cap mkd.				
	T20N R20W S33				
	MNWA AP131 1993				
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.				
	Cor. is located 30 lks. E. of trail road, bears NE and SW, 25 lks. W. of center of wash, 25 lks. wide, 3 ft. deep, drains WSW.				
ريحي	s. 62°38' W., on line 131-132.				
2.48	Point for AP 132.				
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.				
	T20N R20W				
	S33 MNWA AP132				
	1993				

#### Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

,	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 60 lks. E. of intersection of two trail roads, bears ENE and NE and SW.
	N. 86°50' E., on line 132-133.
4.68	Point for AP 133.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T20N R20W MNWA AP133
Ç.	S33 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 36 lks. N. of trail road, bears NNE and WSW, 103 lks. E. of center of wash, 65 lks. wide, 3 ft. deep, drains SSW.
	N. 37°49' E., on line 133-134.
2.11	Point for AP 134.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T20N R20W MNWA
	AP134
	S33 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 40 lks. N. of trail road, bears NE and SSW, 20 lks. S. of center of wash, 25 lks. wide, 7 ft. deep, drains WSW.

#### Metes—and—Bounds Survey of the Mount Nutt Wilderness Area Boundary

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	N. 73°22' E., on line 134-135.
3.38	AP 135, on the line bet. secs. 33 and 34, hereinbefore described.
	In Section 34
	S. 65°29' E., on line 135-136.
7.24	Point for AP 136.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T20N R20W MNWA AP136
	S34 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 50 lks. N. of trail road, bears ENE and WNW, in curve, 2.3 chs. E. of center of wash, 2 chs. wide, 2 ft. deep, drains NNW.
	N. 77°41' E., on line 136-137.
2.68	Point for AP 137.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T20N R20W
	MNWA
	S34 AP137
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
O.	Cor. is located 10 lks. W. of center of wash, 1 ch. wide, 5 ft. deep, drains N., 75 lks. NW of bend in trail road, bears SSW and WSW.

## Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	S. 18°07' W., on line 137-138.
2.75	Point for AP 138.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T20N R20W MNWA AP138
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 45 lks. E. trail roads, bears N. and SSE, 50 lks. W. of center of wash, 2 chs. wide, 15 ft. deep, drains NNW.
	S. 46°53' E., on line 138-139.
3.52	Point for AP 139.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
*	T20N R20W MNWA AP139 S34 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 50 lks. E. of trail road, bears SSW and NNW, 130 lks. S. of right bank of wash, 210 lks. wide, 15 ft. wide, drains NNW.
	S. 12°34' W., on line 139-140.
5.50	Point for AP 140.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

#### Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

**CHAINS** 

T20N R20W
MNWA
AP140

1993


Deposit a magnet in a  $1 \times 1 \times 2 = 5/8$  in. white colored plastic case beneath the stainless steel post.

Cor. is located 30 lks. E. trail roads, bears NNE and SSE.

S. 16°15' E., on line 140-141.

6.42 Point for AP 141.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



1993


Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

Cor. is located 160 lks. N. of trail road, bears ESE and NNW.

S. 58°46' E., on line 141-142.

3.77 Point for AP 142.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

#### Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary R. 20 W. Gila and Salt River Meridia

	T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Cor. is located 50 lks. N. trail road, bears SE and WNW, 20 lks. S. of center of wash, 45 lks. wide, 2 ft. deep, drains WNW.
	S. 28°33' E., on line 142-143.
3.88	Point for AP 143.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T20N R20W
	\ MNWA
	S34 \ AP143
	554
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 50 lks. N. of trail road, bears SSE and NNW, 50 lks. W. of center of wash, 5 lks. wide, 1 ft. deep, drains NW.
	S. 8°37' E., on line 143-144.
3.82	Point for AP 144.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T20N R20W
	MNWA
	S34 AP144
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 50 lks. N. trail road, bears N. and SE, in curve.
	S. 80°49' E., on line 144-145.
6.75	Point for AP 145.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

### BOOK 5441

100

#### Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona **CHAINS** T20N R20W MNWA **AP145** S34 1993 Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post. Cor. is located 45 lks. N. of trail road, bears ESE and WNW. S. 60°29' E., on line 145-146. 2.99 Point for AP 146. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. T20N R20W MNWA AP146 S34 1993 Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post. Cor. is located 5 lks. N. trail road, bears ESE and WNW. S. 79°00' E., on line 146-147. 5.58 Point for AP 147. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T20N R20W MNWA AP147 1993 Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

#### Metes-and-Bounds Survey of the Mount Nutt Wilderness Area Boundary

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

**CHAINS** Cor. is located 121 lks. E. of trail road, bears SW and W. S. 33°16' W., on line 147-148. 3.04 Point for AP 148. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T20N R20W MNWA **AP148** S34 1993 Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post. Cor. is located 30 lks. E. trail road, bears SSE and NE, 20 lks. S. of center of wash, 15 lks. wide, 1 ft. deep. S. 44°47' E., on line 148-149. 5.48 AP 149, identical with AP 1, T. 19 N., R. 20 W., on the line bet. secs. 3 and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 28 ins. long, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T20N R20W MNWA S34 AP149 S3 AP1 T19N 1992, as described in the field note record of the dependent resurvey of the N. Bdy., T. 19 N., R. 20 W., executed concurrently under this same group. DESCRIPTION OF THE MOUNT NUTT WILDERNESS AREA BOUNDARY, IN T. 20 N., R. 20 W., GILA AND SALT RIVER, ARIZONA. The following description is for informational purposes only. Beginning at the stan. cor. of Tps. 21 N., Rs. 19 and 20 W. thence N. 89°53' W. on the Fifth Stan. Par. N. (N.Bdy.), 10.12 chs. dist. to Angle Point 1, T. 20 N., R. 20 W.; thence S. 16°49' E., 4.01 chs. dist. to Angle Point 2; thence S. 12°30' E., 7.82 chs. dist. to Angle Point 3; thence S. 6°21' E., 3.75 chs. dist. to Angle Point 4;

```
CHAINS
        thence S. 32°06' E.,
                              6.25 chs. dist. to Angle Point 5;
        thence S. 30°39' E.,
                              5.88 chs. dist. to Angle Point 6;
        thence S. 6°18' W.,
                              5.24 chs. dist. to Angle Point 7;
        thence S. 29°13' W.,
                              3.19 chs. dist. to Angle Point 8;
        thence S. 0°31' W.,
                             4.64 chs. dist. to Angle Point 9;
        thence S. 26°23' E.,
                             4.22 chs. dist. to Angle Point 10;
        thence S. 29°54' E.,
                             3.11 chs. dist. to Angle Point 11;
        thence S. 66°27' E.,
                             3.38 chs. dist. to Angle Point 12;
        thence S. 50°16' E.,
                             4.71 chs. dist. to Angle Point 13;
        thence S. 38°11' E.,
                             4.67 chs. dist. to Angle Point 14;
        thence S. 27°22' E.,
                             5.39 chs. dist. to Angle Point 15;
        thence N. 74°35' E., 5.27 chs. dist. to Angle Point 16;
        thence S. 67°39' E.,
                             3.20 chs. dist. to Angle Point 17;
        thence S. 84°46' E.,
                             4.84 chs. dist. to Angle Point 18;
        thence S. 45°44' E., 3.08 chs. dist. to Angle Point 19;
        thence N. 49°33' E., 3.14 chs. dist. to Angle Point 20;
        thence S. 16°50' E., 3.04 chs. dist. to Angle Point 21;
        thence S. 26°26' E., 6.55 chs. dist. to Angle Point 22,
             identical with Angle Point 57, T. 20 N., R. 19 W., on the
             line bet. secs. 7 and 12, on the E. bdy. of the Tp.
       From Angle Point 23, identical with Angle Point 62, T. 20 N.,
       R. 19 W., on the line bet. secs. 7 and 12, on the E. bdy. of the
       Tp.
       thence N. 26°47' W., 8.92 chs. dist. to Angle Point 24;
       thence N. 87°43' W., 3.90 chs. dist. to Angle Point 25;
       thence N. 66°51' W., 8.08 chs. dist. to Angle Point 26;
       thence S. 85°55' W., 6.55 chs. dist. to Angle Point 27;
       thence N. 29°16' W., 4.74 chs. dist. to Angle Point 28;
       thence S. 56°58' W., 11.27 chs. dist. to Angle Point 29;
       thence N. 80°39' W., 12.71 chs. dist. to Angle Point 30;
       thence S. 64°50' W., 11.82 chs. dist. to Angle Point 31;
       thence N. 30°07' W., 17.94 chs. dist. to Angle Point 32;
       thence N. 55°59' W., 11.63 chs. dist. to Angle Point 33;
       thence N. 86°42' W., 3.96 chs. dist. to Angle Point 34, on
            the line bet. secs. 1 and 2.
       thence S. 0°04' E., on the line bet. secs. 1 and 2, 25.08 chs.
            dist. to the cor. of secs. 1, 2, 11, and 12;
       thence S. 89°55' W., on the line bet. secs. 2 and 11, 40.08 chs.
            dist. to the 1/4 sec. cor. of secs. 2 and 11;
       thence N. 89°30' W., on the line bet. secs. 2 and 11, 39.90 chs.
            dist. to the cor. of secs. 2, 3, 10, and 11;
       thence N. 89°52' W., on the line bet. secs. 3 and 10, 39.98 chs.
            dist. to the 1/4 sec. cor. of secs. 3 and 10;
       thence S. 89°59' W., on the line bet. secs. 3 and 10, 40.17 chs.
            dist. to the cor. of secs. 3, 4, 9, and 10;
       thence N. 0°05' W., on the line bet. secs. 3 and 4, 39.95 chs.
            dist. to the 1/4 sec. cor. of secs. 3 and 4;
```

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

```
CHAINS
         thence S. 89°39' E., on the E. and W. center line of sec. 3,
              80.18 chs. dist. to the 1/4 sec. cor. of secs. 2 and 3;
         thence N. 0°01' W., on the line bet. secs. 2 and 3, 26.41 chs.
              dist. to the closing cor. of secs. 2 and 3;
         thence S. 89°56' E., on the Fifth Stan. Par. N., (N. Bdy.), 5.61
              chs. dist. to Stan. 1/4 sec. cor. of sec. 35.
         From Angle Point 35, identical with Angle Point 41, T. 21 N.,
         R. 20 W., on the Fifth Stan. Par. N.
         thence S. 39°20' W., 6.00 chs. dist. to Angle Point 36;
         thence S. 25°15' W., 7.75 chs. dist. to Angle Point 37;
         thence S. 7°58' W., 8.92 chs. dist. to Angle Point 38;
         thence S. 34°28' W., 15.81 chs. dist. to Angle Point 39;
         thence S. 48°27' E., 5.79 chs. dist. to Angle Point 40;
         thence S. 57°15' E., 5.19 chs. dist. to Angle Point 41;
         thence S. 85°22' E., 5.50 chs. dist. to Angle Point 42;
         thence N. 76°14' E., 6.28 chs. dist. to Angle Point 43;
         thence S. 26°14' E.,
                               3.27 chs. dist. to Angle Point 44;
         thence S. 2°00' W., 4.17 chs. dist. to Angle Point 45;
         thence N. 86°50' E.,
                               4.55 chs. dist. to Angle Point 46;
         thence S. 75°54' E.,
                               4.49 chs. dist. to Angle Point 47, on
              the line bet. secs. 4 and 5;
         thence S. 49°35' E.,
                               5.58 chs. dist. to Angle Point 48;
         thence S. 33°10' E.,
                               5.43 chs. dist. to Angle Point 49;
         thence S. 8°17' E., 6.70 chs. dist. to Angle Point 50;
         thence S. 71°37' E., 5.10 chs. dist. to Angle Point 51;
         thence N. 50°51' E., 3.41 chs. dist. to Angle Point 52;
         thence S. 65°25' E., 8.39 chs. dist. to Angle Point 53;
         thence S. 86°57' E., 11.58 chs. dist. to Angle Point 54, on
              the line bet. secs. 4 and 9;
         thence S. 53°54' E., 17.57 chs. dist. to Angle Point 55;
         thence S. 48°54' W., 4.69 chs. dist. to Angle Point 56;
         thence S. 20°30' W., 6.78 chs. dist. to Angle Point 57;
         thence S. 39°38' W., 5.18 chs. dist. to Angle Point 58;
         thence S. 68°50' W., 3.26 chs. dist. to Angle Point 59;
         thence S. 21°35' E., 5.29 chs. dist. to Angle Point 60;
         thence S. 22°34' W., 6.65 chs. dist. to Angle Point 61;
         thence S. 10°20' W., 8.85 chs. dist. to Angle Point 62;
         thence S. 20°32' W., 10.84 chs. dist. to Angle Point 63;
         thence S. 31°33' W., 10.25 chs. dist. to Angle Point 64;
         thence S. 20°46' W., 17.41 chs. dist. to Angle Point 65, on
              the line bet. secs. 9 and 16;
         thence S. 19°44' W., 10.23 chs. dist. to Angle Point 66;
         thence S. 19°54' E., 4.79 chs. dist. to Angle Point 67;
         thence S. 22°21' W., 11.42 chs. dist. to Angle Point 68;
         thence S. 66°42' E., 16.49 chs. dist. to Angle Point 69;
         thence S. 54°21' E., 12.29 chs. dist. to Angle Point 70;
         thence S. 36°03' E., 21.40 chs. dist. to Angle Point 71;
         thence S. 33°08' E., 13.82 chs. dist. to Angle Point 72;
```

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

CHAINS	
	thence S. 56°36' E., 14.05 chs. dist. to Angle Point 73;
	thence S. 32°53' E., 6.31 chs. dist. to Angle Point 74, on
	the line bet. secs. 16 and 21;
	thence S. 35°01' E., 11.39 chs. dist. to Angle Point 75, on
	the line bet. secs. 21 and 22;
	thence S. 38°57' E., 6.33 chs. dist. to Angle Point 76;
	thence S. 15°52' E., 15.22 chs. dist. to Angle Point 77;
	thence S. 43°16' E., 8.46 chs. dist. to Angle Point 78;
	thence S. 1°54' W., 9.82 chs. dist. to Angle Point 79;
	thence S. 31°35' E., 4.57 chs. dist. to Angle Point 80;
	thence S. 7°57' E., 7.77 chs. dist. to Angle Point 81;
	thence S. 51°45' W., 15.60 chs. dist. to Angle Point 82;
	thence S. 66°45' W., 5.24 chs. dist. to Angle Point 83, on
	the line bet. secs. 21 and 22;
	thence S. 64°15' W., 5.92 chs. dist. to Angle Point 84;
	thence S. 38°15' W., 4.81 chs. dist. to Angle Point 85;
	thence S. 86°01' W., 3.00 chs. dist. to Angle Point 86;
	thence S. 38°11' W., 5.17 chs. dist. to Angle Point 87;
	thence N. 80°57' E., 12.99 chs. dist. to Angle Point 88;
	thence S. 63°17' E., 1.87 chs. dist. to Angle Point 89, on
	the line bet. secs. 21 and 22;
	thence S. 27°58' E., 2.75 chs. dist. to Angle Point 90, on the line bet. secs. 22 and 27;
	thence S. 4°21' E., 6.60 chs. dist. to Angle Point 91, on
	line 1-2, Ida lode, M.S. 3006A;
	thence S. 39°47' E., on line 1-2, Ida lode, M.S. 3006A, 1.55 chs.
	dist. to cor. 2, Ida lode, M.S. 3006A.
	thence S. 83°42' W., on line 2-3, Ida lode, M.S. 3006A, 2.79 chs.
	dist. to a witness point on the line bet. secs. 27 and 28.
	thence S. 37°51' W., 6.71 chs. dist. to Angle Point 92;
	thence S. 36°12' W., 11.24 chs. dist. to Angle Point 93;
	thence S. 5°23' E., 6.84 chs. dist. to Angle Point 94;
	thence S. 13°25' W., 2.20 chs. dist. to Angle Point 95;
	thence S. 30°26' E., 11.05 chs. dist. to Angle Point 96;
	thence S. 10°29' E., 9.99 chs. dist. to Angle Point 97;
	thence S. 23°51' W., 4.88 chs. dist. to Angle Point 98;
	thence S. 29°02' E., 6.82 chs. dist. to Angle Point 99;
	thence S. 4°14' E., 3.37 chs. dist. to Angle Point 100;
	thence S. 78°22' E., 1.79 chs. dist. to Angle Point 101, on
	the line bet. secs. 27 and 28;
	thence S. 87°52' E., 1.84 chs. dist. to Angle Point 102;
	thence S. 30°55' E., 2.94 chs. dist. to Angle Point 103;
	thence S. 38°36' W., 5.32 chs. dist. to Angle Point 104; thence S. 28°42' E., 2.13 chs. dist. to Angle Point 105;
	thence S. 28°42' E., 2.13 chs. dist. to Angle Point 105; thence S. 76°55' E., 3.78 chs. dist. to Angle Point 106;
	thence S. 59°27' E., 5.71 chs. dist. to Angle Point 107;
1	thence S. 47°49' E., 4.10 chs. dist. to Angle Point 107;
	the line bet. secs. 27 and 34;
	thence S. 60°19' E., 5.01 chs. dist. to Angle Point 109;
1	
	thence S. 2°08' W., 5.41 chs. dist. to Angle Point 110:
	thence S. 2°08' W., 5.41 chs. dist. to Angle Point 110; thence S. 34°49' E., 3.58 chs. dist. to Angle Point 111;
	thence S. 2°08' W., 5.41 chs. dist. to Angle Point 110; thence S. 34°49' E., 3.58 chs. dist. to Angle Point 111;

T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

```
CHAINS
                               4.12 chs. dist. to Angle Point 112;
         thence S. 73°45' E.,
                               4.34 chs. dist. to Angle Point 113;
         thence S. 43°35' E.,
                               8.35 chs. dist. to Angle Point 114;
         thence N. 58'44' E.,
                               7.24 chs. dist. to Angle Point 115;
         thence N. 67°19' E.,
         thence N. 51°07' E.,
                               2.49 chs. dist. to Angle Point 116;
         thence S. 89°15' E.,
                               3.59 chs. dist. to Angle Point 117;
         thence N. 46°20' E.,
                               5.34 chs. dist. to Angle Point 118;
         thence N. 79°42' E.,
                               1.26 chs. dist. to Angle Point 119;
         thence S. 16°13' E.,
                               1.29 chs. dist. to Angle Point 120;
         thence S. 53°58' W.,
                               7.01 chs. dist. to Angle Point 121;
         thence N. 84°34' W.,
                               3.22 chs. dist. to Angle Point 122;
         thence S. 50°45' W.,
                               1.93 chs. dist. to Angle Point 123;
         thence S. 68°01' W.,
                               7.29 chs. dist. to Angle Point 124;
         thence S. 57°36' W.,
                               7.33 chs. dist. to Angle Point 125;
         thence S. 42°03' W., 17.63 chs. dist. to Angle Point 126;
         thence S. 58°03' W., 8.07 chs. dist. to Angle Point 127;
         thence S. 83°09' W., 4.41 chs. dist. to Angle Point 128;
         thence S. 49°54' W.,
                               3.07 chs. dist. to Angle Point 129;
         thence S. 34°54' W.,
                               3.37 chs. dist. to Angle Point 130, on
              the line bet. secs. 33 and 34;
         thence S. 52°44' W,
                               8.81 chs. dist. to Angle Point 131;
         thence S. 62°38' W.,
                               2.48 chs. dist. to Angle Point 132;
         thence N. 86°50' E., 4.68 chs. dist. to Angle Point 133;
         thence N. 37°49' E.,
                               2.11 chs. dist. to Angle Point 134;
         thence N. 73°22' E.,
                               3.38 chs. dist. to Angle Point 135, on
              the line bet. secs. 33 and 34;
         thence S. 65°29' E.,
                               7.24 chs. dist. to Angle Point 136;
         thence N. 77°41' E.,
                               2.68 chs. dist. to Angle Point 137;
         thence S. 18°07' W.,
                               2.75 chs. dist. to Angle Point 138;
         thence S. 46°53' E.,
                               3.52 chs. dist. to Angle Point 139;
         thence S. 12°34' W.,
                               5.50 chs. dist. to Angle Point 140;
         thence S. 16°15' E.,
                               6.42 chs. dist. to Angle Point 141;
         thence S. 58°46' E.,
                               3.77 chs. dist. to Angle Point 142;
         thence S. 28°33' E.,
                               3.88 chs. dist. to Angle Point 143;
         thence S. 8°37' E.,
                               3.82 chs. dist. to Angle Point 144;
         thence S. 80°49' E.,
                               6.75 chs. dist. to Angle Point 145;
         thence S. 60°29' E.,
                               2.99 chs. dist. to Angle Point 146;
         thence S. 79°00' E., 5.58 chs. dist. to Angle Point 147;
         thence S. 33°16' W., 3.04 chs. dist. to Angle Point 148;
         thence S. 44°47' E., 5.48 chs. dist. to Angle Point 149,
              identical with Angle Point 1, T. 19 N., R. 20 W., on the
              line bet. secs. 3 and 34, on the S. bdy. of the Tp.
         Exclusive of Independence Mill Site, Mineral Survey No. 3760B,
         located in sec. 35, T. 20 N., R. 20 W. more particularly
         described as follows:
         From the 1/4 sec. cor. of secs. 35 and 36, T. 20 N., R. 20 W.,
         thence N. 23°26' W., 5.32 chs. dist. to cor. 1, Independence Mill
         Site, M.S. 3760B and point of beginning.
```

#### ROOK 5441 T. 20 N., R. 20 W., Gila and Salt River Meridian, Arizona

	thence S.	88°53'	W. on	line 1-2,	Independence	Mill Site,	5.45
ł	che.	diet.	to cor	2.	<del>-</del>		

thence S. 3°54' W. on line 2-3, Independence Mill Site, 8.77 chs. dist. to cor. 3;

thence S. 83°40' E. on line 3-4, Independence Mill Site, 5.35 chs. dist. to cor. 4;

thence N. 4°22' E. on line 4-1, Independence Mill Site, 9.47 chs. dist. to cor. 1, and place of beginning.

#### General Description

The land encompassed in this survey, is located approximately four and a half miles south of Union Pass, on State Hwy. 68, which is 19 miles west of Kingman, AZ. It can also be accessed from the south from Silver Creek Road, approximately 3 miles northwest of Oatman, Az. The area varies from rugged mountainous terrain in the east portion to rolling, rocky terrain in the west. The elevation ranges from 2,200 to 4,200 ft. above sea level. The sparse soils vary from sand, with pebbles and cobbles, in washes to sandy clays elsewhere. The vegetation consists of creosote, yucca, various cacti, and native grasses. There are scattered stands of crucifixion—thorn, at higher elevations, and desert willows and juniper in lower washes.

Trail roads service the area, which can be accessed, generally, from the north, and south. In sections 1, 4, 5, 9, 16, 21, 22, 27, 28, 33, and 34, trail roads were purposefully excluded from the Mount Nutt Wilderness Area, in executing the boundary survey.

All ravines and dry washes drain generally west. There is a spring located in section 34, in Grapevine Canyon. The access road to this canyon was purposefully excluded from Mount Nutt Wilderness Area in executing the boundary survey.

There are abandoned mining operations and evidence of prospecting in sections 1, 2, 12, 21, 22, 27, 28, 33, 34, and 35.

CHAINS

## B00K 5441

# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

#### FIELD ASSISTANTS

NAMES	CAPACITY
Clyde J. King	Land Surveyor
Daniel R. Muth	Land Surveyor in training
Cheryl A. Baier	Surveying Technician
Gordon R. Bubel	***
Steven J. Buchanan	***
Ted E. Cazier	***
Jeff A. Hill	***
Terry W. Kessel	***
Clinton T. Lancaster	11
Wallace R. Ott, Jr.	11
Timothy F. Patro	***
Steven R. Walton, Jr.	Surveying Aid

### BOOK 5441

#### CERTIFICATE OF SURVEY

I, Belle A. Craig, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 24th day of October, 1991, I have dependently resurveyed a portion of the east boundary, a portion of the subdivisional lines and certain mineral surveys, subdivided section 3 and conducted a metes-and-bounds survey of the Mount Nutt Wilderness Area Boundary in Township 20 North, Range 20 West, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

april 18, 1995	Belle A. Gaz
(Date)	(Cadastral Surveyor)
	CERTIFICATE OF APPROVAL
	BUREAU OF LAND MANAGEMENT Arizona State Office Phoenix, Arizona
portion of the subdivisional section 3 and a metes-and-be Township 20 North, Range 20	of the dependent resurvey of a portion of east boundary, a all lines and certain mineral surveys, the subdivision of bounds survey of the Mount Nutt Wilderness Area Boundary in West, Gila and Salt River Meridian, Arizona, executed by Surveyor, having been critically examined and found ed.
00T 3 1995	Dal C. Wilson
(Date)	(Acting Chief Cadastral Surveyor of Arizona)
	CERTIFICATE OF TRANSCRIPT
	g transcript of the field notes of the above-described W., Gila and Salt River Meridian, Arizona, is a true copy
(Date)	(Acting Chief Cadastral Surveyor of Arizona)