ORIGINAL

BOOK 5490

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
AND THE SUBDIVISION OF CERTAIN SECTIONS,
THE METES-AND-BOUNDS SURVEY OF THE
COTTONWOOD POINT WILDERNESS AREA BOUNDARY,
AND INFORMATIVE TRAVERSES IN
TOWNSHIP 41 NORTH, RANGE 6 WEST
Of the <u>Gila and Salt River Meridian,</u> In the State of <u>Arizona</u>
EXECUTED BY Stephen K. Hansen and Belle A. Craig, Cadastral Surveyors

Under Special Instructions dated <u>July 15, 1993</u>, approved <u>July 15, 1993</u>, which provided for the surveys included under Group Number 760 and assignment instructions dated <u>July 26, 1993</u>.

Survey commenced <u>July 27, 1993</u> Survey completed <u>November 30, 1993</u> TOWNSHIP 41 NORTH , RANGE 6 WEST ,

		T		T	
6		L7 4		11 2 9	9 1
	19		14	10	8
7	8 :	.6 9 1	3 10	11 7	7 12
		15		10	7
		1	3 1	o	
18	17	16	15	14 6	
		**************************************			55
19	20	21	22	23	<u>l</u>
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 5 Subdivision of Section 13 Metes-and-Bounds Survey Informative Traverse pp. 22-24

pp. 25

pp. 25-109

pp. 109-122

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, and the subdivision of certain sections, a metes-and-bounds survey of the Cottonwood Point Wilderness Area Boundary, and informative traverses in Township 41 North, Range 6 West, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this dependent resurvey is as follows: Jos. C. Thoma surveyed the east boundary in 1913-14. Thomas B. Mathews and William L. Nash surveyed a portion of the north boundary and a portion of the subdivisional lines in 1916. B. D. Procter and J. P. Hester resurveyed the east one-half mile of the north boundary of section 2 and surveyed a portion of the north boundary and surveyed and resurveyed a portion of the subdivisional lines in 1933-34.

The survey was executed in accordance with the specifications as set forth in the <u>Manual of Surveying Instructions</u>, 1973, and the Special Instructions dated July 15, 1993, for Group No. 760, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of all lines were determined by direct hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with a Lietz Set 4A electronic instrument.

The geographic position of the 1/4 sec. cor. of secs. 13 and 18, Township 41 North, Ranges 5 and 6 West was determined by the technique of static differential positioning using Ashtech models M-XII and MS-XII geodetic units. U.S. Coast and Geodetic Survey triangulation station "Cane Beds 1952" was used as the control station.

Latitude: 36°57′14.71" N. Longitude: 112°52′58.06" W. NAD 27

The mean magnetic declination as taken from quadrangle map Moccasin, ARIZ., published in 1988 by U.S. Geological Survey, is 13 1/2° E.

CHAINS

Restoring the survey executed by Thomas B. Mathews and William L. Nash in 1916

Beginning at the 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 1 in. diam., firmly set, 16 ins. below ground, with brass cap mkd. 1/4 S23 S24 1916. Add the marks T41N R6W 1993 on the brass cap.

Cor. is located in a barbed wire fence, 4 strand, extends ${\sf E.}$ and ${\sf W.}$

N. 0°08' E., bet. secs. 23 and 24.

Over rolling lands.

39.54 | Barbed wire fence, 4 strand, bears E. and W.

The cor. of secs. 13, 14, 23 and 24, determined latitudinally by the apparent center line of Cane Beds Road, at midpoint between the 66 ft. right-of-way fences, extending E. and W., and longitudinally at the extension of a fence line from the N. This is accepted as the best attainable evidence of the original cor. position.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 38 ins. in the ground, with brass cap mkd.

from which

- A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, bears N. 47°54′ E., 49.6 ft. dist., with brass cap mkd. T41N R6W S13 RM 49.6 FT TO COR 1993, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
- A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, bears S. 43°55′ E., 47.2 ft. dist., with brass cap mkd. T41N R6W S24 RM 47.2 FT TO COR 1993, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

Cor. is located in the center line of Cane Beds Road, graded, 35 lks. wide, bears E. and W.

From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with stainless steel post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap, mkd. and witnessed as described in the field note record of the dependent resurvey of the W. bdy., T. 41 N., R. 5 W., executed concurrently under this same group.

N. 89°54' W., bet. secs. 13 and 24.

Along the apparent center line of Cane Beds Road.

40.00

Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 38 ins. in the ground, with brass cap mkd.

T41N R6W S13 1/4—— S24 1993

from which

- A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, bears S. 26°18′ W., 38.8 ft. dist., with brass cap mkd. T41N R6W S24 RM 38.8 FT TO COR 1993, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
- A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, bears N. 45°55′ W., 44.3 ft. dist., with brass cap mkd. T41N R6W S13 RM 44.3 FT TO COR 1993, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

Cor. is located in the center line of Cane Beds Road, graded, 35 lks. wide, bears E. and W.

	1. 41 N., R. O W., Gila and Sait River Meridian, Arizona
CHAINS	
80.00	The cor. of secs. 13, 14, 23 and 24.
	N. 0°06' W., bet. secs. 13 and 14.
	Along rolling lands.
0.50	A cor. of barbed wire fences, 4 strand, fences extending N., E., and W.
	Along a barbed wire fence, 4 strand.
40.01	The 1/4 sec. cor. of secs. 13 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. 1/4 S14 S13 1916, from which original bearing trees
	A dead and fallen juniper, 22 ins. diam., bears S. 20 1/40 E., 483 lks. dist., with illegible marks on opened blaze.
	A juniper, 24 ins. diam., bears S. 21° W., 238 lks. dist., with illegible marks on partially healed blaze.
	Add the marks T41N R6W 1993 on the brass cap.
	Cor. is located 1 lk. E. of a cor. of barbed wire fences, 4 strand, fences extending N., S., and W.
	N. O°O6' W., beginning new measurement.
30.69	Point for AP 1, sec. 13, identical with AP 6, sec. 14, hereinafter described.
	Ascend steeply over broken and rocky lands.
40.15	The cor. of secs. 11, 12, 13 and 14, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. T41N R6W S11 S12 S14 S13 1916, from which original bearing trees
:	A juniper, 31 ins. diam., bears N. 62 1/2° E., 44 lks. dist., mkd. T41NR6WS12BT on unhealed blaze.
	A dead and fallen pinon, 14 ins. diam., bears S. 19° E, 38 lks. dist., mkd. T41NR6WS13BT on unhealed blaze.
	A pinon, 13 ins. diam., bears S. 37 1/2° W., 16 lks. dist., mkd. T41NR6WS14BT on unhealed blaze.

	1. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	A pinon, 12 ins. diam., bears N. 62 1/2° W., 120 lks. dist., mkd. T41NR6WS11BT on unhealed blaze.
	Add the marks 1993 on the brass cap.
	From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 24 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap, mkd. and witnessed as described in the field note record of the dependent resurvey of the W. bdy., T. 41 N., R. 5 W., executed concurrently under this same group.
	N. 89°53′ W., bet. secs. 12 and 13.
	Over mountainous lands.
40.01	The 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd. 1/4 S12 S13 1916, from which original bearing trees
	A pinon, 9 ins. diam., bears S. 2° W., 64 lks. dist., with illegible marks on unhealed blaze.
	A juniper, 8 ins. diam., bears N. 64 1/2° W., 74 lks. dist., mkd. 1/4S2BT on unhealed blaze.
	Add the marks T41N R6W 1993 CPWA on the brass cap
	N. 89°53' W., beginning new measurement, along the Cottonwood Point Wilderness Area Bdy.
8.715	Point for AP 9, sec. 12, identical with AP 8, sec. 13, on the Cottonwood Point Wilderness Area Bdy., hereinafter described.
	Leave the Cottonwood Point Wilderness Area Bdy.
14.335	Point for AP 4, sec. 12, identical with AP 7, sec. 13, on the Cottonwood Point Wilderness Area Bdy., hereinafter described.
	Thence, along the Cottonwood Point Wilderness Area Bdy.
40.11	The cor. of secs. 11, 12, 13 and 14.
	N. O°O4' W., bet. secs. 11 and 12, along the Cottonwood Point Wilderness Area Bdy.
	Over rolling rocky lands.

	1. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
39.98	The 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 26 ins. above ground, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd. 1/4 S11 S12 1916, from which
	A rock outcrop, 10 x 8 x 5 ft. high, bears S. 21° E., 37 lks. dist., with X BO chiseled on W. face.
	A rock outcrop, 8 x 6 x 4 ft. high, bears N. 73 3/4° W., 91.5 lks. dist., with X BO chiseled on E. face.
	Add the marks T41N R6W 1993 CPWA on the brass cap.
	N. 0°03' W., beginning new measurement.
37.70	Point for AP 1, sec. 11, identical with AP 3, sec. 12, on the Cottonwood Point Wilderness Area Bdy., hereinafter described.
	Leave the Cottonwood Point Wilderness Area Bdy.
40.03	The cor. of secs. 1, 2, 11 and 12, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T41N R6W S2 S1 S11 S12 1916, from which
	A rock outcrop, 6 x 4 x 2 ft. high, bears S. 27° E., 296.5 lks. dist., with X BO chiseled on W. face.
	A pinon, 11 ins. diam., bears S. 38° W., 95 lks. dist., mkd. T41NR6WS11BT.
	Add the marks 1993 on the brass cap.
	Cor. is located 1 lk. E. of a cor. of barbed wire fences, 4 strand, fences extending W. and NE.
	Restoring the survey executed by B. D. Procter and J.P. Hester, in 1933-34
	From the 1/4 sec. cor. of secs. 1 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 30 ins. above ground, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd. 1/4 S1 S12 1934, from which
	A rock outcrop, 20 x 10 x 3 ft. high, bears N. 8° E., 13 lks. dist., with X BO chiseled on W. face.
	A pinon, 4 ins. diam., bears S. 66° W., 43 lks. dist., mkd. X BT.

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Add the marks T41N R6W 1993 on the brass cap.
	N. 89°51′ W., bet. secs. 1 and 12.
	Over rocky, mountainous land.
26.00	Top of cliffs, faces W.
33.84	Point for AP 1, sec. 12, identical with AP 26, sec. 1, on the Cottonwood Point Wilderness Area Bdy., hereinafter described.
40.00	The cor. of secs. 1, 2, 11 and 12.
	Restoring the survey executed by Thomas B. Mathews and William L. Nash, in 1916
	N. 0°12' E., bet. secs. 1 and 2.
11.96	Point for AP 1, sec. 1, identical with AP 63, sec. 2, on the Cottonwood Point Wilderness Area Bdy., hereinafter described.
40.03	The 1/4 sec. cor. of secs. 1 and 2, monumented with an iron post, 1 in. diam., firmly set, projecting 19 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. 1/4 S1 S2 1916, from which an original bearing tree
	A pinon, 7 ins. diam., bears S. 65° W., 26 lks. dist., mkd. 1/4S2BT on partially healed blaze.
	and a bearing tree not of record
	A juniper, 10 ins. diam., bears N. 27° E., 37 lks. dist., mkd. 1/4S1BT.
	Add the marks T41N R6W 1993 on the brass cap.
	N. O°13' W., beginning new measurement.
40.06	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 36 ins. above ground, supporting mound of stone, 4 ft. base, to top, with brass cap, mkd. and witnessed as described in the field note record of the dep. res. of the S. bdy., T. 42 N., R. 6 W., executed concurrently under this same group.

	1. 41 N., R. 6 W., Gila and Sait River Meridian, Arizona
CHAINS	
	From the 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, 1 in. diam, firmly set, projecting 14 ins. above ground, with brass cap mkd. 1/4 S15 S14 1916.
	Add the marks T41N R5W 1993 on the brass cap.
	N. 0°06' E., bet. secs. 14 and 15.
	Over rolling lands of sage.
40.06	The cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2 ins. diam., firmly set, projecting 24 ins. above ground, with brass cap mkd. T41N R6W S10 S11 S15 S14 1916.
	Add the marks 1993 on the brass cap.
	Enom the con of cook 11 12 13 and 14
	From the cor. of secs. 11, 12, 13 and 14.
	N. 89°55′ W., bet. secs. 11 and 14.
7.505	Point for AP 1, sec. 14, identical with AP 18, sec. 11, hereinafter described.
39.00	Wash, 50 lks. wide, 10 ft. deep, drains S.
39.83	Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the original cor.
į	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	1/4 ——
	S14
	1993
	Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located 6 lks. S. of a barbed wire fence, 4 strand, bears E. and W.
79.66	The cor. of secs. 10, 11, 14 and 15.
	From the cor. of secs. 1, 2, 11 and 12.
	N. 89°54′ W., bet. secs. 2 and 11.

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
39.83	Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over an aluminum fence post, with brass cap mkd.
	T41N R6W
	\$2 1/4 ———
	S11 1993
	Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post, alongside the aluminum fence post.
	Cor. is located 4 lks. S. of a barbed wire fence, 4 strand, bears E. and W.
40.15	Wash, 15 lks. wide, 5 ft. deep, drains S.
79.66	The cor. of secs. 2, 3, 10 and 11, monumented with an iron post, 2 ins. diam., firmly set, projecting 19 ins. above ground, with brass cap mkd. T41N R6W S3 S2 1916. A bullet hole in the brass cap had obliterated other markings.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W S3 S2
	S10 S11 1993
	Deposit a magnet in a 1 \times 1 \times 2 5/8 in. magenta colored plastic case beneath the stainless steel post and bury the iron post alongside.
	North, bet. secs. 2 and 3.
	Over rolling lands of sage.
31.01	Point for AP 1, sec. 2, identical with AP 32, sec. 3, on the Cottonwood Point Wilderness Area Bdy., hereinafter described.

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
40.09	The 1/4 sec. cor. of secs. 2 and 3, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. 1/4 S3 S2 1916, from which an original bearing tree
	A juniper, 20 ins. diam., bears S. 56 1/2° E., 7 lks. dist., mkd. 1/4S3BT on partially healed blaze.
	and a new accessory
	A boulder, 5 x 4 x 3 ft. high, bears N. 3° E., 6.5 lks. dist., with X BO chiseled on S. face.
	Add the marks T41N R6W 1993 on the brass cap.
	N. O°O3' W., beginning new measurement.
10.19	Point for AP 33, sec. 3, identical with AP 6, sec. 2, on the Cottonwood Point Wilderness Area Bdy., hereinafter described.
25.25	Point for AP 42, sec. 3, identical with AP 7, sec. 2, on the Cottonwood Point Wilderness Area Bdy., hereinafter described.
37.55	The original witness cor. of secs. 2, 3, 34 and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins above ground, with brass cap mkd. T42N WC S34 S35 R6W S3 S2 T41N 1916, from which original bearing trees
	A pinon, 15 ins. diam., bears N. 74 1/2° E., 54 lks. dist., mkd. WCT42NR6WS35BT on partially healed blaze.
	A pinon, 10 ins. diam., bears S. 25 1/4° E., 99 lks. dist., mkd. WCT41NR6WS2BT on partially healed blaze.
	A pinon, 13 ins. diam., bears S. 52° W., 60 lks. dist., mkd. WCT41NR6WS3BT on partially healed blaze.
	A pinon stump, 6 ins. diam., 4 ft. high, bears N. 22° W., 92 lks. dist., mkd. WCT42NR6WS34BT on partially healed blaze.
	and a new accessory
	A rock outcrop, 10 x 5 x 12 ft. high, bears N. 42 1/2° E., 109.5 lks. dist., with X BO chiseled on S. face.
	Add the marks 1993 on the brass cap.

	1. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	The 1933-34 survey and resurvey of a portion of the N. bdy. monumented and redesignated the true point as the cor. of secs. 2 and 3 only. It was not necessary to recover the true point in the course of this assignment.
	From the 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. 1/4 S16 S15 1916.
	Add the marks 1993 on the brass cap.
	Cor. is located in a barbed wire fence, 3 strand, bears N. and S.
	N. 0°02' W. bet. secs. 15 and 16
	Along a barbed wire fence.
39.94	The cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2 ins. diam., firmly set, projecting 20 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. T41N R6W S9 S10 S16 S15 1916, from which
	A pinon, 7 ins. diam., bears S. 81 3/4° E., 96 lks. dist., mkd. T41NR6WS15BT.
	A juniper, 9 ins. diam., bears N. 15 1/4° W., 26 lks. dist., mkd. X BT.
	Add the marks 1993 on the brass cap
	Restoring the survey executed by B. D. Procter and J.P. Hester, in 1933-34
	N. 0°05' W., bet. secs. 9 and 10.
	Along rocky, mountainous land.
40.03	The 1/4 sec. cor. of secs. 9 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 17 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. 1/4 S9 S10 1934, from which original bearing trees
	A juniper, 23 ins. diam., bears N. 83 1/4° E., 120 lks. dist., mkd. 1/4S1OBT on partially healed blaze.
	A juniper, 15 ins. diam., bears S. 76 1/2° W., 123 lks. dist., mkd. 1/4S9BT. (Record: 131 lks.)

Add the marks 1993 on the brass cap.
N. 0°06' W., beginning new measurement.
The cor. of secs. 3, 4, 9 and 10, monumented with an iron post, 2 ins. diam., firmly set, with brass cap mkd. T41N R6W S4 S3 S9 S10 1934, from which original bearing trees
A pinon, 17 ins. diam., bears N. 60 1/4° E., 460 lks. dist., mkd. T41NR6WS3BT on partially healed blaze.
A pinon, 18 ins. diam., bears S. 79° E., 721 lks. dist., mkd. T41NR6WS1OBT on partially healed blaze. (Record: 724 lks.)
A pinon, 16 ins. diam., bears S. 30 1/4° W., 803 lks. dist., mkd. T41NR6WS9BT on partially healed blaze.
A juniper, 18 ins. diam., bears N. 68 1/4° W., 272 lks. dist., mkd. T41NR6WS4BT on partially healed blaze.
Add the marks 1993 on the brass cap.
From the cor. of secs. 2, 3, 10 and 11.
S. 89°53′ W., bet. secs. 3 and 10.
Point for AP 22, sec. 3, identical with AP 32, sec. 10, on the Cottonwood Point Wilderness Area Bdy., hereinafter described.
Point for AP 21, sec. 3, identical with AP 25, sec. 10, on the Cottonwood Point Wilderness Area Bdy., hereinafter described.
The 1/4 sec. cor. of secs. 3 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. 1/4 S3 S10 1934, from which original bearing trees
A dead and fallen juniper, 21 ins. diam., bears S. 57 1/4° W., 84 lks. dist., mkd. 1/4 on partially healed blaze.
A dead and fallen juniper, 13 ins. diam., bears N. 41° W., 142 lks. dist., mkd. 1/4S3BT.
and new bearing trees
A juniper, 9 ins. diam., bears N. 79° E., 76 1/2 lks. dist., mkd. 1/4S3BT.

B00K¹⁵5490

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	A juniper, 8 ins. diam., bears S. 29 3/4° E., 157 1/2 lks. dist., mkd. 1/4S1OBT.
	Add the marks T41N R6W 1993 on the brass cap.
	S. 89°54′ W., beginning new measurement.
10.64	Point for AP 4, sec. 3, identical with AP 24, sec. 10, on the Cottonwood Point Wilderness Area Bdy., hereinafter described.
35.34	Point for AP 3, sec. 3, identical with AP 18, sec. 10, on the Cottonwood Point Wilderness Area Bdy., hereinafter described.
40.07	The cor. of secs. 1, 2, 11 and 12.
	Restoring the survey executed by Thomas B. Mathews and William L. Nash, in 1916
	From the cor. of secs. 9, 10, 15 and 16.
	N. 89°58' W., bet. secs. 9 and 16, over rolling land.
39.87	The 1/4 sec. cor. of secs. 9 and 16, monumented with an iron post, firmly set, projecting 26 ins. above ground, in a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd. 1/4 S9 S16 1916, from which
	A pinon, 8 ins. diam., bears N. 7 1/2° E., 59 lks. dist., mkd. 1/4S9BT.
	A juniper, 9 ins. diam., bears S. 4 1/2° E., 78 lks. dist., mkd. 1/4S16BT.
	Add the marks 1993 on the brass cap.
	S. 89°53′ W., beginning new measurement.
25.03	Point for AP 5, sec. 16, on the Cottonwood Point Wilderness Area Bdy., hereinafter described.
	Thence, along the Cottonwood Point Wilderness Area Bdy.
30.13	Point for AP 4, sec. 16, on the Cottonwood Point Wilderness Area Bdy., hereinafter described.
	Leave the Cottonwood Point Wilderness Area Bdy.

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
39.37	Point for AP 1, sec. 16, identical with AP 15, sec. 9, on the Cottonwood Point Wilderness Area Bdy., hereinafter described.
40.13	The cor. of secs. 8, 9, 16 and 17, monumented with an iron post, 2 ins. diam., firmly set, projecting 19 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. T41N R6W S8 S9 S17 S16 1916, from which original bearing trees
	A juniper, 15 ins. diam., bears N. 79° E., 152 lks. dist., mkd. T41NR6WS9BT on partially healed blaze. (Record: N. 77 1/2° E., 156 lks.)
	A juniper, 28 ins. diam., bears S. 71 1/4° E., 63 lks. dist., mkd. T41NR6WS16BT on partially healed blaze.
	A pinon, 13 ins. diam., bears S. 46° W., 21 lks. dist., with illegible marks on unhealed blaze.
	A juniper, 15 ins. diam., bears N. 8° W., 22 lks. dist., mkd. T41NR6WS8BT on partially healed blaze.
	Add the marks 1993 on the brass cap.
	N. 0°03' W., bet. secs. 8 and 9.
0.87	Point for AP 9, sec. 8, identical with AP 14, sec. 9, on the Cottonwood Point Wilderness Area Bdy., hereinafter described.
25.75	Point for AP 3, sec. 8, identical with AP 13, sec. 9, on the Cottonwood Point Wilderness Area Bdy., hereinafter described.
39.94	The 1/4 sec. cor. of secs. 8 and 9, determined from the original bearing trees
	A dead cedar, 18 ins. diam., bears N. 74° E., 79 lks. dist., mkd. 1/4S9BT on unhealed blaze. (Record: N. 77 1/2° E.)
	A dead cedar, 18 ins. diam., bears N. 76° W., 77 lks. dist., mkd. 1/4S8BT on unhealed blaze. (Record: N. 80 1/2° W.)
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T41N R6W
	1/4 S8 S9
	1993

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	from which
	A pinon, 15 ins. diam., bears S. 43° E., 56 lks. dist., mkd. 1/4S9BT.
	A pinon, 8 ins. diam., bears S. 60 1/2° W., 47 lks. dist., mkd. 1/4S8BT.
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	North, beginning new measurement.
37.76	Point for AP 2, sec. 8, identical with AP 1, sec. 9, on the Cottonwood Point Wilderness Area Bdy., hereinafter described.
40.04	The cor. of secs. 4, 5, 8 and 9, monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. T41N R6W S5 S4 S8 S9 1916, from which
	A juniper, 15 ins. diam., bears N. 37 3/4° E., 86 lks. dist., mkd. T41NR6WS4BT.
	A juniper, 23 ins. diam., bears S. 55 3/4° E., 53 lks. dist., mkd. T41NR6WS9BT.
	A pinon, 9 ins. diam., bears S. 9° W., 27 lks. dist., mkd. T41NR6WS8BT.
	A pinon, 10 ins. diam., bears N. 20 1/2° W., 38 lks. dist., mkd. T41NR6WS5BT.
	Add the marks 1993 on the brass cap.
	Restoring the resurvey and survey executed by B. D. Procter and J.P. Hester, in 1934
	N. 0°03' W., bet. secs. 4 and 5.
	Over rocky, mountainous land.
29.93	The original witness cor. to the 1/4 sec. cor. of secs. 4 and 5, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, in a collar of stone, with brass cap mkd. 1/4 S5 S4 WC 1916. This point now functions as an angle point.
	Add the marks T41N R6W 1993 on the brass cap.

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	N. 0°03' W., beginning new measurement.
9.83	The 1/4 sec. cor. of secs. 4 and 5, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd. 1/4 S5 S4 1934, from which
	A pinon, 10 ins. diam., bears S. 44° E., 85 lks. dist., mkd. 1/4S4BT.
	A pinon, 17 ins. diam., bears N. 19° W., 60 lks. dist., mkd. 1/4S5BT.
	Add the marks 1993 on the brass cap
	N. O°45' W., beginning new measurement.
2.30	Top of vermillion cliffs, bears E. and W., desc. 880 ft.
20.19	Point for the N. 1/16 sec. cor. of sec. 5 only.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled with a collar of stone, with brass cap mkd.
	T41N R6W N 1/16 S5 1993
	from which
	A pinon, 17 ins. diam., bears S. 26° W., 49 lks. dist., mkd. N1/16S5BT.
	A pinon, 20 ins. diam., bears N. 57 1/2° W., 44 lks. dist., mkd. X BT.
	Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.
33.98	Point for AP 1, sec. 5, identical with AP 6, sec. 4, on the Cottonwood Point Wilderness Area Bdy., hereinafter described.

	1. 41 N., R. 6 W., Gila and Sait River Meridian, Arizona
CHAINS	·
41.03	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap, mkd. and witnessed as described in the field note record of the dependent resurvey of the S. bdy., T. 42 N., R. 6 W., executed concurrently under this same group.
	Restoring the survey executed by Thomas B. Mathews and William L. Nash, in 1916
	From the cor. of secs. 4, 5, 8 and 9.
	N. 89°44′ W., bet. secs. 5 and 8.
2.81	Point for AP 1, sec. 8, identical with AP 19, sec. 5, on the Cottonwood Point Wilderness Area Bdy., hereinafter described.
40.08	Point for the 1/4 sec. cor. of secs. 5 and 8, determined by the method of irregular boundary adjustment, using the record survey by Jeffery Curt Neilson, RLS 20370, in 1992, provided by Bulloch Brothers Engineering, Inc., Cedar City, Utah, specifically Colorado City Road Dedication Plat #11, there is no remaining evidence of the original cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 42 ins. in the ground, with brass cap mkd.
	T41N R6W
	\$5 1/4———
	S8 1993
	from which
	A juniper, 8 ins. diam., bears S. 39 3/4° W., 44 lks. dist., mkd. 1/4S8BT.
	A juniper, 6 ins. diam., bears N. 78 1/4° W., 166 lks. dist., mkd. 1/4S5BT.
	Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Cor. is located in a trail road, bears E. and W.
	N. 89°49′ W., beginning new measurement.

TT		NS
 м	AΙ	Ν.

40.03

The cor. of secs. 5, 6, 7 and 8, reestablished by Jeffery Curt Neilson, RLS 20370, in 1987, monumented with a P.K. nail, 2 1/2 ins. long, firmly set, flush with pavement. This is accepted as the best available evidence of the original cor. position, from which an accessory set by Neilson

An iron pipe, 2 ins. diam., firmly set, projecting 1 in. above ground, bears S. 89°49′ E., 45.5 lks. dist., with brass cap mkd. T41N R6W S6 S5 S7 S8 W 30′ BBE 87 with an arrow pointing towards the cor.

At the cor. point

Set an aluminum post, 36 ins. long, 5/8 ins. diam., 42 ins. in the ground, with aluminum cap mkd.

T41N	R6W
S6	S5
	ļ
S7	S8
19	93

from which

- A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, for a reference monument, bears S. 38°05 W., 50.5 ft. dist., with brass cap mkd. T41N R6W S7 RM 50.0 FT TO COR 1993, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.
- A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, bears N. 42°52′ W., 92.1 ft. dist., with brass cap mkd. T41N R6W S6 RM 92.1 FT TO COR 1993, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the aluminum post.

Cor. is located in the intersection of roads, Central Street, 36 lks. wide, paved, bears N. and S., and Cherry Ave., 36 lks. wide, graded dirt, bears W.

N. 0°21' W., bet. secs. 5 and 6, along Central Street.

40.06

Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the original cor.

CHAINS

Set an aluminum rod, 36 ins. long, 3/4 in. diam., 42 ins. in the ground, with aluminum cap mkd.

T41N R6W 1/4 S6 | S5 1993

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground, for a reference monument, bears S. 68°28′ E., 32.3 ft. dist., with brass cap mkd. T41N R6W S5 RM 32.3 FT TO COR 1993, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 ins. white plastic case beneath the stainless steel post.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 23 ins. in the ground, for a reference monument, bears S. 40°43′ W., 92.2 ft. dist., with brass cap mkd. T41N R6W S6 RM 92.2 FT TO COR 1993, and an arrow pointing to the cor. Deposit a magnet in a 1 x 1 x 2 in. white plastic case beneath the stainless steel post.

Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the aluminum post.

From this cor. point, a rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground, bears N. 41 1/2° E., 131 lks. dist., with plastic cap mkd. BBE INC.

From this same cor. point, a rebar, 1/2 in. diam., firmly set, projecting 4 ins. above ground, bears S. 69 $3/4^{\circ}$ E., 93 lks. dist., with plastic cap mkd. BBE INC.

From this same cor. point, a rebar, 1/2 in. diam., firmly set, projecting 1 ins. above ground, bears S. 58° W., 102 lks. dist., with plastic cap mkd. BBE INC.

Cor. is located in the intersection of roads, Central Street, 36 lks. wide, paved, bears N. and S., and Mojave Ave., 30 lks. wide, graded dirt, bears E.

80.37

The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., monumented with an X, chiseled on the top of a manhole cover, 24, ins. diam., firmly set, flush with pavement, and witnessed as described in the field note record of the dependent resurvey of the S. bdy., T. 42 N., R. 6 W., executed concurrently under this same group.

Subdivision of Section 5, T. 41 N.. R. 6 W.. Gila and Salt River Meridian. Arizona

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	From the 1/4 sec. cor. of secs. 5 and 8.
	N. 0°22' W., on the N. and S. center line of sec. 5.
25.77	Point for AP 12, sec. 5, on the Cottonwood Point Wilderness Area Bdy., hereinafter described.
	Thence, along the Cottonwood Point Wilderness Area Bdy.
39.88	Point for the center 1/4 sec. cor of sec. 5, at intersection with the E. and W. center line of sec. 5.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W C1/4 S5 CPWA 1993
	from which
	A juniper, 8 ins. diam., bears S. 39 1/2° E., 28 lks. dist., mkd. C1/4S5BT.
	A pinon, 8 ins. diam., bears S. 42 1/2° W., 84 lks. dist., mkd. C1/4S5BT.
	Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.
48.35	Point for AP 9, sec. 5, on the Cottonwood Point Wilderness Area Bdy., hereinafter described.
	Leave the Cottonwood Point Wilderness Area Bdy.
59.99	Point for the center N. 1/16 sec. cor. of sec. 5.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T41N R6W
	C N 1/16 S5
	Ċ 1993
:	from which
	A juniper, 8 ins. diam., bears S. 89° E., 122 lks. dist., mkd. X BT.

Subdivision of Section 5, T. 41 N.. R. 6 W.. Gila and Salt River Meridian. Arizona

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	A juniper, 17 ins. diam., bears N. 25° W., 84 lks. dist., mkd. CN1/16S5BT.
i	Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.
80.55	The 1/4 sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp., monumented with a brass tablet, 3 1/2 ins. diam., firmly set in a drill hole, with brass cap mkd. and witnessed as described in the field note record of the dependent resurvey of the S. bdy., T. 42 N., R. 6 W., executed concurrently under this same group.
	From the 1/4 sec. cor. of secs. 4 and 5.
	N. 89°34' W., on the E. and W. center line of sec. 5.
20.15	True point for the center E. 1/16 sec. cor. of sec. 5, falls on the face of a cliff, where it is impracticable to establish a permanent monument.
	From this point, the point selected for the witness cor. for the center E. 1/16 sec. cor. of sec. 5, bears S. 86°03' E., 2.60 chs. dist.
	Set a brass tablet, 3 $1/2$ ins. diam., flush with the surface of a rock outcrop, $20 \times 5 \times 8$ ft. high, in concrete, over a magnet, 1 \times 1 in. cylindrical, for a witness cor., with top mkd. WC T41N R6W E $1/16$ C C S5 1993, and an arrow pointing to the cor.
40.30	The center 1/4 sec. cor. of sec. 5.
45.25	Point for AP 10, sec. 5, hereinafter described.
80.31	The 1/4 sec. cor. of secs. 5 and 6.
	NE 1/4 Sec. 5
	From the true point for the center E. 1/16 sec. cor. of sec. 5.
	N. O°34' W., on the N. and S. center line of the NE 1/4 of sec. 5.
20.15	Point for the NE 1/16 sec. cor. of sec. 5, at intersection with the E. and W. center line of the NE 1/4 of sec. 5.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Subdivision of Section 5, T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T41N R6W NE 1/16 S5 CPWA 1993
	from which
	A boulder, 6 x 6 x 4 ft. high, bears S. 26 3/4° E., 57 lks. dist., with X BO chiseled on N. face.
	A boulder, 6 x 10 x 7 ft. high, bears S. 78 1/4° W., 47 lks. dist., with X BO chiseled on E. face.
	Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.
	Thence, along the Cottonwood Point Wilderness Area Bdy.
23.32	Point for AP 5, sec. 5, on the Cottonwood Point Wilderness Area Bdy., hereinafter described.
	Leave the Cottonwood Point Wilderness Area Bdy
40.85	The E. 1/16 sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. and witnessed as described in the field note record of the dependent resurvey of the S. bdy., T. 42 N., R. 6 W., executed concurrently under this same group.
	From the N. 1/16 sec. cor. of sec. 5 only.
	N. 89°41' W., on the E. and W. center line of the NE 1/4 of sec. 5.
20.08	The NE 1/16 sec. cor. of sec. 5.
	Thence, along the Cottonwood Point Wilderness Area Bdy.
25.28	Point for AP 7, sec. 5, on the Cottonwood Point Wilderness Area Bdy,, hereinafter described.
	Leave the Cottonwood Point Wilderness Area Bdy.
40.16	The center N. 1/16 of sec. 5.

Subdivision of Section 13,

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	From the 1/4 sec. cor. of secs. 13 and 24.
	N. 0001' W., on the N. and S. center line of sec. 13.
40.01	Point for the center 1/4 sec. cor. of sec. 13 at intersection with the E. and W. center line of sec. 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W C 1/4 S13 1993
44.43	Point for AP 15, sec. 13, on the Cottonwood Point Wilderness Area Bdy., hereinafter described.
	Thence, along the Cottonwood Point Wilderness Area Bdy.
80.15	The 1/4 sec. cor. of secs. 12 and 13.
	From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. and witnessed as described in the field note record of the dependent resurvey of a portion of the W. bdy., T. 41 N., R. 5 W., executed concurrently under this same group.
	N. 89054' W., on the E. and W. center line of sec. 13.
40.01	The center 1/4 sec. cor. of sec. 13.
80.06	The 1/4 sec. cor. of secs. 13 and 14.
	Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary, T. 41 N., R. 6 W., Gila and Salt River Mer., Az.
	In Sec. 4
	From AP 1, sec. 4, identical with AP 3, sec. 33, T.42 N., R. 6 W., on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. and witnessed as described in the field note record of the Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary, T. 42 N., R. 6 W., executed concurrently under this same group.

Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

S. 28°39' E., on line 1-2.

6.70

Point for AP 2, sec. 4.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 28°22′ W., on line 2-3.

3.75

Point for AP 3, sec. 4.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.




Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 52°46′ W., on line 3-4.

2.04

Point for AP 4, sec. 4.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

B00K²⁷5490

Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary,
. 41 N.. R. 6 W.. Gila and Salt River Meridian. Arizona

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	N. 61°18′ W., on line 4-5.
3.50	Point for AP 5, sec. 4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W S4
	AP5 CPWA 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 64°46′ W., on line 5-6.
3.99	Point for AP 6, identical with AP 1, sec. 5, on the line bet. secs. 4 and 5.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W S5 S4 AP1 AP6 CPWA 1993
	Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.
	From this cor. point, the cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., bears N. O°45' W., 7.05 chs. dist., hereinbefore described.
	In Sec. 5
	S. 71°24′ W., on line 1-2.
3.96	Point for AP 2, sec. 5.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary, 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T41N R6W S5
	AP2
	CPWA 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 88°54′ W., on line 2-3.
6.17	Point for AP 3, sec. 5.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	S5 / AP3 CPWA 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 22°30′ W., on line 3-4.
6.80	Point for AP 4, sec. 5.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W S5 AP4 CPWA 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 67°26′ W., on 4-5.
8.03	Point for AP 5, sec. 5, on the N. and S. center line of the NE 1/4 of sec. 5.

BOOK 5490 Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

From this cor. point, the NE 1/16 sec. cor. of sec. 5, bears S. 0°34′ W., 3.17 chs. dist., hereinbefore described.

From the point for AP 7, sec. 5, on the E. and W. center line of the NE 1/4 of sec. 5.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.




Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

From this cor. point, the NE 1/16 sec. cor. of sec. 5, bears S. 89°41′ E., 5.20 chs. dist., hereinbefore described.

S. 41°19' W., on line 7-8.

5.78 | Point for AP 8, sec. 5.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.



BOOK 5490 Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS


Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 56°44′ W., on line 8-9.

13.15

Point for AP 9, sec. 5, on the N. and S. center line of sec. 5.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.




Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

From this cor. point, the center 1/4 sec. cor. of sec. 5, bears S. 0°22′ E., 8.47 chs. dist., hereinbefore described.

From the point for AP 12, sec. 5, on the N. and S. center line of sec. 5.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

From this cor. point, the center 1/4 sec. cor. of sec. 5, bears N. 0°22′ W., 14.11 chs. dist., hereinbefore described.

S. 23°51' E., on line 12-13.

12.92

Point for AP 13, sec. 5.

B00K 5490

Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to bedrock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.




Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 46°08' E., on line 13-14.

4.72 | Point for AP 14, sec. 5.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.




Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 65°03' E., on line 14-15.

8.55 | Point for AP 15, sec. 5.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

BOOK 5490 Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

	1. 41 N., R. O W., Gila and Sait River Meridian, Arizona
CHAINS	·
	N. 47°24' E., on line AP 15-16.
3.88	Point for AP 16, sec. 5.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	CPWA AP16
	\s5
į.	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 69°42' E., on line 16-17.
6.07	Point for AP 17, sec. 5.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T41N R6W
	CPWA
	AP17
	S5
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 80°39' E., on line 17-18.
12.47	Point for AP 18, sec. 5.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T41N R6W
	CPWA
	AP18
	S5 \ 1993

Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 1°10' E., on line 18-19.

9.96

Point for AP 19, sec. 5, identical with AP 1, sec. 8, on the line bet. secs. 5 and 8.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

From this cor. point, the cor. of secs. 4, 5, 8 and 9 bears S. 89°44′ E., 2.81 chs. dist., hereinbefore described.


In Sec. 8

S. 50°47' E., on line 1-2.

3.63

Point for AP 2, sec. 8 identical with AP 1, sec. 9, on the line bet. secs. 8 and 9.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

From this cor. point, the cor. of secs. 4, 5, 8 and 9 bears North, 2.28 chs. dist., hereinbefore described.

B00K 5490 Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

	1. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	In Sec. 9
	S. 16°40' E., on line 1-2.
6.93	Point for AP 2, sec. 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W S9 AP2 CPWA 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 13°06' E., on line 2-3.
3.29	Point for AP 3, sec. 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	S9 AP3 CPWA 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 21°15′ W., on line 3-4.
7.48	Point for AP 4, sec. 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	S9 AP4 CPWA 1993

BOOK 5490 Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS


Deposit a magnet in a $1 \times 1 \times 2$ in. white colored plastic case beneath the stainless steel post.

S. 19°10' E., on line 4-5.

6.07

Point for AP 5, sec. 9.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 32°52' E., on line 5-6.

7.47

Point for AP 6, sec. 9.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 23°47′ W., on line 6-7.

5.36

Point for AP 7, sec. 9.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N R6W

Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post. S. 10°04' W., on line 7-8. 6.62 Point for AP 8, sec. 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. **T41N R6W** Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post. S. 11°10' E., on line 8-9. 5.12 Point for AP 9, sec. 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. **T41N R6W** AP9 1993 Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post. S. 53°26' E., on line 9-10. 3.72 Point for AP 10, sec. 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. **T41N R6W** AP10 S9 **CPWA** 1993

Cottonwood Point Wilderness Area Boundary, T. 41 N. R. 6 W. Gila and Salt River Meridian, Arizona


	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 8°04' W., on line 10-11.
4.28	Point for AP 11, sec. 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	S9 AP11 CPWA 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 80°30' W., on line 11-12.
3.85	Point for AP 12, sec. 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W S9
	AP12
	CPWA 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 69°17′ W., on line 12-13.
2.49	Point for AP 13, sec. 9, identical with AP 3, sec 8, on the line bet. secs. 8 and 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

From this cor. point, the 1/4 sec. cor. of secs. 8 and 9 bears N. 0°03′ W., 14.19 chs. dist., hereinbefore described.

In Section 8

S. 59°28′ W., on line 3-4.

4.63 | Point for AP 4, sec. 8.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 21°12′ W., on line 4-5.

9.89 | Point for AP 5, sec. 8.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

$$B00\,\mbox{K}5490 Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary,

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	S. 14°22′ E., on line 5-6.
3.74	Point for AP 6, sec. 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W S8 CPWA AP6
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 73°39' E., on line 6-7.
4.56	Point for AP 7, sec. 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.
	T41N R6W AP7 CPWA S8 1993
3	Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.
	S. 5°19' E., on line 7-8.
5.01	Point for AP 8, sec. 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.
	T41N R6W AP8 CPWA S8 1993

BOOK 5490

Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary.

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona


CHAINS

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 28°15' E., on line 8-9.

3.86 Point for AP 9, sec. 8, identical with AP 14, sec. 9, on the line bet. secs. 8 and 9.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

From this cor. point, the cor. of secs. 8, 9, 16 and 17 bears S. 0°03′ E., 0.87 chs. dist., hereinbefore described.

In Section 9

S. 41°12′ E., on line 14-15.

Point for AP 15, sec. 9, identical with AP 1, sec. 16, on the line bet. secs. 9 and 16.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

From this cor. point, the cor. of secs. 8, 9, 16 and 17 bears S. 89°53′ W., 0.76 chs. dist., hereinbefore described.

BOOK 5490 Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	In Sec. 16
	S. 44°08' E., on line 1-2.
3.34	Point for AP 2, sec. 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.
	T41N R6W CPWA AP2
	S16 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 87°01' E., on line 2-3.
3.43	Point for AP 3, sec. 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	TAIN DEW
ì	T41N R6W CPWA
	AP3
	S16 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 53°20' E., on line 3-4.
4.35	Point for AP 4, sec. 16, on the line bet. secs. 9 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

B00K 5490

Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

T41N R6W CPWA S9 AP4 S16 1993

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

From this cor. point, the cor. of secs. 8, 9, 16 and 17 bears S. 89°53′ W., 10.00 chs. dist., hereinbefore described.

From the point for AP 5, sec. 16, on the line bet. secs. 9 and 16.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T41N R6W CPWA S9 AP5 S16 1993

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

From this cor. point, the 1/4 sec. cor. of secs. 9 and 16 bears N. 89°53′ E., 25.03 chs. dist., hereinbefore described.

S. 3°52' E., on line 5-6.

4.16 Point for AP 6, sec. 16.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.

T41N R6W S16 AP6 CPWA

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

BOOK 5490 Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary,

T. 41	Ν.,	R.	6 W.,	Gila	and	Salt	River	Meridian,	Arizona

	1. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	S. 16°33' E., on line 6-7.
3.81	Point for AP 7, sec. 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
*	T41N R6W S16 AP7 CPWA
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
3	S. 62°09' E., on line 7-8.
2.88	Point for AP 8, sec. 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP8
	S16 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 69°43' E., on line 8-9.
5.35	Point for AP 9, sec. 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP9 S16 1993

BOOK 5490 Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAING	1: 41 N., R. O W., Gila and Salt River Heritalan, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 47°57' E., on line 9-10.
3.73	Point for AP 10, sec. 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.
	T41N R6W
	CPWA
	AP10
	S16
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 65°20' E., on line 10-11.
2.86	Point for AP 11, sec. 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	CPWA
	AP11
	S16 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 87°00' E., on line 11-12.
3.45	Point for AP 12, sec. 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Cottonwood Point Wilderness Area Boundary,

Т	41 N	P	6 W	Gila	and	S=1+	River	Meridian,	Arizona
	71 14.	п.	UW.	. uila	allu	Jail	VIACI	riei iu iaii,	AI IZUIIA

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T41N R6W CPWA AP12 S16 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 35°53' E., on line 12-13.
2.92	Point for AP 13, sec. 16.
,	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP13
	S16 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 84°46' E., on line 13-14.
2.55	Point for AP 14, sec. 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP14
	S16 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 49°21' E., on line 14-15.
2.21	Point for AP 15, sec. 16.

$$B00\,\mbox{K}5490 Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary, T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.


> **T41N R6W CPWA** AP15 S16 1993

Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.

N. 77°15' E., on line 15-16.

5.53 Point for AP 16, sec. 16.

> Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 7°26' E., on line 16-17.

6.77 Point for AP 17, sec. 16.

> Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 65°10' E., on line 17-18.

Cottonwood Point Wilderness Area Boundary, T. 41 N. R. 6 W., Gila and Salt River Meridian, Arizona

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
6.08	Point for AP 18, sec. 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP18
	S16 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 89°36' E., on line 18-19.
5.42	Point for AP 19, sec. 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP19
	S16 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 59°52' E., on line 19-20.
7.52	Point for AP 20, sec. 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP20 S16 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.

$$B00\,\mbox{K}5490 Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary,
T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	N. 38°21′ E., on line 20-21.
9.35	Point for AP 21, sec. 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA
ę.	AP21
	S16 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 83°18' E., on line 21-22.
3.66	Point for AP 22, sec. 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, encircled with a collar of stone, with brass cap mkd.
	T41N R6W
	CPWA AP22
	S16 1993
	Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.
	S. 76°17' E., on line 22-23.
2.90	Point for AP 23, sec. 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	CPWA / AP23/
	S16
	1993

Cottonwood Point Wilderness Area Boundary,

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 41°01' E., on line 23-24.
2.49	Point for AP 24, sec. 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP24 S16 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 43°42' E., on line 24-25.
3.07	Point for AP 25, sec. 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP25 S16
	1993
	Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.
	N. 24°38' E., on line 25-26.
3.63	The cor. of secs. 9, 10, 15 and 16, identical with AP 26, sec. 16, and AP 1, sec. 10, hereinbefore described.
	In Sec. 10
	N. 83°59' E., on line 1-2.
8.68	Point for AP 2, sec. 10.
	l

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N R6W CPWA AP2 S10 1993

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

N. 73°17′ E., on line 2-3.

5.00 | Point for AP 3, sec. 10.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N R6W CPWA/ AP3/ S10 1993

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

N. 25°09' E., on line 3-4.

3.09 | Point for AP 4, sec. 10.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N R6W CPWA AP4 S10 1993

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

N. 3°36' E., on line 4-5.

Cottonwood Point Wilderness Area Boundary,
T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
6.65	Point for AP 5, sec. 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP5 S10 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 20°19' E., on line 5-6.
8.89	Point for AP 6, sec. 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP6 S10 1993
	Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.
	N. 3°43' W., on line 6-7.
5.62	Point for AP 7, sec. 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
·	T41N R6W CPWA AP7 S10 1993

Cottonwood Point Wilderness Area Boundary, N. R. 6 W. Gila and Salt River Meridian, Arizona

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 31°23' E., on line 7-8.
5.23	Point for AP 8, sec. 10.
·	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP8
	/ S10 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 56°18' E., on line 8-9.
5.06	Point for AP 9, sec. 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA
	AP9
	S10
	1993
·	Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.
	N. 10°18' E., on line 9-10.
6.24	Point for AP 10, sec. 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Cottonwood Point Wilderness Area Boundary, 41 N. R. 6 W. Gila and Salt River Meridian. Arizona

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T41N R6W CPWA AP10 S10
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 47°30' W., on line 10-11.
5.29	Point for AP 11, sec. 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W AP11 S10 CPWA 1993
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 43°39' W., on line 11-12.
8.99	Point for AP 12, sec. 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W AP12 S10 CPWA
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 36°22′ W., on line 12-13.
5.97	Point for AP 13, sec. 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

B00K 54 90

Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

	1. 41 N., K. O W., GITA AND SAIL RIVEL MELIUTAN, AL IZONA
CHAINS	
	T41N R6W AP13 CPWA S10
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 15°28' W., on line 13-14.
5.13	Point for AP 14, sec. 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W AP14 CPWA S10
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 0°22' W., on line 14-15.
5.15	Point for AP 15, sec. 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W AP15 CPWA S10
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 44°32' W., on line 15-16.
12.47	Point for AP 16, sec. 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.


BOOK 5490 Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary,

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T41N R6W AP16 CPWA S10
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 17°38' W., on line 16-17.
7.40	The cor. of secs. 3, 4, 9 and 10, identical with AP 17, sec. 10, and AP 1, sec. 3, hereinbefore described.
	In Sec. 3
	N. 36°44' E., on line 1-2.
3.43	Point for AP 2, sec. 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP2
	S3 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 44°19′ E., on line 2-3.
3.83	Point for AP 3, sec. 3, identical with AP 18, sec. 10, on the line bet. secs. 3 and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over an aluminum fence post, with brass cap mkd.

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

From this cor. point, the cor. of secs. 3, 4, 9 and 10 bears S. 89°54′ W., 4.73 chs. dist., hereinbefore described.

In Sec. 10

S. 47°29' E., on line 18-19.

5.14 | Point for AP 19, sec. 10.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 54°51' E., on line 19-20.

4.39 | Point for AP 20, sec. 10.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N R6W CPWA S10 AP20 1993

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

	Cottonwood Point Wilderness Area Boundary, T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	The first term of the same same when the fartany in the fartany in
	S 74°36′ E on line 20 21
	S. 74°26' E., on line 20-21.
5.41	Point for AP 21, sec. 10.
	Set a stainless steel most 20 inc. long 2 1/2 inc. dien
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA
	AP21
	\$10
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case
	beneath the stainless steel post.
	N. 74°43' E., on line 21-22.
6.20	Point for AP 22, sec. 10.
0.20	101110 101 711 22, 3001 201
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	22 ins. in the ground, with brass cap mkd.
	T41N R6W
	CPWA AP22
	AFZZ
	S10
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case
	beneath the stainless steel post.
	N. 57°04' E., on line 22-23.
4.58	Point for AP 23, sec. 10.
7.00	10 110 101 711 23; 300: 10:
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	22 ins. in the ground, with brass cap mkd.
	T41N R6W,
	CPWA /

S10 1993

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 34°00' E., on line 23-24.
4.07	Point for AP 24, sec. 10, identical with AP 4, sec. 3, on the line bet. secs. 3 and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CP AP4 S3 AP24 S10 WA 1993
	Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.
	From this cor. point, the 1/4 sec. cor. of secs. 3 and 10 bear N. 89°54′ E., 10.64 chs. dist., hereinbefore described.
	In Section 3
	N. 22°20' E., on line 4-5.
5.26	Point for AP 5, sec. 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

N. 3°33′ W., on line 5-6.

5.59 | Point for AP 6, sec. 3.

Form 9600-10a (November 1987) USDI-BLM

Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

N. 5°35' E., on line 6-7.

4.61 | Point for AP 7, sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

N. 20°41′ W., on line 7-8.

4.58 | Point for AP 8, sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

N. 7°14' E., on line 8-9.

7.13 | Point for AP 9, sec. 3.

Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

> T41N .R6W CPWA AP9 1993

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

N. 3°26' E., on line 9-10.

6.63 Point for AP 10, sec. 3.

> Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.

N. 51°28' E., on line 10-11.

2.98 Point for AP 11, sec. 3.

> Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

> > **T41N R6W CPWA** AP11 1993

Deposit a magnet in a $1 \times 1 \times 2$ in. White colored plastic case beneath the stainless steel post.

S. 13°34' E., on line 11-12.

Point for AP 12, sec. 3.

3.51

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CH	A	IN	S

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 7°31' E., on line 12-13.

2.90 Point for AP 13, sec. 3.

> Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 24°20' E., on line 13-14.

5.25 Point for AP 14, sec. 3.

> Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 3°33' E., on line 14-15.

5.78 Point for AP 15, sec. 3.

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

> **T41N R6W CPWA AP15** 1993

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 34°05' E., on line 15-16.

3.26 Point for AP 16, sec. 3.

> Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.




Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.

S. 33°37' E., on line 16-17.

5.54 Point for AP 17, sec. 3.

> Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 29°21' E., on line 17-18.

4.38 Point for AP 18, sec. 3.

B00K⁶³5490

Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 30°23' E., on line 18-19.

4.82 | Point for AP 19, sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

N. 54°43' E., on line 19-20.

3.04 | Point for AP 20, sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 30°10' E., on line 20-21.

5.13 Point for AP 21, sec. 3, identical with AP 25, sec. 10, on the line bet. secs. 3 and 10.

Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N R6W S3 AP21 CP S10 AP25 WA

1993

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

From this cor. point, the 1/4 sec. cor. of secs. 3 and 10 bears S. 89°53′ W., 11.74 chs. dist., hereinbefore described.

In Section 10

S. 86°09' E., on line 25-26.

5.01 | Point for AP 26, sec. 10.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N R6W CPWA AP26 S10 1993

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 50°55' E., on line 26-27.

4.94 | Point for AP 27, sec. 10.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N R6W CPWA AP27 S10 1993

Cottonwood Point Wilderness Area Boundary, T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 7°10' W., on line 27-28.
2.35	Point for AP 28, sec. 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W /CPWA /AP28
	\$10
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 60°33' E., on line 28-29.
4.98	Point for AP 29, sec. 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	CPWA
	AP29
	S10 1993
	Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.
	N. 82°45' E., on line 29-30.
4.67	Point for AP 30, sec. 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

T41N R6W CPWA AP30

S10

1993

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

N. 4°41′ W., on line 30-31.

5.23 | Point for AP 31, sec. 10.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

N. 20°22' E., on line 31-32.

2.63 Point for AP 32, sec. 10, identical with AP 22, sec. 3, on the line bet. secs. 3 and 10.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

From this cor. point, the cor. of secs. 2, 3, 10 and 11 bears N. 89°53′ E., 10.40 chs. dist., hereinbefore described.

67

BOOK 5490 Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary, T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
:	In Section 3
	N. 44°23' E., on line 22-23.
3.03	Point for AP 23, sec. 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP23 S3 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 53°40' E., on line 23-24.
4.17	Point for AP 24, sec. 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP24 S3
	1993
	Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.
	N. 29°46' E., on line 24-25.
4.40	Point for AP 25, sec. 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP25 S3
	1993

Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

N. 5°44' E., on line 25-26.

4.56 | Point for AP 26, sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N R6W CPWA AP26 S3

Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.

N. 9°49' W., on line 26-27.

5.14 | Point for AP 27, sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N R6W CPWA AP27 S3

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

N. 24°16′ W., on line 27-28.

4.43 | Point for AP 28, sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N R6W CPWA AP28 S3

Cottonwood Point Wilderness Area Boundary, T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. O°08' W., on line 28-29.
7.13	Point for AP 29, sec. 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP29 S3
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 51°47' E., on line 29-30.
3.00	Point for AP 30, sec. 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP30
	\$3
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 67°17' E., on line 30-31.
1.37	Point for AP 31, sec. 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

BOOK 5490

Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

T41N R6W CPWA AP31


1993

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 66°42' E., on line 31-32.

1.50 Point for AP 32, sec. 3, identical with AP 1, sec. 2, on the line bet. secs. 2 and 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

From this cor. point, the 1/4 sec. cor. of secs. 2 and 3 bears North, 9.08 chs. dist., hereinbefore described.

In Sec. 2

N. 51°42' E., on line 1-2.

1.88 | Point for AP 2, sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T41N R6W CPWA AP2 S2

BOOK 5490

Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

Deposit	a	magnet	in	а	1	х	1	х	2 5/8	in.	white	colored	plastic

Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

N. 14°11' E., on line 2-3.

4.89 | Point for AP 3, sec. 2.

CHAINS


Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

N. 1°19' W., on line 3-4.

6.02 | Point for AP 4, sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.




Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

N. 10°49′ W., on line 4-5.

4.73 | Point for AP 5, sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

|--|


Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

N. 31°30′ W., on line 5-6.

3.17

Point for AP 6, sec. 2, identical with AP 33, sec. 3, on the line bet. secs. 2 and 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

From this cor. point, the 1/4 sec. cor. of secs. 2 and 3 bears S. 0°03' E., 10.19 chs. dist., hereinbefore described.

In Section 3

N. 83°45' W., on line 33-34.

2.14

Point for AP 34, sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

1993

Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.

N. 6°40' W., on line 34-35.

4.74

Point for AP 35, sec. 3.

Cottonwood Point Wilderness Area Boundary, T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CH	ÍΑ	IN	S

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

> **T41N R6W** CPWA AP35

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

N. 15°49' E., on line 35-36.

2.07 Point for AP 36, sec. 3.

> Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

> > **T41N R6W** CPWA AP36 S3 1993

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

N. 17°25′ W., on line 36-37.

7.49 Point for AP 37, sec. 3.

> Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

> > **T41N R6W** CPWA **AP37** 1993

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

N. 10°15′ W., on line 37-38.

6.04 Point for AP 38, sec. 3.

Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N R6W CPWA AP38 S3

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

N. 15°35' W., on line 38-39.

5.95 | Point for AP 39, sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N R6W CPWA AP39 S3 1993

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

N. 88°03' E., on line 39-40.

3.25 | Point for AP 40, sec. 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N R6W CPWA S3 AP40 1993

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 30°04' E., on line 40-41.

6.09 | Point for AP 41, sec. 3.

Form 9600-10a (November 1987) USDI-BLM

Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.




Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 7°19' E., on line 41-42.

5.58 Point for AP 42, sec. 3, identical with AP 7, sec. 2, on the line bet. secs. 2 and 3.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

From this cor. point, the witness cor. of secs. 2 and 3 only, bears N. $0^{\circ}03'$ W., 12.30 chs. dist., hereinbefore described.

In Section 2

S. 19°57' E., on line 7-8.

3.23 | Point for AP 8, sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Cottonwood Point Wilderness Area Boundary, T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	S. 35°18' E., on line 8-9.
6.83	Point for AP 9, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
·	T41N R6W CPWA AP9 S2 1993
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	S. 53°40' E., on line 9-10.
5.70	Point for AP 10, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	CPWA AP10
	S2 APIO
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	S. 43°00' E., on line 10-11.
4.28	Point for AP 11, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP11 S2
	1993

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

S. 24°48' E., on line 11-12.

4.65 | Point for AP 12, sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N R6W CPWA AP12 S2 1993

Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

S. 3°01' E., on line 12-13.

3.52 | Point for AP 13, sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N R6W CPWA AP13 S2 1993

Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

S. 4°17' E., on line 13-14.

3.44 | Point for AP 14, sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N R6W CPWA AP14 S2 1993

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

	1. 41 N., R. 6 W., Gila and Sait River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	S. 18°30' E., on line 14-15.
2.99	Point for AP 15, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP15 S2 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	S. 70°07' E., on line 15-16.
1.46	Point for AP 16, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP16
	\$2 1993
	Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.
	S. 50°01' E., on line 16-17.
1.78	Point for AP 17, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Cottonwood Point Wilderness Area Boundary, T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T41N R6W CPWA AP17 S2
	1993 `
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	S. 45°44' E., on line AP 17-18.
3.29	Point for AP 18, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	CPWA
	AP18
	S2 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	S. 75°28' E., on line AP 18-19.
4.50	Point for AP 19, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	CPWA
	AP19
	\$2 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	N. 64°09' E., on line AP 19-20.
3.29	Point for AP 20, sec. 2.
	· ·

Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary.

CHAINS	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP2O
	S2 1993
	Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.
	N. 65°23' E., on line 20-21.
3.31	Point for AP 21, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP21 S2
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	N. 54°12′ E., on line 21-22.
3.04	Point for AP 22, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP22 S2
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	N. 34°15' E., on line 22-23.
4.44	Point for AP 23, sec. 2.

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

> **T41N R6W** CPWA S2 AP23 1993

Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

N. 32°22' E., on line 23-24.

4.06 Point for AP 24, sec. 2.

> Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

> > **T41N R6W** CPWA AP24 1993

Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

N. 36°15' E., on line 24-25.

6.59 Point for AP 25, sec. 2.

> Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

> > T41N , R6W CPWA AP25 **S2** 1993

Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

N. 1°34' E., on line 25-26.

5.48 Point for AP 26, sec. 2.

Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N R6W CPWA AP26 S2

Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

N. 11°37' E., on line 26-27.

5.37 | Point for AP 27, sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

N. 28°59' E., on line 27-28.

8.61 | Point for AP 28, sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

N. 9°46' E., on line 28-29.

4.64 | Point for AP 29, sec. 2.

Form 9600-10a (November 1987) USDI-BLM

Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

N. 16°01' E., on line 29-30.

5.54 | Point for AP 30, sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

N. 14°18′ W., on line 30-31.

The original witness cor. to the 1/4 sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp., identical with AP 31, sec. 2, and AP 1, sec. 35, T. 42 N., R. 6 W., monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. and witnessed as described in the field note record of the dependent resurvey of the S. bdy., T. 42 N., R. 6 W., executed concurrently under this same group.

From the original witness cor. to the cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., identical with AP 32, sec. 2, and AP 41, sec. 35, T. 42 N., R. 6 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. and witnessed as described in the field note record of the dependent resurvey of the S. bdy., T. 42 N., R. 6 W., executed concurrently under this same group.

S. 55°35' E., on line 32-33.

Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary, T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS 5.96 Point for AP 33, sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 49°14′ W., on line 33-34.

2.87 | Point for AP 34, sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.




Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 65°58' W., on line 34-35.

4.11 | Point for AP 35, sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 2°33′ W., on line 35-36.

85 $^{\rm B00K}$ 5490 Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary,

	Cottonwood Point Wilderness Area Boundary, T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
3.65	Point for AP 36, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA S2 AP36 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
·	S. 21°02' W., on line 36-37.
2.38	Point for AP 37, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA S2 AP37
	1993
	Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.
	S. 59°06' W., on line 37-38.
4.60	Point for AP 38, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W S2 AP38 CPWA 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 8°34′ W., on line 38-39.

B00K⁸⁶5490

Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona **CHAINS** 4.75 Point for AP 39, sec. 2. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. **T41N R6W** CPWA **AP39** 1993 Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post. N. 1°59' W., on line 39-40. 4.28 Point for AP 40, sec. 2. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. **T41N R6W** 1993 Deposit a magnet in a $1 \times 1 \times 2$ in. white colored plastic case beneath the stainless steel post. N. 78°10′ W., on line 40-41. 1.18 Point for AP 41, sec. 2. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. **T41N R6W** S2 AP41 **CPWA** 1993 Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case

beneath the stainless steel post.

B00K⁸⁷5490

Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary, T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

	The first of the different and built ferror file failures.
CHAINS	
	S. 50°13′ W., on line 41-42.
7.26	Point for AP 42, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	CPWA S2 AP42
	1993
•	
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 29°18′ W., on line 42-43.
7.50	Point for AP 43, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
,	CPWA S2 AP43
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 31°01′ W., on line 43-44.
4.68	Point for AP 44, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
:	CPWA S2 AP44
	1993
•	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case
	beneath the stainless steel post.

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

S. 1°35' E., on line 44-45.

2.57

Point for AP 45, sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.

S. 41°57′ W., on line 45-46.

2.22

Point for AP 46, sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 1°05' W., on line 46-47.

3.04

Point for AP 47, sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

Cottonwood Point Wilderness Area Boundary,
41 N.. R. 6 W.. Gila and Salt River Meridian. Arizona

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	S. 27°15' E., on line 47-48.
3.25	Point for AP 48, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	S2 > AP48
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 12°43' W., on line 48-49.
10.13	Point for AP 49, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W / CPWA S2 / AP49
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 13°13′ W., on line 49-50.
12.11	Point for AP 50, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	CPWA S2 AP50
	JE / AFJU
	1993
	Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS	
	S. 22°21′ W., on line 50-51.
5.61	Point for AP 51, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA S2 AP51
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 86°13′ W., on line 51-52.
2.28	Point for AP 52, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	S2 AP52

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 13°09' W., on line 52-53.

3.08 Point for AP 53, sec. 2.

> Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

$B00\,\mbox{K}$ 5490 Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary,

Τ.	41 N.	. R.	6 W.	. Gila	and	Salt	River	Meridian.	Arizona

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	S. 4°14′ W., on line 53-54.
7.53	Point for AP 54, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T41N R6W CPWA S2 AP54 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 18°15' E., on line 54-55.
3.25	Point for AP 55, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA S2 AP55
	Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.
	S. 59°02' E., on line 55-56.
8.04	Point for AP 56, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP56
	S2 1993

B00K 5490

Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary, T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

	1. 41 N., R. O W., Gila and Sait River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 82°01' E., on line 56-57.
3.86	Point for AP 57, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP57
	S2
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 72°31' E., on line 57-58.
4.88	Point for AP 58, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP58
	S2
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 74°32' E., on line 58-59.
3.28	Point for AP 59, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary, T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona


	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T41N R6W CPWA AP59
	S2 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 28°55' E., on line 59-60.
6.79	Point for AP 60, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	CPWA AP60
	S2
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 87°05' E., on line 60-61.
7.33	Point for AP 61, sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	CPWA AP61
	S2 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 64°59' E., on line 61-62.
3.92	Point for AP 62, sec. 2.

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.




Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

N. 57°36' E., on line 62-63.

Point for AP 63, sec. 2, identical with AP 1, sec. 1 on the line bet. secs. 1 and 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

From this cor. point, the cor. of secs. 1, 2, 11 and 12 bears S. 0°12′ W., 11.96 chs. dist., hereinbefore described.

In Sec. 1

N. 31°09' E., on line 1-2.

6.72 | Point for AP 2, sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T41N R6W CPWA AP2 S1 1993

B00K⁹⁵5490

Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary, T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
}	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	N. 25°26' E., on line 2-3.
6.60	Point for AP 3, sec. 1.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP3 S1
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	N. 39°55' E., on line 3-4.
9.96	Point for AP 4, sec. 1.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP4 S1
	1993
	Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.
	N. 27°08' E., on line 4-5.
10.58	Point for AP 5, sec. 1.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP5 S1
	1993

B00K⁹⁶ 54 90

Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary,


T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
•	N. 52°02' E., on line 5-6.
3.62	Point for AP 6, sec. 1.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA
	AP6
;	S1 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	S. 43°26' E., on line 6-7.
1.43	Point for AP 7, sec. 1.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T41N R6W
	S1 AP7 CPWA
	1993
	Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.
	S. 26°46′ W., on line 7-8.
2.56	Point for AP 8, sec. 1.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

_		
	CHA	INS




Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

S. 9°50' W., on line 8-9.

5.70 | Point for AP 9, sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

S. 16°35' W., on line 9-10.

7.27 | Point for AP 10, sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

S. 18°11' W., on line 10-11.


3.83 | Point for AP 11, sec. 1.

Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.




Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

S. 38°37' E., on line 11-12.

5.41 | Point for AP 12, sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

S. 79°39' E., on line 12-13.

7.59 | Point for AP 13, sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

N. 68°38' E., on line 13-14.

Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS						
3.65	Point	for	ΑP	14,	sec.	1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.




Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

S. 75°19' E., on line 14-15.

Point for AP 15, sec. 1. 3.52

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.

S. 1°14' E., on line 15-16.

1.25 Point for AP 16, sec. 1.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

$800\,\text{K}$ 5490° Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary

CHAINS	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
	N. 68°38′ W., on line 16-17.
1.86	Point for AP 17, sec. 1.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T41N R6W S1
	AP17 CPWA
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	S. 64°04′ W., on line 17-18.
4.88	Point for AP 18, sec. 1.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T41N R6W S1
	AP18
	CPWA
	1993
	Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.

Point for AP 19, sec. 1. 3.90

> Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

> > **T41N R6W**

B00k⁰¹5490

Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

	1. 41 N., R. O W., Gila and Sait River Meridian, Arizona
CHAINS	
į	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
<u></u>	S. 14°44′ W., on line 19-20.
2.45	Point for AP 20, sec. 1.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA S1 AP2O
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	S. 39°45' E., on line 20-21.
3.90	Point for AP 21, sec. 1.
:	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA S1 AP21
	1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	N. 88°05' W., on line 21-22.
8.84	Point for AP 22, sec. 1.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T41N R6W S1
	AP22
	CPWA
	1993

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila	and Salt	River Meridian	Arizona
-------------------------	----------	----------------	---------

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
}	S. 85°50' W., on line 22-23.
1.74	Point for AP 23, sec. 1.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T41N R6W
	S1 AP23
	CPWA 1993
-	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	S. 50°27′ W., on line 23-24.
4.10	Point for AP 24, sec. 1.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T41N R6W
	S1 AP24
	CPWA 1993
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	S. 42°20′ W., on line 24-25.
6.15	Point for AP 25, sec. 1.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T41N R6W
	S1 AP25 CPWA
	1993

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

	1. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 5/8 in. white colored plastic case beneath the stainless steel post.
	S. 28°33′ W., on line 25-26.
3.20	Point for AP 26, sec. 1, identical with AP 1, sec. 12, on the line bet. secs. 1 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T41N R6W S1 /AP26 CP
	S12 AP1 WA
	1993
	Deposit a magnet in a 1 \times 1 \times 2 5/8 in. white colored plastic case beneath the stainless steel post.
	From this cor. point, the cor. of secs. 1, 2, 11 and 12 bears N. 89°51′ W., 6.16 chs. dist., hereinbefore described.
	In Sec. 12
	S. 67°41' W., on line 1-2.
4.36	Point for AP 2, sec. 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W S12 /CP
į	₩A
	AP2 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 72°42′ W., on line 2-3.
2.22	Point for AP 3, sec. 12, identical with AP 1, sec. 11, on the line bet. secs. 11 and 12.

Cottonwood Point Wilderness Area Boundary, T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

From this cor. point, the cor. of secs. 1, 2, 11 and 12 bears N. 0°03′ W., 2.33 chs. dist., hereinbefore described.

From the point for AP 4, sec. 12, identical with AP 7, sec. 13, on the line bet. secs. 12 and 13.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

From this cor. point, the cor. of secs. 11, 12, 13 and 14 bears N. 89°53′ W., 25.775 chs. dist., hereinbefore described.

N. 13°27' E., on line 4-5.

8.34 Point for AP 5, sec. 12.

> Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

	1. 41 N., N. O W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 12°19' E., on line 5-6.
7.86	Point for AP 6, sec. 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP6
	\s12 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 84°32′ E., on line 6-7.
3.73	Point for AP 7, sec. 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	CPWA AP7
	S12 1993
·	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 1°52' W., on line 7-8.
7.40	Point for AP 8, sec. 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

$$B00\,\mbox{K}$$ 5490 Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary, T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

T41N R6W CPWA AP8 **S12** 1993

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 10°19′ W., on line 8-9.

8.18 Point for AP 9, sec. 12, identical with AP 8, sec. 13, on the line bet. secs. 12 and 13.

> Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

> > **T41N R6W CPWA** AP9 S12 S13 AP8 1993


Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

From this cor. point, the 1/4 sec. cor. of secs. 12 and 13 bears S. 89°53′ E., 8.715 chs. dist., hereinbefore described.

In Section 13

From the point for AP 15, sec. 13, on the N. and S.center line of sec. 13.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



BOOK 5490 Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

	1. 41 N., K. O W., Gila and Sait Kivel Hel Idian, Al 1201a
CHAINS	
	Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.
	From this cor. point, the center 1/4 sec. cor. of sec. 13 bears S. 0°01' E., 4.42 chs. dist., hereinbefore described.
	S. 64°15′ E., on line 15-16.
6.08	Point for AP 16, sec. 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP16
·	S13 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 75°25' E., on line 16-17.
4.70	Point for AP 17, sec. 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W CPWA AP17
	S13 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 85°56' E., on line 17-18.
6.01	Point for AP 18, sec. 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Metes-and-Bounds Survey of the

Cottonwood Point Wilderness Area Boundary, T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS	
	T41N R6W
	CPWA AP18
	S13 1993
	1333
	Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case
	beneath the stainless steel post.
	N. 77°45' E., on line 18-19.
8.77	Point for AP 19, sec. 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	CPWA
	AP19
	S13 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 64°28' E., on line 19-20.
9.79	Point for AP 20, sec. 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	CPWA AP20 —
	S13 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 68°41' E., on line 20-21.

BOOK 5490 Metes-and-Bounds Survey of the Cottonwood Point Wilderness Area Boundary,

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

7.07

Point for AP 21, sec. 13, identical with AP 1, sec. 18, T. 41 N., R. 5 W., on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. and witnessed as described in the field note record of the dependent resurvey of a portion of the W. bdy., T. 41 N., R. 5 W., executed concurrently under this same group.

Informative Traverses in Certain Sections, T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

The following informative traverse across private land inholdings in certain sections of T. 41 N., R. 6 W., represents a proposed boundary of Cottonwood Point Wilderness Area. Affected and adjoining landowners gave the Bureau of Land Management permission to set monuments on their respective properties. At the time of the approval of these field notes this informative traverse should not be construed to represent anything but a description of a survey between these monuments. The present description of the Cottonwood Point Wilderness Area Boundary is included in this same set of notes.

In Section 5

From AP 5, sec. 5, on the N. and S. center line of the NE 1/4 of sec. 5, hereinbefore described.

N. 69°23' W., on line 5-6.

2.95

Point for AP 6, sec. 5.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in a sandstone boulder, 40 x 20 x 9 ft. high, with brass cap mkd.

> **T41N R6W S5** 1993

Deposit a magnet in a $1 \times 1 \times 2$ in. white colored plastic case beneath the stainless steel post.

S. 29°49' W., on line 6-7.

	1. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona	
CHAINS		
4.82	AP 7, sec. 5, on the E. and W. center line of the NE 1/4 of sec. 5, hereinbefore described.	
	From AP 9, sec. 5, on the N. and S. center line of sec. 5, hereinbefore described.	
	S. 30°10′ W., on line 9-10.	
9.75	Point for AP 10, sec. 5, on the E. and W. center line of sec. 5.	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.	
	T41N R6W	
	$c \xrightarrow{S AP}$	
	5 \ 10 1993	
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.	
	S. 8°16' E., on line 10-11.	
10.06	Point for AP 11, sec. 5.	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.	
	T41N R6W	
	S5 AP11	
	1993	
	Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.	
	S. 40°39' E., on line 11-12.	
5.52	AP 12, sec. 5, on the N. and S. center line of sec. 5, hereinbefore described.	

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona	
CHAINS		
	In Section 11	
	From AP 1, sec. 11, identical with AP 3, sec. 12, on the line bet. secs. 11 and 12, hereinbefore described.	
	S. 72°49' W., on line 1-2.	
5.95	Point for AP 2, sec. 11.	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	
	T41N R6W S11 AP2 1993	
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.	
	S. 34°37′ W., on line 2-3.	
4.28	Point for AP 3, sec. 11.	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	
	T41N R6W S11 AP3 1993	
	Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.	
	S. 7°52' W., on line 3-4.	
1.84	Point for AP 4, sec. 11.	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	
	T41N R6W	
	S11 AP4	
	19́93	
L		

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona	
CHAINS		
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.	
	S. 22°33′ W., on line 4-5.	
3.94	Point for AP 5, sec. 11.	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	
	T41N R6W	
	S11 AP5	
	1993	
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.	
	S. 5°03' W., on line 5-6.	
5.76	Point for AP 6, sec. 11.	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	
	T41N R6W	
	S11 AP6	
	1993	
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.	
5.95	S. 14°05' E., on line 6-7.	
	Point for AP 7, sec. 11.	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	
	T41N R6W	
	S11 AP7	
	1993	

	1. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 47°59' E., on line 7-8.
4.39	Point for AP 8, sec. 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W AP8 S11
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 55°53' E., on line 8-9.
5.60	Point for AP 9, sec. 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	S11 AP9
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 17°03' W., on line 9-10.
6.10	Point for AP 10, sec. 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	S11 AP10
	1993

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona	
	CHAINS	
İ		Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.
		C 108107 N on Jine 10 11
	0.00	S. 10°18′ W., on line 10-11.
1	8.06	Point for AP 11, sec. 11.
į.		Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
		T41N R6W / AP11
		S11 AFTI
		1993
		Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
		S. 3°09' W., on line 11-12.
	5.49	Point for AP 12, sec. 11.
		Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
		T41N R6W
		S11 AP12
		1993
		Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
İ		
		S. 9°58' W., on line 12-13.
	4.75	Point for AP 13, sec. 11.
		Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
		T41N R6W
		S11 AP13
		1993

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
}	S. 5°34' E., on line 13-14.
4.41	Point for AP 14, sec. 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	S11 AP14
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 8°43' W., on line 14-15.
5.37	Point for AP 15, sec. 11.
1	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
T41N R6W S11 AP15	
	Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.
	S. 1°44' E., on line 15-16.
5.04	Point for AP 16, sec. 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
T41N R6W	
	S11 AP16
	1993

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona	
CHAINS		
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.	
	S. 17°17′ W., on line 16-17.	
6.33	Point for AP 17, sec. 11.	
į	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	
	T41N R6W	
	S11 AP17	
	1993	
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.	
į	S. 1°09' E., on line 17-18.	
4.62	Point for AP 18, sec. 11, identical with AP 1, sec. 14, on the line bet. secs. 11 and 14.	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	
i	T41N R6W S11 AP18	
	S14 AP1 1993	
	Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.	
	In Section 14	
	S. 41°50′ W., on line 1-2.	
8.36	Point for AP 2, sec. 14.	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	

	1. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T41N R6W
	S14 AP2
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 23°50' E., on line 2-3.
4.98	Point for AP 3, sec. 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	S14 AP3
	1993
	Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.
	S. 56°52' E., on line 3-4.
4.78	Point for AP 4, sec. 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	S14 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 20°06' E., on line 4-5.
4.10	Point for AP 5, sec. 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

CHAINS

T41N R6W AP5 S14

Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

N. 89°12' E., on line 5-6.

5.67 AP 6, sec. 14, identical with AP 1, sec. 13, on the line bet. secs. 13 and 14.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T41N R6W



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

In Section 13

N. 69°49' E., on line 1-2.

4.21 | Point for AP 2, sec. 13.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 67°35' E., on line 2-3.

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
7.47	Point for AP 3, sec. 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W AP3
	S13 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 75°12' E., on line 3-4.
3.51	Point for AP 4, sec. 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W AP4
	S13 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 57°09' E., on line 4-5.
5.87	Point for AP 5, sec. 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W AP5
	\$13 1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	N. 46°32' E., on line 5-6.

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona			
CHAINS	CHAINS		
8.81	Point for AP 6, sec. 13.		
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.		
	T41N R6W		
	AP6 S13		
į.	1993		
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.		
	N. 15°01' E., on line 6-7.		
O.69 AP 7, sec. 13, identical with AP 4, sec. 12, on the line be secs. 12 and 13, hereinbefore described.			
	From AP 8, sec. 13, identical with AP 9, sec. 12, on the line bet. secs. 12 and 13, hereinbefore described.		
	S. 6°30′ W., on line 8-9.		
4.72	Point for AP 9, sec. 13.		
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.		
	T41N R6W		
	S13 (AP9		
	1993		
Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.			
	S. 7°27' E., on line 9-10.		
9.87	Point for AP 10, sec. 13.		
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.		

	T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T41N R6W
į	S13 \AP10
	1993
	Deposit a magnet in a 1 x 1 x 2 in. White colored plastic case beneath the stainless steel post.
	S. 18°08' E., on line 10-11.
4.98	Point for AP 11, sec. 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	S13 \ AP11
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 4°31' E., on line 11-12.
5.99	Point for AP 12, sec. 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T41N R6W
	S13 AP12
	1993
	Deposit a magnet in a 1 x 1 x 2 in. white colored plastic case beneath the stainless steel post.
	S. 2°29' E., on line 12-13.
3.93	Point for AP 13, sec. 13.
Ī	

Informative Traverses in Certain Sections, T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 12°10' E., on line 13-14.

4.21 Point for AP 14, sec. 13.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a 1 \times 1 \times 2 in. white colored plastic case beneath the stainless steel post.

S. 62°49' E., on line 14-15.

5.51 AP 15, sec. 13, on the N. and S. center line of sec. 13, hereinbefore described.

Description of Cottonwood Point Wilderness Area Boundary, T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

The following description is for informational purposes only.

Beginning at Angle Point 1, sec. 4, identical with Angle Point 3, sec. 33, T. 42 N., R. 6 W., on the N. bdy. of the Tp.

thence S. 28°39' E., 6.70 chs. dist. to Angle Point 2, sec. 4;

thence S. 28°22′ W., 3.75 chs. dist. to Angle Point 3, sec. 4;

thence S. 52°46′ W., 2.04 chs. dist. to Angle Point 4, sec. 4;

thence N. 61°18′ W., 3.50 chs. dist. to Angle Point 5, sec. 4;

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

```
CHAINS
         thence N. 64°46' W., 3.99 chs. dist. to Angle Point 6, sec. 4,
              identical with Angle Point 1, sec. 5, on the line bet. secs.
         thence S. 71°24′ W., 3.96 chs. dist. to Angle Point 2, sec. 5;
         thence N. 88°54' W., 6.17 chs. dist. to Angle Point 3, sec. 5;
         thence S. 22°30′ W., 6.80 chs. dist. to Angle Point 4, sec. 5;
         thence S. 67°26' W., 8.03 chs. dist. to Angle Point 5, sec. 5,
              on the N. and S. centerline of the NE 1/4 of sec. 5;
         thence S. 0°34' E., on the N. and S. centerline of the NE 1/4 of
              sec. 5, 3.17 chs. dist. to the NE 1/16 sec. cor. of sec. 5;
         thence N. 89°41' W., on the E. and W. centerline of the NE 1/4 of
              sec. 5, 5.20 chs. dist. to Angle Point 7, sec. 5;
         thence S. 41°19' W., 5.78 chs. dist. to Angle Point 8, sec. 5;
         thence S. 56°44' W., 13.15 chs. dist. to Angle Point 9, sec. 5,
              on the N. and S. centerline of sec. 5;
         thence S. 0°22' E., on the N. and S. centerline of sec. 5,
              22.58 chs. dist. to Angle Point 12, sec. 5;
         thence S. 23°51' E., 12.92 chs. dist. to Angle Point 13, sec. 5;
         thence S. 46°08' E., 4.72 chs. dist. to Angle Point 14, sec. 5;
         thence S. 65°03' E., 8.55 chs. dist. to Angle Point 15, sec. 5;
         thence N. 47°24' E., 3.88 chs. dist. to Angle Point 16, sec. 5;
         thence N. 69°42' E., 6.07 chs. dist. to Angle Point 17, sec. 5;
        thence S. 80°39' E., 12.47 chs. dist. to Angle Point 18, sec. 5;
         thence S. 1°10' E., 9.96 chs. dist. to Angle Point 19, sec. 5,
              identical with AP 1, sec. 8, on the line bet. secs. 5 and 8;
        thence S. 50°47' E., 3.63 chs. dist. to Angle Point 2, sec. 8,
              identical with AP 1, sec. 9, on the line bet. secs. 8 and 9;
        thence S. 16°40' E., 6.93 chs. dist. to Angle Point 2, sec. 9;
        thence S. 13°06' E., 3.29 chs. dist. to Angle Point 3, sec. 9;
        thence S. 21°15′ W., 7.48 chs. dist. to Angle Point 4, sec. 9;
        thence S. 19°10' E., 6.07 chs. dist. to Angle Point 5, sec. 9;
        thence S. 32°52' E., 7.47 chs. dist. to Angle Point 6, sec. 9;
        thence S. 23°47' W., 5.36 chs. dist. to Angle Point 7, sec. 9;
        thence S. 10°04' W., 6.62 chs. dist. to Angle Point 8, sec. 9;
        thence S. 11°10' E., 5.12 chs. dist. to Angle Point 9, sec. 9;
        thence S. 53°26' E., 3.72 chs. dist. to Angle Point 10, sec. 9;
        thence S. 8°04' W., 4.28 chs. dist. to Angle Point 11, sec. 9;
        thence N. 80°30′ W., 3.85 chs. dist. to Angle Point 12, sec. 9;
        thence S. 69°17' W., 2.49 chs. dist. to Angle Point 13, sec. 9,
             identical with Angle Point 3, sec. 8, on the line bet. secs.
             8 and 9;
        thence S. 59°28' W., 4.63 chs. dist. to Angle Point 4, sec. 8;
        thence S. 21°12′ W., 9.89 chs. dist. to Angle Point 5, sec. 8;
        thence S. 14°22' E., 3.74 chs. dist. to Angle Point 6, sec. 8;
        thence S. 73°39' E., 4.56 chs. dist. to Angle Point 7, sec. 8;
        thence S. 5°19' E., 5.01 chs. dist. to Angle Point 8, sec. 8;
        thence S. 28°15' E., 3.86 chs. dist. to Angle Point 9, sec. 8,
             identical with Angle Point 14, sec. 9, on the line bet.
             secs. 8 and 9;
```

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

```
CHAINS
         thence S. 41°12' E., 1.15 chs. dist. to Angle Point 15, sec. 9,
              identical with Angle Point 1, sec. 16, on the line bet.
              secs. 9 and 16;
         thence S. 44°08' E., 3.34 chs. dist. to Angle Point 2, sec. 16;
         thence S. 87°01' E., 3.43 chs. dist. to Angle Point 3, sec. 16;
         thence N. 53°20' E., 4.35 chs. dist. to Angle Point 4, sec. 16,
             on the line bet. secs. 9 and 16;
         thence N. 89°53' E., on the line bet. secs. 9 and 16, 5.10 chs.
             dist. to Angle Point 5, sec. 16;
         thence S. 3°52' E., 4.16 chs. dist. to Angle Point 6, sec. 16;
         thence S. 16°33′ E., 3.81 chs. dist. to Angle Point 7, sec. 16;
        thence S. 62°09' E., 2.88 chs. dist. to Angle Point 8, sec. 16;
        thence S. 69°43' E., 5.35 chs. dist. to Angle Point 9, sec. 16;
        thence N. 47°57' E., 3.73 chs. dist. to Angle Point 10, sec. 16;
        thence S. 65°20' E., 2.86 chs. dist. to Angle Point 11, sec. 16;
        thence N. 87°00' E., 3.45 chs. dist. to Angle Point 12, sec. 16;
        thence S. 35°53' E., 2.92 chs. dist. to Angle Point 13, sec. 16;
        thence N. 84°46' E., 2.55 chs. dist. to Angle Point 14, sec. 16;
        thence N. 49°21' E., 2.21 chs. dist. to Angle Point 15, sec. 16;
        thence N. 77°15' E., 5.53 chs. dist. to Angle Point 16, sec. 16;
        thence S.
                  7°26' E., 6.77 chs. dist. to Angle Point 17, sec. 16;
        thence S. 65°10' E., 6.08 chs. dist. to Angle Point 18, sec. 16;
        thence N. 89°36' E., 5.42 chs. dist. to Angle Point 19, sec. 16;
        thence N. 59°52' E.,
                              7.52 chs. dist. to Angle Point 20, sec. 16;
        thence N. 38°21' E., 9.35 chs. dist. to Angle Point 21, sec. 16;
        thence N. 83°18' E., 3.66 chs. dist. to Angle Point 22, sec. 16;
        thence S. 76°17' E., 2.90 chs. dist. to Angle Point 23, sec. 16;
        thence N. 41°01' E., 2.49 chs. dist. to Angle Point 24, sec. 16;
        thence N. 43°42' E., 3.07 chs. dist. to Angle Point 25, sec. 16;
        thence N. 24°38' E., 3.63 chs. dist. to the cor. of secs.
             9, 10, 15 and 16, identical with Angle Point 26, sec. 16,
             and Angle Point 1, sec. 10;
        thence N. 83°59' E., 8.68 chs. dist. to Angle Point 2, sec. 10;
        thence N. 73°17' E.,
                              5.00 chs. dist. to Angle Point 3, sec. 10;
        thence N. 25°09' E., 3.09 chs. dist. to Angle Point 4, sec. 10;
        thence N.
                  3°36' E., 6.65 chs. dist. to Angle Point 5, sec. 10;
        thence N. 20°19' E., 8.89 chs. dist. to Angle Point 6, sec. 10;
        thence N. 3°43' W., 5.62 chs. dist. to Angle Point 7, sec. 10;
        thence N. 31°23' E., 5.23 chs. dist. to Angle Point 8, sec. 10;
        thence N. 56°18' E., 5.06 chs. dist. to Angle Point 9, sec. 10;
        thence N. 10°18' E., 6.24 chs. dist. to Angle Point 10, sec. 10;
        thence N. 47°30' W., 5.29 chs. dist. to Angle Point 11, sec. 10;
        thence N. 43°39' W., 8.99 chs. dist. to Angle Point 12, sec. 10;
        thence N. 36°22' W., 5.97 chs. dist. to Angle Point 13, sec. 10;
        thence N. 15°28' W., 5.13 chs. dist. to Angle Point 14, sec. 10;
        thence N. 0°22' W., 5.15 chs. dist. to Angle Point 15, sec. 10;
        thence N. 44°32' W., 12.47 chs. dist. to Angle Point 16, sec. 10;
        thence N. 17°38' W., 7.40 chs. dist. to the cor. of secs.
             3, 4, 9 and 10, identical with Angle Point 17, sec. 10, and
             Angle Point 1, sec. 3;
        thence N. 36°44' E., 3.43 chs. dist. to Angle Point 2, sec. 3;
```

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

```
CHAINS
         thence S. 44°19' E., 3.83 chs. dist. to Angle Point 3, sec. 3,
              identical with Angle Point 18, sec. 10, on the line bet.
              secs. 3 and 10;
         thence S. 47°29' E., 5.14 chs. dist. to Angle Point 19, sec. 10;
         thence S. 54°51' E., 4.39 chs. dist. to Angle Point 20, sec. 10;
         thence S. 74°26' E., 5.41 chs. dist. to Angle Point 21, sec. 10;
         thence N. 74°43' E., 6.20 chs. dist. to Angle Point 22, sec. 10;
         thence N. 57°04' E., 4.58 chs. dist. to Angle Point 23, sec. 10;
         thence N. 34°00' E., 4.07 chs. dist. to Angle Point 24, sec. 10,
              identical with Angle Point 4, sec. 3, on the line bet. secs.
              3 and 10:
         thence N. 22°20' E.,
                              5.26 chs. dist. to Angle Point 5, sec. 3;
         thence N.
                   3°33′ W.,
                              5.59 chs. dist. to Angle Point 6, sec. 3;
         thence N. 5°35' E., 4.61 chs. dist. to Angle Point 7, sec. 3;
         thence N. 20°41' W., 4.58 chs. dist. to Angle Point 8, sec. 3;
                  7°14' E., 7.13 chs. dist. to Angle Point 9, sec. 3;
         thence N.
         thence N. 3°26' E., 6.63 chs. dist. to Angle Point 10, sec. 3;
         thence N. 51°28' E.,
                              2.98 chs. dist. to Angle Point 11, sec. 3;
         thence S. 13°34' E.,
                              3.51 chs. dist. to Angle Point 12, sec. 3;
         thence S.
                  7°31' E., 2.90 chs. dist. to Angle Point 13, sec. 3;
         thence S. 24°20' E., 5.25 chs. dist. to Angle Point 14, sec. 3;
                  3°33' E., 5.78 chs. dist. to Angle Point 15, sec. 3;
         thence S.
        thence S. 34°05' E., 3.26 chs. dist. to Angle Point 16, sec. 3;
                              5.54 chs. dist. to Angle Point 17, sec. 3;
        thence S. 33°37' E.,
        thence S. 29°21' E.,
                              4.38 chs. dist. to Angle Point 18, sec. 3;
        thence S. 30°23' E., 4.82 chs. dist. to Angle Point 19, sec. 3;
        thence N. 54°43' E.,
                              3.04 chs. dist. to Angle Point 20, sec. 3;
        thence S. 30°10' E., 5.13 chs. dist. to Angle Point 21, sec. 3,
             identical with Angle Point 25, sec. 10, on the line bet.
             secs. 3 and 10:
        thence S. 86°09' E.,
                              5.01 chs. dist. to Angle Point 26, sec. 10;
        thence S. 50°55' E.,
                              4.94 chs. dist. to Angle Point 27, sec. 10;
                   7°10′ W.,
        thence S.
                              2.35 chs. dist. to Angle Point 28, sec. 10;
        thence S. 60°33′ E., 4.98 chs. dist. to Angle Point 29, sec. 10;
        thence N. 82°45' E., 4.67 chs. dist. to Angle Point 30, sec. 10;
        thence N. 4°41' W., 5.23 chs. dist. to Angle Point 31, sec. 10;
        thence N. 20°22' E., 2.63 chs. dist. to Angle Point 32, sec. 10,
             identical with Angle Point 22, sec. 3, on the line bet.
             secs. 3 and 10;
        thence N. 44°23' E.,
                              3.03 chs. dist. to Angle Point 23, sec. 3;
        thence N. 53°40' E.,
                              4.17 chs. dist. to Angle Point 24, sec. 3;
        thence N. 29°46' E., 4.40 chs. dist. to Angle Point 25, sec. 3;
                  5°44' E., 4.56 chs. dist. to Angle Point 26, sec. 3;
        thence N.
                   9°49′ W.,
        thence N.
                             5.14 chs. dist. to Angle Point 27, sec. 3;
        thence N. 24°16′ W., 4.43 chs. dist. to Angle Point 28, sec. 3;
        thence N.
                   0°08' W., 7.13 chs. dist. to Angle Point 29, sec. 3;
        thence N. 51°47' E., 3.00 chs. dist. to Angle Point 30, sec. 3;
        thence N. 67°17′ E., 1.37 chs. dist. to Angle Point 31, sec. 3;
        thence S. 66°42' E., 1.50 chs. dist. to Angle Point 32, sec. 3,
             identical with Angle Point 1, sec. 2, on the line bet. secs.
             2 and 3;
```

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

```
CHAINS
        thence N. 51°42′ E., 1.88 chs. dist. to Angle Point 2, sec. 2;
        thence N. 14°11' E., 4.89 chs. dist. to Angle Point 3, sec. 2;
        thence N. 1°19' W., 6.02 chs. dist. to Angle Point 4, sec. 2;
        thence N. 10°49' W., 4.73 chs. dist. to Angle Point 5, sec. 2;
        thence N. 31°30' W., 3.17 chs. dist. to Angle Point 6, sec. 2,
             identical with Angle Point 33, sec. 3, on the line bet.
             secs. 2 and 3:
        thence N. 83°45' W., 2.14 chs. dist. to Angle Point 34, sec. 3;
        thence N. 6°40' W., 4.74 chs. dist. to Angle Point 35, sec. 3;
        thence N. 15°49' E.,
                              2.07 chs. dist. to Angle Point 36, sec. 3;
        thence N. 17°25' W.,
                             7.49 chs. dist. to Angle Point 37, sec. 3;
        thence N. 10°15' W.,
                              6.04 chs. dist. to Angle Point 38, sec. 3;
        thence N. 15°35' W., 5.95 chs. dist. to Angle Point 39, sec. 3;
        thence N. 88°03' E., 3.25 chs. dist. to Angle Point 40, sec. 3;
        thence S. 30°04' E., 6.09 chs. dist. to Angle Point 41, sec. 3;
        thence S. 7°19' E., 5.58 chs. dist. to Angle Point 42, sec. 3,
             identical with Angle Point 7, sec. 2, on the line bet. secs.
             2 and 3:
        thence S. 19°57' E.,
                             3.23 chs. dist. to Angle Point 8, sec. 2;
        thence S. 35°18' E., 6.83 chs. dist. to Angle Point 9, sec. 2;
        thence S. 53°40' E., 5.70 chs. dist. to Angle Point 10, sec. 2;
        thence S. 43°00' E., 4.28 chs. dist. to Angle Point 11, sec. 2;
        thence S. 24°48' E., 4.65 chs. dist. to Angle Point 12, sec. 2;
        thence S. 3°01' E., 3.52 chs. dist. to Angle Point 13, sec. 2;
        thence S. 4°17' E.,
                              3.44 chs. dist. to Angle Point 14, sec. 2;
        thence S. 18°30' E., 2.99 chs. dist. to Angle Point 15, sec. 2;
        thence S. 70°07' E., 1.46 chs. dist. to Angle Point 16, sec. 2;
        thence S. 50°01' E., 1.78 chs. dist. to Angle Point 17, sec. 2;
        thence S. 45°44' E., 3.29 chs. dist. to Angle Point 18, sec. 2;
        thence S. 75°28' E., 4.50 chs. dist. to Angle Point 19, sec. 2;
        thence N. 64°09' E., 3.29 chs. dist. to Angle Point 20, sec. 2;
        thence N. 65°23' E., 3.31 chs. dist. to Angle Point 21, sec. 2;
        thence N. 54°12' E., 3.04 chs. dist. to Angle Point 22, sec. 2;
        thence N. 34°15' E., 4.44 chs. dist. to Angle Point 23, sec. 2;
        thence N. 32°22' E., 4.06 chs. dist. to Angle Point 24, sec. 2;
        thence N. 36°15' E., 6.59 chs. dist. to Angle Point 25, sec. 2;
        thence N. 1°34' E., 5.48 chs. dist. to Angle Point 26, sec. 2;
        thence N. 11°37' E., 5.37 chs. dist. to Angle Point 27, sec. 2;
        thence N. 28°59' E., 8.61 chs. dist. to Angle Point 28, sec. 2;
        thence N. 9°46' E., 4.64 chs. dist. to Angle Point 29, sec. 2;
        thence N. 16°01' E., 5.54 chs. dist. to Angle Point 30, sec. 2;
        thence N. 14°18′ W., 3.73 chs. dist. to the original witness
             cor. to the 1/4 sec. cor. of secs. 2 and 35, on the N. bdy.
             of the Tp., identical with Angle Point 31, sec. 2 and Angle
             Point 1, sec. 35, T. 42 N., R. 6 W.
        From the original witness cor. to the cor. of secs. 1, 2, 35, and
        36, on the N. bdy. of the Tp., identical with Angle Point 32,
        sec. 2 and Angle Point 41, sec. 35, T. 42 N., R. 6 W.
```

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

```
CHAINS
         thence S. 55°35' E.,
                               5.96 chs. dist. to Angle Point 33, sec. 2;
         thence S. 49°14′ W.,
                               2.87 chs. dist. to Angle Point 34, sec. 2;
         thence S. 65°58' W.,
                               4.11 chs. dist. to Angle Point 35, sec. 2;
         thence S.
                   2°33′ W.,
                               3.65 chs. dist. to Angle Point 36, sec. 2;
         thence S. 21°02′ W.,
                               2.38 chs. dist. to Angle Point 37, sec. 2;
         thence S. 59°06' W.,
                               4.60 chs. dist. to Angle Point 38, sec. 2;
                   8°34′ W.,
                               4.75 chs. dist. to Angle Point 39, sec. 2;
         thence N.
                   1°59′ W.,
                               4.28 chs. dist. to Angle Point 40, sec. 2;
         thence N.
         thence N. 78°10' W.,
                               1.18 chs. dist. to Angle Point 41, sec. 2;
         thence S. 50°13′ W.,
                               7.26 chs. dist. to Angle Point 42, sec. 2;
         thence S. 29°18' W.,
                               7.50 chs. dist. to Angle Point 43, sec. 2;
        thence S. 31°01' W.,
                               4.68 chs. dist. to Angle Point 44, sec. 2;
         thence S.
                   1°35′ E.,
                               2.57 chs. dist. to Angle Point 45, sec. 2;
         thence S. 41°57′ W., 2.22 chs. dist. to Angle Point 46, sec. 2;
         thence S.
                   1°05′ W.,
                              3.04 chs. dist. to Angle Point 47, sec. 2;
         thence S. 27°15' E.,
                              3.25 chs. dist. to Angle Point 48, sec. 2;
         thence S. 12°43′ W., 10.13 chs. dist. to Angle Point 49, sec. 2;
         thence S. 13°13' W., 12.11 chs. dist. to Angle Point 50, sec. 2;
        thence S. 22°21' W.,
                              5.61 chs. dist. to Angle Point 51, sec. 2;
         thence S. 86°13′ W., 2.28 chs. dist. to Angle Point 52, sec. 2;
        thence S. 13°09' W.,
                              3.08 chs. dist. to Angle Point 53, sec. 2;
                              7.53 chs. dist. to Angle Point 54, sec. 2;
                   4°14′ W.,
         thence S.
        thence S. 18°15' E.,
                              3.25 chs. dist. to Angle Point 55, sec. 2;
         thence S. 59°02' E., 8.04 chs. dist. to Angle Point 56, sec. 2;
        thence S. 82°01' E.,
                              3.86 chs. dist. to Angle Point 57, sec. 2;
         thence S. 72°31' E.,
                               4.88 chs. dist. to Angle Point 58, sec. 2;
         thence N. 74°32' E.,
                               3.28 chs. dist. to Angle Point 59, sec. 2;
         thence N. 28°55' E.,
                               6.79 chs. dist. to Angle Point 60, sec. 2;
        thence N. 87°05' E.,
                               7.33 chs. dist. to Angle Point 61, sec. 2;
         thence N. 64°59' E., 3.92 chs. dist. to Angle Point 62, sec. 2;
         thence N. 57°36' E., 1.93 chs. dist. to Angle Point 63, sec. 2,
              identical with Angle Point 1, sec. 1, on the line bet. secs.
              1 and 2;
        thence N. 31°09' E., 6.72 chs. dist. to Angle Point 2, sec. 1;
        thence N. 25°26' E.,
                              6.60 chs. dist. to Angle Point 3, sec. 1;
        thence N. 39°55' E., 9.96 chs. dist. to Angle Point 4, sec. 1;
        thence N. 27°08' E., 10.58 chs. dist. to Angle Point 5, sec. 1;
        thence N. 52°02' E., 3.62 chs. dist. to Angle Point 6, sec. 1;
        thence S. 43°26' E.,
                              1.43 chs. dist. to Angle Point 7, sec. 1;
        thence S. 26°46' W.,
                               2.56 chs. dist. to Angle Point 8, sec. 1;
                   9°50' W..
                               5.70 chs. dist. to Angle Point 9, sec. 1;
        thence S.
        thence S. 16°35' W.,
                               7.27 chs. dist. to Angle Point 10, sec. 1;
        thence S. 18°11' W.,
                               3.83 chs. dist. to Angle Point 11, sec. 1;
        thence S. 38°37' E.,
                               5.41 chs. dist. to Angle Point 12, sec. 1;
        thence S. 79°39' E.,
                              7.59 chs. dist. to Angle Point 13, sec. 1;
        thence N. 68°38' E.,
                               3.65 chs. dist. to Angle Point 14, sec. 1;
        thence S. 75°19' E.,
                               3.52 chs. dist. to Angle Point 15, sec. 1;
        thence S. 1°14' E.,
                               1.25 chs. dist. to Angle Point 16, sec. 1;
        thence N. 68°38' W.,
                              1.86 chs. dist. to Angle Point 17, sec. 1;
        thence S. 64°04' W.,
                              4.88 chs. dist. to Angle Point 18, sec. 1;
        thence S. 84°03′ W., 3.90 chs. dist. to Angle Point 19, sec. 1;
```

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona

```
CHAINS
         thence S. 14°44′ W., 2.45 chs. dist. to Angle Point 20, sec. 1;
         thence S. 39°45' E., 3.90 chs. dist. to Angle Point 21, sec. 1;
         thence N. 88°05' W., 8.84 chs. dist. to Angle Point 22, sec. 1;
         thence S. 85°50′ W., 1.74 chs. dist. to Angle Point 23, sec. 1;
         thence S. 50°27′ W., 4.10 chs. dist. to Angle Point 24, sec. 1;
         thence S. 42°20′ W., 6.15 chs. dist. to Angle Point 25, sec. 1;
         thence S. 28°33' W., 3.20 chs. dist. to Angle Point 26, sec. 1,
              identical with Angle Point 1, sec. 12, on the line bet.
              secs. 1 and 12;
         thence S. 67°41′ W., 4.36 chs. dist. to Angle Point 2, sec. 12;
         thence S. 72°42' W., 2.22 chs. dist. to Angle Point 3, sec. 12,
              identical with Angle Point 1, sec. 11, on the line bet.
              secs. 11 and 12;
         thence S. 0°03' E., on the line bet. secs. 11 and 12, 37.70 chs.
              dist. to the 1/4 sec. cor. of secs. 11 and 12;
         thence S. 0°04' E., on the line bet. secs. 11 and 12, 39.98 chs.
              dist. to the cor. of secs. 11, 12, 13 and 14;
         thence S. 89°53' E., on the line bet. secs. 12 and 13, 25.775
              chs. dist. to Angle Point 4, sec. 12;
         thence N. 13°27' E., 8.34 chs. dist. to Angle Point 5, sec. 12;
         thence N. 12°19' E., 7.86 chs. dist. to Angle Point 6, sec. 12; thence S. 84°32' E., 3.73 chs. dist. to Angle Point 7, sec. 12;
         thence S. 1°52' W., 7.40 chs. dist. to Angle Point 8, sec. 12;
         thence S. 10°19' W., 8.18 chs. dist. to Angle Point 9, sec. 12,
              identical with Angle Point 8, sec. 13, on the line bet.
              secs. 12 and 13;
         thence S. 89°53' E., on the line bet. secs. 12 and 13, 8.715 chs.
              dist. to the 1/4 sec. cor. of secs. 12 and 13;
         thence S. 0°01' E., on the N. and S. centerline of sec. 13,
              35.72 chs. dist. to Angle Point 15, sec. 13;
         thence S. 64°15' E., 6.08 chs. dist. to Angle Point 16, sec. 13;
         thence S. 75°25' E., 4.70 chs. dist. to Angle Point 17, sec. 13;
         thence S. 85°56' E., 6.01 chs. dist. to Angle Point 18, sec. 13;
         thence N. 77°45' E., 8.77 chs. dist. to Angle Point 19, sec. 13;
         thence N. 64^{\circ}28' E., 9.79 chs. dist. to Angle Point 20, sec. 13; thence N. 68^{\circ}41' E., 7.07 chs. dist. to Angle Point 21, sec. 13,
              identical with Angle Point 1, sec. 18, T. 41 N., R. 5 W., on
              the E. bdy. of the Tp.
```

T. 41 N., R. 6 W., Gila and Salt River Meridian, Arizona **CHAINS** GENERAL DESCRIPTION The land encompassed in this survey is located about 6 miles easterly of Colorado City, Arizona, near the Utah and Arizona State Line. Elevations range from 5200 to 6200 ft. above sea level. Terrain is mountainous and rocky, interspersed with sandy canyons and washes at the lower elevations. Vegetation at the lower elevations consists of sagebrush and grasses, with pinon pine, ponderosa pine and Utah juniper at the higher elevations. Stands of cottonwoods thrive near natural springs. Access is by way of Cane Beds Road and Rosy Canyon Road. Ranching is the principal commercial use of the area. Mining claims have been staked in the area, but it does not appear that the improvement work has been kept up, or that they are currently valid. No excavation or tailings were in evidence. The mean magnetic declination is 13 1/2° E.

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Gordon R. Bubel	Surveying Technician
Ted E. Cazier	Surveying Technician
Jeff A. Hill	Surveying Technician
Lawrence T. Kempe	Surveying Technician
Mark R. Searles	Surveying Technician
Daniel R. Muth	Co-op Student
Steven R. Walton, Jr.	Survey Aid
	·

BOOK 5490 CERTIFICATE OF SURVEY

We, Stephen K. Hansen and Belle A. Craig, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 15th day of July, 1993, we have dependently resurveyed a portion of the subdivisional lines, and subdivided certain sections, and executed a metes-and-bounds survey of the Cottonwood Point Wilderness Area Boundary and informative traverses in Township 41 North, Range 6 West, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Jan. 17, 1997	Belle A. Cray
(Date)	(Cadastral Surveyor)
12/04/96	Star K Ham
(Date)	(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Arizona State Office Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines, and the subdivision of certain sections, the metes-and-bounds survey of the Cottonwood Point Wilderness Area Boundary, and informative traverses in Township 41 North, Range 6 West, Gila and Salt River Meridian, Arizona, executed by Stephen K. Hansen and Belle A. Craig, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

April 29 1997 (Date)	(Chief Cadastral Surveyor of Arizona)
	CERTIFICATE OF TRANSCRIPT
	ranscript of the field notes of the above-described
(Date)	(Chief Cadastral Surveyor of Arizona)