ORIGINAL

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF
A PORTION OF THE SUBDIVISIONAL LINES,
MINERAL SURVEY NUMBER 1072,
AND A PORTION OF MINERAL SURVEY NUMBER 3931,
AND
THE METES-AND-BOUNDS SURVEY OF THE
DOS CABEZAS MOUNTAINS WILDERNESS AREA BOUNDARY,
IN
TOWNSHIP 14 SOUTH, RANGE 27 EAST
Of theGila and Salt River Meridian, In the State ofArizona
EXECUTED BY
Gordon R. Bubel Cadastral Surveyor

Under Special Instructions dated <u>October 20, 1994</u>, approved <u>October 20, 1994</u>, which provided for the surveys included under Group Number <u>781</u>, and assignment instructions dated <u>January 8, 1997</u>.

Survey Commenced <u>February 24, 1997</u> Survey Completed <u>April 9, 1997</u>

INDEX DIAGRAM

TOWNSHIP 14 SOUTH, RANGE 27 EAST,

6	5	4	3	2	1
7	8	9	10	9 3 11	12
18	17	16	11	14	13
19	20	21	22 6	7 5 23	24
30	29	28	27	5 26	25
31	32	33	34	35	36

Dep. Res. M.S. No. 1072 Dep. Res. Portion of M.S. 3931 Metes-and-Bounds Survey of DCMWA

pp. 12-14

pp. 14-20

pp. 20-31

T. 14 S., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the subdivisional lines, Mineral Survey Number 1072, and a portion of Mineral Survey Number 3931, and the metes-and-bounds survey of the Dos Cabezas Mountains Wilderness Area Boundary, in Township 14 South, Range 27 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this resurvey is as follows: In 1882, Theodore F. White, surveyed the south boundary and a portion of the west boundaries. In 1907, Jesse B. Wright resurveyed the south boundary and a portion of the west boundary, and surveyed a portion of the east boundary and the southerly two tiers of sections. In 1914, William B. Kimmel, retraced a portion of the east boundary, resurveyed the north 1/2 mile bet. secs. 25 and 30, and surveyed the north boundary and a portion of the east boundary. In 1938-39, Benjamin J. Kinsey resurveyed the north boundary of the second latitudinal section line through the township and completed the subdivisional lines. Mineral Survey No. 1072, was surveyed by H.G. Howe in 1892, and Mineral Survey No. 3931, was surveyed by John A. Rockfellow in 1924.

The survey was executed in accordance with the specifications as set forth in the <u>Manual of Surveying Instructions</u>, 1973, and the Special Instructions dated October 20, 1994, for Group No. 781, Arizona.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of all lines were determined by direct hour angle observations on the sun, and refer to the true meridian. Distances and angles were measured with a Sokkia SET 2BII total station instrument.

The geographic position of the corner of sections 24 and 25 only, on the east boundary of the township, was determined by the technique of static differential positioning using Ashtech models M-XII and MS-XII geodetic units. U.S. Coast and Geodetic Survey triangulation station "NINE 1945" was used as the control station.

Latitude: 32°11'40.93" N. Longitude: 109°32'01.15" W. NAD27

The mean magnetic declination as taken from quadrangle map DOS CABEZAS, ARIZ., published in 1978 by U.S. Geological Survey, is $12\ 1/2^\circ$ E.

CHAINS

Restoring the resurvey executed by Benjamin J. Kinsey, in 1938-39

Beginning at the cor. of secs. 24 and 25 only, on the E. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap. mkd. T14S S19 S3O S24 S25 R27E R28E 1914 1995, and witnessed as described in the field notes of the dependent resurvey of a portion of the W. bdy., T. 14 S., R. 28 E., executed concurrently under this same group.

S. 89°59' W., on the N. bdy. of sec. 25, on Dos Cabezas Mountains Wilderness Area Bdy.

Over mountainous land, through dense undergrowth.

Point for the 1/4 sec. cor. of sec. 25 only, at proportionate dist., there is no remaining evidence of the original cor.

from which a 1938 bearing object

A granite face, bears N. 81°44′ W., 59 lks. dist., mkd. X on the N. face.

Cor. position was not remonumented.

From this point, the point erroneously established for the 1/4 sec. cor. of sec. 25 only, during the 1938 resurvey, bears N. 80°18′ W., 0.59 ch. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above the ground, with brass cap mkd. 1/4 S25 1938. Add the marks AM T14S R27E 1997 to the brass cap.

Over mountainous land, through dense undergrowth.

Point for the 1/4 sec. cor. of sec. 24 only, reestablished longitudinally at midpoint bet. the cor. of secs. 24 and 25 only on the E. bdy. of the Tp., and the cor. of secs. 23 and 24 only.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, in a supporting mound of stone, 6 ft. base, to top, with brass cap mkd.

T14S R27E S24 1/4 — 1997

from which

39.92

CHAINS

A XBO, chiseled on the NE face of a rock outcrop, 12 ft. high, 30 ft. long, bears S. 52° W., 6 lks. dist.

From this point, the point erroneously established for the 1/4 sec. cor. of sec. 24 only, during the 1938 resurvey, bears N. 1°46′ W., 0.21 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. 1/4 S24 1938. Remove the iron post and dismantle the mound of stone.

79.22

The cor. of secs. 25 and 26 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 17 ins. above the ground, with brass cap mkd. S24 S26 S25 1938.

from which the 1938 bearing tree

An oak, 13 ins. diam., bears S. 76° E., 166 lks. dist., with healed over blaze. (Record: S. 73° E.)

Add the marks T14S R27E 1997 to the brass cap.

N. 89°14′ W., on the N. bdy. of sec. 26, on the Dos Cabezas Wilderness Area Bdy.

Over mountainous land, through dense undergrowth.

0.62

The cor. of secs. 23 and 24 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 17 ins. above the ground, with brass cap mkd. S23 S24 S26 1938.

from which the original bearing trees

- A forked juniper stump, 24 ins. diam., bears N. 41 3/4° E., 23 lks. dist., with faint illegible scribe marks. (Record: N. 43° E.)
- A juniper, 24 ins. diam., bears N. 62° W., 127 lks. dist., with illegible scribe marks on a partially healed over blaze. (Record: Oak, N. 63° W.)

Add the marks T14S R27E 1997 to the brass cap.

Leave the Dos Cabezas Mountains Wilderness Area Bdy.

40.52

The 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. 1/4 S23 S26 1938.

CHAINS	
	Add the marks T14S R27E 1997 to the brass cap.
	N. 89°12′ W., beginning new measurement.
	Over mountainous land, through moderate undergrowth.
39.79	The cor. of secs. 22 and 23 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd. T14S R27E S22 S23 S26 1938.
	Add the marks 1997 to the brass cap.
40.37	The cor. of secs. 26 and 27 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd. T14S R27E S22 S27 S26 1938, with a mound of stone, 3 ft. base, 2 ft. high, S. of the cor.
	Restoring the survey executed by Benjamin J. Kinsey, in 1938-39
	From the cor. of secs. 22 and 23 only.
	N. 0°15' E., bet. secs. 22 and 23.
	Ascending over mountainous land, through moderate undergrowth and scattered timber.
39.30	The 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd. 1/4 S22 S23 1938.
	Add the marks T14S R27E 1997 to the brass cap.
	Cor. is located on a steep WNW facing slope.
	North, beginning new measurement.
18.22	Point for AP 1, sec. 23, identical with AP 5, sec. 22, on the Dos Cabezas Mountains Wilderness Area Bdy., hereinafter described.
40.03	The cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. T14S R27E S15 S14 S22 S23 1938 (Record: 1939).

CHAINS

from which the original bearing trees

An oak, 7 ins. diam., bears S. 5° E., 19 lks. dist., with healed over blaze. (Record: 26 lks. dist.)

A dead and standing oak, 4 ins. diam., bears S. 68 1/2° W., 13 lks. dist., mkd. T14S R27E S22 BT on an open blaze. (Record: S. 85° W.)

An oak, 8 ins. diam., bears N. 68 1/4° W., 46 lks. dist., with illegible scribe marks on a partially healed over blaze. (Record: N. 70° W.)

Add the marks 1997 to the brass cap.

From the cor. of secs. 13, 14, 23 and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. T14S R27E S14 S13 S23 S24 1938.

from which the original bearing trees

A stumphole, bears N. 66° E., 31 lks. dist., with a fallen oak alongside, with a rotted out blaze.

An oak, 8 ins. diam., bears S. 30° E., 18 lks. dist., with healed over blaze.

An oak, 17 ins. diam., bears S. 34° W., 119 lks. dist., with healed over blaze.

An oak, 17 ins. diam., bears N. 23° W., 127 lks. dist., with healed over blaze.

Add the marks 1997 to the brass cap.

N. 89°43' W., bet. secs. 14 and 23.

Over mountainous land, through dense undergrowth and moderate timber, within the Dos Cabezas Mountains Wilderness Area.

True point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate dist. The cor. point falls in wash, where it is impracticable to establish a permanent monument.

The witness cor. to the 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. WC 1/4 S14 S23 1938.

	T. 14 S., R. 27 E., Gila and Salt River Meridian, Arizona
CHAINS	
	from which the original bearing trees
	An oak, 10 ins. diam., bears S. 60° E., 3 lks. dist., with healed over blaze. (Record: 2 lks. dist.)
	An oak, 8 ins. diam., bears N. 72° W., 3 lks. dist., with healed over blaze. (Record: N. 45° W., 2 lks. dist.)
	Add the marks T14S R27E 1997 to the brass cap.
	S. 89°53′ W., beginning new measurement.
	Over mountainous land, through dense undergrowth.
39.56	The cor. of secs. 14, 15, 22 and 23.
	From the 1/4 sec. cor. of secs. 10 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 17 ins. above the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. 1/4 S10 S11 1939 (Record: 1938).
	from which the remaining original bearing tree
	A alligator juniper, 26 ins. diam., bears S. 45° W., 54 lks. dist., mkd. 1/4 S10 BT, on an open blaze.
	Add the marks T14S R27E 1997 to the brass cap.
	N. 0°03' E., bet. secs. 10 and 11.
	Descending over mountainous land, through dense undergrowth and moderate timber.
9.265	Intersect line 1-2, Red Jacket lode, M.S. No. 1072, hereinafter described.
23.38	Intersect line 4-1, Red Jacket lode, M.S. No. 1072, hereinafter described.
39.92	The cor. of secs. 2, 3, 10 and 11, monumented with an iron post, 2 ins. diam., firmly set, projecting 25 ins. above the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. T14S R27E S2 S3 S10 S11 1938.
	from which the remaining original bearing trees
	An oak, 15 ins. diam., bears N. 57° E., 36 lks. dist., with healed over blaze.
1	

CHAINS

An alligator juniper, 27 ins. diam., bears S. 19° W., 83 lks. dist., mkd. T14S R27E S10 BT on a partially healed over blaze.

Add the marks 1997 to the brass cap.

From the cor. of secs. 1, 2, 11 and 12, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. T14S R27E S2 S1 S11 S12 1939, (Record: 1938).

from which the original bearing trees

A stumphole, bears S. 70° E., 29 lks. dist., with a fallen oak alongside, with a rotted out blaze.

An oak, 8 ins. diam., bears S. 4° W., 15 lks. dist., with healed over blaze.

A stumphole, bears N. 43° W., 64 lks. dist., with a fallen oak alongside, mkd. T14S R27E S2 BT.

Add the marks 1997 to the brass cap.

West, bet. secs. 2 and 11.

Descending over mountainous land, through dense undergrowth and moderate timber.

41.12

The 1/4 sec. cor. of secs. 2 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd. 1/4 S2 S11 1939.

from which the original bearing trees

An oak, 15 ins. diam., bears N. 60° E., 71 lks. dist., with a healed over blaze.

An oak, 28 ins. diam., bears S. 15° E., 62 lks. dist., mkd. 1/4 S11 BT on a partially healed over blaze.

Add the marks T14S R27E 1997 to the brass cap.

S. 89°56' W., beginning new measurement.

Over mountainous land, through moderate undergrowth.


	1. 14 S., R. 27 E., Gila and Sait River Meridian, Arizona
CHAINS	
20.44	Point for AP 1, sec. 11, identical with AP 9, sec. 2, on the Dos Cabezas Mountains Wilderness Area Bdy., hereinafter described.
38.67	The cor. of secs. 2, 3, 10 and 11.
	From the cor. of secs. 14, 15, 22 and 23.
	N. 89°43′ W., bet. secs. 15 and 22.
	Over mountainous land, through dense undergrowth and moderate timber.
38.94	Point for AP 1, sec. 22, identical with AP 12, sec. 15, on the Dos Cabezas Mountains Wilderness Area Bdy., hereinafter described.
40.06	The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 28 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. 1/4 S15 S22 1939.
	from which the original bearing trees
	An oak 14 ins. diam., bears N. 61° E., 26 lks. dist., with healed over blaze. (Record: N. 58° E., 30 lks. dist.)
	An oak 10 ins. diam., bears S. 22 1/2° E., 20 lks. dist., with healed over blaze. (Record: S. 20° E.)
	Add the marks T14S R27E 1997 to the brass cap.
	From the 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 22 ins. above the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. 1/4 S16 S15 1939 (Record: 1938).
	from which the original bearing trees
	An oak, 9 ins. diam., bears N. 44° E., 43 lks. dist., mkd. S15 BT on an open blaze.
	A dead and standing oak, 10 ins. diam., bears S. 55° W., 19 lks. dist., with illegible scribe marks on a rotted out blaze.
	Add the marks T14S R27E 1997 to the brass cap.
	N. 0°09' E., bet. secs. 15 and 16.

CHAINS Descending over mountainous land, through dense undergrowth and moderate timber. 39.69 The cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2 ins. diam., firmly set, projecting 24 ins. above the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. T14S R27E S9 S10 S16 S15 1939 (Record: 1938). from which the remaining original bearing trees A dead and standing oak, 5 ins. diam., bears N. 48° E., 34 lks. dist., with illegible scribe marks on a partially healed over blaze. An oak, 16 ins. diam., bears S. 45° E., 52 lks. dist., with illegible scribe marks on a partially healed over blaze. (Record: 54 lks. dist.) An oak, 8 ins. diam., bears N. 41° W., 48 lks. dist., with healed over blaze. Add the marks 1997 to the brass cap. From the 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 22 ins. above the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. 1/4 S16 S15 1939 (Record: 1938). from which the original bearing trees An oak, 15 ins. diam., bears S. 35° W., 49 lks. dist., mkd. 1/4 S15 BT on an open blaze. (Record: S. 37° W., 52 lks. dist.) An alligator juniper, 23 ins. diam., bears N. 37° W., 47 lks. dist., with illegible scribe marks on a partially healed over blaze. (Record: N. 40° W., 54 lks. dist.) Add the marks T14S R27E to the brass cap. S. 89°50' W., bet. secs. 10 and 15. Over mountainous land, through dense undergrowth and moderate timber. Point for AP 1, sec. 15, identical with AP 7, sec. 10, on the Dos 14.72 Cabezas Mountains Wilderness Area Bdy. The cor. of secs. 9, 10, 15 and 16. 40.07

CHAINS Restoring the survey executed by H.G. Howe, in 1892 From cor. No. 1, Red Jacket lode, determined at record bearing and dist. from United States Mineral Monument No. 1, Tevis Mining District, there is no remaining evidence of the original cor. Set an aluminum driver, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd. T14S R27E S10 COR 1 MS 1072 Cor. is located 15 lks. E. of wash, 15 lks. wide, 5 ft. deep, drains NNW. From this cor. point, U.S.M.M. No.1, Tevis Mining District, bears N. 25°53' W., 60.98 chs. (4024.7 ft.) dist., determined by a mound of stone, 7 ft. base, 6 ft. high, located on edge of granite ledge, from which the remaining original bearing tree An alligator juniper, 16 ins. diam., bears N. 83° W., 42.2 ft. dist., mkd. BT USMM NO. 1 (Record: 41 ft. dist. to face). S. 27°41' E., on line 1-2, Red Jacket lode. Ascending, over mountainous land, through dense brush. 10.33 Intersect the line bet. secs. 10 and 11. From this point, the 1/4 sec. cor. of secs. 10 and 11, bears S. 0°03' W., 9.265 chs. dist., hereinbefore described. 16.13 Point for AP 6, sec. 11, on the Dos Cabezas Mountains Wilderness Area Bdy., hereinafter described. Thence on the Dos Cabezas Mountains Wilderness Area Bdy. 22.58 Point for cor. No. 2, Red Jacket lode, at record bearing and dist.; there is no remaining evidence of the original cor. Cor. is identical with AP 5, sec. 11, of the metes-and-bounds survey of the Dos Cabezas Mountains Wilderness Area Bdy.

CHAINS

Set an aluminum driver, 36 ins. long, 3/4 in. diam., 29 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.




From this cor. point, the center of a mine shaft, 9×6 ft., depth indeterminate, bears N. $43^{\circ}16'$ E., 5.63 chs. dist.

N. $44^{\circ}00'$ E., on line 2-3, Red Jacket lode, on the Dos Cabezas Mountains Wilderness Area Bdy.

Over mountainous land, through moderate undergrowth.

9.09 Point for cor. No. 3, Red Jacket lode, at record bearing and dist.; there is no remaining evidence of the original cor. Cor. is identical with AP 4, sec. 11, of the metes-and-bounds survey of the Dos Cabezas Mountains Wilderness Area Bdy.

Set an aluminum driver, 36 ins. long, 3/4 in. diam., 29 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.



N. 27°41' W., on line 3-4, Red Jacket lode, on the Dos Cabezas Mountains Wilderness Area Bdy.

Over mountainous land, through moderate undergrowth.

7.72 Point for AP 3, sec. 11, on the Dos Cabezas Mountains Wilderness Area Bdy., hereinafter described.

Leave the Dos Cabezas Mountains Wilderness Area Bdy.

CHAINS	
22.58	Point for cor. No. 4, Red Jacket lode, at record bearing and dist.; there is no remaining evidence of the original cor., falls on a sheer granite face, where it is impracticable to establish a permanent monument.
	From this point, the point selected for the witness cor., to cor. No. 4, Red Jacket lode, bears N. 68°11′ E., O.18 chs. dist.
	Set an aluminum driver, 36 ins. long, 3/4 in. diam., 12 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with aluminum cap mkd.
	wc
	T14S R27E
	RJ S11 COR4 MS1072
	1997
	Cor. is located on a small bench, within a steep, rocky NW facing slope.
	S. 44°00′ W., on line 4-1, Red Jacket lode.
	Descending over mountainous land, across NNW facing slope, through dense undergrowth.
2.16	Intersect the line bet. secs. 10 and 11.
	From this point, the cor. of secs. 2, 3, 10 and 11, bears N. 0°03' E., 16.54 chs. dist., hereinbefore described.
9.09	Cor. No.1, Red Jacket lode.
	Dependent Resurvey of a Portion of Mineral Survey No. 3931, T. 14 S., R. 27 E., Gila and Salt River Meridian, Arizona
	Restoring the survey executed by John A. Rockfellow, in 1924

CHAINS

Protection lode

From cor. No. 1, Protection lode, determined by a scattered mound of stone, 4 ft. base, 1/2 ft. high. Cor. is identical with AP 9, sec. 15, of the metes-and-bounds survey of the Dos Cabezas Mountains Wilderness Area Bdy.

from which the original bearing objects

A rhyolite outcropping, 3 1/2 x 2 ft., bears S. 46°41′ W., 15.55 ft. dist., mkd. X BR 1-3931, on an exposed face.

A rhyolite boulder, $4 \times 3 \times 3 = 1/2$ ft. high, bears N. $37^{\circ}55'$ W., 8.25 ft. dist., mkd BXR 1-3931 on the E. face.

At the cor. point.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, encircled with a collar of stone, with brass cap mkd.

T14S R27E MS3931 S15 PRO DCMWA COR1 AP9

1997

Deposit a magnet in a white plastic case beneath the stainless steel post.

Cor. is located on a steep NNE facing slope.

From this cor. point, the 1/4 sec. cor. of secs. 15 and 22, bears S. $7^{\circ}54'$ W., 17.95 chs. dist., hereinbefore described.

N. 88°46′ W., on line 1-2, Protection lode, on the Dos Cabezas Mountains Wilderness Area Bdy.

Over mountainous land, through dense undergrowth, and moderate timber.

4.50 Point for AP 10, sec. 15, on the Dos Cabezas Mountains Wilderness Area Bdy., hereinafter described.

Leave the Dos Cabezas Mountains Wilderness Area Bdy.

CHAINS	
22.68	Cor. No. 2, Protection lode, determined by a scattered mound of stone, 2 ft. base, 2 ft. high.
	from which an original bearing object
	A rhyolite outcropping 2 1/2 x 2 1/2 ft., bears S. 77°57' E., 11.2 ft. dist., mkd. BR 39, no other marks visible.
	Cor. not remonumented
	N. 1°08' E., on line 2-3, Protection lode.
	Over mountainous land, through dense undergrowth, and moderate timber.
9.06	Cor. No. 3, Protection lode, determined by a scattered mound of stone, 3 1/2 ft. base, 1/2 ft. high.
	from which the original bearing objects
	A prominent rhyolite bluff, bears S. 41°14′ W., 5.45 ft. dist., mkd BXR 3-39 at base.
	A rhyolite bedrock, 24 ins. x 20 ins., bears N. 13°22′ W., 10.43 ft. dist., mkd. X BR 3-3931, on an exposed face.
	Cor. not remonumented
	S. 88°48' E., on line 3-4, Protection lode.
	Over mountainous land, through dense undergrowth, and moderate timber.
2.66	Intersect line 5-1, North End lode, point for AP 7, sec. 15, on the Dos Cabezas Mountains Wilderness Area Bdy., hereinafter described.
	Thence on the Dos Cabezas Mountains Wilderness Area Bdy.
22.68	Point for cor. No. 4, Protection lode, at record dist. from cor. No. 1, Protection lode and parallel with line 2-3, Protection lode; there is no remaining evidence of the original cor. Cor. is identical with AP 8, sec. 15, of the metes-and-bounds survey of the Dos Cabezas Wilderness Area Bdy.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to bedrock, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.

CHAINS

Deposit a magnet in a white plastic case beneath the stainless steel post.

S. 1°08′ W., on line 4-1, Protection lode, on the Dos Cabezas Mountains Wilderness Area Bdy.

Over mountainous land, through dense undergrowth, and moderate timber.

9.08

Cor. No. 1, Protection lode.

North End lode

From cor. No. 3, North End lode, monumented with a squared wood post, $48 \times 4 \times 4$ ins., firmly set, projecting 48 ins. above ground, in a supporting mound of stone, 5 ft. base, 2 ft. high, mkd. 3-3931 on the E. face and NWC on the S. face. Cor. is identical with AP 4, sec. 15, of the metes-and-bounds survey of the Dos Cabezas Mountains Wilderness Area Bdy.


from which the original bearing objects

- A rhyolite outcropping 7 x 3 x 1 ft. high, bears S. $47^{\circ}04'$ E., 15.65 ft. dist., mkd. X BR 3-3931 on the W. face.
- A rhyolite outcropping 2 $1/2 \times 2 \times 1 \cdot 1/2$ ft. high, bears S. $35^{\circ}06'$ W., 10.55 ft. dist., mkd. X BR 3-3931 on the exposed face.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, in a supporting mound of stone, 6 ft. base, to top, with brass cap mkd.

CHAINS



Deposit a magnet in a white plastic case beneath the stainless steel post.

Bury the wooden post alongside the stainless steel post.

From this cor. point, the 1/4 sec. cor. of secs. 15 and 16, bears S. 71°31′ W., 23.17 chs. dist., hereinbefore described.

S. 88°14′ E., on line 3-4, North End lode, on the Dos Cabezas Wilderness Area Bdy.

Over mountainous land, through moderate undergrowth.

4.53

Cor. No. 4, North End lode, determined by a scattered mound of stone, 1 ft. base, 1/2 ft. high, with the weathered remains of wood fragments within the scattered mound of stone. Cor. is identical with AP 5, sec. 15, of the metes-and-bounds survey of the Dos Cabezas Mountains Wilderness Area Bdy.


from which the remains of the original bearing trees

An oak stump, 24 ins. diam., bears N. 5°56' E., 24.17 ft. dist., mkd BXT 3931 on an open blaze.

A stumphole, bears S. 84°31′ W., 21.06 ft. dist., with a fallen oak alongside, with a rotted out blaze.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



Deposit a magnet in a white plastic case beneath the stainless steel post.

CHAINS

Bury the wood fragments alongside the stainless steel post.

S. 49°10' E., on line 4-5, North End lode, on the Dos Cabezas Wilderness Area Bdy.

Over mountainous land, through dense undergrowth, and moderate timber.

4.58

Cor. No. 5, North End lode, determined from the original bearing objects. Cor is identical with AP 6, sec. 15, of the metes-and-bounds survey of the Dos Cabezas Mountains Wilderness Area Bdy.


from which the original bearing tree and bearing object

An oak stump, 10 ins. diam., bears S. 17°14' E., 14.90 ft. dist., with illegible scribe marks on an open blaze.

A granite stone, 20 \times 12 \times 8 ins. high, bears N. 61°12′ W., 14.45 ft. dist., mkd X BR 3-3931, on the E. face.

At the cor. point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.



Deposit a magnet in a white plastic case beneath the stainless steel post.

S. 23°45′ W., on line 5-1, North End lode, on the Dos Cabezas Wilderness Area Bdy.


Over mountainous land, through dense undergrowth, and moderate timber.

18.26

Intersect line 3-4, Protection lode, point for AP 7, sec. 15, of the metes-and-bounds survey of the Dos Cabezas Wilderness Area Bdy.

CHAINS

Set an aluminum driver, 36 ins. long, 3/4 in. diam., 29 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.



From this cor. point, cor. No. 3, Protection lode, bears N. 88°48′ W., 2.66 chs. dist.

Leave the Dos Cabezas Mountains Wilderness Area Bdy.

21.24

Cor. No. 1, North End lode, identical with cor. No. 4, Sumpter lode, determined by a scattered mound of stone, 3 ft. base, 1/2 ft. high, with the weathered remains of wood fragments, within the scattered mound of stone.

from which the original bearing tree and bearing object

An oak 24 ins. diam., bears S. 56°58' E., 13.50 ft. dist., with a healed over blaze.

A diorite bluff, bears S. 77°28′ W., 15.07 ft. dist., with illegible marks, at base.

Cor. not remonumented.

The Metes-and-Bounds Survey of the
Dos Cabezas Mountains Wilderness Area Boundary,
T. 14 S., R. 27 E., Gila and Salt River Meridian, Arizona

From AP 1, sec. 2, identical with AP 4, sec. 35, T. 13 S., R. 27 E., on the N. bdy. of the Tp., monumented with an aluminum driver, 3/4 in. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd., T13S R27E S35 AP4 DCMWA S2 AP1 T14S 1997 as described in the field notes of the metes-and-bounds survey of the Dos Cabezas Mountains Wilderness Area Bdy., T. 13 S., R. 27 E., executed concurrently under this same group.

S. 21°16′ W., on line 1-2, sec. 2.

Over mountainous land, along a ridge line.

CHAINS	
15.91	Point for AP 2, sec. 2.
	Set an aluminum driver, 36 ins. long, 3/4 in. diam., 12 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with aluminum cap mkd.
	T14S R27E DCMWA S2 AP2
	1997
	S. 41°03′ W., on line 2-3, sec. 2.
	Over mountainous land, along a ridge line.
13.92	Point for AP 3, sec. 2.
	Set an aluminum driver, 36 ins. long, 3/4 in. diam., 8 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, 2 ft. high, with aluminum cap mkd.
	T14S R27E DCMWA S2 AP3
	1997
	S. 45°18' E., on line 3-4, sec. 2.
	Over mountainous land, along a ridge line.
13.04	Point for AP 4, sec. 2.
	Set an aluminum driver, 36 ins. long, 3/4 in. diam., 6 ins. in the ground, to bedrock, in a supporting mound of stone, 4 1/2 ft. base, to top, with aluminum cap mkd.
	T14S R27E
	S2 DCMWA AP4
	1997
	S. 27°30′ W., on line 4-5, sec. 2.
	Over mountainous land, along a ridge line.


CHAINS 13.58 Point for AP 5, sec. 2. Set an aluminum driver, 36 ins. long, 3/4 in. diam., 6 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, 2 ft. high, with aluminum cap mkd. T14S R27E **DCMWA S2** AP5 1997 S. 41°36' E., on line 5-6, sec. 2. Over mountainous land, along a ridge line. 6.14 Point for AP 6, sec. 2. Set an aluminum driver, 36 ins. long, 3/4 in. diam., 6 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, 2 1/2 ft. high, with aluminum cap mkd. T14S R27E **DCMWA** AP6 1997 S. 54°34′ W., on line 6-7, sec. 2. Over mountainous land, descend along SSW facing slope 25.20 Point for AP 7, sec. 2. Set an aluminum driver, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, to bedrock, in a mound of stone, 1 1/2 ft. base, 1 1/2 ft. high, with aluminum cap mkd. T14S R27E OCMWA AP7 **1**997 S. 48°34' W., on line 7-8, sec. 2. Over mountainous land.

CHAINS	
21.70	Point for AP 8, sec. 2.
	Set an aluminum driver, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, to bedrock, in a mound of stone, 1 1/2 ft. base, 1 1/2 ft. high, with aluminum cap mkd.
	T14S R27E
	S2 AP8
	1997
	S. 3°37′ W., on line 8-9, sec. 2.
	Over mountainous land.
1.98	Point for AP 9, sec. 2, identical with AP 1, sec. 11, on the line bet. secs. 2 and 11, not monumented.
	From this point, the cor. of secs. 2, 3, 10 and 11, bears S. 89°56′ W., 18.23 chs. dist., hereinbefore described.
	Sec. 11
	S. 3°37′ W., on line 1-2, sec. 11.
	Ascending over mountainous land.
15.90	Point for AP 2, sec. 11.
	Set an aluminum driver, 36 ins. long, 3/4 in. diam., 4 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with aluminum cap mkd.
	T14S R27E DCMWA S11 AP2
	1997
	Cor. is located on ridge top.
	S. 35°43′ W., on line 2-3, sec. 11.
	Over mountainous land, along a ridge line.

CHAINS 15.13 Point for AP 3, sec. 11, on line 3-4, Red Jacket lode, M.S. No. 1072. Set an aluminum driver, 36 ins. long, 3/4 in. diam., 29 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd. T14S R27E From this cor. point, the true point for cor. No. 4, Red Jacket lode, bears N. 27°41' W., 14.86 chs. dist., hereinbefore described. From the point for AP 6, sec. 11, on line 1-2, Red Jacket lode, M.S. No. 1072. Set an aluminum driver, 36 ins. long, 3/4 in. diam., 11 ins. in the ground, to bedrock, in a supporting mound of stone, 5 ft. base, to top, with aluminum cap mkd. T14S R27E MS1072 RJ 1997 From this cor. point, cor. No. 1, Red Jacket lode, bears N. 27°41′ W., 16.13 chs. dist., hereinbefore described. S. 33°14′ W., on line 6-7, sec. 11. Over mountainous land. 4.93 AP 7, sec. 11, identical with AP 1, sec. 10, and the 1/4 sec. cor. of secs. 10 and 11, hereinbefore described. Sec. 10 S. 38°01′ W., on line 1-2, sec. 10. Ascending over mountainous land. 9.28 Point for AP 2, sec. 10.

CHAINS

Set an aluminum driver, 36 ins. long, 3/4 in. diam., 12 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with aluminum cap mkd.




S. 88°32' W., on line 2-3, sec. 10.

Over mountainous land, along a ridge line.

10.43 | Point for AP 3, sec. 10.

Set an aluminum driver, 36 ins. long, 3/4 in. diam., 10 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, 2 ft. high, with aluminum cap mkd.




N. 62°48′ W., on line 3-4, sec. 10.

Over mountainous land, along a ridge line.

13.97 | Point for AP 4, sec. 10.

Set an aluminum driver, 36 ins. long, 3/4 in. diam., 13 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, 2 ft. high, with aluminum cap mkd.



S. 75°07' W., on line 4-5, sec. 10.

Over mountainous land, along a ridge line.

CHAINS	
4.69	Point for AP 5, sec. 10.
	Set an aluminum driver, 36 ins. long, 3/4 in. diam., 12 ins. in the ground, to bedrock, in a supporting mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, with aluminum cap mkd.
	T14S R27E S10
	AP5
	DCMWA 1997
	S. 35°19′ W., on line 5-6, sec. 10.
	Over mountainous land.
33.26	Point for AP 6, sec. 10.
	Set an aluminum driver, 36 ins. long, 3/4 in. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 3 1/2 ft. base, to top, with aluminum cap mkd.
	T14S R27E
	S10 AP6 DCMWA 1997
	S. 11°37′ W., on line 6-7, sec. 10.
	Over mountainous land.
10.64	Point for AP 7, sec. 10, identical with AP 1, sec. 15, on the line bet. secs. 10 and 15, not monumented.
	From this point, the 1/4 sec. cor. of secs. 10 and 15, bears N. 89°50' E., 14.72 chs. dist., hereinbefore described.
	Sec. 15
	S. 11°37′ W., on line 1-2, sec. 15.
	Over mountainous land.
17.18	Point for AP 2, sec. 15.

The Metes-and-Bounds Survey of the Dos Cabezas Mountains Wilderness Area Boundary,

T. 14 S., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

Set an aluminum driver, 36 ins. long, 3/4 in. diam., 27 ins. in the ground, to bedrock, in mound of stone, 4 ft. base, to top, with aluminum cap mkd.

S. 8°58' W., on line 2-3, sec. 15.

Over mountainous land.

18.34 | Point for AP 3, sec. 15.

Set an aluminum driver, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.




N. 48°15′ E., on line 3-4, sec. 15.

3.80

AP 4, sec. 15, identical with cor. No. 3, North End lode, M.S. No. 3931, hereinbefore described.

From the point for AP 10, sec. 15, on line 1-2, Protection lode, $M.S.\ No.\ 3931.$

Set an aluminum driver, 36 ins. long, 3/4 in. diam., 23 ins. in the ground, to bedrock, in a mound of stone, $2\ 1/2$ ft. base, to top, with aluminum cap mkd.



CHAINS	
	From this cor. point, cor. No. 2, Protection lode, M.S No. 3931, bears N. 88°46′ W., 18.18 chs. dist., hereinbefore described.
	S. 29°15′ W., on line 10-11, sec. 15.
	Over mountainous land, ascending.
6.40	Point for AP 11, sec. 15.
	Set an aluminum driver, 36 ins. long, 3/4 in. diam., 11 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, 2 1/2 ft. high, with aluminum cap mkd.
	T14S R27E
	S15 AP11
	DCMWA 1997
	Cor. is located on top of Cooper peak.
	S. 27°02' E., on line 11-12, sec. 15.
	Over mountainous land, descending.
13.81	Point for AP 12, sec. 15, identical with AP 1, sec. 22, on the line bet. secs. 15 and 22, not monumented.
	From this point, the 1/4 sec. cor. of secs. 15 and 22, bears N. 89°43′ W., 1.12 chs. dist., hereinbefore described.
	Sec. 22
	S. 27°02' E., on line 1-2, sec. 22.
	Over mountainous land, descending.
7.00	Point for AP 2, sec. 22.
	Set an aluminum driver, 36 ins. long, 3/4 in. diam., 12 ins. in the ground, to bedrock, in a supporting mound of stone, 3 1/2 ft. base, to top, with aluminum cap mkd.

CHAINS	
	T14S R27E DCMWA AP2
	S22
	1997
	S. 60°39' E., on line 2-3, sec. 22.
	Over mountainous land, descending.
12.45	Point for AP 3, sec. 22.
	Set an aluminum driver, 36 ins. long, 3/4 in. diam., 9 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with aluminum cap mkd.
	T14S R27E DCMWA AP3
·	\$22 1997
	S. 68°00′ E., on line 3-4, sec. 22.
	Over mountainous land, descending.
15.62	Point for AP 4, sec. 22.
	Set an aluminum driver, 36 ins. long, 3/4 in. diam., 18 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with aluminum cap mkd.
	T14S R27E
	DCMWA AP4
	1997
	S. 69°53′ E., on line 4-5, sec. 22.
	Over mountainous land, descending.
11.10	Point for AP 5, sec. 22, identical with AP 1, sec. 23, on the line bet. secs. 22 and 23, not monumented.

CHAINS	
	From this point, the 1/4 sec. cor. of secs. 22 and 23, bears South, 18.22 chs. dist., hereinbefore described.
	Sec. 23
	S. 69°53' E., on line 1-2, sec. 23.
	Over mountainous land, along ridge.
5.91	Point for AP 2, sec. 23.
	Set an aluminum driver, 36 ins. long, 3/4 in. diam., 22 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with aluminum cap mkd.
	T14S R27E DCMWA AP2
	S23 1997
	S. 56°11′ E., on line 2-3, sec. 23.
	Over mountainous land.
36.56	Point for AP 3, sec. 23.
	Set an aluminum driver, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.
	T14S R27E DCMWA AP3
	S23 1997
	S. 72°30' E., on line 3-4, sec. 23.
	Over mountainous land.
34.15	Point for AP 4, sec. 23.
	Set an aluminum driver, 36 ins. long, 3/4 in. diam., 13 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with aluminum cap mkd.
L	1

CHAINS T14S R27E **DCMWA** 1997 Cor. is located on top of Howards Peak. S. 20°56' W., on line 4-5, sec. 23. Desc. over mountainous land. Point for AP 5, sec. 23. 21.89 Set an aluminum driver, 36 ins. long, 3/4 in. diam., 9 ins. in the ground, to bedrock, in a supporting mound of stone, 3 1/2 ft. base, to top, with aluminum cap mkd. T14S R27E DCMWA S23 AP5 1997 S. 73°40' E., on line 5-6, sec. 23. Desc. over mountainous land. 19.62 AP 6, sec. 23, identical with the cor. of secs. 23 and 24 only, hereinbefore described. General Description The area encompassed by this survey is located about 8 miles SSW of Bowie, Arizona. The terrain consists of steep, rocky mountainous land, with dense stands of mountain mahogany, scrub oak and alligator juniper. Access is by way of Arizona State Highway Number 186.

T. 14 S., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

Description of the Dos Cabezas Mountains Wilderness Area Bdy. T. 14 S., R. 27 E., Gila and Salt River Meridian, Arizona

The following is for informational purposes only.

```
Beginning at Angle Point 1, sec. 2, identical with Angle Point 4, sec. 35, T. 13 S., R. 27 E., on the N. bdy. of the Tp.

thence S. 21°16′ W., 15.91 chs. dist., to Angle Point 2, sec. 2;
```

```
thence S. 41°03′ W., 13.92 chs. dist., to Angle Point 3, sec. 2; thence S. 45°18′ E., 13.04 chs. dist., to Angle Point 4, sec. 2; thence S. 27°30′ W., 13.58 chs. dist., to Angle Point 5, sec. 2; thence S. 41°36′ E., 6.14 chs. dist., to Angle Point 6, sec. 2; thence S. 54°34′ W., 25.20 chs. dist., to Angle Point 7, sec. 2; thence S. 48°34′ W., 21.70 chs. dist., to Angle Point 8, sec. 2; thence S. 3°37′ W., 1.98 chs. dist., to Angle Point 9, sec. 2, identical with Angle Point 1, sec. 11, on the line bet. secs. 2 and 11;
```

thence S. 3°37′ W., 15.90 chs. dist., to Angle Point 2, sec. 11; thence S. 35°43′ W., 15.13 chs. dist., to Angle Point 3, sec. 11, on line 3-4, Red Jacket Lode, Mineral Survey No. 1072;

thence S. 27°41' E., on line 4-3, Red Jacket lode, Mineral Survey No. 1072, 7.72 chs. dist., to Angle Point 4, sec. 11, identical with cor. No. 3, Red Jacket lode;

thence S. 44°00′ W., on line 3-2, Red Jacket lode, Mineral Survey No. 1072, 9.09 chs. dist., to Angle Point 5, sec. 11, identical with cor. No. 2, Red Jacket lode;

thence N. 27°41′ W., on line 2-1, Red Jacket lode, Mineral Survey No. 1072, 6.45 chs. dist., to Angle Point 6, sec. 11;

thence S. 33°14′ W., 4.93 chs. dist., to Angle Point 7, sec. 11, identical with Angle Point 1, sec. 10, and the 1/4 sec. cor. of secs. 10 and 11;

thence S. 38°01′ W., 9.28 chs. dist., to Angle Point 2, sec. 10; thence S. 88°32′ W., 10.43 chs. dist., to Angle Point 3, sec. 10; thence N. 62°48′ W., 13.97 chs. dist., to Angle Point 4, sec. 10; thence S. 75°07′ W., 4.69 chs. dist., to Angle Point 5, sec. 10; thence S. 35°19′ W., 33.26 chs. dist., to Angle Point 6, sec. 10; thence S. 11°37′ W., 10.64 chs. dist., to Angle Point 7, sec. 10, identical with Angle Point 1, sec. 15, on the line bet. secs. 10 and 15;

thence S. 11°37′ W., 17.18 chs. dist., to Angle Point 2, sec. 15; thence S. 8°58′ W., 18.34 chs. dist., to Angle Point 3, sec. 15; thence N. 48°15′ E., 3.80 chs. dist., to Angle Point 4, sec. 15, identical with cor. No. 3, North End lode, Mineral Survey No. 3931;

thence S. 88°14′ E., on line 3-4, North End lode, Mineral Survey No. 3931, 4.53 chs. dist., to Angle Point 5, sec. 15, identical with cor. No. 4, North End lode;

T. 14 S., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS thence S. 49°10' E., on line 4-5, North End lode, Mineral Survey No. 3931, 4.58 chs. dist., to Angle Point 6, sec. 15, identical with cor. No. 5, North End lode; thence S. 23°45′ W., on line 5-1, North End lode, Mineral Survey No. 3931, 18.26 chs. dist., to Angle Point 7, sec. 15, at intersection with line 3-4, Protection lode, Mineral Survey No. 3931; thence S. 88°48' E., on line 3-4, Protection lode, Mineral Survey No. 3931, 20.02 chs. dist., to Angle Point 8, sec. 15, identical with cor. No. 4, Protection lode. thence S. 1°08' W., on line 4-1, Protection lode, Mineral Survey No. 3931, 9.08 chs. dist., to Angle Point 9, sec. 15, identical with cor. No. 1, Protection lode; thence N. 88°46′ W., on line 1-2, Protection lode, Mineral Survey No. 3931, 4.50 chs. dist., to Angle Point 10, sec. 15; thence S. 29°15' W., 6.40 chs. dist., to Angle Point 11, sec. 15; thence S. 27°02′ E., 13.81 chs. dist., to Angle Point 12, sec. 15, identical with Angle Point 1, sec. 22, on the line bet. secs. 15 and 22; thence S. 27°02' E., 7.00 chs. dist., to Angle Point 2, sec. 22; thence S. 60°39' E., 12.45 chs. dist., to Angle Point 3, sec. 22; thence S. 68°00' E., 15.62 chs. dist., to Angle Point 4, sec. 22; thence S. 69°53' E., 11.10 chs. dist., to Angle Point 5, sec. 22; identical with Angle Point 1, sec. 23, on the line bet. secs. 22 and 23. thence S. 69°53' E., 5.91 chs. dist., to Angle Point 2, sec. 23; thence S. 56°11' E., 36.56 chs. dist., to Angle Point 3, sec. 23; thence S. 72°30' E., 34.15 chs. dist., to Angle Point 4, sec. 23; thence S. 20°56' W., 21.89 chs. dist., to Angle Point 5, sec. 23; thence S. 73°40' E., 19.62 chs. dist., to Angle Point 6, sec. 23, identical with the cor. of secs. 23 and 24 only. thence S. 89°14' E., on the N. bdy. of sec. 26, 0.62 ch., dist. to the cor. of secs. 25 and 26 only. thence N. 89°59' E., on the N. bdy. of sec. 25, 79.22 chs., dist. to the cor. of secs. 24 and 25 only, identical with Angle Point 1, sec. 30, T. 14 S., R. 28 E., on the E. bdy. of the Tp.

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Cheryl A. Baier	Surveying Technician
Geoffrey A. Graham	Surveying Technician
Robert J. Lyle	Surveying Technician
Mark R. Searles	Surveying Technician

CERTIFICATE OF SURVEY

I, Gordon R. Bubel, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 20th day of October, 1994, I have dependently resurveyed a portion of the subdivisional lines, Mineral Survey Number 1072, and a portion of Mineral Survey Number 3931, and performed the metes-and-bounds survey of the Dos Cabezas Mountains Wilderness Area Boundary, in Township 14 South, Range 27 East, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

AUGUST 30,1998	Mh R Bibel
(Date)	(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Arizona State Office Phoenix, Arizona

1

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines, Mineral Survey Number 1072, and a portion of Mineral Survey Number 3931, and the metes-and-bounds survey of the Dos Cabezas Mountains Wilderness Area Boundary, in Township 14 South, Range 27 East, Gila and Salt River Meridian, Arizona, executed by Gordon R. Bubel, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

October 26, 1998	Tenny I Ravnikar
(Date)	(Chief Cadastral Surveyor of Arizona)
- CE	RTIFICATE OF TRANSCRIPT
	nscript of the field notes of the above-described ila and Salt River Meridian, Arizona, is a true copy
(Date)	(Chief Cadastral Surveyor of Arizona)