

ORIGINAL

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

A PORTION OF THE EAST BOUNDARY

AND A PORTION OF THE SUBDIVISIONAL LINES

AND THE SUBDIVISION OF

SECTIONS 13, 14, 24, 26 AND 27,

TOWNSHIP 9 NORTH, RANGE 2 EAST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA.

EXECUTED BY

Stephen K. Hansen, Cadastral Surveyor

Under Special Instructions dated January 11, 2001, approved January 11, 2001, which provided for the surveys included under Group No. 861, and assignment instructions dated January 11, 2001.

Survey commenced January 16, 2001

Survey completed March 6, 2001

INDEX DIAGRAM

TOWNSHIP 9 NORTH RANGE 2 EAST

6	5	4	3	2	1
7	8	9	10	11 15	12 10 ⁴
18	17	16	15	14 14 13	9 13 3 9
19	20	21	22 18	23 13	8 24 2 7
30	29	28	17 27 15	12 26 11	5 25
31	32	33	34	35	36

Subdivision of Section 13	Pages 19-22
Subdivision of Section 14	Pages 22-23
Subdivision of Section 24	Pages 23-27
Subdivision of Section 26	Pages 27-28
Subdivision of Section 27	Pages 28-33

T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the east boundary and a portion of the subdivisional lines and the subdivision of sections 13, 14, 24, 26 and 27, T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this resurvey is as follows:

Alfred N. Oliver surveyed the 2nd Stan. Par. N. through R. 2 E. (S. Bdy.) and a portion of the subdivisional lines in 1910. Sidney E. Blout surveyed a portion of the east boundary and a portion of the subdivisional lines in 1913. Geo F. Rigby surveyed a portion of the subdivisional lines in 1917.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated January 11, 2001, for Group No. 861, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 4400 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from second order U. S. Coast and Geodetic Survey triangulation station MAGGIE 1958, as published by the National Geodetic Survey, NAD 83 (1992). The geographic position of the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., is as follows:

Latitude: 34° 05' 57.35" N. Longitude: 112° 05' 55.40" W.

The mean magnetic declination is 12¼° E.

**Dependent Resurvey of a Portion of the East Boundary,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona**

Restoring the survey executed by
Sidney E. Blout, in 1913

Dependent Resurvey of a Portion of the East Boundary,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Beginning at the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 20 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. T9N R2E R3E S24 S19 S25 S30 1913.</p> <p>Add the marks 2001 to the brass cap.</p> <p>N. 0°01' W., bet. secs. 19 and 24, on the E. bdy. of the Tp.</p> <p>Asc. over rocky mountainous land through scattering palo verde.</p>
19.99	<p>Point for the S. 1/16 sec. cor. of secs. 19 and 24. Not monumented.</p>
39.98	<p>The 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., 36 ins. long, firmly set, projecting 20 ins. above ground, bent badly at the base, with brass cap mkd. S24 1/4 S19 1913.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R2E R3E 1/4 S24 S19 2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Remove the orig. iron post from the area, impracticable to bury.</p> <p>Cor. is located 12 lks. E. of a woven wire fence, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>North, beginning new measurement.</p>
39.98	<p>The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T9N R2E R3E S13 S18 S24 S19 1913.</p> <p>Add the marks 2001 to the brass cap.</p>

Dependent Resurvey of a Portion of the East Boundary,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor. point, the center top of a dog's headstone, 15 x 6 ins., mkd. SNIPPER 1977-1989 "IF WE ONLY LOVED OUR GOD LIKE HE LOVED HIS", bears S. 7° E., 0.28 ch. dist.</p> <hr/> <p>N. 0°03' E., bet. secs. 13 and 18.</p> <p>Over rolling rocky bottomland through thick undergrowth.</p>
19.98	<p>True point for the S. 1/16 sec. cor. of secs. 13 and 18, falls in the left main channel of the Agua Fria River, 2 chs. wide, 3 ft. deep, course S. 50° E., where it is impracticable to establish a permanent monument.</p> <p>From this point, the point selected for a witness cor. to the S. 1/16 sec. cor. of secs. 13 and 18, bears N. 82°03' W., 2.03 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>W C T9N R2E R3E S 1/16 → S13 S18 2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>This off line witness cor. falls on private property. Permission was granted by the owner to establish a monument.</p>
39.96	<p>The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with a mound of stone, 3 ft. base, 1 ft. high, to the W., with brass cap mkd. S13 1/4 S18 1913.</p> <p>Add the marks T9N R2E R3E 2001 to the brass cap, and raise a mound of stone, 3 ft. base, to top, around the iron post.</p> <p>Cor. is located on the S. bank of a wash, 8 lks. wide, 2 ft. deep, drains N. 60° E.</p> <hr style="width: 20%; margin: 10px auto;"/>
20.01	<p>N. 0°02' E., beginning new measurement.</p> <p>Point for the N. 1/16 sec. cor. of secs. 13 and 18.</p>

**Dependent Resurvey of a Portion of the East Boundary,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a brass tablet, 3½ ins. diam., 3½ ins. stem., in a drill hole, and in concrete, on the top face of a rock outcropping, 20 x 5 x 2 ft. high, with brass cap mkd.</p> <p style="text-align: center;">T9N R2E R3E N 1/16 S13 S18 2001</p> <p>From this cor. point, a rebar, origin unknown, ½ in. diam., firmly set, projecting 3 ins. above ground, bears N. 10° E., 0.015 ch. dist., with a steel fence post set firmly alongside.</p>
38.02	<p>The witness cor. for the cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 3 ins. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 3 ft. base, to top, with a mound of stone, 3 ft. base, 1 ft. high, to the W., with brass cap mkd. WC T9N R2E R3E S12 S7 S13 S18 1913.</p> <p>Add the marks 2001 to the brass cap.</p> <hr/> <p>N. 0°02' W., beginning new measurement.</p>
2.00	<p>True point for the cor. of secs. 7, 12, 13 and 18, falls in the rocky bed of the Aqua Fria River, 2 chs. wide, course S. 40° E., where it is impracticable to establish a permanent monument.</p> <hr/> <p>N. 0°02' W., bet. secs. 7 and 12.</p> <p>Over rocky land through thick river undergrowth.</p>
40.06	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, to the W., with brass cap mkd. S12 1/4 S7 1913.</p> <p>Add the marks T9N R2E R3E 2001 to the brass cap.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivisional Lines, T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Restoring the surveys executed by Alfred N. Oliver, in 1910, Sydney E. Blout, in 1913, and Geo F. Rigby, in 1917</p> <hr/>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS

From the cor. of secs. 25, 26, 35 and 36, determined from local monumentation as recovered by Gary Collins, RLS 07335 under the direction of Joseph B. Sarvis, County Engineer, in 1971, and recorded in 1976, as shown on Book 2 of Land Surveys, Page 52, Yavapai County Recorder, Prescott, Arizona. Mr. Collins recovered the orig. stone in 1971 and established new accessories. Additional monumentation was also recovered and new monumentation established on the adjoining section and subdivision of section lines in 1971. This position was again utilized in 1985 by Collins, as shown on Book 4 of Land Surveys, Page 68, Yavapai County Recorder, Prescott, Arizona. Because of a sand and gravel operation in the area, no remains of the stone or Collins accessories were recovered during the course of this survey. Collins local monumentation, hereinafter described, was used to determine this cor. position which is harmoniously related to the General Land Office record, private survey records, and occupation lines; and is accepted as the best attainable evidence of the orig. cor. position.

Because this position is still subject to destruction and is surrounded by private land, no permanent monument was established.

From this point, a rebar, $\frac{5}{8}$ in. diam, firmly set, 4 ins. below ground, with affixed plastic cap mkd. LS 24522, bears S. 48° W., 9 lks. dist. The record of the survey that established this rebar in 1999, is filed at the Yavapai County Recorder in Book 47 of Land Surveys, Page 54. This survey apparently ignored or was unaware of previous recorded surveys that would have determined the orig. position of the cor. with more certainty. It is for these reasons that this monument was not utilized as the true cor. position during the course of this survey.

From this same cor point, a rebar as recovered in a 1999 private survey, $\frac{1}{2}$ in. diam., firmly set, projecting 1 in. above ground, bears S. $0^{\circ}08'$ W., 20.07 chs. dist.

From this same cor. point, the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, monumented with a malpais stone, 8 x 6 ins., firmly set, projecting 6 ins. above ground, at the bottom of a mound of stone, 3 ft. base, 2 ft. high, with the marks $\frac{1}{4}$ chiseled on the W. face, bears S. $0^{\circ}08'$ W., 40.14 chs. dist., from which accessories established in 1971, by Gary Collins, RLS 07335, and recorded by Joseph B. Sarvis, County Engineer, in 1976, as shown in Book 2 of Land Surveys, Page 52, Yavapai County Recorder, Prescott, Arizona

A malpais stone, 10 x 12 ins., firmly set, projecting 8 ins. above ground, with an "X" chiseled on the top, and "BO" chiseled on the N. face, bears S. $70\frac{3}{4}^{\circ}$ E., 8 lks. dist.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A malpais stone, 30 x 12 ins, firmly set, projecting 18 ins. above ground, with a concrete nail set in the top, bears S. $3\frac{1}{4}^{\circ}$ W., 55 lks. dist.</p> <p>A malpais stone, 36 x 24 ins., firmly set, projecting 24 ins. above ground with a concrete nail set in the top, bears N. $36\frac{1}{4}^{\circ}$ W., 54 lks. dist.</p> <p>Cor. is located on W. bank of a wash, 2 chs. wide, 15 ft. deep, drains N. 40° W.</p> <p>From this same point, the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. S25 $\frac{1}{4}$ S36 1913, bears S. $89^{\circ}50'$ E., 39.98 chs. dist.</p> <p>Add the marks T9N R2E 2001 to the brass cap.</p> <p>Cor. is located 15 lks. E. of an improved dirt road, 20 ft. wide, bears N. 10° E. and S. 40° W. on a curve to the right.</p> <p>N. $0^{\circ}08'$ W., bet. secs. 25 and 26.</p> <p>Asc. from the Aqua Fria flood plain over rocky ground through scattering undergrowth.</p>
19.985	<p>An open ended iron pipe as recovered in a 1985 private survey, 1 in. diam., firmly set, projecting 1 in. above ground.</p> <p>Pipe is located $1\frac{1}{2}$ lks. E. of a chain link fence, bears N. and S., and 3 lks S. of a 4 strand barbed wire fence, bears E.</p>
39.97	<p>The $\frac{1}{4}$ sec. cor. of secs. 25 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. $\frac{1}{4}$ S26 S25 1913.</p> <p>Add the marks T9N R2E 2001 to the brass cap.</p> <p>Cor. is located 3 lks. SW of a wooden fence post, 5 ins. diam., with 4 strand barbed wire fence lines extending S. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $0^{\circ}06'$ W., beginning new measurement.</p>
40.06	<p>The cor. of secs. 23, 24, 25 and 26, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, to the W., with brass cap mkd. T9N R2E S23 S24 S26 S25 1913.</p> <p>Add the marks 2001 to the brass cap.</p> <hr style="width: 80%; margin: 10px auto;"/>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°43' W., bet. secs. 24 and 25.</p> <p>Asc. over mountainous land through scattering palo verde.</p> <p>20.00 The E. 1/16 sec. cor. of secs. 24 and 25, monumented with a rebar, ½ in. diam., 16 ins. long, firmly set, projecting 12 ins. above ground, with affixed yellow plastic cap mkd. HOPPS RLS 13011. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R2E</p> <p>S24</p> <p>E 1/16 ———</p> <p>S25</p> <p>2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and deposit the rebar inside of the stainless steel post.</p> <hr style="width: 30%; margin: auto;"/> <p>N. 89°43' W., beginning new measurement.</p>
16.47	<p>The witness cor. for the 1/4 sec. cor. of secs. 24 and 25, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. WC T9N S24 1/4 S25 R2E 1913.</p> <p>Add the marks 2001 to the brass cap.</p> <hr style="width: 30%; margin: auto;"/> <p>N. 89°42' W., beginning new measurement.</p>
3.53	<p>True point for the 1/4 sec. cor. of secs. 24 and 25, established by Gary Collins, RLS 07335, in 1985, monumented with a rebar, ⅝ in. diam., firmly set, projecting 4 ins. above ground, in a collar of stone, with affixed metal washer stamped 7335, falls in the Aqua Fria River, 4 chs. wide, drains S. 60° W. where it is impracticable to establish a more durable monument. This is accepted as a careful and faithful establishment of the cor. position.</p> <hr style="width: 30%; margin: auto;"/>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.04	<p>N. 89°42' W., beginning new measurement.</p> <p>The W. 1/16 sec. cor. of secs. 24 and 25, established by Gary Collins, RLS 07335, in 1985, monumented with a rebar, 5/8 in. diam., 24 ins. long, firmly set, projecting 1 in. above ground, with affixed metal washer stamped RLS 7335. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the cor. point.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R2E</p> <p>S24</p> <p>W 1/16 ———</p> <p>S25</p> <p>2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and deposit the rebar inside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/>
20.04	<p>N. 89°42' W., beginning new measurement.</p> <p>The cor. of secs. 23, 24, 25 and 26.</p> <hr/>
	<p>N. 0°11' W., bet. secs. 23 and 24.</p> <p>Over mountainous land through scattering palo verde and cacti.</p>
20.085	<p>Point for the S. 1/16 sec. cor. of secs. 23 and 24. Not monumented.</p>
40.17	<p>The 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. S23 1/4 S24 1913.</p> <p>Add the marks T9N R2E 2001 to the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/>
39.75	<p>N. 0°07' W., beginning new measurement.</p> <p>The cor. of secs. 13, 14, 23 and 24, monumented with an iron post, 2 ins. diam., loosely set, projecting 11 ins. above ground, with brass cap mkd. T9N R2E S14 S13 S23 S24 1913.</p> <p>At the cor. point</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.10	<p>Reset the iron post, 36 ins. long, 2 ins. diam., 15 ins. in the ground, in a supporting mound of stone, 4½ ft. base, to top.</p> <p>Add the marks 2001 to the brass cap.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°42' W., bet. secs. 13 and 24.</p> <p>Over rolling sandy bottom land through mesquite and palo verde.</p> <p>The E. 1/16 sec. cor. of secs. 13 and 24, established by Donald O. Flahart, RLS 08899, in 1998. monumented with a rebar, 5/8 in. diam., 17 ins. long, firmly set, projecting 2 ins. above ground, with affixed yellow plastic cap mkd. AZ LS 8899, with a steel fence post set firmly alongside. This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R2E</p> <p>S13</p> <p>E 1/16 ———</p> <p>S24</p> <p>2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and deposit the local rebar inside the stainless steel post.</p> <hr/>
20.10	<p>N. 89°42' W., beginning new measurement.</p> <p>The 1/4 sec. cor. of secs. 13 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with a mound of stone, 2 ft. base, 1 ft. high, to the N., with brass cap mkd. S13 1/4 S24 1913.</p> <p>Add the marks T9N R2E 2001 to the brass cap.</p> <hr/>
40.07	<p>N. 89°46' W., beginning new measurement.</p> <p>The cor. of secs. 13, 14, 23, and 24.</p> <hr/> <p>N. 0°01' W., bet. secs. 13 and 14.</p>


**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rocky mesa land through creosote and cacti.
40.02	<p>The 1/4 sec. cor. of secs. 13 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. S14 1/4 S13 1913.</p> <p>Add the marks T9N R2E 2001 to the brass cap.</p> <hr/> <p>North, beginning new measurement.</p>
20.00	Point for the N. 1/16 sec. cor. of secs. 13 and 14. Not monumented.
40.00	<p>The cor. of secs. 11, 12, 13 and 14, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. T9N R2E S11 S12 S14 S13 1913.</p> <p>Add the marks 2001 to the brass cap.</p> <hr/> <p>From the true point for the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°41' W., bet. secs. 12 and 13.</p> <p>Over rocky land through desert undergrowth.</p>
20.07	<p>Point for the E. 1/16 sec. cor. of secs. 12 and 13, falls in the right channel of the Aqua Fria River, on the S. face of a boulder, 5 x 5 x 3 ft., where it is impracticable to establish a durable monument.</p> <p>Chisel an "X" on the S. face of the boulder.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for a reference monument, bears N. 37°52' E., 196.0 ft. dist., with brass cap mkd. RM T9N R2E 1/16 196 FT TO COR S12 2001 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
40.14	<p>The 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, to the N., with brass cap mkd. S12 1/4 S13 1913.</p> <p>Add the marks T9N R2E 2001 to the brass cap.</p> <hr/>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 89°45' W., beginning new measurement.
20.09	Point for the W. 1/16 sec. cor. of secs. 12 and 13. Not monumented.
40.18	The cor. of secs. 11, 12, 13 and 14.
	From the cor. of secs. 25, 26, 35 and 36.
	N. 89°59' W., bet. secs. 26 and 35.
	Along the rocky and disturbed bed of the Aqua Fria River.
20.06	Point for the E. 1/16 sec. cor. of secs. 26 and 35. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <p>T9N R2E S26 E 1/16 ——— S35 2001</p> </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	From this cor. point, a rebar, ½ in. diam., firmly set, projecting 1 in. above ground, with affixed yellow plastic cap mkd. LS 24522, bears S. 33°30' W., 0.055 ch. dist.
21.20	An open end iron pipe as recovered in a 1971 private survey, ¾ in. diam., firmly set in concrete, projecting 6 ins. above ground.
40.12	True point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate dist; there is no remaining evidence of the orig. witness cor., falls in the main channel of the Aqua Fria River, 1 ch. wide, 2 ft. deep, running water in spring and winter, boulder strewn, where it is impracticable to establish a durable monument. From this point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 26 and 35, bears N. 3°11' E., 3.36 chs. dist.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<div style="text-align: center;">  <p>W C T9N R2E S26 1/4 ——— S35 2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From the true cor. point, a rebar, $\frac{1}{2}$ in. diam., firmly set, 3 ins. below ground, bears S. $0^{\circ}06'$ W., 20.04 chs. dist., a PK nail, with cotton spindles, firmly set, bearing N., E. and W., 2 ft. dist from this nail, bears S. $0^{\circ}06'$ W., 40.08 chs. dist. and the stan. $\frac{1}{4}$ sec. cor. of sec. 35, on the S. bdy. of the Tp., monumented with a volcanic stone, 6 x 8 ins., firmly set, projecting 7 ins. above ground, with a mound of stone, 3 ft. base, 1 ft. high, to the W., mkd. $\frac{1}{4}$ on the N. face, bears S. $0^{\circ}06'$ W., 80.20 chs. dist.</p> <p>49.37 From this point, a rebar as recovered in a 1971 private survey, $\frac{5}{8}$ in. diam., firmly set in concrete, projecting 1 in. above ground, bears North, 0.005 ch. dist.</p> <p>60.18 A rebar, origin unknown, $\frac{1}{2}$ in. diam., firmly set, 2 ins. below ground, in the E. bound land of improved dirt road, 20 ft. wide, bears irregularly E. and W.</p> <p>80.24 The cor. of secs. 26, 27, 34 and 35, perpetuated by Gary Collins, RLS 07335, in 1971, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 14 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. YAVAPAI COUNTY T9N R2E S27 S26 S34 S35 1971, from which an orig. bearing tree</p> <p style="padding-left: 40px;">A mesquite stump, 18 ins. diam., projecting 12 ins. above ground, bears N. $59\frac{1}{2}^{\circ}$ E., 130 lks. dist.</p> <p>and an accessory established by Collins</p> <p style="padding-left: 40px;">A rock outcrop, 10 x 3 x 2 ft. high, with a PK nail set through an illegible yellow plastic cap, bears S. $16\frac{3}{4}^{\circ}$ E., 68 lks. dist.</p> <p>This is accepted as a careful and faithful perpetuation of the orig. cor. position.</p> <hr/> <p>N. $0^{\circ}08'$ W., bet. secs. 26 and 27.</p> <p>Desc. over mountainous terrain through scattering mesquite, palo verde, and cacti.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.58	<p>The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 3½ ft. base, to top, with brass cap mkd. S27 1/4 S26 1913.</p> <p>Add the marks T9N R2E 2001 to the brass cap.</p> <hr/> <p>N. 0°03' E., beginning new measurement.</p>
40.50	<p>The cor. of sec. 22, 23, 26 and 27, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with a mound of stone, 2½ ft. base, 1 ft. high, to the W., with brass cap mkd. T9N R2E S22 S23 S27 S26 1913.</p> <p>Add the marks 2001 to the brass cap.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°56' W., bet. secs. 23 and 26.</p> <p>Over mountainous land through scattering palo verde.</p>
40.01	<p>The 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, to the N., with brass cap mkd. S23 1/4 S26 1913.</p> <p>Add the marks T9N R2E 2001 to the brass cap, and raise a mound of stone, 3 ft. base, to top, around the iron post.</p> <hr/> <p>N. 89°56' W., beginning new measurement.</p>
40.10	<p>The cor. of secs. 22, 23, 26 and 27.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°58' W., bet. secs. 14 and 23.</p> <p>Over mountainous land through creosote and cacti.</p>
39.96	<p>The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, to the N., with brass cap mkd. 1/4 S14 S23 1917.</p> <p>Add the marks T9N R2E 2001 to the brass cap, and raise a mound of stone, 3 ft. base, to top, around the iron post.</p> <hr/>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS	
	West, beginning new measurement.
19.98	<p>Point for the W. 1/16 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T9N R2E S14 W 1/16 ——— S23 2001</p>
39.96	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, in a collar of stone, with a mound of stone, 2½ ft. base, 1 ft. high, to the N., with brass cap mkd. T9N R2E S15 S14 S22 S23 1917.</p> <p>Add the marks 2001 to the brass cap.</p>
	<p>N. 0°03' W., bet. secs. 14 and 15.</p> <p>Over mountainous land, through creosote and cacti.</p>
19.99	<p>Point for the S. 1/16 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 3 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T9N R2E S 1/16 S15 S14 2001</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located at the head of a wash, near a trickling desert spring, in thick riparian undergrowth, drains S. 40° W.</p>
39.98	<p>The 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. 1/4 S15 S14 1917.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Add the marks T9N R2E 2001 to the brass cap, and raise a mound of stone, 3 ft. base, to top, around the iron post.</p> <hr/> <p>N. 0°02' W., beginning new measurement.</p>
39.99	<p>The cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with a mound of stone, 3 ft. base, 1 ft. high, to the W., with brass cap mkd. T9N R2E S10 S11 S14 S15 1917.</p> <p>Add the marks 2001 to the brass cap.</p> <hr/>
	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89°58' W., bet. secs. 11 and 14.</p> <p>Over rolling mesa land through scattering undergrowth.</p>
39.99	<p>The 1/4 sec. cor. of secs. 11 and 14, monumented with the rusted remains of the base of the original iron post, 1 in. diam., 4 ins. long, firmly set, 14 ins. below the surface of the ground. The remaining portion of the iron post, 1 in. diam, 32 ins. long, was found lying loosely on the surface of the ground, with brass cap mkd. 1/4 S11 S14 1917.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R2E S11 1/4 ——— S14 2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and deposit the orig. iron post inside of the stainless steel post.</p> <hr/>
39.97	<p>S. 89°58' W., beginning new measurement.</p> <p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/>
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°57' W., bet. secs. 27 and 34.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling rocky land through scattering palo verde and cacti.
32.40	Center line of Coldwater Canyon Road, paved, 30 ft. wide, bears S. 70° E. on a curve to the right, and N. 80° W.
40.12	<p>The 1/4 sec. cor. of secs. 27 and 34, identical with an easterly right-of-way monument for Interstate 17, monumented with a brass cap, 3 ins. diam., firmly set, in a concrete cylinder, 6 ins. diam., projecting 12 ins. above ground, with brass cap mkd. 2074+07 1964. Arizona Department of Transportation perpetuated this cor. position in 1964, according to the Right-of-Way plan of the Phoenix - Cordes Junction State Highway Project No. I-17-1(29)22, copies of which are on file at ADOT, Phoenix, AZ. This is accepted as a careful and faithful perpetuation of the orig. cor. position from which other ADOT right-of-way monuments.</p> <p style="padding-left: 40px;">A brass cap, 3 ins. diam., firmly set, in a concrete cylinder, 6 ins. diam., projecting 12 ins. above ground, with brass cap mkd. 2073 + 88 1964 bears S. 1°32' W., 61 lks. dist.</p> <p style="padding-left: 40px;">A brass cap, 3 ins. diam., firmly set, in a concrete cylinder, 6 ins. diam., projecting 12 ins. above ground, with brass cap mkd. 2071 + 95 1964 bears N. 89°56' W., 70 lks. dist.</p> <p>Cor. is located 1 lk. N. of and angle iron fence post, with 4 strand barbed wire fence lines extending S. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°55' W., beginning new measurement.</p>
2.80	Center line of Interstate 17 north bound off ramp, paved, 25 ft. wide, bears S. 10° E. and N. 10° W.
5.30	Center line, north bound Interstate 17, paved, 40 ft. wide, bears N. and S.
7.20	Center line, south bound Interstate 17, paved, 40 ft. wide, bears N. and S.
10.50	Center line of Coldwater Canyon Road, paved, 30 ft. wide, bears N. 45° E. and S. 80° W. on a curve to the right.
20.08	Point for the W. 1/16 sec. cor. of secs. 27 and 34, occupied with an open ended iron pipe, origin unknown, 1 in. diam., firmly set, projecting 1 in. above ground. Not remonumented.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.16	<p>The cor. of secs. 27, 28, 33 and 34, monumented with an axle, 1½ ins. diam., firmly set, projecting 1 in. above ground, with a granite stone, 18 x 10 x 6 ins., lying loosely alongside. Gary Collins, RLS 7335, recovered the original NE mesquite bearing tree in 1985 that verified this cor. position, as recorded in Book 4 of Land Surveys, Page 79, Yavapai County Recorder, Prescott, Arizona. This is accepted as a careful and faithful perpetuation of the orig. cor. position. Not remonumented.</p> <p>Cor. is located at a fence cor., with woven wire fence lines extending N. and W.</p>
	<p>N. 0°04' E., bet. secs. 27 and 28.</p> <p>Along a woven wire fence through through a rural subdivision.</p>
20.12	<p>Point for the S. 1/16 sec. cor. of secs. 27 and 28. Not monumented.</p>
40.24	<p>Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a brass tablet, 3½ ins. diam., 3½ ins. stem, in a drill hole, and in concrete, with brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R2E 1/4 S28 S27 2001</p> </div> <p>Cor. is located on the NE edge of an iron fence post, 4 ins. diam., firmly set, in concrete, projecting 48 ins. above ground, with 4 strand barbed wire fence lines extending N. and S., and woven wire fence lines extending E. and W.</p>
60.36	<p>Point for the N. 1/16 sec. cor. of secs. 27 and 28, occupied with a rebar, origin unknown, ½ in. diam., 18 ins. long, firmly set, 2 ins. below the surface of the ground.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 34 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R2E N 1/16 S28 S27 2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and deposit the rebar inside the stainless steel post.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Cor. is located on the W. shoulder of a gravel road, bears N. and S.
80.48	<p>The cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. T9N R2E S21 S22 S28 S27 1913.</p> <p>No marks added to the brass cap.</p>
	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89°43' W., bet. secs. 22 and 27.</p> <p>Over rolling rocky land through scattering undergrowth.</p>
34.75	E. right-of-way fence, Interstate 17, 5 strand barbed wire, bears N. 20° E. and S. 20° W.
38.10	Center line of north bound Interstate 17, paved, 40 ft. wide, bears N. 50° E. and S. 50° W.
39.99	<p>The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. S22 1/4 S27 1913.</p> <p>from which an orig. bearing tree</p> <p style="padding-left: 40px;">A mesquite, 18 ins. diam., bears N. 83° W., 87 lks. dist., with fragmentary scribe marks visible on decaying blaze.</p> <p>Add the marks T9N R2E 2001 to the brass cap.</p> <p>From this cor. point, U. S. Coast and Geodetic Survey triangulation station MAGGIE 1958, bears N. 56°48' W., 9.09 chs. dist., monumented with a standard brass disk, 3 ins. diam., cemented flush in a rock outcropping 2 x 2 x 1/2 ft., with top mkd. MAGGIE 1958 and a triangle.</p>
	<p>N. 89°44' W., beginning new measurement.</p>
2.75	Center line of south bound Interstate 17, paved, 40 ft. wide, bears N. 50° E. and S. 50° W.
20.07	The W. 1/16 sec. cor. of secs. 22 and 27, established by Gary Collins, RLS 07335, in 1981, monumented with a rebar, 5/8 in. diam., 16 ins. long, firmly set, projecting 2 ins. above ground, with a steel fence post set firmly alongside, with affixed brass washer stamped LS 7335.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona**

CHAINS	
20.07	<p>This is accepted as a careful and faithful establishment of the cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, with brass cap mkd.</p> <p align="center">T9N R2E S22 W 1/16 ——— S27 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and deposit the local rebar inside the stainless steel post.</p> <hr/> <p>N. 89°44' W., beginning new measurement.</p> <p>The cor. of secs. 21, 22, 27 and 28.</p>
39.97	<p align="center">Subdivision of Section 13, T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 24.</p> <p>N. 0°05' E., on the N. and S. center line of sec. 13.</p> <p>Over mountainous terrain through creosote and cacti.</p> <p>Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E. and W. center line of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p align="center">T9N R2E C 1/4 S13 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
59.98	<p>Point for the center N. 1/16 sec. cor. of sec. 13; falls on bedrock.</p>

Subdivision of Section 13,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Chisel an "X" in the bedrock and set a stainless steel post, 28 ins. long, 2½ ins. diam., over the "X", in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T9N R2E C N 1/16 S13 C 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post, on top of the "X".</p>
79.99	<p>The 1/4 sec. cor. of secs. 12 and 13.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.</p> <p>N. 89°42' W., on the E. and W. center line of sec. 13.</p>
20.09	<p>Point for the center E. 1/16 sec. cor. of sec. 13. Not monumented.</p>
40.18	<p>The center 1/4 sec. cor. of sec. 13.</p>
60.24	<p>Point for the center W. 1/16 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T9N R2E W 1/16 C ——— C S13 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, a rebar, ½ in. diam., firmly set, projecting 3 ins. above ground, with affixed yellow plastic cap mkd. AZ 8899, bears N. 21°26' W., 0.045 ch. dist.</p>
80.30	<p>The 1/4 sec. cor. of secs. 13 and 14.</p> <hr/> <p style="text-align: center;">NE 1/4 Sec. 13</p> <hr/> <p>From the point for the center E. 1/16 sec. cor. of sec. 13.</p>

Subdivision of Section 13,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°03' E., on the N. and S. center line of the NE 1/4 of sec. 13.
20.01	Point for the NE 1/16 sec. cor. of sec. 13, at intersection with the E. and W. center line of the NE 1/4 of sec. 13. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T9N R2E NE 1/16 S13 2001</div> Deposit a magnet in a white plastic case at the base of the stainless steel post.
40.02	The E. 1/16 sec. cor. of secs. 12 and 13. <hr/>
	From the N. 1/16 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp. N. 89°41' W., on the E. and W. center line of the NE 1/4 of sec. 13.
20.08	The NE 1/16 sec. cor. of sec. 13.
40.16	The center N. 1/16 sec. cor. of sec. 13. <hr/>
	NW 1/4 Sec. 13 <hr/>
	From the center W. 1/16 sec. cor. of sec. 13. N. 0°02' E., on the N. and S. center line of the NW 1/4 of sec. 13.
20.00	Point for the NW 1/16 sec. cor. of sec. 13, at intersection with the E. and W. center line of the NW 1/4 of sec. 13. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd. <div style="text-align: center;">T9N R2E NW 1/16 S13 2001</div> Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Subdivision of Section 13,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	From this cor. point, a rebar, ½ in. diam., firmly set, projecting 6 ins. above ground, with affixed yellow plastic cap mkd. AZ LS 8899, bears North, 0.020 ch. dist.
40.00	The point for the W. 1/16 sec. cor. of secs. 12 and 13.
	From the center N. 1/16 sec. cor. of sec. 13.
	N. 89°43' W., on the E. and W. center line of the NW 1/4 of sec. 13.
20.07	The NW 1/16 sec. cor. of sec. 13.
40.14	The point for the N. 1/16 sec. cor. of secs. 13 and 14.
	Subdivision of Section 14, T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 14 and 23.
	N. 0°02' W., on the N. and S. center line of sec. 23.
	Over rocky broken terrain through scattering undergrowth.
19.99	Point for the center S. 1/16 sec. cor. of sec. 14. Not monumented.
39.98	Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E. and W. center line of sec. 14, falls on volcanic bedrock, flush with the surrounding terrain.
	Chisel an "X" in the bedrock and set a stainless steel post, 28 ins. long, 2½ ins. diam., over the "X", in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.
	T9N R2E C 1/4 S14 2001
	Deposit a magnet in a white plastic case at the base of the stainless steel post on top of the "X".
79.99	The 1/4 sec. cor. of secs. 11 and 14.
	From the 1/4 sec. cor. of secs. 13 and 14.
	West, on the E. and W. center line of sec. 14.

**Subdivision of Section 14,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.98	The center 1/4 sec. cor. of sec. 14.
59.96	Point for the center W. 1/16 sec. cor. of sec. 14. Not monumented.
79.94	The 1/4 sec. cor. of secs. 14 and 15.
<hr/>	
SW 1/4 Sec. 14	
<hr/>	
	From the W. 1/16 sec. cor. of secs. 14 and 23.
	N. 0°02' W., on the N. and S. center line of the SW 1/4 of sec. 14.
19.99	Point for the SW 1/16 sec. cor. of sec. 14, at intersection with the E. and W. center line of the SW 1/4 of sec. 14.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.
	T9N R2E SW 1/16 S14 2001
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
39.98	The point for the center W. 1/16 sec. cor. of sec. 14.
<hr/>	
	From the point for the center S. 1/16 sec. cor. of sec. 14.
	West, on the E. and W. center line of the SW 1/4 of sec. 14.
19.98	The SW 1/16 sec. cor. of sec. 14.
39.96	The S. 1/16 sec. cor. of secs. 14 and 15.
<hr/>	
Subdivision of Section 24, T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona	
<hr/>	
	From the 1/4 sec. cor. of secs. 24 and 25.
	N. 0°10' W., on the N. and S. center line of sec. 24.
	Over broken rocky land through thick undergrowth.
20.04	Point for the center S. 1/16 sec. cor. of sec. 24.

Subdivision of Section 24,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T9N R2E C S 1/16 S24 C 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located on the N. bank of a steep wash, ½ ch. wide, 30 ft. deep, drains S. 50° E.</p> <p>From this cor. point, a rebar, ½ in. diam., firmly set, projecting 1 in. above ground, with affixed red plastic cap mkd. TIM RLS 13011 bears N. 65°45' W., 0.012 ch. dist.</p>
40.08	<p>Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E. and W. center line of sec. 24, falls on the sheer side of a rock outcropping on a fractured E. facing slope, where it is impracticable to establish a durable monument.</p> <p>Chisel an "X" in the rock face, 4 x 4 x 2 ft. high, and wedge a magnet in a white plastic case in a crevice below the "X".</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for a reference monument, bears S. 12°52' W., 28.9 ft. dist., with brass cap mkd. RM T9N R2E 28.9 FT TO COR S24 2001, and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.97	<p>The 1/4 sec. cor. of secs. 13 and 24.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp.</p> <p>N. 89°34' W., on the E. and W. center line of sec. 24.</p>
20.05	<p>Point for the center E. 1/16 sec. cor. of sec. 24, occupied with a rebar, ½ in. diam., 16 ins. long, firmly set, projecting 3 ins. above ground, with affixed yellow plastic cap mkd. SURVNET AZ 8899.</p>

Subdivision of Section 24,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T9N R2E E 1/16 C ————— C S24 2001</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post and deposit the local rebar inside the stainless steel post.</p>
40.10	<p>The center 1/4 sec. cor. of sec. 24.</p>
60.15	<p>Point for the center W. 1/16 sec. cor. of sec. 24. Not monumented.</p>
80.20	<p>The 1/4 sec. cor. of secs. 23 and 24.</p>
<hr/> <p>NE 1/4 of Sec. 24</p> <hr/>	
	<p>From the center E. 1/16 sec. cor. of sec. 24.</p>
	<p>N. 0°05' W., on the N. and S. center line of the NE 1/4 of sec. 24.</p>
39.93	<p>The E. 1/16 sec. cor. of secs. 13 and 24.</p>
<hr/> <p>SE 1/4 of Sec. 24</p> <hr/>	
	<p>From the E. 1/16 sec. cor. of secs. 24 and 25.</p>
	<p>N. 0°05' W., on the N. and S. center line of the SE 1/4 of sec. 24.</p>
20.015	<p>Point for the SE 1/16 sec. cor. of sec. 24, at intersection with the E. and W. center line of sec. 24.</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
<p style="text-align: center;">T9N R2E SE 1/16 S24 2001</p>	

**Subdivision of Section 24,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, a rebar, $\frac{1}{2}$ in. diam., firmly set, projecting 5 ins. above ground, in a collar of stone, with affixed red plastic cap mkd. TIM RLS 13011, bears N. $56^{\circ}30'$ W., 0.012 ch. dist.</p>
40.03	The center E. 1/16 sec. cor. of sec. 24.
	<hr/> <p>From the point for the S. 1/16 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp.</p> <p>N. $89^{\circ}39'$ W., on the E. and W. center line of the SE 1/4 of sec. 24.</p>
20.025	The SE 1/16 sec. cor. of sec. 24.
24.70	<p>Intersect the easterly side of a 2 story stucco western theme park church.</p> <p>From this point, the NE cor. of the church bears N. 20° E., 18 lks. dist.</p> <p>From this same point, the SE cor. of the church bears S. 20° W., 7 lks. dist.</p>
24.98	<p>Intersect the southerly side of the same 2 story stucco church.</p> <p>From this point, the SE cor. of the church bears S. 70° E., 25 lks. dist.</p> <p>From this same point, the SW cor. of the church bears N. 70° W., 13 lks. dist.</p>
40.05	The center S. 1/16 sec. cor. of sec. 24.
	<hr/> <p>SW 1/4 Sec. 24</p> <hr/>
	<p>From the W. 1/16 sec. cor. of secs. 24 and 25.</p> <p>N. $0^{\circ}10'$ W., on the N. and S. center line of the SW 1/4 of sec. 24.</p>
20.06	Point for the SW 1/16 sec. cor. of sec. 24, at intersection with the E. and W. center line of sec. 24, occupied with a rebar, $\frac{1}{2}$ in. diam., 18 ins. long, firmly set, projecting 3 ins. above ground, with affixed red plastic cap mkd. TIM RLS 13011.

Subdivision of Section 24,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9NR2E SW 1/16 S24 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post and deposit the local rebar inside of the stainless steel post.</p>
40.12	<p>Point for the center W. 1/16 sec. cor. of sec. 24.</p> <hr/> <p>From the center S. 1/16 sec. cor. of sec. 24.</p> <p>N. 89°38' W., on the E. and W. center line of the SW 1/4 of sec. 24.</p>
20.045	<p>The SW 1/16 sec. cor. of sec. 24.</p>
40.09	<p>The point for the S. 1/16 sec. cor. of secs. 23 and 24.</p> <hr/> <p style="text-align: center;">Subdivision of Section 26, T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the true point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>N. 0°03' W., on the N. and S. center line of sec. 26.</p> <p>Over rolling rocky land through creosote and cacti.</p>
39.77	<p>Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E. and W. center line of sec. 26.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R2E C 1/4 S26 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this cor. point, a rebar, ½ in. diam., firmly set, projecting 1 in. above ground, in a collar of stone, with an affixed and badly deteriorated yellow plastic cap mkd. COLLINS LS 7335, bears N. 0°16' W., 0.09 ch. dist.</p>

**Subdivision of Section 26,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.05	<p>The 1/4 sec. cor. of secs. 23 and 26.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26.</p> <p>S. 89°45' W., on the E. and W. center line of sec. 26.</p>
20.02	<p>Point for the center E. 1/16 sec. cor. of sec. 26.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R2E E 1/16 C ——— C S26 2001</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located 5 lks. S. of a 4 strand barbed wire fence, bears E. and W., and 2 lks. E. of a 4 strand barbed wire fence, bears N. and S.</p> <p>From this cor. point, a rebar, origin unknown, 5/8 in. diam., firmly set, projecting 2 ins. above ground, bears N. 0°59' E., 0.045 ch. dist.</p>
40.04	<p>The center 1/4 sec. cor. of sec. 26.</p>
80.21	<p>The 1/4 sec. cor. of secs. 26 and 27.</p> <hr/> <p style="text-align: center;">SE 1/4 of Sec. 26</p> <hr/> <p>From the E. 1/16 sec. cor. of secs. 26 and 35.</p> <p>N. 0°06' W., on the N. and S. center line of the SE 1/4 of sec. 26.</p>
39.87	<p>The center E. 1/16 sec. cor. of sec. 26.</p> <hr/> <p style="text-align: center;">Subdivision of Section 27, T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 27 and 34.</p> <p>N. 0°03' E., on the N. and S. center line of sec. 27.</p>

Subdivision of Section 27,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Along the E. side of Interstate 17, over rolling rocky land.
2.60	Center line of Coldwater Canyon Road, paved, 30 ft. wide, bears S. 70° E. and N. 70° W.
19.93	Point for the center S. 1/16 sec. cor. of sec. 27. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T9N R2E C S 1/16 S27 C 2001 </div>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
39.86	Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E. and W. center line of sec. 27, falls on the W. bank of a steep wash, ½ ch. wide, 20 ft. deep, on an unstable slope, where it is impracticable to establish a durable monument. Set a magnet in a white plastic case, 18 ins. in the ground. from which <div style="text-align: center;"> A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 59°15' W., 43.5 ft. dist., with brass cap mkd. RM T9N R2E C1/4 S27 43.5 FT TO COR 2001 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post. </div>
60.05	Point for the center N. 1/16 sec. cor. of sec. 27. Not monumented.
76.20	Center line of north bound Interstate 17, paved, 40 ft. wide, bears N. 20° E. on a curve to the right and S. 20° W. on a curve to the left.
80.24	The 1/4 sec. cor. of secs. 22 and 27.
	<hr/> From the 1/4 sec. cor. of secs. 26 and 27. N. 89°32' W., on the E. and W. center line of sec. 27.
40.00	The center 1/4 sec. cor. of sec. 27.

Subdivision of Section 27,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS	
42.15	E. right-of-way fence, Interstate 17, 5 strand barbed wire, bears N. and S.
43.60	Center line of north bound Interstate 17, paved, 40 ft. wide, bears N. and S.
45.35	Center line of south bound Interstate 17, paved, 40 ft. wide, bears N. and S.
60.08	Point for the center W. 1/16 sec. cor. of sec. 27. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T9N R2E W 1/16 C ——— C S27 2001 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.16	The 1/4 sec. cor. of secs. 27 and 28. <hr style="width: 50%; margin: auto;"/> <div style="text-align: center;">SW 1/4 of Sec. 27</div> <hr style="width: 50%; margin: auto;"/> From the W. 1/16 sec. cor. of secs. 27 and 34. N. 0°04' E., on the N. and S. center line of the SW 1/4 of sec. 27.
20.03	Point for the SW 1/16 sec. cor. of sec. 27, at intersection with the E. and W. center line of the SW 1/4 of sec. 27, occupied with a rebar, origin unknown, 5/8 in. diam., 36 ins. long, firmly set, projecting 12 ins. above ground. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T9N R2E SW 1/16 S27 2001 </div> Deposit a magnet in a white plastic case at the base of the stainless steel post. Remove the rebar from the area, impracticable to bury.

Subdivision of Section 27,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located 3 lks. N. of a chain link fence, bears E. and W., and 1 lk. W. of a 4 strand barbed wire fence, extends N.</p> <p>From this cor. point, an open end pipe, origin unknown, 1 in. diam., firmly set, projecting 12 ins. above ground, bears N. 49°05' E., 0.085 ch. dist.</p>
40.06	<p>The center W. 1/16 sec. cor. of sec. 27.</p> <hr/> <p>From the center S. 1/16 sec. cor. of sec. 27.</p> <p>N. 89°49' W., on the E. and W. center line of the SW 1/4 of sec. 27.</p>
6.97	<p>Point for a witness point at intersection with the E. right-of-way of Interstate 17.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP T9N R2E S27 I AFNM S ——— S 17 2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located in the E. right-of-way fence of Interstate 17, 5 strand barbed wire, bears N. 10° E. and S. 10° W.</p> <p>From this cor. point, a brass tablet, 3 ins. diam., firmly set in a concrete cylinder, 6 ins. diam., projecting 5 ins. above ground, mkd. ARIZONA HIGHWAY DEPT 2117-27 1964, bears N. 9°13' E., 5.66 chs. dist.</p> <p>From this same cor. point, a brass tablet, 3 ins. diam., firmly set in a concrete cylinder, 6 ins. diam., projecting 12 ins. above ground, mkd. ARIZONA HIGHWAY DEPT 2106-40 1964, bears S. 9°13' W., 0.22 ch. dist.</p>
8.30	<p>Center line of north bound Interstate 17, paved, 40 ft. wide, bears N. and S.</p>
10.15	<p>Center line of south bound Interstate 17, paved, 40 ft. wide, bears N. and S.</p>

Subdivision of Section 27,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.08	The SW 1/16 sec. cor. of sec. 27.
40.16	The point for the S. 1/16 sec. cor. of secs. 27 and 28.
	<hr/> NW 1/4 Sec. 27 <hr/>
	From the center W. 1/16 sec. cor. of sec. 27.
	N. 0°04' E., on the N. and S. center line of the NW 1/4 of sec. 27.
20.16	The NW 1/16 sec. cor., at intersection with the E. and W. center line of the NW 1/4 of sec. 27, established by Gary Collins, RLS 07335, in 1985, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 2 ins. above ground, with affixed brass washer stamped LS 7335. This is accepted as a careful and faithful establishment of the cor. position.
	At the cor. point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T9N R2E NW 1/16 S27 2001
	Deposit a magnet in a white plastic case at the base of the stainless steel post and deposit the rebar inside of the stainless steel post.
	Cor. is located 8 lks. E. of the shoulder of El Paso Gas Pipeline road, unimproved gravel, bears N. and S.
	<hr/> N. 0°04' E., beginning new measurement.
20.16	The W. 1/16 sec. cor. of secs. 22 and 27.
	<hr/> From the point for the center N. 1/16 sec. cor. of sec. 27.
	N. 89°38' W., on the E. and W. center line of the NW 1/4 of sec. 27.
1.25	Center line of north bound Interstate 17, paved, 40 ft. wide, bears N. and S.
3.10	Center line of south bound Interstate 17, paved, 40 ft. wide, bears N. and S.

Subdivision of Section 27,
T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.07	The NW 1/16 sec. cor. of sec. 27. <hr/>
20.07	N. 89°38' W., beginning new measurement. The N. 1/16 sec. cor. of secs. 27 and 28. <hr/>

T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

This survey is located on the north edge of Black Canyon City, Arizona. Access is by way of Interstate 17 and other public and private roads within Black Canyon City.

The terrain is very mountainous and rocky. The Agua Fria River is the main drainage of the area. Cottonwood trees and thick undergrowth is found in the wet areas. Cacti, creosote and mesquite are scattered in the drier places.

There was no evidence of recent mineral activity.

The primary use of this land is for residential housing, although some of the land is used for grazing.

The mean magnetic declination of $12\frac{1}{4}^{\circ}$ E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.

CERTIFICATE OF SURVEY

I, Stephen K. Hansen, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 11th day of January, 2001, I have dependently resurveyed a portion of the east boundary and portion of the subdivisional lines and subdivided sections 13, 14, 24, 26 and 27, T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

01/09/2002

(Date)

Stephen K. Hansen

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the east boundary and a portion of the subdivisional lines and the subdivision of sections 13, 14, 24, 26 and 27, T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona, executed by Stephen K. Hansen, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

May 10, 2002

(Date)

Kenny S. Ravnikar
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 9 N., R. 2 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~