

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
DEPENDENT RESURVEY OF A PORTION  
OF THE SUBDIVISIONAL LINES  
AND  
THE SUBDIVISION OF SECTIONS 9 AND 10  
**TOWNSHIP 10 NORTH, RANGE 22 EAST,**  
OF THE GILA AND SALT RIVER MERIDIAN,  
IN THE STATE OF ARIZONA.

**EXECUTED BY**

**Dale C. Wilson, Cadastral Surveyor**

Under Special Instructions dated December 4, 2003, approved December 4, 2003, which provided for the surveys included under Group No. 919, and assignment instructions dated December 4, 2003.

**Survey commenced December 16, 2003**

**Survey completed January 12, 2004**

# INDEX DIAGRAM

TOWNSHIP 10 NORTH      RANGE 22 EAST

6	5 11	4 10	3 8	2 5	1
7	8	9 9 8	6 10 5	4 11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 9 ..... Pages 12-13  
 Subdivision of Section 10 ..... Pages 14-16

**T. 10 N., R. 22 E., Gila and Salt River Meridian, Arizona**

CHAINS

The following field notes describe the dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 9 and 10, Township 10 North, Range 22 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

O. D. Wheeler surveyed the east boundary and the subdivisional lines in 1882. Theodore Vander Meer dependently resurveyed the east boundary in 1935. Harry K. Smith dependently resurveyed a portion of the subdivisional lines in 1979.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated December 4, 2003, for Group Number 919, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 4700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

In the course of this survey it was determined that there is an ancient fence projecting east from the 1/4 section corner of sections 5 and 8, four and one half miles to the corner of sections 1 and 12 on the east boundary of the township. The latitudinal portion of the section corner of sections 2, 3, 10 and 11 was coincident with this ancient fence. It was determined that this ancient fence is the best available evidence of the latitudinal position of the original corners of sections 4, 5, 8 and 9 and sections 3, 4, 9 and 10, and the 1/4 section corner of sections 3 and 10. The fences extending north and south at both section corner positions are irregular and exact positions based on these fences are indeterminate.

Geodetic control was derived from second order National Geodetic Survey triangulation station White, as published by the National Geodetic Survey, NAD 83 (1992). The geographic position of the corner of sections 10, 11, 14 and 15, is as follows:

Latitude: 34°16'18.02" N.                      Longitude: 109°59'25.01" W.

The mean magnetic declination is 11 1/2° E.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 10 N., R. 22 E., Gila and Salt River Meridian, Arizona**

CHAINS

Restoring the survey executed by  
O. D. Wheeler, in 1883

---

Beginning at the cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. T10N R22E S10 S11 S15 S14 1978, with a mound of stone, 4 ft. base, 1 ft. high, to the W.

Add the marks 2003 to the brass cap.

N. 0°05' E., bet. secs. 10 and 11.

Over nearly level dry lake bed.

40.21

Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 10 N R 22 E  
1/4  
S 10 | S 11

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Raise a mound of stone, 5 ft. base, 2 ft. high, to the W.

80.42

Point for the cor. of secs. 2, 3, 10 and 11, determined latitudinally in an abandoned fence, bears E. and W., and longitudinally at proportionate distance.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.

T 10 N R 22 E  
S 3 | S 2  
S 10 | S 11

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Raise a mound of stone, 4 ft. base, 1 1/2 ft. high, to the W.

Cor. falls in an abandoned fence line, bears E. and W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 10 N., R. 22 E., Gila and Salt River Meridian, Arizona**

CHAINS

From this point the cor. of secs. 1 and 12 only, on the E. bdy. of the Tp., bears N. 89°24' E., 160.10 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, in a mound of stone, 4 ft. base, 1 ft. high, with brass cap mkd. T10N R22E R23E S1 S6 S12 1935.

from which

A pine, 24 ins. diam., bears S. 64 3/4° W., 120 lks. dist., with a healed blaze. (Record: S. 64° W., 116 lks.)

A juniper, 12 ins. diam., bears N. 33 1/4° W., 42 lks. dist., with scribe marks T10N R22E S1 BT visible on partially open blaze.

Add the marks 2004 to the brass cap.

---

From the cor. of secs. 2, 3, 10 and 11.

N. 0°46' W., bet. secs. 2 and 3.

Over gently rolling land.

40.21

The 1/4 sec. cor. of secs. 2 and 3, monumented with a basalt stone, 22 x 18 x 6 ins., firmly set, 10 ins. in the ground, plainly mkd. 1/4 on W. face, with a mound of stone, 5 ft. base, 1 1/2 ft. high, to the W.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 10 N R 22 E

1/4

S 3 | S 2

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Bury the mkd. stone alongside the stainless steel post.

---

From the 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T10N R22E 1/4 S10 S15 1978, and with a mound of stone, 4 ft. base, 1 ft. high, to the N.

from which

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 10 N., R. 22 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A juniper, 10 ins. diam., bears N. 8 1/4° E., 53 lks. dist., with a healed blaze. (Record: N. 11° E., 36.5 lks.)</p>
	<p>A dead standing pine, 16 ins. diam., bears S. 68 1/4° E., 35 lks. dist., with a healed blaze. (Record: N. 65° E., 53 lks.)</p>
	<p>Add the marks 2004 to the brass cap. S. 89°41' W., bet. secs. 10 and 15.</p>
	<p>Over gently rolling land through scattered juniper and pinon.</p>
20.075	<p>Point for the W. 1/16 sec. cor. of secs. 10 and 15, not monumented.</p>
35.13	<p>Point for the W-W-W 1/256 sec. cor. of secs. 10 and 15.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">           T 10 N R 22 E                              S 10            W-W-W 1/256 ———                              S 15             2004         </p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Cor. falls 6 lks. S. of a fence, bears E. and W.</p>
40.15	<p>The cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T10N R22E S9 S10 S15 S16 1978, with a mound of stone, 4 ft. base, 2 ft. high, to the W.  from which</p> <p>A juniper, 8 ins. diam., bears N. 23° E., 315.5 lks. dist., with scribe marks T10N R22E S9 BT visible on partially healed blaze. (Record: N. 25° E.)</p> <p>A juniper, 12 ins. diam., bears S. 69 1/4° E., 174 lks. dist., with a healed blaze. (Record: S. 71° E.)</p> <p>A juniper, 16 ins. diam., bears S. 7° W., 260.5 lks. dist., with partial scribe marks visible on partially healed blaze. (Record: S. 9° W.)</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 10 N., R. 22 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">An old fence cor., extending N. and W., bears N. 39° W., 68.5 lks. dist. (Record: N. 37° W.)</p> <p>Cor. falls in a fence, bears E. and W.</p> <p>Add the marks 2003 to the brass cap.</p> <hr/>
	<p>N. 0°02' W., bet. sec. 9 and 10.</p> <p>Over gently rolling land through scattered juniper and pine.</p>
20.225	Point for the S. 1/16 sec. cor. of secs. 9 and 10, not monumented.
25.28	<p>Point for the S-N-S 1/256 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 10 N R 22 E S-N-S 1/256 S 9   S 10</p> <p align="center">2004</p>
40.45	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate distance, there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 10 N R 22 E 1/4 S 9   S 10</p> <p align="center">2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Raise a mound of stone 4 base, 2 ft. high to the W.</p> <p>Cor. falls 46 lks. E. of old fence, bears N. and S.</p>
80.90	Point for the cor. of secs. 3, 4, 9 and 10, determined latitudinally in an abandoned fence, bears E. and W., and longitudinally at proportionate distance.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 10 N., R. 22 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to bed rock, encircled with a supporting mound of stone, 4 ft. base to top, with brass cap mkd.</p>
	<p align="center">T 10 N R 22 E S 4   S 3 S 9   S 10</p>
	<p align="center">2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Cor. falls in abandon E-W fence, 24.5 lks. E. of the cor. of existing fences extending N. and W. and 45.5 lks. E. of the cor. of fences extending E., W. and S.</p>
	<hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p>
	<p>N. 89°59' W., bet. secs. 3 and 10.</p>
	<p>Over gently rolling land, sparse sage and grass.</p>
<p>40.23</p>	<p>Point for the 1/4 sec. cor. of secs. 3 and 10, determined latitudinally in an abandoned fence, bears E. and W., and longitudinally at proportionate distance.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, encircled with a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.</p>
	<p align="center">T 10 N R 22 E S 3 1/4 ——— S 10</p>
	<p align="center">2004</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Cor. falls in an abandon fence, bears E. and W.</p>
<p>80.46</p>	<p>The cor. of secs. 3, 4, 9 and 10.</p>
	<hr/> <p>From the cor. sec. of sec. 9, 10, 15 and 16.</p>
	<p>S. 89°40' W., bet. secs. 9 and 16.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 10 N., R. 22 E., Gila and Salt River Meridian, Arizona**

CHAINS	
10.01	<p>Over gently rolling land, through scattered juniper and pine.</p> <p>Point for the E-E 1/64 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, with brass cap mkd.</p> <p align="center">T 10 N R 22 E S 9 E-E 1/64 ——— S 16</p> <p align="center">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. falls 6 lks. N. of a fence, bears E. and W., and 42.5 lks. S. of a fence, bears E. and W.</p>
20.02	<p>Point for the E. 1/16 sec. cor. of secs. 9 and 16, not monumented.</p>
40.04	<p>The 1/4 sec. cor. of secs. 9 and 16, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T10N R22E 1/4 S9 S16 1978, with a mound of stone, 4 ft. base, 2 ft. high, to the N.</p> <p>from which</p> <p>A dead standing pine, 12 ins. diam., bears N. 58 1/4° E., 309.5 lks. dist., with a healed blaze. (Record: N. 61° E.)</p> <p>A juniper, 12 ins. diam., bears N. 5 3/4° W., 236 lks. dist., with scribe marks 1/4 S16 BT visible on partially healed blaze. (Record: S. 8° W.)</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T10N R22E S8 S9 S16 S17 1978, with a mound of stone, 4 ft. base, 1 ft. high, to the W.</p> <p>Cor. falls in a fence, bears E. and W.</p> <p>From this cor. a reinforcement rod 5/8 ins. diam., firmly set, projecting 12 ins. above ground, with a plastic cap mkd. L. S. 16165, bears N. 89°50' E., 44 lks. dist., this monument was established by Ronald Matkin, Arizona Registered Professional Land Surveyor No. 16165 as a right-of-way corner in section 16.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 10 N., R. 22 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same cor. a reinforcement rod 1/2 in. diam., firmly set, in a concrete cylinder, 4 in. diam., projecting 6 ins. above ground, with plastic cap mkd. RES LS 11758, bears S. 89°51' W., 47 lks. dist., this monument was established by Ronald Stoll, Arizona Registered Professional Land Surveyor No. 11758</p> <p>N. 0°06' E., bet. secs. 8 and 9.</p> <p>Over gently rolling land through scattered juniper and pinon.</p>
23.18	<p>Arizona State Highway No. 77, asphalt surfaced, bears N. 18° W. and S. 18° E.</p>
40.16	<p>The 1/4 sec. cor. of secs. 8 and 9, monumented with a malpai stone, 16 x 15 x 6 ins., firmly set, 10 ins. in the ground, in a mound of stone, 4 ft. base, 1/2 ft. high, plainly mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p align="center">T 10 N R 22 E 1/4 S 8   S 9  2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. falls in an abandon fence, bears N. and S.</p> <hr/> <p>N. 0°05' W., beginning new measurement.</p> <p>Over nearly level terrain, through scattered juniper.</p>
40.27	<p>Point for the cor. of secs. 4, 5, 8 and 9, determined latitudinally in an abandoned fence, bears E. and W., and longitudinally at proportionate distance.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in solid rock, with top mkd.</p> <p align="center">T 10 N R 22 E S 5   S 4 S 8   S 9  2004</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 10 N., R. 22 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the brass tablet.</p> <p>Cor. falls 5 lks. west of the cor. of fences, extending N., S. and E., with abandoned fence extending W.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89°20' W., bet. secs. 4 and 9.</p> <p>Over gently rolling land, through scattered juniper.</p>
40.03	<p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate distance, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p align="center">T 10 N R 22 E S 4 1/4 ——— S 9</p> <p align="center">2004</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. falls 41 lks. N. of a fence, bears E. and W.</p> <p>There is no evidence of the ancient fence line in this area.</p>
80.06	<p>The cor. of secs. 4, 5, 8 and 9.</p> <hr/> <p>S. 89°52' W., bet. secs. 5 and 8.</p> <p>Over nearly level land, through scattered juniper.</p>
18.62	<p>Arizona State Highway No. 77, asphalt surfaced, bears S. 18° E. and N. 18° W.</p>
40.12	<p>The 1/4 sec. cor. of secs. 5 and 8, monumented with a basalt stone, 30 x 16 x 8 ins., firmly set, 14 ins. in the ground, plainly mkd. 1/4 on N. face, with a mound of stone, 4 ft. base, 1 ft. high, to the N.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, with a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 10 N., R. 22 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 10 N R 22 E S 5 1/4 ——— S 8  2004  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Bury the mkd. stone alongside the stainless steel post.  <hr/> From the 1/4 sec. cor. of secs. 9 and 16.  N. 0°02' W., on the N. and S. center line of sec. 9.  Over nearly level land.
20.155	Point for the center S. 1/16 sec. cor. of sec. 9, not monumented.
40.31	Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E. and W. center line.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 10 N R 22 E C 1/4 S 9  2004  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.67	The 1/4 sec. cor. of secs. 4 and 9.  <hr/> From the 1/4 sec. cor. of secs. 9 and 10.  S. 89°28' W., on the E. and W. center line of sec. 9.  Over nearly level land.
20.02	Point for the center E. 1/16 sec. cor. of sec. 9, not monumented.
40.04	The center 1/4 sec. cor. of sec. 9.
80.04	The 1/4 sec. cor. of secs. 8 and 9.  <hr/>

**Subdivision of Section 9,  
T. 10 N., R. 22 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p align="center">SE 1/4 of sec. 9</p> <hr/> <p>From the point for the E. 1/16 sec. cor. of secs. 9 and 16. N. 0°02' W., on the N. and S. center line of the SE 1/4 of sec. 9.</p> <p>20.19 Point for the SE 1/16 sec. cor. of sec. 9, at intersection with the E. and W. center line of the SE 1/4, not monumented.</p> <p>40.38 The point for the center E. 1/16 sec. cor. of sec. 9.</p> <hr/> <p>From the point for the S. 1/16 sec. cor. of secs. 9 and 10. S. 89°34' W., on the E. and W. center line of the SE 1/4 sec. 9. Over nearly level land.</p> <p>10.01 Point for the center E-SE 1/64 sec. cor. of sec. 9, not monumented.</p> <p>20.02 The point for the SE 1/16 sec. cor. of sec. 9.</p> <p>40.04 The point for the center S. 1/16 sec. cor. of sec. 9.</p> <hr/> <p>From the E-E 1/64 sec. cor. of secs. 9 and 16. N. 0°02' W., on the N. and S. center line of the SE 1/4 of the SE 1/4, sec. 9. Over nearly level land.</p> <p>20.21 The point for the center E-SE 1/64.</p> <hr/> <p>N. 0°02' W., on the N. and S. center line of the NE 1/4 of the SE 1/4 of sec. 9. Over nearly level land.</p> <p>5.05 Point for the center S-NE-SE 1/256 sec. cor. of sec. 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 10 N R 22 E C-S-NE-SE 1/256 S 9</p> <p align="center">2004</p>
--------	---

**Subdivision of Section 9,  
T. 10 N., R. 22 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 89°32' E., on the E. and W. center line of the SE 1/4 of the NE 1/4 of the SE 1/4 sec. 9.</p> <p>Over nearly level land.</p>
10.01	<p>The S-N-S 1/256 sec. cor. of secs. 9 and 10.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 10 and 15.</p> <p>N. 0°02' E., on the N. and S. center line of sec. 10.</p> <p>Over nearly level land.</p>
20.17	<p>Point for the center S. 1/16 sec. cor. of sec. 10, not monumented.</p>
40.34	<p>Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 10 N R 22 E C 1/4 S 10</p> <p style="text-align: center;">2004</p>
80.67	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>The 1/4 sec. cor. of secs. 3 and 10.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 10 and 11.</p> <p>S. 89°51' W., on the E. and W. center line of sec. 10.</p> <p>Over nearly level land.</p>
40.19	<p>The center 1/4 sec. cor. of sec. 10.</p>
60.285	<p>Point for the center W. 1/16 sec. cor. of sec. 10, not monumented.</p>
80.38	<p>The 1/4 sec. cor. of secs. 9 and 10.</p> <hr/>

**Subdivision of Section 10,  
T. 10 N., R. 22 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	SW 1/4 of sec. 10
	_____
	From the point for the W. 1/16 sec. cor. of secs. 10 and 15.
	North, on the N. and S. center line of the SW 1/4 of sec. 10.
20.195	Point for the SW 1/16 sec. cor. of sec. 10, at intersection with the E. and W. center line of the SW 1/4, not monumented.
40.39	The point for the center W. 1/16 sec. cor. of sec. 10.
	_____
	From the point for the center S. 1/16 sec. cor. of sec. 10.
	S. 89°46' W., on the E. and W. center line of the SW 1/4 sec. 10.
	Over nearly level land.
20.085	The point for the SW 1/16 sec. cor. of sec. 10.
35.145	Point for the center W-W-SW 1/256 sec. cor. of sec. 10, not monumented.
40.17	The point for the S. 1/16 sec. cor. of secs. 9 and 10.
	_____
	From the W-W-W 1/256 sec. cor. of secs. 10 and 15.
	N. 0°01' W., on the N. and S. center line of the SW 1/4 of the SW 1/4 of the SW 1/4, sec. 10.
	Over nearly level land.
10.11	Point for the center W-SW-SW 1/256 sec. cor. of sec. 10., not monumented.
	_____
	N. 0°01' W., on the N. and S. center line of the NW 1/4 of the SW 1/4 of the SW 1/4, sec. 10.
	Over nearly level land.
10.11	The point for the center W-W-SW 1/256 sec. cor. of sec. 10.
	_____
	N. 0°01' W., on the N. and S. center line of the SW 1/4 of the NW 1/4 of the SW 1/4, sec. 10.
	Over nearly level land.
5.05	Point for the SW-NW-SW 1/256 sec. cor. of sec. 10.

**Subdivision of Section 10,  
T. 10 N., R. 22 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 22 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with brass cap mkd.

T 10 N R 22 E  
SW-NW-SW 1/256  
S 10

2004

Deposit a magnet in a white plastic case at the base of the  
stainless steel post.

---

S. 89°47' W., on the E. and W. center line of the SW 1/4 of the  
NW 1/4 of the SW 1/4, sec. 10.

Over nearly level land.

5.02

The S-N-S 1/256 sec. cor. of secs. 9 and 10.

---

GENERAL DESCRIPTION

---

The area encompassed in this survey lies approximately 2 miles  
northeast of Show Low, Arizona. The majority of the area is  
level to gently rolling with a number of dry lake beds  
throughout. The elevation is from 6300 to 6400 feet above sea  
level. Access to the area is by Arizona State Highway No. 77 in  
the southwest corner of section 9 and numerous trail roads  
throughout. Vegetation consists of scattered stands of juniper  
and piñon, sage and native grasses. The only apparent use of  
the area is grazing

The mean magnetic declination of 11 1/2° E. was derived from the  
United States Geological Survey computer program GEOMAG,  
utilizing the World Magnetic Model for Epoch 2000 for the dates  
of survey.

---



CERTIFICATE OF SURVEY

I, Dale C. Wilson, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 4th day of December, 2003, I have dependently resurveyed a portion of the subdivisional lines and subdivided sections 9 and 10, T. 10 N., R. 22 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

8/16/04  
(Date)

Dale C. Wilson  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 9 and 10, T. 10 N., R. 22 E., Gila and Salt River Meridian, in the State of Arizona, executed by Dale C. Wilson, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

August 17, 2004  
(Date)

Denny D. Lawmiller  
(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 10 N., R. 22 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~\_\_\_\_\_~~  
~~(Date)~~

~~\_\_\_\_\_~~  
~~(Chief Cadastral Surveyor of Arizona)~~