ORIGINAL

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES AND A PORTION OF THE SUBDIVISION OF SECTIONS 22, 23, 26 AND 35

AND

THE SUBDIVISION OF A PORTION OF SECTIONS 22, 23 AND 26, AND THE METES-AND-BOUNDS SURVEY IN SECTIONS 23, 26, AND 35,

TOWNSHIP 8 NORTH, RANGE 27 EAST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA.

EXECUTED BY

Joe R. Salazar, Cadastral Surveyor

Under Special Instructions dated July 23, 2003, approved July 23, 2003, which provided for the surveys included under Group No. 910, and assignment instructions dated July 23, 2003.

Survey commenced August 12, 2003
Survey completed August 16, 2004

INDEX DIAGRAM

TOWNSHIP 8 NORTH RANGE 27 EAST GILA AND SALT RIVER MERIDIAN, ARIZONA

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22 6	23 6	24
30	29	28	27	26 5	25
31	32	33	34 4	35	36

Subdivision of Section 22 Pages 8-9
Subdivision of Section 23 Pages 10-13
Subdivision of Section 26 Pages 13-16
Subdivision of Section 35 Pages 16-19
Metes and Bounds Survey in Section 23 Page 19
Metes and Bounds Survey in Section 26 Page 20
Metes and Bounds Survey in Section 35 Pages 20-23

T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the subdivisional lines and a portion of the subdivision of sections 22, 23, 26 and 35, and the subdivision of a portion of sections 22, 23 and 26 and the metes-and-bounds survey in sections 23, 26 and 35, T. 8 N., R. 27 E., of the Gila and Salt River Meridian, Arizona.

W. R. Fitzgerald surveyed the S. bdy. in 1883. A. E. Shoemaker surveyed the subdivisional lines in 1883. Ty white, Claude F. Warner and Frank Motoh resurveyed the S. bdy. and the subdivisional lines in 1940. Harry K. Smith dependently resurveyed a portion of the subdivisional lines and subdivided sections 22, 23, 26, 27 and 35 in 1976-78. William P Carpender dependently resurveyed a portion of the S. bdy. in 1990. Stephen K. Hansen dependently resurveyed a portion of the subdivision of section 26 and a metes-and-bounds survey in 1992.

Mark B. Clements, Arizona Registered Land Surveyor No. 22754, executed a survey for the Black River Land Exchange identifying two parcels in the survey of a portion of sections 22, 23 and 26, T. 8 N., R. 27 E. as Tract A and the survey of a portion of section 35, T. 8 N., R. 27 E. as Tract B, in September, 2001 and his survey was utilized as the basis for this survey.

The survey was executed in accordance with the specifications as set forth in the <u>Manual of Instructions for the Survey of the Public Lands of the United States, 1973</u>, and the Special Instructions dated July 23, 2003, for Group No. 910.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5400 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from second order Arizona Department of Transportation triangulation station "PORT", as published by the National Geodetic Survey, NAD 83 (1992). The geographic position of the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of Tp. is as follows:

Latitude: 34°02'17.70" N. Longitude: 109°28'23.04" W.

The mean magnetic declination is 11 1/4° E.

CHAINS

Restoring the survey executed by Ty White, Claude F. Warner and Frank Motoh, in 1940

Beginning at the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. T8N R27E S34 S35 S3 S2 T7N R27E 1940.

from which the remaining original bearing trees

- A pine, 36 ins. diam., bears S. 46 3/4° E., 75 lks. dist., with scribe marks T7N R27E S2 BT visible on partially open blaze.
- A pine, 38 ins. diam., bears N. 40° W., 53 lks. dist., with a healed blaze.

Add the marks 2003 to the brass cap.

N. 0°17' W., bet. secs. 34 and 35.


Over rolling terrain through dense piñon and juniper.

AP 2 of a metes-and-bounds survey in sec. 35, established by Mark B. Clements, Arizona R.L.S. No. 22754, monumented with an aluminum post, 1 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. 2001 22754, with a metal fence post, with forest service sign attached, alongside.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 N R 27 E



Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Deposit the aluminum post inside the stainless steel post.

Cor. is located on steep W. slope of ridge, bears N. and S.

	T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona
CHAINS	
41.95	The 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. 1/4 S34 S35 1940.
	from which the original bearing trees
	A pine, 18 ins. diam., bears S. 43 1/2° E., 64 lks. dist., with a healed blaze.
	A pine, 28 ins. diam., bears N. 86° W., 28 lks. dist., with a healed blaze.
	Add the marks T8N R27E 2003 to the brass cap.
	Restoring the resurvey executed by Harry K. Smith, in 1976-78
	From the E. 1/16 sec. cor. of secs. 26 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T8N R27E E1/16 S26 S35 1976.
	from which the original bearing trees
	A pine, 10 ins. diam., bears N. 47 1/2° E., 53 lks. dist., with scribe marks E1/16 S26 BT visible on partially open blaze.
	A pine, 14 ins. diam., bears S. 62 1/2° E., 78 lks. dist., with scribe marks E1/16 S35 BT visible on partially open blaze.
	Add the marks 2003 to the brass cap.
	N. 86°30' W., bet. secs. 26 and 35.
	Over rolling terrain through dense piñon and juniper.
1.84	AP 10 of a metes-and-bounds survey in sec. 35, established by Mark B. Clements, Arizona R.L.S. No. 22754, monumented with an aluminum post, 1 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. 2001 22754.
19.80	Graveled road, 12 ft. wide, bears N. and S.
20.05	The 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. S26 1/4 S35 1940.
	from which the original bearing trees

CHAINS

- A pine, 20 ins. diam., bears N. 1/2° E., 48 lks. dist., with healed blaze.
- A pine, 18 ins. diam., bears S. 14 1/2° W., 40 lks. dist., with healed blaze.

Add the marks T8N R27E 2003 to the brass cap.

From the 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd. T8N R27E S23 1/4 S26 1992 1976 1940.

from which the 1976 bearing trees

- A pine, 10 ins. diam., bears S. 7 3/4° W., 67 lks. dist., with healed blaze.
- A pine, 12 ins. diam., bears N. 12° W., 59 lks. dist., with healed blaze.

Add the marks 2003 to the brass cap.

N. 84°08' W., bet. secs. 23 and 26.

Over rolling terrain through dense piñon and juniper.

7.48 Poi

Point for AP 1 of a metes-and-bounds survey in sec. 23, identical to AP 2 of a metes-and-bounds survey in sec. 26, at intersection with the W. right-of-way of State Highway No. 373, bears S. 28°31' E. and N. 28°31' W., not monumented.

20.29

The W. 1/16 sec. cor. of secs. 23 and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T8N R27E W1/16 S23 S26 1976.

from which the original bearing trees

- A pine, 13 ins. diam., bears N. 40 3/4° E., 5.00 chs. dist., with healed blaze.
- A pine, 15 ins. diam., bears S. 12 1/2° E., 7.57 chs. dist., with healed blaze.

Add the marks 2003 to the brass cap.

Cor. is located in a 3 in. diam. pipe fence, extending N. and S.

From the S. 1/16 sec. cor. of secs. 22 and 23, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T8N R27E S1/16 S22 S23 1976.

CHAINS

from which the original bearing trees

- A pine, 12 ins. diam., bears N. 83 1/4° E., 94 lks. dist., with healed blaze.
- A pine, 12 ins. diam., bears N. 15 1/4° W., 2.57 chs. dist., with healed blaze.

Add the marks 2003 to the brass cap.

Cor. is located in 3 in. diam. pipe fence, extending E. and W.

N. 0°42' E., bet. secs. 22 and 23.

Over rolling terrain through dense piñon and juniper.

9.73

The N-S 1/64 sec. cor. of secs. 22 and 23, determined by Mark B. Clements, Arizona R.L.S. No. 22754, monumented with an aluminum post, 1 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. T8N R27E N-S 1/64 S22 S23 2001 LS 22754, witnessed with a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 8 N R 27 E N-S 1/64 S 22 | S 23

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Deposit the aluminum post inside the stainless steel post.

Cor. is located on the S. slope of ridge, bears E. and W.

N. 0°42' E., beginning new measurement.

9.73

The 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above a mound of stone, 4 ft. base, 18 ins. high, with brass cap mkd. 1/4 S22 S23 1976 1940.

from which the remaining original bearing trees

CHAINS

- A pine, 14 ins. diam., bears S. 49 3/4° E., 35 lks. dist., with healed blaze.
- A pine, 12 ins. diam., bears N. 41 3/4° W., 14.5 lks. dist., with healed blaze.

Add the marks T8N R27E 2003 to the brass cap.

Dependent Resurvey of a Portion of the Subdivision of Section 22,

T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona

Restoring the survey executed by Harry K. Smith, in 1976-78

From the SE 1/16 sec. cor. of sec. 22, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. T8N R27E SE1/16 S22 1976.

from which the original bearing trees

- A pine, 12 ins. diam., bears S. 75 1/4° W., 1.08 chs. dist., with healed blaze.
- A pine, 12 ins. diam., bears N. 40 3/4° W., 1.02 chs. dist., with healed blaze.

Add the marks 2003 to the brass cap.

N. 0°41' E., on the N. and S. center line of the SE 1/4 of sec. 22.

9.89

The center N-SE 1/64 sec. cor. of sec. 22, determined by Mark B. Clements, Arizona R.L.S. No. 22754, monumented with an aluminum post, 1 in. diam., firmly set, in a mound of stone, 4 ft. base, 24 ins. high, with aluminum cap mkd. T8N R27E 1/64 S22 LS 22754.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 8 N R 27 E S 22 C-N-SE 1/64

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Dependent Resurvey of a Portion of the Subdivision of Section 22,

GUATNO	r
CHAINS	
	Deposit the aluminum post inside the stainless steel post.
	N. 0°41' E., beginning new measurement.
3.40	State Highway No. 260, asphalt surface, bears NE and SW.
9.89	The center E. 1/16 sec. cor. of sec. 22, monumented with an iron post, 2 1/2 ins. diam., firmly set, in a mound of stone, 4 ft. base to top, with brass cap mkd. T8N R27E C E 1/16 C S22 1976.
	from which the original bearing trees
	A pine, 12 ins. diam., bears S. 86 3/4° W., 65 lks. dist., with healed blaze.
	A pine, 12 ins. diam., bears N. 36° W., 52 lks. dist., with healed blaze.
	Add the marks 2003 to the brass cap.
	From the S. 1/16 sec. cor. of secs. 22 and 23.
	S. 87°53' W., on the E. and W. center line of the SE 1/4 of sec. 22.
20.21	The SE 1/16 sec. cor. of sec. 22.
	Subdivision of a Portion of Section 22, T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona
	From the N-S 1/64 sec. cor. of secs. 22 and 23.
	S. 88°20' W., on the E. and W. center line of the NE 1/4 of the SE 1/4 of sec. 22.
	Over rolling terrain through dense piñon and juniper.
20.21	The center N-SE 1/64 sec. cor. of sec. 22.

Dependent Resurvey of a Portion of the Subdivision of Section 23,

	The second secon
CHAINS	Restoring the survey executed by Harry K. Smith, in 1976-78
	From the 1/4 sec. cor. of secs. 23 and 26.
	N. 0°44' E., on the N. and S. center line of sec. 23.
i.	Over rolling terrain through dense piñon and juniper.
19.80	The center S. 1/16 sec. cor. of sec. 23, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. T8N R27E C S1/16 S23 C 1976, witnessed with a mound of stone, 4 ft. base, 2 ft. high, W. of cor.
	from which the original bearing trees
	A pine, 20 ins. diam., bears N. 28 1/2° E., 45.5 lks. dist., with healed blaze.
	A pine, 15 ins. diam., bears S. 3° W., 1.25 chs. dist., with healed blaze.
	Add the marks 2003 to the brass cap.
	N. 0°44' E., beginning new measurement.
9.90	Point for the center N-S 1/64 sec. cor. of sec. 23, not monumented.
19.80	The center 1/4 sec. cor. of sec. 23, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T8N R27E C1/4 S23 1976, witnessed with a mound of stone, 4 ft. base, 2 ft. high, W. of cor.
	from which the original bearing trees
	A pine, 13 ins. diam., bears S. 61 3/4° E., 52 lks. dist., with healed blaze.
	A pine, 12 ins. diam., bears S. 61° W., 1.195 chs. dist., with healed blaze.
	From this point, Arizona Department of Transportation triangulation station "PORT", bears N. 66°49' E., 791.97 chs. dist., monumented with an aluminum tablet, 3 ins. diam.,
	projecting 4 ins. above the ground, encased in concrete, 10 ins. diam., mkd PORT 1978.
	From the W. 1/16 sec. cor. of secs. 23 and 26.

Dependent Resurvey of a Portion of the Subdivision of Section 23,

CHAINS	
	N. 0°44' E., on the N. and S. center line of the SW 1/4 of sec. 23.
	Over rolling terrain through dense piñon and juniper.
19.63	The SW 1/16 sec. cor. of sec. 23, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T8N R27E SW 1/16 S23 1976.
	from which the original bearing trees
	A pine, 15 ins. diam., bears N. 18° E., 58 lks. dist., with healed blaze.
	A pine, 12 ins. diam., bears S. 33 1/4° W., 88 lks. dist., with healed blaze.
	Add the marks 2003 to the brass cap.
	Cor. is located in fence intersection, extending N., S. and W.
	N. 0°44' E., beginning new measurement.
9.82	The center N-SW 1/64 sec. cor. of sec. 23, determined by Mark B. Clements, Arizona R.L.S. No. 22754, monumented with an iron pipe, 1 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd., T8N R27E C-N-SW 1/64 S23 2001 LS22754.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.
	T 8 N R 27 E C-N-SW 1/64
	2004
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Deposit the iron post inside the stainless steel post.
	N. 0°45' E., beginning new measurement.

Dependent Resurvey of a Portion of the Subdivision of Section 23,

CHAINS	
9.82	The center W. 1/16 sec. cor. of sec. 23, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. T8N R27E C W 1/16 C S23 1976, witnessed with a mound of stone, 4 ft. base, 3 ft. high, N. of cor.
	from which the original bearing trees
	A pine, 15 ins. diam., bears N. 43° E., 61 lks. dist., with healed blaze.
	A pine, 11 ins. diam., bears S. 10 1/2° W., 87.5 lks. dist., with healed blaze.
	Add the marks 2003 to the brass cap.
	From the center S. 1/16 sec. cor. of sec. 23.
	N. 84°37' W., on the E. and W. center line of the SW 1/4 of sec. 23.
	Over rolling terrain through dense piñon and juniper.
18.91	Intersect the W. right-of-way of State Highway No. 373, on a curve, hereinafter described.
20.28	The SW 1/16 sec. cor. of sec. 23.
	N. 84°36' W., beginning new measurement.
20.28	The S. 1/16 sec. cor. of secs. 22 and 23.
	Subdivision of a Portion of Section 23, T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona
	From the center N-S 1/64 sec. cor. of sec. 23.
	N. $84^{\circ}51'$ W., on the E. and W. center line of the NE $1/4$ of the SW $1/4$ of sec. 23.
	Over rolling terrain through dense piñon and juniper.
19.24	AP 3, sec. 23, of a metes-and-bounds survey in sec. 23, at intersection with the W. right-of-way of State Highway No. 373, on a curve, established by Mark B. Clements, Arizona R.L.S. No. 22754, monumented with an aluminum post, 1 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. 2001 LS 22754.

Subdivision of a Portion of Section 23, T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 N R 27 E S 23 AP3

2004

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Deposit the aluminum post inside the stainless steel post.

20.27 The center N-SW 1/64 sec. cor. of sec. 23.

N. $84^{\circ}50'$ W., on the E. and W. center line of the NW 1/4 of the SW 1/4 of sec. 23.

20.28 The N-S 1/64 sec. cor. of secs. 22 and 23.

Dependent Resurvey of a Portion of the Subdivision of Section 26, T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona

Restoring the survey executed by Harry K. Smith, in 1976-78

From the center N. 1/16 sec. cor. of sec. 26, monumented with an iron post, firmly set, projecting 12 ins. above the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd. T8N R27E C N 1/16 S26 C 1992 1976.

from which the original bearing trees

- A pine, 12 ins. diam., bears N. 78 1/2° E., 1.03 chs. dist., with healed blaze.
- A pine, 12 ins. diam., bears S. 83 1/2° W., 26.5 lks. dist., with healed blaze.

Add the marks 2003 to the brass cap.

N. 0°12' E., on the N. and S. center line of sec. 26.

Dependent Resurvey of a Portion of the Subdivision of Section 26,

CHAINS	
	Over rolling terrain through dense piñon and juniper.
7.71	Intersect W. right-of-way of State Highway No. 373, bears S. 28°31' E. and N. 28°31' W.
9.27	The point for AP 5 of the 1992 metes-and-bounds survey in the NE 1/4 of sec. 26, at intersection with the center line of State Highway No. 373.
10.29	The center N-N 1/64 sec. cor. of sec. 26, determined by Mark B. Clements, Arizona R.L.S. No. 22754 monumented with a rebar, 3/8 in. diam., firmly set, projecting 3 ins. above the ground, with a Forest Service iron post and sign alongside.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 8 N R 27 E
	N-N 1/64 S 26
	Ċ
	2004 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Deposit the rebar inside the stainless steel post.
	N. 0°10' E., beginning new measurement.
10.28	The 1/4 sec. cor. of secs. 23 and 26.
	From the NW 1/16 sec. cor. of sec. 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T8N R27E NW1/16 S26 1976.
	from which the remaining original bearing tree
	A pine, 13 ins. diam., bears N. 80° E., 9 lks. dist., with a healed blaze.
	Add the marks 2003 to the brass cap.
	Cor. is located in fence corner, extending N. and W.
	N. 0°04' E., on the N. and S. center line of the NW 1/4 of sec. 26.

Dependent Resurvey of a Portion of the Subdivision of Section 26,

CHAINS	
	Over rolling terrain through dense piñon and juniper.
10.39	The center N-NW 1/64 sec. cor. of sec. 26, determined by Raymond Lee Jones, Arizona R.L.S. No. 5713 and accepted by Mark B. Clements, Arizona R.L.S. No. 22754, monumented with a rebar, 5/8 in. diam., firmly set, projecting 5 ins. above the ground.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 8 N R 27 E S 26 C-N-NW 1/64
·	2004
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Deposit the rebar inside the stainless steel post.
	Cor. is located in pipe fence line, extending N. and S.
	N. 0°04' E., beginning new measurement.
10.39	The W. 1/16 sec. cor. of secs. 23 and 26.
	Subdivision of a Portion of Section 26, T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona
	From the center N-N 1/64 sec. cor. of sec. 26.
	N. 84°27' W., on the E. and W. center line of the NE 1/4 of the NW 1/4 of sec. 26.
	Over rolling terrain through dense piñon.
1.50	AP 1 of a metes-and-bounds survey in sec. 26, established by Mark B. Clements, Arizona R.L.S. No. 22754, at intersection with W. right-of-way of State Highway No. 373, monumented with an aluminum post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. 2001 LS22754.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Subdivision of a Portion of Section 26, T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona

CULTUG	
CHAINS	T 8 N R 27 E
	s 26 \
	AP1
	2004
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Deposit the aluminum post inside the stainless steel post.
20.26	The center N-NW 1/64 sec. cor. of sec. 26.
	Dependent Resurvey of a Portion of the Subdivision of Section 35, T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona
	Restoring the survey executed by Harry K. Smith, in 1976-78
	From the 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above a mound of stone, 3 ft. base, 1 1/2 ft. high, with brass cap mkd. T8N R27E 1/4 S35 S2 T7N 1990 1940.
	from which the original bearing trees
	A pine, 25 ins. diam., bears N. 30° E., 39 lks. dist., with scribe marks 1/4 S35 visible on partially open blaze.
	A pine, 22 ins. diam., bears S. 40 1/4° E., 97 lks. dist., with a healed blaze.
	Add the marks 2004 to the brass cap.
	N. 0°21' W., on the N. and S. center line of sec. 35.
23.50	Intersect line 3-4 sec. 35, hereinafter described.
41.09	The center 1/4 sec. cor. of sec. 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above a mound of stone, 3 ft. base, 1 1/2 ft. high, with brass cap mkd. T8N R27E C1/4 S35 1976.
	from which the original bearing trees

Dependent Resurvey of a Portion of the Subdivision of Section 35,

CHAINS	
S.Z.I.N.C	A pine, 10 ins. diam., bears N. 64 1/2° E., 22 lks. dist., with scribe marks C1/4 S35 BT visible on partially open blaze.
	A pine, 8 ins. diam., bears S. 9° E., 41.5 lks. dist., with scribe marks C1/4 S35 BT visible on partially open blaze.
	Add the marks 2004 to the brass cap.
	N. 0°21' W., beginning new measurement.
20.48	The center N. 1/16 sec. cor. of sec. 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above a mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. T8N R27E C N1/16 S35 C 1976.
	from which the original bearing trees
	A pine, 13 ins. diam., bears N. 74 3/4° E., 42.5 lks. dist., with healed blaze.
	A pine, 15 ins. diam., bears S. 31 1/4° E., 11.5 lks. dist., with healed blaze.
	Add the marks 2003 to the brass cap.
	Cor. is located in fence, extending E. and W. and 7 ft. W. of fence corner extending N. and W.
	N. 0°22' W., beginning new measurement.
20.48	The 1/4 sec. cor. of secs. 26 and 35.
	From the 1/4 sec. cor. of secs. 35 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above a mound of stone, 2 ft. base, 1 ft. high, with brass cap mkd. 1/4 S35 S36 1940.
	from which the original bearing trees
	A pine, 14 ins. diam., bears N. 56° E., 21 lks. dist., with scribe marks 1/4 S36 BT visible on partially open blaze.
	A pine, 11 ins. diam., bears N. 40° W., 20 lks. dist., with scribe marks 1/4 S35 BT visible on partially open blaze.
	Add the marks T8N R27E 2004 to the brass cap.

Dependent Resurvey of a Portion of the Subdivision of Section 35,

CHAINS	
	N. 88°03' W., on the E. and W. center line of sec. 35.
19.40	Intersect the W. right-of-way of State Highway No. 373, hereinafter described.
40.53	The center 1/4 sec. cor. of sec. 35.
	N. 88°04' W., beginning new measurement.
29.69	Intersect line 1-2 sec. 35, hereinafter described.
40.06	The 1/4 sec. cor. of secs. 34 and 35.
	From the center N. 1/16 sec. cor. of sec. 35.
	N. 87°21' W., on the E. and W. center line of the NW 1/4 of sec. 35.
	Over rolling terrain in dense piñon and juniper.
18.11	AP 1 of a metes-and-bounds survey in sec. 35, established by Mark B. Clements, Arizona R.L.S. No. 22754, monumented with an aluminum post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. 2001 LS 22754, witnessed with a mound of stone, 2 ft. base, 1 ft. high, S. of cor.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 8 N R 27 E
	s 35
	AP1
	2004
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Deposit the aluminum post inside the stainless steel post.
	Cor. is located 8 ft. W. of corner of fences, extending E. and SSW.
25.03	The center E-W-NW 1/256 sec. cor. of sec. 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. S35 C-E-W-NW 1/256 1976.

Dependent Resurvey of a Portion of the Subdivision of Section 35,

CHAINS	
	from which the original bearing trees
	A pine, 15 ins. diam., bears S. 25° W., 67 lks. dist., with healed blaze.
	A pine, 20 ins. diam., bears N. 83 3/4° W., 62 lks. dist., with healed blaze.
	Add the marks T8N R27E 2003 to the brass cap.
	Cor. is located in fence corner, extending N. and E.
	Metes-and-Bounds Survey in Section 23, T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona
	From AP 1 of a metes-and-bounds survey in sec. 23 identical to AP 2 of a metes-and-bounds survey in sec. 26, hereinbefore described.
	N. 28°31' W., on line 1-2 sec. 23, along the W. right-of-way of State Highway No. 373.
	Over rolling terrain through scattered piñon and juniper.
21.42	AP 2, sec. 23, identical to the point of curvature, monumented with a brass tablet, flush with ground in concrete, mkd. PC 313+05.79 50 1959, witnessed with a 4 in. angle iron, 2 ft. high, alongside.
	Thence on line 2-3 sec. 23, along a circular curve to the right, having a central angle of 46°17', a radius of 998.9 ft., along the W. right-of-way of State Highway No. 373, the cord of said arc bears N. 5°22' W., 11.90 chs.
2.19	Intersect the E. and W. center line of the SW 1/4 of sec. 23.
	From this point the SW 1/16 sec. cor. of sec. 23, bears N. 84°37' W., 1.37 chs. dist.
12.23	AP 3, sec. 23, at intersection with the E. and W. center line of the NE 1/4 of the SW 1/4 of sec. 23, hereinbefore described.
	From this point, the center N-SW 1/64 sec. cor. of sec. 23, bears N. 84°51' W., 1.03 chs. dist.
	From this same point, a brass tablet, flush with ground in concrete, mkd. 19, witnessed with a 4 in. angle iron, 2 ft. high, alongside, mkd. PT 324+84.17, bears N. 29°51' E., 6.34 chs. dist.

Metes-and-Bounds Survey in Section 26, T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	From AP 1, sec. 26, hereinbefore described.
	From this cor., the center N-N 1/64 sec. cor. of sec. 26, hereinbefore described, bears S. 84°27' E., 1.50 chs. dist.
	From this same cor., a right-of-way monument, bears S. 28°31' E., 6.67 chs. dist., monumented with a brass cap, flush with ground in concrete, mkd. PT 286+41.93 50 1958, witnessed with a 4 in. angle iron, 2 ft. high, alongside.
	N. 28°31' W., on line 1-2 sec. 26, along the W. right-of-way of State Highway No. 373.
	Over rolling terrain through scattered piñon and juniper.
12.41	AP 1, sec. 23, identical to AP 2, sec. 26, hereinbefore described.
	Metes-and-Bounds Survey in Section 35, T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona
	From AP 1, sec. 35, hereinbefore described.
	S. 29°26' W., on line 1-2 sec. 35.
	Over rolling terrain through dense piñon and juniper, along ridge.
23.32	Intersect the E. and W. center line of sec. 35.
	From this point, the 1/4 sec. cor. of secs. 34 and 35, bears N. 88°04' W., 10.37 chs. dist.
44.22	AP2, sec. 35, hereinbefore described.
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of Tp., hereinbefore described.
	N. 57°43' E., on a line to AP3, sec. 35.
	Over rolling terrain through scattered piñon and juniper.
43.08	AP 3, sec. 35, established by Mark B. Clements, Arizona R.L.S. No. 22754, monumented with an aluminum post, 1 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. 2001 LS 22754, witnessed with a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	At the corner point

Metes-and-Bounds Survey in Section 35,

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft base, to top, with brass cap mkd.
	T 8 N R 27 E
	AP3
	s 35
	2004
	Deposit a magnet, in a white plastic case, at the base of th stainless steel post.
	Deposit the aluminum post inside the stainless steel post.
	S. 89°58' E., on line 3-4.
	Over rolling terrain through scattered piñon and juniper.
3.52	Intersect the N. and S. center line of sec. 35.
	From this point, the center 1/4 sec. cor. of sec. 35, bear N. 0°21' W., 17.59 chs. dist.
27.20	AP 4, sec. 35, at intersection with the W. right-of-way of Stat Highway No. 373, on a curve, established by Mark B. Clements Arizona R.L.S. No. 22754 monumented with a aluminum post, 1 in diam., firmly set, projecting 4 ins. above the ground, wit aluminum cap mkd. LS22754 2001, witnessed with a mound of stone 2 ft. base, 1 ft. high, W. of cor.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam. 22 ins. in the ground, with brass cap mkd.
	T 8 N R 27 E
	AP4 /
	s 35
	2004
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Deposit the aluminum post inside the stainless steel post.

Metes-and-Bounds Survey in Section 35, T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	From this cor., a brass tablet, 2 ins. below the ground in concrete, mkd. PT 186+19.40 1950, witnessed with a 4 in. angle iron, 2 1/2 ft. high, alongside, bears S. 34°57' E., 17.98 chs. dist.
	Thence on line 4-5 sec. 35, along a circular curve to the right, having a central angle of 13°28', a radius of 1195.0 ft., along the W. right-of-way of State Highway No. 373, the cord of said arc bears N. 1°15' W., 4.24 chs. dist.
4.25	AP 5, sec. 35, identical to the point of tangency, monumented with a brass tablet, flush with ground, in concrete, mkd. PT 200+79.38 50 1959, witnessed with a 4 in. angle iron, projecting 24 ins. above the ground, alongside, mkd. PT 200+79.38.
	N. 5°21' E., on line 5-6 sec. 35, along the W. right-of-way of State Highway No. 373.
	Over rolling terrain through scattered piñon and juniper.
0.30	AP 6, sec. 35, identical to the point of curvature, monumented with a brass tablet, loosely set, flush with ground in concrete, mkd. 200+99.68 50 1959.
	Thence on line 6-7 sec. 35, along a circular curve to the left, having a central angle of 34°03', a radius of 1388.0 ft., along the W. right-of-way of State Highway No. 373, the cord of said arc bears N. 11°30' W., 12.31 chs. dist.
12.50	Point for AP 7, sec. 35, identical to the point of tangency, not monumented.
	From this point, a brass tablet, flush with ground in concrete, mkd. 209+51.06, witnessed with a 4 in. angle iron, projecting 24 ins. above the ground, alongside, bears N. 61°19' E., 1.52 chs. dist.
	N. 28°42' W., on line 7-8 sec. 35, along the W. right-of-way of State Highway No. 373.
0.31	Intersect the E. and W. center line of sec. 35.
	From this point, the 1/4 sec. cor. of secs. 35 and 36, bears S. 88°03' E., 19.40 chs. dist.
1.67	AP 8, sec. 35, identical to the point of curvature, monumented with a brass tablet, flush with ground in concrete, mkd. 210+60.47 50, witnessed with a 4 in. angle iron, projecting 24 ins. above the ground, alongside.

Metes-and-Bounds Survey in Section 35, T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS				
	Thence on line 8-9 sec. 35, along a circular curve to the right having a central angle of 31°14', a radius of 1958.5 ft., along the W. right-of-way of State Highway No. 373, the cord of said arc bears N. 13°03' W., 15.98 chs. dist.			
16.18	AP 9, sec. 35, identical to the point of tangency, monumented with a brass tablet, flush with ground in concrete, mkd. 220+99.44 1959, witnessed with a 4 in. angle iron, projecting 24 ins. above the ground, alongside, mkd. PT 220+99.44.			
	N. 2°32' E., on line 9-10 sec. 35, along the W. right-of-way of State Highway No. 373.			
	Over rolling terrain through scattered piñon and juniper.			
23.83	AP 10, sec. 35.			
	GENERAL DESCRIPTION			
	The area surveyed is located approximately 2 miles north of Greer, Arizona. Access is provided by State Road No. 373 with numerous track and logging roads in the vicinity.			
	The main drainage of the area is the Little Colorado River, which flows easterly. Elevation ranges from 7800 to 8300 feet above sea level. There is thick stands of pine, with scattered juniper and spruce.			
	There are some housing in the area. The main use of the area is livestock grazing and outdoor recreation.			
	The mean magnetic declination of 11 1/4° E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2000 for the dates of survey.			

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Nelson Kinsel	Surveying Technician
	·

CERTIFICATE OF SURVEY

I, Joe R. Salazar, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 23 day of July, 2003, I have dependently resurveyed a portion of the subdivisional lines and a portion of the subdivision of sections 22, 23, 26 and 35 and the subdivision of a portion of sections 22, 23 and 26 and the metes-and-bounds survey in section 23, 26 and 35, T. 8 N., R. 27 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

///b/04/ /(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and a portion of the subdivision of sections 22, 23, 26 and 35 and the subdivision of a portion of sections 22, 23 and 26 and the metes-and-bounds survey in section 23, 26 and 35, T. 8 N., R. 27 E., Gila and Salt River Meridian, in the State of Arizona, executed by Joe R. Salazar, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

12/08/04 Stephen K. Hansen

(Date) Acting(Chief Cadastral Surveyor of Arizona)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.

(Date)

(Chief Cadastral Surveyor of Arizona)