ORIGINAL

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE

EAST BOUNDARY

AND THE SURVEY OF THE NORTH BOUNDARY

AND THE SUBDIVISIONAL LINES

TOWNSHIP 41 NORTH, RANGE 3 WEST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA.

EXECUTED BY

W. William Foster, Cadastral Surveyor

Under Special Instructions dated May 5, 2005, approved May 5, 2005, which provided for the surveys included under Group No. 959, and assignment instructions dated May 5, 2005.

Survey commenced May 18, 2005

Survey completed August 4, 2005

INDEX DIAGRAM

TOWNSHIP 41 NORTH RANGE 3 WEST GILA AND SALT RIVER MERIDIAN, ARIZONA

13		12		11		10		9		8	
6	58	5	45	4	37	3	30	2	21	1	7
57		57		45		37		29		20	
7	56	8	44	9	36	10	28	11	19	12	7
55		54		43		35		27		19	
18	53	17	42	16	34	15	26	14	18	13	6
52		52		42		34		26		17	
19	51	20	41	21	33	22	25	23	16	24	5
50		49		40		32		24		16	
30	48	29	39	28	32	27	23	26	15	25	5
48		47		39		31		22		14	
31	46	32	38	33	30	34	21	35	13	36	4
										L	

T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of the east boundary and the survey of the north boundary and the subdivisional lines, Township 41 North, Range 3 West, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Jos. C. Thoma surveyed the south boundary (Tenth Standard Parallel North), in 1914. Andrew Nelson and Walter A. Stumm surveyed the east boundary , in 1911. Adrien J. Rodriguez, Cadastral Surveyor, surveyed the west boundary in 2003. Adrien J. Rodriguez, Cadastral Surveyor, resurveyed the south boundary (Tenth Standard Parallel North), in 2004.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated May 5, 2005, for Group Number 959, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from a tie to third order United States Coast and Geological Survey triangulation station EASY 1953, as published by the National Geodetic Survey, NAD 83 (1992). The geographic position of the southeast township corner, is as follows:

Latitude: 36°54'12.14" N. Longitude: 112°33'30.56" W.

The mean magnetic declination is 12 1/4° E.

Restoring the survey executed by Andrew Nelson and Walter A. Stumm, in 1911

Beginning at the true point for the stan. cor. of Tps. 41 N., Rs. 2 and 3 W.; falls in Kanab Creek, 300 ft. wide, 25 ft. deep, course S. 35° W., determined at record bearing and dist. from the 2004 witness cor.

From this true point, the witness cor. to the stan. cor. of Tps. 41 N., Rs. 2 and 3 W., bears S. 45°00' E., 5.00 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. WC SC T41N R3W R2W S36 S31 2004, with an arrow pointing to the true cor. position.

From this same true point, U.S.C. & G.S. triangulation station "EASY 1953", monumented with a brass tablet, 3 ins. diam., in a 12 ins. square concrete column, firmly set, projecting 5 ins. above the ground, bears S. 67°28' W., forward bearing, 416.63 chs. dist.

North, bet. secs. 31 and 36, on the E. bdy. of the Tp.

Over rolling land through dense grass and medium growth of sage brush.

40.00

Point for the 1/4 sec. cor. of secs. 31 and 36 at proportionate dist., find a 6 ins. long piece of an iron post, 1 in. diam., with brass cap mkd. 1/4 S36 S31 1911 laying loose, there is no other evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

T 41 N 1/4 R 3 W | R 2 W S 36 | S 31

2005

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Cor. is located beneath a 5 strand barbed wire fence, bears N.

80.00

The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 3 ins. diam., firmly set, flush with the ground, with brass cap mkd. T41N R3W R2W S25 S30 S36 S31 1911.

Add the marks 2005 to the brass cap.

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	Cor. is located beneath a 5 strand barbed wire fence , bears N. and S. and a 12 KV power line, bears E. and W.
	North, bet. secs. 25 and 30.
	Over rolling to level land through dense native grasses and sage brush.
40.03	The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. 1/4 S25 S30 1911.
	Add the marks T41N R3W R2W and 2005 to the brass cap.
	Cor. is located at intersection of barbed wire fences, bears N., E. and S.
	N. 0°01' W., beginning new measurement.
39.89	Center line of Arizona State Highway No. 389, asphalt surface, 32 ft. wide, bears N. 45° E. and S. 45° W.
40.02	The cor. of secs. 19, 24, 25 and 30, monumented with an iron post, 3 ins. diam., buried 8 ins. below the surface in a metal hand hole. Brass cap is badly corroded and is impossible to read.
	Cor. is located in the W. bound lane of Arizona State Highway No. 389, 18 lks. from edge of asphalt.
	North, bet. secs. 19 and 24.
	Over rolling land through native grasses and sage brush.
39.99	The 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. 1/4 S24 S19 1911.
	Add the marks T41N R3W R2W and 2005 to the brass cap.
	Cor. is located beneath a 5 strand barbed wire fence, bears N. and S.
	North, beginning new measurement.

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
40.01	The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. T41N R3W R2W S13 S18 S24 S19 1911.
	Add the marks 2005 to the brass cap.
	Cor. is located beneath a 5 strand barbed wire fence, bears N. and S.
	N. 0°01' W., bet. secs. 13 and 18.
	Over rolling to broken land through scattered sage and scrub juniper trees.
40.05	The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd. 1/4 S13 S18 1911.
	from which the original bearing trees
	A juniper, 18 ins. diam., bears S. 43 1/4° E., 2.76 chs. dist., with scribe marks S 1 BT visible on partially open blaze. (Record: S. 41 1/2° E.)
	A juniper, multibranched, 13 ins. diam., bears S. 85 1/4° W., 93 1/2 lks. dist., with scribe marks BT visible on partially open blaze. (Record: N. 86°20' W.)
	Add the marks T41N R3W R2W and 2005 to the brass cap.
	N. 0°01' W., beginning new measurement.
40.04	The cor. of secs. 7, 12, 13, and 18, monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. T41N R3W R2W S12 S7 S13 S18 1911.
	from which the original bearing trees
	A juniper, 18 ins. diam., bears S. 80° W., 2.27 chs. dist., with scribe marks BT visible on partially open blaze. (Record: S. 83 1/4° W., 2.23 chs. dist.)
	A juniper, 30 ins. diam., bears N. 56 1/4° W., 1.42 chs. dist., with scribe marks 12 BT visible on partially open blaze. (Record: N. 51°50' W., 1.45 chs. dist.)
	Add the marks 2005 to the brass cap.
	There is no remaining evidence of the mound of stone.

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Cor. is located beneath a 5 strand barbed wire fence, bears N. and S.
	N. 0°01' E., bet. secs. 7 and 12.
	Over rolling land through medium growth scrub juniper.
40.04	The 1/4 sec. cor. of secs. 7 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. 1/4 S12 S7 1911.
	from which the original bearing trees
	A juniper, 13 ins. diam., bears N. 45° 50' E., 2.245 chs. dist., with scribe marks 7 BT visible on partially open blaze.
	A juniper, 18 ins. diam., bears N. 23° W., 1.245 chs. dist., with a healed blaze. (Record: N. 22° W.)
	Add the marks T41N R3W R2W and 2005 to the brass cap.
	Cor. is located beneath 5 strand barbed wire fence, bears N. and S.
40.04	N. 0°02' W., beginning new measurement. The cor. of secs. 1, 6, 7 and 12, monumented with an iron post,
	3 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. T41N R3W R2W S1 S6 S12 S7 1911.
	Add the marks 2005 to the brass cap.
	Cor. is located beneath 5 strand barbed wire fence, bears N. and S.
	·
	N. 0°02' W., bet. secs. 1 and 6.
	Over level land through heavy native grasses and scattered sage brush.
40.05	The 1/4 sec. cor. of secs. 1 and 6, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. 1/4 S1 S6 1911.
	Add the marks T41N R2W R3W and 2005 to the brass cap.

Dependent Resurvey of the East Boundary

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	Cor. is located 3 lks. W. of chain link fence cor., bears E. and S. and 1 lk. E. of 5 strand barbed wire fence, bears N. and S.
	N. 0°01' E., beginning new measurement.
40.05	The cor. of Tps. 41 and 42 N., Rs 2 and 3 W., monumented with an iron post, 3 ins. diam., firmly set, projecting 16 ins. above the ground, with brass cap mkd. T42N R3W R2W S36 S31 S1 S6 R3W R2W T41N 1911 2003.
	Add the marks 2005 to the brass cap.
	Cor. is located at intersection of 5 strand barbed wire fences, bears N., E. and S.
	Survey of the North Boundary, T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
	From the cor. of Tps. 41 and 42 N., Rs. 2 and 3 W.
	S. 89°58' W., bet. secs. 1 and 36, on the N. bdy. of the Tp.
	Over level land through dense native grasses and scattered sage brush.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 42 N R 3 W
	s 36 1/4 ——
	s 1 T 41 N
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 1, 2, 35 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the North Boundary,

T.	41	N.,	R.	3	W.	, Gila	and	Salt	River	Meridian,	Arizona

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	m 40 m n 0 m
	T 42 N R 3 W S 35 S 36
	S 2 S 1
	T 41 N
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land , level. Sage brush and native grasses. Soil, sandy.
	S. 89°58' W., bet. secs. 2 and 35.
	Over level land, through scattered sage brush and native grasses.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 42 N R 3 W
	s 35 1/4 ——
	s 2
	T 41 N
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 2, 3, 34 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 42 N R 3 W
	S 34 S 35 S 3 S 2 T 41 N
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

Survey of the North Boundary,

5. 41 N., R. 3 W., Gila and Salt River Meridian, Arizon

CHAINS	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
	Land, level vegetation, sage brush and native grasses. Soil, sandy.
	S. 89°58' W., bet. secs. 3 and 34.
	Over rolling land, through scattered sage brush and nativ grasses.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam. 25 ins. in the ground, with brass cap mkd.
	T 42 N R 3 W S 34
	1/4
	T 41 N
	2005
	Deposit a magnet in a white plastic case at the base of th stainless steel post.
	Cor. is located on E. edge of bladed road, 15 ft. wide, bear S. 30° E. and N. 30° W.
40.18	Center line of bladed road, bears S. 30° E. and N. 30° W.
40.44	Barbed wire fence, 4 strand, bears N. 30° W.
80.00	True point for the cor. of secs. 3, 4, 33 and 34, falls in wash, 130 ft. wide, 6 ft. deep, drains S. 40° E., where it i impractical to establish a permanent monument.
	From this true point, the point selected for an offline witnes cor., bears S. 1°28' E., 1.19 chs. dist.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam. 25 ins. in the ground, with brass cap mkd.

Survey of the North Boundary, T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	WC T 42 N R 3 W S 33 S 34 S 4 S 3 T 41 N 2005 Deposit a magnet in a white plastic case at the base of the stainless steel post. Land, level to rolling. Vegetation, sage brush and native grasses. Soil, sandy.
	S. 89°58' W., bet. secs. 4 and 33. Over rolling land, gradually ascending, through medium growth sage brush and scrub juniper bush.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd. T 42 N R 3 W S 33 1/4 —— S 4 T 41 N 2005 Deposit a magnet in a white plastic case at the base of the
80.00	stainless steel post. Point for the cor. of secs. 4, 5, 32 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 42 N R 3 W S 32 S 33 S 5 S 4 T 41 N 2005

Survey of the North Boundary,

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling. Vegetation, sage brush and scrub juniper. Soil, sandy.
	S. 89°58' W., bet. secs. 5 and 32.
	Over rolling land, through medium growth sage brush and scrub juniper.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 42 N R 3 W S 32
	1/4
	S 5 T 41 N
	1 31 1
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 5, 6, 31 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 42 N R 3 W S 31 S 32 S 6 S 5 T 41 N
	2005
	from which
	A forked juniper, 12 ins. diam., bears N. 82 1/2° E., 1.02 chs. dist., mkd. T42NR3W S32 BT.
	A piñon pine, 7 ins. diam., bears S. 62 3/4° W., 31 lks. dist., mkd. T41NR3W S6 BT.

Survey of the North Boundary, L N., R. 3 W., Gila and Salt River Meridia

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling.
	Vegetation, sage brush, native grasses, scrub juniper, piñon
	pine and various cacti.
	Soil, sandy.
	S. 89°58' W., bet. secs. 6 and 31.
	Over broken land, through scrub juniper and piñon pine, sage brush and native grasses.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 42 N R 3 W
	1 42 N R 3 W S 31
İ	1/4 —
	S 6
	T 41 N
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.68	The cor. of Tps. 41 and 42 N., Rs. 3 and 4 W., monumented with a stainless steel post, firmly set, projecting 3 ins. above a supporting mound of stone, 3 ft. base, 1 1/2 ft. high, with brass cap mkd. T42N R4W R3W S36 S31 S1 S6 T41N 2003.
	Survey of the Subdivisional Lines, T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
	From the stan. cor. of secs. 35 and 36, on the S. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd. T41N SC S35 R3W S36 2004 1914.
	N. 0°01' W., bet. secs. 35 and 36.
	Over level land, through native grasses.
40.00	Point for the 1/4 sec. cor. of secs. 35 and 36.

<u></u>	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W 1/4
	s 35 s 36
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 25, 26, 35 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W
	S 26 S 25
	s 35 s 36
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located beneath a power line, bears E. and W.
	Land, level. Vegetation, grassy. Soil, sandy.
	From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the ${ m Tp}$.
	S. 89°59' W., bet. secs. 25 and 36.
	Over level land, through native grasses.
40.01	Point for the 1/4 sec. cor. of secs. 25 and 36.
	Set a stainless steel post, 28 ins. long, 2 $1/2$ ins. diam., 24 ins. in the ground, with brass cap mkd.

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	T 41 N R 3 W S 25 1/4 S 36
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.02	The cor. of secs. 25, 26, 35 and 36.
	Land, level. Vegetation, native grasses. Soil, sandy.
	N. 0°01' W., bet. secs. 25 and 26.
	Over level to rolling land, through native grasses and scattered sage brush.
1.50	Power line, bears N. 45° E. and S. 45° W.
3.24	Arizona State Highway No. 389, asphalt surfaced, 32 ft. wide, bears N. 45° E. and S. 45° W.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W 1/4 S 26 S 25
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 23, 24, 25 and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,
41 N., R. 3 W., Gila and Salt River Meridia

<u></u>	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 41 N R 3 W S 23 S 24
	S 26 S 25
	5 20 5 25
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, level to rolling. Vegetation, native grasses and sage brush. Soil, sandy and caliche.
	From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.
	S. 89°57' W., bet. secs. 24 and 25.
	Over level land, through scattered sage and native grasses.
8.35	Asphalt road, 25 ft. wide, bears S. 10° E. and N. 10° W.
23.85	Power line, bears N. 25° E. and S. 25° W.
40.00	Point for the 1/4 sec. cor. of secs. 24 and 25.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 24 1/4 —— S 25
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	The cor. of secs. 23, 24, 25 and 26.
	Land, level. Vegetation, native grasses and sage brush. Soil, sandy clay.
	N. 0°01' W., bet. secs. 23 and 24.

GUATNG	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	Over rolling land through native grasses and scattered sage brush.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W 1/4 S 23 S 24
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 13, 14, 23 and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 14 S 13 S 23 S 24
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, level to broken. Vegetation, native grasses and sage brush. Soil, sandy clay.
	From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.
	S. 89°57' W., bet. secs. 13 and 24.
·	Over level to broken land through native grasses and scattered sage brush.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines, F. 41 N., R. 3 W., Gila and Salt River Meridian, Arizo

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 41 N R 3 W
	S 13
	1/4 S 24
	2005
	Deposit a magnet in a white plastic case at the base of the
	stainless steel post.
44.98	Power line, bears S. 30° E. and N. 30° W.
47.98	Asphalt road, 25 ft. wide, bears S. 30° E. and N. 30° W.
80.00	The cor. of secs. 13, 14, 23 and 24.
	Land, level to broken. Vegetation, native grasses and sage brush. Soil, sandy clay.
	N. 0°01' W., bet. secs. 13 and 14.
	Over level to broken land, through native grasses.
32.69	Power line, bears S. 45° E. and N. 45° W.
33.74	Asphalt road, 25 ft. wide, bears S. 50° E. and N. 50° W.
40.00	True point for the 1/4 sec. cor. of secs. 13 and 14 falls on the S. face of a steep slope, where it is impractical to establish a permanent monument.
	From this true point, the point selected for an offline witness corner, bears S. 31°37' W., 89 lks. dist.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	WC T 41 N R 3 W 1/4 S 14 S 13
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 11, 12, 13 and 14.

Survey of the Subdivisional Lines,

1. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.
	T 41 N R 3 W S 11 S 12
	S 14 S 13
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, level to broken. Vegetation, native grasses, scrub juniper and piñon pine. Soil, rocky and sandy.
	From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.
	S. 89°53' W., bet. secs. 12 and 13.
	Over rolling land through medium growth scrub juniper and piñon pine.
39.99	Point for the 1/4 sec. cor. of secs. 12 and 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W
	5 12
	1/4 —— S 13
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.98	The cor. of secs. 11, 12, 13 and 14.
	Land, rolling. Vegetation, scrub juniper and piñon pine. Soil, rocky and sandy.
	N. 0°01' W., bet. secs. 11 and 12.

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	Over rolling land, through medium growth scrub juniper and piñon pine.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W 1/4 S 11 S 12
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 1, 2, 11 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 2 S 1 S 11 S 12
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling. Vegetation, scrub juniper, piñon pine, sage brush and native grasses. Soil, sandy.
	From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.
	S. 89°50' W., bet. secs. 1 and 12.
	Over rolling to level land, through scattered sage brush and native grasses.
39.98	Point for the 1/4 sec. cor. of secs. 1 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines, T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 41 N R 3 W
	S 1
	1/4 —
	S 12
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.96	The cor. of secs. 1, 2, 11 and 12.
	Land, rolling to level. Vegetation, sage brush and native grasses. Soil, sandy.
	N. 0°03' W., bet. secs. 1 and 2.
	Over level land, through scattered sage brush and native grasses.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W 1/4 S 2 S 1
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.28	The cor. of secs. 1, 2, 35 and 36 on the N. bdy. of the Tp.
	Land. level. Vegetation, native grasses and scattered sage brush. Soil, sandy.
	From the stan. cor. of secs. 34 and 35, on the S. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. SC T41N R3W S34 S35 2004 1914.
	N. 0°01' W., bet. secs. 34 and 35.

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Over rolling land, through native grasses and scattered sage brush.
4.38	Power line, bears N. 45° E. and S. 45° W.
6.46	Arizona State Highway No. 389, asphalt surfaced, 32 ft. wide, bears N. 45° E. and S. 45° W.
40.00	Point for the 1/4 sec. cor. of secs. 34 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W
	1/4
	S 34 S 35
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 26, 27, 34 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W
	s 27 s 26
	S 34 S 35
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling to broken. Vegetation, native grasses and sage brush. Soil, sandy clay.
	From the cor. of secs. 25, 26, 35 and 36.
	West, bet. secs. 26 and 35.
İ	Over rolling to broken land, through scattered sage brush and native grasses.
3.39	Arizona State Highway No. 389, asphalt surfaced, 32 ft. wide, bears N. 45° E. and S. 45° W.

Survey of the Subdivisional Lines, T. 41 N. R. 3 W. Gila and Salt River Meridian, Arizona

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
40.02	Point for the 1/4 sec. cor. of secs. 26 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 26 1/4
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.04	The cor. of secs. 26, 27, 34 and 35.
	Land, rolling to broken. Vegetation, sage brush and native grasses. Soil, sandy clay.
	N 0°011 W 1-4
	N. 0°01' W., bet. secs. 26 and 27.
	Over broken land, through native grasses and scattered scrub juniper.
40.00	True point for the 1/4 sec. cor. of secs. 26 and 27, falls in a wash, 3 ft. wide, 1 ft. deep, drains N. 85° W., where it is impractical to establish a permanent monument.
	From this true point, the point selected for an offline witness cor. to the 1/4 sec. cor. of secs 26 and 27, bears N. 10°45' W., 44 lks. dist.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	wc
	T 41 N R 3 W
	1/4 S 27 S 26
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located at the toe of a slope and ascend over broken land through scattered scrub juniper trees.

Survey of the Subdivisional Lines,
41 N., R. 3 W., Gila and Salt River Meridian, Ariz

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
80.00	Point for the cor. of secs. 22, 23, 26 and 27.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in solid rock, with top mkd.
	T 41 N R 3 W S 22 S 23 S 27 S 26
	2005
	from which
	A piñon pine, 4 ins. diam., bears N. 13 3/4° E., 88 lks. dist., mkd. X BT.
	A piñon pine, 11 ins. diam., bears S. 5 1/2° E., 52 lks. dist., mkd. T41NR3W S26 BT.
	Deposit a magnet at the base of the brass tablet.
	Land, rolling and broken. Vegetation, scrub juniper trees. Soil, sandy and rocky.
	From the cor. of secs. 23, 24, 25 and 26. West, bet. secs. 23 and 26.
	Over broken land, through sage brush and native grasses.
40.02	Point for the 1/4 sec. cor. of secs. 23 and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 23 1/4
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.04	The cor. of secs. 22, 23, 26 and 27.
	Land, broken.

Survey of the Subdivisional Lines, T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	Vegetation, sage brush and native grasses. Soil, sandy and rocky.
	N. 0°01' W., bet. secs. 22 and 23.
	Over rolling to broken land, through native grasses and scattered sage brush.
40.00	True point for the 1/4 sec. cor. of secs 22 and 23, falls on the E. face of a steep slope, where it is impractical to establish a permanent monument.
·	From this true point, the point selected for an offline witness cor., bears S. 81°05' W., 49 lks. dist.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in solid rock, with top mkd.
	WC T 41 N R 3 W 1/4 -> S 22 S 23
	2005
	from which
	A piñon pine, 4 ins. diam., bears S. 42° W., 67 lks. dist., mkd. X BT.
	A piñon pine, 4 ins. diam., bears N. 67° W., 35 lks. dist., mkd. X BT.
	Deposit a magnet at the base of the brass tablet.
79.00	Wash, 6 ft. wide, 1 ft. deep, drains N. 60° E.
80.00	Point for the cor. of secs. 14, 15, 22 and 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 15 S 14 S 22 S 23
	2005

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located at toe of slope and 5 chains N. of a ridge, bears SSE and NNW and 3 chains E. of same ridge.
	Land, rolling to broken. Vegetation, sage brush, scrub juniper, piñon pine and native grasses. Soil, sandstone and sandy clay.
	From the cor. of secs. 13, 14, 23 and 24.
	West, bet. secs. 14 and 23.
	Over rolling to broken land, dense sage brush and scattered juniper bush.
40.02	True point for the 1/4 sec. cor. of secs. 14 and 23, falls in a drainage, 4 ft. wide, 2 ft. deep, drains N. 45° E., where it is impractical to establish a permanent monument.
	From this true point, the point selected for an offline witness cor., bears S. 9°37' W., 28 lks. dist.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	$ \begin{array}{c} & \text{WC} \uparrow \\ & \text{T 41 N R 3 W} \\ & \text{S 14} \\ & 1/4 \frac{\text{S 23}}{\text{S 23}} \end{array} $
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. falls at toe of mesa, ascend.
80.04	The cor. of secs. 14, 15, 22 and 23.
	Land, rolling to broken. Vegetation, sage brush and native grasses. Soil, rocky and sandy.
	N. 0°01' W., bet. secs. 14 and 15.

Survey of the Subdivisional Lines, . 41 N.. R. 3 W., Gila and Salt River Meridian, Ari

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Over rolling to broken land, through dense sage brush and scattered juniper.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 15.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W 1/4
	S 15 S 14
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 10, 11, 14 and 15, falls on a sandstone outcrop.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in solid rock, with top mkd.
	T 41 N R 3 W S 10 S 11
	S 15 S 14
	2005
	Deposit a magnet at the base of the brass tablet.
	Land, rolling to broken. Vegetation, sage brush and native grasses. Soil, rocky and sandy.
	From the cor. of secs. 11, 12, 13 and 14.
	West, bet. secs. 11 and 14.
	Over broken to level land, through sage brush and native grasses.
40.02	Point for the 1/4 sec. cor. of secs. 11 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	Survey of the Subdivisional Lines, T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 41 N R 3 W
	1/4
	S 14
·	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
41.75	Graded road, 15 ft. wide, bears S. 70° E. and N. 70° W.
80.04	The cor. of secs. 10, 11, 14 and 15.
	Land, rolling to broken.
	Vegetation, sage brush and native grasses. Soil, rocky and sandy.
	N. 0°01' W., bet. secs. 10 and 11.
	Over broken land through sage brush and native grasses.
24.33	Graded road, 15 ft. wide, bears S. 45° E. and N. 45° W.
39.39	Graded road, 15 ft. wide, bears N. 35° E. and S. 35° W.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W
	1/4
	S 10 S 11
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
70.35	Graded road, 15 ft. wide, bears S. 85° E. and N. 85° W.
80.00	Point for the cor. of secs. 2, 3, 10 and 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines, T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 41 N R 3 W
	S 3 S 2
	S 10 S 11
,	
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located on the W. edge of a bladed road, 15 ft. wide, bears S. 20° E. and N. 20° W.
	Land, broken to level. Vegetation, sage brush and native grasses. Soil, sandy clay.
	From the cor. of secs. 1, 2, 11 and 12.
	West, bet. secs. 2 and 11.
	Over rolling land, through dense sage brush, native grasses and scattered scrub juniper.
40.02	Point for the 1/4 sec. cor. of secs. 2 and 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 2 1/4 S 11
	2005
	from which
	A forked juniper, 22 ins. diam., bears N. 27 1/2° E., 34 lks. dist., mkd. 1/4 S11 BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.87	Graded road, 15 ft. wide, bears S. 20° E. and N. 20° W.
80.04	The cor. of secs. 2, 3, 10 and 11.
	Land, rolling. Vegetation, sage brush and native grasses. Soil, rocky and sandy.

Survey of the Subdivisional Lines, T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	N. 0°02' W., bet. secs. 2 and 3.
	Over rolling land, through sage brush, native grasses and scattered cacti.
0.35	Graded road, 15 ft. wide, bears S. 20° E. and N. 20° W.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W
	s 3 s 2
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.22	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp.
	Land, rolling. Vegetation, sage brush, native grasses and cacti. Soil, rocky and sandy.
	From the stan. cor. of secs. 33 and 34, on the S. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, flush with the ground, with brass cap mkd. SC T41N R3W S33 S34 2004 1914.
	N. 0°02' W., bet. secs. 33 and 34.
	Over level land, through dense native grasses and scattered sage brush.
40.00	Point for the 1/4 sec. cor. of secs. 33 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W
	1/4
	S 33 S 34
	2005

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 27, 28, 33 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 28 S 27 S 33 S 34
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, level. Vegetation, native grasses and scattered sage brush. Soil, sandy clay.
	From the cor. of secs. 26, 27, 34 and 35.
	West, bet. secs. 27 and 34.
	Over level to broken land, through native grasses, scattered sage brush and various cacti.
40.05	Point for the 1/4 sec. cor. of secs. 27 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 27 1/4
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
69.42	Graded road, 15 ft. wide, bears S. 15° E. and N. 15° W.
80.10	The cor. of secs. 27, 28, 33 and 34.
	Land, level. Vegetation, native grasses and scattered sage brush.

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	Soil, sandy clay.
	N. 0°02' W., bet. secs. 27 and 28.
	Over rolling to broken land, through native grasses.
19.38	Graded road, 15 ft. wide, bears S. 40° E. and N. 40° W.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W 1/4
	S 28 S 27
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 21, 22, 27 and 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 21 S 22 S 28 S 27
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, level. Vegetation, native grasses and scattered sage brush. Soil, sandy clay.
	From the cor. of secs. 22, 23, 26 and 27.
	West, bet. secs. 22 and 27.
	Over broken land, through scattered juniper, piñon pine, sage brush and native grasses.
40.05	Point for the 1/4 sec. cor. of secs. 22 and 27.

Survey of the Subdivisional Lines, T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 22 1/4 —— S 27
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.10	The cor. of secs. 21, 22, 27 and 28.
	Land, level to broken. Vegetation, native grasses and scattered sage brush. Soil, sandy clay.
	N. 0°02' W., bet. secs. 21 and 22.
	Over rolling to broken, through sage brush, native grasses and juniper bushes.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W
	1/4 s 21 s 22
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	True point for the cor. of secs. 15, 16, 21 and 22.
	From this true point, a point mistakenly set in the field at the incorrect position for the cor. of secs. 15, 16, 21 and 22, which will now function as a point selected for a witness cor., bears N. 9°00' E., 0.02 chs. dist.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 41 N R 3 W
	<u>s 16 s 15</u>
Ì	S 21 S 22
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling to broken. Vegetation, sage brush and native grasses. Soil, rocky and sandy.
	From the cor. of secs. 14, 15, 22 and 23.
	West, bet. secs. 15 and 22.
	Over rolling to broken land, through medium growth sage brush and juniper.
40.05	Point for the 1/4 sec. cor. of secs. 15 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 15 1/4 S 22
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located on a spur, bears N. 40° E.
80.10	The cor. of secs. 15, 16, 21 and 22.
	Land, rolling to broken. Vegetation, sage brush and native grasses. Soil, rocky and sandy.
	N. 0°02' W., bet. secs. 15 and 16.
	Over broken land, through sage brush, native grasses and juniper.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16.

Survey of the Subdivisional Lines, T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona

·	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 41 N R 3 W 1/4 S 16 S 15
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 9, 10, 15 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 9 S 10 S 16 S 15
	2005
}	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling to broken. Vegetation, sage brush and native grasses. Soil, rocky and sandy.
	From the cor. of secs. 10, 11, 14 and 15.
	West, bet. secs. 10 and 15.
	Over rolling land, through scattered sage brush, and scrub juniper.
40.05	Point for the 1/4 sec. cor. of secs. 10 and 15.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines, I. 41 N., R. 3 W., Gila and Salt River Meridian. Arizona

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 41 N R 3 W
	1/4 = 10 1/4 = 1
	s 15
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.10	The cor. of secs. 9, 10, 15 and 16.
	Land, rolling. Vegetation, sage brush, native grasses and juniper. Soil, rocky and sandy.
	N. 0°02' W., bet. secs. 9 and 10.
	Over rolling land, through scattered juniper bush, medium growth sage brush and native grasses.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W
	1/4 S 9 S 10
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 3, 4, 9 and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 4 S 3 S 9 S 10
	2005
	from which

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	A piñon pine, 10 ins. diam., bears N. 84° E., 43 lks. dist., mkd. T41NR3W S10 BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling. Vegetation, sage brush, piñon pine and native grasses. Soil, sandy clay.
	From the cor. of secs. 2, 3, 10 and 11.
	West, bet. secs. 3 and 10.
	Over rolling land, through scattered scrub juniper.
30.35	Graded road, 15 ft. wide, bears S. 70° E. and N. 70° W.
40.05	Point for the $1/4$ sec. cor. of secs. 3 and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 3 1/4
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.10	The cor. of secs. 3, 4, 9 and 10.
	Land, rolling. Vegetation, sage brush, piñon pine and native grasses. Soil, sandy clay.
	N. 0°02' E., bet. secs. 3 and 4.
	Over rolling to level land, through scattered scrub juniper, medium growth sage brush and native grasses.
1.42	Graded road, 15 ft. wide, bears N. 75° E. and S. 75° W.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 41 N R 3 W
	1/4
	S 4 S 3
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.16	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp.
	Land, rolling. Vegetation, sage brush, piñon pine and native grasses. Soil, sandy clay.
	From the stan. cor. of secs. 32 and 33, on the S. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 13 ins. above the ground, with brass cap mkd. T41N SC R3W S32 S33 2004 1914.
	N. 0°03' W., bet. secs. 32 and 33.
	Over rolling to broken land, through native grasses and scattered cacti.
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	m 41 N D 2 W
	T 41 N R 3 W 1/4
	s 32 s 33
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	True point for the cor. of secs. 28, 29, 32 and 33, falls on E. face of extremely steep slope, where it is impractical to establish a permanent monument.
	From this true point, the point selected for an offline witness cor., bears S. 84°13' W., 3.97 chs. dist.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in solid rock, with top mkd.

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	WC
	T 41 N R 3 W
	S 29 S 28 ->
	s 32 s 33
	2005
	Deposit a magnet at the base of the brass tablet.
	Land, rolling to broken.
	Vegetation, sage brush, piñon pine and native grasses.
	Soil, sandy clay.
	From the cor. of secs. 27, 28, 33 and 34.
	<u> </u>
	West, bet. secs. 28 and 33.
	Over broken land, through scattered scrub juniper and piñon pine
	and native grasses.
40.02	Doint for the 1/4 cas can of case 20 and 22
40.02	Point for the 1/4 sec. cor. of secs. 28 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	24 ins. in the ground, with brass cap mkd.
	24 Ins. In the ground, with brass cap mkd.
	T 41 N R 3 W
	S 28
	1/4 ——
	s 33
	2005
	Deposit a magnet in a white plastic case at the base of the
	stainless steel post.
	Feet.
80.04	The cor. of secs. 28, 29, 32 and 33.
	, , =
1	Land, broken.
	Vegetation, sage brush, piñon pine and native grasses.
	Soil, sandy clay.
1	
1	
1	N. 0°03' W., bet. secs. 28 and 29.
	Over rolling land, through scrub juniper bush, sage brush and
	native grasses.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 29.

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W 1/4 S 29 S 28
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 20, 21, 28 and 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 20 S 21 S 29 S 28
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling. Vegetation, sage brush, piñon pine and native grasses. Soil, sandy clay.
	From the cor. of secs. 21, 22, 27 and 28.
	West, bet. secs. 21 and 28.
	Over rolling land, through dense sage brush and native grasses.
14.58	Graded Road, 15 ft. wide, bears S. 10° E. and N. 10° W.
40.02	Point for the 1/4 sec. cor. of secs. 21 and 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 21 1/4 S 28 2005

Survey of the Subdivisional Lines,
T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.04	The cor. of secs. 20, 21, 28 and 29.
	Land, rolling. Vegetation, sage brush, and native grasses. Soil, sandy clay.
	N. 0°03' W., bet. secs. 20 and 21.
	Over broken mountainous land, through scrub juniper and native grasses.
40.00	True point for the 1/4 sec. cor. of secs. 20 and 21, falls on N. face of steep rocky slope, where it is impractical to establish a permanent monument.
	From this true point, the point selected for an offline witness cor., bears N. 53°59' E., 1.90 chs. dist.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	WC
	T 41 N R 3 W
	1/4 _S 20 S 21
	∠ '
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located on a spur, bears S. 80° E.
80.00	Point for the cor. of secs. 16, 17, 20 and 21.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 17 S 16 S 20 S 21
	2005
	2000

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling to broken. Vegetation, sage brush, piñon pine and native grasses. Soil, sandy clay.
	From the cor. of secs. 15, 16, 21 and 22.
	West, bet. secs. 16 and 21.
	Over broken rocky land.
40.02	True point for the 1/4 sec. cor. of secs. 16 and 21, falls on a steep sandstone face, where it is impractical to establish a permanent monument.
	From this true point, the point selected for an offline witness cor., bears S. 32°27' W., 19 lks. dist.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in solid rock, with top mkd.
	WC T 41 N R 3 W 1/4 S 16 S 21
	2005
	from which
	A sandstone, 32 X 21 X 3 ft., bears S. 17 3/4° W., 71 lks. dist., mkd. X BO.
	Deposit a magnet at the base of the brass tablet.
80.04	The cor. of secs. 16, 17, 20 and 21.
	Land, broken and rocky. Vegetation, scrub juniper, native grasses. Soil, sandy clay and sandstone outcrops.
	N. 0°03' W., bet. secs. 16 and 17.
	Over rolling and broken land, through dense sage brush and native grasses, and scattered juniper.

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
40.00	Point for the 1/4 sec. cor. of secs. 16 and 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W 1/4 S 17 S 16
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 8, 9, 16 and 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 8 S 9 S 17 S 16
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling to broken. Vegetation, sage brush, piñon pine and native grasses. Soil, sandy clay.
	From the cor. of secs. 9, 10, 15 and 16.
	West, bet. secs. 9 and 16.
	Over rolling and broken land, through dense sage brush and native grasses, scattered juniper.
40.02	Point for the 1/4 sec. cor. of secs. 9 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
1	

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	T 41 N R 3 W S 9 1/4 —— S 16
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.04	The cor. of secs. 8, 9, 16 and 17.
	Land, rolling to broken. Vegetation, sage brush, piñon pine and native grasses. Soil, sandy clay.
	N. 0°03' W., bet. secs. 8 and 9.
	Over rolling to broken land, through dense sage brush and native grasses, scattered juniper.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W 1/4 S 8 S 9
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
74.82	Graded road, 15 ft. wide, bears N. 85° E. and S. 85° W.
80.00	Point for the cor. of secs. 4, 5, 8 and 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 5 S 4 S 8 S 9
	2005
1	

	Survey of the Subdivisional Lines, T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, level to broken. Vegetation, sage brush, piñon pine and native grasses. Soil, sandy clay.
	From the cor. of secs. 3, 4, 9 and 10.
	West, bet. secs. 4 and 9.
	Over rolling land, through native grasses and flowers, scattered cacti.
6.61	Graded road, 15 ft. wide, bears N. 80° E. and S. 80° W.
40.02	Point for the 1/4 sec. cor. of secs. 4 and 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W
	S 4
	1/4 ——— s 9
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.04	The cor. of secs. 4, 5, 8 and 9.
	Land, rolling. Vegetation, sage brush, flowers and native grasses. Soil, caliche.
	N. 0°03' E., bet. secs. 4 and 5.
	Over level land, through medium growth sage brush, native grasses and scattered scrub juniper.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	T 41 N R 3 W 1/4 S 5 S 4
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.09	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp.
	Land, level. Vegetation, sage brush, flowers and native grasses. Soil, caliche.
	From the stan. cor. of secs. 31 and 32, on the S. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 15 ins. above the ground, with brass cap mkd. T41N SC S31 R3W S32 2003 2004 1914.
	N. 0°03' W., bet. secs. 31 and 32.
	Over broken to level land, through sage brush and scattered scrub juniper.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W 1/4 S 31 S 32
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 29, 30, 31 and 32, falls on a sandstone shelf.
·	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in solid rock, with top mkd.

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 41 N R 3 W
	<u>s 30 s 29</u>
	s 31 s 32
	2005
	from which
	Trom willon
	A piñon pine, 4 ins. diam., bears N. 61 1/2° E., 81 lks. dist., mkd. X BT.
	A piñon pine, 4 ins. diam., bears S. 62 1/2° E., 95 lks. dist., mkd. X BT.
	A piñon pine, 4 ins. diam., bears S. 23° W., 64 lks. dist., mkd. X BT.
	A piñon pine, 4 ins. diam., bears N. 46 3/4° W., 54 lks. dist., mkd. X BT.
	Deposit a magnet at the base of the brass tablet.
	Land, broken. Vegetation, piñon pine, sage brush, native grasses and cacti. Soil, sandstone and caliche.
	From the cor. of secs. 28, 29, 32 and 33.
	S. 89°59' W., bet. secs. 29 and 32.
	Over broken mountainous land, through scattered scrub juniper and native grasses.
40.02	True point for the 1/4 sec. cor. of secs. 29 and 32, falls on the E. face of a steep slope, where it is impractical to establish a permanent monument.
	From this true point, the point selected for an offline witness cor., bears N. 78°51' E., 4.28 chs. dist.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	WC T 41 N R 3 W S 29 1/4 =
	2005

	Survey of the Subdivisional Lines,
CHAINS	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located on a sandy spur, bears S. 90° E.
80.04	The cor. of secs. 29, 30, 31 and 32.
	Land, mountainous. vegetation, scrub juniper and native grasses Soil, caliche.
	West, bet. secs. 30 and 31.
	Over rolling to broken land, through medium growth scrub juniper and piñon pine.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W
	s 30 1/4 ——
	s 31
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.97	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T41N R4W R3W S25 S30 S36 S31 2003.
	From the cor. of secs. 29, 30, 31 and 32.
	N. 0°03' W., bet. secs. 29 and 30.
	Over rolling land, through medium growth scrub piñon pine, juniper, native grasses and scattered cacti.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a supporting mound of stone, 3 ft. base, to top, with brass cap mkd.

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 41 N R 3 W 1/4
	s 30 s 29
	2005
	from which
	A sandstone, 10 X 9.5 X 2.5 ft. high, bears N. 43 1/4° E., 18 lks. dist., mkd. X BO.
	A sandstone, 10 X 6 X 3 ft. high, bears S. 43 1/4° E., 26 lks. dist., mkd. X BO.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Over broken land.
80.00	Point for the cor. of secs. 19, 20, 29 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 19 S 20 S 30 S 29
	2005
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, rolling to broken. Vegetation, piñon pine, scrub juniper, sage brush, cacti and native grasses. Soil, sandy and rocky.
	From the cor. of secs. 20, 21, 28 and 29.
	S. 89°59' W., bet. secs. 20 and 29.
	Over broken land, through scattered juniper bush, sage brush and native grasses.
40.02	True point for the 1/4 sec. cor. of secs. 20 and 29, falls on a steep slope, where it is impractical to establish a permanent monument.

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	From this true point, the point selected for an offline witness cor. bears N. 25°43' W., 17 lks. dist.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in solid rock, with top mkd.
	WC
	T 41 N R 3 W S 20
	1/4 —— S 29
	2005
	Deposit a magnet at the base of the brass tablet.
80.04	The cor. of secs. 19, 20, 29 and 30.
	Land, rolling to broken. Vegetation, piñon pine, scrub juniper, sage brush, cacti and native grasses. Soil, sandy and rocky.
	West, bet. secs. 19 and 30.
	Over broken land, through scattered scrub juniper, piñon pine and sandstone surfaces.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in solid rock, with top mkd.
	T 41 N R 3 W
	2005
	from which
	A sandstone, 17 X 5 X 1.7 ft. high, bears N. 41 1/2° E., 47 lks. dist., mkd. X BO.
	Deposit a magnet at the base of the brass tablet.

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
79.88	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with a stainless steel pipe, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T41N R4W R3W S24 S19 S25 S30 2003.
	Land, broken. Vegetation, scattered scrub juniper, piñon pine. Soil, sandstone.
	From the cor. of secs. 19, 20, 29 and 30.
	N. 0°03' W., bet. secs. 19 and 20.
	Over broken land, through scattered piñon and juniper bush.
40.00	True point for the 1/4 sec. cor. of secs. 19 and 20, falls on the right edge of a drainage, 18 ft. wide, 2 ft. deep, drains N. 45° E., where it is impractical to establish a permanent monument.
	From this true point, the point selected for an offline witness cor. bears N. 37°50' W., 50 lks. dist.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in a sandstone, 6.75 X 3 X 2.6 ft. high, with top mkd.
	WC T 41 N R 3 W
	1/4 s 19 s 20
	2005
•	Deposit a magnet at the base of the brass tablet.
80.00	True point for the cor. of secs. 17, 18, 19 and 20, falls at the intersection of sandy washes, 145 ft. wide , 2 ft. deep, draining S. 8° E. and S. 70° E., where it is impractical to establish a permanent monument.
	From this true point, the point selected for an offline witness cor. bears S. 80°04' E., 65 lks. dist.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona						
CHAINS							
	WC T 41 N R 3 W						
	S 18 S 17						
	s 19 s 20						
	2005						
	Deposit a magnet in a white plastic case at the base of the stainless steel post.						
	Land, broken. Vegetation, scattered scrub juniper, piñon pine. Soil, sandy.						
	From the cor. of secs. 16, 17, 20 and 21.						
	S. 89°59' W., bet. secs. 17 and 20.						
	Over rolling land, through medium growth juniper and sage.						
40.02	Point for the 1/4 sec. cor. of secs. 17 and 20.						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.						
	T 41 N R 3 W S 17 1/4						
	2005						
	from which						
	A piñon pine, 11 ins. diam., bears N. 37 3/4° W., 8 lks. dist., mkd. 1/4 S 17 BT.						
	Deposit a magnet in a white plastic case at the base of the stainless steel post.						
80.04	The cor. of secs. 17, 18, 19 and 20.						
	Land, rolling. Vegetation, piñon pine, juniper and sage brush. Soil, sandy clay.						
	West, bet. secs. 18 and 19.						

		Surve	? of	the	Subc	livis	ional	Lines	•		
T.	41	N R	. 3	W	Gila	and	Salt	River	Meridian.	Arizona	

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Over rough broken land, through scattered scrub oak, juniper and piñon pine.
40.00	True point for the 1/4 sec. cor. of secs. 18 and 19, falls in a drainage, 4 ft. wide, 1 ft. deep, draining S. 85° W., where it is impractical to establish a permanent monument.
	From this true point, the point selected for an offline witness cor. bears S. 6°40' E., 12 lks. dist.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in solid rock, with top mkd.
	T 41 N R 3 W S 18
	1/4 —— S 19
	2005
	Deposit a magnet at the base of the brass tablet.
79.79	The true point for the cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., falls in drain, 300 ft. wide, 100 ft. deep, determined at record bearing and dist. from the 2003 witness cor.
	From this true point, the witness cor. to the cor. of secs. 13, 18, 19 and 24, bears N. 41°55' W., 4.23 chs. dist., monumented with a brass tablet, 3 1/4 ins. diam., set flush in a drill hole in a solid rock, 50 x 25 x 10 ft. high, with top mkd. WC T41N R4W R3W S13 S18 S24 S19 2003, with an arrow pointing to the true cor. position.
	Land, rough and broken. Vegetation, scrub oak, juniper and piñon pine. Soil, sandstone, sandy clay.
	From the cor. of secs. 17, 18, 19 and 20.
	N. 0°03' W., bet. secs. 17 and 18.
	Over broken land, through dense sage brush, native grasses and juniper.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 18, falls on a sandstone surface.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, cemented in a drill hole in solid rock, with top mkd.

Survey of the Subdivisional Lines, T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona						
CHAINS							
	T 41 N R 3 W						
•	1/4						
	s 18 s 17						
ı							
	2005						
	from which						
	A piñon pine, 10 ins. diam., bears N. 28 1/4° E., 33 lks. dist., mkd. 1/4 S17 BT.						
	A piñon pine, 4 ins. diam., bears S. 57 1/2° W., 20 lks. dist., mkd. X BT.						
	Deposit a magnet at the base of the brass tablet.						
64.03	Graded road, 15 ft. wide, bears S. 60° E. and N. 60° W.						
80.00	True point for the cor. of secs. 7, 8, 17 and 18, falls in a						
	wash, 3 ft. wide, 8 ins. deep, drains S. 5° W., where it is impractical to establish a permanent monument.						
	From this true point the point colored for an affiliar with an						
	From this true point, the point selected for an offline witness cor., bears N. 46°15' E., 37 lks. dist.						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.						
	WC						
	T 41 N R 3 W						
	<u>s 7 s 8</u>						
	S 18 S 17						
	2005						
	Deposit a magnet in a white plastic case at the base of the stainless steel post.						
	Land, broken to rolling and level.						
	Vegetation, sage brush, native grasses and juniper. Soil, sandy clay.						
l							
	From the cor. of secs. 8, 9, 16 and 17.						
	S. 89°59' W., bet. secs. 8 and 17.						
	Over level to rolling land, through scattered sage brush, dense native grasses and scattered scrub juniper.						

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
22.12	Graded road, 15 ft. wide, bears N. 10° E. and S. 10° W.
40.02	Point for the 1/4 sec. cor. of secs. 8 and 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 8 1/4
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.04	The true point for the cor. of secs. 7, 8, 17 and 18.
	Land, level to rolling. Vegetation, sage brush, native grasses and juniper. Soil, sandy clay.
	West, bet. secs. 7 and 18.
	Over level to rolling land, through dense sage brush, native grasses and scattered juniper bush.
14.25	Graded road, 12 ft. wide, bears S. 25° E. and N. 25° W.
21.71	Graded road, 12 ft. wide, bears S. 15° E. and N. 15° W.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
:	T 41 N R 3 W
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
79.70	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground with brass cap mkd. T41N R4W R3W S12 S7 S13 S18 2003.
	Land, level to rolling. Vegetation, sage brush, native grasses and juniper bush. Soil, sandy clay.
	From the true point for the cor. of secs. 7, 8, 17 and 18.
	N. 0°03' W., bet. secs. 7 and 8.
	Over level land,, through dense sage brush and native grasses.
19.70	Graded road, 12 ft. wide, bears N. 65° E. and S. 65° W.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W 1/4 S 7 S 8
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.00	Point for the cor. of secs. 5, 6, 7 and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 6 S 5 S 7 S 8
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Land, level. Vegetation, sage brush, native grasses and scrub juniper. Soil, sandy clay.

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	From the cor. of secs. 4, 5, 8 and 9.
	S. 89°59' W., bet. secs. 5 and 8.
	Over level to rolling land, through scattered scrub juniper, piñon pine and sage brush.
37.77	Graded road, 12 ft. wide, bears N. 10° E. and S. 10° W.
40.02	Point for the 1/4 sec. cor. of secs. 5 and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 5
	1/4 S 8
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
77.69	Graded road, 12 ft. wide, bears S. 20° E. and N. 20° W.
80.04	The cor. of secs. 5, 6, 7 and 8.
	Land, level to rolling. Vegetation, scrub juniper, piñon pine and sage brush. Soil, sandy clay.
	S. 89°59' W., bet. secs. 6 and 7.
	Over rolling land, through sage brush, scattered scrub juniper and piñon pine.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W S 6 1/4 ——
	s 7
	2005

	T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.60	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. T41N R4W R3W S1 S6 S12 S7 2003.
	Land, rolling to level. Vegetation, sage brush, native grasses and scrub juniper. Soil, sandy clay.
	From the cor. of secs. 5, 6, 7 and 8.
	N. 0°04' E., bet. secs. 5 and 6.
	Over level ground, gradually ascending, through scattered scrub juniper, dense sage brush and native grasses.
8.01	Graded road, 12 ft. wide, bears S. 35° E. and N. 35° W.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 6.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 N R 3 W
	1/4 s 6 s 5
	2005
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.05	The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp.
	Land, level. Vegetation, native grasses, sage brush and scrub juniper. Soil, sandy clay.

T. 41 N., R. 3 W., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The area surveyed is within the Kaibab Paiute Indian reservation. The terrain is level to broken and mountainous. The drainage is southerly, with Cottonwood Creek and Canyon Wash being the principal drainages. Six Mile Village is located in sections 11 and 12.

The elevation varies from 4500 ft. to 6300 ft. The soil is mostly sandy with some sandstone outcrops scattered through out the Tp. Vegetation consists mostly of sage brush, native grasses, scattered cacti and scrub juniper and piñon pine.

Principal access to the township is provided by State Highway No. 389. There are various trail roads through out the Tp.

The mean magnetic declination of 12 $1/4^{\circ}$ E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2005 for the dates of survey.

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

ETEND A	ASSISTANTS
NAMES	CAPACITY
Joseph R. Salazar	Land Surveyor
Michelle M. Meece	Land Surveyor-in-Training
Nathan F. Allen	Surveying Technician
Gene L. Staples	Surveying Technician
Charles E. Wright	Surveying Technician

CERTIFICATE OF SURVEY

I, W. William Foster, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 5th day of May, 2005, I have dependently resurveyed the east boundary and surveyed the north boundary and the subdivisional lines, T. 41 N., R. 3 W., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and in specific manner described in the foregoing field notes.

5/01/06	W. Wellin Fosk
(Date)	(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the east boundary and the survey of the north boundary and the subdivisional lines, T. 41 N., R. 3 W., Gila and Salt River Meridian, in the State of Arizona, executed by W. William Foster, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

5/09/06 (Date)	Steplen K. Hansen (Chief Cadastral Surveyor of Arizona)
	-CERTIFICATE OF TRANSCRIPT
described surveys in T.	going transcript of the field notes of the above 41 N., R. 3 W., Gila and Salt River Meridian,
Arizona, is a true copy of	(Chief Gadagtral Surveyor of Arizona)