ORIGINAL

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SECOND GUIDE MERIDIAN WEST (EAST BOUNDARY),

A PORTION OF THE SOUTH BOUNDARY

AND A PORTION OF THE SUBDIVISIONAL LINES

AND THE

METES-AND-BOUNDS SURVEY OF THE MOUNT LOGAN WILDERNESS AREA BOUNDARY,

TOWNSHIP 34 NORTH, RANGE 9 WEST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA.

EXECUTED BY

Gordon R. Bubel and Geoffrey A. Graham, Cadastral Surveyors

Under Special Instructions dated August 31, 1998, approved August 31, 1998, which provided for the surveys included under Group No. 833, and assignment instructions dated August 31, 1998 and May 29, 2003.

Survey commenced September 8, 1998
Survey completed October 26, 2003

INDEX DIAGRAM

TOWNSHIP 34 NORTH RANGE 9 WEST GILA AND SALT RIVER MERIDIAN, ARIZONA

	T		γ		
6	5	4	3	2	1
_	_	_		17	13
7	8	9	10	15 11	12
			19		13
18	17	16	15	14	13
19	20	23 21	22	23	24 4
		21	18	4.4	11
30	29	28	17 27	14 26	9 25
					8
31	32	33	34	35	36
					6

Metes-and-Bounds Survey of the MLWA Bdy. Pages 24-92

T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion the Second Guide Meridian West (East boundary), a portion of the south boundary and a portion of the subdivisional lines and the mete-and-bounds survey of the Mount Logan Wilderness Area Boundary, Township 34 North, Range 9 West, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Dupree R. Averill and William E. Hiester surveyed the Second Guide Meridian West (east boundary), the south, west and north boundaries in 1917, and the subdivisional lines in 1917-21.

The survey was executed in accordance with the specifications as set forth in the <u>Manual of Instructions for the Survey of the Public Lands of the United States, 1973</u>, and the Special Instructions dated August 31, 1998, for Group No. 833, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Sokkia SetIIB2 total station and Trimble Navigation 4400, 5700 and 5800 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static post observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) KING KINGMAN CORS ARP, FRED FREDONIA CORS ARP and FERN FERNO MESA CORS ARP. The NAD 83 (CORS96) (EPOCH:2002), geographic position of the cor. of sections 25, 26, 35 and 36 is as follows:

Latitude: 36°18'37.16" N. Longitude: 113°13'05.31" W.

The mean magnetic declination is 13° E.

Dependent Resurvey of a Portion of the Second Guide Meridian West (East Boundary), T. 34 N., R. 9 E., Gila and Salt River Meridian, Arizona

Restoring the survey executed by Dupree R. Averill and William E. Hiester, in 1917

Dependent Resurvey of a Portion of the Second Guide Meridian West (East Boundary.),

T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona

	The state of the s
CHAINS	
	Beginning at the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. T34N R9W R8W S24 S19 S25 S30 1917.
	from which the remaining original bearing trees
	A piñon, 12 ins. diam., bears N. 63 1/2° E., 80 lks.

- A piñon, 12 ins. diam., bears N. 63 1/2° E., 80 lks. dist., with scribe marks T34NR8WS19BT visible on an unhealed blaze. (Record, N. 75 1/4° E., 86 lks. dist.)
- A piñon, 10 ins. diam., bears S. 61 1/2° W., 60 lks. dist., with scribe marks T34NR8WS25BT visible on an unhealed blaze. (Record, S. 58° W., 57 lks. dist.)

Add the marks 1999 to the brass cap.

N. 0°02' W., bet. secs. 19 and 24.

4.18 Point for AP 6, sec. 24, identical with AP 54, sec. 19, T. 34 N., R. 8 W., on the Mount Logan Wilderness Area Bdy.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

1999

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Leave the Mount Logan Wilderness Area.

Point for AP 5, sec. 24, identical with AP 1, sec. 19, T. 34 N., R. 8 W., on the Mount Logan Wilderness Area Bdy.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Second Guide Meridian West (East Boundary.),

T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona

CHAINS

T 34 N
R 9 W R 8 W
ML WA

AP 5 AP 1
S 24 S 19

1999

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Enter the Mount Logan Wilderness Area.

39.95

The 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. 1/4 S24 S19 1917.

from which

- A juniper, 24 ins. diam., bears N. 48 1/2° E., 61 lks. dist., with scribe marks 1/4 S19BT visible on an unhealed blaze.
- A juniper, 10 ins. diam., bears S. 34 1/2° W., 22 lks. dist., with scribe marks 1/4 S24BT visible on a partly healed blaze.

Add the marks T34N R9W R8W 1999 to the brass cap.

From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 36 ins. above ground, in a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, with brass cap mkd. 1/4 S13 S18 1917.

from which the original bearing trees

- A pine, 30 ins. diam., bears N. 23° E., 43 lks. dist., with healed blaze.
- A pine, 30 ins. diam., bears S. 82 1/2° W., 57 lks. dist., with healed blaze.

Add the marks T34N R9W R8W 1998 to the brass cap.

N. 0°01' W., bet. secs. 13 and 18.

Over mountainous land, through medium pine timber.

8.40


Point for AP 1, sec. 13, identical with AP 33, sec. 18, T. 34 N., R. 8 W., on the Mount Logan Wilderness Area Bdy.

Dependent Resurvey of a Portion of the Second Guide Meridian West (East Boundary.),

T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona

CHAINS

Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, encircled with a collar, with aluminum cap mkd.



1999

Leave the Mount Logan Wilderness Area.

39.99

The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T34N R9W R8W S12 S7 S13 S18 1917.

from which

- A pine, 36 ins. diam., bears N. 57 1/2° E., 1.03 chs. dist., with healed blaze.
- A pine stump, 34 ins. diam., bears S. 26 $1/2^{\circ}$ W., 54 lks. dist.
- A pine, 42 ins. diam., bears N. 54° W., 2.68 chs. dist., with illegible scribe marks visible on partially open blaze. (Record, 186 lks. dist.)

Add the marks 1998 to the brass cap.

Dependent Resurvey of a Portion of the South Boundary, T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona

Restoring the survey executed by Dupree R. Averill and William E. Hiester, in 1917

From the cor. of Tps. 33 and 34 N., Rs. 8 and 9 W., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. T34N R9W R8W S36 S31 S1 S6 T33N 1917.

from which the remains of the original bearing trees

A juniper, 13 ins. diam., bears N. 66° E., 1.59 chs. dist., with scribe marks T34NR8WS31BT visible on partially healed blaze. (Record, N. 71° E.)

Dependent Resurvey of a Portion of the South Boundary, T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona

CHAINS

- A juniper, 10 ins. diam., bears S. 33 1/4° E., 1.18 chs. dist., with scribe marks T33NR8WS6BT visible on partially healed blaze. (Record, S. 36° E.)
- A dead and down juniper, 22 ins. diam., bears S. 55 1/2° W., 37 lks. dist., with scribe mark S visible on weathered blaze. (Record, S. 50° W., 33 lks. dist.)
- A dead and down juniper, 11 ins. diam., bears N. 55 1/2° W., 1.21 chs. dist., with scribe marks T33NR9WS BT visible on weathered blaze. (Record, N. 53 3/4° W., 116 lks. dist.)

Add the marks 2003 to the brass cap.

S. 89°47' W., bet. secs. 1 and 36.

23.74

Point for AP 14, sec. 36, identical with AP 1, sec. 1, T. 33 N., R. 9 W. on the Mount Logan Wilderness Area Bdy. on the 5200 ft. contour.

Set an aluminum drive rod, 3/4 in. diam., 30 ins. long, 22 ins. in the ground to refusal, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.

Leave the Mount Logan Wilderness Area.

40.15

The 1/4 sec. cor. of secs. 1 and 36, monumented with a bent iron post, 1 in. diam., firmly set, with brass cap mkd. 1/4 S36 S1 1917.

from which the remains of the original bearing tree

A dead and down juniper, 6 ins. diam., bears N. 22° E., 22 lks. dist., with illegible scribe marks visible on an extremely weathered blaze. (Record, piñon, N. 18 1/2° E., 19 lks. dist.)

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the South Boundary, T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona

CHAINS

T 34 N R 9 W S 36 1/4 S 1 T 33 N

2003

Deposit a magnet in a white plastic case at the base and the iron post, 36 ins. long, alongside the stainless steel post.

S. 89°58' W., beginning new measurement.

39.86

The cor. of secs. 1, 2, 35 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd. T34N R9W S35 S36 S2 S1 T33N 1917.

from which the remains of the original bearing trees

- A dead and down juniper, 12 ins. diam., bears N. 24 1/2° E., 3.27 chs. dist., with scribe marks S3 visible on an extremely weathered blaze.
- A dead and down juniper, 18 ins. diam., bears S. 2° E., 1.27 chs. dist., no scribe marks visible on weathered blaze. (Record, S. 23° E.)

Add the marks 2003 to the brass cap.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona

Restoring the survey executed by Dupree R. Averill and William E. Hiester, in 1917-21

From the 1/4 sec. cor. of secs. 25 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 20 ins. above ground, in a scattered mound of stone, with brass cap mkd. 1/4 S25 S36 1917.

from which the original bearing trees

- A juniper, 14 ins. diam., bears N. 8 1/2° E., 44 lks. dist., with illegible scribe marks visible on partially healed blaze. (Record: N. 4 1/2° E.)
- A juniper, 16 ins. diam., bears S. 23 1/4° W., 1.92 chs. dist., with a healed blaze.

Dependent Resurvey of a Portion of the Subdivisional Lines,

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Add the marks T34N R9W 2003 to the brass cap. Rebuild mound of stone, 3 ft. base, 1 1/2 ft. high. S. 89°51' W., bet. secs. 25 and 36.
18.52	Point for AP 1, sec. 36, identical with AP 39, sec. 25, on the Mount Logan Wilderness Area Bdy. on the 5200 ft. contour.
	Set an aluminum drive rod, 38 ins. long, 3/4 in. diam., 24 ins. in the ground to refusal, in a mound of stone, 4 ft. base, to top, with aluminum cap mkd.
	T 34 N R 9 W S 25 AP 39 M L S 36 AP 1 W A 2003
	Raise mound of stone, 4 ft. base to top.
	Leave the Mount Logan Wilderness Area.
40.09	The cor. of secs. 25, 26, 35 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 30 ins. above ground in a scattered mound of stone, with brass cap mkd. T34N R9W S26 S25 S35 S36 1917.
,	Add the marks 1999 to the brass cap.
	Rebuild mound of stone, 4 1/2 ft. base, to top.
	N. 0°04' W., bet. secs. 25 and 26.
40.13	The 1/4 sec. cor. of secs. 25 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 20 ins. above ground in a scattered mound of stone, with brass cap mkd. 1/4 S26 S25 1917.
	from which the original bearing trees
	A forked juniper, 24 ins. diam. at base, bears N. 52 1/2° E., 1.48 chs. dist., with scribe marks 1/4 S25BT visible on open blaze on a 10 inch diam. limb.
	A juniper, 14 ins. diam., bears S. 23 1/4° W., 1.06 chs. dist., with healed blaze. (Record: S. 27° W., 102 lks. dist.)
	Add the marks T34N R9W 1999 to the brass cap.

Dependent Resurvey of a Portion of the Subdivisional Lines,


T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona CHAINS

Rebuild mound of stone, 3 1/2 ft. base, to top.

N. 0°05' W., beginning new measurement.

4.51 Point for AP 1, sec. 25, identical with AP 28, sec. 26, on the Mount Logan Wilderness Area Bdy. on the 5200 ft. contour.

> Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.



2003

Enter the Mount Logan Wilderness Area.

40.14 The cor. of secs. 23, 24, 25 and 26, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above ground in a scattered mound of stone, with brass cap mkd. T34N R9W S23 S24 S26 S25 1917.

from which the original bearing trees

- A juniper, 13 ins. diam., bears N. 29 3/4° E., 1.54 chs. dist., with scribe marks T34NR9WS24BT visible on partially healed blaze. (Record, N. 31 1/2° E.)
- A juniper, 12 ins. diam., bears S. 74 1/4° E., 2.14 chs. dist., with scribe marks T34NR9WS25BT visible on partially healed blaze. (Record, S. 72° E.)
- A juniper, 29 ins. diam. at base, bears S. 66° W., 1.89 chs. dist., with scribe marks T34NR9WS26BT visible on partially healed blaze on a 7 inch diam. limb. (Record, S. 68° W.)
- A piñon, 9 ins. diam., bears N. 76 3/4° W., 2.52 chs. dist., with scribe marks T34NR9WS23BT visible on partially healed blaze. (Record, N. 75 1/2° W.)

Add the marks 2003 to the brass cap.

Rebuild mound of stone, 5 ft. base, to top.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the Tp., hereinbefore described.
	N. 89°49' W., bet. secs. 24 and 25.
2.95	Point for AP 7, sec. 24, identical with AP 16, sec. 25, on the Mount Logan Wilderness Area Bdy.
	Set an aluminum drive rod, 35 ins. long, 3/4 in. diam., 30 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
	S 24
	s 25 AP 16 MLWA
	2003
	Cor. is located on the southerly offset from BLM road 1023.
·	Leave the Mount Logan Wilderness Area.
5.96	Point for AP 18, sec. 25, on the Mount Logan Wilderness Area Bdy.
	Set an aluminum drive rod, 29 ins. long, 3/4 in. diam., 26 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
	S 24
	AP 18 S 25 MLWA
	2003
	Cor. is located on the southerly offset from BLM road 1023.
	Thence, continue on a portion of the Mount Logan Wilderness Area Bdy.
14.29	Point for AP 19, sec. 25, on the Mount Logan Wilderness Area Bdy.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	<u> </u>
	S 25 AP 19 MLWA
	2003
	Cor. is located on the southeasterly offset from BLM road 1023.
	Leave the Mount Logan Wilderness Area.
15.28	Point for AP 1, sec. 24, identical with AP 15, sec. 25, on the Mount Logan Wilderness Area Bdy.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	M L AP 1 \ S 24
	W AP 15 / S 25
	A / 2003
	Cor. is located on the westerly offset from BLM road 1023.
	Enter the Mount Logan Wilderness Area.
40.20	The 1/4 sec. cor. of secs. 24 and 25, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, with brass cap mkd. 1/4 S24 S25 1917.
	from which the original bearing trees
	A piñon, 13 ins. diam., bears N. 38° E., 95 lks. dist., with scribe marks 1/4 S24BT visible on partially healed blaze.
	A piñon, 16 ins. diam., bears S. 31° E., 1.01 chs. dist., with scribe marks S25B visible through pitch covered blaze.
	At the corner point
	Reset the iron post, 36 ins. long, 26 ins. in the ground, in a mound of stone, 3 ft. base, to top.
	Add the marks T34N R9W 2003 to the brass cap.
·	

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	N. 89°55' W., beginning new measurement.
40.14	The cor. of secs. 23, 24, 25 and 26.
	From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.
	N. 89°44' W., bet. secs. 12 and 13.
	Over rolling and mountainous land, through heavy pine timber.
11.80	Point for AP 1, sec. 12, identical with AP 15, sec. 13, on the Mount Logan Wilderness Area Bdy.
	Not monumented.
	Enter the Mount Logan Wilderness Area.
40.20	The 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. 1/4 S12 S13 1921.
	from which the remaining original bearing tree
	A pine, 16 ins. diam., bears N. 0 3/4° W., 72 lks. dist., with healed blaze. (Record, N. 2° E.)
	Add the marks T34N R9W 1999 to the brass cap.
	From the witness cor. to the 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. 1/4 WC S11 S12 1921.
	Add the marks T34N R9W 1999 to the brass cap.
	N. 0°05' E., bet. secs. 11 and 12.
	Ascend over badlands.
0.99	True point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate dist.; falls on the face of W. sloping spur, where it is impracticable to establish a permanent monument.
37.49	Point for AP 1, sec. 11, identical with AP 22, sec. 12, on the Mount Logan Wilderness Area Bdy.
	Not monumented.
	Leave the Mount Logan Wilderness Area.

	Dependent Resurvey of a Portion of the Subdivisional Lines, T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona				
CHAINS					
40.76	The cor. of secs. 1, 2, 11 and 12, monumented with an iron post, 2 ins. diam., firmly set, projecting 20 ins. above ground, in a scattered mound of stone, with brass cap mkd. T34N R9W S2 S1 S11 S12 1921.				
	from which the remaining original bearing trees				
	A pine, 36 ins. diam., bears N. 53° E., 1.12 chs. dist., with illegible scribe marks visible on partially open blaze.				
	A pine, 30 ins. diam., bears S. 48 1/4° W., 1.78 chs. dist., with healed blaze. (Record: 181 lks.)				
	Add the marks 1999 to the brass cap.				
	Rebuild mound of stone, 4 ft. base, to top.				
	From the 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd. 1/4 S27 S26 1921.				
	from which				
	A juniper, 22 ins. diam. at base, bears S. 36 1/2° E., 1.54 chs. dist., with scribe marks 1/4 S26BT visible on weathered blaze on a 10 inch diam. limb.				
	A juniper, 7 ins. diam., bears N. 83 3/4° W., 14 lks. dist., with scribe marks 1/4 S27BT visible on weathered blaze.				
	Add the marks T34N R9W 2003 to the brass cap.				
	N. 0°05' E., bet. secs. 26 and 27.				
33.23	Point for AP 1, sec. 26, identical with AP 16, sec. 27, on the Mount Logan Wilderness Area Bdy., on the 5200 ft. contour.				
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.				
	T 34 N R 9 W MLWA AP 16 AP 1				
	s 27 s 26				
	2003				

Enter the Mount Logan Wilderness Area.

Dependent Resurvey of a Portion of the Subdivisional Lines,

T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona CHAINS

40.04

The cor. of secs. 22, 23, 26 and 27, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above a mound of stone, 4 ft. base, 1 ft. high, with brass cap mkd. T34N R9W S22 S23 S27 S26 1921.

from which the original bearing trees

- A juniper, 20 ins. diam. at base, bears N. 33 1/2° E., 68 lks. dist., with scribe marks R9WS23BT visible on shattered blaze on a 7 inch diam. limb.
- A juniper, 30 ins. diam. at base, bears S. 23 1/2° E., 45 lks. dist., with scribe marks T34NR9WS26BT visible on partially healed blaze on an 11 inch diam. limb.
- A juniper, 24 ins. diam. at base, bears S. 44 1/2° W., 34 lks. dist., with scribe marks T34NR9WS27BT visible on partially healed blaze on a 7 inch diam. limb.
- A juniper, 15 ins. diam., bears N. 86° W., 1.45 chs. dist., with scribe marks T34NR9WS22BT visible on partially healed blaze.

Add the marks 2003 to the brass cap.

Rebuild mound of stone, 4 ft. base, 1 1/2 ft. high.

From the cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2 ins. diam., firmly set, projecting 22 ins. above ground, in a scattered mound of stone, with brass cap mkd. T34N R9W S10 S11 S15 S14 1921.

from which the remains of the original bearing trees

- A pine, 11 ins. diam., bears N. 33 1/2° E., 22 lks. dist., with illegible scribe marks visible on partially open blaze.
- A pine, 15 ins. diam., bears S. 9 3/4° E., 97 lks. dist., with scribe marks T34NR9WS14BT visible on partially open blaze.
- A pine stump, 13 ins. diam., bears S. 62 1/2° W., 25 lks. dist., with scribe marks 4NR9WS15BT visible on an open blaze.

Add the marks 1999 to the brass cap.

Rebuild mound of stone, 3 1/2 ft. base, 2 ft. high.

Cor. is located in a barbed wire fence, bears E. and W.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	N. 0°01' E., bet. secs. 10 and 11. Over mountainous land, through heavy timber.
39.98	The 1/4 sec. cor. of secs. 10 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 25 ins. above ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd. 1/4 S10 S11 1921.
	from which
	An oak, 11 ins. diam., bears S. 83° E., 57 lks. dist., with healed blaze.
	A juniper, 26 ins. diam., bears N. 26 1/4° W., 26 lks. dist., with healed blaze.
	Add the marks T34N R9W 1999 to the brass cap.
	N. 0°02' W., beginning new measurement.
23.84	Point for AP 1, sec. 10, identical with AP 11, sec. 11, on the Mount Logan Wilderness Area Bdy.
	Not monumented.
	Leave the Mount Logan Wilderness Area.
39.97	The cor. of secs. 2, 3, 10 and 11, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above ground, in a scattered mound of stone, with a stone, 8 X 7 ins., firmly set, projecting 10 ins. above ground, mkd. with an X on top, along N. side, with brass cap mkd. T34N R9W S3 S2 S10 S11 1921.
	from which the original bearing trees
	A pine, 16 ins. diam., bears N. 50 1/2° E., 68 lks. dist., with healed blaze.
	A juniper, 11 ins. diam., bears S. 46 1/2° E., 29 lks. dist., with illegible scribe marks visible on partially open blaze. (Record, 31 lks. dist.)
	A pine, 30 ins. diam., bears S. 66° W., 2.58 chs. dist., with healed blaze. (Record, 261 lks. dist.)
	Add the marks 1999 to the brass cap.
	Rebuild mound of stone, 4 1/2 ft. base, to top.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	From the cor. of secs. 1, 2, 11 and 12.
	S. 89°58' W., bet. secs. 2 and 11.
	Over mountainous land, through medium timber.
17.12	Point for AP 1, sec. 2, identical with AP 3, sec. 11, on the Mount Logan Wilderness Area Bdy.
	Not monumented.
	Enter the Mount Logan Wilderness Area.
39.72	The 1/4 sec. cor. of secs. 2 and 11, on the Mount Logan Wilderness Area Bdy., monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. 1/4 S2 S11 1921.
	from which the remaining original bearing tree
	A forked juniper, 30 ins. diam., at base, bears S. 17 1/4° W., 1.84 chs. dist., with illegible scribe marks on a 10 inch diam. limb. (Record: 182 lks.)
	Add the marks T34N R9W 1999 to the brass cap.
	S. 89°55' W., beginning new measurement.
	Leave the Mount Logan Wilderness Area.
39.94	The cor. of secs. 2, 3, 10 and 11.
	From the 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, in a scattered mound of stone, with brass cap mkd. 1/4 S28 S27 1921.
	from which the original bearing trees
	A juniper, 14 ins. diam., bears East, 1.38 chs. dist., with scribe marks 1/4 S27BT visible on weathered blaze.
	A juniper, 39 ins. diam. at base, bears N. 61 3/4° W., 561ks. dist., with scribe marks 1/4 S28BT visible on partially healed blaze on a 9 inch diam. limb.
	Add the marks T34N R9W 2003 to the brass cap.
	Rebuild mound of stone, 6 ft. base, 1 ft. high.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	North, bet. secs. 27 and 28.
	North, bet. secs. 27 and 28.
14.37	Point for AP 1 sec. 27, identical with AP 18, sec. 28, on the Mount Logan Wilderness Area Bdy. on the 5000 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W MLWA AP 18 AP 1 S 28 S 27
	2003
	Enter the Mount Logan Wilderness Area.
39.82	The cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. T34N R9W S21 S22 S28 S27 1921.
	from which the original bearing trees
	A juniper, 14 ins. diam., bears N. 87° E., 34 lks. dist., with scribe marks T34NR9WS22BT visible on partially healed blaze. (Record, 24 lks. dist.)
	A juniper, 13 ins. diam., bears S. 19 1/2° E., 26 lks. dist., with scribe marks T34NR9WS27BT visible on partially healed blaze.
	A juniper, 16 ins. diam., bears S. 22° W., 43 lks. dist., with scribe marks T34NR9WS28BT visible on weathered blaze.
	A juniper, 32 ins. diam. at base, bears N. 76 1/4° W., 59 lks. dist., with illegible scribe marks visible on mostly healed blaze on a 9 inch diam. limb.
	Add the marks 2003 to the brass cap.
	From the cor. of secs. 22, 23, 26 and 27.
	S. 89°59' W., bet. secs. 22 and 27.
40.26	The 1/4 sec. cor. of secs. 22 and 27, monumented with the base of an iron post, 1 in. diam., firmly set, in scattered a mound of stone, with the remaining portion laying loose nearby, with brass cap mkd. 1/4 S22 S27 1921.

С	HA	I	N	s

from which the original bearing trees

- A piñon, 18 ins. diam., bears S. 10 1/4° W., 40 lks. dist., with scribe marks 1/4 BT visible on extremely weathered blaze.
- A piñon, 12 ins. diam., bears N. 16 3/4° W., 31 lks. dist., with illegible scribe marks visible on extremely weathered blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, in a supporting mound of stone, 7 ft. base, 1 1/2 ft. high, with brass cap mkd.

2003

Deposit a magnet, in a white plastic case, at the base and the remains of the iron post alongside the stainless steel post.

- S. 89°56' W., beginning new measurement.
- 39.96 The cor. of secs. 21, 22, 27 and 28.

From the cor. of secs. 10, 11, 14 and 15.

S. 89°55' W., bet. secs. 10 and 15.

Over mountainous land, through heavy timber.

Point for AP 1, sec. 15, identical with AP 8, sec. 10, on the Mount Logan Wilderness Area Bdy.

Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 22 ins. in the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.

1999

CHAINS	1. 34 M., K. 9 M., Gila and Sait River Meridian, Arizona
	Cor. is located 1 lk. N. of a barbed wire fence, bears E. and W.
	From this cor. point, the SE cor. of a wildlife water catchment bears N. 24°26' W., 0.68 ch. dist.
	Thence, continue on a portion of the Mount Logan Wilderness Area Bdy.
40.08	The 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, in a scattered mound of stone, with brass cap mkd. 1/4 S10 S15 1921.
	from which the original bearing trees
	A piñon, 8 ins. diam., bears N. 4° E., 54 lks. dist., with illegible scribe marks visible on partially open blaze.
	A piñon, 14 ins. diam., bears S. 62 1/2° E., 64 lks. dist., with healed blaze.
	Add the marks T34N R9W 1999 to the brass cap.
	Rebuild the mound of stone, 2 1/2 ft. base, 1 ft. high.
	Cor. is located in barbed wire fence, bears E. and W.
	S. 89°58' W., beginning new measurement, on a portion of the Mount Logan Wilderness Area Bdy.
5.50	Point for AP 3, sec. 15, on the Mount Logan Wilderness Area Bdy.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.
	T 34 N R 9 W
	s 10
	S 15 AP 3 MLWA
	1999
	Cor. is located 2 lk. S. of a barbed wire fence, bears E. and W.
	Leave the Mount Logan Wilderness Area.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
16.14	An iron rod, 3/4 in. diam., firmly set, projecting 16 ins. above ground, with attached aluminum cap, 1 1/2 ins. diam., mkd. 1467 KAIBAB N.F. BDRY MON 1963, bears South, 2.5 lks. dist.
31.42	An iron rod, 3/4 in. diam., firmly set, projecting 17 ins. above ground, with attached aluminum cap, 1 1/2 ins. diam. mkd. KAIBAB N.F. BDRY MON 1467 1963, bears South, 4 lks. dist.
40.14	The cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2 ins. diam., firmly set, projecting 17 ins. above ground, with brass cap mkd. T34N R9W S9 S10 S16 S15 1921.
	from which the remains of the original bearing trees
	A dead piñon, 16 ins. diam., bears N. 76° E., 45 lks. dist., with illegible faint scribe marks on an open blaze. (Record, N. 73 1/4° E., 47 lks. dist.)
	A piñon, 14 ins. diam., bears S. 73 3/4° E., 19 lks. dist., with illegible scribe marks on a partially healed blaze.
	A piñon, 18 ins. diam., bears S. 40 1/2° W., 2.09 chs. dist., with scribe marks T34NR9WS16BT visible on partially open blaze.
	A piñon, 16 ins. diam., bears N. 7 1/2° W., 1.33 chs. dist., with scribe marks 9BT visible on partially open blaze. (Record, N. 8° W., 136 lks. dist.)
	Add the marks 1999 to the brass cap.
	Cor. is located at intersection of barbed wire fences, extending N. and E.
	From the cor. of secs. 21, 22, 27 and 28.
	N. 89°51' W., bet. secs. 21 and 28.
39.92	The 1/4 sec. cor. of secs. 21 and 28, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. 1/4 S21 S28 1921.
	from which the original bearing trees
	A juniper, 18 ins. diam. at base, bears S. 40° E., 1.12 chs. dist., with scribe marks 1/4 S28BT visible on weathered blaze on a 9 inch diam. limb.
	A piñon, 12 ins. diam., bears N. 50 3/4° W., 64 lks. dist., with scribe marks 1/4 S21BT visible on partially healed blaze.

CHAINS

Add the marks T34N R9W 2003 to the brass cap.

Raise mound of stone, 3 ft. base, to top.


Cor. is located on E. aspect of round knob.

N. 89°53' W., beginning new measurement.

21.40

Point for AP 1, sec. 28, identical with AP 21, sec. 21, on the Mount Logan Wilderness Area Bdy. on the 5000 ft. contour.

Set an aluminum drive rod, 67 ins. long, 3/4 in. diam., 62 ins. in the ground to refusal, with aluminum cap mkd.



Leave the Mount Logan Wilderness Area.

39.74

The cor. of secs. 20, 21, 28 and 29, monumented with an iron post, 2 ins. diam., firmly set, projecting 20 ins. above ground, in a scattered mound of stone, with brass cap mkd. T34N R9W S20 S21 S29 S28 1921.

from which the original bearing trees

- A juniper, 20 ins. diam., bears N. 76 3/4° E., 2.32 chs. dist., with scribe marks T34NR9WS21BT visible on partially healed blaze.
- A juniper, 24 ins. diam. at base, bears S. 80 1/4° E., 1.75 chs. dist., with scribe marks T34NR9WS28BT visible on partially healed blaze on a 10 inch diam. limb.
- A juniper, 26 ins. diam. at base, bears S. 37 3/4° W., 1.28 chs. dist., with a healed blaze.
- A juniper, 22 ins. diam. at base, bears N. 77 3/4° W., 1.32 chs. dist., with hack marks on an 8 ins. diam. limb, and a healed blaze on a 10 inch diam. limb.

Add the marks 2003 to the brass cap.

Rebuild mound of stone, 3 ft. base, 1 1/2 ft. high.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	N. 0°03' E., bet. secs. 20 and 21.
23.30	Point for AP 8, sec. 20, identical with AP 12, sec. 21, on the Mount Logan Wilderness Area Bdy.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA AP 8 AP 12 S 20 S 21
	2003
	Cor. is located on the easterly offset from Cold Spring Wash road.
	Enter the Mount Logan Wilderness Area.
40.04	The 1/4 sec. cor. of secs. 20 and 21, monumented with an iron post, 1 in. diam., firmly set, projecting 17 ins. above ground, in a scattered mound of stone, with brass cap mkd. 1/4 S20 S21 1921.
	from which the original bearing trees
	A juniper, 12 ins. diam., bears N. 67° E., 51 lks. dist., with scribe marks 1/4 S21BT visible on weathered blaze.
	A juniper, 12 ins. diam., bears S. 86 3/4° W., 1.43 chs. dist., with scribe marks 4 S20BT visible on partially healed blaze.
	Add the marks T34N R9W 2003 to the brass cap.
	Rebuild mound of stone, 3 ft. base, 1 ft. high.
	N. 0°07' W., beginning new measurement.
19.95	Point for AP 1, sec. 20, identical with AP 11, sec. 21, on the Mount Logan Wilderness Area Bdy.
	Set an aluminum drive rod, 32 ins. long, 3/4 in. diam., 27 ins. in the ground to refusal, with aluminum cap mkd.

CHAINS T 34 N R 9 W S 20 | S 21 AP 11 AP 1 2003 Cor. is located in the drainage from Bull Point.

Leave the Mount Logan Wilderness Area.

40.06

The cor. of secs. 16, 17, 20 and 21, monumented with an iron post, 2 ins. diam., firmly set, projecting 21 ins. above ground, in a scattered mound of stone, with brass cap mkd. T34N R9W S17 S16 S20 S21 1921.

from which the remains of the original bearing trees

- A dead and down piñon, 12 ins. diam., bears N. 39 1/2° E., 38 lks. dist., with faint scribe marks T34N visible on extremely weathered blaze. (Record, N. 28 1/2° E., 36 lks. dist.)
- A piñon, 12 ins. diam., bears S. 49 1/2° E., 60 lks. dist., with scribe marks T34NR9WS21BT visible on weathered blaze.
- A piñon, 10 ins. diam., bears S. 18 1/2° W., 52 lks. dist., with scribe marks T34NR9WS20BT visible on partially healed blaze.
- A partially decayed, fallen juniper, 13 ins. diam., bears N. 52 1/2° W., 11 lks. dist., no marks visible.

Add the marks 2003 to the brass cap.

Rebuild mound of stone, 4 ft. base, 1 1/2 ft. high.

Metes-and-Bounds Survey of the Mount Logan Wilderness Area Boundary,

T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona

In Section 13

Note: All AP's in section 13 are offset 50 lks., more or less, southerly and or westerly of a track road, excluding it from the wilderness area.

	T. 54 N., R. 9 W., Gila and Sait River Meridian, Arizona
CHAINS	
	From AP 1, sec. 13, identical with AP 33, sec. 18, T. 34 N., R. 8 W., on the E. bdy. of the Tp., hereinbefore described.
	S. 80°12' W., on line 1-2, sec. 13.
	Thence, along track road.
1.97	Point for AP 2, sec. 13.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 13
	AP 2 MLWA
	1998
	N. 88°45' W., on line 2-3, sec. 13.
1.92	Point for AP 3, sec. 13.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	AP 3
	MLWA
	N. 45°26' W., on line 3-4, sec. 13.
4.45	Point for AP 4, sec. 13.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 34 ins. in the ground, with aluminum cap mkd.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	s 13
	AP 4
	MLWA
	1998
	N. 46°13' W., on line 4-5, sec. 13.
3.18	Point for AP 5, sec. 13.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	\s 13
	AP 5
	MLWA \
	1998
	N. 24°13' W., on line 5-6, sec. 13.
5.63	Point for AP 6, sec. 13.
	Set an aluminum drive rod, 72 ins. long, 3/4 in. diam., 65 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	AP 6 S13
	1998
	N. 5°00' E., on line 6-7, sec. 13.
3.27	Point for AP 7, sec. 13.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	AP 7 S 13 MLWA
	MLWA
	1998
	N. 17°06' E., on line 7-8, sec. 13.
2.82	Point for AP 8, sec. 13.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	AP 8 /
	AP 8 s 13
	MLWA /
	1998
	N. 14°02' E., on line 8-9, sec. 13.
2 01	
2.81	Point for AP 9, sec. 13.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	AP 9 s 13
	MLWA S 13
	1998
	N. 2°16' E., on line 9-10, sec. 13.
2.53	Point for AP 10, sec. 13.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 29 ins. in the ground, with aluminum cap mkd.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	AP 10/
	MLWA S 13
	1998
	N. 17°16' E., on line 10-11, sec. 13.
1.99	Point for AP 11, sec. 13.
	Set an aluminum drive rod, 72 ins. long, 3/4 in. diam., 65 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	AP 11 S 13 MLWA
	1998
	N. 37°34' W., on line 11-12, sec. 13.
2.29	Point for AP 12, sec. 13.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	AP 12 S 13 MLWA
	1998
	N 40°461 W 16 10 10
	N. 48°46' W., on line 12-13, sec. 13.
3.16	Point for AP 13, sec. 13.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, in a mound of stone, 2 ft. base, to top, with aluminum cap mkd.

	T. 54 N., R. 9 W., Gila and Sait River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	AP 13 / S 13
	MLWA S 13
	1998
	N. 17°02' E., on line 13-14, sec. 13.
4.27	Point for AP 14, sec. 13.
	Set an aluminum drive rod, 72 ins. long, 3/4 in. diam., 63 ins. in the ground, in a mound of stone, 2 ft. base, to top, with aluminum cap mkd.
	T 34 N R 9 W
	AP 14 \ S 13
	MLWA /
	1998
	N. 19°30' W., on line 14-15, sec. 13.
0.41	The point for AP 15, sec. 13, identical with AP 1, sec. 12, on the line bet. secs. 12 and 13, hereinbefore described.
	From this point, the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., bears S. 89°44' E., 11.80 chs. dist., hereinbefore described.
	In Section 12
	Note: AP 1 to AP 18 in section 12 are offset 50 lks., more or less, southerly and or westerly of a track road, excluding it from the wilderness area.
	From the point for AP 1, sec. 12, identical with AP 15, sec. 13, on the line bet. secs. 12 and 13.
	N. 19°30' W., on line 1-2, sec. 12.
2.70	Point for AP 2, sec. 12.
	Set an aluminum drive rod, 72 ins. long, 3/4 in. diam., 66 ins. in the ground, with aluminum cap mkd.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	AP 2 S 12
	MLWA
	1999
	N. 32°58' W., on line 2-3, sec. 12.
4.06	Point for AP 3, sec. 12.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 29 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	AP 3 \ s 12
	MLWA D 12
	1999
	N. 30°33' W., on line 3-4, sec. 12.
6.68	Point for AP 4, sec. 12.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	AP 4
	MLWA S 12
	1999
	N. 2°53' E., on line 4-5, sec. 12.
5.78	Point for AP 5, sec. 12.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 29 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.
1 1	

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	AP 5 S 12 MLWA
	PLIWA
	1999
	N. 14°14' W., on line 5-6, sec. 12.
2.64	Point for AP 6, sec. 12.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.
	T 34 N R 9 W
	AP 6 S 12 MLWA
	1999
	N. 37°07' W., on line 6-7, sec. 12.
2.69	Point for AP 7, sec. 12.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.
	T 34 N R 9 W
	AP 7 \ S 12 MLWA
	1999
	N. 18°42' W., on line 7-8, sec. 12.
5.41	Point for AP 8, sec. 12.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	AP 8 S 12
	MLWA \
	1999
	N. 40°31' E., on line 8-9, sec. 12.
1.64	Point for AP 9, sec. 12.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 14 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA S 12 AP 9
	1999
	N. 69°35' E., on line 9-10, sec. 12.
2.91	Point for AP 10, sec. 12.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA AP 10 S 12
	1999
	N. 3°01' E., on line 10-11, sec. 12.
4.78	Point for AP 11, sec. 12.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, with aluminum cap mkd.
	,

T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona

CHAINS T 34 N R 9 W s 12 AP 11 MLWA 1999 N. 1°31' W., on line 11-12, sec. 12. 1.77 Point for AP 12, sec. 12. Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 29 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd. T 34 N R 9 W S 12 MLWA 1999 N. 77°01' W., on line 12-13, sec. 12. 1.63 Point for AP 13, sec. 12. Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd. T 34 N R 9 W AP 13 s 12 MLWA 1999 N. 1°20' W., on line 13-14, sec. 12. 5.09 Point for AP 14, sec. 12. Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.

Metes-and-Bounds Survey of the Mount Logan Wilderness Area Boundary, 34 N., R. 9 W., Gila and Salt River Meridian, A

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	т 34 м к 9 w
	AP 14 S 12
	MLWA
	1999
	N. 8°24' W., on line 14-15, sec. 12.
3.89	Point for AP 15, sec. 12.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.
	T 34 N R 9 W
	AP 15 S 12 MLWA
	1999
	N. 61°02' W., on line 15-16, sec. 12.
2.48	Point for AP 16, sec. 12.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.
	T 34 N R 9 W
	AP 16 S 12
	MLWA
	1999
	N. 29°18' W., on line 16-17, sec. 12.
1.11	Point for AP 17, sec. 12.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.
	1

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	т 34 ү к 9 ж
	AP 17 \ S 12
	MLWA
	1999
	N. 20°15' W., on line 17-18, sec. 12.
1.80	Point for AP 18, sec. 12.
·	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.
	T 34 N R 9 W
	AP 18 S 12 MLWA
	1999
	Cor. is located on edge of cliff, bears E. and W.
	Leave track road.
	N. 47°39' W., on line 18-19, sec. 12.
31.38	Point for AP 19, sec. 12.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	AP 19 S 12
	MLWA
	1999
	N. 61°04' W., on line 19-20, sec. 12.
9.03	Point for AP 20, sec. 12.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 10 ins. in the ground, to bedrock, in a supporting mound of stone, 3 1/2 ft. base, 2 ft. high, with aluminum cap mkd.

Metes-and-Bounds Survey of the Mount Logan Wilderness Area Boundary, N. B. 9 W. Gila and Salt River Meridian

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	AP 20 S 12
	MLWA
	1999
	N. 85°19' W., on line 20-21, sec. 12.
25.24	Point for AP 21, sec. 12.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 12
	AP 21 MLWA
	1999
	N. 85°36' W., on line 21-22, sec. 12.
0.17	The point for AP 22, sec. 12, identical with AP 1, sec. 11, on the line bet. secs. 11 and 12, hereinbefore described.
	From this point, the cor. of secs. 1, 2, 11 and 12, bears N. 0°05' E., 3.27 chs. dist., hereinbefore described.
	In Section 11
	From the point for AP 1, sec. 11, identical with AP 22, sec. 12, on the line bet. secs. 11 and 12.
	N. 85°36' W., on line 1-2, sec. 11.
13.88	Point for AP 2, sec. 11.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, with aluminum cap mkd.

Metes-and-Bounds Survey of the Mount Logan Wilderness Area Boundary, W., Gila and Salt River Meridian, Arizona

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	s 11
	AP 2
	MLWA
	1999
	N. 56°17' W., on line 2-3, sec. 11.
3.94	The point for AP 3, sec. 11, identical with AP 1, sec. 2, on the line bet. secs. 2 and 11, hereinbefore described.
	From this point, the cor. of secs. 1, 2, 11 and 12, bears N. 89°58' E., 17.12 chs. dist., hereinbefore described.
	In Section 2
	From the point for AP 1, sec. 2, identical with AP 3, sec. 11, on the line bet. secs. 2 and 11.
	N. 56°17' W., on line 1-2, sec. 2.
3.29	Point for AP 2, sec. 2.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 29 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	AP 2 S 2 MLWA
	1999
	N. 9°47' W., on line 2-3, sec. 2.
2.04	Point for AP 3, sec. 2.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 24 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.
	1

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	AP 3 S 2
	MLWA
	1999
	N. 44°01' W., on line 3-4, sec. 2.
15.78	Point for AP 4, sec. 2.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 33 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.
	T 34 N R 9 W S 2
	AP 4
	MLWA
	1999
	S. 36°34' W., on line 4-5, sec. 2.
7.31	Point for AP 5, sec. 2.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.
	т 34 м р 9 w
	S 2 AP 5 MLWA
	/ 1999
	S. 24°13' W., on line 5-6, sec. 2.
10.24	The 1/4 sec. cor. of secs. 2 and 11, identical with AP 6, sec. 2 and AP 4, sec. 11, hereinbefore described.
	In Section 11
	From the 1/4 sec. cor. of secs. 2 and 11, identical with AP 4, sec. 11 and AP 6, sec. 2.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	S. 68°50' W., on line 4-5, sec. 11.
4.52	Point for AP 5, sec. 11.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 2 1/2 ft. base, 1 ft. high, with aluminum cap mkd.
	T 34 N R 9 W
	S 11 AP 5 MLWA
	1999
	S. 67°00' W., on line 5-6, sec. 11.
8.84	Point for AP 6, sec. 11.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.
	T 34 N R 9 W
	S 11 AP 6 MLWA
	1999
	S. 61°31' W., on line 6-7, sec. 11.
7.63	Point for AP 7, sec. 11.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 2 ft. base, 1 ft. high, with aluminum cap mkd.
	T 34 N R 9 W
	S 11 AP 7 MLWA
	1999
	S. 65°25' W., on line 7-8, sec. 11.
5.14	Point for AP 8, sec. 11.
	1

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.
	T 34 N R 9 W
	s 11
	AP 8 MLWA
	1999
	S. 75°32' W., on line 8-9, sec. 11.
8.54	Point for AP 9, sec. 11.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.
	T 34 N R 9 W
	s 11
	AP 9 MLWA
	1999
	S. 46°33' W., on line 9-10, sec. 11.
2.94	Point for AP 10, sec. 11.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 26 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.
	T 34 N R 9 W
	s 11 /
	AP 10 MLWA
	1999
	S. 78°36' W., on line 10-11, sec. 11.
5.91	The point for AP 11, sec. 11, identical with AP 1, sec. 10, on
	the line bet. secs. 10 and 11, hereinbefore described.

<u></u>	1. 34 M., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	From this point, the cor. of secs. 2, 3, 10 and 11, bears N. 0°02' W., 16.13 chs. dist., hereinbefore described.
	In Section 10
	From the point for AP 1, sec. 10, identical with AP 11, sec. 11, on the line bet. secs. 10 and 11.
	S. 78°36' W., on line 1-2, sec. 10.
11.59	Point for AP 2, sec. 10.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 8 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with aluminum cap mkd.
	T 34 N R 9 W
	S 10/
	AP 2 MLWA
	1999
	S. 9°59' W., on line 2-3, sec. 10.
8.22	Point for AP 3, sec. 10.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.
	T 34 N R 9 W
	s 10 /
	AP 3 MLWA
	1999
	Cor. is located atop of prominent unnamed peak.
	S. 14°01' W., on line 3-4, sec. 10.
26.53	Point for AP 4, sec. 10.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 2 1/2 ft. base, 1 ft. high, with aluminum cap mkd.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	s 10 / AP 4
	MLWA
	1999
	S. 30°06' W., on line 4-5, sec. 10.
7.43	Point for AP 5, sec. 10.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 27 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 10 AP 5 MLWA
	1999
	S. 19°18' W., on line 5-6, sec. 10.
14.29	Point for AP 6, sec. 10.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 10 AP 6
	MLWA MLWA
	1999
	S. 36°32' E., on line 6-7, sec. 10.
7.37	Point for AP 7, sec. 10.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 22 ins. in the ground, to bedrock, in a mound of stone, 2 1/2 ft. base,
	to top, with aluminum cap mkd.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	S 10 AP 7
	MLWA
	1999
	From this cor. point, the NE cor. of wildlife water catchment bears S. 38°54' W., 0.59 ch. dist.
	S. 0°48' E., on line 7-8, sec. 10.
1.88	AP 8, sec. 10, identical with AP 1, sec. 15, on the line bet. secs. 10 and 15, hereinbefore described.
	From this cor., the cor. of secs. 10, 11, 14 and 15, bears N. 89°55' E., 23.25 chs. dist., hereinbefore described.
	In Section 15
	From AP 3, sec. sec. 15, on the line bet. secs. 10 and 15, hereinbefore described.
	S. 34°08' W., on line 3-4, sec. 15.
3.79	Point for AP 4, sec. 15.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.
	T 34 N R 9 W
	S 15 AP 4
	MLWA
	1999
	S. 2°25' W., on line 4-5, sec. 15.
7.67	Point for AP 5, sec. 15.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 30 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.

Metes-and-Bounds Survey of the Mount Logan Wilderness Area Boundary, N., R. 9 W., Gila and Salt River Meridian, Ari:

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W S 15 AP 5 MLWA 1999
	S. 25°09' W., on line 5-6, sec. 15.
4.75	Point for AP 6, sec. 15.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 2 1/2 ft. base, to top, with aluminum cap mkd.
	T 34 N R 9 W
	S 15 AP 6 MLWA 1999
	S. 31°37' W., on line 6-7, sec. 15.
9.79	Point for AP 7, sec. 15.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 19 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.
	T 34 N R 9 W
	S 15 AP 7
	MLWA
	1999
	S. 22°05' W., on line 7-8, sec. 15.
9.68	Point for AP 8, sec. 15.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 19 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	S 15 AP 8
	/ MLWA
	1999
	<u> </u>
	S. 18°23' W., on line 8-9, sec. 15.
4.28	Point for AP 9, sec. 15.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 19 ins. in the ground, to bedrock, in a mound of stone, 3 1/2 ft. base, to top, with aluminum cap mkd.
	T 34 N R 9 W
	S 15 AP 9 MLWA
	1999
	S. 1°58' E., on line 9-10, sec. 15.
13.73	Point for AP 10, sec. 15.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 28 ins. in the ground, encircled with a collar of stone, with aluminum cap mkd.
	T 34 N R 9 W
	S 15 AP 10 MLWA
	1999
	S. 18°18' E., on line 10-11, sec. 15.
3.55	Point for AP 11, sec. 15.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 8 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top, with aluminum cap mkd.

T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona

CHAINS T 34 N R 9 W s 15 AP 11 MLWA 1999 S. 49°58' W., on line 11-12, sec. 15. 8.28 Point for AP 12, sec. 15. Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 20 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with aluminum cap mkd. T 34 N R 9 W S 15 AP 12 MLWA 1999 S. 44°05' W., on line 12-13, sec. 15. 20.59 Point for AP 13, sec. 15. Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 10 ins. in the ground, to bedrock, in a mound of stone, 2 ft. base, 1 ft. high, with aluminum cap mkd. T 34 N R 9 W S 15 AP 13 MLWA 1999 S. 8°58' W., on line 13-14, sec. 15. 6.48 The cor. of secs. 15, 16, 21 and 22, identical with AP 14, sec. 15, and AP 1, sec. 21, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. T34N R9W S16 S15 S21 S22 1921. from which the original bearing trees A juniper, 9 ins. diam., bears N. 19° E., 9 lks. dist., with scribe marks T34NR9WS15BT visible on partially open blaze.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	A juniper, 10 ins. diam., bears S. 36 3/4° E., 44 lks. dist., with scribe marks T34NR9WS22BT visible on partially open blaze.
	A juniper, 18 ins. diam., bears S. 55 3/4° W., 43 lks. dist., with scribe marks T34NR9WS21BT visible on partially open blaze.
	A juniper, 13 ins. diam., bears N. 37 1/2° W., 31 lks. dist., with scribe marks T34NR9WS16BT visible on partially open blaze.
	Add the marks 1999 to the brass cap.
	In Section 21
	From the cor. of secs. 15, 16, 21 and 22, identical with AP 1, sec. 21, and AP 14, sec. 15.
	S. 65°24' W., on line 1-2, sec. 21.
13.72	Point for AP 2, sec. 21.
	Set an aluminum drive rod, 28 ins. long, 3/4 in. diam., 20 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
	S 21 AP 2
	MLWA
	2003
	Cor. is located at end of ridge off W. side of Bull Point.
	S. 84°11' W., on line 2-3, sec. 21.
18.41	Point for AP 3, sec. 21.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 35 ins. in the ground, with aluminum cap mkd.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	s 21
	AP 3
	MLWA
	2003
	Cor. is located above box canyon at head of drainage from W. side of Bull Point.
	N. 72°31' W., on line 3-4, sec. 21.
7.59	Point for AP 4, sec. 21.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 21
	MLWA AP 4
	2003
	Cor. is located on right bank of drainage from W. side of Bull Point.
	N. 88°32' W., on line 4-5, sec. 21.
5.52	Point for AP 5, sec. 21.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.
·	T 34 N R 9 W
	S 21
	AP 5 MLWA
	2003
	Cor. is located on right bank of drainage from W. side of Bull Point.
	S. 69°33' W., on line 5-6, sec. 21.

CURTNO	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
11.08	Point for AP 6, sec. 21.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 21 MLWA
	AP 6
	2003
	Cor. is located on right bank of drainage from W. side of Bull Point.
	S. 67°09' W., on line 6-7, sec. 21.
5.78	Point for AP 7, sec. 21.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 21
	AP 7 MLWA
	2003
	Cor. is located on right bank of drainage from W. side of Bull Point.
	S. 48°50' W., on line 7-8, sec. 21.
5.51	Point for AP 8, sec. 21.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 21
	AP 8 MLWA
	2003

Metes-and-Bounds Survey of the Mount Logan

Wilderness Area Boundary, T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona CHAINS Cor. is located on right bank of drainage from W. side of Bull Point. S. 80°36' W., on line 8-9, sec. 21. 5.81 Point for AP 9, sec. 21. Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd. T 34 N R 9 W S 21 AP 9 MLWA 2003 Cor. is located on right bank of drainage from W. side of Bull Point. S. 64°23' W., on line 9-10, sec. 21. 5.58 Point for AP 10, sec. 21. Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd. T 34 N R 9 W S 21 **AP 10** MLWA 2003 Cor. is located on right bank of drainage from W. side of Bull Point. S. 75°24' W., on line 10-11, sec. 21. 5.65 AP 11, sec. 21, identical with AP 1, sec. 20, on the line bet. secs. 20 and 21, hereinbefore described. From this cor. point, the 1/4 sec. cor. of secs. 20 and 21, bears S. 0°07' E., 19.95 chs. dist., hereinbefore described.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	In Section 20
	From AP 1, sec. 20, identical with AP 11, sec. 21, on the line bet. secs. 20 and 21, hereinbefore described.
	S. 52°52' W., on line 1-2, sec. 20.
3.49	Point for AP 2, sec. 20.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 20 AP 2 MLWA
	2003
	Cor. is located at intersection of drainage from Bull Point and Cold Spring Wash.
	S. 14°50' E., on line 2-3, sec. 20.
6.37	Point for AP 3, sec. 20.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 20 AP 3 MLWA
	2003
	Cor. is located on right bank of Cold Spring Wash.
	S. 15°01' W., on line 3-4, sec. 20.
7.63	Point for AP 4, sec. 20.
·	


T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona

CHAINS Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W Cor. is located on right bank of Cold Spring Wash. S. 30°30' W., on line 4-5, sec. 20. 6.79 Point for AP 5, sec. 20. Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd. T 34 N R 9 W S 20 AP 5 MLWA 2003 Cor. is located on the right bank of Cold Spring Wash and the 45 lk. offset from Cold Spring Wash road. S. 59°22' E., on line 5-6, sec. 20. 3.80 Point for AP 6, sec. 20. Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd. T 34 N R 9 W Cor. is located on the 45 lk. offset from Cold Spring Wash road. S. 11°35' E., on line 6-7, sec. 20. 6.04 Point for AP 7, sec. 20.

T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona

CHAINS

Set an aluminum drive rod, 31 ins. long, 3/4 in. diam., 25 ins. in the ground to refusal, with aluminum cap mkd.



Cor. is located on the 45 lk. offset from Cold Spring Wash road.

S. 16°07' E., on line 7-8, sec. 20.

7.66 AP 8, sec. 20, identical with AP 12, sec. 21, on the line bet. secs. 20 and 21, hereinbefore described.

From this cor. point, the 1/4 sec. cor. of secs. 20 and 21, bears N. 0°03' E., 16.74 chs. dist., hereinbefore described.

In Section 21


From AP 12, sec. 21, identical with AP 8, sec. 20, on the line bet. secs. 20 and 21.

S. 39°19' E., on line 12-13, sec. 21.

6.26 Point for AP 13, sec. 21.

Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 35 ins. in the ground, with aluminum cap mkd.

T 34 N R 9 W



2003

Cor. is located on the 45 lk. offset from Cold Spring Wash road.

S. 43°52' E., on line 13-14, sec. 21.

8.02 Point for AP 14, sec. 21, on the 5000 ft. contour.

Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	MLWA
	AP 14 /
	S 21
	2003
	Cor. is located on the 45 lk. offset from Cold Spring Wash road.
	N. 32°22' E., on line 14-15, sec. 21.
5.55	Point for AP 15, sec. 21, on the 5000 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA
	AP 15 S 21
	N. 68°48' E., on line 15-16, sec. 21.
6.22	Point for AP 16, sec. 21, on the 5000 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA
	S 21 AP 16
	2003
	S. 16°07' W., on line 16-17, sec. 21.
6.31	Point for AP 17, sec. 21, on the 5000 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	S 21 AP 17
	MLWA
	2003
	S. 41°25' E., on line 17-18, sec. 21.
6.12	Point for AP 18, sec. 21, on the 5000 ft. contour.
	Set an aluminum drive rod, 34 ins. long, 3/4 in. diam., 28 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA
	AP 18 S 21
	2003
	S. 80°20' E., on line 18-19, sec. 21.
5.99	Point for AP 19, sec. 21, on the 5000 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 31 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA AP 19
	s 21/
	2003
	S. 31°17' W., on line 19-20, sec. 21.
6.09	Point for AP 20, sec. 21, on the 5000 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.

Metes-and-Bounds Survey of the Mount Logan Wilderness Area Boundary, 34 N., R. 9 W., Gila and Salt River Meridian. Aris

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	s 21 /
	AP 20
	AWA
	2003
	S. 60°51' W., on line 20-21, sec. 21.
5.74	AP 21, sec. 21, identical with AP 1, sec. 28, on the line bet. secs. 21 and 28, hereinbefore described.
	From this cor. point, the cor. of secs. 20, 21, 28 and 29, bears N. 89°53' W., 18.34 chs. dist., hereinbefore described.
	In Section 28
	From AP 1, sec. 28, identical with AP 21, sec. 21, on the line bet. secs. 21 and 28.
	S. 25°23' W., on line 1-2, sec. 28.
5.53	Point for AP 2, sec. 28, on the 5000 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 28 AP 2 MLWA
	2003
	S. 37°35' E., on line 2-3, sec. 28.
6.09	Point for AP 3, sec. 28, on the 5000 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., flush with the ground, with aluminum cap mkd.

MLWA AP 3 S 28 2003 S. 32*24' E., on line 3-4, sec. 28. Point for AP 4, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 26 ins. long, 3/4 in. diam., 21 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 4 S 28 2003 S. 89*12' E., on line 4-5, sec. 28. Point for AP 5, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 21 ins. long, 3/4 in. diam., 17 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 5 S 28 2003 N. 59*39' E., on line 5-6, sec. 28. Point for AP 6, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins. in the ground to refusal, with aluminum cap mkd.		T. 34 N., R. 9 W., Gila and Salt River Meridian, An	rizona	
MLWA AP 3 S 28 2003 S. 32°24' E., on line 3-4, sec. 28. Point for AP 4, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 26 ins. long, 3/4 in. diam., 21 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 4 S 28 2003 S. 89°12' E., on line 4-5, sec. 28. Point for AP 5, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 21 ins. long, 3/4 in. diam., 17 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 5 S 28 2003 N. 59°39' E., on line 5-6, sec. 28. Point for AP 6, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins.	CHAINS			
S. 32°24' E., on line 3-4, sec. 28. Point for AP 4, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 26 ins. long, 3/4 in. diam., 21 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 4 S 28 2003 S. 89°12' E., on line 4-5, sec. 28. Point for AP 5, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 21 ins. long, 3/4 in. diam., 17 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 5 S 28 2003 N. 59°39' E., on line 5-6, sec. 28. Point for AP 6, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins.		T 34 N R 9 W		
S 28 2003 S. 32°24' E., on line 3-4, sec. 28. Point for AP 4, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 26 ins. long, 3/4 in. diam., 21 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 4 S 28 2003 S. 89°12' E., on line 4-5, sec. 28. Point for AP 5, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 21 ins. long, 3/4 in. diam., 17 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 5 S 28 2003 N. 59°39' E., on line 5-6, sec. 28. Point for AP 6, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins.		1		
S. 32°24' E., on line 3-4, sec. 28. Point for AF 4, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 26 ins. long, 3/4 in. diam., 21 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AF 4 S 28 2003 S. 89°12' E., on line 4-5, sec. 28. Point for AF 5, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 21 ins. long, 3/4 in. diam., 17 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AF 5 S 28 2003 N. 59°39' E., on line 5-6, sec. 28. Point for AF 6, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins.				
S. 32°24' E., on line 3-4, sec. 28. Point for AP 4, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 26 ins. long, 3/4 in. diam., 21 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 4 S 28 2003 S. 89°12' E., on line 4-5, sec. 28. Point for AP 5, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 21 ins. long, 3/4 in. diam., 17 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 5 S 28 2003 N. 59°39' E., on line 5-6, sec. 28. Point for AP 6, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins. Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins.		S 28 \		
Point for AP 4, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 26 ins. long, 3/4 in. diam., 21 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 4 S 28 2003 S. 89°12' E., on line 4-5, sec. 28. Point for AP 5, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 21 ins. long, 3/4 in. diam., 17 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 5 S 28 2003 N. 59°39' E., on line 5-6, sec. 28. 6.52 Point for AP 6, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins.		2003		
Set an aluminum drive rod, 26 ins. long, 3/4 in. diam., 21 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 4 S 28 2003 S. 89°12' E., on line 4-5, sec. 28. 6.49 Point for AP 5, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 21 ins. long, 3/4 in. diam., 17 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 5 S 28 2003 N. 59°39' E., on line 5-6, sec. 28. 6.52 Point for AP 6, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins.		S. 32°24' E., on line 3-4, sec. 28.		
in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 4 S 28 2003 S. 89°12' E., on line 4-5, sec. 28. 6.49 Point for AP 5, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 21 ins. long, 3/4 in. diam., 17 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 5 S 28 2003 N. 59°39' E., on line 5-6, sec. 28. Point for AP 6, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins.	5.93	Point for AP 4, sec. 28, on the 5000 ft. contour.		
MLWA AP 4 S 28 2003 S. 89°12' E., on line 4-5, sec. 28. 6.49 Point for AP 5, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 21 ins. long, 3/4 in. diam., 17 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 5 S 28 2003 N. 59°39' E., on line 5-6, sec. 28. 6.52 Point for AP 6, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins.		Set an aluminum drive rod, 26 ins. long, 3/4 in. in the ground to refusal, with aluminum cap mkd.	diam.,	21 ins.
S 28 2003 S. 89°12' E., on line 4-5, sec. 28. 6.49 Point for AP 5, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 21 ins. long, 3/4 in. diam., 17 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 5 S 28 2003 N. 59°39' E., on line 5-6, sec. 28. Point for AP 6, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins.				
S. 89°12' E., on line 4-5, sec. 28. Point for AP 5, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 21 ins. long, 3/4 in. diam., 17 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 5 S 28 2003 N. 59°39' E., on line 5-6, sec. 28. Point for AP 6, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins.		AP 4		
S. 89°12' E., on line 4-5, sec. 28. Point for AP 5, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 21 ins. long, 3/4 in. diam., 17 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 5 S 28 2003 N. 59°39' E., on line 5-6, sec. 28. Point for AP 6, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins.		S 28		
Point for AP 5, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 21 ins. long, 3/4 in. diam., 17 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 5 S 28 2003 N. 59°39' E., on line 5-6, sec. 28. Point for AP 6, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins.		2003		
Set an aluminum drive rod, 21 ins. long, 3/4 in. diam., 17 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 5 S 28 2003 N. 59°39' E., on line 5-6, sec. 28. Point for AP 6, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins.		S. 89°12' E., on line 4-5, sec. 28.		
in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 5 S 28 2003 N. 59°39' E., on line 5-6, sec. 28. Point for AP 6, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins.	6.49	Point for AP 5, sec. 28, on the 5000 ft. contour.		
MLWA AP 5 S 28 2003 N. 59°39' E., on line 5-6, sec. 28. Point for AP 6, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins.			diam.,	17 ins.
AP 5 S 28 2003 N. 59°39' E., on line 5-6, sec. 28. 6.52 Point for AP 6, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins.		T 34 N R 9 W		
N. 59°39' E., on line 5-6, sec. 28. Point for AP 6, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins.				
N. 59°39' E., on line 5-6, sec. 28. Point for AP 6, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins.		s 28		
6.52 Point for AP 6, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins.		2003		
Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins.		N. 59°39' E., on line 5-6, sec. 28.		
Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins. in the ground to refusal, with aluminum cap mkd.	6.52	Point for AP 6, sec. 28, on the 5000 ft. contour.		
		Set an aluminum drive rod, 37 ins. long, 3/4 in. in the ground to refusal, with aluminum cap mkd.	diam.,	32 ins.

Metes-and-Bounds Survey of the Mount Logan

Wilderness Area Boundary, T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona CHAINS T 34 N R 9 W MLWA AP 6 S 28 2003 N. $50^{\circ}09'$ E., on line 6-7, sec. 28. 12.18 Point for AP 7, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 30 ins. long, 3/4 in. diam., 25 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 7 S 28 2003 N. 79°41' E., on line 7-8, sec. 28. 4.87 Point for AP 8, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 39 ins. in the ground, with aluminum cap mkd. T 34 N R 9 W MLWA AP 8 2003 Cor. is located at head of wash, drains S. 40° W. S. 27°28' W., on line 8-9, sec. 28. 5.84 Point for AP 9, sec. 28, on the 5000 ft. contour. Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 39 ins. in the ground, with aluminum cap mkd.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	S 28 AP 9 MLWA
	/ MLWA
	2003
	S. 20°33' W., on line 9-10, sec. 28.
5.20	Point for AP 10, sec. 28, on the 5000 ft. contour.
	Set an aluminum drive rod, 3/4 in. diam., 42 ins. long, 38 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 28 AP 10 MLWA
	MLWA
	2003
-	
	S. 12°26' E., on line 10-11, sec. 28.
5.57	Point for AP 11, sec. 28, on the 5000 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 35 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 28 AP 11 MLWA
	2003
	S. 14°43' E., on line 11-12, sec. 28.
5.34	Point for AP 12, sec. 28, on the 5000 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 35 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 28 AP 12 MLWA
	2003

Metes-and-Bounds Survey of the Mount Logan Wilderness Area Boundary, L. R. 9 W. Gila and Salt River Meridia

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	S. 30°52' E., on line 12-13, sec. 28.
5.68	Point for AP 13, sec. 28, on the 5000 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 28 MLWA AP 13
	2003
	S. 64°26' E., on line 13-14, sec. 28.
6.32	Point for AP 14, sec. 28, on the 5000 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 35 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA AP 14
	S 28 2003
	S. 88°45' E., on line 14-15, sec. 28.
8.80	Point for AP 15, sec. 28, on the 5000 ft. contour.
	Set an aluminum drive rod, 30 ins. long, 3/4 in. diam., 23 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA AP 15
	S 28 2003
	S. 81°00' E., on line 15-16, sec. 28.
5.70	Point for AP 16, sec. 28, on the 5000 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	MLWA
	AP 16
	S 28
	2003
	N. 76°02' E., on line 16-17, sec. 28.
6.16	Point for AP 17, sec. 28, on the 5000 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., flush
	with the ground, with aluminum cap mkd.
}	T 34 N R 9 W
	,
	MLWA /
	AP 17 /
	S 28
	2003
:	
	N. 33°51' E., on line 17-18, sec. 28.
6.30	AP 18, sec. 28, identical with AP 1, sec. 27, on the line bet.
	secs. 27 and 28, hereinbefore described.
i	From this cor. point, the 1/4 sec. cor. of secs. 27 and 28,
	bears South, 14.37 chs. dist., hereinbefore described.
	In Section 27
	From AP 1, sec. 27, identical with AP 18, sec. 28, on the line
	bet. secs. 27 and 28.
	S. 68°37' E., on line 1-2, sec. 27.
5.66	Point for AP 2, sec. 27, on the 5000 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 39 ins.
	in the ground, with aluminum cap mkd.

Metes-and-Bounds Survey of the Mount Logan Wilderness Area Boundary, W., Gila and Salt River Meridian, Ari

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	MLWA
	AP 2
	s 27
	S. 83°18' E., on line 2-3, sec. 27.
5.56	Point for AP 3, sec. 27, on the 5000 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA AP 3
	AF 3
	S 27
	2003
	N. 72°07' E., on line 3-4, sec. 27.
5.28	Point for AP 4, sec. 27, on the 5000 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA AP 4
	S 27
	2003
	N. 58°38' E., on line 4-5, sec. 27.
6.40	Point for AP 5, sec. 27, on the 5000 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.

Metes-and-Bounds Survey of the Mount Logan

Wilderness Area Boundary, T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona CHAINS T 34 N R 9 W AP 5 MLWA S 27 2003 N. 60°45' E., on line 5-6, sec. 27. Point for AP 6, sec. 27, on the 5000 ft. contour. 12.42 Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd. T 34 N R 9 W MLWA AP 6 S 27 2003 Cor. is located on right bank of wash drains S. 27° W., from N. 32° E. S. 60°16' E., on line 6-7, sec. 27, across the wash and rising 200 ft. to the 5200 ft. contour. 7.21 Point for AP 7, sec. 27, on the 5200 ft. contour. Set an aluminum drive rod, 30 ins. long, 3/4 in. diam., 25 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 7 S 27 2003 Cor. is located on southerly aspect of round knoll. S. 74°33' E., on line 7-8, sec. 27. 7.03 Point for AP 8, sec. 27, on the 5200 ft. contour.

T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona

CHAINS Set an aluminum drive rod, 33 ins. long, 3/4 in. diam., 27 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 8 S 27 2003 N. 23°07' E., on line 8-9, sec. 27. 5.69 Point for AP 9, sec. 27, on the 5200 ft. contour. Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd. T 34 N R 9 W MLWA AP 9 S 27 2003 Cor. is located on southeast aspect of saddle. N. 57°54' E., on line 9-10, sec. 27. 6.56 Point for AP 10, sec. 27, on the 5200 ft. contour. Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd. T 34 N R 9 W MLWA AP 10 S 27 2003 S. 76°14' E., on line 10-11, sec. 27. 6.03 Point for AP 11, sec. 27, on the 5200 ft. contour.

T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona

CHAINS Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 11 S 27 2003 N. 27°39' E., on line 11-12, sec. 27. 5.23 Point for AP 12, sec. 27, on the 5200 ft. contour. Set an aluminum drive rod, 29 ins. long, 3/4 in. diam., 24 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 12 S 27 2003 N. 51°17' E., on line 12-13, sec. 27. 6.52 Point for AP 13, sec. 27, on the 5200 ft. contour. Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd. T 34 N R 9 W MLWA **AP 13** S 27 2003 Cor. is located on the right bank of Bull Spring wash. N. 68°53' E., on line 13-14, sec. 27, across Bull Spring wash. 8.74 Point for AP 14, sec. 27, on the 5200 ft. contour.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA AP 14 S 27
	2003
	Cor. is located on left bank of Bull Spring wash.
	S. 10°52' E., on line 14-15, sec. 27.
4.31	Point for AP 15, sec. 27, on the 5200 ft. contour.
	Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 32 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA AP 15
	S 27
	2003
	N. 79°30' E., on line 15-16, sec. 27.
5.02	AP 16, sec. 27, identical with AP 1, sec. 26, on the line bet. secs. 26 and 27, hereinbefore described.
	From this cor. point, the cor. of secs. 22, 23, 26 and 27, bears N. 0°05' E., 6.81 chs. dist., hereinbefore described.
	In Section 26
	From AP 1, sec. 26, identical with AP 16, sec. 27, on the line bet. secs. 26 and 27.
	S. 49°15' E., on line 1-2, sec. 26.
5.74	Point for AP 2, sec. 26, on the 5200 ft. contour.

T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona

CHAINS Set an aluminum drive rod, 26 ins. long, 3/4 in. diam., 18 ins. in the ground to refusal, in a mound of stone, 2 ft. base, to top, with aluminum cap mkd. T 34 N R 9 W MLWA AP 2 S 26 2003 N. 62°58' E., on line 2-3, sec. 26. Point for AP 3, sec. 26, on the 5200 ft. contour. 5.49 Set an aluminum drive rod, 29 ins. long, 3/4 in. diam., 24 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 3 2003 S. 31°24' E., on line 3-4, sec. 26. 5.91 Point for AP 4, sec. 26, on the 5200 ft. contour. Set an aluminum drive rod, 39 ins. long, 3/4 in. diam., 35 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W 2003 S. 16°15' E., on line 4-5, sec. 26. 5.01 Point for AP 5, sec. 26, on the 5200 ft. contour. Set an aluminum drive rod, 30 ins. long, 3/4 in. diam., 24 ins. in the ground to refusal, with aluminum cap mkd.

Metes-and-Bounds Survey of the Mount Logan Wilderness Area Boundary, N., R. 9 W., Gila and Salt River Meridian. A

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	MLWA
	AP 5
	s 26
	2003
	N. 35°01' E., on line 5-6, sec. 26.
5.68	Point for AP 6, sec. 26, on the 5200 ft. contour.
	Set an aluminum drive rod, 24 ins. long, 3/4 in. diam., 18 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
İ	MLWA /
	AP 6 S 26
	2003
	N. 8°14' E., on line 6-7, sec. 26.
5.73	Point for AP 7, sec. 26, on the 5200 ft. contour.
	Set an aluminum drive rod, 35 ins. long, 3/4 in. diam., 30 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA AP 7 /S 26
	2003
	N. 51°45' E., on line 7-8, sec. 26.
5.98	Point for AP 8, sec. 26, on the 5200 ft. contour.
	Set an aluminum drive rod, 24 ins. long, 3/4 in. diam., 17 ins. in the ground to refusal, with aluminum cap mkd.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	MLWA
	AP 8
	\$ 26
	2003
	S. 3°03' E., on line 8-9, sec. 26.
5.98	Point for AP 9, sec. 26, on the 5200 ft. contour.
	Set an aluminum drive rod, 26 ins. long, 3/4 in. diam., 20 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
	S 26 AP 9 MLWA
	2003
	S. 33°29' E., on line 9-10, sec. 26.
5.52	Point for AP 10, sec. 26, on the 5200 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 26 AP 10 MLWA
	S. 20°02' E., on line 10-11, sec. 26.
5.37	Point for AP 11, sec. 26, on the 5200 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.

Metes-and-Bounds Survey of the Mount Logan Wilderness Area Boundary, 9 W.. Gila and Salt River Mer

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	MLWA
	S 26 AP 11
	2003
	S. 56°46' E., on line 11-12, sec. 26.
5.64	Point for AP 12, sec. 26, on the 5200 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA AP 12
	S 26
	2003
	S. 35°15' E., on line 12-13, sec. 26.
6.16	Point for AP 13, sec. 26, on the 5200 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA
	AP 13
	s 26
	2003
	N. 72°53' E., on line 13-14, sec. 26.
5.67	Point for AP 14, sec. 26, on the 5200 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	MLWA
	AP 14
	S 26
	2002
	S. 86°36' E., on line 14-15, sec. 26.
5.57	Point for AP 15, sec. 26, on the 5200 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 39 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA
	AP 15
	s 26
	2003
	S. 67°25' E., on line 15-16, sec. 26.
5.87	Point for AP 16, sec. 26, on the 5200 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA AP 16
	s 26
	2003
	N. 52°44' E., on line 16-17, sec. 26.
	Enter Hell's Hollow.
4 00	
4.89	Point for AP 17, sec. 26, on the 5200 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 40 ins. in the ground, with aluminum cap mkd.

Metes-and-Bounds Survey of the Mount Logan

Metes-and-Bounds Survey of the Mount Logan Wilderness Area Boundary,		
	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona	
CHAINS		
	T 34 N R 9 W	
	MLWA /	
	AP 17	
	s 26	
	2003	
	Cor. is located on the right bank of Hell's Hollow.	
	N. 21°09' E., on line 17-18, sec. 26.	
6.18	Point for AP 18, sec. 26, on the 5200 ft. contour.	
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.	
	T 34 N R 9 W	
	MLWA	
	AP 18	
	/ S 26	
	2003	
	Cor. is located on the right bank of Hell's Hollow.	
	N. 41°28' E., on line 18-19, sec. 26.	
5.60	Point for AP 19, sec. 26, on the 5200 ft. contour.	
	Set an aluminum drive rod, 78 ins. long, 3/4 in. diam., 74 ins. in the ground, with aluminum cap mkd.	
	T 34 N R 9 W	
	MLWA AP 19	
	s 26	
	2003	
	Cor. is located on the right bank of Hell's Hollow.	
	N. 21°11' E., on line 19-20, sec. 26.	
12.49	Point for AP 20, sec. 26, on the 5200 ft. contour.	

T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona

CHAINS Set an aluminum drive rod, 69 ins. long, 3/4 in. diam., 62 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA AP 20 / 2003 Cor. is located in Hell's Hollow. N. 62°52' E., on line 20-21, sec. 26, crossing Hell's Hollow. 3.90 Point for AP 21, sec. 26, on the 5200 ft. contour. Set an aluminum drive rod, 40 ins. long, 3/4 in. diam., 33 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W AP 21 2003 Cor. is located on the left bank of Hell's Hollow. S. 27°49' W., on line 21-22, sec. 26. 7.02 Point for AP 22, sec. 26, on the 5200 ft. contour. Set an aluminum drive rod, 30 ins. long, 3/4 in. diam., 26 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W S 26 AP 22 MLWA Cor. is located on the left bank of Hell's Hollow. S. 2°32' E., on line 22-23, sec. 26. 7.59 Point for AP 23, sec. 26, on the 5200 ft. contour.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 35 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 26 AP 23 MLWA
	2003
	Cor. is located on the left bank of Hell's Hollow.
	S. 18°10' W., on line 23-24, sec. 26.
7.36	Point for AP 24, sec. 26, on the 5200 ft. contour.
	Set an aluminum drive rod, 36 ins. long, 3/4 in. diam., 29 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N, R 9 W
	S 26 AP 24 MLWA
	2003
	Cor. is located on the left bank of Hell's Hollow.
	S. 7°21' W., on line 24-25, sec. 26.
6.26	Point for AP 25, sec. 26, on the 5200 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 26 MLWA AP 25
	2003
	Cor. is located on the left bank of Hell's Hollow.
	S. 54°15' E., on line 25-26, sec. 26.
	Leave Hell's Hollow.
6.59	Point for AP 26, sec. 26, on the 5200 ft. contour.

	1. 54 M., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Set an aluminum drive rod, 26 ins. long, 3/4 in. diam., 22 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA AP 26 S 26
	2003
	S. 87°50' E., on line 26-27, sec. 26.
2.02	Waterline, plastic pipe, 1 in. diam., bears N. 45° E. and S. 45° W.
5.44	Point for AP 27, sec. 26, on the 5200 ft. contour.
	Set an aluminum drive rod, 28 ins. long, 3/4 in. diam., 23 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA
	s 26 AP 27
	2003
	S. 66°43' E., on line 27-28, sec. 26.
5.13	AP 28, sec. 26, identical with AP 1, sec. 25, on the line bet. secs. 25 and 26, hereinbefore described.
	From this cor. point, the 1/4 sec. cor. of secs. 25 and 26, bears S. 0°05' E., 4.51 chs. dist., hereinbefore described.
	In Section 25
	Note: AP 2 through AP 15 in section 25, are offset 45 lks., more or less, northerly and or westerly of BLM road 1023, excluding it from the wilderness area.
	From AP 1, sec. 25, identical with AP 28, sec. 26, on the line bet. secs. 25 and 26.
	S. 10°13' E., on line 1-2, sec. 25.

Metes-and-Bounds Survey of the Mount Logan

	Metes-and-Bounds Survey of the Mount Logan Wilderness Area Boundary,			
	T. 34 N., R. 9 W., Gila and Salt River Meridian, An	rizona		
CHAINS				
8.56	Point for AP 2, sec. 25, on the 5200 ft. contour.			
	Set an aluminum drive rod, 38 ins. long, 3/4 in. in the ground to refusal, with aluminum cap mkd.	diam.,	33	ins.
	T 34 N R 9 W			
	MLWA			
•	\AP 2			
	s 25			
	2002			
	2003			
	N. 37°39' E., on line 2-3, sec. 25.			
	Thence, along BLM road 1023.			
5.34	Point for AP 3, sec. 25.			
	Set an aluminum drive rod, 42 ins. long, 3/4 in. in the ground, with aluminum cap mkd.	diam.,	37	ins.
	T 34 N R 9 W			
	AP 3 /s 25			
	MLWA S 25			
	2003			
	N. 31°15' E., on line 3-4, sec. 25.			
5.49	Point for AP 4, sec. 25.			
	Set an aluminum drive rod, 34 ins. long, 3/4 in. in the ground to refusal, with aluminum cap mkd.	diam.,	25	ins.
	T 34 N R 9 W			
	AP 4 S 25 MLWA			
	2003			
	N. 44°45' E., on line 4-5, sec. 25.			
6.51	Point for AP 5, sec. 25.			
5.51	101111 101 111 0, 566. 25.			

T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona

CHAINS Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd. T 34 N R 9 W 2003 N. 23°11' E., on line 5-6, sec. 25. 7.24 Point for AP 6, sec. 25. Set an aluminum drive rod, 23 ins. long, 3/4 in. diam., 18 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA / 2003 N. 65°11' E., on line 6-7, sec. 25. 5.78 Point for AP 7, sec. 25. Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd. T 34 N R 9 W MLWA AP 7 2003 N. 88°45' E., on line 7-8, sec. 25. 5.30 Point for AP 8, sec. 25. Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 35 ins. in the ground, with aluminum cap mkd.

Metes-and-Bounds Survey of the Mount Logan

Wilderness Area Boundary, T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona CHAINS T 34 N R 9 W MLWA AP 8 2003 N. 51°02' E., on line 8-9, sec. 25. 9.28 Point for AP 9, sec. 25. Set an aluminum drive rod, 29 ins. long, 3/4 in. diam., 22 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W MLWA S 25 2003 N. 80°27' E., on line 9-10, sec. 25. 4.56 Point for AP 10, sec. 25. Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd. T 34 N R 9 W MLWA AP 10 S 25 2003 N. 45°49' E., on line 10-11, sec. 25. 18.89 Point for AP 11, sec. 25. Set an aluminum drive rod, 32 ins. long, 3/4 in. diam., 28 ins. in the ground to refusal, with aluminum cap mkd.

Metes-and-Bounds Survey of the Mount Logan Wilderness Area Boundary, , R. 9 W., Gila and Salt River Meridian, Ari:

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	MLWA
	AP 11
	s 25
	2003
	N. 74°52' E., on line 11-12, sec. 25.
3.56	Point for AP 12, sec. 25.
	Set an aluminum drive rod, 39 ins. long, 3/4 in. diam., 32 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA
	AP 12
	s 25
	2003
	S. 74°38' E., on line 12-13, sec. 25.
5.19	Point for AP 13, sec. 25.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 34 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA
	AP 13
	s 25
	2003
	S. 43°58' E., on line 13-14, sec. 25.
5.67	Point for AP 14, sec. 25.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	MLWA
	AP 14
1	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
	s 25
	2003
	N. 16°34' E., on line 14-15, sec. 25.
6.19	AP 15, sec. 25., identical with AP 1, sec. 24, on the line bet. secs. 24 and 25, hereinbefore described.
	From this cor. point, the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., bears S. 89°49' E., 15.28 chs. dist., hereinbefore described.
	In Section 24
	Note: All AP's in section 24, are offset 45 lks., more or less, northerly and or westerly of BLM road 1023, excluding it from the wilderness area.
	From AP 1, sec. 24, identical with AP 15, sec. 25, on the line bet. secs. 24 and 25.
	N. 3°34' W., on line 1-2, sec. 24.
	Thence, along BLM road 1023.
5.12	Point for AP 2, sec. 24.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 30 ins. into crack of a rock outcrop, 30 X 12 X 8 ft., with aluminum cap mkd.
	T 34 N R 9 W
	AP 2
	MLWA \
	\sqrt{s} 24
	\
	2003
	Raise mound of stone, 2 ft. base to top.
	S. 80°46' E., on line 2-3, sec. 24.

T.	34 N.	, R.	9	W.,	Gila	and	Salt	River	Meridian,	Arizona

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
7.98	Point for AP 3, sec. 24.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA
	S 24 AP 3
	2003
	S. 45°04' E., on line 3-4, sec. 24.
4.38	Point for AP 4, sec. 24.
	Set an aluminum drive rod, 37 ins. long, 3/4 in. diam., 31 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA AP 4
	S 24
	2003
	N. 44°35' E., on line 4-5, sec. 24.
6.58	Point for AP 5, sec. 24, identical with AP 1, sec. 19, T. 34 N., R. 8 W., on the E. bdy of the Tp., hereinbefore described.
	From AP 6, sec. 24, identical with AP 54, sec. 19, T. 34 N., R. 8 W., on the E. bdy. of the Tp., hereinbefore described.
	S. 35°14' W., on line 6-7, sec. 24.
	Thence, along BLM road 1023.
5.11	AP 7, sec. 24, identical with AP 16, sec. 25, on the line bet. secs. 24 and 25, hereinbefore described.
	From this cor. point, the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., bears S. 89°49' E., 2.95 chs. dist., hereinbefore described.

CHAINS	1. 34 K., K. 9 W., Gila and Sait River Meridian, Arizona
	In Section 25
	Note: AP 16 through AP 32 in section 25, are offset 45 lks., more or less, southerly and or easterly of BLM road 1023, excluding it from the wilderness area.
	From AP 16, sec. 25, identical with AP 7, sec. 24, on the line bet. secs. 24 and 25
	S. 72°35' W., on line 16-17, sec. 25.
	Thence, along BLM road 1023.
1.60	Point for AP 17, sec. 25.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 25
	AP 17 MLWA
	2003
	N. 71°52' W., on line 17-18, sec. 25.
1.57	AP 18, sec. 25, on the line bet. secs. 24 and 25, hereinbefore described.
	From this cor. point, the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp. bears S. 89°49' E., 5.96 chs. dist., hereinbefore described.
	From AP 19, sec. 25, on the line bet. secs. 24 and 25, hereinbefore described.
	From this cor. point, the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp. bears S. 89°49' E., 14.29 chs. dist., hereinbefore described.
	S. 12°36' W., on line 19-20, sec. 25.
7.82	Point for AP 20, sec. 25.
	Set an aluminum drive rod, 32 ins. long, 3/4 in. diam., 27 ins. in the ground to refusal, with aluminum cap mkd.

CHAINS		
	T 34 N R 9 W	
	\$ 25 /	
	AP 20	
	MLWA	
	2003	
	N. 56°08' W., on line 20-21, sec. 25.	
9.92	Point for AP 21, sec. 25.	
	Set an aluminum drive rod, 30 ins. long, 3/4 in. diam., 18 i in the ground to refusal, with aluminum cap mkd.	ins
	T 34 N R 9 W	
	s 25	
	AP 21	
	MLWA	
	2003	
	S. 71°15' W., on line 21-22, sec. 25.	
6.19	Point for AP 22, sec. 25.	
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 i in the ground, with aluminum cap mkd.	ins
	T 34 N R 9 W	
	S 25 AP 22 MLWA	
	2003	
	S. 35°54' W., on line 22-23, sec. 25.	
6.71	Point for AP 23, sec. 25.	
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 in the ground, with aluminum cap mkd.	ins

Metes-and-Bounds Survey of the Mount Logan Wilderness Area Boundary, R. 9 W. Gila and Salt River Meridian, Ari

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	S 25 AP 23
	MLWA
	2003
	S. 54°56' W., on line 23-24, sec. 25.
11.69	Point for AP 24, sec. 25.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 35 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 25 /AP 24
	MLWA
	2003
	S. 70°48' W., on line 24-25, sec. 25.
4.86	Point for AP 25, sec. 25.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	s 25
	AP 25
	MLWA
	2003
	G 55°171 77 25 25
	S. 55°17' W., on line 25-26, sec. 25.
7.77	Point for AP 26, sec. 25.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.
	I

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Ar	:izona
CHAINS		
	T 34 N R 9 W	
	s 25 _	
	AP 26	
	MLWA	
	2003	
	S. 86°01' W., on line 26-27, sec. 25.	
5.86	Point for AP 27, sec. 25.	
	Set an aluminum drive rod, 42 ins. long, 3/4 in. in the ground, with aluminum cap mkd.	diam., 37 ins.
	T 34 N R 9 W	
	S 25 AP 27 MLWA	
	2003	
	S. 58°26' W., on line 27-28, sec. 25.	
5.43	Point for AP 28, sec. 25.	
	Set an aluminum drive rod, 42 ins. long, 3/4 in. in the ground, with aluminum cap mkd.	diam., 37 ins.
	T 34 N R 9 W	
	S 25 AP 28 MLWA	
	2003	
	S. 17°33' W., on line 28-29, sec. 25.	
4.91	Point for AP 29, sec. 25.	
	Set an aluminum drive rod, 42 ins. long, 3/4 in. in the ground, with aluminum cap mkd.	diam., 38 ins.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	S 25 / AP 29
	MLWA MLWA
	2003
	S. 44°54' W., on line 29-30, sec. 25.
7.59	Point for AP 30, sec. 25.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 36 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 25 AP 30 MLWA
	,
	2003
	S. 30°30' W., on line 30-31, sec. 25.
5.39	Point for AP 31, sec. 25.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 25 / AP 31
	S 25 AP 31 MLWA
	2003
	S. 37°58' W., on line 31-32, sec. 25.
5.90	Point for AP 32, sec. 25, on the 5200 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 25 AP 32
	2003 MLWA

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	Leave BLM road 1023.
	S. 8°04' E., on line 32-33, sec. 25.
5.46	Point for AP 33, sec. 25, on the 5200 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 25 AP 33 MLWA
	2003
	S. 30°28' E., on line 33-34, sec. 25.
5.63	Point for AP 34, sec. 25, on the 5200 ft. contour.
	Set an aluminum drive rod, 31 ins. long, 3/4 in. diam., 26 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA
	S 25 AP 34
	2003
	S. 63°20' E., on line 34-35, sec. 25.
7.14	Point for AP 35, sec. 25, on the 5200 ft. contour.
	Set an aluminum drive rod, 26 ins. long, 3/4 in. diam., 21 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA
	S 25 AP 35
	2003
	S. 38°07' E., on line 35-36, sec. 25.
8.27	Point for AP 36, sec. 25, on the 5200 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground, with aluminum cap mkd.
	·

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	S 25 \AP 36
	2003
	S. 7°05' E., on line 36-37, sec. 25.
6.38	Point for AP 37, sec. 25, on the 5200 ft. contour.
	Set an aluminum drive rod, 24 ins. long, 3/4 in. diam., 19 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
	MLWA
	S 25 / AP 37
	2003
	S. 5°39' W., on line 37-38, sec. 25.
5.43	Point for AP 38, sec. 25.
	Set an aluminum drive rod, 18 ins. long, 3/4 in. diam., 12 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
	S 25 \(AP 38
	2003
	2003
	S. 50°15' E., on line 38-39, sec. 25.
5.49	AP 39, sec. 25, identical with AP 1, sec. 36, hereinbefore described.
	From this cor. point, the 1/4 sec. cor. of secs. 25 and 36, bears N. 89°51' E., 18.52 chs. dist., hereinbefore described.
	In Section 36
	From AP 1, sec. 36, identical with AP 39, sec. 25, on the line bet. secs. 25 and 36.

Metes-and-Bounds Survey of the Mount Logan Wilderness Area Boundary, R. 9 W., Gila and Salt River Meridian, Arizona

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	S. 38°26' W., on line 1-2, sec. 36.
4.40	Point for AP 2, sec. 36, on the 5200 ft. contour.
	Set an aluminum drive rod, 30 ins. long, 3/4 in. diam., 26 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
	s 36 AP 2 MLWA
	MLWA
	2003
	S. 35°35' E., on line 2-3, sec. 36.
5.66	Point for AP 3, sec. 36, on the 5200 ft. contour.
	Set an aluminum drive rod, 23 ins. long, 3/4 in. diam., 16 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
	S 36 AP 3
	/ MLWA
	2003
	S. 14°08' W., on line 3-4, sec. 36.
5.38	Point for AP 4, sec. 36, on the 5200 ft. contour.
	Set an aluminum drive rod, 38 ins. long, 3/4 in. diam., 34 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
	S 36 AP 4 MLWA
	2003
	S. 31°24' E., on line 4-5, sec. 36.
6.10	Point for AP 5, sec. 36.
	Set an aluminum drive rod, 28 ins. long, $3/4$ in. diam., 24 ins. in the ground to refusal, with aluminum cap mkd.

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	T 34 N R 9 W
	s 36 AP 5
	\ MLWA
	2003
	S. 12°57' E., on line 5-6, sec. 36.
11.02	Point for AP 6, sec. 36, on the 5200 ft. contour.
	Set an aluminum drive rod, 33 ins. long, $3/4$ in. diam., 27 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
	S 36 AP 6
	2003
	S. 25°15' E., on line 6-7, sec. 36.
5.97	Point for AP 7, sec. 36, on the 5200 ft. contour.
	Set an aluminum drive rod, 29 ins. long, 3/4 in. diam., 21 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
	\ MLWA
	s 36 AP 7
	2003
	S. 64°16' E., on line 7-8, sec. 36.
5.40	Point for AP 8, sec. 36, on the 5200 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins.
	in the ground, with aluminum cap mkd.
	T 34 N R 9 W
	S 36 AP 8
	MLWA
	2003
	·····
I	

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	S. 16°09' E., on line 8-9, sec. 36.
6.43	Point for AP 9, sec. 36, on the 5200 ft. contour.
	Set an aluminum drive rod, 21 ins. long, 3/4 in. diam., 16 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
	s 36 AP 9 MLWA
	2003
	S. 36°10' E., on line 9-10, sec. 36.
9.75	Point for AP 10, sec. 36, on the 5200 ft. contour.
	Set an aluminum drive rod, 31 ins. long, 3/4 in. diam., 27 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
	S 36 AP 10 MLWA
	2003
	S. 1°34' W., on line 10-11, sec. 36.
5.80	Point for AP 11, sec. 36, on the 5200 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 38 ins. in the ground to refusal, with aluminum cap mkd.
	T 34 N R 9 W
	S 36 AP 11 MLWA
	2003
	S. 30°21' E., on line 11-12, sec. 36.
5.81	Point for AP 12, sec. 36, on the 5200 ft. contour.
	Set an aluminum drive rod, 42 ins. long, 3/4 in. diam., 37 ins. in the ground, with aluminum cap mkd.

T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona

CHAINS T 34 N R 9 W S 36 \AP 12 MLWA 2003 S. 39°41' E., on line 12-13, sec. 36. 10.04 Point for AP 13, sec. 36, on the 5200 ft. contour. Set an aluminum drive rod, 25 ins. long, 3/4 in. diam., 21 ins. in the ground to refusal, with aluminum cap mkd. T 34 N R 9 W S 36 AP 13 MLWA 2003 S. 29°03' E., on line 13-14 sec. 36. 11.90 AP 14, sec. 36, identical with AP 1, sec. 1, T. 33 N., R. 9 W., on the S. bdy. of the Tp., hereinbefore described. GENERAL DESCRIPTION The area embraced by this survey lies in the Sawmill Mountains, on the Uinkaret plateau. The terrain is mountainous and rolling, Mount Logan, the highest point, is located in the west one half of section 12. West of Mount Logan lies Hells Hole, a nearly inaccessible depression, 2000 ft. below Mount Logan. Heavy stands of ponderosa pine, oak and juniper are found throughout the area. The soil is generally 3rd and 4th rate. Hiking, camping and ranching are the primary uses of the land. The mean magnetic declination of 13° E., was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2000 for the dates of the survey.

T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona

CHAINS

Description of the Mount Logan Wilderness Area Bdy. T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona

The following is for informational purposes only.

Beginning at Angle Point 1, sec. 13, identical with Angle Point 33, sec. 18, T. 34 N., R. 8 W., on the E. bdy. of the Tp.

thence S. 80°12' W., 1.97 chs. dist. to Angle Point 2, sec. 13; thence N. 88°45' W., 1.92 chs. dist. to Angle Point 3, sec. 13; thence N. 45°26' W., 4.45 chs. dist. to Angle Point 4, sec. 13; thence N. 46°13' W., 3.18 chs. dist. to Angle Point 5, sec. 13; thence N. 24°13' W., 5.63 chs. dist. to Angle Point 6, sec. 13; thence N. 5°00' E., 3.27 chs. dist. to Angle Point 7, sec. 13; thence N. 17°06' E., 2.82 chs. dist. to Angle Point 8, sec. 13; thence N. 14°02' E., 2.81 chs. dist. to Angle Point 9, sec. 13; thence N. 2°16' E., 2.53 chs. dist. to Angle Point 10, sec. 13; thence N. 17°16' E., 1.99 chs. dist. to Angle Point 11, sec. 13; thence N. 37°34' W., 2.29 chs. dist. to Angle Point 12, sec. 13; thence N. 48°46' W., 3.16 chs. dist. to Angle Point 13, sec. 13; thence N. 17°02' E., 4.27 chs. dist. to Angle Point 14, sec. 13; thence N. 19°30' W., 0.41 ch. dist. to Angle Point 15, sec. 13, identical with Angle Point 1, sec. 12, on the line bet. secs. 12 and 13;

thence N. 19°30' W., 2.70 chs. dist. to Angle Point 2, sec. 12; thence N. 32°58' W., 4.06 chs. dist. to Angle Point 3, sec. 12; thence N. 30°33' W., 6.68 chs. dist. to Angle Point 4, sec. 12; thence N. 2°53' E., 5.78 chs. dist. to Angle Point 5, sec. 12; thence N. 14°14' W., 2.64 chs. dist. to Angle Point 6, sec. 12; thence N. 37°07' W., 2.69 chs. dist. to Angle Point 7, sec. 12; thence N. 18°42' W., 5.41 chs. dist. to Angle Point 8, sec. 12; thence N. 40°31' E., 1.64 chs. dist. to Angle Point 9, sec. 12; thence N. 69°35' E., 2.91 chs. dist. to Angle Point 10, sec. 12; thence N. 3°01' E., 4.78 chs. dist. to Angle Point 11, sec. 12; 1°31' W., 1.77 chs. dist. to Angle Point 12, sec. 12; thence N. thence N. 77°01' W., 1.63 chs. dist. to Angle Point 13, sec. 12; thence N. 1°20' W., 5.09 chs. dist. to Angle Point 14, sec. 12; thence N. 8°24' W., 3.89 chs. dist. to Angle Point 15, sec. 12; thence N. 61°02' W., 2.48 chs. dist. to Angle Point 16, sec. 12; thence N. 29°18' W., 1.11 chs. dist. to Angle Point 17, sec. 12; thence N. 20°15' W., 1.80 chs. dist. to Angle Point 18, sec. 12; thence N. 47°39' W., 31.38 chs. dist. to Angle Point 19, sec. 12; thence N. 61°04' W., 9.03 chs. dist. to Angle Point 20, sec. 12; thence N. 85°19' W., 25.24 chs. dist. to Angle Point 21, sec. 12; thence N. 85°36' W., 0.17 ch. dist. to Angle Point 22, sec. 12, identical with Angle Point 1, sec. 11, on the line bet.

secs. 11 and 12;
thence N. 85°36' W., 13.88 chs. dist. to Angle Point 2, sec. 11;
thence N. 56°17' W., 3.94 chs. dist. to Angle Point 3, sec. 11,
 identical with Angle Point 1, sec. 2, on the line bet.
 secs. 2 and 11;

T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona

```
CHAINS
          thence N. 56°17' W., 3.29 chs. dist. to Angle Point 2, sec. 2;
          thence N. 9°47' W., 2.04 chs. dist. to Angle Point 3, sec. 2;
         thence N. 44°01' W., 15.78 chs. dist. to Angle Point 4, sec. 2;
         thence S. 36°34' W., 7.31 chs. dist. to Angle Point 5, sec. 2;
         thence S. 24°13' W., 10.24 chs. dist. to Angle Point 6, sec. 2,
               identical with Angle Point 4, sec. 11, and the 1/4 sec.
               cor. of secs. 2 and 11;
         thence S. 68°50' W., 4.52 chs. dist. to Angle Point 5, sec. 11;
         thence S. 67°00' W., 8.84 chs. dist. to Angle Point 6, sec. 11;
         thence S. 61°31' W., 7.63 chs. dist. to Angle Point 7, sec. 11;
         thence S. 65°25' W., 5.14 chs. dist. to Angle Point 8, sec. 11;
         thence S. 75°32' W., 8.54 chs. dist. to Angle Point 9, sec. 11;
         thence S. 46°33' W., 2.94 chs. dist. to Angle Point 10, sec. 11;
         thence S. 78°36' W., 5.91 chs. dist. to Angle Point 11, sec. 11,
               identical with Angle Point 1, sec. 10, on the line bet.
               secs. 10 and 11;
         thence S. 78°36' W., 11.59 chs. dist. to Angle Point 2, sec. 10;
         thence S. 9°59' W., 8.22 chs. dist. to Angle Point 3, sec. 10;
         thence S. 14°01' W., 26.53 chs. dist. to Angle Point 4, sec. 10;
         thence S. 30°06' W., 7.43 chs. dist. to Angle Point 5, sec. 10;
         thence S. 19°18' W., 14.29 chs. dist. to Angle Point 6, sec. 10;
         thence S. 36°32' E., 7.37 chs. dist. to Angle Point 7, sec. 10;
         thence S. 0°48' E., 1.88 chs. dist. to Angle Point 8, sec. 10,
               identical with Angle Point 1, sec. 15, on the line bet.
               secs. 10 and 15;
         thence S. 89°55' W., 16.83 chs. dist., bet. secs. 10 and 15, to
               the 1/4 sec. cor. of sections 10 and 15, identical with
               Angle Point 2, sec. 15;
         thence S. 89°58' W., 5.50 chs. dist., bet. secs. 10 and 15, to
               Angle Point 3, sec. 15;
         thence S. 34°08' W., 3.79 chs. dist. to Angle Point 4, sec. 15;
         thence S. 2°25' W., 7.67 chs. dist. to Angle Point 5, sec. 15;
         thence S. 25°09' W., 4.75 chs. dist. to Angle Point 6, sec. 15;
         thence S. 31°37' W., 9.79 chs. dist. to Angle Point 7, sec. 15;
         thence S. 22°05' W.,
                              9.68 chs. dist. to Angle Point 8, sec. 15;
         thence S. 18°23' W., 4.28 chs. dist. to Angle Point 9, sec. 15;
         thence S. 1°58' E., 13.73 chs. dist. to Angle Point 10, sec. 15;
         thence S. 18°18' E., 3.55 chs. dist. to Angle Point 11, sec. 15;
         thence S. 49°58' W., 8.28 chs. dist. to Angle Point 12, sec. 15;
         thence S. 44°05' W., 20.59 chs. dist. to Angle Point 13, sec. 15;
         thence S. 8°58' W, 6.48 chs. dist. to Angle Point 14, sec. 15,
               identical with Angle Point 1, sec. 21, and the cor. of
               secs. 15, 16, 21 and 22;
         thence S. 65°24' W., 13.72 chs. dist. to Angle Point 2, sec. 21;
         thence S. 84°11' W., 18.41 chs. dist. to Angle Point 3, sec. 21;
         thence N. 72°31' W.,
                             7.59 chs. dist. to Angle Point 4, sec. 21;
        thence N. 88°32' W., 5.52 chs. dist. to Angle Point 5, sec. 21;
        thence S. 69°33' W., 11.08 chs. dist. to Angle Point 6, sec. 21;
        thence S. 67°09' W., 5.78 chs. dist. to Angle Point 7, sec. 21;
        thence S. 48°50' W., 5.51 chs. dist. to Angle Point 8, sec. 21;
        thence S. 80°36' W., 5.81 chs. dist. to Angle Point 9, sec. 21;
        thence S. 64°23' W., 5.58 chs. dist. to Angle Point 10, sec. 21;
```

T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona CHAINS thence S. 75°24' W., 5.65 chs. dist. to Angle Point 11, sec. 21, identical with Angle Point 1, sec. 20, on the line bet. secs. 20 and 21; thence S. 52°52' W., 3.49 chs. dist. to Angle Point 2, sec. 20; thence S. 14°50' E., 6.37 chs. dist. to Angle Point 3, sec. 20; thence S. 15°01' W., 7.63 chs. dist. to Angle Point 4, sec. 20; thence S. 30°30' W., 6.79 chs. dist. to Angle Point 5, sec. 20; thence S. 59°22' E., 3.80 chs. dist. to Angle Point 6, sec. 20; thence S. 11°35' E., 6.04 chs. dist. to Angle Point 7, sec. 20; thence S. 16°07' E., 7.66 chs. dist. to Angle Point 8, sec. 20, identical with Angle Point 12, sec. 21, on the line bet. secs. 20 and 21; thence S. 39°19' E., 6.26 chs. dist. to Angle Point 13, sec. 21; thence S. 43°52' E., 8.02 chs. dist. to Angle Point 14, sec. 21; thence N. 32°22' E., 5.55 chs. dist. to Angle Point 15, sec. 21; thence N. 68°48' E., 6.22 chs. dist. to Angle Point 16, sec. 21; thence S. 16°07' W., 6.31 chs. dist. to Angle Point 17, sec. 21; thence S. 41°25' E., 6.12 chs. dist. to Angle Point 18, sec. 21; thence S. 80°20' E., 5.99 chs. dist. to Angle Point 19, sec. 21; thence S. 31°17' W., 6.09 chs. dist. to Angle Point 20, sec. 21; thence S. 60°51' W., 5.74 chs. dist. to Angle Point 21, sec. 21, identical with Angle Point 1, sec. 28, on the line bet. secs. 21 and 28; thence S. 25°23' W., 5.53 chs. dist. to Angle Point 2, sec. 28; thence S. 37°35' E., 6.09 chs. dist. to Angle Point 3, sec. 28; thence S. 32°24' E., 5.93 chs. dist. to Angle Point 4, sec. 28; thence S. 89°12' E., 6.49 chs. dist. to Angle Point 5, sec. 28; thence N. 59°39' E., 6.52 chs. dist. to Angle Point 6, sec. 28; thence N. 50°09' E., 12.18 chs. dist. to Angle Point 7, sec. 28; thence N. 79°41' E., 4.87 chs. dist. to Angle Point 8, sec. 28; thence S. 27°28' W., 5.84 chs. dist. to Angle Point 9, sec. 28; thence S. 20°33' W., 5.20 chs. dist. to Angle Point 10, sec. 28; thence S. 12°26' E., 5.57 chs. dist. to Angle Point 11, sec. 28; thence S. 14°43' E., 5.34 chs. dist. to Angle Point 12, sec. 28; thence S. 30°52' E., 5.68 chs. dist. to Angle Point 13, sec. 28; thence S. 64°26' E., 6.32 chs. dist. to Angle Point 14, sec. 28; thence S. 88°45' E., 8.80 chs. dist. to Angle Point 15, sec. 28; thence S. 81°00' E., 5.70 chs. dist. to Angle Point 16, sec. 28; thence N. 76°02' E., 6.16 chs. dist. to Angle Point 17, sec. 28; thence N. 33°51' E., 6.30 chs. dist. to Angle Point 18, sec. 28, identical with Angle Point 1, sec. 27, on the line bet. secs. 27 and 28; thence S. 68°37' E., 5.66 chs. dist. to Angle Point 2, sec. 27; thence S. 83°18' E., 5.56 chs. dist. to Angle Point 3, sec. 27; thence N. 72°07' E., 5.28 chs. dist. to Angle Point 4, sec. 27; thence N. 58°38' E., 6.40 chs. dist. to Angle Point 5, sec. 27; thence N. 60°45' E., 12.42 chs. dist. to Angle Point 6, sec. 27; thence S. 60°16' E., 7.21 chs. dist. to Angle Point 7, sec. 27; thence S. 74°33' E., 7.03 chs. dist. to Angle Point 8, sec. 27; thence N. 23°07' E., 5.69 chs. dist. to Angle Point 9, sec. 27; thence N. 57°54' E., 6.56 chs. dist. to Angle Point 10, sec. 27; thence S. 76°14' E., 6.03 chs. dist. to Angle Point 11, sec. 27; thence N. 27°39' E., 5.23 chs. dist. to Angle Point 12, sec. 27;

```
CHAINS
          thence N. 51°17' E., 6.52 chs. dist. to Angle Point 13, sec. 27;
          thence N. 68°53' E., 8.74 chs. dist. to Angle Point 14, sec. 27;
         thence S. 10^{\circ}52' E., 4.31 chs. dist. to Angle Point 15, sec. 27; thence N. 79^{\circ}30' E., 5.02 chs. dist. to Angle Point 16, sec. 27,
                identical with Angle Point 1, sec. 26, on the line bet.
                secs. 26 and 27;
          thence S. 49°15' E., 5.74 chs. dist. to Angle Point 2, sec. 26;
          thence N. 62°58' E., 5.49 chs. dist. to Angle Point 3, sec. 26;
          thence S. 31°24' E., 5.91 chs. dist. to Angle Point 4, sec. 26;
          thence S. 16°15' E.,
                               5.01 chs. dist. to Angle Point 5, sec. 26;
          thence N. 35°01' E.,
                               5.68 chs. dist. to Angle Point 6, sec. 26;
         thence N. 8°14' E., 5.73 chs. dist. to Angle Point 7, sec. 26;
         thence N. 51°45' E., 5.98 chs. dist. to Angle Point 8, sec. 26;
                              5.98 chs. dist. to Angle Point 9, sec. 26;
         thence S. 3°03' E.,
         thence S. 33°29' E., 5.52 chs. dist. to Angle Point 10, sec. 26;
         thence S. 20°02' E., 5.37 chs. dist. to Angle Point 11, sec. 26;
         thence S. 56°46' E., 5.64 chs. dist. to Angle Point 12, sec. 26;
         thence S. 35°15' E., 6.16 chs. dist. to Angle Point 13, sec. 26;
         thence N. 72°53' E., 5.67 chs. dist. to Angle Point 14, sec. 26;
         thence S. 86°36' E., 5.57 chs. dist. to Angle Point 15, sec. 26;
         thence S. 67°25' E.,
                               5.87 chs. dist. to Angle Point 16, sec. 26;
         thence N. 52°44' E.,
                              4.89 chs. dist. to Angle Point 17, sec. 26;
         thence N. 21°09' E., 6.18 chs. dist. to Angle Point 18, sec. 26;
         thence N. 41°28' E., 5.60 chs. dist. to Angle Point 19, sec. 26;
         thence N. 21°11' E., 12.49 chs. dist. to Angle Point 20, sec. 26;
         thence N. 62°52' E., 3.90 chs. dist. to Angle Point 21, sec. 26;
         thence S. 27°49' W.,
                               7.02 chs. dist. to Angle Point 22, sec. 26;
         thence S. 2°32' E.,
                               7.59 chs. dist. to Angle Point 23, sec. 26;
         thence S. 18°10' W.,
                               7.36 chs. dist. to Angle Point 24, sec. 26;
         thence S. 7°21' W., 6.26 chs. dist. to Angle Point 25, sec. 26;
         thence S. 54°15' E.,
                              6.59 chs. dist. to Angle Point 26, sec. 26;
         thence S. 87°50' E., 5.44 chs. dist. to Angle Point 27, sec. 26;
         thence S. 66°43' E.,
                              5.13 chs. dist. to Angle Point 28, sec. 26,
               identical with Angle Point 1, sec. 25, on the line bet.
               secs. 25 and 26;
         thence S. 10°13' E., 8.56 chs. dist. to Angle Point 2, sec. 25;
         thence N. 37°39' E., 5.34 chs. dist. to Angle Point 3, sec. 25;
         thence N. 31°15' E., 5.49 chs. dist. to Angle Point 4, sec. 25;
         thence N. 44°45' E.,
                              6.51 chs. dist. to Angle Point 5, sec. 25;
         thence N. 23°11' E.,
                              7.24 chs. dist. to Angle Point 6, sec. 25;
         thence N. 65°11' E.,
                              5.78 chs. dist. to Angle Point 7, sec. 25;
         thence N. 88°45' E., 5.30 chs. dist. to Angle Point 8, sec. 25;
         thence N. 51°02' E., 9.28 chs. dist. to Angle Point 9, sec. 25;
         thence N. 80°27' E.,
                              4.56 chs. dist. to Angle Point 10, sec. 25;
         thence N. 45°49' E., 18.89 chs. dist. to Angle Point 11, sec. 25;
         thence N. 74°52' E., 3.56 chs. dist. to Angle Point 12, sec. 25;
         thence S. 74°38' E.,
                              5.19 chs. dist. to Angle Point 13, sec. 25;
         thence S. 43°58' E., 5.67 chs. dist. to Angle Point 14, sec. 25;
         thence N. 16°34' E.,
                              6.19 chs. dist. to Angle Point 15, sec. 25,
               identical with Angle Point 1, sec. 24, on the line bet.
               secs. 24 and 25;
         thence N. 3°34' W., 5.12 chs. dist. to Angle Point 2, sec. 24;
         thence S. 80°46' E., 7.98 chs. dist. to Angle Point 3, sec. 24;
```

T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona

CHAINS

thence S. 45°04' E., 4.38 chs. dist. to Angle Point 4, sec. 24; thence N. 44°35' E., 6.58 chs. dist. to Angle Point 5, sec. 24, identical with Angle Point 1, sec. 19, T. 34 N. R. 8 W., on the E. bdy. of the Tp.

From Angle Point 6, sec. 24, identical with Angle Point 54, sec. 19, T. 34 N., R. 8 W., on the E. bdy. of the Tp.

thence S. 35°14' W., 5.11 chs. dist. to Angle Point 7, sec. 24, identical with Angle Point 16, sec. 25, on the line bet. secs. 24 and 25.

thence S. 72°35' W., 1.60 chs. dist. to Angle Point 17, sec. 25; thence N. 71°52' W., 1.57 chs. dist. to Angle Point 18, sec. 25, on the line bet. secs. 24 and 25.

thence N. 89°49' W., 8.33 chs. dist., bet. secs. 24 and 25, to Angle Point 19, sec. 25;

thence S. 12°36' W., 7.82 chs. dist. to Angle Point 20, sec. 25; thence N. 56°08' W., 9.92 chs. dist. to Angle Point 21, sec. 25; thence S. 71°15' W., 6.19 chs. dist. to Angle Point 22, sec. 25; thence S. 35°54' W., 6.71 chs. dist. to Angle Point 23, sec. 25; thence S. 54°56' W., 11.69 chs. dist. to Angle Point 24, sec. 25; thence S. 70°48' W., 4.86 chs. dist. to Angle Point 25, sec. 25; thence S. 55°17' W., 7.77 chs. dist. to Angle Point 26, sec. 25; thence S. 86°01' W., 5.86 chs. dist. to Angle Point 27, sec. 25; thence S. 58°26' W., 5.43 chs. dist. to Angle Point 28, sec. 25; thence S. 17°33' W., 4.91 chs. dist. to Angle Point 29, sec. 25; thence S. 44°54' W., 7.59 chs. dist. to Angle Point 30, sec. 25; thence S. 30°30' W., 5.39 chs. dist. to Angle Point 31, sec. 25; thence S. 37°58' W., 5.90 chs. dist. to Angle Point 32, sec. 25; thence S. 8°04' E., 5.46 chs. dist. to Angle Point 33, sec. 25; thence S. 30°28' E., 5.63 chs. dist. to Angle Point 34, sec. 25; thence S. 63°20' E., 7.14 chs. dist. to Angle Point 35, sec. 25; thence S. 38°07' E., 8.27 chs. dist. to Angle Point 36, sec. 25; thence S. 7°05' E., 6.38 chs. dist. to Angle Point 37, sec. 25; thence S. 5°39' W., 5.43 chs. dist. to Angle Point 38, sec. 25; thence S. 50°15' E., 5.49 chs. dist. to Angle Point 39, sec. 25, identical with Angle Point 1, sec. 36, on the line bet.

secs. 25 and 36;

thence S. 38°26' W., 4.40 chs. dist. to Angle Point 2, sec. 36;

thence S. 35°35' E., 5.66 chs. dist. to Angle Point 3, sec. 36;

thence S. 14°08' W., 5.38 chs. dist. to Angle Point 4, sec. 36;

thence S. 31°24' E., 6.10 chs. dist. to Angle Point 5, sec. 36;

thence S. 12°57' E., 11.02 chs. dist. to Angle Point 6, sec. 36;

thence S. 25°15' E., 5.97 chs. dist. to Angle Point 7, sec. 36;

thence S. 64°16' E., 5.40 chs. dist. to Angle Point 8, sec. 36;

thence S. 16°09' E., 6.43 chs. dist. to Angle Point 9, sec. 36;

thence S. 36°10' E., 9.75 chs. dist. to Angle Point 10, sec. 36;

thence S. 30°21' E., 5.81 chs. dist. to Angle Point 11, sec. 36;

thence S. 39°41' E., 10.04 chs. dist. to Angle Point 13, sec. 36;

	T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona
CHAINS	
	thence S. 29°03' E., 11.90 chs. dist. to Angle Point 14, sec. 36, identical with Angle Point 1, sec. 1, T. 33 N., R. 8 W., on the S. bdy, of the Tp.
·	

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

FIELD ASSISTANTS				
NAMES	CAPACITY			
Stephen K. Hansen	Land Surveyor			
Daniel L. Maxey	Land Surveyor			
Joe R. Salazar	Land Surveyor			
W. William Foster	Surveying Technician			
Cheryl A. Hansen	Surveying Technician			
Robert J. Lyle	Surveying Technician			
Mark R. Searles	Surveying Technician			

CERTIFICATE OF SURVEY

We, Gordon R. Bubel and Geoffrey A. Graham, Cadastral Surveyors, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 31st day of August, 1998, We have dependently resurveyed a portion of the Second Guide Meridian West (east boundary), a portion of the south boundary and a portion of the subdivisional lines and executed the metes-and-bounds survey of the Mount Logan Wilderness Area Boundary, in T. 34 N., R. 9 W., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

5/10/2006	M. R. Bild
(Date)	(Cadastral Surveyor)
S/10/2006 (Date)	M. A. A. June (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Phoenix, Arizona

The foregoing field notes of the dependent resurvey of a portion of the Second Guide Meridian West (east boundary), a portion of the south boundary and a portion of the subdivisional lines and the metes-and-bounds survey of the Mount Logan Wilderness Area Boundary, T. 34 N., R. 9 W., Gila and Salt River Meridian, in the State of Arizona, executed by Gordon R. Bubel and Geoffrey A. Graham, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

5/18/2006
(Acting Chief Cadastral Surveyor of Arizona)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 34 N., R. 9 W., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.

(Date) (Acting Chief Cadastral Surveyor of Arizona)