

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE FOURTH GUIDE MERIDIAN EAST (EAST BOUNDARY),

THE SOUTH AND NORTH BOUNDARIES

AND THE SUBDIVISIONAL LINES

AND

THE SURVEY OF THE SUBDIVISION  
OF ALL SECTIONS

**TOWNSHIP 22 NORTH, RANGE 16 EAST,**

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA.

**EXECUTED BY**

**Joe R. Salazar, Cadastral Surveyor**

Under Special Instructions dated April 29, 2005, approved April 29, 2005, which provided for the surveys included under Group No. 958, and assignment instructions dated December 15, 2006.

**Survey commenced January 9, 2007**

**Survey completed May 2, 2007**

**INDEX DIAGRAM**

TOWNSHIP 22 NORTH                      RANGE 16 EAST  
GILA AND SALT RIVER MERIDIAN, ARIZONA

19 6 66	18 5 54	18 4 44	17 3 36	16 2 27	15 1 9
65 7 63	64 8 52	53 9 42	43 10 34	35 11 25	26 12 8
62 18 61	62 17 50	51 16 40	41 15 32	33 14 24	25 13 7
60 19 58	59 20 47	48 21 39	40 22 31	32 23 23	23 24 6
58 30 57	57 29 46	47 28 38	39 27 29	30 26 21	22 25 5
56 31 55 15	56 32 44 14	45 33 36 13	37 34 28 12	29 35 20 11	21 36 4 10

Subdivision of all Sections ..... Pages 67-101

**T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS

The following field notes describe the dependent resurvey of the Fourth Guide Meridian East (east boundary), the south and north boundaries and the subdivisional lines and the survey of the subdivision of all sections., Township 22 North, Range 16 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Orville D. Wheeler surveyed the Fourth Guide Meridian East (east boundary), the south and north boundaries and the subdivisional lines, in 1882. Joe R. Salazar resurveyed the west boundary in 2004-05.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 1973, and the Special Instructions dated April 29, 2005, for Group No. 958, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation 5700 model receivers.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) Ashler Hills, Flagstaff 1 and Gila County. The NAD 83 (CORS96) (Epoch 2002), geographic position of the corner of Townships 21 and 22 North, Ranges 16 and 17 East, is as follows:

Latitude: 35°15'26.82" N.                      Longitude: 110°35'07.94" W.

The mean magnetic declination is 11 1/4 ° E.

---

Dependent Resurvey of the Fourth Guide Meridian East (East boundary),  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona

CHAINS

Restoring the survey executed by  
Orville D. Wheeler, in 1882

Beginning at the cor. of Tps. 21 and 22 N., Rs. 16 and 17 E.,  
monumented with a weathered and fragmented sandstone,  
14 X 12 X 8 ins., firmly set 6 ins. in the ground, clearly mkd.  
with 6 grooves on N. face.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with brass cap mkd.

	T 22 N	
R 16 E		R 17 E
S 36		S 31
S 1		S 6
	T 21 N	

2007

Deposit a magnet in a white plastic case at the base of and the  
orig. stone alongside of the stainless steel post.

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, S. of cor.

N. 1°18' E., bet. secs. 31 and 36, on the E. bdy. of the Tp.

Over severely broken terrain, through scattered sage brush and  
Mormon Tea.

40.41 The 1/4 sec. cor. of secs. 31 and 36, monumented with a  
weathered and fragmented flint stone, 12 X 9 X 8 ins., firmly  
set, 3 ins. in the ground, with no visible marks.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
22 ins. in the ground, with brass cap mkd.

	T 22 N	
	1/4	
R 16 E		R 17 E
S 36		S 31

2007

Deposit a magnet in a white plastic case at the base of and the  
orig. stone alongside of the stainless steel post.

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.

Dependent Resurvey of the Fourth Guide Meridian East (East boundary),  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>N. 0°52' E., beginning new measurement.</p>								
40.47	<p>The cor. of secs. 25, 30, 31 and 36, monumented with a sandstone, 16 X 14 X 12 ins., firmly set 9 ins. in the ground, witnessed with a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>At a corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <table data-bbox="792 745 1036 877" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 22 N</td></tr> <tr><td style="text-align: center;">R 16 E</td><td style="text-align: center;">R 17 E</td></tr> <tr><td style="text-align: center;">S 25</td><td style="text-align: center;">S 30</td></tr> <tr><td style="text-align: center;">S 36</td><td style="text-align: center;">S 31</td></tr> </table> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of and orig. stone alongside of the stainless steel post.</p> <p>Rebuild mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>	T 22 N		R 16 E	R 17 E	S 25	S 30	S 36	S 31
T 22 N									
R 16 E	R 17 E								
S 25	S 30								
S 36	S 31								
40.14	<p>N. 1°41' E., bet. secs. 25 and 30.</p> <p>Over severely broken terrain, through scattered sage brush and Mormon Tea.</p> <p>The 1/4 sec. cor. of secs. 25 and 30, , determined E., 1 lk. dist. from an imbedded mound of stone, 2 1/2 ft. base, 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <table data-bbox="792 1600 1036 1717" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 22 N</td></tr> <tr><td style="text-align: center;">R 16 E</td><td style="text-align: center;">R 17 E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S 25</td><td style="text-align: center;">S 30</td></tr> </table> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 22 N		R 16 E	R 17 E	1/4		S 25	S 30
T 22 N									
R 16 E	R 17 E								
1/4									
S 25	S 30								

Dependent Resurvey of the Fourth Guide Meridian East (East boundary),  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona

CHAINS									
	Rebuild mound of stone, 3 ft. base, 2 ft. high, W. of cor.								
	N. 1°51' E., beginning new measurement.								
39.91	<p>The cor. of secs. 19, 24, 25 and 30, monumented with a flint stone, 16 X 10 X 8 ins., firmly set, 5 ins. in the ground, clearly mkd. with 5 grooves on N. edge and 2 grooves on S. edge, witnessed with a mound of stone, 2 1/2 ft. base, 1 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 22 N</td></tr> <tr><td style="text-align: center;">R 16 E</td><td style="text-align: center;">R 17 E</td></tr> <tr><td style="text-align: center;">S 24</td><td style="text-align: center;">S 19</td></tr> <tr><td style="text-align: center;">S 25</td><td style="text-align: center;">S 30</td></tr> </table>	T 22 N		R 16 E	R 17 E	S 24	S 19	S 25	S 30
T 22 N									
R 16 E	R 17 E								
S 24	S 19								
S 25	S 30								
	2007								
	Deposit a magnet in a white plastic case at the base of and the orig. stone alongside of the stainless steel post.								
	Rebuild mound of stone, 3 ft. base, 2 ft. high, W. of cor.								
	N. 0°43' E., bet. secs. 19 and 24.								
	Over broken terrain, through scattered sage brush and Mormon Tea.								
40.21	<p>The 1/4 sec. cor. of secs. 19 and 24, monumented with a flint stone, 12 X 5 X 5 ins., loosely set 1 in. in the ground, clearly mkd 1/4 on S. face, witnessed with a mound of stone, 3 ft. base, 1 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 22 N</td></tr> <tr><td style="text-align: center;">R 16 E</td><td style="text-align: center;">R 17 E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S 24</td><td style="text-align: center;">S 19</td></tr> </table>	T 22 N		R 16 E	R 17 E	1/4		S 24	S 19
T 22 N									
R 16 E	R 17 E								
1/4									
S 24	S 19								
	2007								

**Dependent Resurvey of the Fourth Guide Meridian East (East boundary),  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<p>Deposit a magnet in a white plastic case at the base of and the orig. stone alongside of the stainless steel post.</p> <p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/> <p>N. 1°06' E., beginning new measurement.</p>								
40.14	<p>Point for the cor. of secs. 13, 18, 19 and 24, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T 22 N</td></tr> <tr><td>R 16 E</td><td>R 17 E</td></tr> <tr><td>S 13</td><td>S 18</td></tr> <tr><td>S 24</td><td>S 19</td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 1°06' E., bet. secs. 13 and 18.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>	T 22 N		R 16 E	R 17 E	S 13	S 18	S 24	S 19
T 22 N									
R 16 E	R 17 E								
S 13	S 18								
S 24	S 19								
40.14	<p>Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">T 22 N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R 16 E</td><td>R 17 E</td></tr> <tr><td>S 13</td><td>S 18</td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 22 N		1/4		R 16 E	R 17 E	S 13	S 18
T 22 N									
1/4									
R 16 E	R 17 E								
S 13	S 18								
80.28	<p>The cor. of secs. 7, 12, 13 and 18, monumented with a flint stone, 16 X 12 X 8 ins., firmly set 4 ins. in the ground, clearly mkd. with 4 grooves on S. face, witnessed with a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>At the corner point</p>								

Dependent Resurvey of the Fourth Guide Meridian East (East boundary),  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 22 N</td></tr> <tr><td style="text-align: center;">R 16 E</td><td style="text-align: center;">R 17 E</td></tr> <tr><td style="text-align: center;">S 12</td><td style="text-align: center;">S 7</td></tr> <tr><td style="text-align: center;">S 13</td><td style="text-align: center;">S 18</td></tr> </table>	T 22 N		R 16 E	R 17 E	S 12	S 7	S 13	S 18
T 22 N									
R 16 E	R 17 E								
S 12	S 7								
S 13	S 18								
	<p style="text-align: center;">2007</p>								
	<p>Deposit a magnet in a white plastic case at the base of and the orig. stone alongside of the stainless steel post.</p>								
	<p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/>								
	<p>N. 0°28' W., bet. secs. 7 and 12.</p>								
	<p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>								
40.02	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented with a flint stone, 14 X 8 X 6 ins., firmly set 2 ins. in the ground, with no visible marks, witnessed with a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.</p>								
	<p>At the corner point</p>								
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 22 N</td></tr> <tr><td style="text-align: center;">R 16 E</td><td style="text-align: center;">R 17 E</td></tr> <tr><td colspan="2" style="text-align: center;">1/4</td></tr> <tr><td style="text-align: center;">S 12</td><td style="text-align: center;">S 7</td></tr> </table>	T 22 N		R 16 E	R 17 E	1/4		S 12	S 7
T 22 N									
R 16 E	R 17 E								
1/4									
S 12	S 7								
	<p style="text-align: center;">2007</p>								
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>								
	<p>Rebuild mound of stone, 3 ft. base, 2 ft. high, W. of cor. and incorporate orig. stone in the mound of stone.</p> <hr/>								
	<p>N. 0°30' E., beginning new measurement.</p>								
40.18	<p>The cor. of secs. 1, 6, 7 and 12, monumented with a sandstone, 16 X 8 X 6 ins., firmly set 3 ins. in the ground, mkd. with X A on W. face, witnessed with a scattered mound of stone, 3 ft. base, 1 ft. high, W. of cor. This is accepted as the best available evidence of the orig. cor. position.</p>								

Dependent Resurvey of the Fourth Guide Meridian East (East boundary),  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona

CHAINS									
	At the corner point								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 22 N</td></tr> <tr><td style="text-align: center;">R 16 E</td><td style="text-align: center;">R 17 E</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td style="text-align: center;">S 12</td><td style="text-align: center;">S 7</td></tr> </table>	T 22 N		R 16 E	R 17 E	S 1	S 6	S 12	S 7
T 22 N									
R 16 E	R 17 E								
S 1	S 6								
S 12	S 7								
	2007								
	Deposit a magnet in a white plastic case at the base of and the stone alongside of the stainless steel post.								
	Rebuild mound of stone, 5 ft. base, 2 ft. high, W. of cor.								
	From this cor. point, a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, in a collar of stone, bears N. 79°49' E., 1.89 chs. dist.								
	N. 2°41' E., bet. secs. 1 and 6.								
	Over broken terrain, through scattered sage and Mormon Tea.								
14.60	Southerly right-of-way fence of BIA Route 15, bears N. 88°30' E. and S. 88°30' W.								
	From this point, a right-of-way marker, monumented with a 3 in. diam. brass cap, incased in concrete, 6 ins. diam., flush with the ground, mkd. BIA NAVAJO ROADS 19, with a 4 in. angle iron alongside, projecting 17 ins. above the ground, in the southerly right-of-way fence, bears S. 88°30' W., 23 lks. dist.								
16.12	Center of right-of-way fences falls in pavement of BIA Route 15, 38 ft. wide, bears N. 88°30' E. and S. 88°30' W.								
17.64	Northerly right-of-way fence of BIA Route 15, bears N. 88°30' E. and S. 88°30' W.								
	From this point, a right-of-way marker, monumented with a 3 in. diam. brass cap, incased in concrete, 6 ins. diam., flush with ground, mkd. BIA NAVAJO ROADS 19, with a 4 in. angle iron alongside, projecting 19 ins. above the ground, in the northerly right-of-way fence, bears S. 88°30' W., 43 lks. dist.								
25.65	Center of Trans Western pipelines, bears N. 85°45' E. and S. 85°45' W.								

**Dependent Resurvey of the Fourth Guide Meridian East (East boundary),  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.28	<p>The 1/4 sec. cor. of secs. 1 and 6, monumented with a basalt stone, 13 X 10 X 6 ins., loosely set 2 ins. in the ground, mkd. 1/4 A, with a rebar, 5/8 in. diam., 16 ins. long, projecting 4 ins. above the ground alongside. This is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N 1/4 R 16 E R 17 E S 1   S 6</p> <p style="text-align: center;">2007</p> <p>Deposit rebar inside of, a magnet in a white plastic case at the base of and the stone alongside of the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°09' W., beginning new measurement.</p>
11.40	<p>Center of El Paso Natural Gas pipelines, bears N. 82°00' E. and S. 82°00' W.</p>
40.01	<p>The cor. of Tps. 22 and 23 N., Rs. 16 and 17 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T23N R16E R17E S36 S31 S1 S6 T22N 2005, witnessed with a mound of stone, 3 1/2 ft. base, 2 ft. high, S. of cor.</p> <p>Add the marks 2007 to the brass cap.</p> <hr style="width: 50%; margin: auto;"/> <p style="text-align: center;"><b>Dependent Resurvey of the South Boundary, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr style="width: 50%; margin: auto;"/> <p style="text-align: center;">Restoring the survey executed by Orville D. Wheeler, in 1882</p> <hr style="width: 50%; margin: auto;"/> <p>From the cor. of Tps. 21 and 22 N., Rs. 16 and 17 E., hereinbefore described.</p> <p>S. 89°56' W., bet. secs. 1 and 36, on the S. bdy. of the Tp.</p> <p>Over severely broken, rocky terrain.</p>

**Dependent Resurvey of South Boundary,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
37.90	<p>Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 16 E S 36 1/4 ——— S 1 T 21 N</p> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
75.80	<p>The cor. of secs. 1, 2, 35 and 36, determined E., 1 lk. dist. from a mound of stone, 3 ft. base, 1 ft. high, no mkd. stone found.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 16 E S 35   S 36 S 2   S 1 T 21 N</p> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Incorporate mound of stone into mound of stone around stainless steel post.</p> <hr/> <p>N. 89°50' W., bet. secs. 2 and 35.</p> <p>Over severely broken, rocky terrain.</p>
38.02	<p>Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

**Dependent Resurvey of South Boundary,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 16 E S 35 1/4 ——— S 2 T 21 N  2007  Deposit a magnet in a white plastic case at the base of the stainless steel post.
76.04	Point for the cor. of secs. 2, 3, 34 and 35, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">             T 22 N R 16 E              S 34   S 35              ——— ———              S 3   S 2              T 21 N           </div> 2007  Deposit a magnet in a white plastic case at the base of the stainless steel post.  Raise a mound of stone (petrified wood), 3 ft. base, 2 ft. high, W. of cor.
38.02	<hr/> N. 89°50' W., bet. secs. 3 and 34.  Over severely broken, rocky terrain.  Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.  <div style="text-align: center;">             T 22 N R 16 E                S 34            1/4 ———                S 3            T 21 N             2007             Deposit a magnet in a white plastic case at the base of the stainless steel post.         </div>

**Dependent Resurvey of South Boundary,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
44.41	From this point, a hand operated water pump atop of a concrete slab, 10 ft. square, 1 ft. thick, inscribed BIRD SPRINGS PROJECT, bears North, 5.97 chs. dist.
53.98	From this point, a hand operated water pump atop of a concrete slab, 10 ft. square, 1 ft. thick, 4 ft. above the ground, inscribed M54 WELL, bears North, 4.87 chs. dist.
76.04	The cor. of secs. 3, 4, 33 and 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T22N R16E S33 S34 S4 S3 T21N 2005, witnessed with a mound of stone, 3 ft. base, 2 ft. high, N. of cor.  Add the marks 2007 to the brass cap. <hr style="width: 50%; margin-left: 0;"/> S. 89°43' W., bet. secs. 4 and 33.  Over broken terrain, through scattered sage brush and Mormon Tea.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 22 N R 16 E                  S 33              1/4 ———                  S 4            T 21 N             2007         </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.  Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.
80.00	Point for the cor. of secs. 4, 5, 32 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 22 N R 16 E            S 32   S 33            S 5   S 4            T 21 N             2007         </div>

**Dependent Resurvey of South Boundary,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.</p> <hr/> <p>S. 89°43' W., bet. secs. 5 and 32.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 16 E S 32 1/4 ——— S 5 T 21 N</p> <p>2007</p> </div>
80.00	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a steel spike, 6 ins. long, flush with the surface of the ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, in a collar of stone, for a reference monument, bears N. 54°52' E., 77.1 ft. dist. with brass cap mkd. RM T22N R16E S32 77.1 FT TO COR 2007 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, in a collar of stone, for a reference monument, bears S. 38°12' E., 61.1 ft. dist. with brass cap mkd. RM T21N R16E S5 61.1 FT TO COR 2007 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Dependent Resurvey of South Boundary,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Cor. is located in a wash, drains S. 20° W.</p> <hr/> <p>S. 89°43' W., bet. secs. 6 and 31.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E S 31 1/4 ——— S 6 T 21 N</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.20	<p>The cor. of Tps. 21 and 22 N., Rs. 15 and 16 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set projecting 2 ins. above the ground, with brass cap mkd. T22N R15E R16E S36 S31 S1 S6 T21N 2005.</p> <p>Add the marks 2007 to the brass cap.</p> <hr/> <p style="text-align: center;"><b>Dependent Resurvey of the North Boundary, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p style="text-align: center;">Restoring the survey executed by Orville D. Wheeler, in 1882</p> <hr/> <p>From the cor. of Tps. 22 and 23 N., Rs. 16 and 17 E., hereinbefore described.</p> <p>S. 89°43' W., bet. secs. 1 and 36, on the N. bdy. of the Tp.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
39.95	<p>Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.</p>

**Dependent Resurvey of North Boundary,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 16 E S 36 1/4 ——— S 1 T 22 N</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.90	<p>Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 16 E S 35   S 36 S 2   S 1 T 22 N</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of and a cast iron meat grinder with Universal Meat Chopper No 323 New Britain CONN USA stamped on a side, alongside the stainless steel post.</p> <hr/> <p>S. 89°43' W., bet. secs. 2 and 35.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
39.95	<p>Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 N R 16 E S 35 1/4 ——— S 2 T 22 N</p> <p style="text-align: center;">2007</p>

**Dependent Resurvey of North Boundary,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS											
79.90	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 2, 3, 34 and 35, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T 23 N</td> <td>R 16 E</td> </tr> <tr> <td>S 34</td> <td>S 35</td> </tr> <tr> <td>S 3</td> <td>S 2</td> </tr> <tr> <td colspan="2">T 22 N</td> </tr> </table> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>S. 89°43' W., bet. secs. 3 and 34.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>	T 23 N	R 16 E	S 34	S 35	S 3	S 2	T 22 N			
T 23 N	R 16 E										
S 34	S 35										
S 3	S 2										
T 22 N											
39.95	<p>Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T 23 N</td> <td>R 16 E</td> </tr> <tr> <td>S 34</td> <td></td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td>S 3</td> <td></td> </tr> <tr> <td colspan="2">T 22 N</td> </tr> </table> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 23 N	R 16 E	S 34		1/4	—	S 3		T 22 N	
T 23 N	R 16 E										
S 34											
1/4	—										
S 3											
T 22 N											
79.90	<p>Point for the cor. of secs. 3, 4, 33 and 34, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>										

**Dependent Resurvey of North Boundary,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS

T 23 N	R 16 E
S 33	S 34
S 4	S 3
T 22 N	

2007

Deposit a magnet in a white plastic case at the base of the stainless steel post.

---

S. 89°43' W., bet. secs. 4 and 33.

Over broken terrain, through scattered sage brush and Mormon Tea.

39.95

Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 N	R 16 E
S 33	
1/4	—
S 4	
T 22 N	

2007

Deposit a magnet in a white plastic case at the base of the stainless steel post.

79.90

Point for the cor. of secs. 4, 5, 32 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 N	R 16 E
S 32	S 33
S 5	S 4
T 22 N	

2007

Deposit a magnet in a white plastic case at the base of the stainless steel post.

---

S. 89°43' W., bet. secs. 5 and 32.

**Dependent Resurvey of North Boundary,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS					
39.95	<p>Over broken terrain, through scattered sage brush and Mormon Tea.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 N R 16 E</p> <p style="margin-left: 100px;">S 32</p> <p style="margin-left: 80px;">1/4 ———</p> <p style="margin-left: 100px;">S 5</p> <p>T 22 N</p> <p style="margin-top: 10px;">2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>				
79.90	<p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 N R 16 E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 31</td> <td style="padding: 0 5px;">S 32</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 6</td> <td style="padding: 0 5px;">S 5</td> </tr> </table> <p>T 22 N</p> <p style="margin-top: 10px;">2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of and a 1 1/2 X 1 X 1/2 in. rubber figurine of a blue Triceratops Dinosaur alongside of the stainless steel post.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>S. 89°43' W., bet. secs. 6 and 31.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>	S 31	S 32	S 6	S 5
S 31	S 32				
S 6	S 5				
39.95	<p>Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>				

**Dependent Resurvey of North Boundary,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 23 N R 16 E S 31 1/4 ——— S 6 T 22 N  2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
78.90	The cor. of Tps. 22 and 23 N., Rs. 15 and 16 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T23N R15E R16E S36 S31 S1 S6 T22N 2005.  Add the marks 2007 to the brass cap.
<hr/> <b>Dependent Resurvey of the Subdivisional Lines, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b> <hr/>	
Restoring the survey executed by Orville D. Wheeler, in 1882	
	From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.  N. 2°36' W., bet. secs. 35 and 36.  Over severely broken, rocky terrain.
40.24	Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 16 E 1/4 S 35   S 36  2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.
80.48	Point for the cor. of secs. 25, 26, 35 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 22 N	R 16 E
S 26	S 25
S 35	S 36

2007

Deposit a magnet in a white plastic case at the base of the stainless steel post.

---

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.

S. 89°36' W., bet. secs. 25 and 36.

Over severely broken, rocky terrain.

40.48

Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist., there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 11 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 22 N	R 16 E
S 25	
1/4	—
S 36	

2007

Deposit a magnet in a white plastic case at the base of the stainless steel post.

80.96

The cor. of secs. 25, 26, 35 and 36.

---

N. 4°26' E., bet. secs. 25 and 26.

Over severely broken, rocky terrain.

40.32

Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate dist., there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.64	<p style="text-align: center;">T 22 N R 16 E 1/4 S 26   S 25</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.</p>
38.59	<p style="text-align: center;">T 22 N R 16 E S 23   S 24 S 26   S 25</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°52' W., bet. secs. 24 and 25.</p> <p>Over severely broken, rocky terrain.</p> <p>Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E S 24 1/4 ——— S 25</p> <p style="text-align: center;">2007</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
77.18	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The cor. of secs. 23, 24, 25 and 26.</p> <hr/> <p>N. 0°26' W., bet. secs. 23 and 24.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
40.20	<p>Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 16 E 1/4 S 23   S 24</p> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.40	<p>Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 16 E S 14   S 13 S 23   S 24</p> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°55' W., bet. secs. 13 and 24.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.52	<p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E S 13 1/4 ——— S 24</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
79.04	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/> <p>N. 0°30' E., bet. secs. 13 and 14.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
40.20	<p>Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E 1/4 S 14   S 13</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.40	<p>The cor. of secs. 11, 12, 13 and 14, monumented with a sandstone, 10 X 8 X 6 ins., loosely set 2 ins. in the ground, mkd. S12 on NE face, in an imbedded mound of stone, 2 1/2 ft. base, 1 ft. high. This is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 22 N R 16 E S 11   S 12 S 14   S 13</p>
	<p style="text-align: center;">2007</p>
	<p>Incorporate stone in mound of stone.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°59' W., bet. secs. 12 and 13.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
<p>39.93</p>	<p>Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 22 N R 16 E S 12 1/4 ——— S 13</p> <p style="text-align: center;">2007</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
<p>79.87</p>	<p>The cor. of secs. 11, 12, 13 and 14.</p> <hr/> <p>N. 0°08' E., bet. secs. 11 and 12.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
<p>39.87</p>	<p>The 1/4 sec. cor. of secs. 11 and 12, monumented with a basalt stone, 14 X 7 X 6 ins., loosely set 1 in. in the ground, mkd. 1/4 A, in a mound of stone, 2 ft. base, 1/2 ft. high. This is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 22 N R 16 E 1/4 S 11   S 12</p> <p align="center">2007</p> <p>Deposit a magnet in a white plastic case at the base of and the stone alongside of the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <hr/> <p>N. 5°29' E., beginning new measurement.</p>
38.83	<p>The cor. of secs. 1, 2, 11 and 12, monumented with a sandstone outcrop, projecting 60 X 60 X 25 ins. above ground, mkd. with 1 groove on E. face and 5 grooves on S. face. Not remonumented.</p> <p>from which new accessories</p> <p>An X B0 chiseled on the NW face of a sandstone cliff, bears S. 2°10' E., 27 lks. dist.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 21 ins. in the ground, in a mound of stone, 3 ft. base to top, for a reference monument, bears N. 65°57' W., 12.9 ft. dist., with brass cap mkd. RM T22N R16E 12.9 FT TO COR S2 2007 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 88°45' W., bet. secs. 1 and 12.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
38.05	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 16 E S 1 1/4 ——— S 12  2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.  Raise a mound of stone, 2 ft. base, 1 ft. high, N. of cor.
76.10	The cor. of secs. 1, 2, 11 and 12.  <hr/> N. 1°27' W., bet. secs. 1 and 2.  Over broken terrain, through scattered sage brush and Mormon Tea.
6.52	Southerly right-of-way fence of BIA Route 15, bears N. 82°22' E. and S. 82°22' W.
8.04	Center of right-of-way fences falls in pavement of BIA Route 15, bears N. 82°22' E. and S. 82°22' W.
9.56	Northerly right-of-way fence of BIA Route 15, bears N. 82°22' E. and S. 82°22' W.
26.58	Center of Trans Western pipelines, bears S. 79°45' E. and N. 79°45' W.
40.79	Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, with brass cap mkd.
	T 22 N R 16 E 1/4 S 2   S 1  2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.  Cor. is located on the E. edge of graded road, bears N. 40° E. and S. 40° W.
42.71	Center of El Paso Natural Gas pipelines, bears N. 82°00' E. and S. 82°00' W.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS							
81.53	<p>The cor. of secs 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 5°11' W., bet. secs. 34 and 35.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>						
33.00	Left bank of Coyote Wash, drains S. 15° W., thence along wash.						
39.34	<p>Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a steel spike, 6 ins. long, flush with the surface of the ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 24°22' E., 50.0 ft. dist. with brass cap mkd. RM T22N R16E 50.0 FT TO COR S35 2007 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 57°40' W., 50.0 ft. dist. with brass cap mkd. RM T22N R16E 50.0 FT TO COR S34 2007 and an arrow pointing to the corner. Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. falls in Coyote Wash where it is impracticable to establish a permanent monument.</p>						
39.60	Right bank of Coyote Wash, drains S. 75° W., thence leave wash.						
78.68	<p>Point for the cor. of sec. cor. of secs. 26, 27, 34 and 35, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 22 N</td> <td>R 16 E</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> <tr> <td>S 34</td> <td>S 35</td> </tr> </table> <p>2007</p> </div>	T 22 N	R 16 E	S 27	S 26	S 34	S 35
T 22 N	R 16 E						
S 27	S 26						
S 34	S 35						

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.70	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89°11' W., bet. secs. 26 and 35.</p> <p>Over broken terrain, with little or no vegetation.</p> <p>The 1/4 sec. cor. of secs. 26 and 35, determined S., 1 lk. dist. from a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 16 E</p> <p>S 26</p> <p>1/4 ———</p> <p>S 35</p> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Rebuild a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.</p> <hr/> <p>S. 86°28' W., beginning new measurement.</p>
38.88	<p>The cor. of secs. 26, 27, 34 and 35.</p> <hr/> <p>N. 5°34' E., bet. secs. 26 and 27.</p> <p>Over broken terrain, with little or no vegetation.</p>
39.36	<p>Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a steel spike, 6 ins. long, flush with the surface of the ground.</p> <p>from which</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS							
	<p>A brass tablet, 3 1/4 ins. diam., cemented in a drill hole, on a limestone outcrop, projecting 4 X 4 X 3 ft., for a reference monument, bears N. 6°05' E., 30.6 ft. dist., with brass cap mkd. RM T22N R16E 1/4 30.6 FT TO COR S26 2007 and an arrow pointing to the cor. Deposit a cylindrical magnet, 1 X 3/4 in., beneath the brass tablet, in drill hole</p> <p>An X B0 chiseled on the W. face of a limestone outcrop, projecting 5 X 3 X 3 ft., bears N. 53°50' E., 74.5 lks. dist.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.</p> <p>Cor. falls in a rocky wash, where it is impracticable to establish a permanent monument.</p>						
78.72	<p>The cor. of secs. 22, 23, 26 and 27, monumented with a limestone, 23 X 14 X 9 ins., firmly set in a mound of stone, 5 ft. base, 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T 22 N R 16 E</td> </tr> <tr> <td style="text-align: center;">S 22</td> <td style="text-align: center;">S 23</td> </tr> <tr> <td style="text-align: center;">S 27</td> <td style="text-align: center;">S 26</td> </tr> </table> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. and incorporate the orig. stone in the mound of stone.</p>	T 22 N R 16 E		S 22	S 23	S 27	S 26
T 22 N R 16 E							
S 22	S 23						
S 27	S 26						
39.09	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 87°10' W., bet. secs. 23 and 26.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p> <p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>						

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p align="center">T 22 N R 16 E S 23 1/4 ——— S 26</p> <p align="center">2007</p>
78.18	<p>Deposit a magnet in a white plastic case at the base and a 3 1/2 in. black action figurine of a soldier alongside of the stainless steel post.</p> <p>The cor. of secs. 22, 23, 26 and 27.</p> <hr/>
	<p>N. 1°09' W., bet. secs. 22 and 23.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
40.54	<p>Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 22 N R 16 E 1/4 S 22   S 23</p> <p align="center">2007</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p>
81.08	<p>Point for the cor. of secs. 14, 15, 22 and 23, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">T 22 N R 16 E S 15   S 14 S 22   S 23</p> <p align="center">2007</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.57	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 87°41' W., bet. secs. 14 and 23.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p> <p>Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 16 E S 14 1/4 ——— S 23</p> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.15	<p>The cor. of secs. 14, 15, 22 and 23.</p> <hr/> <p>N. 2°07' E., bet. secs. 14 and 15.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
40.56	<p>Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 16 E 1/4 S 15   S 14</p> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

## CHAINS

81.12

The cor. of secs. 10, 11, 14 and 15, monumented with a sandstone, 18 X 15 X 12 ins., firmly set 15 ins. in the ground, mkd. with 4 grooves on S. face, in a scattered mound of stone, 3 ft. base, 1 ft. high.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N	R 16 E
S 10	S 11
S 15	S 14

2007

Deposit a magnet in a white plastic case at the base of and orig. stone alongside of the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Set a steel fence post, 6 ft. long, alongside of stainless steel post.

---

From the cor. of secs. 11, 12, 13 and 14.

S. 89°57' W., bet. secs. 11 and 14.

Over broken terrain, through scattered sage brush and Mormon Tea.

39.95

The 1/4 sec. cor. of secs. 11 and 14, monumented with a flint stone, 16 X 10 X 4 ins., loosely set 2 ins. in the ground, mkd. 1/4 on the N. face.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 22 N	R 16 E
	S 11
1/4	—
	S 14

2007

Deposit a magnet in a white plastic case at the base of and orig. stone alongside of the stainless steel post.

---

S. 86°08' W., beginning new measurement.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
36.91	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/> <p>N. 0°43' W., bet. secs. 10 and 11.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
39.36	<p>The 1/4 sec. cor. of secs 10 and 11, monumented with a sandstone, 12 X 7 X 6 ins., firmly set 3 ins. in the ground, with illegible marks on the S. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E 1/4 S 10   S 11  2007</p> <p>Deposit a magnet in a white plastic case at the base of and the orig. stone alongside of the stainless steel post.</p> <p>Set a steel fence post, 6 ft. long, alongside of stainless steel post.</p> <hr/> <p>N. 1°30' E., beginning new measurement.</p>
37.52	<p>Southerly right-of-way fence of BIA Route 15, bears N. 82°22' E. and S. 82°22' W.</p> <p>From this point, a right-of-way marker, monumented with a 3 in. diam. brass cap, incased in concrete, 6 ins. diam., projecting 2 ins. above the ground, mkd. BIA NAVAJO ROADS 19 ELEV 5374.15 1983, with a 4 in. angle iron alongside, projecting 18 ins. above the ground, mkd. HWRW 1142+46.02 BK 1142+14.78 AHD, in the southerly right-of-way fence, bears S. 88°22' W., 20.94 chs. dist.</p>
39.06	<p>Center of right-of-way fences falls in the pavement of BIA Route 15, 38 ft. wide, bears N. 82°22' E. and S. 82°22' W.</p>
40.59	<p>Northerly right-of-way fence of BIA Route 15, bears N. 82°22' E. and S. 82°22' W.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS									
40.89	<p>From this point, a right-of-way marker, monumented with a 3 in. diam. brass cap, incased in concrete, 6 ins. diam., flush with the ground, mkd. BIA NAVAJO ROADS 19 ELEV 5371.75 193, with a 4 in. angle iron alongside, projecting 18 ins. above the ground, mkd. HWRW 1142+46 BK 1142+14.78 AHD in the northerly right-of-way fence, bears S. 88°22' W., 21.42 chs. dist.</p> <p>Point for the cor. of secs. 2, 3, 10 and 11, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 22 N</td><td>R 16 E</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td>S 10</td><td>S 11</td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.</p> <p>Set a steel fence post, 6 ft. long, alongside of stainless steel post.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89°25' W., bet. secs. 2 and 11.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>	T 22 N	R 16 E	S 3	S 2	S 10	S 11		
T 22 N	R 16 E								
S 3	S 2								
S 10	S 11								
39.99	<p>Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 22 N</td><td>R 16 E</td></tr> <tr><td>S 2</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 11</td><td></td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>	T 22 N	R 16 E	S 2		1/4	—	S 11	
T 22 N	R 16 E								
S 2									
1/4	—								
S 11									
52.89	<p>Southerly right-of-way fence of BIA Route 15, bears N. 82°22' E. and S. 82°22' W.</p>								

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
65.25	Center of right-of-way fences falls in pavement of BIA Route 15, 38 ft. wide, bears N. 82°22' E. and S. 82°22' W.
77.61	Northerly right-of-way fence of BIA Route 15, bears N. 82°22' E. and S. 82°22' W.
79.98	The cor. of secs. 2, 3, 10 and 11. <hr/>
	N. 1°24' W., bet. secs. 2 and 3.  Over broken terrain, through scattered sage brush and Mormon Tea.
31.78	Center of El Paso Natural Gas pipelines, bears N. 82°22' E. and S. 82°22' W.
39.55	Center of Trans Western pipelines, bears N. 83°02' E. and S. 83°02' W.
40.88	Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 22 N R 16 E                1/4            S 3   S 2              2007         </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.  Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.
81.95	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., hereinbefore described. <hr/>
	From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.  N. 6°10' W., bet. secs. 33 and 34.  Over broken terrain, through scattered sage brush and Mormon Tea.
40.00	Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate dist., there is no remaining evidence of the orig. cor.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E 1/4 S 33   S 34</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Point for the cor. of secs. 27, 28, 33 and 34, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E S 28   S 27 S 33   S 34</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 88°58' W., bet. secs. 27 and 34.</p> <p>Over broken terrain, with little or no vegetation.</p>
38.76	<p>Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E S 27 1/4 ——— S 34</p> <p style="text-align: center;">2007</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
77.52	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/> <p>N. 3°31' E., bet. secs. 27 and 28.</p> <p>Over severely broken, rocky terrain.</p>
39.84	<p>True point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate dist., there is no remaining evidence of the orig. cor., is located on a steep E. face of Mesa, where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 27 and 28, bears S. 23°33' W., 50 lks. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p> <p>T 22 N R 16 E</p> <p>1/4 ↗</p> <p>S 28   S 27</p> <p>2007</p> </div>
79.68	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 16 E</p> <p>S 21   S 22</p> <hr style="width: 50%; margin: 0 auto;"/> <p>S 28   S 27</p> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of and a Nebraska license plate, 8 X 3 ins., mkd. 32X1736 NEB 1986, alongside the stainless steel post.</p> <hr/>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 88°09' W., bet. secs. 22 and 27.</p> <p>Over severely broken, rocky terrain.</p>
40.14	<p>Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 16 E</p> <p>S 22</p> <p>1/4 ———</p> <p>S 27</p> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.28	<p>The cor. of secs. 21, 22, 27 and 28.</p> <hr/> <p>N. 0°13' W., bet. secs. 21 and 22.</p> <p>Over severely broken, rocky terrain.</p>
39.77	<p>Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 16 E</p> <p>1/4</p> <p>S 21   S 22</p> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located on rocky, NW slope of a mesa.</p>
79.54	<p>Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 16 E S 16   S 15 S 21   S 22  2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.  Set a steel fence post, 6 ft. long, alongside of the stainless steel post.
	<hr/> From the cor. of secs. 14, 15, 22 and 23.  N. 89°14' W., bet. secs. 15 and 22.  Over broken terrain, with little or no vegetation.
39.44	Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T 22 N R 16 E S 15 1/4 ——— S 22  2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
78.89	The cor. of secs 15, 16, 21 and 22.
	<hr/> N. 1°00' E., bet. secs. 15 and 16.  Over broken terrain, with little or no vegetation.
39.77	Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 16 E 1/4 S 16   S 15  2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.  Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.  Set a steel fence post, 6 ft. long, alongside of the stainless steel post.
79.54	The cor. of secs. 9, 10, 15 and 16, monumented with a sandstone, 24 X 14 X 8 ins., firmly set 8 ins. in the ground, mkd. with 3 grooves on E. face and 4 grooves on S. face.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 9 ins. in the ground, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.
	T 22 N R 16 E S 9   S 10 S 16   S 15  2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.  Incorporate orig. stone into mound of stone around stainless steel post.  Set a steel fence post, 6 ft. long, alongside of the stainless steel post.
	<hr/> From the cor. of secs. 10, 11, 14 and 15.  S. 89°50' W., bet. secs. 10 and 15.  Over severely broken, rocky terrain.
40.56	The 1/4 sec. cor. of secs. 10 and 15, monumented with a flint stone, 16 X 9 X 8 ins. firmly set 9 ins. in the ground, mkd. 1/4 on N. face.  At the corner point

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E S 10 1/4 ——— S 15</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of and orig. stone alongside of the stainless steel post.</p> <p>Set a steel fence post, 6 ft. long, alongside of the stainless steel post.</p> <p style="text-align: center;">—————</p> <p>S. 89°29' W., beginning new measurement.</p>
39.94	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p style="text-align: center;">—————</p> <p>N. 0°01' W., bet. secs. 9 and 10.</p> <p>Over severely broken, rocky terrain.</p>
39.78	<p>The 1/4 sec. cor. of secs. 9 and 10, monumented with a flint stone, 19 X 11 X 10 ins., loosely set 2 ins. in the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E 1/4 S 9   S 10</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base and orig. stone alongside of the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>Set a steel fence post, 6 ft. long, alongside of the stainless steel post.</p> <p style="text-align: center;">—————</p> <p>N. 0°47' E., beginning new measurement.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS							
35.18	<p>Southerly right-of-way fence of BIA Route 15, bears S. 86°25' E. and N. 86°25' W.</p> <p>From this point, a right-of-way marker, monumented with a 3 in. diam. brass cap, incased in concrete, 6 ins. diam., 2 ins. above the ground, mkd. BIA NAVAJO ROADS 19 ELEV 5299.67 1983, with a 4 in. angle iron alongside, projecting 18 ins. above the ground, mkd. HWRW 1099+15.13, in right-of-way fence, bears N. 86°25' W., 6.05 chs. dist.</p>						
36.70	Center of right-of-way fences falls in the pavement of BIA Route 15, 38 ft. wide, bears S. 86°25' E. and N. 86°25' W.						
38.22	<p>Northerly right-of-way fence of BIA Route 15, bears S. 86°25' E. and N. 86°25' W.</p> <p>From this point, a right-of-way marker, monumented with a 3 in. diam. brass cap, incased in concrete, 6 ins. diam., 6 ins. below the surface of the ground, mkd. BIA NAVAJO ROADS 19 ELEV 5294.96 1983, with a 4 in. angle iron alongside, projecting 15 ins. above the ground, mkd. 1099+15.13, in right-of-way fence, bears N. 86°25' W., 5.90 chs. dist.</p>						
40.81	<p>Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 22 N</td><td>R 16 E</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td>S 9</td><td>S 10</td></tr> </table> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Set a steel fence post, 6 ft. long, alongside of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 89°55' W., bet. secs. 3 and 10.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>	T 22 N	R 16 E	S 4	S 3	S 9	S 10
T 22 N	R 16 E						
S 4	S 3						
S 9	S 10						

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.26	<p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E S 3 1/4 ——— S 10</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.52	<p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/> <p>N. 1°00' W., bet. secs. 3 and 4.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
22.15	<p>Center of El Paso Natural Gas pipelines, bears N. 82°20' E. and S. 82°20' W.</p>
29.85	<p>Center of Trans Western pipelines, bears N. 85°45' E. and S. 85°45' W.</p>
40.81	<p>Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E 1/4 S 4   S 3</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
81.67	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 4°19' W., bet. secs. 32 and 33.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.65	<p>Over broken terrain, through scattered sage brush and Mormon Tea.</p> <p>Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E 1/4 S 32   S 33</p> <p style="text-align: center;">2007</p> <p>Raise a mound of stone (petrified wood), 3 ft. base, 2 ft. high, W. of cor.</p>
79.30	<p>Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E S 29   S 28 S 32   S 33</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 89°21' W., bet. secs. 28 and 33.</p> <p>Over broken terrain, with little or no vegetation.</p>
38.68	<p>Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 16 E S 28 1/4 ——— S 33  2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Cor. is located on the southerly slope of clay ridge, bears E. and W.
77.36	The cor. of secs. 28, 29, 32 and 33. <hr/> N. 1°12' E., bet. secs. 28 and 29.  Over broken terrain, with little or no vegetation.
39.54	Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 16 E 1/4 S 29   S 28  2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.
79.08	The cor. of secs. 20, 21, 28 and 29, determined E., 1 lk. dist. from an imbedded mound of stone, 4 ft. base, 1 ft. high.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.
	T 22 N R 16 E S 20   S 21 ——— S 29   S 28  2007

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.29	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Incorporate mound of stone into mound of stone around stainless steel post.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 89°03' W., bet. secs. 21 and 28.</p> <p>Over broken terrain, with little or no vegetation.</p> <p>Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 16 E</p> <p>S 21</p> <p>1/4 ———</p> <p>S 28</p> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
80.59	<p>The cor. of secs. 20, 21, 28 and 29.</p> <hr/> <p>N. 0°45' E., bet. secs. 20 and 21.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
40.63	<p>Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 16 E</p> <p>1/4</p> <p>S 20   S 21</p> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS							
81.26	<p>The cor. of secs. 16, 17, 20 and 21, monumented with a sandstone, 15 X 13 X 10 ins., firmly set 6 ins. in the ground, witnessed with a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 22 N</td> <td>R 16 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 17</td> <td>S 16</td> </tr> <tr> <td style="border-right: 1px solid black;">S 20</td> <td>S 21</td> </tr> </table> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor. and incorporate orig. stone in mound of stone.</p> <p>Set a steel fence post, 6 ft. long, alongside of stainless steel post.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>West, bet. secs. 16 and 21.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>	T 22 N	R 16 E	S 17	S 16	S 20	S 21
T 22 N	R 16 E						
S 17	S 16						
S 20	S 21						
19.68	<p>Point for the E. 1/16 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 22 N</td> <td>R 16 E</td> </tr> <tr> <td></td> <td>S 16</td> </tr> <tr> <td>E 1/16</td> <td style="border-top: 1px solid black;">S 21</td> </tr> </table> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post, 6 ft. long, alongside of stainless steel post.</p>	T 22 N	R 16 E		S 16	E 1/16	S 21
T 22 N	R 16 E						
	S 16						
E 1/16	S 21						

Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.36	<p>The 1/4 sec. cor. of secs. 16 and 21, monumented with a sandstone, 14 X 8 X 6 ins., firmly set 4 ins. in the ground, witnessed with a mound of stone, 3 ft. base, 1 ft. high, N. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, in a supporting mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E S 16 1/4 ——— S 21</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor. and incorporate orig. stone in mound of stone.</p> <p>Set a steel fence post, 6 ft. long, alongside of the stainless steel post.</p> <p>Cor. is located on the southerly edge of a mesa.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°27' W., beginning new measurement.</p>
19.925	<p>Point for the W. 1/16 sec. cor. of secs. 16 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E S 16 W 1/16 ——— S 21</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, N. of cor.</p> <p>Set a steel fence post, 6 ft. long, alongside of the stainless steel post.</p>
39.85	<p>The cor. of secs. 16, 17, 20 and 21.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS

---

N. 1°38' E., bet. secs. 16 and 17.

Over broken terrain, through scattered sage brush and Mormon Tea.

39.66 Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist., there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

T 22 N R 16 E  
1/4  
S 17 | S 16

2007

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.

Set a steel fence post, 6 ft. long, alongside of the stainless steel post.

79.32 The cor. of secs. 8, 9, 16 and 17, monumented with a flint stone, 16 X 8 X 4, loosely set 2 ins. in the ground, witnessed with an imbedded mound of stone, 2 ft. base, 1 ft. high, W. of cor.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N R 16 E  
S 8 | S 9  
S 17 | S 16

2007

Deposit a magnet in a white plastic case at the base of and the orig. stone alongside of the stainless steel post.

Rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Set a steel fence post, 6 ft. long, alongside of the stainless steel post.

---

From the cor. of secs. 9, 10, 15 and 16.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 89°55' W., bet. secs. 9 and 16.
	Over broken terrain, through scattered sage brush and Mormon Tea.
19.58	Point for the E. 1/16 sec. cor. of secs. 9 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, with brass cap mkd.
	T 22 N R 16 E S 9 E 1/16 ——— S 16  2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Set a steel fence post, 6 ft. long, alongside of the stainless steel post.
39.16	Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate dist., there is no remaining evidence of the orig. cor.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 16 E S 9 1/4 ——— S 16  2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.
	Set a steel fence post, 6 ft. long, alongside of the stainless steel post.
	Cor. is located on the rocky southerly slope of a ridge.
58.74	Point for the W. 1/16 sec. cor. of secs. 9 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 16 E S 9 W 1/16 ——— S 16  2007  Deposit a magnet in a white plastic case at the base of the stainless steel post.  Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.  Set a steel fence post, 6 ft. long, alongside of the stainless steel post.
78.32	The cor. of secs. 8, 9, 16 and 17.  <hr/> N. 3°10' W., bet. secs. 8 and 9.  Over broken terrain, through scattered sage brush and Mormon Tea.
38.14	The 1/4 sec. cor. of secs. 8 and 9, determined E., 1 lk. dist. from a mound of stone, 3 ft. base, 1 1/2 ft. high.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">             T 22 N R 16 E                        1/4              S 8   S 9               2007           </div> Deposit a magnet in a white plastic case at the base of the stainless steel post.  Rebuild mound of stone, 4 ft. base, 2 ft. high, W. of cor.
42.19	<hr/> N. 0°42' E., beginning new measurement.  The cor. of secs. 4, 5, 8 and 9, monumented with a flint stone, 16 X 8 X 5 ins., lying loose in a mound of stone, 3 ft. base, 1 1/2 high, mkd. with 5 grooves on one face.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS									
	<table style="margin: auto;"> <tr><td>T 22 N</td><td>R 16 E</td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td>S 8</td><td>S 9</td></tr> </table> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of and the orig. stone alongside of the stainless steel post.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89°52' W., bet. secs. 4 and 9.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>	T 22 N	R 16 E	S 5	S 4	S 8	S 9		
T 22 N	R 16 E								
S 5	S 4								
S 8	S 9								
24.98	<p>Northerly right-of-way fence of BIA Route 15, bears S. 82°01' E. and N. 82°01' W.</p> <p>From this point, a right-of-way marker, monumented with a 3 in. diam. brass cap, incased in concrete, 6 ins. diam., 4 ins. below the surface of the ground, mkd. BIA NAVAJO ROADS 19 ELEV 5203.58, with a 4 in. angle iron alongside, projecting 17 ins. above the ground, in right-of-way fence, mkd. HWRW 1090+35, bears S. 82°01' E., 5.98 chs. dist.</p>								
35.70	<p>Center of right-of-way fences falls in the pavement of BIA Route 15, 38 ft. wide, bears S. 82°01' E. and N. 82°01' W.</p>								
40.22	<p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 22 N</td><td>R 16 E</td></tr> <tr><td>S 4</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S 9</td><td></td></tr> </table> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Cor. is located on the southerly slope of Navajo Route 15.</p> </p>	T 22 N	R 16 E	S 4		1/4	—	S 9	
T 22 N	R 16 E								
S 4									
1/4	—								
S 9									

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
46.42	<p>Southerly right-of-way fence of BIA Route 15, bears S. 82°01' E. and N. 82°01' W.</p> <p>From this point, a right-of-way marker, monumented with a 3 in. diam. brass cap, incased in concrete, 6 ins. diam., projecting 19 ins. above the ground, mkd. BIA NAVAJO ROADS 19 ELEV 5278.07 1982, in right-of-way fence, bears S. 82°01' E., 27.20 chs. dist.</p>
80.44	<p>The cor. of secs. 4, 5, 8 and 9.</p> <hr/> <p>N. 0°38' W., bet. secs. 4 and 5.</p> <p>Over gently rolling terrain, through scattered sage brush and Mormon Tea.</p>
4.76	<p>Southerly right-of-way fence of BIA Route 15, bears S. 83°21' E. and S 88°28' W., on a curve.</p> <p>From this point, a right-of-way marker, monumented with a 3 in. diam. brass cap, incased in concrete, 6 ins. diam., projecting 2 ins. above the ground, mkd. BIA NAVAJO ROADS 19 ELEV 5222.41, with a 4 in. angle iron alongside, projecting 28 ins. above the ground, mkd. HWRW 1052+69.96 in right-of-way fence, bears S. 83°21' E., 4.54 chs. dist.</p>
6.26	<p>Center of pavement of BIA Route 15, 38 ft. wide, bears S. 83°33' E. and S. 88°28' W., on a curve.</p>
7.76	<p>Northerly right-of-way fence of BIA Route 15, bears S. 83°53' E. and S. 88°28' W., on a curve.</p> <p>From this point, a right-of-way marker, monumented with a 3 in. diam. brass cap, incased in concrete, 6 ins. diam., 1 in. below the surface of the ground, mkd. BIA NAVAJO ROADS 19 ELEV 5226.80, with a 4 in. angle iron alongside, projecting 22 ins. above the ground, in right-of-way fence, bears S. 83°53' E., 4.99 chs. dist.</p>
11.45	<p>Center of El Paso Natural Gas pipelines, bears N. 82°08' E. and S. 82°08' W.</p>
20.25	<p>Center of Trans Western pipelines, bears N. 83°02' E. and S. 83°02' W.</p>
40.74	<p>Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 16 E 1/4 S 5   S 4  2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.  Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.
81.46	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described.  <hr/> From the cor. of secs 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.  N. 2°10' W., bet. secs. 31 and 32.  Over gently rolling terrain, through scattered sage brush and Mormon Tea.
39.88	Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 16 E 1/4 S 31   S 32  2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.76	Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 22 N R 16 E S 30   S 29 S 31   S 32  2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.  <hr/>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
38.52	<p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89°50' W., bet. secs. 29 and 32.</p> <p>Over gently rolling terrain, through scattered sage brush and Mormon Tea.</p> <p>Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 16 E</p> <p>S 29</p> <p>1/4 ———</p> <p>S 32</p> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located on the S. edge of graded road, bears WSW and ENE.</p>
77.04	<p>The cor. of secs. 29, 30, 31 and 32.</p> <hr/> <p>S. 89°45' W., bet. secs. 30 and 31.</p> <p>Over gently rolling terrain, through scattered sage brush and Mormon Tea.</p>
38.67	<p>Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 N R 16 E</p> <p>S 30</p> <p>1/4 ———</p> <p>S 31</p> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, N. of cor.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

## CHAINS

77.76

The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T22N R15E R16E S25 S30 S36 S31 2005.

Add the marks 2007 to the brass cap.

---

From the cor. of secs. 29, 30, 31 and 32.

N. 0°11' E., bet. secs. 29 and 30.

Over broken terrain, through scattered sage brush and Mormon Tea.

39.85

Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate dist., there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 N R 16 E  
1/4  
S 30 | S 29

2007

Deposit a magnet in a white plastic case at the base of and an open face fishing reel, mkd. Swift 600F, alongside the stainless steel post.

79.70

Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist., there is no remaining evidence of the orig. cor.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

T 22 N R 16 E  
S 19 | S 20  
S 30 | S 29

2007

Deposit a magnet in a white plastic case at the base of the stainless steel post.

---

From the cor. of secs. 20, 21, 28 and 29.

N. 89°22' W., bet. secs. 20 and 29.

Over broken terrain, through scattered sage brush and Mormon Tea.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.21	<p>Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E S 20 1/4 ——— S 29</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
78.42	<p>The cor. of secs. 19, 20, 29 and 30.</p> <hr/> <p>S. 89°49' W., bet. secs. 19 and 30.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
39.26	<p>Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E S 19 1/4 ——— S 30</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of and a Diawa open face fishing reel alongside the stainless steel post.</p>
78.59	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T22N R15E R16E S24 S19 S25 S30 2005, witnessed with a steel fence post set alongside.</p> <p>Add the marks 2007 to the brass cap.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°45' W., bet. secs. 19 and 20.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.85	<p>Over broken terrain, through scattered sage brush and Mormon Tea.</p> <p>Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E 1/4 S 19   S 20</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p>
79.70	<p>The cor. of secs. 17, 18, 19 and 20, monumented with a sandstone, 18 X 16 X 6 ins., loosely set 2 ins. in the ground, witnessed with a mound of stone, 3 ft. base, 1 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, in a supporting mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E S 18   S 17 S 19   S 20</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Incorporate orig. stone and accessory mound of stone into mound of stone around stainless steel post.</p> <p>Set a steel fence post, 6 ft. long, alongside of stainless steel post.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°46' W., bet. secs. 17 and 20.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over broken terrain, through scattered sage brush and Mormon Tea.
40.18	<p>The 1/4 sec. cor. of secs. 17 and 20, monumented with a sandstone, 20 X 16 X 6 ins. firmly set 4 ins. in the ground, witnessed with a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E S 17 1/4 ——— S 20</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Rebuild mound of stone, 2 1/2 ft. base, 2 ft. high, N. of cor. and incorporate orig. stone in mound of stone.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 88°49' W., beginning new measurement.</p>
40.33	<p>The cor. of secs. 17, 18, 19 and 20.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>S. 89°52' W., bet. secs. 18 and 19.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
39.24	<p>Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E S 18 1/4 ——— S 19</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of and a 3 1/2 in. black and gray figurine of a Ninja alongside of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Set a steel fence post, 6 ft. long, alongside of stainless steel post.
78.11	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T22N R15E R16E S13 S18 S24 S19 2005, witnessed with a steel fence post set alongside.</p> <p>Add the marks 2007 to the brass cap.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 1°14' E., bet. secs. 17 and 18.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
40.24	<p>Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 22 N R 16 E 1/4 S 18   S 17</p> <p align="center">2007</p>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.
	Set a steel fence post, 6 ft. long, alongside of the stainless steel post.
80.48	<p>Point for the cor. of secs. 7, 8, 17 and 18, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 22 N R 16 E S 7   S 8 S 18   S 17</p> <p align="center">2007</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Set a steel fence post, 6 ft. long, alongside of the stainless steel post.</p> <p>Cor. is located 30 lks. S. of a wash, 35 ft. wide, 2 ft. deep, drains S. 25° W.</p> <p>From this cor. point, an iron pipe of unknown origin, 1 1/2 ins. diam., firmly set, projecting 17 ins. above the ground, in a collar of stone, bears S. 27°50' W., 85 lks. dist.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89°39' W., bet. secs. 8 and 17.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
40.51	<p>Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 22 N R 16 E S 8 1/4 ——— S 17</p> <p align="center">2007</p>
81.02	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, N. of cor.</p> <p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/>
29.09	<p>S. 89°23' W., bet. secs. 7 and 18.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p> <p>From this point, a hand operated water pump atop of a concrete slab, 11 ft. sq., 1 ft. thick, 2 ft. above the ground, bears South, 10.33 chs. dist.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.45	<p>Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E S 7 1/4 ——— S 18</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Set a steel fence post, 6 ft. long, alongside of stainless steel post.</p> <p>From this cor. point, a rebar of unknown origin, 1/2 in. diam., firmly set, projecting 2 ins. above the ground, in a collar of stone, bears S. 3°37' E., 35 lks. dist.</p>
80.42	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T22N R15E R16E S12 S7 S13 S18 2005, witnessed with a steel fence post set alongside.</p> <p>Add the marks 2007 to the brass cap.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°30' W., bet. secs. 7 and 8.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
40.23	<p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E 1/4 S 7   S 8</p> <p style="text-align: center;">2007</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS													
	Deposit a magnet in a white plastic case at the base of and a 3 1/2 in. black figurine of a Ninja Warrior alongside the stainless steel post.												
59.18	Southerly right-of-way fence of BIA Route 15, bears N. 54°12' E. and S. 54°12' W.												
61.03	Center of right-of-way fences falls in pavement of BIA Route 15, 38 ft. wide, bears N. 54°12' E. and S. 54°12' W.												
62.89	Northerly right-of-way fence of BIA Route 15, bears N. 54°12' E. and S. 54°12' W.												
73.07	Center of Trans Western pipelines, bears N. 45°34' E. and S. 45°34' W.												
79.98	Center of El Paso Natural Gas pipelines, bears N. 80°57' E. and S. 80°57' W.												
80.46	Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist., there is no remaining evidence of the orig. cor.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.												
	<table style="margin: auto;"> <tr> <td colspan="4">T 22 N R 16 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 6</td> <td style="border-right: 1px solid black;"></td> <td style="border-right: 1px solid black;">S 5</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black;">S 7</td> <td style="border-right: 1px solid black;"></td> <td style="border-right: 1px solid black;">S 8</td> <td></td> </tr> </table> <p style="text-align: center;">2007</p>	T 22 N R 16 E				S 6		S 5		S 7		S 8	
T 22 N R 16 E													
S 6		S 5											
S 7		S 8											
	Deposit a magnet in a white plastic case at the base of the stainless steel post.												
	Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.												
	From the cor. of secs. 4, 5, 8 and 9.												
	S. 89°49' W., bet. secs. 5 and 8.												
	Over broken terrain, through scattered sage brush and Mormon Tea.												
39.92	The 1/4 sec. cor. of secs. 5 and 8, monumented with a flint stone, 15 X 8 X 6, loosely set in a mound of stone, 2 1/2 ft. base, 1 ft. high, mkd. 1/4 on a face.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.												

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 16 E S 5 1/4 ——— S 8  2007
	Deposit a magnet in a white plastic case at the base of and the orig. stone alongside of the stainless steel post.  Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.  <hr style="width: 20%; margin: auto;"/> N. 88°50' W., beginning new measurement.
5.72	Southerly right-of-way fence of BIA Route 15, bears N. 78°02' E. and S. 64°09' W., on a curve.  From this point, a right-of-way marker, monumented with a 3 in. diam. brass cap, incased in concrete, 6 ins. diam., 1 in. below the surface of the ground, mkd. BIA NAVAJO ROADS 19 ELEV 5166.02 1983 with a 4 in. angle iron alongside, projecting 22 ins. above the ground, mkd. HWRW 1005+66.36, in right-of-way fence, bears S. 64°09' W., 19.47 chs. dist.
10.32	Center of right-of-way fences falls in the pavement of BIA Route 15, 38 ft. wide, bears N. 75°54' E. and S. 61°58' W., on a curve.
14.17	Northerly right-of-way fence of BIA Route 15, bears N. 74°11' E. and S. 60°14' W., on a curve.  From this point, a right-of-way marker, monumented with a 3 in. diam. brass cap, incased in concrete, 6 ins. diam., projecting 3 ins. above the ground, mkd. BIA NAVAJO ROADS 19 ELEV 5176.80 1983, with a 4 in. angle iron alongside, projecting 20 ins. above the ground, mkd. HWRW 1005+66.36, in right-of-way fence, bears S. 60°14' W., 12.50 chs. dist.
32.55	Center of Trans Western pipelines, bears N. 45°35' E. and S. 45°35' W.
37.51	Center of El Paso Natural Gas pipelines, bears N. 80°57' E. and S. 80°57' W.
40.21	The cor. of secs. 5, 6, 7 and 8.  <hr style="width: 80%; margin: auto;"/> S. 89°31' W., bet. secs. 6 and 7.  Over gently rolling terrain, through scattered sage brush and Mormon Tea.

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.21	<p>Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E S 6 1/4 ——— S 7</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.66	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T22N R15E R16E S1 S6 S7 S12 2005, witnessed with a steel fence post set alongside.</p> <p>Add the marks 2007 to the brass cap.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°30' W., bet. secs. 5 and 6.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
40.23	<p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E 1/4 S 6   S 5</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Dependent Resurvey of the Subdivisional Lines,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.38	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p align="center"><b>Subdivision of Section 1, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 12.</p> <p>N. 0°06' W., on the N. and S. center line of sec. 1.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
10.80	<p>Southerly right-of-way fence of BIA Route 15, bears N. 82°22' E. and S. 82°22' W.</p> <p>From this point, a right-of-way marker, monumented with a 3 in. diam. brass cap, incased in concrete, 6 ins. diam., flush with ground, mkd. BIA NAVAJO ROADS 19, with a 4 in. angle iron alongside, projecting 17 ins. above the ground, in the southerly right-of-way fence, bears N. 88°22' E., 29.24 chs. dist.</p>
12.33	<p>Center of right-of-way fences falls in the pavement of BIA Route 15, 38 ft. wide, bears N. 82°22' E. and S. 82°22' W.</p>
13.86	<p>Northerly right-of-way fence of BIA Route 15, bears N. 82°22' E. and S. 82°22' W.</p> <p>From this point, a right-of-way marker, monumented with a 3 in. diam. brass cap, incased in concrete, 6 ins. diam., flush with ground, mkd. BIA NAVAJO ROADS 19, with a 4 in. angle iron alongside, projecting 19 ins. above the ground, in the northerly right-of-way fence, bears N. 88°22' E., 28.84 chs. dist.</p>
23.54	<p>Center of Trans Western pipelines, bears N. 85°45' E. and S. 85°45' W.</p>
40.50	<p>Point for the center 1/4 sec. cor. of sec. 1, at intersection with the E. and W. center line of the sec.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T 22 N R 16 E C 1/4 S 1</p> <p align="center">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Subdivision of Section 1,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
47.09	Center of El Paso Natural Gas pipelines, bears N. 82°24' E. and S. 82°24' W.
80.87	The 1/4 sec. cor. of secs. 1 and 36, on the N. bdy. of the Tp. <hr/> From the 1/4 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp.  S. 89°11' W., on the E. and W. center line of sec. 1.  Over broken terrain, through scattered sage brush and Mormon Tea.
40.00	The center 1/4 sec. cor. of sec. 1.
79.00	The 1/4 sec. cor. of secs. 1 and 2. <hr/>
<b>Subdivision of Section 2, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b>	
	From the 1/4 sec. cor. of secs. 2 and 11.  N. 1°26' W., on the N. and S. center line of sec. 2.  Over broken terrain, through scattered sage brush and Mormon Tea.
1.60	Southerly right-of-way fence of BIA Route 15, bears N. 82°23' E. and S. 82°23' W.
3.12	Center of right-of-way fences falls in the pavement of BIA Route 15, 38 ft. wide, bears N. 82°23' E. and S. 82°23' W.
4.64	Northerly right-of-way fence of BIA Route 15, bears N. 82°23' E. and S. 82°23' W.
36.99	Center of Trans Western pipelines, bears S. 72°07' E. and N. 72°07' W.
37.72	Center of El Paso Natural Gas pipelines, bears N. 82°20' E. and S. 82°20' W.
40.84	Point for the center 1/4 sec. cor. of sec. 2, at intersection with the E. and W. center line of the sec.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**Subdivision of Section 2,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 16 E C 1/4 S 2  2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.
81.75	The 1/4 sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp. <hr/>
	From the 1/4 sec. cor. of secs. 1 and 2.
	S. 89°30' W., on the E. and W. center line of sec. 2.
	Over broken terrain, through scattered sage brush and Mormon Tea.
15.36	Center of El Paso Natural Gas pipelines, bears N. 82°20' E. and S. 82°20' W.
39.97	The center 1/4 sec. cor. of sec. 2.
49.27	Center of Trans Western pipelines, bears S. 72°07' E. and N. 72°07' W.
68.15	Center of Trans Western pipelines, bears N. 83°02' E. and S. 83°02' W.
79.94	The 1/4 sec. cor. of secs. 2 and 3. <hr/>
	<b>Subdivision of Section 3, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b> <hr/>
	From the 1/4 sec. cor. of secs. 3 and 10.
	N. 1°12' W., on the N. and S. center line of sec. 3.
	Over broken terrain, through scattered sage brush and Mormon Tea.
27.47	Center of El Paso Natural Gas pipelines, bears N. 82°22' E. and S. 82°22' W.
34.71	Center of Trans Western pipelines, bears N. 83°02' E. and S. 83°02' W.

**Subdivision of Section 3,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.85	<p>Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E. and W. center line of the sec.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E C 1/4 S 3</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
81.81	<p>The 1/4 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 2 and 3.</p> <p>S. 89°52' W., on the E. and W. center line of sec. 3.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
40.11	The center 1/4 sec. cor. of sec. 3.
80.22	<p>The 1/4 sec. cor. of secs. 3 and 4.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 4, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 4 and 9.</p> <p>N. 0°49' W., on the N. and S. center line of sec. 4.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
0.65	Center of right-of-way fences falls in the pavement of BIA Route 15, 38 ft. wide, bears S. 82°01' E. and N. 82°01' W.
2.18	Northerly right-of-way fence of BIA Route 15, bears S. 82°01' E. and N. 82°01' W.
16.80	Center of El Paso Natural Gas pipelines, bears N. 82°08' E. and S. 82°08' W.
25.04	Center of Trans Western pipelines, bears N. 83°02' E. and S. 83°02' W.

**Subdivision of Section 4,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.78	<p>Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E. and W. center line of the sec.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E C 1/4 S 4</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
81.57	<p>The 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 4.</p> <p>S. 89°49' W., on the E. and W. center line of sec. 4.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
40.09	<p>The center 1/4 sec. cor. of sec. 4.</p>
80.18	<p>The 1/4 sec. cor. of secs. 4 and 5.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 5, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 8.</p> <p>N. 0°40' W., on the N. and S. center line of sec. 5.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
1.43	<p>Southerly right-of-way fence of BIA Route 15, bears N. 80°53' E. and S. 67°08' W., on a curve.</p> <p>From this point, a right-of-way marker, monumented with a 3 in. diam. brass cap, incased in concrete, 6 ins. diam., projecting 10 ins. above the ground, mkd. BIA NAVAJO ROADS 19 ELEV 5942.75 1983, with a 4 in. angle iron alongside, projecting 18 ins. above the ground, mkd. HWRW 1024+23.55, in right-of-way fence, bears N. 80°53' E., 1.97 chs. dist.</p>
2.96	<p>Center of right-of-way fences falls in the pavement of BIA Route 15, 38 ft. wide, bears N. 81°10' E. and S. 68°08' W., on a curve.</p>

**Subdivision of Section 5,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
4.50	<p>Northerly right-of-way fence of BIA Route 15, bears N. 81°30' E. and S. 73°24' W.</p> <p>From this point, a right-of-way marker, monumented with a 3 in. diam. brass cap, incased in concrete, 6 ins. diam., flush with the ground, mkd. BIA NAVAJO ROADS 19 ELEV 5202.09 1983, with a 4 in. angle iron alongside, projecting 15 ins. above the ground, mkd. HWRW 1024+23.55 in right-of-way fence, bears N. 81°30' E., 1.58 chs. dist.</p>
6.06	Center of El Paso Natural Gas pipelines, bears N. 82°08' E. and S. 82°08' W.
15.48	Center of Trans Western pipelines, bears N. 83°02' E. and S. 83°02' W.
40.96	<p>Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E. and W. center line of the sec.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E C 1/4 S 5</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
81.39	<p>The 1/4 sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 4 and 5.</p> <p>N. 89°52' W., on the E. and W. center line of sec. 5.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
39.94	The center 1/4 sec. cor. of sec. 5.
80.02	<p>The 1/4 sec. cor. of secs. 5 and 6.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 6, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 6 and 7.</p> <p>N. 0°19' W., on the N. and S. center line of sec. 6.</p>

**Subdivision of Section 6,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over broken terrain, through scattered sage brush and Mormon Tea.
40.28	Point for the center 1/4 sec. cor. of sec. 6, at intersection with the E. and W. center line of the sec.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  T 22 N R 16 E C 1/4 S 6  2007  Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.52	The 1/4 sec. cor. of secs. 6 and 31, on the N. bdy. of the Tp. <hr/> From the 1/4 sec. cor. of secs. 5 and 6.  S. 89°35' W., on the E. and W. center line of sec. 6.  Over broken terrain, through scattered sage brush and Mormon Tea.
40.08	The center 1/4 sec. cor. of sec. 6.
79.28	The 1/4 sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T22N R15E R16E 1/4 S1 S6 2005.  Add the marks 2007 to the brass cap. <hr/>
	<b>Subdivision of Section 7, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b>
	From the 1/4 sec. cor. of secs. 7 and 18.  N. 0°21' W., on the N. and S. center line of sec. 7.  Over broken terrain, through scattered sage brush and Mormon Tea.
30.68	Southerly right-of-way fence of BIA Route 15, bears N. 54°11' E. and S. 54°11' W.

**Subdivision of Section 7,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	From this point, a right-of-way marker, monumented with a 3 in. diam. brass cap, incased in concrete, 6 ins. diam., 2 ins. below the surface of the ground, mkd. BIA NAVAJO ROADS 19 ELEV 4989.15 1983, with a 4 in. angle iron alongside, projecting 18 ins. above the ground, mkd. HWRW 933+95 934+00 in right-of-way fence, bears S. 54°11' W., 38.52 chs. dist.
32.54	Center of right-of-way fences falls in the pavement of BIA Route 15, 38 ft. wide, bears N. 54°11' E. and S. 54°11' W.
34.40	Northerly right-of-way fence of BIA Route 15, bears N. 54°11' E. and S. 54°11' W.
	From this point, a right-of-way marker, monumented with a 3 in. diam. brass cap, incased in concrete, 6 ins. diam., 2 ins. below the ground, mkd. BIA NAVAJO ROADS 19 ELEV 4989.99 1983, with a 4 in. angle iron alongside, projecting 29 ins. above the ground, mkd. HWRW 933+95.25 AHD 934+00.53 BK in right-of-way fence, bears S. 54°11' W., 40.68 chs. dist.
40.28	Point for the center 1/4 sec. cor. of sec. 7, at intersection with the E. and W. center line of the sec.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 16 E C 1/4 S 7
	2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
40.99	Center of Trans Western pipelines, bears N. 50°58' E. and S. 50°58' W.
74.00	Center of El Paso Natural Gas pipelines, bears N. 80°57' E. and S. 80°57' W.
80.56	The 1/4 sec. cor. of secs. 6 and 7.
	From the 1/4 sec. cor. of secs. 7 and 8.
	S. 89°27' W., on the E. and W. center line of sec. 7.
	Over broken terrain, through scattered sage brush and Mormon Tea.
26.78	Southerly right-of-way fence of BIA Route 15, bears N. 54°11' E. and S. 54°11' W.

**Subdivision of Section 7,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
29.41	Center of right-of-way fences falls in the pavement of BIA Route 15, 38 ft. wide, bears N. 54°11' E. and S. 54°11' W.
32.03	Northerly right-of-way fence of BIA Route 15, bears N. 54°11' E. and S. 54°11' W.
40.33	The center 1/4 sec. cor. of sec. 7.
41.22	Center of Trans Western pipelines, bears N. 50°58' E. and S. 50°58' W.
80.04	The 1/4 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T22N R15E R16E 1/4 S12 S7 2005, witnessed with a steel fence post set alongside.  Add the marks 2007 to the brass cap.
<hr/> <b>Subdivision of Section 8, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b> <hr/>	
	From the 1/4 sec. cor. of secs. 8 and 17.  N. 0°43' W., on the N. and S. center line of sec. 8.  Over broken terrain, through scattered sage brush and Mormon Tea.
39.13	Point for the center 1/4 sec. cor. of sec. 8, at intersection with the E. and W. center line of the sec.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  T 22 N R 16 E C 1/4 S 8  2007  Deposit a magnet in a white plastic case at the base of the stainless steel post.  Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.  Set a steel fence post, 6 ft. long, alongside of the stainless steel post.
79.90	The 1/4 sec. cor. of secs. 5 and 8.

**Subdivision of Section 8,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 8 and 9.</p> <p>N. 88°05' W., on the E. and W. center line of sec. 8.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
38.91	The center 1/4 sec. cor. of sec. 8.
79.30	The 1/4 sec. cor. of secs. 7 and 8.
<hr/> <p><b>Subdivision of Section 9, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 9 and 16.</p> <p>N. 0°22' W., on the N. and S. center line of sec. 9.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
38.95	<p>Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E. and W. center line of the sec.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E C 1/4 S 9</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.54	Southerly right-of-way fence of BIA Route 15, bears S. 82°01' E. and N. 82°01' W.
80.43	The 1/4 sec. cor. of secs. 4 and 9.
	<hr/> <p>From the 1/4 sec. cor. of secs. 9 and 10.</p> <p>S. 88°52' W., on the E. and W. center line of sec. 9.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
39.41	The center 1/4 sec. cor. of sec. 9.

**Subdivision of Section 9,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.43	<p>The 1/4 sec. cor. of secs. 8 and 9.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 10, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 10 and 15.</p> <p>N. 0°38' E., on the N. and S. center line of sec. 10.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
39.45	<p>Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E. and W. center line of the sec.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E C 1/4 S 10</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post, 6 ft. long, alongside of the stainless steel post.</p>
72.70	<p>Southerly right-of-way fence of BIA Route 15, bears N. 85°33' E. and N. 88°50' W., in a curve.</p> <p>From this point, a right-of-way marker, monumented with a 3 in. diam. brass cap, incased in concrete, 6 ins. diam., 2 ins. below the surface of the ground, mkd. BIA NAVAJO ROADS 19 ELEV 5324.60 1983, with a 4 in. angle iron alongside, projecting 17 ins. above the ground, mkd. 1119+99, in right-of-way fence, bears N. 88°50' W., 14.77 chs. dist.</p>
74.21	<p>Center of right-of-way fences falls in the pavement of BIA Route 15, 38 ft. wide, bears N. 85°33' E. and N. 88°50' W., in a curve.</p>
75.73	<p>Northerly right-of-way fence of BIA Route 15, bears N. 85°33' E. and N. 88°50' W.</p>

**Subdivision of Section 10,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this point, a right-of-way marker, monumented with a 3 in. diam. brass cap, incased in concrete, 6 ins. diam., projecting 20 ins. above the ground, mkd. BIA NAVAJO ROADS 19 ELEV 5323.24 1983, in right-of-way fence, bears N. 88°50' W., 14.61 chs. dist.</p>
80.29	<p>The 1/4 sec. cor. of secs. 3 and 10.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 10 and 11.</p> <p>S. 89°58' W., on the E. and W. center line of sec. 10.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
39.64	<p>The center 1/4 sec. cor. of sec. 10.</p>
80.01	<p>The 1/4 sec. cor. of secs. 9 and 10.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 11, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 11 and 14.</p> <p>N. 2°45' E., on the N. and S. center line of sec. 11.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
38.46	<p>Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E. and W. center line of the sec.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 1 in. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E C 1/4 S 11</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located in two track road, bears E. and W.</p>
78.25	<p>The 1/4 sec. cor. of secs. 2 and 11.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 11 and 12.</p>

**Subdivision of Section 11,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	S. 87°45' W., on the E. and W. center line of sec. 11.  Over broken terrain, through scattered sage brush and Mormon Tea.
38.22	The center 1/4 sec. cor. of sec. 11.
77.41	The 1/4 sec. cor. of secs. 10 and 11.
<hr/>	
<b>Subdivision of Section 12, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b>	
<hr/>	
	From the 1/4 sec. cor. of secs. 12 and 13.  N. 1°23' E., on the N. and S. center line of sec. 12.  Over severely broken terrain, through scattered sage brush and Mormon Tea.
39.96	Point for the center 1/4 sec. cor. of sec. 12, at intersection with the E. and W. center line of the sec.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 16 E C 1/4 S 12  2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.  Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
79.38	The 1/4 sec. cor. of secs. 1 and 12.
<hr/>	
	From the 1/4 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp.  S. 89°54' W., on the E. and W. center line of sec. 12.  Over severely broken terrain, through scattered sage brush and Mormon Tea.
38.64	The center 1/4 sec. cor. of sec. 12.

**Subdivision of Section 12,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.44	<p>The 1/4 sec. cor. of secs. 11 and 12.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 13, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 24.</p> <p>N. 0°48' E., on the N. and S. center line of sec. 13.</p> <p>Over severely broken terrain, through scattered sage brush and Mormon Tea.</p>
40.17	<p>Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E. and W. center line of the sec.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E C 1/4 S 13</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
80.34	<p>The 1/4 sec. cor. of secs. 12 and 13.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.</p> <p>S. 89°58' W., on the E. and W. center line of sec. 13.</p> <p>Over severely broken terrain, through scattered sage brush and Mormon Tea.</p>
39.72	<p>The center 1/4 sec. cor. of sec. 13.</p>
79.45	<p>The 1/4 sec. cor. of secs. 13 and 14.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 14, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of 14 and 23.</p> <p>N. 0°12' E., on the N. and S. center line of sec. 14.</p>

**Subdivision of Section 14,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over severely broken, rocky terrain.
40.34	Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E. and W. center line of the sec.  Set a brass tablet, 3 1/4 ins. diam., cemented in a drill hole, on rock shelf, 2 ins. below the surface of the ground, with top mkd.  <div style="text-align: center;">T 22 N R 16 E C 1/4 S 14  2007</div> Deposit a cylindrical magnet, 3/4 X 1 in., beneath the brass tablet, in the drill hole.  Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.
81.96	The 1/4 sec. cor. of secs. 11 and 14. <hr/> From the 1/4 sec. cor. of secs. 13 and 14. S. 87°54' W., on the E. and W. center line of sec. 14. Over severely broken, rocky terrain.
39.77	The center 1/4 sec. cor. of sec. 14.
77.98	The 1/4 sec. cor. of secs. 14 and 15. <hr/>
	<b>Subdivision of Section 15, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b>
	From the 1/4 sec. cor. of secs. 15 and 22. N. 1°20' E., on the N. and S. center line of sec. 15. Over severely broken, rocky terrain.
40.16	Point for the center 1/4 sec. cor. of sec. 15, at intersection with the E. and W. center line of the sec.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

**Subdivision of Section 15,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 22 N R 16 E C 1/4 S 15</p> <p>2007</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.45	<p>The 1/4 sec. cor. of secs. 10 and 15.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 15.</p> <p>N. 89°47' W., on the E. and W. center line of sec. 15.</p> <p>Over severely broken, rocky terrain.</p>
40.00	<p>The center 1/4 sec. cor. of sec. 15.</p>
79.69	<p>The 1/4 sec. cor. of secs. 15 and 16.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 16, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 16 and 21.</p> <p>N. 1°08' E., on the N. and S. center line of sec. 16.</p> <p>Over severely broken, rocky terrain.</p>
39.91	<p>Point for the center 1/4 sec. cor. of sec. 16, at intersection with the E. and W. center line of the sec.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E C 1/4 S 16</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post, 6 ft. long, alongside of stainless steel post.</p> <p>Cor. is located on Westerly slope of a Mesa.</p>
79.62	<p>The 1/4 sec. cor. of secs. 9 and 16.</p>

**Subdivision of Section 16,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<hr/> <p>From the 1/4 sec. cor. of secs. 15 and 16.</p> <p>N. 89°49' W., on the E. and W. center line of sec. 16.</p> <p>Over severely broken, rocky terrain.</p>
19.63	<p>Point for the center E. 1/16 sec. cor. of sec. 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E CE 1/16 S 16</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Set a steel fence post, 6 ft. long, alongside of stainless steel post.</p> <p>Cor. is located on the NW slope of a mesa.</p>
39.26	<p>The center 1/4 sec. cor. of sec. 16.</p>
59.02	<p>Point for the center W. 1/16 sec. cor. of sec. 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E CW 1/16 S 16</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>Set a steel fence post, 6 ft. long, alongside of the stainless steel post.</p>
78.78	<p>The cor. of secs. 16 and 17.</p> <hr/> <p style="text-align: center;"><b>NE 1/4 of Section 16,</b></p> <hr/>

**Subdivision of Section 16,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.74	<p>From the center E. 1/16 sec. cor. of sec. 16.</p> <p>N. 1°04' E., on the N. and S. center line of the NE 1/4 of sec. 16.</p> <p>Over severely broken, rocky terrain.</p> <p>The E. 1/16 sec. cor. of secs. 9 and 16.</p> <hr/> <p style="text-align: center;"><b>SE 1/4 of Section 16,</b></p> <hr/> <p>From the E. 1/16 sec. cor. of secs. 16 and 21.</p> <p>N. 1°04' E., along the N. and S. center line of the SE 1/4 of sec. 16.</p> <p>Over severely broken, rocky terrain.</p>
39.84	<p>The center E. 1/16 sec. cor. of sec. 16.</p> <hr/> <p style="text-align: center;"><b>SW 1/4 of Section 16,</b></p> <hr/> <p>From the W. 1/16 sec. cor. of secs. 16 and 21.</p> <p>N. 1°23' E., along the N. and S. center line of the SW 1/4 of sec. 16.</p> <p>Over severely broken, rocky terrain.</p>
39.78	<p>The center W. 1/16 sec. cor. of sec. 16.</p> <hr/> <p style="text-align: center;"><b>NW 1/4 of Section 16,</b></p> <hr/> <p>From the center W. 1/16 sec. cor. of sec. 16.</p> <p>N. 1°23' E., along the N. and S. center line of the NW 1/4 of sec. 16.</p> <p>Over severely broken, rocky terrain.</p>
39.68	<p>The W. 1/16 sec. cor. of secs. 9 and 16.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 17, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>

**Subdivision of Section 17,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 17 and 20.</p> <p>N. 1°23' E., on the N. and S. center line of sec. 17.</p> <p>Over severely broken, rocky terrain.</p>
39.45	<p>True point for the center 1/4 sec. cor. of sec. 17, at intersection with the E. and W. center line of the sec., is located on the steep S. slope of wash, drains WNW, where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for a witness cor. to the center 1/4 sec. cor. of sec. 17, bears S. 30°57' E., 30 lks. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p> <p>T 22 N R 16 E</p>  <p>C 1/4 S 17</p> <p>2007</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.</p>
79.40	<p>The 1/4 sec. cor. of secs. 8 and 17.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 16 and 17.</p> <p>S. 89°56' W., on the E. and W. center line of sec. 17.</p> <p>Over severely broken, rocky terrain.</p>
40.35	<p>The center 1/4 sec. cor. of sec. 17.</p>
80.76	<p>The 1/4 sec. cor. of secs. 17 and 18.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 18, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 18 and 19.</p> <p>N. 0°22' E., on the N. and S. center line of sec. 18.</p>

**Subdivision of Section 18,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over broken terrain, through scattered sage brush and Mormon Tea.
40.06	Point for the center 1/4 sec. cor. of sec. 18, at intersection with the E. and W. center line of the sec.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  T 22 N R 16 E C 1/4 S 18  2007  Deposit a magnet in a white plastic case at the base of the stainless steel post.  Set a steel fence post, 6 ft. long, alongside of stainless steel post.
80.12	The 1/4 sec. cor. of secs. 7 and 18. <hr/> From the 1/4 sec. cor. of secs. 17 and 18.  S. 89°37' W., on the E. and W. center line of sec. 18.  Over broken terrain, through scattered sage brush and Mormon Tea.
39.85	The center 1/4 sec. cor. of sec. 18.
79.27	The 1/4 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T22N R15E R16E 1/4 S13 S18 2005.  Add the marks 2007 to the brass cap.  Set a steel fence post, 6 ft. long, alongside of stainless steel post. <hr/> <p style="text-align: center;"><b>Subdivision of Section 19, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> From the 1/4 sec. cor. of secs. 19 and 30.  N. 0°45' W., on the N. and S. center line of sec. 19.  Over broken terrain, through scattered sage brush and Mormon Tea.

**Subdivision of Section 19,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.87	<p>Point for the center 1/4 sec. cor. of sec. 19, at intersection with the E. and W. center line of the sec.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E C 1/4 S 19</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.74	<p>The 1/4 sec. cor. of secs. 18 and 19.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 20.</p> <p>S. 89°50' W., on the E. and W. center line of sec. 19.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea. _____</p>
39.25	<p>The center 1/4 sec. cor. of sec. 19.</p>
78.35	<p>The 1/4 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T22N R15E R16E 1/4 S24 S19 2005, witnessed with a steel fence post set alongside.</p> <p>Add the marks 2007 to the brass cap.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 20, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 20 and 29.</p> <p>N. 0°03' E., on the N. and S. center line of sec. 20.</p> <p>Over severely broken, rocky terrain.</p>
40.24	<p>Point for the center 1/4 sec. cor. of sec. 20, at intersection with the E. and W. center line of the sec.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

**Subdivision of Section 20,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 22 N R 16 E C 1/4 S 20  2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
80.98	The 1/4 sec. cor. of secs. 17 and 20. <hr/> From the 1/4 sec. cor. of secs. 20 and 21. N. 89°56' W., on the E. and W. center line of sec. 20. Over severely broken, rocky terrain.
39.69	The center 1/4 sec. cor. of sec. 20.
79.46	The 1/4 sec. cor. of secs. 19 and 20. <hr/>
	<b>Subdivision of Section 21, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b>
	From the 1/4 sec. cor. of secs. 21 and 28. N. 0°26' E., on the N. and S. center line of sec. 21. Over severely broken, rocky terrain.
40.20	Point for the center 1/4 sec. cor. of sec. 21, at intersection with the E. and W. center line of the sec.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 16 E C 1/4 S 21  2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.
80.20	The 1/4 sec. cor. of secs. 16 and 21. <hr/> From the 1/4 sec. cor. of secs. 21 and 22.

**Subdivision of Section 21,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	S. 89°39' W., on the E. and W. center line of sec. 21. Over severely broken, rocky terrain.
39.83	The center 1/4 sec. cor. of sec. 21.
79.91	The 1/4 sec. cor. of secs. 20 and 21.
<hr/> <b>Subdivision of Section 22, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b> <hr/>	
	From the 1/4 sec. cor. of secs. 22 and 27. N. 0°41' W., on the N. and S. center line of sec. 22. Over severely broken, rocky terrain.
40.16	Point for the center 1/4 sec. cor. of sec. 22, at intersection with the E. and W. center line of the sec.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 16 E C 1/4 S 22  2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.  Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.
80.31	The 1/4 sec. cor. of secs. 15 and 22.
<hr/>	
	From the 1/4 sec. cor. of secs. 22 and 23. N. 88°41' W., on the E. and W. center line of sec. 22. Over severely broken, rocky terrain.
39.79	The center 1/4 sec. cor. of sec. 22.
79.58	The 1/4 sec. cor. of secs. 21 and 22.
<hr/> <b>Subdivision of Section 23, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b> <hr/>	


**Subdivision of Section 23,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 23 and 26.</p> <p>N. 0°47' W., on the N. and S. center line of sec. 23.</p> <p>Over severely broken, rocky terrain.</p>
40.37	<p>Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E. and W. center line of the sec.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E C 1/4 S 23</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.74	<p>The 1/4 sec. cor. of secs. 14 and 23.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 23 and 24.</p> <p>S. 87°26' W., on the E. and W. center line of sec. 23.</p> <p>Over severely broken, rocky terrain.</p>
39.33	<p>The center 1/4 sec. cor. of sec. 23.</p>
78.67	<p>The 1/4 sec. cor. of secs. 22 and 23.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 24, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 24 and 25.</p> <p>N. 0°14' E., on the N. and S. center line of sec. 24.</p> <p>Over severely broken, rocky terrain.</p>
40.20	<p>Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E. and W. center line of the sec.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>

**Subdivision of Section 24,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>T 22 N R 16 E C 1/4 S 24</p> <p>2007</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 5 ft. base, 3 ft. high, W. of cor.</p>
80.37	<p>The 1/4 sec. cor. of secs. 13 and 24.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp.</p> <p>S. 89°52' W., on the E. and W. center line of sec. 24.</p> <p>Over severely broken, rocky terrain.</p>
38.92	<p>The center 1/4 sec. cor. of sec. 24.</p>
77.98	<p>The 1/4 sec. cor. of secs. 23 and 24.</p> <hr/>
	<p><b>Subdivision of Section 25, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 25 and 36.</p> <p>N. 3°07' E., on the N. and S. center line of sec. 25.</p> <p>Over severely broken, rocky terrain.</p>
40.22	<p>Point for the center 1/4 sec. cor. of sec. 25, at intersection with the E. and W. center line of the sec.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>T 22 N R 16 E C 1/4 S 25</p> <p>2007</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p>
80.33	<p>The 1/4 sec. cor. of secs. 24 and 25.</p>

**Subdivision of Section 25,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<hr/> <p>From the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp.</p> <p>S. 89°39' W., on the E. and W. center line of sec. 25.</p> <p>Over severely broken, rocky terrain.</p>
39.48	The center 1/4 sec. cor. of sec. 25.
79.01	The 1/4 sec. cor. of secs. 25 and 26.
	<hr/> <p style="text-align: center;"><b>Subdivision of Section 26, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 26 and 35.</p> <p>N. 5°47' E., on the N. and S. center line of sec. 26.</p> <p>Over severely broken, rocky terrain.</p>
38.38	<p>True point for the center 1/4 sec. cor. of sec. 26, at intersection with the E. and W. center line of the sec., is located on the steep S. face of a Mesa where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for a witness cor. to the center 1/4 sec. cor. of sec. 26, bears N. 14°19' E., 37 lks. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p> <p>T 22 N R 16 E</p> <p>C 1/4 / S 26</p>  <p>2007</p> </div>
78.29	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>The 1/4 sec. cor. of secs. 23 and 26.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26.</p> <p>S. 87°56' W., on the E. and W. center line of sec. 26.</p>

**Subdivision of Section 26,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over severely broken, rocky terrain.
39.97	The center 1/4 sec. cor. of sec. 26.
78.84	The 1/4 sec. cor. of secs. 26 and 27.
<hr/> <p><b>Subdivision of Section 27, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
	From the 1/4 sec. cor. of secs. 27 and 34.
	N. 4°32' E., on the N. and S. center line of sec. 27.
	Over severely broken, rocky terrain.
39.60	True point for the center 1/4 sec. cor. of sec. 27, at intersection with the E. and W. center line of the sec., is located on the steep S. face of a Mesa where it is impracticable to establish a permanent monument.
	From this true point, the point selected for a witness cor. to the center 1/4 sec. cor. of sec. 27, bears N. 10°13' W., 1.00 ch. dist.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<pre> WC T 22 N   R 16 E   C 1/4   S 27       ↓       2007 </pre>
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
79.19	The 1/4 sec. cor. of secs. 22 and 27.
	From the 1/4 sec. cor. of secs. 26 and 27.
	N. 88°33' W., on the E. and W. center line of sec. 27.
	Over severely broken, rocky terrain.
39.45	The center 1/4 sec. cor. of sec. 27.

**Subdivision of Section 27,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
78.89	<p>The 1/4 sec. cor. of secs. 27 and 28.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 28, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 28 and 33.</p> <p>N. 2°22' E., on the N. and S. center line of sec. 28.</p> <p>Over severely broken, rocky terrain.</p>
39.69	<p>Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E. and W. center line of the sec.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E C 1/4 S 28</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.37	<p>The 1/4 sec. cor. of secs. 21 and 28.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 27 and 28.</p> <p>S. 89°12' W., on the E. and W. center line of sec. 28.</p> <p>Over severely broken, rocky terrain.</p>
39.49	<p>The center 1/4 sec. cor. of sec. 28.</p>
78.98	<p>The 1/4 sec. cor. of secs. 28 and 29.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 29, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 29 and 32.</p> <p>N. 0°42' E., on the N. and S. center line of sec. 29.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>

**Subdivision of Section 29,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
39.70	<p>Point for the center 1/4 sec. cor. of sec. 29, at intersection with the E. and W. center line of the sec.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E C 1/4 S 29</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.39	<p>The 1/4 sec. cor. of secs. 20 and 29.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 28 and 29.</p> <p>N. 89°35' W., on the E. and W. center line of sec. 29.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
38.86	<p>The center 1/4 sec. cor. of sec. 29.</p>
77.72	<p>The 1/4 sec. cor. of secs. 29 and 30.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 30, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 30 and 31.</p> <p>N. 0°15' W., on the N. and S. center line of sec. 30.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
39.87	<p>Point for the center 1/4 sec. cor. of sec. 30, at intersection with the E. and W. center line of the sec.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E C 1/4 S 30</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Subdivision of Section 30,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
79.74	<p>The 1/4 sec. cor. of secs. 19 and 30.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 29 and 30.</p> <p>S. 89°47' W., on the E. and W. center line of sec. 30.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
38.97	The center 1/4 sec. cor. of sec. 30.
78.18	<p>The 1/4 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. T22N R15E R16E 1/4 S25 S30 2005.</p> <p>Add the marks 2007 to the brass cap.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 31, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 6 and 31, on the S. bdy. of the Tp.</p> <p>N. 1°13' W., on the N. and S. center line of sec. 31.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
39.60	Two track road, bears N. 50° E. and S. 50° W.
39.88	<p>Point for the center 1/4 sec. cor. of sec. 31, at intersection with the E. and W. center line of the sec.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E C 1/4 S 31</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
79.76	<p>The 1/4 sec. cor. of secs. 30 and 31.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 31 and 32.</p>

**Subdivision of Section 31,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>S. 89°44' W., on the E. and W. center line of sec. 31.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
39.00	Two track road, bears N. 50° E. and S. 50° W.
39.34	The center 1/4 sec. cor. of sec. 31.
78.98	<p>The 1/4 sec. cor. of secs. 31 and 36, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T22N R15E R16E 1/4 S36 S31 2005.</p> <p>Add the marks 2007 to the brass cap.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 32, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.</p> <p>N. 3°14' W., on the N. and S. center line of sec. 32.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
39.76	<p>Point for the center 1/4 sec. cor. of sec. 32, at intersection with the E. and W. center line of the sec.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E C 1/4 S 32</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p>
79.51	<p>The 1/4 sec. cor. of secs. 29 and 32.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 32 and 33.</p> <p>S. 89°56' W., on the E. and W. center line of sec. 32.</p>

**Subdivision of Section 32,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over broken terrain, through scattered sage brush and Mormon Tea.
39.26	The center 1/4 sec. cor. of sec. 32.
78.52	The 1/4 sec. cor. of secs. 31 and 32
<hr/> <p><b>Subdivision of Section 33, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
	From the 1/4 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp.
	N. 5°15' W., on the N. and S. center line of sec. 33.
	Over broken terrain, through scattered sage brush and Mormon Tea.
39.82	Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E. and W. center line of the sec.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 N R 16 E C 1/4 S 33
	2007
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.
79.64	The 1/4 sec. cor. of secs. 28 and 33.
	From the 1/4 sec. cor. of secs. 33 and 34.
	S. 89°32' W., on the E. and W. center line of sec. 33.
	Over broken terrain, through scattered sage brush and Mormon Tea.
39.34	The center 1/4 sec. cor. of sec. 33.

**Subdivision of Section 33,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
78.68	<p>The 1/4 sec. cor. of secs. 32 and 33.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 34, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp.</p> <p>N. 5°41' W., on the N. and S. center line of sec. 34.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
39.67	<p>Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E. and W. center line of the sec.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E C 1/4 S 34</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.</p>
79.34	<p>The 1/4 sec. cor. of secs. 27 and 34.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 34 and 35.</p> <p>N. 89°23' W., on the E. and W. center line of sec. 34.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
38.39	<p>The center 1/4 sec. cor. of sec. 34.</p>
76.78	<p>The 1/4 sec. cor. of secs. 33 and 34.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 35, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp.</p>

**Subdivision of Section 35,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>N. 4°28' W., on the N. and S. center line of sec. 35.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
39.80	<p>Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E. and W. center line of the sec.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E C 1/4 S 35</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p>
81.10	<p>The 1/4 sec. cor. of secs. 26 and 35.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 35 and 36.</p> <p>S. 89°25' W., on the E. and W. center line of sec. 35.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
39.30	<p>The center 1/4 sec. cor. of sec. 35.</p>
77.78	<p>The 1/4 sec. cor. of secs. 34 and 35</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 36, T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 36, on the S. bdy. of the Tp.</p> <p>N. 0°45' W., on the N. and S. center line of sec. 36.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
40.30	<p>Point for the center 1/4 sec. cor. of sec. 36, at intersection with the E. and W. center line of the sec.</p>

Subdivision of Section 36,  
T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 N R 16 E C 1/4 S 36</p> <p style="text-align: center;">2007</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
80.63	<p>The 1/4 sec. cor. of secs. 25 and 36.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp.</p> <p>S. 89°47' W., on the E. and W. center line of sec. 36.</p> <p>Over broken terrain, through scattered sage brush and Mormon Tea.</p>
39.34	<p>The center 1/4 sec. cor. of sec. 36.</p>
78.53	<p>The 1/4 sec. cor. of secs. 35 and 36.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>This survey is located on the Navajo Indian Reservation, north of the town of Winslow Arizona.</p> <p>Most of the township consists of rugged, steep and broken terrain, with gently rolling terrain in the north west portion of township. Vegetation consists of native grasses, Mormon Tea and sage brush, used primarily for grazing of sheep, cattle and horses.</p> <p>BIA Route 15 traverses the township in an easterly and westerly direction.</p> <p>The mean magnetic declination of 11 1/4° E. was derived from the National Geophysical Data Center's magnetic declination calculator GEOMAG v6.0, utilizing the International Geomagnetic Reference Field model for years 2005 through 2010, for the dates of survey.</p> <hr/>



CERTIFICATE OF SURVEY

I, Joe R. Salazar, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 29th day of April, 2005, I have dependently resurveyed the Fourth Guide Meridian East (east boundary), the south and north boundaries and the subdivisional lines and surveyed the subdivision of all sections, T. 22 N., R. 16 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 1973 and in specific manner described in the foregoing field notes.

11/14/2007  
(Date)

Joe R. Salazar  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the dependent resurvey of the Fourth Guide Meridian East (east boundary), the south and north boundaries and the subdivisional lines and survey of the subdivision of all sections, T. 22 N., R. 16 E., Gila and Salt River Meridian, in the State of Arizona, executed by Joe R. Salazar, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

DEC. 6, 2007  
(Date)

Paul J. Moss  
Acting (Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 22 N., R. 16 E., Gila and Salt River Meridian, Arizona, is a true copy of the orig. field notes.~~

~~\_\_\_\_\_~~  
~~(Date)~~

~~\_\_\_\_\_~~  
~~(Chief Cadastral Surveyor of Arizona)~~