ORIGINAL

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

SOUTH, WEST, AND NORTH BOUNDARIES

THE SUBIVISIONAL LINES

AND

SUBDIVISION OF CERTAIN SECTIONS

TOWNSHIP 38 NORTH, RANGE 10 EAST,

OF THE GILA AND SALT RIVER MERIDIAN,

IN THE STATE OF ARIZONA.

EXECUTED BY

Fabian Yazzie, Cadastral Surveyor

Under Special Instructions dated November 15, 2012, approved November 15, 2012, which provided for the surveys included under Group No. 1114, and assignment instructions dated November 15, 2012.

Survey commenced November 27, 2012

Survey completed May 21, 2013

INDEX DIAGRAM

TOWNSHIP 38 NORTH RANGE 10 EAST GILA & SALT RIVER MERIDIAN, ARIZONA

	21		20		19		18		17		16
15	6	68	5	56	4	48	3	4 0	2	31	1
	67		66		55		47		39		30
14	7	65	8	54	9	46	10	38	11	29	12
	65		64		53		45		37		28
13	18	63	17	53	16	44	15	36	14	27	13
	62		61		52		44		36		26
12	19	61	20	51	21	43	22	35	23	25	24
	60		59		50		42		34		25
11	30	58	29	50	28	42	27	33	26	24	25
	58		57		49		41		33		23
10	31	56	32	48	33	40	34	32	35	22	36
	8		7		7		6		5		4

Establishment of t	the Standard (Corner of		
Township 37 North	, Ranges 9 and	d 10 East	 Pages	9-10
Subdivision of Sec	ction 1		 Pages 6	8-69
Subdivision of Sec	ction 2		 Page	70
Subdivision of Sec	ction 12		 Pages 7	0-72
Subdivision of Sec	ction 13		 Page	72

T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the survey of the South, West, and North boundaries, the subdivisional lines, and the subdivision of certain sections, Township 38 North, Range 10 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Joe R. Salazar established the closing corner of Townships 36 North, Ranges 9 and 10 East, on the Ninth Standard Parallel North, in a plat only survey, under Group No. 1059, in 2009. Fabian Yazzie surveyed the Ninth Standard Parallel North (south boundary), Township 37 North, Range 11 East, under Group No. 1105, in 2012. Fabian Yazzie surveyed the west boundary of Township 38 North, Range 11 East, under Group No. 1106, in 2012.

The survey was executed in accordance with the specifications as set forth in the <u>Manual of Instructions for the Survey of the Public Lands of the United States, 2009</u>, and the Special Instructions dated November 15, 2012, for Group Number 1114, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation R8 and 5700 model receivers.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) AI8805 FRED FREDONIA CORS, DI2245 P011 SPIDERROCKAZ2005 CORS, DJ8981 FST5 FLAGSTAFF 5 CORS, AZFL NAU FLAGSTAFF CORS, and DK8419 AZPG CITY OF PAGE CORS. The NAD 83 (2011) (EPOCH: 2010), geographic position of the corner of Townships 37 and 38 North, Ranges 10 and 11 East, is as follows:

Latitude: 36°38'32.799" N. Longitude: 111°15'47.196" W.

The geographic position of the corner of Townships 38 and 39 North, Ranges 9 and 10 East, is as follows:

Latitude: 36°43'45.955" N. Longitude: 111°22'15.362" W.

The mean magnetic declination is 11° E.

CHAINS

Beginning at the cor. of Tps. 37 and 38 N., Rs. 10 and 11 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 3 ins. above ground, with brass cap mkd. T38N R10E R11E S36 S31 S1 S6 T37N 2012.

West, bet. secs. 1 and 36, on the S. bdy. of the Tp.

Over gently rolling land.

40.00 Point for the 1/4 sec. cor. of secs. 1 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

- 74.70 Trail road, bears N. 30° E. and S. 30° W.
- 80.00 | Point for the cor. of secs. 1, 2, 35 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Cor. is located 20 lks. S. of a graded road, 12 ft. wide, bears S. 60° E. and N. 60° W., and 32 lks. E. of an intersecting graded road, 12 ft. wide, extending S. 40° E. and S. 60° E.

Land, gently rolling.

Soil, sandy loam and scattered sandstone rock outcrops. Timber, juniper.

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona									
CHAINS										
	Undergrowth, native grasses, salt brush and Mormon tea.									
	West, bet. secs. 2 and 35, on the S. bdy. of the Tp.									
	Over gently rolling land.									
40.00	Point for the 1/4 sec. cor. of secs. 2 and 35.									
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.									
	T 38 N R 10 E									
	S 35 1/4 ——									
	S 2									
	T 37 N									
	2012									
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.									
	Set a steel fence post nearby.									
80.00	Point for the cor. of secs. 2, 3, 34 and 35.									
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.									
	T 38 N R 10 E									
	S 34 S 35									
	S 3 S 2 T 37 N									
	2012									
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.									
	Set a steel fence post nearby.									
	Land, gently rolling. Soil, sandy loam and sandstone rock outcrops. Timber, juniper and pinon. Undergrowth, native grasses, salt brush and rabbit brush.									

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	West, bet. secs. 3 and 34, on the S. bdy. of the Tp.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	S 34 1/4 ——
	S 3 T 37 N
	2012
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
76.95	Top of a sandstone rim, 40 ft. high, bears N. and S. 5° E.
80.00	Point for the cor. of secs. 3, 4, 33 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, with brass cap mkd.
	T 38 N R 10 E
	S 33 S 34
	S 4 S 3 T 37 N
	2012
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located on top of Many Ghosts Hill, a sandstone mesa, and is 1.65 chs. N. of the south rim, 40 ft. high, bears S. 40° E. and N. 55° W., and 4.35 chs. E. of the west rim, 50 ft. high, bears N. and S. 45° E.
	Land, rolling. Soil, sandy loam and sandstone rock outcrops. Timber, juniper and pinon. Undergrowth, native grasses, salt brush, yucca, Mormon tea and rabbit brush.

		T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
	CHAINS	
		West, bet. secs. 4 and 33, on the S. bdy. of the Tp.
		Over rolling land.
	40.00	Point for the 1/4 sec. cor. of secs. 4 and 33.
		Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
		T 38 N R 10 E
		S 33 1/4 ——
		S 4 T 37 N
		2012
•		Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
		Set a steel fence post nearby.
	80.00	Point for the cor. of secs. 4, 5, 32 and 33.
		Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
		T 38 N R 10 E
		S 32 S 33 S 5 S 4
		T 37 N
		2012
		Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
		Set a steel fence post nearby.
		Land, rolling. Soil, sandy loam and sandstone rock outcrops. Timber, juniper. Undergrowth, native grasses, yucca, Mormon tea and salt brush.
		——————————————————————————————————————
		West, bet. secs. 5 and 32, on the S. bdy. of the Tp.
		Over gently rolling land.
	40.00	Point for the 1/4 sec. cor. of secs. 5 and 32.
		Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	T 38 N R 10 E
	S 32 1/4 ———
	S 5
	T 37 N
	2012
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 5, 6, 31 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 31 S 32
	S 6 S 5 T 37 N
	2012
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling. Soil, sandy loam.
	Timber, juniper.
	Undergrowth, native grasses, sage brush, yucca, Mormon tea and salt brush.
	West, bet. secs. 6 and 31, on the S. bdy. of the Tp.
	Over gently rolling land.
31.65	Trail road, bears S. 55° E. and N. 55° W.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS	
	T 38 N R 10 E
	S 31
	1/4
	S 6
	T 37 N

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

79.45 | Point for the cor. of Tps. 37 and 38 N., Rs. 9 and 10 E.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

From this cor. point, point for the stan. cor. of Tps. 37 N., Rs. 9 and 10 E., determined East, 480.00 chs. from the stan. cor. of Tps. 37 N., Rs. 10 and 11 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. SC T37N R10E R11E S36 S31 T36N R10E S1 2012.

Point for the stan. cor. of Tps. 37 N., Rs. 9 and 10 E.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in solid sandstone bedrock, with brass cap mkd.

2012

CHAINS

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

From this cor. point, the closing cor. of Tps. 36 N., Rs. 9 and 10 E., bears East, 13.66 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 ins. above ground, with brass cap mkd. T37N R10E S31 S1 S6 R9E R10E T36N CC 2009. Add the marks 2012 to the brass cap.

Land, gently rolling.

Soil, sandy loam.

Timber, juniper and pinon.

Undergrowth, native grasses, sage brush, yucca, Mormon tea and salt brush.

Survey of the West Boundary, T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona

From the cor. of Tps. 37 and 38 N., Rs. 9 and 10 E., hereinbefore described.

North, bet. secs. 31 and 36, on the W. bdy. of the ${\rm Tp.}$

Over rolling land.

40.00

Point for the 1/4 sec. cor. of secs. 31 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

80.00

Point for the cor. of secs. 25, 30, 31 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona											
CHAINS												
	T 38 N R 9 E R 10 E S 25 S 30 S 36 S 31											
	2012											
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.											
	Set a steel fence post nearby.											
	Land, rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, sparse yucca, and Mormon tea. North, bet. secs. 25 and 30, on the W. bdy. of the Tp.											
	Over gently rolling land.											
40.00	Point for the 1/4 sec. cor. of secs. 25 and 30.											
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.											
	T 38 N R 9 E R 10 E 1/4											
	S 25 S 30											
	2012											
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.											
	Set a steel fence post nearby.											
	Cor. is located 2.00 chs. S. of a power line, 2 strand, bears S. 75° E. and N. 75° W., and 3.00 chs. S. of BIA Route 20A, a graded road, 30 ft. wide, bears S. 80° E. and N. 80° W.											
76.50	Circular White Ridge Mesa rim, 70 ft. high, bears N. 80° E. and S. 80° W.											
80.00	Point for the cor. of secs. 19, 24, 25 and 30.											
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.											
L												

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	T 38 N R 9 E R 10 E S 24 S 19 S 25 S 30
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	From this cor., a third order bench mark DISTRICT, bears S. 78° W., 79.58 chs. dist., monumented with a brass tablet, 3 1/2 ins. diam., firmly set, flush with the surface of sandstone bedrock, near cliff edge, mkd. U.S. GEOLOGICAL SURVEY BENCHMARK 1954 ELEVATION ABOVE SEA FEET DISTRICT.
	Land, rolling and broken. Soil, sandy loam and sandstone rock outcrops. Timber, juniper. Undergrowth, native grasses, rabbit brush and Mormon tea.
	North, bet. secs. 19 and 24, on the W. bdy. of the Tp.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 9 E R 10 E 1/4
	S 24 S 19
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
:	Set a steel fence post nearby.
	Cor. is located on the W. gentle slope of a hill, and is 98 lks. E. of a trail road, bears N. 10° E. and S. 10° W.
80.00	Point for the cor. of secs. 13, 18, 19 and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground to sandstone bedrock, with brass cap mkd.

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona											
CHAINS												
	T 38 N R 9 E R 10 E S 13 S 18 S 24 S 19											
	2013											
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.											
	Set a steel fence post nearby.											
	Land, rolling. Soil, sandy loam and sandstone rock outcrops. Timber, juniper. Undergrowth, native grasses, yucca, rabbit brush and Mormon tea.											
	North, bet. secs. 13 and 18, on the W. bdy. of the Tp.											
	Over rolling and broken land.											
40.00	Point for the 1/4 sec. cor. of secs. 13 and 18.											
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to sandstone bedrock, with brass cap mkd.											
	T 38 N R 9 E R 10 E 1/4											
	S 13 S 18											
	2013											
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.											
	Set a steel fence post nearby.											
80.00	Point for the cor. of secs. 7, 12, 13 and 18.											
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.											
	T 38 N R 9 E R 10 E S 12 S 7 S 13 S 18											
	2013											

Survey of the West Boundary,

т.	38	м.,	ĸ.	TO	в.,	Glia	and	Sait	River	meridian,	Arizona

CHAINS

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Land, rolling and broken.

Soil, sandy loam and sandstone rock outcrops.

Timber, juniper.

Undergrowth, native grasses, yucca and Mormon tea.

North, bet. secs. 7 and 12, on the W. bdy. of the Tp.

Over rolling land.

40.00

Point for the 1/4 sec. cor. of secs. 7 and 12.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

80.00

Point for the cor. of secs. 1, 6, 7 and 12.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

2013

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Land, rolling, broken and rugged.

Soil, sandy loam and sandstone rock outcrops.

Timber, juniper.

	1. 36 N., R. 10 E., Gila and Sait River Meridian, Arizona
CHAINS	Undergrowth, native grasses, yucca and Mormon tea.
	North, bet. secs. 1 and 6, on the W. bdy. of the Tp.
	Over rolling land.
13.65	Barbed wire fence, 5 strand, bears N. 35° E. and S. 35° W.
29.80	Circular White Ridge Mesa rim, 80 ft. high, bears S. 75° E. and N. 20° W.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 6.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 9 E R 10 E 1/4
	S 1 S 6
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
58.20	Circular White Ridge Mesa rim, 60 ft. high, bears N. 50° E. and S. 60° W.
68.80	Wash, 40 ft. wide, 20 ft. deep, drains N. 75° E.
80.00	Point for the cor. Tps. 38 and 39 N., Rs. 9 and 10 E.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 9 E R 10 E S 36 S 31 S 1 S 6 T 38 N
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.

CHAINS

Cor. is located 3.30 chs. W. of a barbed wire fence, 5 strand, bears N. 30 $^{\circ}$ E. and S. 30 $^{\circ}$ W.

From this cor. point, the cor. of Tps. 39 and 40 N., Rs. 9 and 10 E., bears North, 480.00 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in sandstone bedrock, projecting 6 ins. above ground, with brass cap mkd. T40N R9E R10E S36 S31 S1 S6 T39N 2005. Add the marks 2012 to the brass cap.

Land, rolling and broken.

Soil, sandy loam.

Timber, juniper.

Undergrowth, native grasses, yucca and Mormon tea.

Survey of the North Boundary, T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona

From the cor. of Tps. 38 and 39 N., Rs. 10 and 11 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. T39N R10E R11E S36 S31 S1 S6 T38N 2012.

West, bet. secs. 1 and 36, on the N. bdy. of the Tp.

Over rolling land.

40.00

Point for the 1/4 sec. cor. of secs. 1 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Cor. is located 1.30 chs. W. of a trail road, bears N. 10° E. and S. 10° W.

80.00

Point for the cor. of secs. 1, 2, 35 and 36.

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

2012

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

From this cor., a right-of-way monument, bears S. 1° E., 5.20 chs. dist., monumented with a brass tablet, 2 1/2 ins. diam., set flush in a concrete cylinder, 6 ins. diam., firmly set, projecting 6 ins. above ground, mkd. BIA ROADS 1969, with an angle iron, firmly set nearby, faintly mkd. 1005+79.35 P.O.T. HWY R of W.

From the same cor., a right-of-way monument, bears S. 22° W., 7.00 chs. dist., monumented with a brass tablet, 2 1/2 ins. diam., set flush in a concrete cylinder, 6 ins. diam., firmly set, projecting 5 ins. above ground, mkd. BIA ROADS 1969, with an angle iron, firmly set nearby, faintly mkd. 1005+79.35 P.O.T. HWY R of W.

Land, gently rolling and nearly level.

Soil, sandy loam.

Timber, no timber.

Undergrowth, native grasses, salt brush and Mormon tea.

West, bet. secs. 2 and 35, on the N. bdy. of the Tp.

Over gently rolling land.

- 2.37 E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
- 4.09 State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 25° E. and N. 25° W.
- 5.69 W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
- 40.00 Point for the 1/4 sec. cor. of secs. 2 and 35.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

GUATNO	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	T 39 N R 10 E S 35
	1/4 ————————————————————————————————————
	T 38 N
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 2, 3, 34 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E
	S 34 S 35 S 3 S 2
	T 38 N
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	From this cor., the center line of a three-way intersection of trail roads, bears S. 80° W., 1.00 ch. dist., extending N. 60° E., E., and S. 65° W.
	Land, gently rolling.
	Soil, sandy loam. Timber, no timber.
	Undergrowth, native grasses, sage brush and Mormon tea.
	West, bet. secs. 3 and 34, on the N. bdy. of the Tp.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

CHAINS	
	T 39 N R 10 E
	S 34
	1/4 —— S 3
	T 38 N
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
73.77	E. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
74.51	Center line of Black Mesa and Lake Powell Railroad, bears S. 20° E. and N. 20° W.
75.45	W. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
80.00	Point for the cor. of secs. 3, 4, 33 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E S 33 S 34 S 4 S 3 T 38 N
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 24 lks. E. of a trail road, bears S. 25° E. and N. 25° W.
	Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, sage brush, yucca and Mormon tea.
	West, bet. secs. 4 and 33, on the N. bdy. of the Tp.
	Over gently rolling land.
	over genery retring rand.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 33.

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam. 25 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E S 33 1/4
	T 38 N
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 4, 5, 32 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam. 25 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E S 32 S 33 S 5 S 4
	T 38 N
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 50 lks. E. of a wash, 17 ft. wide, 2 ft. deep drains N. 30° W.
	Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, sage brush, yucca and Mormon tea.
	West, bet. secs. 5 and 32, on the N. bdy. of the Tp.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam. 24 ins. in the ground, with brass cap mkd.

	Survey of the North Boundary, T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	T 39 N R 10 E S 32 1/4 —— S 5 T 38 N
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 5, 6, 31 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 39 N R 10 E S 31 S 32 S 6 S 5
	T 38 N
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 1.65 chs. E. of a wash, 12 ft. wide, 4 ft. deep, drains N. 25° W.
	Land, rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, yucca and Mormon tea.
	West, bet. secs. 6 and 31, on the N. bdy. of the Tp.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	T 39 N R 10 E S 31 1/4 — S 6 T 38 N
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
78.91	The cor. of Tps. 38 and 39 N., Rs. 9 and 10 E., hereinbefore described.
	Land, rolling and broken. Soil, sandy loam and sandstone rock outcrops. Timber, sparse juniper. Undergrowth, native grasses, yucca and Mormon tea.
	Survey of the Subdivisional Lines, T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
	From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°01' W., bet. secs. 35 and 36.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 35 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	S 35 S 36
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 1.74 chs. N. of a bladed road, 12 ft. wide, bears N. 45° E. and S. 50° W.
80.00	Point for the cor. of secs. 25, 26, 35 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 38 N R 10 E S 26 S 25 S 35 S 36

2013

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Land, gently rolling.

Soil, sandy loam.

Timber, sparse juniper.

Undergrowth, native grasses, salt brush, yucca and Mormon tea.

From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 6 ins. above ground, with brass cap mkd. T38N R10E R11E S25 S30 S36 S31 2012.

West, bet. secs. 25 and 36.

Over gently rolling land.

34.60 Trail road, bears N. 10° E. and S. 10° W.

40.00 Point for the 1/4 sec. cor. of secs. 25 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 38 N R 10 E S 25 1/4 —— S 36

2013

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Cor. is located 96 lks. E. of a trail road, bears N. 10° E. and S. 10° W.

80.00 The cor. of secs. 25, 26, 35 and 36.

CHAINS	
	Land, gently rolling. Soil, sandy loam, gravel and sandstone. Timber, scattered juniper. Undergrowth, native grasses, salt brush, yucca and Mormon tea.
	N. 0°01' W., bet. secs. 25 and 26.
	Over gently rolling land.
10.35	Trail road, bears N. 40° E. and S. 40° W.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in solid sandstone bedrock, with brass cap mkd.
	T 38 N R 10 E
	1/4 S 26 S 25
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
61.65	Trail road, bears S. 10° E. and N. 10° W.
80.00	Point for the cor. of secs. 23, 24, 25 and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	S 23 S 24
	S 26 S 25
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 3.30 chs. E. of a trail road, bears S. 40° E. and N. 40° W.
	Land, gently rolling. Soil, sandy loam. Timber, sparse juniper.

CHAINS	
	Undergrowth, native grasses, salt brush, rabbit brush, sage brush, yucca and Mormon tea.
	From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 4 ins. above ground, with brass cap mkd. T38N R10E R11E S24 S19 S25 S30 2012.
	West, bet. secs. 24 and 25.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 24 and 25.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 24 1/4 —— S 25
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
60.81	E. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
61.74	Center line of Black Mesa and Lake Powell Railroad, bears S. 15° E. and N. 15° W.
62.59	W. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
80.00	The cor. of secs. 23, 24, 25 and 26.
	Land, gently rolling. Soil, sandy loam. Timber, no timber. Undergrowth, native grasses, salt brush, yucca and Mormon tea.
	N. 0°01' W., bet. secs. 23 and 24.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	T 38 N R 10 E 1/4 S 23 S 24
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
43.20	W. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
44.84	Center line of Black Mesa and Lake Powell Railroad, bears S. 30° E. and N. 30° W.
46.21	E. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
80.00	Point for the cor. of secs. 13, 14, 23 and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	S 14 S 13 S 23 S 24
	'
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 2.30 chs. N. and 3.30 chs. E. of a power line, 2 strand, bears S. 55° E. and N. 55° W.
	Land, gently rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, native grasses, salt brush, yucca and Mormon tea.
	From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 4 ins. above ground, with brass cap mkd. T38N R10E R11E S13 S18 S24 S19 2012.
	West, bet. secs. 13 and 24.

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 13
	1/4
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located on top of a mesa plateau.
80.00	The cor. of secs. 13, 14, 23 and 24.
	Land, gently rolling and broken. Soil, sandy loam and sandstone rock outcrops. Timber, juniper. Undergrowth, native grasses, salt brush, yucca and Mormon tea.
	N. 0°01' W., bet. secs. 13 and 14.
	Ascending over gently rolling land.
38.50	Base of sandstone rim, 50 ft. high, bears S. 15° E. and N. 15° W.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E 1/4 S 14 S 13
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
74.10	Trail road, bears S. 20° E. and N. 20° W.
80.00	Point for the cor. of secs. 11, 12, 13 and 14.

Survey of the Subdivisional Lines

	Survey of the Subdivisional Lines, T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 11 S 12 S 14 S 13
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 1.00 ch. E. and 1.70 chs. S. of a trail road, bears N. 20° E. and S. 32° W., and 3.75 chs. E. of sandstone mesa rim, 30 ft. high, bears N. 5° E. and S. 5° E.
	Land, gently rolling and broken. Soil, sandy loam and sandstone rock outcrops. Timber, sparse juniper. Undergrowth, native grasses, rabbit brush and yucca.
	From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 2 ins. above ground, with brass cap mkd. T38N R10E R11E S12 S7 S13 S18 2012.
	West, bet. secs. 12 and 13.
	Over gently rolling land.
7.50	E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
9.13	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 25° E. and N. 25° W.
10.80	W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 12 and 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	T 38 N R 10 E
	S 12 1/4 ——
	S 13
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
73.80	Trail road, bears N. 25° E. and S. 25° W.
80.00	The cor. of secs. 11, 12, 13 and 14.
	Land, gently rolling. Soil, sandy loam. Timber, no timber. Undergrowth, native grasses, yucca and Mormon tea.
	N. 0°01' W., bet. secs. 11 and 12.
	Over gently rolling land on top of mesa plateau.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	1/4 S 11 S 12
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
55.30	BIA Route 20A, a graded road, 30 ft. wide, bears N. 60° E. and S. 60° W.
80.00	Point for the cor. of secs. 1, 2, 11 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
İ	

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	T 38 N R 10 E
	<u>S 2 S 1</u>
	S 11 S 12
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 2.65 chs. E. of a trail road, bears S. 10° E. and N. 5° W.
	Land, gently rolling and broken. Soil, sandy loam. Timber, no timber. Undergrowth, native grasses, rabbit brush, yucca and Mormon tea.
	From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 2 ins. above ground, with brass cap mkd. T38N R10E R11E S1 S6 S12 S7 2012.
	West, bet. secs. 1 and 12.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	S 1
	1/4 —— S 12
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
44.94	E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
46.61	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 25° E. and N. 25° W.

CHAINS	
48.25	W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
59.90	BIA Route 20A, a graded road, 30 ft. wide, bears N. 55° E. and S. 55° W.
73.65	Trail road, bears S. 20° E. and N. 20° W.
80.00	The cor. of secs. 1, 2, 11 and 12.
	Land, gently rolling. Soil, sandy loam. Timber, no timber. Undergrowth, native grasses, rabbit brush, salt brush, yucca and Mormon tea.
	N. 0°01' W., bet. secs. 1 and 2.
	Over gently rolling land on top of mesa plateau.
40.00	Point for the 1/4 sec. cor. of secs. 1 and 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E 1/4 S 2 S 1
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
67.83	W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
71.30	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 25° E. and N. 25° W.
73.49	From this point, a right-of-way monument, bears W., 2.66 chs. dist., monumented with a brass tablet, 2 1/2 ins. diam., set flush in a concrete cylinder, 6 ins. diam., firmly set, projecting 5 ins. above ground, mkd. BIA ROADS 1969, with an angle iron, firmly set nearby, faintly mkd. 1005+79.35 P.O.T. HWY R of W.
74.78	From this point, a right-of-way monument, bears E., 8.64 lks. dist., monumented with a brass tablet, 2 1/2 ins. diam., set flush in a concrete cylinder, 6 ins. diam., firmly set, projecting 6 ins. above ground, mkd. BIA ROADS 1969, with an

	1. 30 N., K. 10 E., Gila and Salt River Meliuran, Alizona
CHAINS	
	angle iron, firmly set nearby, faintly mkd. 1005+79.35 P.O.T. HWY R of W.
74.94	E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
80.00	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described.
	Land, gently rolling. Soil, sandy loam. Timber, no timber. Undergrowth, native grasses, rabbit brush, yucca and Mormon tea.
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°01' W., bet. secs. 34 and 35.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 34 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E 1/4 S 34 S 35
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 32 lks. N. of a trail road, bears S. 10° E. and N. 5° W.
77.10	Trail road, bears S. 20° E. and N. 20° W.
80.00	Point for the cor. of secs. 26, 27, 34 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 27 S 26 S 34 S 35
	2013

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 1.40 chs. E. of a trail road, bears S. 10° E. and N. 5° W.
	Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, sage brush, yucca and Mormon tea.
	From the cor. of secs. 25, 26, 35 and 36.
	West, bet. secs. 26 and 35.
	Over gently rolling land.
7.15	Trail road, bears N. 40° E. and S. 40° W.
34.80	Trail road, bears N. 10° E. and S. 10° W.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	S 26 1/4 ——
	S 35
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The cor. of secs. 26, 27, 34 and 35.
	Land, gently rolling. Soil, sandy loam. Timber, no timber. Undergrowth, native grasses, sage brush, salt brush and Mormon tea.
	N. 0°01' W., bet. secs. 26 and 27.
	Over gently rolling land.

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. solid sandstone bedrock, with brass cap mkd.
	T 38 N R 10 E
	1/4 S 27 S 26
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 22, 23, 26 and 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 22 S 23
	S 27 S 26
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, sage brush, salt brush, yucca and Mormon tea.
	From the cor. of secs. 23, 24, 25 and 26.
	West, bet. secs. 23 and 26.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 23 1/4 — S 26
	2013

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The cor. of secs. 22, 23, 26 and 27.
	Land, gently rolling. Soil, sandy loam and sandstone rock outcrops. Timber, no timber. Undergrowth, native grasses, sage brush and Mormon tea.
	N. 0°01' W., bet. secs. 22 and 23.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	1/4 S 22 S 23
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
80.00	Point for the cor. of secs. 14, 15, 22 and 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 15 S 14 S 22 S 23
	2013
, , , , , , , , , , , , , , , , , , ,	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling. Soil, sandy loam. Timber, no timber. Undergrowth, native grasses, yucca, sage brush and Mormon tea.

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	From the cor. of secs. 13, 14, 23 and 24.
	West, bet. secs. 14 and 23.
	Over gently rolling land.
21.41	E. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
22.45	Center line of Black Mesa and Lake Powell Railroad, bears S. 35° E. and N. 35° W.
23.66	W. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	S 14
	1/4 —— S 23
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The cor. of secs. 14, 15, 22 and 23.
	Land, gently rolling. Soil, sandy loam. Timber, no timber. Undergrowth, native grasses, yucca, sage brush and Mormon tea.
	N. 0°01' W., bet. secs. 14 and 15.
	Over gently rolling land.
28.25	Power line, 2 strand, bears S. 60° E. and N. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 15.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	T 38 N R 10 E
	1/4 S 15 S 14
	'
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 10, 11, 14 and 15.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 10 S 11 S 15 S 14
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 2.80 chs. S. of BIA Route 20A, a graded road, 30 ft. wide, bears N. 60° E. and S. 60° W.
	Land, gently rolling. Soil, sandy loam. Timber, no timber. Undergrowth, native grasses, yucca, sage brush and Mormon tea.
	From the cor. of secs. 11, 12, 13 and 14.
	West, bet. secs. 11 and 14.
	Descending sandstone mesa plateau.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	S 11 1/4 ——
	S 14
	2013

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 18lks. E. of a trail road, bears S. 5° E. and N. 5° W.
73.29	E. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
74.14	Center line of Black Mesa and Lake Powell Railroad, bears S. 35° E. and N. 35° W.
75.00	W. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
75.65	Trail road, bears S. 50° E. and N. 50° W.
80.00	The cor. of secs. 10, 11, 14 and 15.
	Land, gently rolling and broken. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, yucca, sage brush and Mormon tea.
	N. 0°01' W., bet. secs. 10 and 11.
	Over gently rolling land.
2.80	BIA Route 20A, a graded road, 30 ft. wide, bears N. 60° E. and S. 60° W.
7.59	W. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
9.06	Center line of Black Mesa and Lake Powell Railroad, bears S. 35° E. and N. 35° W.
10.54	E. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E 1/4 S 10 S 11
	2013
	2013

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 2, 3, 10 and 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 3 S 2 S 10 S 11
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling. Soil, sandy loam. Timber, no timber. Undergrowth, native grasses, yucca, salt brush and Mormon tea.
	From the cor. of secs. 1, 2, 11 and 12.
:	West, bet. secs. 2 and 11.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 2 1/4 —— S 11
	2013 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The cor. of secs. 2, 3, 10 and 11.
	Land, gently rolling and broken.

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Soil, sandy loam, gravel and sandstone. Timber, no timber.
į.	Undergrowth, native grasses, yucca, salt brush and Mormon tea.
	N. 0°01' W., bet. secs. 2 and 3.
	Gently ascending mesa plateau.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	1/4 S 3 S 2
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., hereinbefore described.
	Land, gently rolling to broken and nearly level. Soil, sandy loam. Timber, no timber. Undergrowth, native grasses, cholla grass and Mormon tea.
	From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°02' W., bet. secs. 33 and 34.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 33 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E 1/4 S 33 S 34
	2013
1	1

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 27, 28, 33 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 28 S 27 S 33 S 34
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, yucca, sage brush and Mormon tea.
	From the cor. of secs. 26, 27, 34 and 35.
	West, bet. secs. 27 and 34.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 27
	1/4 = 3 2 7 S 34
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The cor. of secs. 27, 28, 33 and 34.
	Land, gently rolling.

CHAINS	
--------	--

Soil, sandy loam.

Timber, scattered juniper.

Undergrowth, native grasses, yucca and Mormon tea.

N. 0°02' W., bet. secs. 27 and 28.

Over gently rolling land.

40.00 | Point for the 1/4 sec. cor. of secs. 27 and 28.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 38 N R 10 E 1/4 S 28 | S 27

2013

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

80.00 Point for the cor. of secs. 21, 22, 27 and 28.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 38 N R 10 E S 21 S 22 S 28 S 27

2013

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Land, gently rolling.

Soil, sandy loam.

Timber, sparse juniper.

Undergrowth, native grasses, sage brush, salt brush and Mormon tea.

From the cor. of secs. 22, 23, 26 and 27.

West, bet. secs. 22 and 27.

Over gently rolling land.

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
40.00	Point for the 1/4 sec. cor. of secs. 22 and 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 22
	1/4
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The cor. of secs. 21, 22, 27 and 28.
	Land, gently rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, native grasses, sage brush, salt brush, yucca and
	Mormon tea.
	N. 0°02' W., bet. secs. 21 and 22.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	1/4 S 21 S 22
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 15, 16, 21 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS	
	T 38 N R 10 E
	S 16 S 15
	S 21 S 22
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, native grasses, yucca and Mormon tea.
	From the cor. of secs. 14, 15, 22 and 23.
	West, bet. secs. 15 and 22.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 15 1/4 — S 22
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The cor. of secs. 15, 16, 21 and 22.
	Land, gently rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, native grasses, sage brush, yucca and Mormon tea.
	N. 0°02' W., bet. secs. 15 and 16.
	Over gently rolling land.
20.90	Power line, 2 strand, bears N. 45° E. and S. 45° W.

CHAINS	1. 30 N., R. 10 E., GIII and Bale River Meriaran, Millond
22.90	BIA Route 20A, a graded road, 30 ft. wide, bears N. 45° E. and S. 45° W.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, encircled with a collar of stone, 4 ft. base, to top, with brass cap mkd.
	T 38 N R 10 E 1/4 S 16 S 15
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 9, 10, 15 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 9 S 10 S 16 S 15
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling and scattered sandstone rock outcrops. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, salt brush, sage brush, yucca and
	Mormon tea.
	From the cor. of secs. 10, 11, 14 and 15.
	West, bet. secs. 10 and 15.
	Over gently rolling land.
5.35	BIA Route 20A, a graded road, 30 ft. wide, bears N. 60° E. and S. 60° W.

	T. 38 N., R. 10 E., Gila and Sait River Meridian, Arizona
CHAINS	
40.00	Point for the 1/4 sec. cor. of secs. 10 and 15.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	S 10 1/4 ——
	S 15
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	From this cor. point, the center line of four-way intersection of trail roads, bears S. 80° W., 1.95 chs. dist., extending N. 5° E., S. 70° E., S. 5° W. and N. 75° W.
80.00	The cor. of secs. 9, 10, 15 and 16.
	Land, gently rolling. Soil, sandy loam and scattered sandstone rock outcrops. Timber, scattered juniper. Undergrowth, native grasses, salt brush, sage brush, yucca and Mormon tea.
	N. 0°02' W., bet. secs. 9 and 10.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	1/4 S 9 S 10
	2013
1	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 3, 4, 9 and 10.

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 4 S 3
	S 9 S 10
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling. Soil, sandy loam and scattered sandstone rock outcrops. Timber, sparse juniper. Undergrowth, native grasses, yucca and Mormon tea.
	From the cor. of secs. 2, 3, 10 and 11.
	West, bet. secs. 3 and 10.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 10.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	S 3 1/4 ——
	S 10
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
44.06	E. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
44.92	Center line of Black Mesa and Lake Powell Railroad, bears S. 30° E. and N. 30° W.
45.79	W. right-of-way fence of Black Mesa and Lake Powell Railroad, woven and barbed wire, parallels railroad.
80.00	The cor. of secs. 3, 4, 9 and 10.

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Land, gently rolling. Soil, sandy loam and gravel. Timber, no timber. Undergrowth, native grasses, yucca and Mormon tea.
	N. 0°02' W., bet. secs. 3 and 4.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	1/4 S 4 S 3
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described.
	Land, gently rolling. Soil, sandy loam. Timber, no timber. Undergrowth, native grasses, salt brush, yucca and Mormon tea.
	From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°03' W., bet. secs. 32 and 33.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E 1/4 S 32 S 33
	2013

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 28, 29, 32 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 29 S 28 S 32 S 33
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, rolling. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, sage brush, yucca and Mormon tea.
	From the cor. of secs. 27, 28, 33 and 34.
	West, bet. secs. 28 and 33.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 33.
40.00	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 28 1/4 ———
	S 33
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The cor. of secs. 28, 29, 32 and 33.

CHAINS	Land, gently rolling.
	Soil, sandy loam.
	Timber, juniper. Undergrowth, native grasses, sage brush, yucca and Mormon tea.
	N. 0°03' W., bet. secs. 28 and 29.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	1/4 S 29 S 28
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 20, 21, 28 and 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	S 20 S 21 S 29 S 28
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 1.55 chs. W. of a trail road, bears S. 20° E. and N. 20° W.
	Land, gently rolling. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, sage brush, salt brush, yucca and Mormon tea.
	From the cor. of secs. 21, 22, 27 and 28.

CHAINS	
	West, bet. secs. 21 and 28.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 21 1/4 — S 28
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located inside and near the NE portion of a dry watering hole for livestock, 462 ft. X 198 ft.
80.00	The cor. of secs. 20, 21, 28 and 29.
	Land, gently rolling and scattered sandstone rock outcrops. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, salt brush, sage brush, yucca and Mormon tea.
	N. 0°03' W., bet. secs. 20 and 21.
	Over gently rolling land.
6.25	Power line, 2 strand, bears N. 65° E. and S. 65° W.
8.00	BIA Route 20A, a graded road, 30 ft. wide, bears N. 65° E. and S. 65° W.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 21.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E 1/4
	S 20 S 21
	2013

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 16, 17, 20 and 21.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
;	T 38 N R 10 E S 17 S 16 S 20 S 21
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, salt brush, sage brush, yucca and Mormon tea.
	From the cor. of secs. 15, 16, 21 and 22.
	West, bet. secs. 16 and 21.
	Over gently rolling land.
11.10	Power line, 2 strand, bears N. 10° E. and S. 10° W.
19.15	BIA Route 20A, a graded road, 30 ft. wide, bears N. 30° E. and S. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 21.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	S 16 1/4 ——
	S 21
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

	1. John, K. To I., Gifa and Bale River Meriatan, Arizona
CHAINS	
	Set a steel fence post nearby.
80.00	The cor. of secs. 16, 17, 20 and 21.
	Land, gently rolling and sandstone rock outcrops. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, yucca and Mormon tea.
	N. 0°03' W., bet. secs. 16 and 17.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	1/4 S 17 S 16
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 8, 9, 16 and 17.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	S 8 S 9 S 17 S 16
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling and sandstone rock outcrops. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, salt brush, yucca and Mormon tea.
	From the cor. of secs. 9, 10, 15 and 16.

OTTO TATO	T. 38 N., R. 10 E., Gila and Sait River Meridian, Arizona
CHAINS	
	West, bet. secs. 9 and 16.
	Over gently rolling land.
38.05	Trail road, bears S. 30° E. and N. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 9 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	1/4
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	From this cor. point, the center line of four-way intersection of trail roads, bears N. 12° E., 2.65 chs. dist., extending N. 65° E., S. 25° E., S. 65° W. and N. 25° W.
45.35	Trail road, bears N. 65° E. and S. 65° W.
80.00	The cor. of secs. 8, 9, 16 and 17.
	Land, gently rolling. Soil, sandy loam. Timber, juniper. Undergrowth, native grasses, sage brush, salt brush, yucca and Mormon tea.
	N. 0°03' W., bet. secs. 8 and 9.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	1/4 S 8 S 9
	2013

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 4, 5, 8 and 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 5 S 4 S 8 S 9
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 46 lks. S. of a trail road, bears S. 65° E. and N. 65° W., and the same trail road curves back to the W. 2.80 chs. dist.
	Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, sage brush, yucca and Mormon tea.
	From the cor. of secs. 3, 4, 9 and 10.
	West, bet. secs. 4 and 9.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 4 1/4 —— S 9
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
66.65	Power line, 2 strand, bears S. 25° E. and N. 25° W.
80.00	The cor. of secs. 4, 5, 8 and 9.
	Land, gently rolling. Soil, sandy loam and sandstone bedrock. Timber, sparse juniper. Undergrowth, native grasses, sage brush and Mormon tea.
	N. 0°03' W., bet. secs. 4 and 5.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E 1/4 S 5 S 4
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described.
	Land, gently rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, native grasses, salt brush and sage brush.
	From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°03' W., bet. secs. 31 and 32.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	T 38 N R 10 E 1/4 S 31 S 32
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 29, 30, 31 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 30 S 29 S 31 S 32
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling. Soil, sandy loam and sandstone rock outcrops. Timber, scattered juniper. Undergrowth, native grasses, sage brush and Mormon Tea.
	From the cor. of secs. 28, 29, 32 and 33.
	West, bet. secs. 29 and 32.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 29 1/4 — S 32
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Set a steel fence post nearby.
80.00	The cor. of secs. 29, 30, 31 and 32.
	Land, gently rolling.
	Soil, sandy loam.
	Timber, scattered juniper. Undergrowth, native grasses, yucca and Mormon tea.
	West, bet. secs. 30 and 31.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 30 and 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	S 30 1/4 ———
	S 31
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
79.36	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.
	Land, gently rolling.
	Soil, sandy loam. Timber, scattered juniper.
	Undergrowth, native grasses, sage brush and Mormon tea.
	From the cor. of secs. 29, 30, 31 and 32.
	N. 0°03' W., bet. secs. 29 and 30.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	T 38 N R 10 E 1/4 S 30 S 29
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
54.60	BIA Route 20A, a graded road, 30 ft. wide, bears N. 65° E. and S. 65° W.
56.30	Power line, 2 strand, bears N. 60° E. and S. 60° W.
80.00	Point for the cor. of secs. 19, 20, 29 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 19 S 20 S 30 S 29
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling and broken. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, yucca, salt brush and Mormon tea.
	From the cor. of secs. 20, 21, 28 and 29.
	West, bet. secs. 20 and 29.
	Over gently rolling land.
13.30	Power line, 2 strand, bears N. 65° E. and S. 65° W.
18.25	BIA Route 20A, a graded road, 30 ft. wide, bears N. 60° E. and S. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 20 and 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

CHAINS 80.00	T 38 N R 10 E $\frac{\text{S 20}}{1/4} = \frac{\text{S 20}}{\text{S 29}}$ 2013 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
80.00	$1/4 \ \frac{\text{S 20}}{\text{S 29}}$ 2013 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
80.00	$1/4 \ \frac{\text{S 20}}{\text{S 29}}$ 2013 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
80.00	$1/4 \; {\text{S 29}}$ 2013 Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
80.00	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.
80.00	Set a steel fence post nearby.
80.00	
80.00	
	The cor. of secs. 19, 20, 29 and 30.
	Land, gently rolling and broken.
	Soil, sandy loam.
	Timber, scattered juniper. Undergrowth, native grasses, yucca, sage brush and Mormon tea.
	West, bet. secs. 19 and 30.
	Over gently rolling land on top of Circular White Ridge Mesa.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	S 19
	1/4
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post. $$
	Set a steel fence post nearby.
79.27	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.
	Land, gently rolling.
	Soil, sandy loam.
	Timber, scattered juniper. Undergrowth, native grasses, yucca, sage brush and Mormon tea.

	1. 56 N., R. 10 E., GIIA and Balt Rivel Melidian, Millond
CHAINS	
	From the cor. of secs. 19, 20, 29 and 30.
	N. 0°03' W., bet. secs. 19 and 20.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 19 and 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E 1/4 S 19 S 20
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
76.30	Circular White Ridge Mesa rim, 60 ft. high, bears S. 80° E. and S. 70° W.
80.00	Point for the cor. of secs. 17, 18, 19 and 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	S 18 S 17 S 19 S 20
	·
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Cor. is located in a sandstone canyon, 28 lks. W. and 56 lks. N. of wash, 10 ft. wide, 3 ft. deep, drains N. 10° E.
	Land, gently rolling and broken. Soil, sandy loam and sandstone bedrock. Timber, scattered juniper and pinon. Undergrowth, native grasses, sage brush and Mormon tea.
	From the cor. of secs. 16, 17, 20 and 21.
	West, bet. secs. 17 and 20.
	Gently ascending slope of Circular White Ridge Mesa.
	Schery abconding brope of circular white Ridge Mesa.

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
9.05	Circular White Ridge Mesa rim, 60 ft. high, bears N. 10° E. and S. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	S 17 1/4 ———
	S 20
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
71.55	Circular White Ridge Mesa rim, 40 ft. high, bears S. 5° E. and N. 10° W.
74.70	Circular White Ridge Mesa rim, 40 ft. high, bears S. 15° E. and N. 5° W.
80.00	The cor. of secs. 17, 18, 19 and 20.
	Land, gently rolling and broken. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, salt brush, sage brush and Mormon tea.
	West, bet. secs. 18 and 19.
	Ascending E. slope of Circular White Ridge Mesa.
5.90	Circular White Ridge Mesa rim, 40 ft. high, bears N. 25° E. and S. 25° W.
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	S 18 1/4 ——
	S 19
	2013

	T. 38 N., R. 10 E., Gila and Sait River Meridian, Arizona
CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
79.18	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.
	Land, broken to gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, sage brush and Mormon tea.
	From the cor. of secs. 17, 18, 19 and 20.
	N. 0°03' W., bet. secs. 17 and 18.
	Descending through canyon valley.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E
	S 18 S 17
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 1.80 chs. N. of a wash, 5 ft. wide, 5 ft. deep, drains N. 55° E.
80.00	Point for the cor. of secs. 7, 8, 17 and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 7 S 8
	S 18 S 17
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
1	

Set a steel fence post nearby. Land, gently rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, native grasses, yucca, sage brush and Mormon tea. From the cor. of secs. 8, 9, 16 and 17. West, bet. secs. 8 and 17. Over gently rolling land. Point for the 1/4 sec. cor. of secs. 8 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam. 25 ins. in the ground, with brass cap mkd. T 38 N R 10 E S 8 1/4 S 17 2013 Deposit a magnet, in a white plastic case, at the base of th stainless steel post. Set a steel fence post nearby.
Land, gently rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, native grasses, yucca, sage brush and Mormon tea. From the cor. of secs. 8, 9, 16 and 17. West, bet. secs. 8 and 17. Over gently rolling land. Point for the 1/4 sec. cor. of secs. 8 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam. 25 ins. in the ground, with brass cap mkd. T 38 N R 10 E S 8 1/4 — S 17 2013 Deposit a magnet, in a white plastic case, at the base of th stainless steel post.
Soil, sandy loam. Timber, sparse juniper. Undergrowth, native grasses, yucca, sage brush and Mormon tea. From the cor. of secs. 8, 9, 16 and 17. West, bet. secs. 8 and 17. Over gently rolling land. Point for the 1/4 sec. cor. of secs. 8 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam. 25 ins. in the ground, with brass cap mkd. T 38 N R 10 E S 8 1/4 S 17 2013 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
West, bet. secs. 8 and 17. Over gently rolling land. 40.00 Point for the 1/4 sec. cor. of secs. 8 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam. 25 ins. in the ground, with brass cap mkd. T 38 N R 10 E S 8 1/4 — S 17 2013 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
Over gently rolling land. 40.00 Point for the 1/4 sec. cor. of secs. 8 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam. 25 ins. in the ground, with brass cap mkd. T 38 N R 10 E S 8 1/4 — S 17 2013 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
Point for the 1/4 sec. cor. of secs. 8 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam. 25 ins. in the ground, with brass cap mkd. T 38 N R 10 E S 8 1/4 — S 17 2013 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam. 25 ins. in the ground, with brass cap mkd.
25 ins. in the ground, with brass cap mkd.
$\frac{\text{S 8}}{1/4} \frac{\text{S 17}}{\text{S 17}}$ 2013 Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
Set a steel fence post nearby.
Cor. is located 1.15 chs. E. of a wash, 8 ft. wide, 4 ft. deep, drains N. 60° E.
47.45 Circular White Ridge Mesa rim, 80 ft. high, bears N. and S. 20° W.
50.60 Circular White Ridge Mesa rim, 80 ft. high, bears N. 5° E. and S. 15° W.
60.35 Circular White Ridge Mesa rim, 60 ft. high, bears N. 20° E. and S. 10° W.
71.35 Top of Circular White Ridge Mesa rim, 70 ft. high, bears N. 15° E. and S. 5° E.
72.65 Base of Circular White Ridge Mesa rim, 70 ft. high, bears N. and S. 15° E.
80.00 The cor. of secs. 7, 8, 17 and 18.
Land, gently rolling and broken.

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, salt brush, yucca and Mormon tea.
	West, bet. secs. 7 and 18.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 18.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in solid sandstone bedrock, with brass cap mkd.
	T 38 N R 10 E S 7 1/4 —— S 18
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
53.10	Base of Circular White Ridge Mesa rim, 60 ft. high, bears N. 50° E. and S. 50° W.
55.55	Top of Circular White Ridge Mesa rim, 60 ft. high, bears N. 20° E. and S. 25° W.
79.09	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.
	Land, gently rolling to broken. Soil, sandy loam and sandstone bedrock. Timber, pinon and juniper. Undergrowth, native grasses, yucca, sage brush and Mormon tea.
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0°03' W., bet. secs. 7 and 8.
	Gently rolling, through canyon valley.
40.00	Point for the 1/4 sec. cor. of secs. 7 and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	T 38 N R 10 E
	1/4 S 7 S 8
	2012
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
69.15	Base of Circular White Ridge Mesa rim, 60 ft. high, bears N. 50° E. and S. 80° W.
71.05	Top of Circular White Ridge Mesa rim, 60 ft. high, bears N. 50° E. and S. 60° W.
80.00	Point for the cor. of secs. 5, 6, 7 and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 6 S 5 S 7 S 8
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Land, gently rolling and broken. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, sage brush, yucca and Mormon tea.
	From the cor. of secs. 4, 5, 8 and 9.
	West, bet. secs. 5 and 8.
	Over gently rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	m 20 M D 10 H
	T 38 N R 10 E S 5
	1/4 ——
	S 8
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
73.10	Base of Circular White Ridge Mesa rim, 60 ft. high, bears N. 35° E. and S. 20° W.
75.45	Top of Circular White Ridge Mesa rim, 60 ft. high, bears N. 30° E. and S. 20° W.
80.00	The cor. of secs. 5, 6, 7 and 8.
	Land, gently rolling and broken. Soil, sandy loam. Timber, scattered juniper. Undergrowth, native grasses, sage brush, yucca and Mormon tea.
	West, bet. secs. 6 and 7.
	On top of Circular White Ridge Mesa, over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E S 6 1/4 — S 7
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 95.6 lks. W. of a trail road, bears S. and N. 10° W.
79.00	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.

G113 7310	
CHAINS	
	Land, rolling.
	Soil, sandy loam.
	Timber, juniper.
	Undergrowth, native grasses, yucca, cholla grass, sage brush and Mormon tea.
	Mornion tea.
	From the cor. of secs. 5, 6, 7 and 8.
	N. 0°03' W., bet. secs. 5 and 6.
	Over gently rolling land.
5.80	Top of Circular White Ridge Mesa rim, 70 ft. high, bears E. and W.
7.40	Base of Circular White Ridge Mesa rim, 70 ft. high, bears
7.40	S. 75° E. and S. 45° W.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 6.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	25 ins. in the ground, with brass cap mkd.
	*
	T 38 N R 10 E
	1/4 S 6 S 5
	2013
	Denogit a magnet in a white plactic case at the hage of the
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	bearinged beeer peser
	Set a steel fence post nearby.
80.00	The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp.,
00.00	hereinbefore described.
	Land, broken to gently rolling.
	Soil, sandy loam.
	Timber, juniper. Undergrowth, native grasses, yucca, sage brush and Mormon tea.
	ondergrowth, hative grasses, yucca, sage brush and Mormon tea.
	Subdivision of Section 1,
	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 1 and 12.
	North, on the N. and S. center line of sec. 1.
	Noten, on the N. and S. tenter line of Sec. 1.
	Over gently rolling land.

Subdivision of Section 1, T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHATIVS	
40.00	Point for the center 1/4 sec. cor. of sec. 1, at intersection with the E. and W. center line sec. 1.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E C 1/4 S 1
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
50.00	Trail road, bears N. 80° E. and S. 80° W.
80.00	The 1/4 sec. cor. of secs. 1 and 36, on the N. bdy. of the Tp.
	From the $1/4$ sec. cor. of secs. 1 and 6, on the E. bdy. of t Tp.
	West, on the E. and W. center line of sec. 1.
	Over gently rolling land.
34.20	Trail road, bears S. 10° E. and N. 10° W.
40.00	The center 1/4 sec. cor. of sec. 1.
53.15	Bladed road, 20 ft. wide, bears N. 20° E. and S. 20° W.
55.85	Barbed wire fence, 4 strand, bears N. 5° E. and S. 5° W.
63.65	E. right-of-way fence of State Highway 98, barbed wir 4 strand, parallels highway.
65.30	State Highway 98, an asphalt surfaced road, 35 ft. wide, bea S. 25° E. and N. 25° W.
66.95	W. right-of-way fence of State Highway 98, barbed wir 4 strand, parallels highway.
70.30	Trail road, bears S. 20° E. and N. 20° W.
70.90	Trail road, bears N. 10° E. and S. 10° W.
70.70	

Subdivision of Section 2, T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona

	T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
CHAINS	
	From the 1/4 sec. cor. of secs. 2 and 11.
	N. 0°01' W., on the N. and S. center line of sec. 2.
	Over gently rolling land.
40.00	Point for the center 1/4 sec. cor. of sec. 2, at intersection with the E. and W. center line sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E C 1/4 S 2
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set two steel fence posts NE and SW of cor. as a guard post against traffic on trail road.
	Cor. is located in the SW edge of a trail road, bears S. 40° E. and N. 40° W.
80.00	The 1/4 sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp.
	From the 1/4 sec. cor. of secs. 1 and 2.
	West, on the E. and W. center line of sec. 2.
	Over gently rolling land.
40.00	The center 1/4 sec. cor. of sec. 2.
80.00	The 1/4 sec. cor. of secs. 2 and 3.
	Subdivision of Section 12, T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 12 and 13.
	North, on the N. and S. center line of sec. 12.
	Over gently rolling land.
35.55	Trail road, bears S. 50° E. and N. 50° W.

Subdivision of Section 12, T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS 40.00	Point for the center 1/4 sec. cor. of sec. 12, at intersection with the E. and W. center line sec. 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E C 1/4 S 12
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
62.36	W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
65.96	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 25° E. and N. 25° W.
66.75	From this point, a right-of-way monument, bears W., 2.06 chs. dist., monumented with a brass tablet, 2 1/2 ins. diam., set flush in a concrete cylinder, 6 ins. diam., firmly set along W. right-of-way fence, projecting 7 ins. above ground, mkd. BIA ROADS 1969.
68.03	From this point, a right-of-way monument, bears E., 68.3 lks. dist., monumented with a brass tablet, 2 1/2 ins. diam., set flush in a concrete cylinder, 6 ins. diam., firmly set along E. right-of-way fence, projecting 5 ins. above ground, mkd. BIA ROADS 1969, with an angle iron, firmly set nearby, faintly mkd. 00+69.01 HWY R of W.
69.47	E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
80.00	The 1/4 sec. cor. of secs. 1 and 12.
	From the 1/4 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp.
	West, on the E. and W. center line of sec. 12.
	Over gently rolling land.
26.22	E. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
27.85	State Highway 98, an asphalt surfaced road, 35 ft. wide, bears S. 25° E. and N. 25° W.

Subdivision of Section 12, T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona

O112 T220	1. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
29.53	W. right-of-way fence of State Highway 98, barbed wire, 4 strand, parallels highway.
40.00	The center 1/4 sec. cor. of sec. 12.
45.55	Trail road, bears S. 50° E. and N. 50° W.
56.90	Trail road, bears N. 25° E. and S. 25° W.
80.00	The 1/4 sec. cor. of secs. 11 and 12.
	Subdivision of Section 13, T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 13 and 24.
	North, on the N. and S. center line of sec. 13.
	Over gently rolling land.
40.00	Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E. and W. center line sec. 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 38 N R 10 E C 1/4 S 13
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The 1/4 sec. cor. of secs. 12 and 13.
	From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.
	West, on the E. and W. center line of sec. 13.
	Over gently rolling land.
40.00	The center 1/4 sec. cor. of sec. 13.
80.00	The 1/4 sec. cor. of secs. 13 and 14.

T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The area surveyed is within the Navajo Indian Reservation, is 18 miles northwest of the Kaibeto community, 16 miles southeast of the Lechee community, and 19 miles southeast of Page, Arizona. Primary access is graded road BIA Route 20A, by way of State Highway 98. A series of trail roads provide access throughout the township. ATV's were required to access the majority of the areas within the township.

There are no major housing developments, only smaller housing clusters and single home units scattered throughout the township. The Black Mesa and Lake Powell Railroad that supplies coal to the Navajo power plant in Page, meanders through the east half of the township.

The highest elevation of this survey, 6100 feet above sea level, is one-third of township near the west boundary, atop Circular White Ridge Mesa. The lowest elevation, at 5500 feet is in the open valley between the mesa plateau in the northeast, and Circular White Ridge Mesa, decreasing in elevation toward the northern portion of the township.

The vegetation consists of scattered juniper throughout the township and sparse pinon in the higher elevation. Sage brush, salt brush, yucca, rabbit brush, Mormon tea and native grasses, are more prominent throughout the township. There is presence of grazing cattle, sheep and horses in the area. The soil is mostly sandy loam with scattered sandstone rock outcrops, and sandstone mesas in the west and eastern portion of the township.

The mean magnetic declination of 11° E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2010-2005 for the dates of survey.

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

TILLED AUGUSTANTIS	
NAMES	CAPACITY
Mark R. Searles	Surveying Technician
Daniel Bryan	Engineering Technician
Byron Shorty	Engineering Technician
Kevin Tso	Engineering Technician

CERTIFICATE OF SURVEY

I, Fabian Yazzie, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 15th day of November, 2012, I have surveyed the South, West, and North boundaries, the subdivisional lines, and the subdivision of certain sections, T. 38 N., R. 10 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and in specific manner described in the foregoing field notes.

7/24/2013 (Cadagtija) Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Phoenix, Arizona

The foregoing field notes of the survey of the South, West, and North boundaries, and the subdivisional lines, and the subdivision of certain sections, T. 38 N., R. 10 E., Gila and Salt River Meridian, in the State of Arizona, executed by Fabian Yazzie, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

(Chief Cadastral Surveyor of Arizona)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 38 N., R. 10 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.

(Chief Cadastral Surveyor of Arizona)