

ORIGINAL

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
SURVEY OF A PORTION OF THE NINTH STANDARD PARALLEL NORTH (SOUTH BOUNDARY) ,  
SURVEY OF A PORTION OF THE SECOND GUIDE MERIDIAN EAST (WEST BOUNDARY) ,  
THE EAST AND NORTH BOUNDARIES  
AND THE  
THE SUBIVISIONAL LINES  
AND  
SUBDIVISION OF CERTAIN SECTIONS  
**TOWNSHIP 37 NORTH, RANGE 9 EAST,**  
OF THE GILA AND SALT RIVER MERIDIAN,  
IN THE STATE OF ARIZONA.

**EXECUTED BY**

**Blas J. Urena, Cadastral Surveyor**

Under Special Instructions dated July 31, 2013, approved July 31, 2013, which provided for the surveys included under Group No. 1121, and assignment instructions dated July 31, 2013.

**Survey commenced July 25, 2013**

**Survey completed September 18, 2013**

# INDEX DIAGRAM

TOWNSHIP 37 NORTH                      RANGE 09 EAST  
 GILA & SALT RIVER MERIDIAN, ARIZONA

25	24	23	22	21	20
14    6	74    5	60    4	50    3	41    2	33    1    20
73	72	59	49	41	33
13    7	71    8	58    9	48    10	40    11	32    12    19
70	69	57	48	39	31
12    18	68    17	56    16	47    15	39    14	30    13    18
67	67	55	46	38	30
11    19	66    20	54    21	45    22	37    23	29    24    17
65	64	53	44	36	28
11    30	64    29	52    28	44    27	36    26	28    25    16
62	62	51	43	35	27
10    31	61    32	51    33	42    34	34    35	26    36    15
9	8	7	6	5	4

Subdivision of Section 4 ..... Pages 74-75  
 Subdivision of Section 5 ..... Pages 75-76  
 Subdivision of Section 9 ..... Pages 76-78  
 Subdivision of Section 16 ..... Pages 78-79  
 Subdivision of Section 21 ..... Pages 79-80  
 Subdivision of Section 22 ..... Pages 80-81  
 Subdivision of Section 27 ..... Pages 81-82  
 Subdivision of Section 34 ..... Pages 82-83  
 Subdivision of Section 35 ..... Pages 83-84

## T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the survey of a portion of the Ninth Standard Parallel North (South Boundary), a portion of the Second Guide Meridian East (West Boundary), the East and North boundaries, and the subdivisional lines, and the subdivision of certain sections, Township 37 North, Range 9 East, Gila and Salt River Meridian, Arizona.

The history of surveys pertaining to this survey is as follows:

Leonard R. Sandoval established the standard corner of Townships 37 North, Ranges 8 and 9 East, on the Ninth Standard Parallel North and the true point for the southwest corner of Township 40 North, Range 9 East, on the Second Guide Meridian East, under Group No. 950, in 2005. Joe R. Salazar established the closing corner of Townships 36 North, Ranges 8 and 9 East, on the Ninth Standard Parallel North, in a plat only survey, under Group No. 1059, in 2009. Fabian Yazzie established the corner of Townships 37 and 38 North, Ranges 9 and 10 East, and established the standard corner of Townships 37 North, Ranges 9 and 10 East, on the Ninth Standard Parallel North, under Group No. 1114, in 2012-2013. John F. Hesse, U. S. Mineral Surveyor, surveyed Mineral Surveys 2757, 2758, 2759, 2760, 2761, 2762, and 2763, in 1910.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and the Special Instructions dated July 31, 2013, for Group Number 1121, Arizona.

The true meridian direction and length of all lines were determined by real time kinematic global positioning system observations using Trimble Navigation R8 and 5700 model receivers.

Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) AI8805 FRED FREDONIA CORS ARP, DI2245 P011 SPIDERROCKAZ2005 CORS ARP, and DL1882 AZFL NAU FLAGSTAFF CORS ARP. The NAD 83 (2011) (EPOCH: 2010.0000), geographic position of the corner of Townships 37 North, Ranges 9 and 10 East, is as follows:

Latitude: 36°33'19.635" N.                      Longitude: 111°22'15.365" W.

The geographic position of the corner of Townships 37 and 38 North, Ranges 8 and 9 East, is as follows:

Latitude: 36°38'32.795" N.                      Longitude: 111°28'43.533" W.

The mean magnetic declination is 11° E.

---

Survey of a Portion of the Ninth Standard Parallel North(South Boundary),  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Beginning at the stan. cor. of Tps. 37 N., Rs. 9 and 10 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. SC T37N R9E R10E S36 S31 T36N R9E S1 2012.</p> <p>Add the marks 2013 to the brass cap.</p> <p>West, along the S. bdy. of sec. 36.</p> <p>Over rolling to broken to rolling land.</p> <p>40.00 Point for the stan. 1/4 sec. cor. of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 37 N R 9 E 1/4 S 36 -----</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the stan. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T 37 N R 9 E S 35   S 36 -----</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, rolling to broken to rolling. Soil, sandy loam and scattered sandstone rock outcrops. Timber, scattered juniper. Undergrowth, sage and native grasses.</p> <hr/>

Survey of a Portion of the Ninth Standard Parallel North(South Boundary),  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	West, along the S. bdy. of sec. 35.
	Over rolling land.
17.95	Underground water line, bears N. 60° E. and S. 60° W.
18.40	Barbed wire fence, 5 strand, bears N. 60° E. and S. 60° W.
40.00	Point for the stan. 1/4 sec. cor. of sec. 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">SC T 37 N R 9 E 1/4 S 35</p> <hr style="width: 10%; margin: auto;"/>
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
47.48	Barbed wire fence, 5 strand, bears N. and S.
76.60	Underground water line, bears S. 15° E. and N. 15° W.
77.04	E. right-of-way fence of BIA Route N20, barbed wire, 5 strand, parallels highway.
78.70	BIA Route N20, asphalt surfaced, 33 ft. wide, bears S. 10° E. and N. 10° W.
80.00	Point for the stan. cor. of secs. 34 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, to bedrock, in a mound of stone, 2 1/2 ft. base, to top of brass cap mkd.
	<p style="text-align: center;">SC T 37 N R 9 E S 34   S 35</p> <hr style="width: 10%; margin: auto;"/>
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	Cor. is located 2 lks. E. of W. right-of-way fence of BIA Route N20, barbed wire, 5 strand, bears S. 10° E. and N. 10° W.

Survey of a Portion of the Ninth Standard Parallel North (South Boundary),  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, sage brush and native grasses.</p> <hr/>
	<p>West, along the S. bdy. of sec. 34.</p>
	<p>Over rolling land.</p>
40.00	<p>Point for the stan. 1/4 sec. cor. of sec. 34.</p>
	<p>Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in a drill hole, in solid sandstone bedrock, with top mkd.</p>
	<p style="text-align: center;">SC T 37 N R 9 E 1/4 S 34</p> <hr style="width: 10%; margin: auto;"/>
	<p style="text-align: center;">2013</p>
	<p>Deposit fragment of a magnet in the drill hole.</p>
	<p>Raise a mound of stone, 3 ft. base, 1.5 ft. high, North of the cor.</p>
80.00	<p>Point for the stan. cor. of secs. 33 and 34.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T 37 N R 9 E S 33   S 34</p> <hr style="width: 10%; margin: auto;"/>
	<p style="text-align: center;">2013</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
	<p>Set a steel fence post nearby.</p>
	<p>Land, rolling. Soil, sandy loam and scattered sandstone rock outcrops. Timber, scattered juniper. Undergrowth, sage brush and native grasses.</p> <hr/>

Survey of a Portion of the Ninth Standard Parallel North(South Boundary),  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>West, along the S. bdy. of sec. 33.</p> <p>Over rolling land.</p>
40.00	<p>Point for the stan. 1/4 sec. cor. of sec. 33.</p> <p>Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in a drill hole, in solid sandstone bedrock, with top mkd.</p>
	<p style="text-align: center;">SC T 37 N R 9 E <u>1/4 S 33</u></p> <p style="text-align: center;">2013</p>
	<p>Deposit fragment of a magnet in the drill hole.</p> <p>Set a steel fence post nearby.</p> <p>From this cor. point, Dove Spring Water Well, bears N. 69°52' E., 11.05 chs. dist.</p>
49.90	<p>Power line, 4 strand, bears S. 25° E. and N. 25° W.</p>
58.30	<p>High voltage transmission line, 5 strand, bears S. 15° E. and N. 15° W.</p>
63.70	<p>High voltage transmission line, 8 strand, bears S. 10° E. and N. 10° W.</p>
65.65	<p>High voltage transmission line, 8 strand, bears S. 10° E. and N. 10° W.</p>
80.00	<p>Point for the stan. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T 37 N R 9 E <u>S 32   S 33</u></p> <p style="text-align: center;">2013</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>

Survey of a Portion of the Ninth Standard Parallel North(South Boundary),  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy loam and scattered sandstone rock outcrops. Timber, scattered juniper. Undergrowth, sage brush and native grasses.</p> <hr/>
40.00	<p>West, along the S. bdy. of sec. 32.</p> <p>Over rolling to broken to rolling land. Point for the stan. 1/4 sec. cor. of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T 37 N R 9 E 1/4 S 32</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">2013</p>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
	<p>Point for the stan. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T 37 N R 9 E S 31   S 32</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">2013</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, rolling to broken to rolling. Soil, sandy loam and scattered sandstone rock outcrops. Timber, scattered juniper and piñon. Undergrowth, sage brush and native grasses.</p> <hr/>

Survey of a Portion of the Ninth Standard Parallel North(South Boundary),  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>West, along the S. bdy. of sec. 31.</p> <p>Over rolling land.</p> <p>6.70 High voltage transmission line, 8 strand, bears S. 5° E. and N. 5° W.</p> <p>40.00 Point for the stan. 1/4 sec. cor. of sec. 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a mound of stone, 3 ft. base, to top of brass cap mkd.</p> <p style="text-align: center;">SC T 37 N R 9 E 1/4 S 31 ----- 2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>66.74 The closing cor. of Tps. 36 N., Rs. 8 and 9 E. at the intersection of the Second Guide Meridian East with the Ninth Standard Parallel North, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. T37N R9E S31 S1 S6 R8E R9E T36N 2009 2010 2012.</p> <p>Add the marks 2013 to the brass cap.</p> <p>from which</p> <p style="padding-left: 40px;">A reference monument, a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, bears S. 60°17' E., 939.9 ft. dist. (Record S. 60°18' E., 940.0 ft. dist.), with brass cap mkd. RM T36N R9E S6 940.0 FT TO COR 2009 2010 and an arrow point to the cor. Add the marks 2013 to the brass cap.</p> <p style="padding-left: 40px;">A reference monument, a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, bears N. 7°30' W., 25.0 ft. dist. (Record N. 7°13' W.), with brass cap mkd. RM T37N R9E S31 25.0 FT TO COR 2009 2010 and an arrow point to the cor. Add the marks 2013 to the brass cap.</p> <p>80.00 The stan. cor. of Tps. 37 N., Rs. 8 and 9 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. SC T37N R8E R9E S36 S31 2005 2010, with a steel fence post nearby.</p>
--------	---

**Survey of a Portion of the Ninth Standard Parallel North (South Boundary),  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS

Add the marks 2013 to brass cap.

Land, rolling.

Soil, sandy loam.

Timber, scattered juniper and piñon.

Undergrowth, sage brush and native grasses.

**Survey of a Portion of the Second Guide Meridian East  
(West Boundary),  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona**

From the stan. cor. of Tps. 37 N., Rs. 8 and 9 E., hereinbefore described.

North bet. secs. 31 and 36.

Over rolling land.

40.00 Point for the 1/4 sec. cor. of secs. 31 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	T 37 N	
	R 8 E	R 9 E
	1/4	
S 36		S 31

2013

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

80.00 Point for the cor. of secs. 25, 30, 31, and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	T 37 N	
R 8 E		R 9 E
S 25		S 30
S 36		S 31

2013

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Survey of a Portion of the Second Guide Meridian East (West Boundary),  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Land, rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>North, bet. secs. 25 and 30.</p> <p>Over rolling land.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, in a supporting mound of stone, 3 1/2 ft. base, to top of brass cap mkd.</p> <div style="text-align: center;"> <p>T 37 N R 8 E   R 9 E 1/4 S 25   S 30</p> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 19, 24, 25, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 37 N R 8 E   R 9 E S 24   S 19 S 25   S 30</p> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>North, bet. secs. 19 and 24.</p> <p>Over rolling land.</p> <p>39.10 Track road, bears S. 75° E. and N. 75° W.</p>
--------	--

Survey of a Portion of the Second Guide Meridian East (West Boundary),  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 37 N R 8 E R 9 E 1/4 S 24   S 19 2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 37 N R 8 E   R 9 E S 13   S 18 S 24   S 19 2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Timber, juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>North, bet. secs. 13 and 18.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, to sandstone bedrock, in a supporting mound of stone, 3 ft. base, to top of brass cap mkd.</p>

Survey of a Portion of the Second Guide Meridian East (West Boundary),  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">T 37 N R 8 E R 9 E 1/4 S 13   S 18  2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>80.00 Point for the cor. of secs. 7, 12, 13, and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 8 E   R 9 E S 12   S 7 S 13   S 18  2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, rolling. Soil, sandy loam and scattered sandstone rock outcrops. Timber, sparse juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>North, bet. secs. 7 and 12.</p> <p>Over rolling land.</p> <p>10.35 Underground water line, bears N. 40° E. and S. 40° W.</p> <p>13.40 Power line, 2 strand, bears N. 80° E. and S. 80° W.</p> <p>29.77 BIA Route N6210, a graded road, 27 ft. wide, bears N 45° E. and S. 40° W.</p> <p>39.15 Track road, bears S. 35° E. and N. 35° W.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
--------	---

Survey of a Portion of the Second Guide Meridian East (West Boundary),  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 37 N R 8 E R 9 E 1/4 S 12   S 7 2013</p>
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
40.00	<p style="text-align: center;">T 37 N R 8 E   R 9 E S 1   S 6 S 12   S 7 2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over rolling land.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
80.00	<p style="text-align: center;">T 37 N R 8 E R 9 E 1/4 S 1   S 6 2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Point for the cor. of secs. 1, 6, 31, and 36.</p>

**Survey of a Portion of the Second Guide Meridian East (West Boundary),  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS

Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in a drill hole, in sandstone outcropping, with top mkd.

T 38 N	
R 8 E	R 9 E
S 36	S 31
S 1	S 6
T 37 N	

2013

Deposit fragment of a magnet in the drill hole.

From this cor. point, the true point cor. of Tps. 39 and 40 N., Rs. 8 and 9 E., bears North, 960.00chs. dist., from this true point, a witness cor. of Tps. 39 and 40 N., Rs. 8 and 9 E., bears N 24°00' E., 50 lks. dist., monumented with a brass tablet, 3 1/4 ins. cemented in sandstone bedrock, mkd WC T40N R8E R9E S36 S31 S1 S6 T39 N 2005 and an arrow point to the true point. Add the marks 2013 to brass tablet.

From this same cor. point, the cor. of Tps. 37 and 38 N., Rs. 9 and 10 E., bears East, 479.46 chs. dist., hereinafter described.

Land, rolling.

Soil, sandy loam and scattered sandstone rock outcrops.

Timber, sparse juniper.

Undergrowth, sage brush and native grasses.

---

**Survey of the East Boundary,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona**

---

From the stan. cor. of Tps. 37 N., Rs. 9 and 10 E., hereinbefore described.

North, bet. secs. 31 and 36.

Over rolling land.

40.00 Point for the 1/4 sec. cor. of secs. 31 and 36.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 37 N	
R 9 E	R 10 E
1/4	
S 36	S 31

2013

Survey of the East Boundary,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>								
60.21	Barbed wire fence, 5 strand, bears N. 60° E. and S. 60° W.								
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 37 N</td></tr> <tr><td>R 9 E</td><td>R 10 E</td></tr> <tr><td>S 25</td><td>S 30</td></tr> <tr><td>S 36</td><td>S 31</td></tr> </table> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, sage brush and native grasses.</p> <hr/> <p>North, bet. secs. 25 and 30.</p> <p>Over rolling land.</p>	T 37 N		R 9 E	R 10 E	S 25	S 30	S 36	S 31
T 37 N									
R 9 E	R 10 E								
S 25	S 30								
S 36	S 31								
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T 37 N</td></tr> <tr><td>R 9 E</td><td>R 10 E</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>S 25</td><td>S 30</td></tr> </table> <p>2013</p> </div>	T 37 N		R 9 E	R 10 E	1/4		S 25	S 30
T 37 N									
R 9 E	R 10 E								
1/4									
S 25	S 30								
80.00	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Point for the cor. of secs. 19, 24, 25, and 30.</p>								

Survey of the East Boundary,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS									
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 37 N</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R 9 E</td><td style="padding: 0 5px;">R 10 E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 24</td><td style="padding: 0 5px;">S 19</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 25</td><td style="padding: 0 5px;">S 30</td></tr> </table> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, rolling. Soil, sandy loam and scattered sandstone rock outcrops. Timber, scattered juniper. Undergrowth, sage brush and native grasses.</p> <hr style="width: 60%; margin: 20px auto;"/> <p>North, bet. secs. 19 and 24.</p> <p>Over rolling land.</p>	T 37 N		R 9 E	R 10 E	S 24	S 19	S 25	S 30
T 37 N									
R 9 E	R 10 E								
S 24	S 19								
S 25	S 30								
27.25	<p>Barbed wire fence, 4 strand, bears N. 15° E. and S. 15° W.</p>								
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T 37 N</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R 9 E</td><td style="padding: 0 5px;">R 10 E</td></tr> <tr><td colspan="2" style="text-align: center; padding: 0 5px;">1/4</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S 24</td><td style="padding: 0 5px;">S 19</td></tr> </table> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>	T 37 N		R 9 E	R 10 E	1/4		S 24	S 19
T 37 N									
R 9 E	R 10 E								
1/4									
S 24	S 19								
80.00	<p>Point for the cor. of secs. 13, 18, 19, and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								

Survey of the East Boundary,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS

T 37 N	
R 9 E	R 10 E
S 13	S 18
S 24	S 19

2013

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

Land, rolling.

Soil, sandy loam and scattered sandstone rock outcrops.

Timber, scattered juniper.

Undergrowth, sage brush and native grasses.

North, bet. secs. 13 and 18.

Over rolling land.

40.00 Point for the 1/4 sec. cor. of secs. 13 and 18.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 37 N	
R 9 E	R 10 E
1/4	
S 13	S 18

2013

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Set a steel fence post nearby.

80.00 Point for the cor. of secs. 7, 12, 13, and 18.

Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in a drill hole, in solid limestone bedrock, with top mkd.

T 37 N	
R 9 E	R 10 E
S 12	S 7
S 13	S 18

2013

Deposit fragment of a magnet in the drill hole.

Survey of the East Boundary,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, NW of the corner.</p> <p>Land, rolling. Soil, sandy loam, scattered sandstone, and limestone rock outcrops. Timber, scattered juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>North, bet. secs. 7 and 12.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 37 N R 9 E R 10 E 1/4 S 12   S 7 2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 1, 6, 7, and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 37 N R 9 E   R 10 E S 1   S 6 S 12   S 7 2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>

**Survey of the East Boundary,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Land, rolling. Soil, sandy loam and scattered sandstone rock outcrops. Timber, scattered juniper and piñon. Undergrowth, sage brush and native grasses.</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 6.</p> <div style="text-align: center;"> <p>T 37 N R 9 E R 10 E 1/4 S 1   S 6 2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>The cor. of Tps. 37 and 38 N., Rs. 9 and 10 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. T38N R9E R10E S36 S31 S1 S6 T37N 2012. With a steel fence post nearby.</p> <p>Add the marks 2013 to the brass cap</p> <p>Land, rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p style="text-align: center;"><b>Survey of the North Boundary, T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the cor. of Tps. 37 and 38 N., Rs. 9 and 10 E., hereinbefore described.</p> <p>West, bet. secs. 1 and 36.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, underpinned with a steel fence post, 5 1/2 ft. long, 66 ins. in the ground, with brass cap mkd.</p>

Survey of the North Boundary,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 38 N R 9 E S 36 1/4 ——— S 1 T 37 N  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 1, 2, 35, and 36.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 9 E S 35   S 36 S 2   S 1 T 37 N  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Land, rolling and broken. Soil, sandy loam. Timber, sparse juniper. Undergrowth, sage brush and native grasses.
	<hr/> West, bet. secs. 2 and 35.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 35.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 38 N R 9 E S 35 1/4 ——— S 2 T 37 N  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Survey of the North Boundary,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS											
73.25	Power line, 2 strand, bears N. and S.										
80.00	Point for the cor. of secs. 2, 3, 34, and 35.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 38 N</td><td>R 9 E</td></tr> <tr><td>S 34</td><td>S 35</td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td colspan="2">T 37 N</td></tr> </table> <p>2013</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, sage brush and native grasses.  <hr/> West, bet. secs. 3 and 34.  Over rolling and broken land.	T 38 N	R 9 E	S 34	S 35	S 3	S 2	T 37 N			
T 38 N	R 9 E										
S 34	S 35										
S 3	S 2										
T 37 N											
31.65	BIA Route N201, a graded road, 18 ft. wide, bears N 20° E. and S. 20° W.										
40.00	Point for the 1/4 sec. cor. of secs. 3 and 34.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T 38 N</td><td>R 9 E</td></tr> <tr><td>S 34</td><td></td></tr> <tr><td>1/4</td><td>_____</td></tr> <tr><td>S 3</td><td></td></tr> <tr><td colspan="2">T 37 N</td></tr> </table> <p>2013</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.	T 38 N	R 9 E	S 34		1/4	_____	S 3		T 37 N	
T 38 N	R 9 E										
S 34											
1/4	_____										
S 3											
T 37 N											
80.00	Point for the cor. of secs. 3, 4, 33, and 34.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.										

Survey of the North Boundary,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	<table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 10px;">T 38 N</td> <td style="padding: 2px 10px;">R 9 E</td> </tr> <tr> <td style="padding: 2px 10px; border-right: 1px solid black;">S 33</td> <td style="padding: 2px 10px;">S 34</td> </tr> <tr> <td style="padding: 2px 10px; border-right: 1px solid black;">S 4</td> <td style="padding: 2px 10px;">S 3</td> </tr> <tr> <td colspan="2" style="padding: 2px 10px;">T 37 N</td> </tr> </table> <p style="margin-top: 5px;">2013</p>	T 38 N	R 9 E	S 33	S 34	S 4	S 3	T 37 N			
T 38 N	R 9 E										
S 33	S 34										
S 4	S 3										
T 37 N											
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling and broken. Soil, sandy loam. Timber, sparse juniper. Undergrowth, sage brush and native grasses.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>West, bet. secs. 4 and 33.</p> <p>Over rolling and broken land.</p>										
1.55	High voltage transmission line, 8 strand, bears N. 5° E. and S. 5° W.										
3.50	High voltage transmission line, 8 strand, bears N. 5° E. and S. 5° W.										
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 10px;">T 38 N</td> <td style="padding: 2px 10px;">R 9 E</td> </tr> <tr> <td colspan="2" style="padding: 2px 10px;">S 33</td> </tr> <tr> <td colspan="2" style="padding: 2px 10px;">1/4 ———</td> </tr> <tr> <td colspan="2" style="padding: 2px 10px;">S 4</td> </tr> <tr> <td colspan="2" style="padding: 2px 10px;">T 37 N</td> </tr> </table> <p style="margin-top: 5px;">2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>	T 38 N	R 9 E	S 33		1/4 ———		S 4		T 37 N	
T 38 N	R 9 E										
S 33											
1/4 ———											
S 4											
T 37 N											
40.25	Dirt road, 10 ft. wide, bears S. 15° E. and N. 15° W.										
41.00	Underground water line, bears S. 30° E. and N. 30° W.										
41.65	Power line, 2 strand, bears S. 10° E. and N. 10° W.										
60.65	High voltage transmission line, 5 strand, bears N. and S.										

**Survey of the North Boundary,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS									
66.27	E. right-of-way fence of BIA Route N20, barbed wire, 5 strand, parallels highway.								
67.79	BIA Route N20, asphalt surfaced, 33 ft. wide, bears N. 10° E. and S. 10° W.								
69.27	W. right-of-way fence of BIA Route N20, barbed wire, 5 strand, parallels highway.								
79.80	Dirt road, 10 ft. wide, along a curve, concave to the N.								
80.00	Point for the cor. of secs. 4, 5, 32, and 33.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of the ground, with brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 38 N</td> <td>R 9 E</td> </tr> <tr> <td>S 32</td> <td>S 33</td> </tr> <tr> <td>S 5</td> <td>S 4</td> </tr> <tr> <td colspan="2" style="text-align: center;">T 37 N</td> </tr> </table> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Cor. is located on the S. edge of a dirt road, 10 ft. wide, along a curve, concave to the N.</p> <p>From this cor. point, a steel water valve, 9 ins. diam., bears N 28°08' E., 1.04 chs. dist.</p> <p>From this same cor. point, the NE cor. of a wood frame dwelling, bears N 38°13' W., 1.11 chs. dist.</p> <p>From this same cor. point, the SE cor. of the same dwelling, bears N 68°23' W., 74 lks. dist.</p> <p>Land, rolling and broken. Soil, sandy loam. Timber, sparse juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>West, bet. secs. 5 and 32.</p> <p>Over rolling land.</p>	T 38 N	R 9 E	S 32	S 33	S 5	S 4	T 37 N	
T 38 N	R 9 E								
S 32	S 33								
S 5	S 4								
T 37 N									
1.00	Power line, 1 strand, bears N. 35° E. and S. 35° W.								
1.15	Power line, 1 strand, bears N. and S.								
11.40	Power line, 2 strand, bears S. 10° E. and N. 10° W.								

Survey of the North Boundary,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 38 N R 9 E S 32 1/4 — S 5 T 37 N</p> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 31, and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 38 N R 9 E S 31   S 32 S 6   S 5 T 37 N</p> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Land, rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>West, bet. secs. 6 and 31.</p> <p>Over rolling land.</p>
0.85	High voltage transmission line, 8 strand, bears N. and S.
40.00	<p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Survey of the North Boundary,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 38 N R 9 E S 31 1/4 ——— S 6 T 37 N  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
79.46	The cor. of secs. 1, 6, 31, and 36, hereinbefore described.  Land, rolling. Soil, sandy loam and sandstone rock outcrops. Timber, sparse juniper. Undergrowth, sage brush and native grasses.
	<hr/> <b>Survey of the Subdivisional Lines, T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona</b> <hr/>
	From the stan. cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°01' W., bet. secs. 35 and 36.
	Over rolling land.
10.40	Underground water line, bears N. 60° E. and S. 60° W.
10.66	Barbed wire fence, 5 strand, bears N. 60° E. and S. 60° W.
35.50	Track road, bears N. 35° E. and S. 35° W.
40.00	Point for the 1/4 sec. cor. of secs. 35 and 36.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 9 E 1/4 S 35   S 36  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	Point for the cor. of secs. 25, 26, 35, and 36.

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E S 26   S 25 S 35   S 36</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, rolling. Soil, sandy loam and rocky. Timber, scattered juniper. Undergrowth, sage brush native grasses.</p> <hr/>
	<p>From the cor. of secs. 25, 30, 31, and 36 on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 25 and 36.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E S 25 1/4 ——— S 36</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
78.95	<p>Track road, bears S. 35° E. and N. 40° W.</p>
80.00	<p>The cor. of secs. 25, 26, 35, and 36.</p> <p>Land, rolling to broken to rolling. Soil, sandy loam and sandstone. Timber, scattered juniper. Undergrowth, sage brush and native grasses.</p> <hr/>

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°01' W., bet. secs. 25 and 26.  Over rolling and broken land.
1.70	Track road, bears S. 30° E. and N. 30° W.
40.00	Point for the 1/4 sec. cor. of secs. 25 and 26.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top of brass cap mkd.  <div style="text-align: center;">           T 37 N R 9 E                  1/4            S 26   S 25              2013         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.
79.71	Barbed wire fence, 4 strand, bears S. 15° E. and N. 15° W.
80.00	Point for the cor. of secs. 23, 24, 25, and 26.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 37 N R 9 E            S 23   S 24            S 26   S 25              2013         </div>
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.  Land, rolling to broken to rolling. Soil, sandy loam and sandstone. Timber, scattered juniper. Undergrowth, sage brush and native grasses.
	From the cor. of secs. 19, 24, 25, and 30 on the E. bdy. of the Tp., hereinbefore described.  West, bet. secs. 24 and 25.  Over rolling land.

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS 40.00	<p>Point for the 1/4 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E S 24 1/4 — S 25</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>The cor. of secs. 23, 24, 25, and 26.</p> <p>Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, sage brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E 1/4 S 23   S 24</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 13, 14, 23, and 24.</p> <p>Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in a drill hole, in sandstone outcropping, with top mkd.</p>

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 9 E S 14   S 13 S 23   S 24  2013
	Deposit fragments of a magnet, in the drill hole.  Set a steel fence post, +/- 17 ft, East of the cor.  Land, rolling to broken to rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, native grasses, salt brush, yucca, and Mormon tea.
	<hr/> From the cor. of secs. 13, 18, 19, and 24 on the E. bdy. of the Tp., hereinbefore described.  West, bet. secs. 13 and 24.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 13 and 24.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 9 E S 13 1/4 ——— S 24  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.  Cor. is located 3 lks. W. of a juniper, 4 ins. diam.
80.00	The cor. of secs. 13, 14, 23, and 24.  Land, rolling. Soil, sandy loam and sparse sandstone rock outcrops. Timber, sparse juniper. Undergrowth, sage brush and native grasses.
	<hr/> N. 0°01' W., bet. secs. 13 and 14.  Over rolling land.

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS 40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E 1/4 S 14   S 13</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 11, 12, 13, and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E S 11   S 12 S 14   S 13</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, rolling. Soil, sandy loam and sandstone. Timber, scattered juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 12, 13, and 18 on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 12 and 13.</p> <p>Over rolling land.</p>
39.31	Track road, bears S. 65° E. and N. 65° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 9 E S 12 1/4 ——— S 13  2013  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.  80.00 The cor. of secs. 11, 12, 13, and 14.  Land, gently rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, sage brush and native grasses.
	N. 0°01' W., bet. secs. 11 and 12.  Over rolling and broken land.  40.00 Point for the 1/4 sec. cor. of secs. 11 and 12.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 9 E 1/4 S 11   S 12  2013  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.  80.00 Point for the cor. of secs. 1, 2, 11, and 12.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 37 N R 9 E S 2   S 1 ——— S 11   S 12  2013  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a steel fence post nearby.</p> <p>From this cor. point, U. S. L. M. No. 2, bears N 89° 38' W., 7.01 chs. dist., monumented with a sandstone, 20 x 6 ins., projecting 24 ins. mkd. U S L M No 2 X, on the NE face and an X on the SW face. This monument is located on a high sandstone mesa (180 ft.), known to locals as Rock No. 3.</p> <p>Land, rolling to broken to rolling. Soil, sandy loam and scattered sandstone rock outcrops. Timber, scattered juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>From the cor. of secs. 1, 6, 7, and 12 on the E. bdy. of the Tp., hereinbefore described.</p> <p>West, bet. secs. 1 and 12.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 37 N R 9 E</p> <p>S 1</p> <p>1/4 ———</p> <p>S 12</p> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>The cor. of secs. 1, 2, 11, and 12.</p> <p>Land, rolling to broken to rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 1 and 2.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in a drill hole, in sandstone outcropping, with top mkd.</p>

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 9 E 1/4 S 2   S 1  2013
	Deposit fragments of a magnet, in the drill hole.
80.00	The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.  Land, rolling and broken. Soil, sandy loam and scattered sandstone rock outcrops. Timber, sparse juniper. Undergrowth, sage brush and native grasses.
	<hr/> From the stan. cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described.  N. 0°01' W., bet. secs. 34 and 35.  Over gently rolling land.
10.51	BIA Route N20, asphalt surfaced, 33 ft. wide, bears S. 15° E. and N. 15° W.
40.00	Point for the 1/4 sec. cor. of secs. 34 and 35.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 9 E 1/4 S 34   S 35  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.
80.00	Point for the cor. of secs. 26, 27, 34, and 35.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 9 E S 27   S 26 S 34   S 35  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.  Cor. is located 14 lks. N. of a track road, bears N. 80° E. and S. 80° W.  Land, rolling. Soil, sandy loam and sandstone. Timber, sparse juniper. Undergrowth, sage brush and native grasses.
	<hr/> From the cor. of secs. 25, 26, 35, and 36.  West, bet. secs. 26 and 35.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 35.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 9 E S 26 1/4 ——— S 35  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.
46.40	Barbed wire fence, 5 strand, bears N. 2° E. and S. 2° W.
80.00	The cor. of secs. 26, 27, 34, and 35.  Land, rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, sage brush and native grasses.
	<hr/>

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°01' W., bet. secs. 26 and 27.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 37 N R 9 E                  1/4            S 27   S 26             2013         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.
80.00	Point for the cor. of secs. 22, 23, 26, and 27.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 37 N R 9 E            S 22   S 23            S 27   S 26             2013         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.  Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, sage brush and native grasses.  <hr/> From the cor. of secs. 23, 24, 25, and 26.  West, bet. secs. 23 and 26.  Over rolling and broken land.
0.09	Barbed wire fence, 4 strand, bears S. 17° E. and N. 17° W.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 26.

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 37 N R 9 E S 23 1/4 ——— S 26
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
42.54	Barbed wire fence, 5 strand, bears N. 2° E. and S. 2° W.
80.00	The cor. of secs. 22, 23, 26, and 27.
	Land, rolling to broken to rolling. Soil, sandy loam and sparse sandstone rock outcrops. Timber, scattered juniper. Undergrowth, sage brush and native grasses.
	-----
	N. 0°01' W., bet. secs. 22 and 23.
	Over rolling land.
36.65	Track road, bears S. 20° E. and N. 20° W.
40.00	Point for the 1/4 sec. cor. of secs. 22 and 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 9 E 1/4 S 22   S 23
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
45.00	Power line, 2 strand, bears E. and W.
80.00	Point for the cor. of secs. 14, 15, 22, and 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 37 N R 9 E S 15   S 14 S 22   S 23</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>West, bet. secs. 14 and 23.</p> <p>Over rolling and broken land.</p>
40.00	<p>True point for the 1/4 sec. cor. of secs. 14 and 23; falls on the face of a sandstone outcropping, 12 ft. high, where it is impracticable to establish a permanent monument.</p> <p>From this true point, the point selected for a witness cor. to the 1/4 sec. cor. of secs. 14 and 23, bears S. 70° 33' W., 50.0 lks. dist.</p> <p>Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in a drill hole, in sandstone outcropping, with top mkd.</p> <p style="text-align: center;">WC T 37 N R 9 E S 14 1/4 ————— → S 23</p> <p style="text-align: center;">2013</p>
80.00	<p>Deposit fragments of a magnet, in drill hole.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, S. of the cor.</p> <p>The cor. of secs. 14, 15, 22, and 23.</p> <p>Land, rolling and broken. Soil, sandy loam and sparse sandstone rock outcrops. Timber, scattered juniper. Undergrowth, sage brush and native grasses.</p> <hr/>

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0°01' W., bet. secs. 14 and 15.  Over rolling and broken land.
0.51	Track road, bears N. 70° E. and S. 70° W.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 15.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, to sandstone bedrock, in a mound of stone, 3 ft. base, to top of brass cap mkd.  <div style="text-align: center;">           T 37 N R 9 E                  1/4            S 15   S 14              2013         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.
80.00	Point for the cor. of secs. 10, 11, 14, and 15.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 37 N R 9 E            S 10   S 11            S 15   S 14              2013         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.  Land, rolling to broken to rolling. Soil, sandy loam and sandstone. Timber, sparse juniper. Undergrowth, sage brush and native grasses.  <hr/> From the cor. of secs. 11, 12, 13, and 14.  West, bet. secs. 11 and 14.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 11 and 14.

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E S 11 1/4 ——— S 14</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>The cor. of secs. 10, 11, 14, and 15.</p> <p>Land, rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E 1/4 S 10   S 11</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 2, 3, 10, and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E S 3   S 2 S 10   S 11</p> <p style="text-align: center;">2013</p>

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.  Land, rolling to broken to rolling. Soil, sandy loam and sandstone. Timber, sparse juniper. Undergrowth, sage brush and native grasses.
	<hr/> From the cor. of secs. 1, 2, 11, and 12.  West, bet. secs. 2 and 11.  Over rolling and broken land.
39.50	Track road, bears S. 20° E. and N. 20° W.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 11.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 9 E S 2 1/4 ——— S 11  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.
80.00	The cor. of secs. 2, 3, 10, and 11.  Land, rolling to broken to rolling. Soil, sandy loam and sandstone. Timber, sparse juniper. Undergrowth, sage brush and native grasses.
	<hr/> N. 0°01' W., bet. secs. 2 and 3.  Over rolling land.
1.60	Power line, 2 strand, bears N. 80° E. and S. 80° W.
1.70	Track road, bears N. 65° E. and S. 65° W.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 3.

**Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E 1/4 S 3   S 2</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, sage brush and native grasses.</p> <hr/> <p>From the stan. cor. of secs. 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02' W., bet. secs. 33 and 34.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E 1/4 S 33   S 34</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 27, 28, 33, and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 9 E S 28   S 27 S 33   S 34  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.  Land, rolling to broken to rolling. Soil, sandy loam and sandstone. Timber, sparse juniper. Undergrowth, sage brush and native grasses.
	<hr/> From the cor. of secs. 26, 27, 34, and 35.  West, bet. secs. 27 and 34.  Over rolling land.
13.45	Underground water line, bears S. 30° E and N. 30° W.
13.54	E. right-of-way fence of BIA Route N20, barbed wire, 5 strand, parallels highway.
16.19	BIA Route N20, asphalt surfaced, 33 ft. wide, bears S. 30° E. and N. 30° W.
17.90	W. right-of-way fence of BIA Route N20, barbed wire, 5 strand, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 37 N R 9 E S 27 1/4 ——— S 34  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.
80.00	The cor. of secs. 27, 28, 33, and 34.

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy loam and sandstone. Timber, none. Undergrowth, sage brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E 1/4 S 28   S 27</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 21, 22, 27, and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E S 21   S 22 S 28   S 27</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, gently rolling. Soil, sandy loam and sandstone. Timber, sparse juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>West, bet. secs. 22 and 27.</p> <p>Over rolling land.</p>

**Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a supporting mound of stone, 4 ft. base, to top of brass cap mkd.</p> <div style="text-align: center;"> <p>T 37 N R 9 E</p> <p>S 22</p> <p>1/4 ———</p> <p>S 27</p> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
54.65	E. right-of-way fence of BIA Route N20, barbed wire, 5 strand, parallels highway.
56.58	BIA Route N20, asphalt surfaced, 33 ft. wide, bears S. 30° E. and N. 30° W.
57.93	W. right-of-way fence of BIA Route N20, barbed wire, 5 strand, parallels highway.
79.50	Track road, bears S. 20° E. and N. 20° W.
80.00	<p>The cor. of secs. 21, 22, 27, and 28.</p> <p>Land, rolling.</p> <p>Soil, sandy loam and sandstone.</p> <p>Timber, sparse juniper.</p> <p>Undergrowth, sage brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 21 and 22.</p> <p>Over rolling land.</p>
1.30	Track road, bears S. 20° E. and N. 20° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top of brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 9 E 1/4 S 21   S 22  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.
52.12	BIA Route N20, asphalt surfaced, 33 ft. wide, bears S. 20° E. and N. 20° W.
77.50	Track road, bears S. 55° E. and N. 55° W.
80.00	Point for the cor. of secs. 15, 16, 21, and 22.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T 37 N R 9 E S 16   S 15 S 21   S 22  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.  Land, rolling. Soil, sandy loam and sandstone. Timber, sparse juniper. Undergrowth, sage brush and native grasses.
	<hr/> From the cor. of secs. 14, 15, 22, and 23.  West, bet. secs. 15 and 22.  Over rolling land.
1.25	Track road, bears N. 70° E. and N. 70° W.
1.95	Track road, bears S. 15° E. and N. 15° W.
38.10	Track road, bears S. 15° E. and N. 15° W.
40.00	Point for the 1/4 sec. cor. of secs. 15 and 22.

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E S 15 1/4 ——— S 22</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>The cor. of secs. 15, 16, 21, and 22.</p> <p>Land, rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, sage brush and native grasses.</p> <hr/>
	<p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top of brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E 1/4 S 16   S 15</p> <p style="text-align: center;">2013</p>
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 9, 10, 15, and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T 37 N R 9 E S 9   S 10 ----- S 16   S 15</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, rolling to broken to rolling. Soil, sandy loam and sparse sandstone rock outcrops. Timber, sparse juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>West, bet. secs. 10 and 15.</p> <p>Over rolling and broken land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 37 N R 9 E S 10 1/4 ----- S 15</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
42.00	<p>Track road, bears S. 20° E. and N. 20° W.</p>
80.00	<p>The cor. of secs. 9, 10, 15, and 16.</p> <p>Land, rolling to broken to rolling. Soil, sandy loam and sparse sandstone rock outcrops. Timber, sparse juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over rolling and broken land.</p>

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E 1/4 S 9   S 10</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located on a side of a slope, bears SE and NW.</p>
77.90	Track road, bears S. 35° E. and N. 35° W.
80.00	<p>Point for the cor. of secs. 3, 4, 9, and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E S 4   S 3 S 9   S 10</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, rolling to broken to rolling. Soil, sandy loam and sparse sandstone rock outcrops. Timber, sparse juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>West, bet. secs. 3 and 10.</p> <p>Over rolling land.</p>
2.40	Track road, bears N. 55° E. and S. 50° W.
9.05	Power line, 2 strand, bears N. 80° E. and S. 80° W.
39.85	Power line, 2 strand, bears N. 80° E. and S. 80° W.

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E S 3 1/4 ——— S 10</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
42.90	Track road, bears S. 75° E. and N. 75° W.
43.15	Track road, bears S. 45° E. and N. 45° W.
80.00	<p>The cor. of secs. 3, 4, 9, and 10.</p> <p>Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, sage brush and native grasses.</p> <hr/> <p>N. 0°02' W., bet. secs. 3 and 4.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E 1/4 S 4   S 3</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
41.25	BIA Route N201, a graded road, 18 ft. wide, bears N 50° E. and S. 50° W.
79.99	The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described.

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy loam and sandstone. Timber, sparse juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>From the stan. cor. of secs. 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03' W., bet. secs. 32 and 33.</p> <p>Over rolling land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E 1/4 S 32   S 33</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 28, 29, 32, and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E S 29   S 28 S 32   S 33</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, rolling. Soil, sandy loam, rocky and sandstone. Timber, sparse juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>From the cor. of secs. 27, 28, 33, and 34.</p>

**Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	West, bet. secs. 28 and 33.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 37 N R 9 E S 28 1/4 ——— S 33
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
54.80	High voltage transmission line, 8 strand, bears N. 5° E. and S. 5° W.
56.80	High voltage transmission line, 8 strand, bears N. 5° E. and S. 5° W.
59.15	Power line, 4 strand, bears N. 5° E. and S. 5° W.
61.45	Power line, 4 strand, bears N. and S.
80.00	The cor. of secs. 28, 29, 32, and 33.
	Land, rolling. Soil, sandy loam and sandstone. Timber, none. Undergrowth, sage brush and native grasses.
	-----
	N. 0°03' W., bet. secs. 28 and 29.
	Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 9 E 1/4 S 29   S 28  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.
80.00	Point for the cor. of secs. 20, 21, 28, and 29.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 9 E S 20   S 21 S 29   S 28  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.  Land, rolling. Soil, sandy loam and sparse sandstone rock outcrops. Timber, sparse juniper. Undergrowth, sage brush and native grasses.
	<hr/> From the cor. of secs. 21, 22, 27, and 28.  West, bet. secs. 21 and 28.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 21 and 28.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top of brass cap mkd.
	T 37 N R 9 E S 21 1/4 ——— S 28  2013

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
44.15	High voltage transmission line, 8 strand, bears N. 5° E. and S. 5° W.
46.15	High voltage transmission line, 8 strand, bears N. 5° E. and S. 5° W.
57.80	Power line, 5 strand, bears N. and S.
69.50	Track road, bears S. 10° E. and N. 10° W.
71.10	Power line, 4 strand, bears S. 20° E. and N. 20° W.
79.00	Track road, bears S. 45° E. and N. 45° W.
80.00	<p>The cor. of secs. 20, 21, 28, and 29.</p> <p>Land, rolling. Soil, sandy loam and sandstone. Timber, none. Undergrowth, sage brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 20 and 21.</p> <p>Over rolling land.</p>
1.14	Track road, bears S. 45° E. and N. 45° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E 1/4 S 20   S 21</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
63.18	Power line, 2 strand, bears N. 80° E. and S. 80° W.
65.86	Track road, bears S. 20° E. and N. 20° W.
66.93	Power line, 4 strand, bears S. 20° E. and N. 20° W.

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS							
78.72	Track road, bears S. 15° E. and N. 15° W.						
80.00	Point for the cor. of secs. 16, 17, 20, and 21.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top of brass cap mkd.  <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 37 N</td> <td>R 9 E</td> </tr> <tr> <td style="border-right: 1px solid black;">S 17</td> <td style="border-right: 1px solid black;">S 16</td> </tr> <tr> <td style="border-right: 1px solid black;">S 20</td> <td style="border-right: 1px solid black;">S 21</td> </tr> </table> <p>2013</p> </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post +/- 15 ft. E. of the cor.  Land, rolling. Soil, sandy loam, rocky, and sparse sandstone rock outcrops. Timber, sparse juniper. Undergrowth, sage brush and native grasses.  <hr/> From the cor. of secs. 15, 16, 21, and 22.  West, bet. secs. 16 and 21.  Over rolling land.	T 37 N	R 9 E	S 17	S 16	S 20	S 21
T 37 N	R 9 E						
S 17	S 16						
S 20	S 21						
9.90	E. right-of-way fence of BIA Route N20, barbed wire, 5 strand, parallels highway.						
11.16	BIA Route N20, asphalt surfaced, 33 ft. wide, bears S. 25° E. and N. 25° W.						
13.08	W. right-of-way fence of BIA Route N20, barbed wire, 5 strand, parallels highway.						
13.95	Underground water line, bears S. 25° E. and N. 25° W.						
33.50	High voltage transmission line, 8 strand, bears N. 5° E. and S. 5° W.						
35.50	High voltage transmission line, 8 strand, bears N. 5° E. and S. 5° W.						
40.00	Point for the 1/4 sec. cor. of secs. 16 and 21.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.						

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 9 E S 16 1/4 ——— S 21  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.
57.55	Power line, 5 strand, bears N. and S.
80.00	The cor. of secs. 16, 17, 20, and 21.  Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, sage brush and native grasses.
	N. 0°03' W., bet. secs. 16 and 17.  Over rolling and broken land.
40.00	Point for the 1/4 sec. cor. of secs. 16 and 17.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 9 E 1/4 S 17   S 16  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.
80.00	Point for the cor. of secs. 8, 9, 16, and 17.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 9 E S 8   S 9 S 17   S 16  2013

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, rolling to broken to rolling. Soil, sandy loam, rocky, and sparse sandstone rock outcrops. Timber, sparse juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>West, bet. secs. 9 and 16.</p> <p>Over rolling land.</p>
22.84	High voltage transmission line, 8 strand, bears N. 5° E. and S. 5° W.
24.84	High voltage transmission line, 8 strand, bears N. 5° E. and S. 5° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 37 N R 9 E</p> <p>S 9</p> <p>1/4 ———</p> <p>S 16</p> <p>2013</p> </div> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>The cor. is located 1.14 chs. S. of a track road, bears S 65° E. and N. 65° W.</p>
40.88	E. right-of-way fence of BIA Route N20, barbed wire, 5 strand, parallels highway.
42.49	BIA Route N20, asphalt surfaced, 33 ft. wide, bears S. 20° E. and N. 20° W.
44.09	W. right-of-way fence of BIA Route N20, barbed wire, 5 strand, parallels highway.
57.30	Power line, 5 strand, bears N. and S.

**Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
70.75	Underground water line, bears S. 60° E. and N. 60° W.
80.00	The cor. of secs. 8, 9, 16, and 17.  Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, sage brush and native grasses.
	N. 0°03' W., bet. secs. 8 and 9.  Over rolling and broken land.
4.80	Underground water line, bears S. 60° E. and N. 60° W.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 9.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 37 N R 9 E                  1/4              S 8   S 9              2013         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.
42.30	Power line, 4 strand, bears S. 75° E. and N. 75° W.
42.60	Track road, bears S. 75° E. and N. 75° W.
79.00	W. right-of-way fence of BIA Route N20, barbed wire, 5 strand, bears S. 45° E. and N. 45° W.
80.00	Point for the cor. of secs. 4, 5, 8, and 9.  Set a mag nail, 2 1/2 ins. long, flush with the surface of asphalt, with a brass washer, 1 1/2 ins. diam., mkd. BLM 2013.  from which  <div style="margin-left: 40px;">           A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 28 ins. in the ground, for a reference monument, bears S. 19°59' W., 50.0 ft. dist., with brass cap mkd. RM T37N R9E S8 50.0 FT TO COR. 2013, and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.         </div>

**Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 28 ins. in the ground, for a reference monument, bears N. 70°00' W., 90.0 ft. dist., with brass cap mkd. RM T37N R9E S5 90.0 FT TO COR. 2013, and an arrow pointing to the cor. Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.</p> <p>Cor. is located 1.15 chs. W. of the intersection of B. I. A. Route N20 and B. I. A. Route N6210, on the of B. I. A. Route N6210, a part paved and part graded road, 30 ft. wide, bears E. and W.</p> <p>Land, rolling to broken to rolling. Soil, sandy loam and sparse sandstone rock outcrops. Timber, sparse juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>West, bet. secs. 4 and 9.</p> <p>Over rolling and broken land.</p>
1.20	Track road, bears S. 35° E. and N. 35° W.
12.20	High voltage transmission line, 8 strand, bears N. 5° E. and S. 5° W.
14.20	High voltage transmission line, 8 strand, bears N. 5° E. and S. 5° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Set a brass tablet, 3 1/2 ins. diam., 2 1/2 ins. stem, cemented in a drill hole, in limestone outcropping, with top mkd.</p> <p style="text-align: center;">T 37 N R 9 E S 4 1/4 ——— S 9</p> <p style="text-align: center;">2013</p> <p>Deposit fragments of a magnet, in drill hole.</p> <p>Raise a mound of stone, 4 1/2 ft. base, 2 1/2 ft. high, N. of the cor.</p> <p>From this cor. point, the NE fence cor. of a chain link fence, 8 ft. high, with fences extending S. 10° E. and N. 65° W., enclosing a water tank and a cell phone tower, bears S. 45°28' W., 4.10 chs. dist.</p>

**Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>From this same cor. point, an angle point on the same chain link fence, 8 ft. high, with fences extending S. 24° W. and N. 10° W., enclosing a water tank and a cell phone tower, bears S. 39°01' W., 4.48 chs. dist.</p> <p>From the same cor. point, the SE fence cor. of the same chain link fence, 8 ft. high, with fences extending N. 24° E. and N. 66° W., enclosing a water tank and a cell phone tower, bears S. 36°23' W., 5.44 chs. dist.</p> <p>From the same cor. point, the SW fence cor. of the same chain link fence, 8 ft. high, with fences extending N. 22° E. and S. 66° E., enclosing a water tank and a cell phone tower, bears S. 50°39' W., 5.95 chs. dist.</p> <p>From the same cor. point, the NW fence cor. of the same chain link fence, 8 ft. high, with fences extending S. 65° E. and S. 22° W., enclosing a water tank and a cell phone tower, bears S. 59°32' W., 4.68 chs. dist.</p>
43.80	Track road, bears N. 10° E. and S. 10° W.
43.95	Underground water line, bears N. 10° E. and S. 10° W.
44.15	Power line, 2 strand, bears S. 15° E. and N. 15° W.
57.05	Power line, 5 strand, bears N. and S.
76.71	E. right-of-way fence of BIA Route N20, barbed wire, 5 strand, bears S. 45° E. and N. 45° W.
78.85	BIA Route N20, asphalt surfaced, 33 ft. wide, along a curve concaved to NE.
80.00	<p>The cor. of secs. 4, 5, 8, and 9.</p> <p>Land, rolling to broken to rolling. Soil, sandy loam, scattered sandstone, and limestone rock outcrops. Timber, sparse juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>N. 0°03' W., bet. secs. 4 and 5.</p> <p>Over rolling land.</p>
1.48	BIA Route N20, asphalt surfaced, 33 ft. wide, along a curve concaved to NE.
4.26	E. right-of-way fence of BIA Route N20, barbed wire, 5 strand, bears S. 45° E. and N. 45° W.

**Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
25.93	E. right-of-way fence of BIA Route N20, barbed wire, 5 strand, bears N. 15° E. and S. 15° W.
31.90	Power line, 2 strand, bears N. 70° E. and S. 70° W.
31.94	BIA Route N20, asphalt surfaced, 33 ft. wide, bears N. 15° E. and S. 15° W.
35.91	W. right-of-way fence of BIA Route N20, barbed wire, 5 strand, parallels highway.
40.00	Point for the 1/4 sec. cor. of secs. 4 and 5.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 37 N R 9 E                  1/4              S 5   S 4              2013         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.
80.00	The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described.  Land, rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, sage brush and native grasses.  <hr/> From the stan. cor. of secs. 31 and 32, on the S. bdy. of the Tp., hereinbefore described.  N. 0°03' W., bet. secs. 31 and 32.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 31 and 32.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. base, to top of brass cap mkd.

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 9 E 1/4 S 31   S 32  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.  Cor. is located 1 lk. E. of a juniper, 6 ins. diam.
80.00	Point for the cor. of secs. 29, 30, 31, and 32.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 9 E S 30   S 29 S 31   S 32  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.  Cor. is located 14 lks. E. of a juniper, 6 ins. diam.  Land, rolling. Soil, sandy loam and sandstone. Timber, scattered juniper. Undergrowth, sage brush and native grasses.
	<hr/> From the cor. of secs. 28, 29, 32, and 33.  West, bet. secs. 29 and 32.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 29 and 32.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 9 E S 29 1/4 ——— S 32  2013

**Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>The cor. of secs. 29, 30, 31, and 32.</p> <p>Land, rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>West, bet. secs. 30 and 31.</p> <p>Over rolling and broken land.</p>
1.25	Track road, bears N. 50° E. and S. 55° W.
5.42	Track road, bears N. and S.
6.08	High voltage transmission line, 8 strand, bears S. 5° E. and N. 5° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E S 30 1/4 ——— S 31</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Cor. is located 5 lks. NE of a juniper, 12 ins. diam.</p>
79.91	<p>The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling to broken to rolling. Soil, sandy loam, rocky, and sandstone. Timber, scattered juniper. Undergrowth, sage brush and native grasses.</p> <hr/>

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over rolling land.</p>
0.65	Track road, bears N. 65° E. and S. 65° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E 1/4 S 30   S 29</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 19, 20, 29, and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E S 19   S 20 S 30   S 29</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, gently rolling and broken. Soil, sandy loam and sandstone. Timber, scattered juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>West, bet. secs. 20 and 29.</p> <p>Over rolling land.</p>
40.00	Point for the 1/4 sec. cor. of secs. 20 and 29.

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E S 20 1/4 ——— S 29</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>The cor. of secs. 19, 20, 29, and 30.</p> <p>Land, rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>West, bet. secs. 19 and 30.</p> <p>Over rolling land.</p>
4.85	Track road, bears S. 15° E. and N. 15° W
5.50	High voltage transmission line, 8 strand, bears S. 5° E. and N. 5° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E S 19 1/4 ——— S 30</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
79.82	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., hereinbefore described.

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>From the cor. of secs. 19, 20, 29, and 30. N. 0°03' W., bet. secs. 19 and 20. Over rolling land.</p>
39.85	Track road, bears N. 60° E. and S. 60° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E 1/4 S 19   S 20</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
80.00	<p>Point for the cor. of secs. 17, 18, 19, and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E S 18   S 17 S 19   S 20</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, rolling. Soil, sandy loam, rocky, and sandstone. Timber, scattered juniper. Undergrowth, sage brush and native grasses.</p> <hr/>

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the cor. of secs. 16, 17, 20, and 21.
	West, bet. secs. 17 and 20.
	Over rolling land.
0.40	Track road, bears S. 15° E. and N. 15° W.
2.15	Power line, 4 strand, bears S. 20° E. and N. 20° W.
2.40	Track road, bears S. 20° E. and N. 20° W.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 9 E S 17 1/4 ——— S 20  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
40.15	Underground water line, bears N. 45° E. and S. 45° W.
41.45	Track road, bears N. 35° E. and S. 35° W.
80.00	The cor. of secs. 17, 18, 19, and 20.
	Land, rolling. Soil, sandy loam and sandstone. Timber, sparse juniper. Undergrowth, sage brush and native grasses.
	West, bet. secs. 18 and 19.
	Over rolling land.
4.55	Track road, bears S. 5° E. and N. 5° W
4.90	High voltage transmission line, 8 strand, bears S. 5° E. and N. 5° W.
40.00	Point for the 1/4 sec. cor. of secs. 18 and 19.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 9 E S 18 1/4 ——— S 19  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.
79.73	The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., hereinbefore described.  Land, rolling. Soil, sandy loam. Timber, scattered juniper. Undergrowth, sage brush and native grasses.
	<hr/> From the cor. of secs. 17, 18, 19, and 20.  N. 0°03' W., bet. secs. 17 and 18.  Over rolling land.
40.00	Point for the 1/4 sec. cor. of secs. 17 and 18.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top of brass cap mkd.
	T 37 N R 9 E 1/4 S 18   S 17  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.
80.00	Point for the cor. of secs. 7, 8, 17, and 18.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 9 E S 7   S 8 S 18   S 17  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.  Land, rolling. Soil, sandy loam, rocky, and sandstone. Timber, scattered juniper. Undergrowth, sage brush and native grasses.
	<hr/> From the cor. of secs. 8, 9, 16, and 17.  West, bet. secs. 8 and 17.  Over rolling land.
39.50	Track road, bears N. 20° E. and S. 20° W.
40.00	Point for the 1/4 sec. cor. of secs. 8 and 17.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 9 E S 8 1/4 ——— S 17  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.  From this cor. point, a windmill, bears N. 22°32' W., 27.39 chs. dist.  From this same cor. point, a water well, bears N. 13°43' W., 32.48 chs. dist.
80.00	The cor. of secs. 7, 8, 17, and 18.

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy loam. Timber, sparse juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>West, bet. secs. 7 and 18.</p> <p>Over rolling land.</p>
3.45	Track road, bears S. 10° E. and N. 10° W.
4.30	High voltage transmission line, 8 strand, bears S. 10° E. and N. 10° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E S 7 1/4 ——— S 18</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>
79.64	<p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <p>Land, rolling. Soil, sandy loam and sandstone. Timber, scattered juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0°03' W., bet. secs. 7 and 8.</p> <p>Over rolling land.</p>
38.10	Graded road, 18 ft. wide, bears N. 85° E. and S. 85° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 9 E 1/4 S 7   S 8  2013
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>From this cor. point, the NW fence cor. of the Copper Mine Chapter House Tract, barbed wire, 6 ft. high, with fences extending S. 49°47' E. and N. 49°09' E., bears S. 79°41' E., 27.06 chs. dist.</p> <p>From this same cor. point, the SW fence cor. of the Copper Mine Chapter House Tract, chain link, 6 ft. high, with fences extending N. 40°07' E. and N. 49°47' W., bears S. 71°08' E., 37.06 chs. dist.</p> <p>From this same cor. point, a rebar, 1/2 in. diam., with a plastic cap, 1 in. diam., mkd. "GPS RLS 42048", at an angle point on the fence of the Copper Mine Chapter House Tract, chain link fence, 6 ft. high, with fences extending S. 40°07' W. and N. 50°58' W., bears S. 76°24' E., 38.60 chs. dist.</p> <p>From this same cor. point, an angle point on fence of the Copper Mine Chapter House Tract, chain link and wire fence, 6 ft. high, with fences extending N. 40°00' E. and S. 50°58' E., bears S. 77°05' E., 37.66 chs. dist.</p> <p>From this same cor. point, the SE fence cor. of the Copper Mine Chapter House Tract, wire fence, 6 ft. high, with fences extending S. 40°00' W. and N. 49°49' W., bears S. 86°15' E., 41.58 chs. dist.</p> <p>From this same cor. point, the NE fence cor. of the Copper Mine Chapter House Tract, wire fence, 6 ft. high, with fences extending S. 49°49' E. and S. 40°09' W., bears N. 83°43' E., 34.06 chs. dist.</p>
54.90	Graded road, 26 ft. wide, bears N. 40° E. and S. 40°W.
80.00	<p>Point for the cor. of secs. 5, 6, 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p>

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
	T 37 N R 9 E S 6   S 5 S 7   S 8  2013
	<p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>Land, rolling. Soil, sandy loam, rocky, and sandstone. Timber, scattered juniper. Undergrowth, sage brush and native grasses.</p> <hr/> <p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>West, bet. secs. 5 and 8.</p> <p>Over rolling land.</p>
1.17	W. right-of-way of BIA Route N20, at the BIA Route N6210, at a cattle guard, 30 ft. wide, cattle guard bears N. and S.
40.00	<p>Point for the 1/4 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in a collar of stone, 3 ft. base, to top of brass cap mkd.</p> <p style="text-align: center;">             T 37 N R 9 E              S 5              1/4 ———              S 8                2013           </p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>From this cor. point, U. S. L. M. No. 2758, bears S 78° 22' E., 15.30 chs. dist., monumented with an X on a sandstone outcropping, 4 x 2 ft., mkd. U S L M No 2758 X. With a mound of stone 6 ft. base, 4 ft. high, 2.6 lks. dist., N 45° E.</p> <p>The cor. is located, in a mining area.</p>

Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
61.90	BIA Route N6210, a graded road, 26 ft. wide, bears N. 50° E. and S. 50° W.
80.00	The cor. of secs. 5, 6, 7, and 8.  Land, gently rolling and broken. Soil, sandy loam. Timber, scattered juniper. Undergrowth, sage brush native grasses. <hr/>
	West, bet. secs. 6 and 7.  Over rolling and broken land.
0.70	Track road, bears S. 20° E. and N. 20° W.
1.61	Wire fence, 4 ft. high, bears S. 20° E. and N. 20° W.
1.92	Wire fence, 6 ft. high, bears S. 20° E. and N. 20° W.
3.45	High voltage transmission line, 8 strand, bears N. 5° E. and S. 5° W.
40.00	Point for the 1/4 sec. cor. of secs. 6 and 7.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 37 N R 9 E                      S 6            1/4 ———                      S 7             2013         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.
79.55	The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., hereinbefore described.  Land, rolling to broken to rolling. Soil, sandy loam, rocky and sandstone. Timber, sparse juniper. Undergrowth, sage brush and native grasses. <hr/>
	From the cor. of secs. 5, 6, 7, and 8.  N. 0°03' W., bet. secs. 5 and 6.

**Survey of the Subdivisional Lines,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	Over rolling land.
2.30	Track road, bears S. 60° E. and N. 60° W.
39.80	Track road, bears S. 40° E. and N. 40° W.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 6.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           T 37 N R 9 E                  1/4            S 6   S 5              2013         </div> Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.  The cor. is located, 12 lks. E. of a track road, bears, S. 40° E. and N. 40° W.
80.00	The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., hereinbefore described.  Land, rolling to broken to rolling. Soil, sandy loam and sparse sandstone rock outcrops. Timber, sparse juniper. Undergrowth, sage brush and native grasses.
<hr/> <b>Subdivision of Section 4, T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona</b> <hr/>	
	From the 1/4 sec. cor. of secs. 4 and 9.  N. 0°02' W., on the N. and S. center line of sec. 4.  Over rolling land.
16.15	BIA Route N201, a graded road, 15 ft. wide, bears N. 80° E. and S. 80° W.
40.00	Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E. and W. center line.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

**Subdivision of Section 4,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	T 37 N R 9 E C 1/4 S 4  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
73.70	Underground water line, bears S. 20° E. and N. 20° W.
78.75	Dirt road, 10 ft. wide, bears S. 15° E. and N. 15° W.
97.995	The 1/4 sec. cor. of secs. 4 and 33.
	<hr/>
	From the 1/4 sec. cor. of secs. 3 and 4.
	West, on the E. and W. center line of sec. 4.
	Over rolling land.
6.85	High voltage transmission line, 8 strand, bears N. 5° E. and S. 5° W.
8.85	High voltage transmission line, 8 strand, bears N. 5° E. and S. 5° W.
38.15	Track road, bears S. 5° E. and N. 5° W.
38.30	Underground water line, bears S. 5° E. and N. 5° W.
40.00	The center 1/4 sec. cor. of sec. 4.
58.85	High voltage transmission line, 5 strand, bears N. and S.
75.64	E. right-of-way fence of BIA Route N20, barbed wire, 5 strand, parallels highway.
77.50	BIA Route N20, asphalt surfaced, 33 ft. wide, bears N. 15° E. and S. 15° W.
78.73	W. right-of-way fence of BIA Route N20, barbed wire, 5 strand, parallels highway.
80.00	The 1/4 sec. cor. of secs. 4 and 5.
	<hr/>
	<b>Subdivision of Section 5, T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona</b>
	<hr/>
	From the 1/4 sec. cor. of secs. 5 and 8.

**Subdivision of Section 5,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	N. 0°03' W., on the N. and S. center line of sec. 5. Over rolling and broken land.
7.70	Barbed wire fence, 4 strand, bears N. 60° E. and S. 60° W., leaving mining area.
9.35	Graded road, 26 ft. wide, bears N. 55° E. and S. 55° W.
40.00	Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E. and W. center line.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, in a supporting mound of stone, 5 ft. base, to top of brass cap mkd.  T 37 N R 9 E C 1/4 S 5  2013  Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.
80.00	The 1/4 sec. cor. of secs. 5 and 32. <hr/>
	From the 1/4 sec. cor. of secs. 4 and 5. West, on the E. and W. center line of sec. 5. Over rolling and broken land.
5.05	Power line, 2 strand, bears S. 10° E. and N. 10° W.
40.00	The center 1/4 sec. cor. of sec. 5.
80.00	The 1/4 sec. cor. of secs. 5 and 6. <hr/>
	<b>Subdivision of Section 9, T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona</b>
	From the 1/4 sec. cor. of secs. 9 and 16. N. 0°02' W., on the N. and S. center line of sec. 9. Over rolling and broken land.
35.65	Top edge of mesa, bears S. 30° E. and W.

Subdivision of Section 9,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to bedrock, in a supporting mound of stone, 5 ft. base, to top of brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E C 1/4 S 9</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p> <p>The cor. falls on top a small mesa.</p>
42.40	Top edge of mesa, bears N. 35° E. and S. 35° W.
80.00	The 1/4 sec. cor. of secs. 4 and 9.
	<hr/> <p>From the 1/4 sec. cor. of secs. 9 and 10.</p> <p>West, on the E. and W. center line of sec. 9.</p> <p>Over rolling and broken land.</p>
17.50	High voltage transmission line, 8 strand, bears N. 5° E. and S. 5° W.
19.50	High voltage transmission line, 8 strand, bears N. 5° E. and S. 5° W.
39.15	Top edge of mesa, bears S. 10° E. and N. 10° W.
40.00	The center 1/4 sec. cor. of sec. 9.
40.60	Top edge of mesa, bears N. 5° E. and S. 5° W.
48.10	Underground water line, bears N. and S.
48.52	E. right-of-way fence of BIA Route N20, barbed wire, 5 strand, parallels highway.
50.04	BIA Route N20, asphalt surfaced, 33 ft. wide, bears S. 10° E. and N. 10° W.
51.57	W. right-of-way fence of BIA Route N20, barbed wire, 5 strand, parallels highway.
57.20	Power line, 5 strand, bears N. and S.

**Subdivision of Section 9,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
74.50	Track road, bears S. 70° E. and W.
74.65	Power line, 4 strand, bears S. 75° E. and N. 75° W.
80.00	The 1/4 sec. cor. of secs. 8 and 9.
<hr/> <p><b>Subdivision of Section 16, T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
	From the 1/4 sec. cor. of secs. 16 and 21.
	N. 0°02' W., on the N. and S. center line of sec. 16.
	Over rolling and broken land.
40.00	Point for the center 1/4 sec. cor. of sec. 16, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, underpinned with an aluminum rod, 36 ins. long, 3/4 in. diam., 58 ins. in the ground, with brass cap mkd.
	T 37 N R 9 E C 1/4 S 16  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
	From this cor. point, Copper Mine water well, bears N. 42°13' E., 11.88 chs. dist.
72.68	BIA Route N20, asphalt surfaced, 33 ft. wide, bears S. 20° E. and N. 20° W.
80.00	The 1/4 sec. cor. of secs. 9 and 16.
	From the 1/4 sec. cor. of secs. 15 and 16.
	West, on the E. and W. center line of sec. 16.
	Over rolling and broken land.
25.95	E. right-of-way fence of BIA Route N20, barbed wire, 5 strand, parallels highway.
27.18	BIA Route N20, asphalt surfaced, 33 ft. wide, bears S. 25° E. and N. 25° W.

**Subdivision of Section 16,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
28.20	High voltage transmission line, 8 strand, bears N. 10° E. and S. 10° W.
29.13	W. right-of-way fence of BIA Route N20, barbed wire, 5 strand, parallels highway.
30.15	High voltage transmission line, 8 strand, bears N. 10° E. and S. 10° W.
40.00	The center 1/4 sec. cor. of sec. 16.
45.20	Underground water line, bears S. 35° E. and N. 35° W.
57.45	Power line, 5 strand, bears N. and S.
80.00	The 1/4 sec. cor. of secs. 16 and 17.
<hr/> <p style="text-align: center;"><b>Subdivision of Section 21, T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona</b></p> <hr/>	
	From the 1/4 sec. cor. of secs. 21 and 28.
	N. 0°02' W., on the N. and S. center line of sec. 21.
	Over rolling land.
40.00	True point the center 1/4 sec. cor. of sec. 21, at intersection with the E. and W. center line; falls on the face of a sandstone outcropping, 10 ft. high, where it is impracticable to establish a permanent monument.
	From this true point, the point selected for a witness cor. to the center 1/4 sec. cor. of sec. 21, bears S. 50° 00' W., 50.0 lks dist.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	WC T 37 N R 9 E → C 1/4 S 21
	2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.
80.00	The 1/4 sec. cor. of secs. 16 and 21.

**Subdivision of Section 21,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
	From the 1/4 sec. cor. of secs. 21 and 22. West, on the E. and W. center line of sec. 21. Over rolling land.
38.85	High voltage transmission line, 8 strand, bears N. 5° E. and S. 5° W.
40.00	The center 1/4 sec. cor. of sec. 21.
40.85	High voltage transmission line, 8 strand, bears N. 5° E. and S. 5° W.
57.70	Power line, 5 strand, bears N. and S.
75.70	Track road, bears N. and S.
76.15	Power line, 4 strand, bears S. 15° E. and N. 15° W.
76.25	Track road, bears S. 15° E. and N. 15° W.
80.00	The 1/4 sec. cor. of secs. 20 and 21.
<hr/> <b>Subdivision of Section 22, T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona</b> <hr/>	
	From the 1/4 sec. cor. of secs. 22 and 27. N. 0°02' W., on the N. and S. center line of sec. 22. Over rolling land.
40.00	Point for the center 1/4 sec. cor. of sec. 22, at intersection with the E. and W. center line.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  T 37 N R 9 E C 1/4 S 22  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.  Set a steel fence post nearby.  The cor. falls, 1.14 chs. E. of a track road, bears N. and S.
48.65	Power line, 2 strand, bears E. and W.

**Subdivision of Section 22,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
80.00	<p>The 1/4 sec. cor. of secs. 15 and 22.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 22 and 23. West, on the E. and W. center line of sec. 22. Over rolling land.</p>
1.00	Track road, bears S. 20° E. and N. 20° W.
1.65	Track road, bears S. 35° E. and N. 35° W.
40.00	The center 1/4 sec. cor. of sec. 22.
73.66	E. right-of-way fence of BIA Route N20, barbed wire, 5 strand, parallels highway.
75.01	BIA Route N20, asphalt surfaced, 33 ft. wide, bears S. 25° E. and N. 25° W.
76.92	W. right-of-way fence of BIA Route N20, barbed wire, 5 strand, parallels highway.
80.00	<p>The 1/4 sec. cor. of secs. 21 and 22.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 27, T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> <p>From the 1/4 sec. cor. of secs. 27 and 34. N. 0°02' W., on the N. and S. center line of sec. 27. Over rolling land.</p>
40.00	<p>Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E C 1/4 S 27</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post.</p> <p>Set a steel fence post nearby.</p>

**Subdivision of Section 27,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	
46.66	BIA Route N20, asphalt surfaced, 33 ft. wide, bears S. 20° E. and N. 20° W.
80.00	The 1/4 sec. cor. of secs. 22 and 27.
	<hr/> From the 1/4 sec. cor. of secs. 26 and 27. West, on the E. and W. center line of sec. 27. Over rolling land.
33.45	Underground water line, bears S. 30° E. and N. 30° W.
34.17	E. right-of-way fence of BIA Route N20, barbed wire, 5 strand, parallels highway.
36.56	BIA Route N20, asphalt surfaced, 33 ft. wide, bears S. 30° E. and N. 30° W.
38.27	W. right-of-way fence of BIA Route N20, barbed wire, 5 strand, parallels highway.
40.00	The center 1/4 sec. cor. of sec. 27.
80.00	The 1/4 sec. cor. of secs. 27 and 28.
	<hr/> <p style="text-align: center;"><b>Subdivision of Section 34, T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona</b></p> <hr/> From the stan. 1/4 sec. cor. of sec. 34, on the S. bdy. of the Tp. N. 0°02' W., on the N. and S. center line of sec. 34. Over rolling land.
40.00	Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 37 N R 9 E C 1/4 S 34  2013
	Deposit a magnet, in a white plastic case, at the base of the stainless steel post.
	Set a steel fence post nearby.

Subdivision of Section 34,  
T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.00	<p>The 1/4 sec. cor. of secs. 27 and 34.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 34 and 35. West, on the E. and W. center line of sec. 34. Over rolling land.</p>
2.20	E. right-of-way fence of BIA Route N20, barbed wire, 5 strand, parallels highway.
3.71	BIA Route N20, asphalt surfaced, 33 ft. wide, bears S. 15° E. and N. 15° W.
5.18	W. right-of-way fence of BIA Route N20, barbed wire, 5 strand, parallels highway.
40.00	The center 1/4 sec. cor. of sec. 34.
80.00	<p>The 1/4 sec. cor. of secs. 33 and 34.</p> <hr/> <p style="text-align: center;">Subdivision of Section 35, T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the stan. 1/4 sec. cor. of sec. 35, on the S. bdy. of the Tp. N. 0°02' W., on the N. and S. center line of sec. 35. Over rolling land.</p>
40.00	<p>Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 37 N R 9 E C 1/4 S 35</p> <p style="text-align: center;">2013</p> <p>Deposit a magnet, in a white plastic case, at the base of the stainless steel post. Set a steel fence post nearby.</p>
77.69	Track road, bears S. 85° E. and N. 85° W.
80.00	<p>The 1/4 sec. cor. of secs. 26 and 35.</p> <hr/>

**Subdivision of Section 35,  
T. 38 N., R. 9 E., Gila and Salt River Meridian, Arizona**

CHAINS	<p>From the 1/4 sec. cor. of secs. 35 and 36. West, on the E. and W. center line of sec. 34. Over rolling land.</p> <p>40.00 The center 1/4 sec. cor. of sec. 35.</p> <p>80.00 The 1/4 sec. cor. of secs. 34 and 35.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <hr/> <p>The area surveyed is within the Navajo Indian Reservation, is 22 miles southeast of the Lechee community, and 25 miles southeast of Page, Arizona, the Copper Mine community is located in sec. 8 of the township. Primary access is BIA Route N20, asphalt surfaced road, by way of State Highway 98. A series of trail roads provide access throughout the township. ATV's were required to access some areas within the township.</p> <p>There are no major housing developments, only smaller housing clusters and single home units scattered throughout the township. The approximate elevation ranges from 5,860 to 6,320 ft. above sea level.</p> <p>An abandoned mining operation is situated between sections 5 and 8. Mineral Surveys No. 2757, 2758, 2759, 2760, 2761, 2762, and 2763 are situated in sections 1, 2, 5, 8, and 12.</p> <p>The vegetation consists of scattered juniper and piñon in the higher elevation, and sparse juniper in the lower elevation. Sage brush and native grasses are more prominent throughout the township. There is presence of grazing cattle, sheep and horses in the area. The soil is mostly sandy loam with scattered sandstone rock outcrops.</p> <p>The mean magnetic declination of 11° E. was derived from the United States Geological Survey computer program GEOMAG, utilizing the World Magnetic Model for Epoch 2010 for the dates of survey.</p> <hr/>
--------	--



## CERTIFICATE OF SURVEY

I, Blas J. Urena, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of special instructions bearing date of the 31th day of July, 2013, I have surveyed a portion of the Ninth Standard Parallel North (South Boundary), a portion of the Second Guide Meridian East (West Boundary), the East and North boundaries, and the subdivisional lines, and the subdivision of certain sections, T. 37 N., R. 9 E., of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, 2009, and in specific manner described in the foregoing field notes.

6/02/2014

(Date)

Blas J. Urena

(Cadastral Surveyor)


## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Phoenix, Arizona

The foregoing field notes of the survey of a portion of the Ninth Standard Parallel North (South Boundary), a portion of the Second Guide Meridian East (West Boundary), the East and North boundaries, and the subdivisional lines, and the subdivision of certain sections, T. 37 N., R. 9 E., Gila and Salt River Meridian, in the State of Arizona, executed by Blas J. Urena, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

6/11/2014

(Date)



(Chief Cadastral Surveyor of Arizona)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 37 N., R. 9 E., Gila and Salt River Meridian, Arizona, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor of Arizona)~~